

glossaries-extra.sty v2.0: documented code

Nicola L.C. Talbot

Dickimaw Books

<http://www.dickimaw-books.com/>

2026-03-06

This is the documented code for the `glossaries-extra` package. See `glossaries-extra-manual.pdf` for the user manual.

Contents

1	Main Package Code (<code>glossaries-extra.sty</code>)	2
1.1	Package Initialisation and Options	2
1.2	Extra Utilities	38
1.3	Modifications to Commands Provided by <code>glossaries</code>	58
1.3.1	Existence Checks	65
1.3.2	Document Definitions	79
1.3.3	Existing Glossary Style Modifications	86
1.3.4	Entry Formatting, Hyperlinks and Indexing	91
1.3.5	Entry Counting	158
1.3.6	Acronym Modifications	175
1.3.7	Indexing and Displaying Glossaries	180
1.4	Link Counting	236
1.5	Integration with <code>glossaries-accsupp</code>	238
1.6	Categories	293
1.7	Abbreviations	326
1.7.1	Abbreviation Styles Setup	355
1.7.2	Predefined Styles	360
1.8	Using Entries in Headings	360
1.9	Prefixes	383
1.10	Multi (Combined/Compound) Entries	389
1.11	Multi-Lingual Support	437
2	Predefined Abbreviation Styles (<code>glossaries-extra-abbrstyles.def</code>)	438
2.1	Predefined Styles (Default Font)	458
2.2	Predefined Styles (Small Capitals)	479
2.3	Predefined Styles (Fake Small Capitals)	496

2.4	Predefined Styles (Emphasized)	514
2.5	Predefined Styles (User Parentheses Hook)	540
2.6	Predefined Styles (Hyphen)	553
2.7	Predefined Styles (No Short on First Use)	592
3	Commands Specific to bib2gls (glossaries-extra-bib2gls.sty)	598
4	Style Adjustments (glossaries-extra-stylemods.sty)	663
4.1	Package Initialisation	663
4.2	List-Like Styles	664
4.3	Longtable Styles	668
4.4	Long Ragged Styles	670
4.5	Supertabular Styles	673
4.6	Super Ragged Styles	675
4.7	Inline Style	677
4.8	Tree Styles	677
4.9	Multicolumn Styles	703
5	bookindex style (glossary-bookindex.sty)	712
6	longextra styles (glossary-longextra.sty)	720
7	topic styles (glossary-topic.sty)	772
8	table styles (glossary-table.sty)	778
9	Rollback Files	820
9.1	Rollback v1.48 (glossaries-extra-2021-11-22.sty)	820
9.2	Rollback v1.48 (glossaries-extra-bib2gls-2021-11-22.sty)	1122
9.3	Rollback v1.48 (glossaries-extra-stylemods-2021-11-22.sty)	1157
9.4	Rollback v1.48 (glossary-bookindex-2021-11-22.sty)	1187
9.5	Rollback v1.48 (glossary-longextra-2021-11-22.sty)	1191
9.6	Rollback v1.48 (glossary-topic-2021-11-22.sty)	1209

1 Main Package Code (glossaries-extra.sty)

1.1 Package Initialisation and Options

```

\NeedsTeXFormat{LaTeX2e}

Rollback releases:
\DeclareRelease{v1.48}{2021-11-22}{glossaries-extra-2021-11-22.sty}
\DeclareCurrentRelease{1.9}{2025-11-03}

Declare package:
\ProvidesPackage{glossaries-extra}[2026/03/06 v2.0 (NLCT)]

Requires xkeyval to define package options.
\RequirePackage{xkeyval}

```

Requires etoolbox package.

```
\RequirePackage{etoolbox}
```

Has glossaries already been loaded?

```
\@ifpackageloaded{glossaries}
{%
```

Already loaded so pass any options to `\setupglossaries`. This means that the options that can only be set when `glossaries` is loaded can't be used.

```
\newcommand{\glstr@dooption}[1]{\setupglossaries{#1}}%
\let\glstr@declareoption\@glstr@declareoption
}
{%
```

Not already loaded, so pass options to `glossaries`.

```
\newcommand{\glstr@dooption}[1]{%
\PassOptionsToPackage{#1}{glossaries}%
}%
```

Set the defaults.

```
\PassOptionsToPackage{toc}{glossaries}
\PassOptionsToPackage{nopostdot}{glossaries}
\PassOptionsToPackage{noredefwarn}{glossaries}
\@ifpackageloaded{polyglossia}%
{%}%
{%
\@ifpackageloaded{babel}%
{\PassOptionsToPackage{translate=babel}{glossaries}}%
{}%
}%
\newcommand*{\glstr@declareoption}[2]{%
\DeclareOptionX{#1}{#2}%
\DeclareOption{#1}{#2}%
}
}
```

Declare package options.

`\glstrundefaction` Determines what to do if an entry hasn't been defined. The two arguments are the error or warning message and the help message if an error should be produced.

```
\newcommand*{\glstrundefaction}[2]{%
\@glstrundeftag\PackageError{glossaries-extra}{#1}{#2}%
}
```

`\glstr@warnonexistsordo` If user wants `undefaction=warn`, then `glossaries v4.19` is required.

```
\newcommand*{\glstr@warnonexistsordo}[1]{}
```

`\glstrundeftag` Text to display when an entry doesn't exist.

```
\newcommand*{\glstrundeftag}{??}
\newcommand*{\glstrundeftag}{}
```

This text is switched on at the start of the document to prevent unwanted text inserted into the preamble if any tests are made before the start of the document.

```

\@glxtr@warn@undefaction This is how \glxtrundefaction should behave if undefaction=warn is set.
    \newcommand*{\@glxtr@warn@undefaction}[2]{%
        \@glxtrundeftag\GlossariesExtraWarning{#1}%
    }

\@glxtr@err@undefaction This is how \glxtrundefaction should behave if undefaction=error is set.
    \newcommand*{\@glxtr@err@undefaction}[2]{%
        \@glxtrundeftag\PackageError{glossaries-extra}{#1}{#2}%
    }

\@glxtr@warn@onexistsordo This is how \glxtr@warnonexistsordo should behave if undefaction=warn is
set.
    \newcommand*{\@glxtr@warn@onexistsordo}[1]{%
        \GlossariesExtraWarning{\string#1\space hasn't been defined, so
            some errors won't be converted to warnings.
            (This most likely means your version of
            glossaries.sty is below version 4.19.)}%
    }

\@glxtr@redef@forlgsentries
    \newcommand*{\@glxtr@redef@forlgsentries}{}

\glxtr@do@redef@forlgsentries
    \newcommand*{\@glxtr@do@redef@forlgsentries}{%
        \renewcommand*{\forlgsentries}[3][\gldefaulttype]{%
            \protected@edef\@glo@list{\csname glolist@##1\endcsname}%
            \ifdefstring{\@glo@list}{,}%
            {%
                \GlossariesExtraWarning{\string\forlgsentries:
                    No entries defined in glossary '##1'}%
            }%
            {%
                \@for##2:=\@glo@list\do
                {%
                    \ifdefempty{##2}{}{##3}%
                }%
            }%
        }%
    }%

undefaction
    \define@choicekey{glossaries-extra.sty}{undefaction}%
    [\glxtr@undefaction@val\glxtr@undefaction@nr]%
    {warn,error}%
    {%
        \ifcase\glxtr@undefaction@nr\relax
            \let\glxtrundefaction\@glxtr@warn@undefaction
            \let\glxtr@warnonexistsordo\@glxtr@warn@onexistsordo
            \let\@glxtr@redef@forlgsentries\@glxtr@do@redef@forlgsentries

```

```

\or
\let\glstrundefaction\@glstr@err@undefaction
\let\glstr@warnonexistsordo\@gobble
\let\@glstr@redef@for@gl@sentries\relax
\fi
}

```

To assist bib2gls, v1.08 introduces the `record` option, which will write information to the aux file whenever an entry needs to be indexed.

`\@glstr@record` Does nothing by default.
`\newcommand*{\@glstr@record}[3]{}`

`\glstr@recordsee` Does nothing by default.
`\newcommand*{\glstr@recordsee}[2]{}`

`\@glstr@defaultnumberformat`
`\newcommand*{\@glstr@defaultnumberformat}{\glstrnumberformat}%`

`\glstrSetDefaultNumberFormat`
`\newcommand*{\glstrSetDefaultNumberFormat}[1]{%`
`\renewcommand*{\@glstr@defaultnumberformat}{#1}%`
`}%`

The `record` option is somewhat problematic. On the first L^AT_EX run the entries aren't defined. This isn't as straight-forward as commands like `\cite` since attributes associated with the entry's category may switch off the indexing or the entry's glossary type might require a particular counter. This kind of information can't be determined until the entry has been defined. So there are two different commands here. One that's used if the entry hasn't been defined, which tries to use sensible defaults, and one which is used when the entry has been defined.

`\@glstr@do@record@wrglossary` The `record=only` option sets `\@do@wrglossary` to this command, which means it's done within `\glstradd` and `\glstrlink`, and so is only done if the entry exists.

```

\newcommand*{\@glstr@do@record@wrglossary}[1]{%
\begingroup
\ifKV@glstrlink@noindex
\else

\protected@edef\@glstr@label{\glstrdetoklabel{#1}}%
\let\glstrlabel\@glstr@label
\glstrwriteentry{#1}%
{%
\ifdefempty{\@glstr@thevalue}%
{%
\ifx\@glstr@org@theHvalue\@glstr@theHvalue
\else
\let\theHglstrentrycounter\@glstr@theHvalue

```

```

\fi
\glxtr@saveentrycounter
\let\@@do@wrglossary\@glxtr@dorecord
}%
{%
\let\theglentrycounter\@glxtr@thevalue
\let\theHglentrycounter\@glxtr@theHvalue
\let\@@do@wrglossary\@glxtr@dorecordnodefer
}%
\ifx\@glxtr@record@setting\@glxtr@record@setting@alsoindex
\glxtr@@do@wrglossary{#1}%
\else
\@@glxtrwrglossmark

```

Increment associated counter.

```

\glxtr@inc@wrglossaryctr{#1}%
\@@do@wrglossary
\fi
}%
\fi
\endgroup
}

```

`\glxtr@do@alsoindex@wrglossary` The `record=alsoindex` option needs to both record and index.

```

\newcommand*{\glxtr@do@alsoindex@wrglossary}[1]{%
\glxtr@@do@wrglossary{#1}%
\@glxtr@do@record@wrglossary{#1}%
}

```

`\@@glxtr@record` The `record=only` option sets `\@glxtr@record` to this. This performs the recording if the entry *doesn't exist* and is done at the start of `\@gls@field@link` and commands like `\@gls@` (before the existence test). This means that it disregards the `wrgloss` key.

The first argument is the option list (as passed in the first optional argument to commands like `\gls`). This allows the `noindex` setting to be picked up. The second argument is the entry's label. The third argument is the key family (`glslink` in most cases, `glossadd` for `\glsadd`).

```

\newcommand*{\@@glxtr@record}[3]{%

```

Save the label in case it's needed. This needs to be outside the existence check to allow the post-link hook to reference it.

```

\protected@edef\@gls@label{\glsetoklabel{#2}}%
\let\glslabel\@gls@label
\ifglentryexists{#2}{}%
{%
\@@glxtrwrglossmark
\begingroup
\let\@glsnumberformat\@glxtr@defaultnumberformat
\def\@glxtr@thevalue{}%

```

```

\def\@glstr@theHvalue{\@glstr@thevalue}%
\let\@glstr@org@theHvalue\@glstr@theHvalue

```

Entry hasn't been defined, so we'll have to assume it's `\glscounter` by default.

```

\let\@glscounter\glscounter

```

Unless the `equations` option is on and this is inside a numbered maths environment.

```

\if@glstr@equations
  \@glstr@use@equation@counter
\fi

```

Check for default options (which may switch off indexing).

```

\@glsc@setdefault@glslink@opts

```

Implement any pre-key settings.

```

\csuse{\@glstr@#3@prekeys}%

```

Assign keys.

```

\setkeys{#3}{#1}%

```

Implement any post-key settings. Is the auto-add on?

```

\glstr@do@autoadd{#3}%

```

Check post-key hook.

```

\csuse{\@glstr@#3@postkeys}%

```

Increment associated counter.

```

\glstr@inc@wrglossaryctr{#2}%

```

Check if `noindex` option has been used.

```

\ifKV@glslink@noindex
\else
  \glswriteentry{#2}%
  {%

```

Check if `thevalue` has been set.

```

    \ifdefempty{\@glstr@thevalue}%
    {%

```

Key `thevalue` hasn't been set, but check if `theHvalue` has been set. (Not particularly likely, but allow for it.)

```

      \ifx\@glstr@org@theHvalue\@glstr@theHvalue
      \else
        \let\theHglentrycounter\@glstr@theHvalue
      \fi

```

Save the entry counter.

```

\glstr@saveentrycounter

```

Temporarily redefine `\@do@wrglossary` for use with `\glstr@do@wrglossary`.

```

\let\@do@wrglossary\@glstr@dorecord
}%
{%

```

thevalue has been set, so there's no need to defer writing the location value. (If it's dependent on the page counter, the counter key should be set instead.)

```

\let\theglsentrycounter\@glxtr@thevalue
\let\theHglentrycounter\@glxtr@theHvalue
\let\@do@wrglossary\@glxtr@dorecordnodefer
}%
\ifx\@glxtr@record@setting\@glxtr@record@setting@alsoindex
\glxtr@do@wrglossary{#2}%
\else

```

No need to escape special characters.

```

\@do@wrglossary
\fi
}%
\fi
\endgroup
}%
}

```

\@glxtr@glslink@prekeys

```
\newcommand{\@glxtr@glslink@prekeys}{\glslinkpresetkeys}
```

\@glxtr@glslink@postkeys

```
\newcommand{\@glxtr@glslink@postkeys}{\glslinkpostsetkeys}
```

\@glxtr@glossadd@prekeys

```
\newcommand{\@glxtr@glossadd@prekeys}{\glsaddpresetkeys}
```

\@glxtr@glossadd@postkeys

```
\newcommand{\@glxtr@glossadd@postkeys}{\glsaddpostsetkeys}
```

\@glxtr@dorecord If record=alsoindex or record=hybrid is used, then \@glslocref may have been escaped, but this isn't appropriate here.

```

\newcommand*\@glxtr@dorecord{%
\@glxtr@dorecord\@gls@label\glxtr@record\@glxtr@do@nameref@record
}

```

\@@glxtr@dorecord

```

\newcommand*\@@glxtr@dorecord[3]{%
\global\let\@glsrecordlocref\theglsentrycounter
\let\@glxtr@orgprefix\@glo@counterprefix
\ifx\theglsentrycounter\theHglentrycounter
\def\@glo@counterprefix{}%
\else

```

Protect against non-expandable commands occurring in the location.

```

\protected@edef\@glxtr@theentrycounter{\theglsentrycounter}%
\protected@edef\@glxtr@theHentrycounter{\theHglentrycounter}%
\@onelevel@sanitize\@glxtr@theentrycounter

```



```

\@onelevel@sanitize\@glxstr@theHentrycounter
\@xp@glxstr@getcounterprefix
{\@glxstr@theentrycounter}{\@glxstr@theHentrycounter}%
\fi

```

Don't protect the `\@glxstr@recordloc` from premature expansion. If the counter isn't page then it needs expanding. If the location includes `\thepage` then `\protected@write` will automatically deal with it.

```

\ifx\@glxstr@record@setting\@glxstr@record@setting@nameref
#3%
{\#1}{\@glo@counterprefix}{\@glxstr@counter}{\@glxstr@numberformat}%
{\@glxstr@recordloc}%
\else
\@bibglxstr@write@aux{\string#2%
{\#1}{\@glo@counterprefix}{\@glxstr@counter}{\@glxstr@numberformat}%
{\@glxstr@recordloc}}%
\fi
\@glxstr@counterrecordhook
\let\@glo@counterprefix\@glxstr@orgprefix
}

```

`\@glxstr@dorecordnodefer` As above, but don't defer expansion of location. This uses `\theglentrycounter` directly for the location rather than `\@glxstr@loc` since there's no need to guard against premature expansion of the page counter.

```

\newcommand*\@glxstr@dorecordnodefer{%
\ifx\theglentrycounter\theHglentrycounter
\ifx\@glxstr@record@setting\@glxstr@record@setting@nameref
\@glxstr@do@nameref@record
{\@glxstr@label}{\@glxstr@counter}{\@glxstr@numberformat}%
{\theglentrycounter}%
\else
\@bibglxstr@write@aux{\string\@glxstr@record
{\@glxstr@label}{\@glxstr@counter}{\@glxstr@numberformat}%
{\theglentrycounter}}%
\fi
\else
\@xp@glxstr@getcounterprefix{\theglentrycounter}{\theHglentrycounter}%
\ifx\@glxstr@record@setting\@glxstr@record@setting@nameref
\@glxstr@do@nameref@record
{\@glxstr@label}{\@glo@counterprefix}{\@glxstr@counter}%
{\@glxstr@numberformat}{\theglentrycounter}%
\else
\@bibglxstr@write@aux{\string\@glxstr@record
{\@glxstr@label}{\@glo@counterprefix}{\@glxstr@counter}{\@glxstr@numberformat}%
{\theglentrycounter}}%
\fi
\fi
\@glxstr@counterrecordhook
}

```

`\@glxtr@ifnum@mmode` Check if in a numbered maths environment. The `amsmath` package is automatically loaded by `datatool-base`, which is required by `glossaries`, so `\ifst@rred` and `\if@display` should both be defined.

```
\newcommand{\@glxtr@ifnum@mmode}[2]{%
  \ifmmode
    \ifst@rred
      #2%
    \else
```

Non-`amsmath` environments and regular inline math mode isn't flagged as starred by `amsmath`, but we can't use `\mathchoice` in this case as it's not the current style that's relevant. Instead we can use `amsmath`'s `\if@display`. This may not work for environments that aren't provided by `amsmath`.

```
    \if@display #1\else #2\fi
  \fi
\else
  #2%
\fi
}
```

`\@glxtr@do@nameref@record` With `record=nameref`, the current label information is included in the record, but this may not have been defined, so `\csuse` will prevent an undefined control sequence error and just leave the last two arguments blank if there's no information. In the event that a record is in `amsmath`'s `align` environment `\@currentHref` will be out. There may be other instances where `\@currentHref` is out, so this also saves `\theHglentrycounter`, which is useful if it can't be obtained by prefixing `\theHglentrycounter`.

```
\newcommand*{\@glxtr@do@nameref@record}[5]{%
  \gls@ifnotmeasuring
  {%
    \@bibgls@write@aux{}\string\glxtr@record@nameref
    {#1}{#2}{#3}{#4}{#5}%
    {\csuse{\@currentlabelname}}{\csuse{\@currentHref}}%
    {\theHglentrycounter}}%
  }%
}
```

`\@@glxtr@recordcounter`

```
\newcommand*{\@@glxtr@recordcounter}{%
  \@glxtr@noop@recordcounter
}
```

`\@glxtr@noop@recordcounter`

```
\newcommand*{\@glxtr@noop@recordcounter}[1]{%
  \PackageError{glossaries-extra}{\string\GlsXtrRecordCounter\space
    requires record=only or record=hybrid package option}{}%
}
```

```

\@glxtr@op@recordcounter
    \newcommand*{\@glxtr@op@recordcounter}[1]{%
        \protected@eappto\@glxtr@counterrecordhook{\noexpand\@glxtr@docounterrecord{#1}}%
    }

\@glxtr@recordsee Deal with \glssee in record mode. (This doesn't increment the associated
counter.)
    \newcommand*{\@glxtr@recordsee}[2]{%
        \@glxtrwrglossmark
        \def\@gls@xref{#2}%
        \@onelevel@sanitize\@gls@xref
        \@bibgls@write@aux{}\string\@glxtr@recordsee{#1}{\@gls@xref}}%
    }

\printunsrtglossaryunit
    \newcommand{\printunsrtglossaryunit}{%
        \print@noop@unsrtglossaryunit
    }

\glxtr@setup@record Initialise.
    \newcommand*{\glxtr@setup@record}{\let\@do@wrglossary\glxtr@do@wrglossary}

@indexonly@saveentrycounter Only store the entry counter information if the indexing is on.
    \newcommand*{\glxtr@indexonly@saveentrycounter}{%
        \ifKV@glslink@noindex
        \else
            \glxtr@saveentrycounter
        \fi
    }

\glxtr@addloclistfield
    \newcommand*{\glxtr@addloclistfield}{%
        \key@ifundefined{glossentry}{loclist}%
        {%
            \define@key{glossentry}{loclist}{\def\@glo@loclist{##1}}%
            \appto\@gls@keymap{, {loclist}{loclist}}%
            \appto\@newglossaryentryprehook{\def\@glo@loclist{}}%
            \appto\@newglossaryentryposthook{%
                \gls@assign@field{\@glo@label}{loclist}{\@glo@loclist}%
            }%
            \glssetnoexpandfield{loclist}%
        }%
        {}%
    }

The loclist field is just a comma-separated list. The location field is the format-
ted list.
    \key@ifundefined{glossentry}{location}%
    {%
        \define@key{glossentry}{location}{\def\@glo@location{##1}}%
    }

```

```

\appto\@gls@keymap{,{location}{location}}%
\appto\@newglossaryentryprehook{\def\@glo@location{}}%
\appto\@newglossaryentryposthook{%
  \gls@assign@field{ }\@glo@label}{location}{\@glo@location}%
}%
\glssetnoexpandfield{location}%
}%
{}%

```

Add a key to store the group heading.

```

\key@ifundefined{glossentry}{group}%
{%
  \define@key{glossentry}{group}{\def\@glo@group{##1}}%
  \appto\@gls@keymap{,{group}{group}}%
  \appto\@newglossaryentryprehook{\def\@glo@group{}}%
  \appto\@newglossaryentryposthook{%
    \gls@assign@field{ }\@glo@label}{group}{\@glo@group}%
  }%
  \glssetnoexpandfield{group}%
}%
{}%
}

```

`\@glsxtr@record@setting` Keep track of the record package option.

```

\newcommand*{\@glsxtr@record@setting}{off}

```

`\@glsxtr@record@setting@alsoindex` As from v1.46, the `record=alsoindex` is renamed to `record=hybrid` with `record=alsoindex` as a deprecated synonym to avoid confusion. The internal commands that include `alsoindex` in the name will remain unchanged to avoid breaking things, but this command will need to be redefined by `record=hybrid`.

```

\newcommand*{\@glsxtr@record@setting@alsoindex}{alsoindex}

```

`\@glsxtr@record@setting@only`

```

\newcommand*{\@glsxtr@record@setting@only}{only}

```

`\@glsxtr@record@setting@nameref`

```

\newcommand*{\@glsxtr@record@setting@nameref}{nameref}

```

`\@glsxtr@if@record@only`

```

\newcommand*{\@glsxtr@if@record@only}[2]{%
  \ifx\@glsxtr@record@setting\@glsxtr@record@setting@only
    #1%
  \else
    \ifx\@glsxtr@record@setting\@glsxtr@record@setting@nameref
      #1%
    \else
      #2%
    \fi
  \fi
}

```

```

\@glxtr@record@setting@off
\newcommand*{\@glxtr@record@setting@off}{off}

tr@warn@hybrid@noprintgloss Used by hybrid method if \printglossary isn't used.
\newcommand\@glxtr@warn@hybrid@noprintgloss{%
  \ifdefstring{\@glo@types}{,}%
  {%
    \GlossariesExtraWarningNoLine{No glossaries have been defined}%
  }%
  {%
    \GlossariesExtraWarningNoLine{No \string\printglossary\space
      or \string\printglossaries\space
      found. ^^JYou have requested the hybrid setting
      record=\@glxtr@record@setting\space which requires a
      combination of bib2gls (to fetch entries) and makeindex/xindy
      (to sort and collate the entries). If you only want to use
      bib2gls then change the option to record=only or record=nameref}%
  }%
}

\@glxtr@record@only@setup Initialisation code for record=only and record=nameref
\newcommand*{\@glxtr@record@only@setup}{%
  \def\glxtr@setup@record{%
    \@glxtr@autoseeindexfalse
    \let\@do@seeglossary\@glxtr@recordsee
    \let\@glxtr@record\@glxtr@record
    \let\@do@wrglossary\@glxtr@do@record@wrglossary
    \let\@gls@saveentrycounter\relax
    \let\glxtrundefaction\@glxtr@warn@undefaction
    \let\glxtr@warnonexistssordo\@glxtr@warn@onexistssordo
    \glxtr@addloclistfield
    \renewcommand*{\@glxtr@autoindexcrossrefs}{}%
    \let\@glxtr@recordcounter\@glxtr@op@recordcounter
    \def\printunsrtglossaryunit{\print@op@unsrtglossaryunit}%
  }
  Switch off the index suppression for aliased entries. (bib2gls will deal with
  them.)
  \def\glxtrsetaliasnoindex{}%
  \@gls@setupsort@none was only introduced to glossaries v4.30, so it may not be
  available. If it's defined, use it to remove the unnecessary overhead of escaping
  and sanitizing the sort value.
  \ifdef\@gls@setupsort@none{\@gls@setupsort@none}{}%
  Warn about using \printglossary:
  \def\glxtrNoGlossaryWarning{\@glxtr@record@noglossarywarning}%
  Load glossaries-extra-bib2gls:
  \RequirePackage{glossaries-extra-bib2gls}%
}%
}

```

record Now define the record package option. As from v1.46, `record=alsoindex` is a deprecated synonym of `record=hybrid` to avoid confusion.

```
\define@choicekey{glossaries-extra.sty}{record}
[\@glxtr@record@setting\glxtr@record@nr]%
{off,only,alsoindex,nameref,hybrid}%
[only]%
{%
  \ifcase\glxtr@record@nr\relax
```

Don't record.

```
\def\glxtr@setup@record{%
  \renewcommand*{\@do@seeglossary}{\@glxtr@doseeglossary}%
  \renewcommand*{\@glxtr@record}[3]{%
    \let\@do@wrglossary\glxtr@do@do@wrglossary
    \let\@glxtr@saveentrycounter\glxtr@indexonly@saveentrycounter
    \let\glxtrundefaction\glxtr@err@undefaction
    \let\glxtr@warnonexistssordo\@gobble
    \let\@glxtr@recordcounter\glxtr@noop@recordcounter
    \def\printunsrtglossaryunit{\print@noop@unsrtglossaryunit}%
    \undef\glxtrsetaliasnoindex
  }%
\or
```

Only record (don't index).

```
\@glxtr@record@only@setup
\or
```

Record and index. This option doesn't load `glossaries-extra-bib2gls` as the sorting is performed by `xindy` or `makeindex`. Index in this sense refers to the indexing mechanism used with indexing applications such as `makeindex` and `xindy`, but this could be confused with recording locations so "alsoindex" is now deprecated in favour of "hybrid", which is more obvious.

```
\def\glxtr@setup@record{%
  \renewcommand*{\@glxtr@record@setting@alsoindex}{alsoindex}%
  \renewcommand*{\@do@seeglossary}{\@glxtr@dosee@alsoindex@glossary}%
  \let\@glxtr@record\@glxtr@record
  \let\@do@wrglossary\glxtr@do@alsoindex@wrglossary
  \let\@glxtr@saveentrycounter\glxtr@indexonly@saveentrycounter
  \let\glxtrundefaction\glxtr@warn@undefaction
  \let\glxtr@warnonexistssordo\glxtr@warn@onexistssordo
  \glxtr@addloclistfield
  \let\@glxtr@recordcounter\glxtr@op@recordcounter
  \def\printunsrtglossaryunit{\print@op@unsrtglossaryunit}%
  \undef\glxtrsetaliasnoindex
}%
\or
```

Only record (don't index) but also include `nameref` information.

```
\@glxtr@record@only@setup
\ifundef\hyperlink
{\GlossariesExtraWarning{You have requested record=nameref but
```

```

        the document doesn't support hyperlinks}}%
    {}%
\or
Hybrid record (use bib2gls to fetch definitions) and index (use makeindex/xindy
to sort and collate).
\def\glstr@setup@record{%
  \renewcommand*{\@glstr@record@setting@alsoindex}{hybrid}%
  \renewcommand*{\@do@seeglossary}{\@glstr@dosee@alsoindex@glossary}%
  \let\@glstr@record\@glstr@record
  \let\@do@wrglossary\glstr@do@alsoindex@wrglossary
  \let\@glstr@saveentrycounter\glstr@indexonly@saveentrycounter
  \let\glstrundefaction\glstr@warn@undefaction
  \let\glstr@warnonexistsordo\glstr@warn@onexistsordo
  \glstr@addloclistfield
  \let\@glstr@recordcounter\glstr@op@recordcounter
  \def\printunsrtglossaryunit{\print@op@unsrtglossaryunit}%
  \undef\glstrsetaliasnoindex
}%
\fi
}

```

bibglssaux Provide an option to put the records in a different aux file that will only be read by bib2gls and not by L^AT_EX. A large number of records in the aux file can slow down the document build as L^AT_EX has to parse it all. This will require an extra write register, so may not be so desirable for documents with small glossaries but a large number of temporary files.

```

\define@key{glossaries-extra.sty}{bibglssaux}{%
  \glstrsetbibglssaux{#1}%
}

```

\glstrsetbibglssaux

```

\newcommand{\glstrsetbibglssaux}[1]{%
  \renewcommand{\@glstr@setup@bibglssaux}{\@glstr@setup@bibglssaux{#1}}%
}

```

\@glstr@setup@bibglssaux

```

\newcommand{\@glstr@setup@bibglssaux}{%
  \renewcommand{\glstrsetbibglssaux}[1]{%
    \@glstr@setup@bibglssaux{##1}%
  }%
}
\AtBeginDocument{\@glstr@setup@bibglssaux}

```

\@@glstr@setup@bibglssaux

```

\newcommand{\@@glstr@setup@bibglssaux}[1]{%
  \ifstrempy{#1}%
  {\renewcommand{\bibglstr@write@aux}{\protected@write\@auxout}}%
  {\@set@bibglstr@write@aux{#1.aux}}%
}

```

`\@bibgls@write@aux` Just used for writing records.

```
\newcommand{\@bibgls@write@aux}{\protected@write\@auxout}
```

`\@set@bibgls@write@aux`

```
\newcommand{\@set@bibgls@write@aux}[1]{%
\protected@write\@auxout{%
{\string\providecommand{\string\@bibgls@input}[1]{}}%
\protected@write\@auxout{\string\@bibgls@input{#1}}%
\global\newwrite\@bibgls@auxout
\openout\@bibgls@auxout=#1
\AtEndDocument{\closeout\@bibgls@auxout}%
\gdef\@bibgls@write@aux{\protected@write\@bibgls@auxout}%
\gdef\@set@bibgls@write@aux#1{\GlossariesExtraWarning{repeated
invocation of bibglsaux option ignored}}%
}
```

Version 1.06 changes the `docdef` option to a choice rather than boolean setting. The available values are: `false`, `true` or `restricted`. The `restricted` option permits document definitions as long as they occur before the first glossary is displayed.

`\@glxstr@docdefval` The `docdef` value is stored as an integer: 0 (`false`), 1 (`true`) and 2 (`restricted`).

```
\newcommand*{\@glxstr@docdefval}{0}
```

Need to provide conditional commands that are backward compatible:

`\if@glxstrdocdef`

```
\newcommand*{\if@glxstrdocdef}{\ifnum\@glxstr@docdefval>0 }
```

`\@glxstrdocdeftrue`

```
\newcommand*{\@glxstrdocdeftrue}{\def\@glxstr@docdefval{1}}
```

`\@glxstrdocdeffalse`

```
\newcommand*{\@glxstrdocdeffalse}{\def\@glxstr@docdefval{0}}
```

`docdef` By default don't allow entries to be defined in the document to encourage the user to define them in the preamble, but if the user is really determined to define them in the document allow them to request this.

```
\define@choicekey{glossaries-extra.sty}{docdef}
[\@glxstr@docdefsetting\@glxstr@docdefval]%
{false,true,restricted,atom}[true]%
{%
\ifnum\@glxstr@docdefval>1\relax
\renewcommand*{\@glsdofexistsorwarn}{\glsdofexists}%
\else
\renewcommand*{\@glsdofexistsorwarn}{\glsdofexistsorwarn}%
\fi
}
```



```

\if@glxtrdocdefrestricted
    \newcommand*{\if@glxtrdocdefrestricted}{\ifnum\@glxtr@docdefval>1 }

\@glxdoifexistsorwarn Need an error to notify user if an undefined entry is being referenced in the
glossary for the docdef=restricted option. This is used by \glossentryname
(but not by \glossentrydesc etc as one error per entry is sufficient).
    \newcommand*{\@glxdoifexistsorwarn}{\glxdoifexistsorwarn}

indexcrossrefs Automatically index cross references at the end of the document
    \define@boolkey{glossaries-extra.sty}[@glxtr]{indexcrossrefs}[true]{%
        \if@glxtrindexcrossrefs
        \else
            \renewcommand*{\@glxtr@autoindexcrossrefs}{}%
        \fi
    }

Switch off since this can increase the build time.
    \@glxtrindexcrossrefsfalse

But allow see and seealso keys to switch it on automatically.

\@glxtr@autoindexcrossrefs
    \newcommand*{\@glxtr@autoindexcrossrefs}{\@glxtrindexcrossrefstrue}

autoseeindex Provide a boolean option to allow the user to prevent the automatic indexing
of the cross-referencing keys see, seealso and alias.
    \define@boolkey{glossaries-extra.sty}[@glxtr@]{autoseeindex}[true]{%
    }
    \@glxtr@autoseeindextrue

equations Provide a boolean option to automatically switch to the equation counter when
in a numbered maths environment.
    \define@boolkey{glossaries-extra.sty}[@glxtr@]{equations}[true]{%
    }
    \@glxtr@equationsfalse

\glxtr@float
    \let\glxtr@float\@float

\glxtr@dblfloat
    \let\glxtr@dblfloat\@dblfloat

floats Provide a boolean option to automatically switch to the the corresponding
counter when in a float.
    \define@boolkey{glossaries-extra.sty}[@glxtr@]{floats}[true]{%
        \if@glxtr@floats
            \renewcommand*{\@float}[1]{\renewcommand{\glscounter}{##1}\glxtr@float{##1}}%
            \renewcommand*{\@dblfloat}[1]{\renewcommand{\glscounter}{##1}\glxtr@dblfloat{##1}}%
        \else

```

```

\let\@float\glxtr@float
\let\@dblfloat\glxtr@dblfloat
\fi
}
\@glxtr@floatsfalse

\GlossariesExtraInfo Allow users to suppress information messages.
\newcommand*\GlossariesExtraInfo[1]{\PackageInfo{glossaries-extra}{#1}}

\GlossariesExtraWarning Allow users to suppress warnings.
\newcommand*\GlossariesExtraWarning[1]{\PackageWarning{glossaries-extra}{#1}}

\GlossariesExtraWarningNoLine Allow users to suppress warnings.
\newcommand*\GlossariesExtraWarningNoLine[1]{%
\PackageWarningNoLine{glossaries-extra}{#1}}

\@glxtr@declareoption{nowarn}{%
\let\GlossariesExtraWarning\@gobble
\let\GlossariesExtraWarningNoLine\@gobble
\glxtr@doption{nowarn}%
}

\@glxtr@defpostpunc Redefines \glspostdescription. The postdot and nopostdot options will have
to redefine this.
\newcommand*\@glxtr@defpostpunc{}

postdot Shortcut for nopostdot=false
\@glxtr@declareoption{postdot}{%
\glxtr@doption{nopostdot=false}%
\renewcommand*\@glxtr@defpostpunc{%
\renewcommand*\glspostdescription{%
\ifglsnopostdot\else.\spacefactor\sfcode'\. \fi}%
}%
}

nopostdot Needs to redefine \@glxtr@defpostpunc
\define@choicekey{glossaries-extra.sty}{nopostdot}{true,false}[true]{%
\glxtr@doption{nopostdot=#1}%
\renewcommand*\@glxtr@defpostpunc{%
\renewcommand*\glspostdescription{%
\ifglsnopostdot\else.\spacefactor\sfcode'\. \fi}%
}%
}

postpunc Set the post-description punctuation. This also sets the \ifglsnopostdot con-
ditional, which now indicates if the post-description punctuation has been sup-
pressed.
\define@key{glossaries-extra.sty}{postpunc}{%
\glxtr@doption{nopostdot=false}%

```

```

\ifstrequal{#1}{dot}%
{%
  \renewcommand*{\@glsxtr@defpostpunc}{%
    \renewcommand*{\glspostdescription}{.\spacefactor\sfcode`. }%
  }%
}%
{%
  \ifstrequal{#1}{comma}%
  {%
    \renewcommand*{\@glsxtr@defpostpunc}{%
      \renewcommand*{\glspostdescription}{,}%
    }%
  }%
  {%
    \ifstrequal{#1}{none}%
    {%
      \glsxtr@dooption{nopostdot=true}%
      \renewcommand*{\@glsxtr@defpostpunc}{%
        \renewcommand*{\glspostdescription}{}%
      }%
    }%
  }%
  {%
    \renewcommand*{\@glsxtr@defpostpunc}{%
      \renewcommand*{\glspostdescription}{#1}%
    }%
  }%
}%
}%
}

```

`\glsxtrabbrvtype` Glossary type for abbreviations.

```
\newcommand*{\glsxtrabbrvtype}{\glsdefaulttype}
```

`\@glsxtr@abbreviationsdef` Set by abbreviations option.

```
\newcommand*{\@glsxtr@abbreviationsdef}{}%
```

`\abbreviationsname` v1.50 unconditionally provide this command, so it can be redefined by a language module.

```

\@ifpackageloaded{babel}%
{\providecommand{\abbreviationsname}{\acronymname}}%
{\providecommand{\abbreviationsname}{Abbreviations}}%

```

`\@glsxtr@doabbreviationsdef`

```

\newcommand*{\@glsxtr@doabbreviationsdef}{%
  \newglossary[glg-abr]{abbreviations}{gls-abr}{glo-abr}{\abbreviationsname}%
  \renewcommand*{\glsxtrabbrvtype}{abbreviations}%
  \newcommand*{\printabbreviations}[1][1]{%
    \printglossary[type=\glsxtrabbrvtype,##1]%
  }%
  \disable@keys{glossaries-extra.sty}{abbreviations}%
}

```

If the acronym option hasn't been used, change `\acronymtype` to `\glstrabbrvtype`.

```

\ifglssacronym
\else
\renewcommand*{\acronymtype}{\glstrabbrvtype}%
\fi
}%

```

abbreviations If abbreviations, create a new glossary type for abbreviations.

```

\@glstr@declareoption{abbreviations}{%
\let\@glstr@abbreviationsdef\@glstr@doabbreviationsdef
}

```

`\shortcut@gl`

```

\newcommand{\shortcut@gl}{\cgl}

```

`\shortcut@glsp`

```

\newcommand{\shortcut@glsp}{\cglsp}

```

`\shortcut@Gls`

```

\newcommand{\shortcut@Gls}{\cGls}

```

`\shortcut@Glspl`

```

\newcommand{\shortcut@Glspl}{\cGlspl}

```

`\shortcut@GLS`

```

\newcommand{\shortcut@GLS}{\cGLS}

```

`\shortcut@GLSpl`

```

\newcommand{\shortcut@GLSpl}{\cGLSpl}

```

DefineAbbreviationShortcuts Enable shortcut commands for the abbreviations. Unlike the analogous command provided by glossaries, this uses `\newcommand` instead of `\let` as a safety feature (except for `\newabbr` which is also provided with `\GlsXtrDefineAcShortcuts`).

```

\newcommand*{\GlsXtrDefineAbbreviationShortcuts}{%
\newcommand*{\ab}{\shortcut@gl}%
\newcommand*{\abp}{\shortcut@glsp}%
\newcommand*{\as}{\glstrshort}%
\newcommand*{\asp}{\glstrshortpl}%
\newcommand*{\al}{\glstrlong}%
\newcommand*{\alp}{\glstrlongpl}%
\newcommand*{\af}{\glstrfull}%
\newcommand*{\afp}{\glstrfullpl}%
\newcommand*{\Ab}{\shortcut@Gls}%
\newcommand*{\Abp}{\shortcut@Glspl}%
\newcommand*{\As}{\Glsxtrshort}%
\newcommand*{\Asp}{\Glsxtrshortpl}%
\newcommand*{\Al}{\Glsxtrlong}%
}

```

```

\newcommand*{\Alp}{\Glsxtrlongpl}%
\newcommand*{\Af}{\Glsxtrfull}%
\newcommand*{\Afp}{\Glsxtrfullpl}%
\newcommand*{\AB}{\shortcut@GLS}%
\newcommand*{\ABP}{\shortcut@GLSpl}%
\newcommand*{\AS}{\Glsxtrshort}%
\newcommand*{\ASP}{\Glsxtrshortpl}%
\newcommand*{\AL}{\Glsxtrlong}%
\newcommand*{\ALP}{\Glsxtrlongpl}%
\newcommand*{\AF}{\Glsxtrfull}%
\newcommand*{\AFP}{\Glsxtrfullpl}%
\glsmfuaddmap{\ab}{\Ab}%
\glsmfublocker{\AB}%
\glsmfuaddmap{\abp}{\Abp}%
\glsmfublocker{\ABP}%
\glsmfuaddmap{\as}{\As}%
\glsmfublocker{\AS}%
\glsmfuaddmap{\asp}{\Asp}%
\glsmfublocker{\ASP}%
\glsmfuaddmap{\al}{\Al}%
\glsmfublocker{\AL}%
\glsmfuaddmap{\alp}{\Alp}%
\glsmfublocker{\ALP}%
\glsmfuaddmap{\af}{\Af}%
\glsmfublocker{\AF}%
\glsmfuaddmap{\afp}{\Afp}%
\glsmfublocker{\AFP}%

\providecommand*{\newabbr}{\newabbreviation}%

```

Disable this command after it's been used.

```

\let\GlsXtrDefineAbbreviationShortcuts\relax
}

```

`\GlsXtrDefineAcShortcuts` Enable shortcut commands for the abbreviations, but uses the analogous commands provided by glossaries.

```

\newcommand*{\GlsXtrDefineAcShortcuts}{%
  \newcommand*{\ac}{\shortcut@gls}%
  \newcommand*{\acp}{\shortcut@GLSpl}%
  \newcommand*{\acs}{\Glsxtrshort}%
  \newcommand*{\acsp}{\Glsxtrshortpl}%
  \newcommand*{\acl}{\Glsxtrlong}%
  \newcommand*{\aclp}{\Glsxtrlongpl}%
  \newcommand*{\acf}{\Glsxtrfull}%
  \newcommand*{\acfp}{\Glsxtrfullpl}%
  \newcommand*{\Ac}{\shortcut@GLS}%
  \newcommand*{\Acp}{\shortcut@GLSpl}%
  \newcommand*{\Acs}{\Glsxtrshort}%
  \newcommand*{\Acsp}{\Glsxtrshortpl}%
  \newcommand*{\Acl}{\Glsxtrlong}%
}

```

```

\newcommand*\Aclp{\Glsxtrlongpl}%
\newcommand*\Acf{\Glsxtrfull}%
\newcommand*\Acfp{\Glsxtrfullpl}%
\newcommand*\AC{\shortcut@GLS}%
\newcommand*\ACP{\shortcut@GLSpl}%
\newcommand*\ACS{\Glsxtrshort}%
\newcommand*\ACSP{\Glsxtrshortpl}%
\newcommand*\ACL{\Glsxtrlong}%
\newcommand*\ACLP{\Glsxtrlongpl}%
\newcommand*\ACF{\Glsxtrfull}%
\newcommand*\ACFP{\Glsxtrfullpl}%
\glsmfuaddmap{ac}{Ac}%
\glsmfublocker{AC}%
\glsmfuaddmap{acp}{Acp}%
\glsmfublocker{ACP}%
\glsmfuaddmap{acs}{Acs}%
\glsmfublocker{ACS}%
\glsmfuaddmap{acsp}{Acsp}%
\glsmfublocker{ACSP}%
\glsmfuaddmap{acl}{Acl}%
\glsmfublocker{ACL}%
\glsmfuaddmap{aclp}{Aclp}%
\glsmfublocker{ACLP}%
\glsmfuaddmap{acf}{Acf}%
\glsmfublocker{ACF}%
\glsmfuaddmap{acfp}{Acfp}%
\glsmfublocker{ACFP}%

\providecommand*\newabbr{\newabbreviation}%

```

Disable this command after it's been used.

```

\let\GlsXtrDefineAcShortcuts\relax
}

```

`\GlsXtrDefineOtherShortcuts` Similarly provide shortcut versions for the commands provided by the `symbols` and `numbers` options.

```

\newcommand*\GlsXtrDefineOtherShortcuts{%
  \newcommand*\newentry{\newglossaryentry}%
  \ifdef\printsymbols
  {%
    \newcommand*\newsym{\glsxtrnewsymbol}%
  }{%
  \ifdef\printnumbers
  {%
    \newcommand*\newnum{\glsxtrnewnumber}%
  }{%
  \let\GlsXtrDefineOtherShortcuts\relax
}

```

Always use the long forms, not the shortcuts, where portability is an issue.

(For example, when defining entries in a file that may be input by multiple documents.)

`\@glxtr@setupshortcuts` Command used to set the shortcuts option.

```
\newcommand*{\@glxtr@setupshortcuts}{}
```

`\@glxtr@shortcutsval` Store the value of the shortcuts option. (Needed by bib2gls.)

```
\newcommand*{\@glxtr@shortcutsval}{\ifglxsacrshortcuts acro\else none\fi}%
```

shortcuts Provide shortcuts option. Unlike the glossaries version, this is a choice rather than a boolean key but it also provides `shortcuts=true` and `shortcuts=false`, which are equivalent to `shortcuts=all` and `shortcuts=none`. Multiple use of this option in the *same* option list will override each other. New to v1.17: `shortcuts=ac` which implements `\GlsXtrDefineAcShortcuts` (not included in `shortcuts=all` as it conflicts with other shortcuts).

```
\define@choicekey{glossaries-extra.sty}{shortcuts}%
[\@glxtr@shortcutsval\@glxtr@shortcutsnr]%
{acronyms,acro,abbreviations,abbr,other,all,true,ac,acother,abother,none,false}[true]{%
  \ifcase\@glxtr@shortcutsnr\relax % acronyms
    \renewcommand*{\@glxtr@setupshortcuts}{%
      \glxsacrshortcutstrue
      \DefineAcronymSynonyms
    }%
  \or % acro
    \renewcommand*{\@glxtr@setupshortcuts}{%
      \glxsacrshortcutstrue
      \DefineAcronymSynonyms
    }%
  \or % abbreviations
    \renewcommand*{\@glxtr@setupshortcuts}{%
      \GlsXtrDefineAbbreviationShortcuts
    }%
  \or % abbr
    \renewcommand*{\@glxtr@setupshortcuts}{%
      \GlsXtrDefineAbbreviationShortcuts
    }%
  \or % other
    \renewcommand*{\@glxtr@setupshortcuts}{%
      \GlsXtrDefineOtherShortcuts
    }%
  \or % all
    \renewcommand*{\@glxtr@setupshortcuts}{%
      \glxsacrshortcutstrue

      \GlsXtrDefineAcShortcuts
      \GlsXtrDefineAbbreviationShortcuts
      \GlsXtrDefineOtherShortcuts
    }%
  \or % true
```

```

\renewcommand*{\@glxtr@setupshortcuts}{%
  \glsacrshortcutstrue

  \GlsXtrDefineAcShortcuts
  \GlsXtrDefineAbbreviationShortcuts
  \GlsXtrDefineOtherShortcuts
}%

\or % ac
\renewcommand*{\@glxtr@setupshortcuts}{%
  \glsacrshortcutstrue
  \GlsXtrDefineAcShortcuts
}%

\or % acother

\renewcommand*{\@glxtr@setupshortcuts}{%
  \glsacrshortcutstrue
  \GlsXtrDefineAcShortcuts
  \GlsXtrDefineOtherShortcuts
}%

\or % abother

\renewcommand*{\@glxtr@setupshortcuts}{%
  \glsacrshortcutstrue
  \GlsXtrDefineAbbreviationShortcuts
  \GlsXtrDefineOtherShortcuts
}%

```

Leave none and false as last option.

```

\else % none, false
\renewcommand*{\@glxtr@setupshortcuts}{}%
\fi
}

```

`\@glxtr@doaccsupp`

```
\newcommand*{\@glxtr@doaccsupp}{}
```

glossaries-accsupp can't be loaded after glossaries-extra. glossaries-accsupp v4.29+ checks `\@glxtr@doaccsupp` to determine if it's been loaded too late.

accsupp If accsupp, load glossaries-accsupp package.

```

\@glxtr@declareoption{accsupp}{%
\renewcommand*{\@glxtr@doaccsupp}{\RequirePackage{glossaries-accsupp}}}

```

`\@glxtr@doloadprefix`

```
\newcommand*{\@glxtr@doloadprefix}{}
```

prefix If prefix, load glossaries-prefix package.

```

\@glxtr@declareoption{prefix}{%
\renewcommand*{\@glxtr@doloadprefix}{\RequirePackage{glossaries-prefix}}}

```


`\glsxtrNoGlossaryWarning` Warning text displayed in document if the external glossary file given by the argument is missing.

```
\newcommand{\glsxtrNoGlossaryWarning}[1]{%
  \GlossariesExtraWarning{Glossary ‘#1’ is missing}%
  \@glsxtr@defaultnoglossarywarning{#1}%
}
```

`nomissingglsstext` If true, suppress the text and warning produced if the external glossary file is missing.

```
\define@choicekey{glossaries-extra.sty}{nomissingglsstext}
[{\@glsxtr@nomissingglsstextval\@glsxtr@nomissingglsstextnr}%
{true,false}[true]{%
  \ifcase\@glsxtr@nomissingglsstextnr\relax % true
  \renewcommand{\glsxtrNoGlossaryWarning}[1]{\null}%
  \else % false
  \renewcommand{\glsxtrNoGlossaryWarning}[1]{%
    \@glsxtr@defaultnoglossarywarning{#1}%
  }%
  \fi
}
```

Provide option to load glossaries-extra-stylemods (Deferred to the end.)

`\@glsxtr@redefstyles`

```
\newcommand*{\@glsxtr@redefstyles}{}
```

`stylemods`

```
\define@key{glossaries-extra.sty}{stylemods}[default]{%
  \ifstrequal{#1}{default}%
  {%
    \renewcommand*{\@glsxtr@redefstyles}{%
      \RequirePackage{glossaries-extra-stylemods}}%
  }%
  {%
    \ifstrequal{#1}{all}%
    {%
      \renewcommand*{\@glsxtr@redefstyles}{%
        \PassOptionsToPackage{all}{glossaries-extra-stylemods}%
        \RequirePackage{glossaries-extra-stylemods}%
      }%
    }%
    {%
      \renewcommand*{\@glsxtr@redefstyles}{}%
      \@for\@glsxtr@tmp:=#1\do{%
        \IfFileExists{glossary-\@glsxtr@tmp.sty}%
        {%
          \eappto\@glsxtr@redefstyles{%
            \noexpand\RequirePackage{glossary-\@glsxtr@tmp}}%
          }%
        }%
      }%
    }%
  }%
}
```

```

    {%
      \PackageError{glossaries-extra}%
      {Glossaries style package ‘glossary-@glstr@tmp.sty’
       doesn’t exist (did you mean to use the ‘style’ key?)}%
      {The list of values (#1) in the ‘stylemods’ key should
       match the glossary-xxx.sty files provided with
       glossaries.sty}%
    }%
  }%
  \appto@glstr@redefstyles{\RequirePackage{glossaries-extra-stylemods}}%
}
}%
}

```

`\@glstr@do@style`

```
\newcommand*{\@glstr@do@style}{}
```

`style` Since the `stylemods` option can automatically load extra style packages, deal with the `style` option after those packages have been loaded.

```
\define@key{glossaries-extra.sty}{style}{%
```

Defer actual style change:

```
\renewcommand*{\@glstr@do@style}{%
```

Set this as the default style:

```
\setkeys{glossaries.sty}{style={#1}}%
```

Set this style:

```
\setglossarystyle{#1}%
}%
}

```

`\glstr@inc@wrglossaryctr` Increments the associated counter if enabled. Does nothing by default. The optional argument is the entry label in case it’s required, but the `wrglossary` counter is globally used by all entries.

```
\newcommand*{\glstr@inc@wrglossaryctr}[1]{}
```

```
\GlsXtrInternalLocationHyperlink{<counter>}{<prefix>}
{<location>}
```

`\GlsXtrInternalLocationHyperlink`

The first two arguments are always control sequences.

```
\newcommand*{\GlsXtrInternalLocationHyperlink}[3]{%
  \glstrhyperlink{#1#2#3}{#3}%
}
```

`\wrglossary@locationhyperlink`

```
\newcommand*{\@glstr@wrglossary@locationhyperlink}[3]{%
  \pageref{wrglossary.#3}%
}
```

`indexcounter` Define the `wrglossary` counter that's incremented every time an entry is indexed, except for cross-references. This is designed for use with `bib2gls v1.4+`. It can work with the other indexing methods but it will interfere with the number list collation. This option automatically implements `counter=wrglossary`.

Since `glossaries` automatically loads `amsmath`, there may be a problem if the indexing occurs in the `equation` environment, because only one `\label` is allowed in each instance of that environment. It's best to change the counter when in maths mode.

```
\@glstr@declareoption{indexcounter}{%
\glstr@doooption{counter=wrglossary}%
\ifundef\c@wrglossary
{%
\newcounter{wrglossary}%
\renewcommand{\thewrglossary}{\arabic{wrglossary}}%
}%
}%
\renewcommand*{\glstr@inc@wrglossaryctr}[1]{%
```

Only increment if the current counter is `wrglossary`.

```
\ifdefstring\@glstr@counter{wrglossary}%
{%
\refstepcounter{wrglossary}%
\label{wrglossary.\thewrglossary}%
\@glstrwrglosscountermark{\thewrglossary}%
}%
}%
}%
\renewcommand*{\GlsXtrInternalLocationHyperlink}[3]{%
\ifdefstring\glstr@entrycounter{wrglossary}%
{%
\@glstr@wrglossary@locationhyperlink{##1}{##2}{##3}%
}%
{\glstrhyperlink{##1##2##3}{##3}}%
}%
}
```

`\@glstrwrglossmark` Marks the place where indexing occurs. Does nothing by default.

```
\newcommand*{\@glstrwrglossmark}{}%
```

`\@@glstrwrglossmark` Since `\glsadd` can be used in the preamble, this action needs to be disabled until the start of the document.

```
\newcommand*{\@@glstrwrglossmark}{}%
\AtBeginDocument{\renewcommand*{\@glstrwrglossmark}{\@glstrwrglossmark}}
```

`\glstrwrglossmark`

```
\newcommand*{\glstrwrglossmark}{\ensuremath{\cdot}}
```

`\@glstrwrglosscountermark` Marks the place where `wrglossary` counter is incremented. Does nothing by default.

```
\newcommand*{\@glstrwrglosscountermark}[1]{}%
```

```

\@@glsxtrwrglosscountermark
    \newcommand*{\@@glsxtrwrglosscountermark}[1]{}
    \AtBeginDocument{\renewcommand*{\@@glsxtrwrglosscountermark}{\@@glsxtrwrglosscountermark}}

\glsxtrwrglosscountermark
    \newcommand*{\glsxtrwrglosscountermark}[1]{\glsshowtargetfonttext{[#1]}}

\@glsxtr@doshowtarget
    \newcommand\@glsxtr@doshowtarget[2]{#2}

\glsxtrundefdebug Don't do anything until after the document environment has begun.
    \newcommand*{\glsxtrundefdebug}[1]{}

\@glsxtrundefdebug Use the same font as the targets.
    \newcommand*{\@glsxtrundefdebug}[1]{%
        \if@gls@debug \glsshowtargetfonttext{[#1]}\fi
    }

debug Provide extra debug options.
    \define@choicekey{glossaries-extra.sty}{debug}
    [ \@glsxtr@debugval \@glsxtr@debugnr ] %
    {true,false,showtargets,showwrgloss,all,showaccsupp}[true]{%
        \ifcase\@glsxtr@debugnr\relax % true
            \glsxtr@doption{debug=true}%
            \renewcommand*{\@glsxtrwrglossmark}{}%
            \renewcommand*{\@glsxtrwrglosscountermark}[1]{}%
        \or % false
            \glsxtr@doption{debug=false}%
            \renewcommand*{\@glsxtrwrglossmark}{}%
            \renewcommand*{\@glsxtrwrglosscountermark}[1]{}%
            \let\@glsxtr@doshowtarget\@secondoftwo
        \or % showtargets
            \glsxtr@doption{debug=showtargets}%
            \def\@glsxtr@doshowtarget{\@glsxtr@showtargetleft}%
        \or % showwrgloss
            \glsxtr@doption{debug=true}%
            \renewcommand*{\@glsxtrwrglossmark}{\glsxtrwrglossmark}%
            \renewcommand*{\@glsxtrwrglosscountermark}{\glsxtrwrglosscountermark}%
        \or % all
            \glsxtr@doption{debug=true,debug=showaccsupp}%
            % debug=showwrgloss:
            \renewcommand*{\@glsxtrwrglossmark}{\glsxtrwrglossmark}%
            \renewcommand*{\@glsxtrwrglosscountermark}{\glsxtrwrglosscountermark}%
            % debug=showtargets:
            \def\@glsxtr@doshowtarget{\@glsxtr@showtargetleft}%
        \or % showaccsupp
            \glsxtr@doption{debug=showaccsupp}%
        \fi
    }

```

```

\glsxtrshowtargetouter
\newcommand*\glsxtrshowtargetouter{\glsshowtargetouter}

\glsxtrshowtargetinner
\newcommand*\glsxtrshowtargetinner[1]{\glsshowtargetinner{#1}}

Debugging show targets.

\@glsxtrshowtargetleft
\newcommand{\@glsxtrshowtargetleft}[2]{\@glsshowtarget{#1}#2\@glsxtrshowtargetmark}%

\@glsxtrshowtargetright
\newcommand{\@glsxtrshowtargetright}[2]{\@glsxtrshowtargetmark#2\@glsshowtarget{#1}}%

\@glsxtrshowtargetmark
\newcommand{\@glsxtrshowtargetmark}{}%

```

showtargets Implements debug=showtargets and provides extra adjustments.

```

\define@choicekey{glossaries-extra.sty}{showtargets}
[\@glsxtr@showtargetsval\@glsxtr@showtargetsnr]%
{left,right,innerleft,innerright,annoteleft,annoteright}%
{%
\glsxtr@doooption{debug=showtargets}%
\ifcase\@glsxtr@showtargetsnr\relax
\def\@glsxtr@doshowtarget{\@glsxtrshowtargetleft}%
\def\glsxtrshowtargetouter{\glsshowtargetouter}%
\def\glsxtrshowtargetinner{\glsshowtargetinner}%
\let\@glsxtrshowtargetmark\empty
\or
\def\@glsxtr@doshowtarget{\@glsxtrshowtargetright}%
\def\glsxtrshowtargetouter{\glsshowtargetouter}%
\def\glsxtrshowtargetinner{\glsshowtargetinner}%
\let\@glsxtrshowtargetmark\empty
\or
\def\@glsxtr@doshowtarget{\@glsxtrshowtargetleft}%
\def\glsxtrshowtargetouter{\glsxtrshowtargetinner}%
\def\glsxtrshowtargetinner{\glsshowtargetinnersymleft}%
\let\@glsxtrshowtargetmark\empty
\or
\def\@glsxtr@doshowtarget{\@glsxtrshowtargetright}%
\def\glsxtrshowtargetouter{\glsxtrshowtargetinner}%
\def\glsxtrshowtargetinner{\glsshowtargetinnersymright}%
\let\@glsxtrshowtargetmark\empty
\or
\def\@glsxtr@doshowtarget{\@glsxtrshowtargetleft}%
\def\glsxtrshowtargetouter{\glsxtrshowtargetinner}%
\def\glsxtrshowtargetinner{\glsshowtargetinnersymleft}%
\def\@glsxtrshowtargetmark{\@glsshowtargetmarkfmt\glsxtrshowtargetsymbolright}%
\or

```

```

\def\@glxtr@doshowtarget{\@glxtr@showtargetright}%
\def\glxtr@showtargetouter{\glxtr@showtargetinner}%
\def\glxtr@showtargetinner{\glsshowtargetinnersymright}%
\def\@glxtr@showtargetmark{\@glsshowtargetmarkfmt\glxtr@showtargetsymbolleft}%
\fi
}

```

Pass all other options to glossaries.

`\glxtr@processunknownoptions` Need to compensate for the problem identified in <https://www.dickimaw-books.com/bugtracker.php?key=171>

```

\newcommand*{\glxtr@processunknownoptions}{}

\@ifpackageloaded{glossaries}
{
  \DeclareOptionX*{%
    \edef\glxtr@processunknownoptions{%
      \noexpand\setupglossaries{\expandonce\CurrentOption}}
  }
  {
    \DeclareOptionX*{%
      \expandafter\glxtr@doooption\expandafter{\CurrentOption}}
  }
}

```

Process options.

```
\ProcessOptionsX
```

Load glossaries if not already loaded.

```

\RequirePackage{glossaries}
\glxtr@processunknownoptions

```

Load the glossaries-accsupp package if required.

```
\@glxtr@doaccsupp
```

Load the glossaries-prefix package if required.

```
\@glxtr@doloadprefix
```

Redefine `\glspostdescription` if required.

```
\@glxtr@defpostpunc
```

`\glsexindexsetting` This command was new to glossaries v4.50 so may not be defined. Note that `record=only` and `record=nameref` implement `sort=none`, which will change the default definition of `\glsexindexsetting`.

```

\let\@glxtr@org@indexingsetting\glsexindexsetting
\providecommand{\glsexindexsetting}{\ifglsexindy xindy\else makeindex\fi}
\ifx\@glxtr@org@indexingsetting\glsexindexsetting
  \renewcommand{\glsexindexsetting}{%
    \@glxtr@if@record@only{bib2gls}{\ifglsexindy xindy\else makeindex\fi}%
  }
\else
  \@glxtr@if@record@only{\renewcommand{\glsexindexsetting}{bib2gls}}{}%
\fi

```

The following commands are new to glossaries v4.50, so provide them if an older version is present.

```

\glssentencecase
    \providecommand{\glssentencecase}[1]{\makefirstuc{#1}}

\glslowercase This uses \MakeTextLowercase because if \glslowercase isn't defined then
textcase has been loaded and we might have an older kernel.
    \providecommand{\glslowercase}[1]{\MakeTextLowercase{#1}}

\glsupercase Not using \unexpanded because ditto the above.
    \providecommand{\glsupercase}[1]{\mfirstucMakeUppercase{#1}}

\glspdfsentencecase For use in PDF strings. Ensure argument fully expanded first. This command
is provided rather than defined to allow for the possibility that it may be added
to glossaries at a later date.
    \ExplSyntaxOn
    \providecommand{\glspdfsentencecase}[1]{ \exp_args:Ne \MFUsentencecase { #1 } }
    \ExplSyntaxOff

\@Glsentryfield This command was new to glossaries v4.50 so won't be defined for older versions.
    \def\@Glsentryfield#1#2{%
        \glstexorpdfstring{\@Gls@entry@field{#1}{#2}}%
        {\glspdfsentencecase{\@Gls@entry@field{#1}{#2}}}%
    }

\glstexorpdfstring
    \ifdef\glstexorpdfstring
    {}
    {
        \ifdef\texorpdfstring
        {\newcommand{\glstexorpdfstring}{\texorpdfstring}}
        {\newcommand{\glstexorpdfstring}[2]{#1}}
    }

\@glstr@org@MakeUppercase Save the original definition of \MakeUppercase in case it needs to be restored.
    \let\@glstr@org@MakeUppercase\MakeUppercase

\glsmeasurewidth \glsmeasurewidth was only introduced to glossaries v4.51 so may not be avail-
able. This provides a definition that simply uses \settowidth.
    \providecommand{\glsmeasurewidth}[2]{%
        \settowidth{#1}{#2}%
    }

```

If mfirstuc v2.08+ is installed, provide interface commands. The simplest method is to test the existence of \MFUsentencecase, which is provided by mfirstuc v2.08+ but also by glossaries v4.50+. So it may be defined because glossaries v4.50+ is installed, in which case \glsmfuexcl etc are also defined,

but it may be defined because mfirstuc v2.08+ is installed but an older version of glossaries may be present, in which case \glsmfuexcl etc won't be defined.

```
\ExplSyntaxOn
\ifdef\MFUsentencecase
{%
```

Automatically identify exclusions, blockers and mappings.

```
\glsmfuexcl
\providecommand{\glsmfuexcl}[1]{\MFUexcl{#1}}

\glsmfublocker
\providecommand{\glsmfublocker}[1]{\MFUblocker{#1}}

\glsmfuaddmap
\providecommand{\glsmfuaddmap}[2]{\MFUaddmap{#1}{#2}}
```

Don't alter \MakeUppercase

```
\@glstr@saveMakeUppercase
\newcommand{\@glstr@saveMakeUppercase}{}

\@glstr@restoreMakeUppercase
\newcommand{\@glstr@restoreMakeUppercase}{}

\@glstr@assignMakeUppercase
\newcommand{\@glstr@assignMakeUppercase}{}

}
{
```

Provide \MFUsentencecase for use where expandable contexts are required.

```
\MFUsentencecase
\providecommand{\MFUsentencecase}[1]{\text_titlecase_first:n{#1}}
```

Provide support for exclusions with \MFUsentencecase.

```
\glsmfuexcl
\providecommand{\glsmfuexcl}[1]{
\tl_if_in:NnF \l_text_case_exclude_arg_tl {#1}
{
\tl_put_right:Nn \l_text_case_exclude_arg_tl {#1}
}
}
```

Just treat blockers and mappings as exclusions.

```
\glsmfublocker
\providecommand{\glsmfublocker}[1]{\glsmfuexcl{#1}}
```


`\glsmfuaddmap`

```
\providecommand{\glsmfuaddmap}[2]{\glsmfuexcl{#1}\glsmfublocker{#2}}
```

With old versions of mfirstuc, save and restore `\MakeUppercase` in the heading hooks.

```
\newcommand{\@glxtr@saveMakeUppercase}{%  
  \let\@glxtr@org@MakeUppercase\MakeUppercase  
}  
\newcommand{\@glxtr@restoreMakeUppercase}{%  
  \let\MakeUppercase\@glxtr@org@MakeUppercase  
}  
\newcommand{\@glxtr@assignMakeUppercase}{%  
  \let\MakeUppercase\MakeTextUppercase  
}  
}
```

Finished L^AT_EX3 code.

```
\ExplSyntaxOff
```

`\glsdoshowtarget` Added to glossaries v4.50 so many not be defined. Need to redefine it so use `\def`.

```
\def\glsdoshowtarget{\@glxtr@doshowtarget}
```

`\glxtrshowtargetsymbolright`

```
\newcommand{\glxtrshowtargetsymbolright}{%  
  \ifmmode \mbox{\tiny$\triangleleft$}\else {\tiny$\triangleleft$}\fi  
}
```

`\glxtrshowtargetsymbolleft`

```
\newcommand{\glxtrshowtargetsymbolleft}{%  
  \ifmmode \mbox{\tiny$\triangleright$}\else {\tiny$\triangleright$}\fi  
}
```

`\glsshowtargetinner` Only added to glossaries in v4.50 so may not be defined.

```
\providecommand*\glsshowtargetinner[1]{\glsshowtargetfonttext{[#1]}}
```

`\glsshowtargetfont` Only added to glossaries in v4.45 so may not be defined.

```
\providecommand*\glsshowtargetfont{\ttfamily\footnotesize}
```

`\glsshowtargetfonttext` Text-block command that checks for math-mode. Only added to glossaries in v4.50 so may not be defined.

```
\providecommand*\glsshowtargetfonttext[1]{%  
  \ifmmode \nfss@text{\glsshowtargetfont #1}\else {\glsshowtargetfont #1}\fi  
}
```

`\glsshowtargetinnersymleft`

```
\newcommand*\glsshowtargetinnersymleft[1]{%  
  \glsshowtargetinner{#1}\allowbreak\glxtrshowtargetsymbolleft}
```

```

\glsshowtargetinnersymright
    \newcommand*{\glsshowtargetinnersymright}[1]{%
        \glxtrshowtargetsymbolright\allowbreak\glsshowtargetinner{#1}}

\glsshowtargetouter Only added to glossaries in v4.45 so may not be defined.
    \providecommand*{\glsshowtargetouter}[1]{%
        \glsshowtargetsymbol\marginpar{\glsshowtargetsymbol\glsshowtargetfont #1}}

\@glsshowtarget Only added to glossaries in v4.32 so may not be defined.
    \providecommand*{\@glsshowtarget}[1]{%

\glsshowtarget This command was introduced to glossaries v4.32 so it may not be defined.
Therefore it's defined here using \def. \glsshowtargetouter was introduced
in glossaries v4.45, so that also may not be defined.
    \def\glsshowtarget#1{%
        \glxtrtitleorpdforheading
        {%
            \ifmode
                \nfss@text{\glxtrshowtargetinner{#1}}%
            \else
                \ifinner
                    \glxtrshowtargetinner{#1}%
                \else
                    \glxtrshowtargetouter{#1}%
                \fi
            \fi
        }%
        {[#1]}%
        {\protect\glsshowtargetinner{#1}}}%
    }

\@glsshowtargetmarkfmt
    \newcommand*{\@glsshowtargetmarkfmt}[1]{%
        \glxtrtitleorpdforheading
        {%
            \ifmode \nfss@text{#1}\else #1\fi
        }%
        {}%
        {\ifmode \nfss@text{#1}\else #1\fi}%
    }

\@glxtr@org@doseeglossary Save original definition of \@do@seeglossary
    \let\@glxtr@org@doseeglossary\@do@seeglossary

\@glxtr@doseeglossary This doesn't increment the associated counter.
    \newcommand*{\@glxtr@doseeglossary}[2]{%
        \glsdoifexists{#1}%
        {%

```

```

\@glsxtrwrglossmark
\@glsxtr@org@doseeglossary{#1}{#2}%
}%
}

tr@dosee@alsoindex@glossary

\newcommand*{\@glsxtr@dosee@alsoindex@glossary}[2]{%
\@glsxtr@recordsee{#1}{#2}%
\@glsxtr@doseeglossary{#1}{#2}%
}

\@glsxtr@org@gloautosee Save and restore original definition of \@glo@autosee. (That command may
not be defined as it was only introduced to glossaries v4.30, in which case the
synonym won't be defined either.)
\let\@glsxtr@org@gloautosee\@glo@autosee

Check if user tried autoseeindex=false when it can't be supported.
\if@glsxtr@autoseeindex
\else
\ifdef\@glsxtr@org@gloautosee
{}%
{\PackageError{glossaries-extra}{‘autoseeindex=false’ package
option requires at least v4.30 of glossaries.sty}%
{You need to update the glossaries.sty package}%
}
\fi

\@glo@autosee If \@glo@autosee has been defined (glossaries v4.30 onwards), redefine it to test
the autoseeindex option.
\ifdef\@glo@autosee
{%
\renewcommand*{\@glo@autosee}{%
\if@glsxtr@autoseeindex\@glsxtr@org@gloautosee\fi}%
}%
{}

\gls@checkseeallowed Don't prohibit the use of the see key before the indexing files have been opened
if the automatic see indexing has been disabled, since it's no longer an issue.
\renewcommand*{\gls@checkseeallowed}{%
\if@glsxtr@autoseeindex\@gls@see@noindex\fi
}

Define abbreviations glossaries if required.
\@glsxtr@abbreviationsdef
\let\@glsxtr@abbreviationsdef\relax

Setup shortcuts if required.
\@glsxtr@setupshortcuts

```

Redefine `\@glxtr@redef@forglsentries` if required.

```
\@glxtr@redef@forglsentries
```

`\glossariesextrasetup` Allow user to set options after the package has been loaded. First modify `\glxtr@doption` so that it now uses `\setupglossaries`:

```
\renewcommand{\glxtr@doption}[1]{\setupglossaries{#1}}%
```

Disable options that can only be used when the package is loaded:

```
\disable@keys{glossaries-extra.sty}{accsupp}
```

Now define the user command:

```
\newcommand*{\glossariesextrasetup}[1]{%
  \let\glxtr@setup@record\relax
  \let\glxtr@setup@shortcuts\relax
  \let\glxtr@redef@forglsentries\relax
  \let\glxtr@doload@prefix\relax
  \setkeys{glossaries-extra.sty}{#1}%
  \@glxtr@abbreviationsdef
  \let\glxtr@abbreviationsdef\relax
  \@glxtr@setup@shortcuts
  \glxtr@setup@record
  \@glxtr@redef@forglsentries
  \@glxtr@doload@prefix
}
```

`\glxtr@org@@do@wrglossary` Save original definition of `\@@do@wrglossary`.

```
\let\glxtr@org@@do@wrglossary\@@do@wrglossary
```

`\glxtr@@do@wrglossary` The new version adds code that can show a marker for debugging and increments the associated counter if enabled.

```
\newcommand*{\glxtr@@do@wrglossary}[1]{%
  \@glxtrwrglossmark
  \glxtr@inc@wrglossaryctr{#1}%
  \glxtr@org@@do@wrglossary{#1}%
}
```

`\glxtr@saveentrycounter` Save original definition of `\@gls@saveentrycounter`.

```
\let\glxtr@saveentrycounter\@gls@saveentrycounter
```

`\@gls@saveentrycounter` Change `\@gls@saveentrycounter` so that it only stores the entry counter information if the indexing is on.

```
\let\@gls@saveentrycounter\glxtr@indexonly@saveentrycounter
```

`\@xp@gls@getcounterprefix` This command is provided by `glossaries v4.50` so may not be defined. Provide a similar command in case the new version hasn't been installed.

```
\providecommand*\@xp@gls@getcounterprefix[2]{%
  \bgroup
  \glswrglossdisableanchorcmds
  \protected@edef\@do@gls@getcounterprefix{%
```

```

\noexpand\egroup
\noexpand\@gls@getcounterprefix{#1}{#2}%
}%
\do@gls@getcounterprefix
}

\glswrglossdisableanchorcmds

\providecommand{\glswrglossdisableanchorcmds}{\let\glstexorpdfstring\@secondoftwo}

\@gls@getcounterprefix This command is provided by the base glossaries package, but is redefined here.
The standard indexing methods don't directly store the hypertarget but instead
need to split it into the counter, prefix and location parts, which can be recon-
stituted in the location list. Unfortunately, not all targets are in this form, so
the links fail. With record=nameref, the complete target name can be saved, so
this modification adjusts the warning.

The expansion should now be performed in \@xp@gls@getcounterprefix.
Any commands that were using \@gls@getcounterprefix directly need to be
use \@xp@gls@getcounterprefix instead.

\renewcommand*\@gls@getcounterprefix[2]{%
\def\@gls@thisloc{#1}\def\@gls@thisHloc{#2}%
\ifx\@gls@thisloc\@gls@thisHloc
\def\@glo@counterprefix{}%
\else
\def\@gls@get@counterprefix##1.#1##2\end@getprefix{%
\def\@glo@tmp{##2}%
\ifx\@glo@tmp\@empty
\def\@glo@counterprefix{}%
\else
\def\@glo@counterprefix{##1}%
\fi
}%
\@gls@get@counterprefix#2.#1\end@getprefix

Warn if no prefix can be formed, unless record=nameref.

\ifx\@glo@counterprefix\@empty
\ifx\@glxtr@record@setting\@glxtr@record@setting@nameref
\else
\GlossariesExtraWarning{Hyper target '#2' can't be formed by
prefixing^^Jlocation '#1'. You need to modify the
definition of \string\theH\@gls@counter^^Jotherwise you
will get the warning: "'name{\@gls@counter.#1}' has been^^J
referenced but does not exist"%
\ifx\@glxtr@record@setting\@glxtr@record@setting@only
. You may want to consider using record=nameref instead%
\fi}%
\fi
\fi
\fi
}

```

Provide script dialect hook (does nothing unless redefined by glossaries-extra-bib2gls).

```
\@glxtrdialecthook
\newcommand*{\@glxtrdialecthook}{}

Set up record option if required.
\glxtr@setup@record

Disable preamble-only options and switch on the undefined tag at the start
of the document.
\AtBeginDocument{%
  \disable@keys{glossaries-extra.sty}{abbreviations,docdef,record}%
  \def\glxtrundefdebug{\@glxtrundefdebug}%
  \def\@glxtrundeftag{\glxtrundeftag}%
}
```

1.2 Extra Utilities

```
\GlsXtrIfUnusedOrUndefined{<label>}{<true>}{<false>}
```

\GlsXtrIfUnusedOrUndefined

Does *<true>* if the entry given by *<label>* is either undefined or hasn't been used (or has had the first use flag reset).

```
\newcommand*{\GlsXtrIfUnusedOrUndefined}[3]{%
  \ifglentryexists{#1}%
  {\ifbool{glo@glsetoklabel{#1}@flag}{#3}{#2}}%
  {#2}%
}
```

Starred form of `\ifglossaryexists` was only introduced to glossaries v4.46 so provide it if it hasn't been defined.

```
\ifdef\s@ifglossaryexists
{}
{
```

\ifglossaryexists

```
\renewcommand{\ifglossaryexists}{%
  \ifstar\s@ifglossaryexists\@ifglossaryexists
}
```

\@ifglossaryexists

```
\newcommand{\@ifglossaryexists}[3]{%
  \ifcsundef{@glotype@#1@out}{#3}{#2}%
}
```

\s@ifglossaryexists

```
\newcommand{\s@ifglossaryexists}[3]{%
  \ifcsundef{glolist@#1}{#3}{#2}%
}
```

}

`\glxtrifemptyglossary{<type>}{<true>}{<false>}`

`\glxtrifemptyglossary`

Provide command to determine if any entries have been added to the glossary (where the glossary label is provided in the first argument). The entries are stored in the comma-separated list `\glolist@<type>`. If this hasn't been defined, the glossary doesn't exist. If it has been defined and is simply a comma, the glossary exists and is empty. (It's initialised to a comma.)

```
\newcommand{\glxtrifemptyglossary}[3]{%
  \ifcsdef{glolist@#1}%
  {%
    \ifcsstring{glolist@#1}{,}{#2}{#3}%
  }%
  {%
    \glxtrundefaction{Glossary type '#1' doesn't exist}{}%
    #2%
  }%
}
```

`\GlsXtrIfInGlossary{<label>}{<type>}{<true>}{<false>}`

`\GlsXtrIfInGlossary`

Test if the given entry is in the given glossary list. This may not correspond to the `type` key as the entry may have been copied to the list. Does `<false>` and issues warning if the glossary doesn't exist.

```
\ExplSyntaxOn
\clist_new:N \__glossariesxtr_glolist_clist
\newcommand*{\GlsXtrIfInGlossary}[4]{%
  \tl_if_exist:cTF { glolist@#2 }
  {
    \exp_args:NNv \clist_set:Nn
      \__glossariesxtr_glolist_clist { glolist@#2 }
    \clist_if_in:NnTF
      \__glossariesxtr_glolist_clist { #1 }
      { #3 } { #4 }
  }
  {
    \glxtrundefaction{Glossary ~ type ~ '#1' ~ doesn't ~ exist}{%
      #4
    }
  }
}
\ExplSyntaxOff
```

`\glxtrifkeydefined` Tests if the key given in the first argument has been defined.

```
\newcommand*{\glxtrifkeydefined}[3]{%
  \key@ifundefined{glossentry}{#1}{#3}{#2}%
}
```

}

`\glxtrprovidestoragekey` Like `\glsaddstoragekey` but does nothing if the key has already been defined.

```
\newcommand*{\glxtrprovidestoragekey}{%
  \ifstar\sglsxtr@provide@storagekey\glxtr@provide@storagekey
}
```

`\@glxtr@provide@storagekey` Unstarred version.

```
\newcommand*{\@glxtr@provide@storagekey}[3]{%
  \key@ifundefined{glossentry}{#1}%
  {%
    \define@key{glossentry}{#1}{\csdef{@glo@#1}{##1}}%
    \appto\@gls@keymap{,{#1}{#1}}%
    \appto\@newglossaryentryprehook{\csdef{@glo@#1}{#2}}%
    \appto\@newglossaryentryposthook{%
      \letcs{@glo@tmp}{@glo@#1}%
      \gls@assign@field{#2}{\@glo@label}{#1}{\@glo@tmp}%
    }%
  }%
```

Allow the user to omit the user level command if they only intended fetching the value with `\glxtrusefield`

```
\ifblank{#3}
{%
  \newcommand*{#3}[1]{\@gls@entry@field{##1}{#1}}%
}%
}%
{%
```

Provide the no-link command if not already defined.

```
\ifblank{#3}
{%
  \providecommand*{#3}[1]{\@gls@entry@field{##1}{#1}}%
}%
}%
}
```

`\s@glxtr@provide@storagekey` Starred version.

```
\newcommand*{\s@glxtr@provide@storagekey}[1]{%
  \key@ifundefined{glossentry}{#1}%
  {%
    \expandafter\newcommand\expandafter*\expandafter
    {\csname gls@assign@#1@field\endcsname}[2]{%
      \@gls@expand@field{##1}{#1}{##2}%
    }%
  }%
  {%
    \@glxtr@provide@addstoragekey{#1}%
  }%
```


The name of a text-block control sequence can be stored in a field (given by `\GlsXtrFmtField`). This command can then be used with `\glstrfmt` [*options*]{*label*}{*text*} which effectively does `\glslink`[*options*]{*label*}{*cs*}{*text*}} If the field hasn't been set for that entry just *text* is done.

```
\GlsXtrFmtField
\newcommand{\GlsXtrFmtField}{useri}

\GlsXtrFmtDefaultOptions
\newcommand{\GlsXtrFmtDefaultOptions}{noindex}

\glstrfmt
\glstrfmt[options]{entry-label}{text}[insert]
The post-link hook isn't done. This now has a starred form that checks for a
final optional argument.
\newrobustcmd*{\glstrfmt}{\ifstar\s@glstrfmt\@glstrfmt}

\@glstrfmt Unstarred form.
\newcommand*{\@glstrfmt}[3][\@glstrfmt{#1}{#2}{#3}]{%

\s@glstrfmt Starred form.
\newcommand*{\s@glstrfmt}[3][\@glstrfmt{#1}{#2}{#3}]{%
\new@ifnextchar[\s@glstrfmt{#1}{#2}{#3}]{%
{\@glstrfmt{#1}{#2}{#3}}}%
}

\s@glstrfmt Pick up final optional argument.
\def\s@glstrfmt#1#2#3[#4]{\@glstrfmt{#1}{#2}{#3}{#4}}

\@glstrfmt Actual inner working.
\newcommand*{\@glstrfmt}[4]{%
\begin{group}
\def\glslabel{#2}%
\glsdoifexistsordo{#2}%
{%
\ifglshasfield{\GlsXtrFmtField}{#2}%
{%
\let\do@gl@link@checkfirsthyper\relax
\expandafter\@gl@link\expandafter[\GlsXtrFmtDefaultOptions,#1]{#2}%
{\glstrfmtdisplay{\glscurrentfieldvalue}{#3}{#4}}%
}%
{\glstrfmtdisplay{@firstofone}{#3}{#4}}%
}%
}%
{\%
```

Has the default `noindex` been counteracted? If so, this needs `\glsadd` in case `bib2gls` needs to pick up the record.

```
\begingroup
\@gls@setdefault@glslink@opts
\setkeys{glslink}{\GlsXtrFmtDefaultOptions,#1}%
\ifKV@glslink@noindex\else\glsadd{#2}\fi
\endgroup
\glsxtrfmtdisplay{@firstofone}{#3}{#4}%
}%
\endgroup
}
```

`\Glsxtrfmt[<options>]{<entry-label>}{<text>}[<insert>]`

`\Glsxtrfmt`

As `\glsxtrfmt` but applies a sentence-case change to *<text>*. This is provided to allow a mapping with `mfirstuc v2.08+` in the event that an automated case-change is required.

```
\newrobustcmd*{\Glsxtrfmt}{\@ifstar\s@Glsxtrfmt\@Glsxtrfmt}
\glsmfuaddmap{\glsxtrfmt}{\Glsxtrfmt}
```

`\@Glsxtrfmt` Unstarred form.

```
\newcommand*{\@Glsxtrfmt}[3][\@Glsxtrfmt]{#1}{#2}{\glssentencecase{#3}}{}}
```

`\s@Glsxtrfmt` Starred form.

```
\newcommand*{\s@Glsxtrfmt}[3][\@Glsxtrfmt]{#1}{#2}{\glssentencecase{#3}}{}}
\new@ifnextchar[\s@Glsxtrfmt]{#1}{#2}{\glssentencecase{#3}}{}}{}}
{\@Glsxtrfmt{#1}{#2}{\glssentencecase{#3}}{}}{}}{}}
}
```

`\glsxtrfmtdisplay` The command used internally by `\glsxtrfmt` to do the actual formatting. The first argument is the control sequence name, the second is the control sequence's argument, the third is the inserted material (if starred form used).

```
\newcommand{\glsxtrfmtdisplay}[3]{\csuse{#1}{#2}#3}
```

`\glsxtrentryfmt` No link or indexing.

```
\newcommand*{\glsxtrentryfmt}[2]{%
\glstexorpdfstring{\@glsxtrentryfmt{#1}{#2}}{\glsxtrpdfentryfmt{#1}{#2}}}%
}
```

`\glsxtrpdfentryfmt` Used for the PDF bookmarks.

```
\newcommand*{\glsxtrpdfentryfmt}[2]{#2}
```

`\@glsxtrentryfmt`

```
\newrobustcmd*{\@glsxtrentryfmt}[2]{%}
```

Locally define `\glslabel` in case the helper command needs to access the label.

```
{%
  \protected@edef\glslabel{#1}%
  \glstoifexistsordo{#1}%
  {%
    \ifglshasfield{\GlsXtrFmtField}{#1}%
    {%
      \csuse{\glscurrentfieldvalue}{#2}%
    }%
    {#2}%
  }%
  {#2}%
}%
}
```

`\Glsxtrentryfmt` Sentence-case version.

```
\newcommand*{\Glsxtrentryfmt}[2]{%
  \glstexorpdfstring
  {\@Glsxtrentryfmt{#1}{\glssentencecase{#2}}}%
  {\Glsxtrpdfentryfmt{#1}{#2}}%
}
\glsmfuaddmap{\Glsxtrentryfmt}{\Glsxtrentryfmt}
```

`\Glsxtrpdfentryfmt` Used for the PDF bookmarks.

```
\newcommand*{\Glsxtrpdfentryfmt}[2]{\MFUsentencecase{#2}}
```

`\glxstrfieldlistadd` If a field stores an etoolbox internal list (e.g. `loclist`) then this macro provides a convenient way of adding to the list via etoolbox's `\listcsadd`. The first argument is the entry's label, the second is the field label and the third is the element to add to the list.

```
\newcommand*{\glxstrfieldlistadd}[3]{%
  \listcsadd{glo@\glsetoklabel{#1}@#2}{#3}%
}
```

`\glxstrfieldlistgadd` Similarly but uses `\listcsgadd`.

```
\newcommand*{\glxstrfieldlistgadd}[3]{%
  \listcsgadd{glo@\glsetoklabel{#1}@#2}{#3}%
}
```

`\glxstrfieldlistseadd` Similarly but uses `\listcseadd`.

```
\newcommand*{\glxstrfieldlistseadd}[3]{%
  \listcseadd{glo@\glsetoklabel{#1}@#2}{#3}%
}
```

`\glxstrfieldlistxadd` Similarly but uses `\listcsxadd`.

```
\newcommand*{\glxstrfieldlistxadd}[3]{%
  \listcsxadd{glo@\glsetoklabel{#1}@#2}{#3}%
}
```

Now provide commands to iterate over these lists.

```
\glxtrfielddolistloop
\newcommand*\glxtrfielddolistloop[2]{%
  \dolistcsloop{glo@\glsetoklabel{#1}@#2}%
}

\glxtrfieldforlistloop
\newcommand*\glxtrfieldforlistloop[3]{%
  \forlistcsloop{#3}{glo@\glsetoklabel{#1}@#2}%
}

\glxtrfieldformatlist
\newrobustcmd*\glxtrfieldformatlist[2]{%
  \begingroup
  \def\@dtl@formatlist@itemsep{%
    \def\@dtl@formatlist@lastitem{%
      \def\@dtl@formatlist@prelastitem{%
        \def\@dtl@formatlist@prelastitemsep{%
          \forlistcsloop{\@dtl@formatlist@handler}{glo@\glsetoklabel{#1}@#2}%
          \@dtl@formatlist@prelastitem\@dtl@formatlist@lastitem
        }
      }
    }
  }
}
```

List element tests:

```
\glxtrfieldifinlist First argument label, second argument field, third argument item, fourth true
part and fifth false part.
\newcommand*\glxtrfieldifinlist[5]{%
  \ifinlistcs{#3}{glo@\glsetoklabel{#1}@#2}{#4}{#5}%
}

\glxtrfieldxifinlist Expands item.
\newcommand*\glxtrfieldxifinlist[5]{%
  \xifinlistcs{#3}{glo@\glsetoklabel{#1}@#2}{#4}{#5}%
}
```

```
\glxtrforcsvfield
\newcommand*\glxtrforcsvfield{%
  \ifstar\s@glxtrforcsvfield\@glxtrforcsvfield
}
```

```
\@glxtrforcsvfield Unstarred version.
\newcommand*\@glxtrforcsvfield[3]{%
  \@glxtrifhasfield{#2}{#1}%
  {%
    \let\glxtrendfor\@endfortrue
```

```

\@for\@glstr@label:=\glscurrentfieldvalue\do
{\expandafter#3\expandafter{\@glstr@label}}}%
{}%
}

```

\s@glstrforcsvfield Starred version.

```

\newcommand*\s@glstrforcsvfield}[3]{%
\s@glstrifhasfield{#2}{#1}%
{%
\let\glxtrendfor\@endfortrue
\@for\@glstr@label:=\glscurrentfieldvalue\do
{\expandafter#3\expandafter{\@glstr@label}}}%
}%
}

```

\glstrfieldformatcsvlist

```

\newrobustcmd*\glstrfieldformatcsvlist}[2]{%
\@glstrifhasfield{#2}{#1}%
{\@dtlformatlist\glscurrentfieldvalue}%
}%
}

```

\GlsXtrIfFieldValueInCsvList{<label>}{<field>}{<list>}{<true>}{<false>}

\GlsXtrIfFieldValueInCsvList

```

\newcommand*\GlsXtrIfFieldValueInCsvList{%
\ifstar\s@GlsXtrIfFieldValueInCsvList\s@GlsXtrIfFieldValueInCsvList
}

```

Note \DTLifinlist performs one level on the list but not the element.

\GlsXtrIfFieldValueInCsvList Unstarred version.

```

\newcommand*\@GlsXtrIfFieldValueInCsvList}[5]{%
\@glstrifhasfield{#2}{#1}%
{%
\expandafter\DTLifinlist\expandafter{\glscurrentfieldvalue}%
{#3}{#4}{#5}%
}%
{#5}%
}

```

\GlsXtrIfFieldValueInCsvList Starred version.

```

\newcommand*\s@GlsXtrIfFieldValueInCsvList}[5]{%
\s@glstrifhasfield{#2}{#1}%
{%
\expandafter\DTLifinlist\expandafter{\glscurrentfieldvalue}%
{#3}{#4}{#5}%
}%
}

```

```
{#5}%
}
```

```
\GlsXtrIfValueInFieldCsvList{<label>}{<field>}{<value>}{<true>}{<false>}
```

\GlsXtrIfValueInFieldCsvList

Essentially the reverse. Tests if the given value is in the given field which should contain a comma-separated list.

```
\newcommand*{\GlsXtrIfValueInFieldCsvList}{%
  \ifstar\s@GlsXtrIfValueInFieldCsvList\@GlsXtrIfValueInFieldCsvList
}
```

\GlsXtrIfValueInFieldCsvList Unstarred version.

```
\newcommand*{\@GlsXtrIfValueInFieldCsvList}[5]{%
  \@glstrifhasfield{#2}{#1}%
  {%
    \DTLifinlist{#3}{\glscurrentfieldvalue}{#4}{#5}%
  }%
  {#5}%
}
```

\GlsXtrIfValueInFieldCsvList Unstarred version.

```
\newcommand*{\s@GlsXtrIfValueInFieldCsvList}[5]{%
  \s@glstrifhasfield{#2}{#1}%
  {%
    \DTLifinlist{#3}{\glscurrentfieldvalue}{#4}{#5}%
  }%
  {#5}%
}
```

```
\xGlsXtrIfValueInFieldCsvList{<label>}{<field>}{<value>}{<true>}{<false>}
```

\xGlsXtrIfValueInFieldCsvList

As above but fully expand <value>.

```
\newcommand*{\xGlsXtrIfValueInFieldCsvList}{%
  \ifstar\s@\xGlsXtrIfValueInFieldCsvList\@xGlsXtrIfValueInFieldCsvList
}
```

\xGlsXtrIfValueInFieldCsvList Unstarred version.

```
\newcommand*{\@xGlsXtrIfValueInFieldCsvList}[5]{%
  \@glstrifhasfield{#2}{#1}%
  {%
    \protected@edef\@gls@tmp{#3}%
    \expandafter\DTLifinlist\expandafter{\@gls@tmp}{\glscurrentfieldvalue}{#4}{#5}%
  }%
  {#5}%
}
```

`\GlsXtrIfValueInFieldCsvList` Unstarred version.

```
\newcommand*{\s@GlsXtrIfValueInFieldCsvList}[5]{%
\s@glstrifhasfield{#2}{#1}%
{%
\protected@edef\@glstmp{#3}%
\expandafter\DTLifinlist\expandafter{\@glstmp}{\glscurrentfieldvalue}{#4}{#5}%
}%
{#5}%
}
```

`\glstrifhasfield`

`\glstrifhasfield{<field>}{<label>}{<true>}{<false>}`

A simpler alternative to `\ifglshasfield` that doesn't complain if the entry or the field doesn't exist. (No mapping is used.) Grouping is added to the unstarred version allow for nested use.

```
\newrobustcmd{\glstrifhasfield}{%
\@ifstar{\s@glstrifhasfield}{\@glstrifhasfield}%
}
```

`\@glstrifhasfield` Unstarred version adds grouping.

```
\newcommand{\@glstrifhasfield}[4]{%
{\s@glstrifhasfield{#1}{#2}{#3}{#4}}%
}
```

`\s@glstrifhasfield` Starred version omits grouping.

```
\newcommand{\s@glstrifhasfield}[4]{%
\letcs{\glscurrentfieldvalue}{glo@glsetoklabel{#2}@#1}%
\ifundef\glscurrentfieldvalue
{#4}%
{%
\ifdefempty\glscurrentfieldvalue{#4}{#3}%
}%
}
```

`\GlsXtrIfFieldNonZero` Designed for numeric fields.

```
\newcommand{\GlsXtrIfFieldNonZero}{%
\@ifstar\s@GlsXtrIfFieldNonZero\@GlsXtrIfFieldNonZero
}
```

`\@GlsXtrIfFieldNonZero`

```
\newcommand{\@GlsXtrIfFieldNonZero}[4]{%
\@GlsXtrIfFieldCmpNum{#1}{#2}{=}{0}{#4}{#3}%
}
```

`\s@GlsXtrIfFieldNonZero`

```
\newcommand{\s@GlsXtrIfFieldNonZero}[4]{%
\s@GlsXtrIfFieldCmpNum{#1}{#2}{=}{0}{#4}{#3}%
}
```

```
\GlsXtrIfFieldEqNum{<field>}{<label>}{<value>}{<true>}
{<false>}
```

\GlsXtrIfFieldEqNum

Designed for numeric fields.

```
\newcommand{\GlsXtrIfFieldEqNum}{%
  \ifstar\s@GlsXtrIfFieldEqNum\@GlsXtrIfFieldEqNum
}
```

\@GlsXtrIfFieldEqNum

```
\newcommand{\@GlsXtrIfFieldEqNum}[5]{%
  \@GlsXtrIfFieldCmpNum{#1}{#2}{=}{#3}{#4}{#5}%
}
```

\s@GlsXtrIfFieldEqNum

```
\newcommand{\s@GlsXtrIfFieldEqNum}[5]{%
  \s@GlsXtrIfFieldCmpNum{#1}{#2}{=}{#3}{#4}{#5}%
}
```

```
\GlsXtrIfFieldCmpNum{<field>}{<label>}{<comparison>}
{<value>}{<true>}{<false>}
```

\GlsXtrIfFieldCmpNum

Designed for numeric fields.

```
\newcommand{\GlsXtrIfFieldCmpNum}{%
  \ifstar\s@GlsXtrIfFieldCmpNum\@GlsXtrIfFieldCmpNum
}
```

\@GlsXtrIfFieldCmpNum

```
\newcommand{\@GlsXtrIfFieldCmpNum}[6]{%
  {%
    \letcs{\glscurrentfieldvalue}{glo@\glsdetoklabel{#2}@#1}%
    \ifundef\glscurrentfieldvalue
    {\def\glscurrentfieldvalue{0}}%
    {%
      \ifdefempty\glscurrentfieldvalue
      {\def\glscurrentfieldvalue{0}}%
      {}%
    }%
    \ifnum\glscurrentfieldvalue#3#4\relax #5\else #6\fi
  }%
}
```

\s@GlsXtrIfFieldCmpNum

```
\newcommand{\s@GlsXtrIfFieldCmpNum}[6]{%
  \letcs{\glscurrentfieldvalue}{glo@\glsdetoklabel{#2}@#1}%
  \ifundef\glscurrentfieldvalue
  {\def\glscurrentfieldvalue{0}}%
```



```

{%
\ifdefempty\glscurrentfieldvalue
{\def\glscurrentfieldvalue{0}}%
}%
}%
\ifnum\glscurrentfieldvalue#3#4\relax #5\else #6\fi
}

```

```
\GlsXtrIfFieldUndef{<field>}{<label>}{<true>}{<false>}
```

\GlsXtrIfFieldUndef

Just uses \ifcsundef.

```

\newcommand{\GlsXtrIfFieldUndef}[2]{%
\ifcsundef{glo@\glsdetoklabel{#2}@#1}%
}

```

\glstrusefield Provide a user-level alternative to \@gls@entry@field. The first argument is the entry label. The second argument is the field label.

```

\newcommand*{\glstrusefield}[2]{%
\@gls@entry@field{#1}{#2}%
}

```

\Glsxtrusefield Provide a user-level alternative to \@Gls@entry@field. Now uses \MFUsentencecase in PDF bookmarks.

```

\newcommand*{\Glsxtrusefield}[2]{%
\@Glsentryfield{#1}{#2}%
}
\glsmfuaddmap{\glstrusefield}{\Glsxtrusefield}

```

\GLSxtrusefield As above but convert to all caps. Note that with mfirstuc v2.08+, \mfirstucMakeUppercase is expandable, so therefore \glssupercase should also be expandable.

```

\newcommand*{\GLSxtrusefield}[2]{%
\glssupercase{\csuse{glo@\glsdetoklabel{#1}@#2}}%
}
\glsmfublocker{\GLSxtrusefield}

```

\glstrentryparentname

```

\newcommand*{\glstrentryparentname}[1]{%
\ifcsdef{glo@\glsdetoklabel{#1}@parent}%
{\csuse{glo@\csuse{glo@\glsdetoklabel{#1}@parent}@name}}%
}%
}

```

\glstrdeffield Just use \csdef to provide a field value for the given entry.

```
\newcommand*{\glstrdeffield}[2]{\csdef{glo@\glsdetoklabel{#1}@#2}}
```

\glstredeffield Just use \csedef to provide a field value for the given entry.

```
\newcommand*{\glstredeffield}[2]{\protected@csedef{glo@\glsdetoklabel{#1}@#2}}
```

`\glxtrapptocsvfield` Similar to the above but will append value with a leading comma if the field is already defined. This is used by `bib2gls`. There's no check if the entry has been defined. (Because of the way that `bib2gls`'s `save-from-alias` etc options are implemented, the entry may not have yet been written to the `glstex` file when this command is used.)

```
\newcommand*{\glxtrapptocsvfield}[3]{%
  \ifcsdef{glo@\glsdetoklabel{#1}@#2}%
    {\csappto{glo@\glsdetoklabel{#1}@#2}{, #3}}%
    {\csdef{glo@\glsdetoklabel{#1}@#2}{#3}}%
}
```

`\glxtrsetfieldifexists`

```
\newcommand*{\glxtrsetfieldifexists}[3]{\glsoifexists{#1}{#3}}
```

`\GlsXtrSetField` Allow the user to set a field. First argument entry label, second argument field label, third argument value.

```
\newrobustcmd*{\GlsXtrSetField}[3]{%
  \glxtrsetfieldifexists{#1}{#2}%
  {\csdef{glo@\glsdetoklabel{#1}@#2}{#3}}%
}
```

`\GlsXtrLetField` Uses `\cslet` instead. Third argument should be a macro.

```
\newrobustcmd*{\GlsXtrLetField}[3]{%
  \glxtrsetfieldifexists{#1}{#2}%
  {\cslet{glo@\glsdetoklabel{#1}@#2}{#3}}%
}
```

`\csGlsXtrLetField` Uses `\csletcs` instead. Third argument should be a control sequence name.

```
\newrobustcmd*{\csGlsXtrLetField}[3]{%
  \glxtrsetfieldifexists{#1}{#2}%
  {\csletcs{glo@\glsdetoklabel{#1}@#2}{#3}}%
}
```

`\GlsXtrLetFieldToField` Sets the field for one entry to the field for another entry. Third argument should be the other entry and the fourth argument that other field label.

```
\newrobustcmd*{\GlsXtrLetFieldToField}[4]{%
  \glxtrsetfieldifexists{#1}{#2}%
  {\csletcs{glo@\glsdetoklabel{#1}@#2}{glo@\glsdetoklabel{#3}@#4}}%
}
```

`\gGlsXtrSetField` Allow the user to set a field. First argument entry label, second argument field label, third argument value.

```
\newrobustcmd*{\gGlsXtrSetField}[3]{%
  \glxtrsetfieldifexists{#1}{#2}%
  {\csgdef{glo@\glsdetoklabel{#1}@#2}{#3}}%
}
```

```

\GlsXtrSetField
\newrobustcmd*{\xGlsXtrSetField}[3]{%
  \glstrsetfieldifexists{#1}{#2}%
  {\protected@csxdef{glo@\glsetoklabel{#1}@#2}{#3}}%
}

```

```

\eGlsXtrSetField
\newrobustcmd*{\eGlsXtrSetField}[3]{%
  \glstrsetfieldifexists{#1}{#2}%
  {\protected@csedef{glo@\glsetoklabel{#1}@#2}{#3}}%
}

```

Version 1.55: Provide L^AT_EX3 commands for testing field values. These don't use `\glstrifhasfield`.

`\ExplSyntaxOn`

Test if field is defined. Syntax: `{<entry-label>} {<field-label>}`

```

\prg_new_conditional:Npnn \glossaries_if_field_exists:nn #1 #2
{ p , T , F , TF }
{
  \tl_if_exist:cTF { glo@ \glsetoklabel { #1 } @ #2 }
  { \prg_return_true: }
  { \prg_return_false: }
}

```

Test if field is set (defined and not empty and not `\relax`). Syntax:

`{<entry-label>} {<field-label>}`

```

\prg_new_conditional:Npnn \glossaries_if_field_set:nn #1 #2
{ p , T , F , TF }
{
  \tl_if_exist:cTF { glo@ \glsetoklabel { #1 } @ #2 }
  {
    \tl_if_empty:cTF { glo@ \glsetoklabel { #1 } @ #2 }
    { \prg_return_false: }
    {
      \tl_if_eq:cNTF
      { glo@ \glsetoklabel {#1 } @ #2 } \@gls@default@value
      { \prg_return_false: }
      { \prg_return_true: }
    }
  }
  { \prg_return_false: }
}

```

Test if field is defined and equal to the given token list variable. Syntax:

`{<entry-label>} {<field-label>} <tl-var>`

```

\prg_new_conditional:Npnn \glossaries_if_field_eq:nnN #1 #2 #3
{ p , T , F , TF }
{
  \tl_if_exist:cTF { glo@ \glsetoklabel { #1 } @ #2 }

```

```

{
  \tl_if_eq:cnTF { glo@ \glsdetoklabel {#1 } @ #2 } #3
  { \prg_return_true: }
  { \prg_return_false: }
}
{ \prg_return_false: }
}

```

Test if field is defined and equal to the given token list. Syntax: $\{\langle entry-label \rangle\}$
 $\{\langle field-label \rangle\} \{\langle tl \rangle\}$

```

\prg_new_conditional:Npnn \glossaries_if_field_eq:nnn #1 #2 #3
{ T , F , TF }
{
  \tl_if_exist:cTF { glo@ \glsdetoklabel { #1 } @ #2 }
  {
    \tl_if_eq:cnTF { glo@ \glsdetoklabel { #1 } @ #2 } { #3 }
    { \prg_return_true: }
    { \prg_return_false: }
  }
  { \prg_return_false: }
}

```

Test if field is defined and equal to another field (same entry). Syntax:
 $\{\langle entry-label \rangle\} \{\langle field-label \rangle\} \{\langle field2-label \rangle\}$

```

\prg_new_conditional:Npnn \glossaries_if_field_eq_field:nnn #1 #2 #3
{ p , T , F , TF }
{
  \tl_if_exist:cTF { glo@ \glsdetoklabel { #1 } @ #2 }
  {
    \tl_if_eq:ccTF
    { glo@ \glsdetoklabel { #1 } @ #2 }
    { glo@ \glsdetoklabel { #1 } @ #3 }
    { \prg_return_true: }
    { \prg_return_false: }
  }
  { \prg_return_false: }
}

```

Test if field is defined and equal to a field in a different entry. Syntax:
 $\{\langle entry-label \rangle\} \{\langle field-label \rangle\} \{\langle entry2-label \rangle\} \{\langle field2-label \rangle\}$

```

\prg_new_conditional:Npnn \glossaries_if_field_eq_field:nnnn #1 #2 #3 #4
{ p , T , F , TF }
{
  \bool_lazy_and:nnTF
  { \tl_if_exist_p:c { glo@ \glsdetoklabel { #1 } @ #2 } }
  { \tl_if_exist_p:c { glo@ \glsdetoklabel { #3 } @ #4 } }
  {
    \tl_if_eq:ccTF
    { glo@ \glsdetoklabel { #1 } @ #2 }
    { glo@ \glsdetoklabel { #3 } @ #4 }
    { \prg_return_true: }
  }
}

```

```

        { \prg_return_false: }
    }
    { \prg_return_false: }
}

```

Recover field content. An error will occur if the field or entry doesn't exist.

Syntax: $\{\langle entry-label \rangle\} \{\langle field-label \rangle\}$

```

\cs_new:Nn \glossaries_use_field:nn
{
    \tl_use:c { glo@ \glsdetoklabel { #1 } @ #2 }
}
\ExplSyntaxOff

```

$\backslash\text{GlsXtrIfFieldEqStr}$ Starred version uses starred version of $\backslash\text{glstrifhasfield}$ (that is, no grouping).

```

\newcommand*{\GlsXtrIfFieldEqStr}{%
    \ifstar\s@GlsXtrIfFieldEqStr\@GlsXtrIfFieldEqStr
}

```

$\backslash\text{@GlsXtrIfFieldEqStr}$

```

\newrobustcmd*{\@GlsXtrIfFieldEqStr}[5]{%
    \@glstrifhasfield{#1}{#2}%
    {%
        \ifdefstring{\glscurrentfieldvalue}{#3}{#4}{#5}%
    }%
    {#5}%
}

```

$\backslash\text{s@GlsXtrIfFieldEqStr}$

```

\newrobustcmd*{\s@GlsXtrIfFieldEqStr}[5]{%
    \s@glstrifhasfield{#1}{#2}%
    {%
        \ifdefstring{\glscurrentfieldvalue}{#3}{#4}{#5}%
    }%
    {#5}%
}

```

$\backslash\text{GlsXtrIfFieldEqXpStr}$ Like the above but first expands the string. Starred version uses starred version of $\backslash\text{glstrifhasfield}$ (that is, no grouping).

```

\newcommand*{\GlsXtrIfFieldEqXpStr}{%
    \ifstar\s@GlsXtrIfFieldEqXpStr\@GlsXtrIfFieldEqXpStr
}

```

$\backslash\text{@GlsXtrIfFieldEqXpStr}$

```

\newrobustcmd*{\@GlsXtrIfFieldEqXpStr}[5]{%
    \@glstrifhasfield{#1}{#2}%
    {%
        \protected@edef\@gls@tmp{#3}%
        \ifdefequal{\glscurrentfieldvalue}{\@gls@tmp}{#4}{#5}%
    }
}

```

```
}%
{#5}%
}
```

`\s@GlsXtrIfFieldEqXpStr`

```
\newrobustcmd*{\s@GlsXtrIfFieldEqXpStr}[5]{%
\s@glstrifhasfield{#1}{#2}%
{%
\protected@edef\@glstmp{#3}%
\ifdefequal{\glscurrentfieldvalue}{\@glstmp}{#4}{#5}%
}%
{#5}%
}
```

`\GlsXtrIfXpFieldEqXpStr` Like the above but also expands the field value. Starred version uses starred version of `\glstrifhasfield` (that is, no grouping).

```
\newcommand*{\GlsXtrIfXpFieldEqXpStr}{%
\@ifstar\s@GlsXtrIfXpFieldEqXpStr\@GlsXtrIfXpFieldEqXpStr
}
```

`\@GlsXtrIfXpFieldEqXpStr`

```
\newrobustcmd*{\@GlsXtrIfXpFieldEqXpStr}[5]{%
\@glstrifhasfield{#1}{#2}%
{%
\protected@edef\@glstmp{\glscurrentfieldvalue}%
\let\glscurrentfieldvalue\@glstmp
\protected@edef\@glstmp{#3}%
\ifdefequal{\glscurrentfieldvalue}{\@glstmp}{#4}{#5}%
}%
{#5}%
}
```

`\s@GlsXtrIfXpFieldEqXpStr`

```
\newrobustcmd*{\s@GlsXtrIfXpFieldEqXpStr}[5]{%
\s@glstrifhasfield{#1}{#2}%
{%
\protected@edef\@glstmp{\glscurrentfieldvalue}%
\let\glscurrentfieldvalue\@glstmp
\protected@edef\@glstmp{#3}%
\ifdefequal{\glscurrentfieldvalue}{\@glstmp}{#4}{#5}%
}%
{#5}%
}
```

`\GlsXtrForeignText{\langle entry label \rangle}{\langle text \rangle}`

`\GlsXtrForeignText`

If a field is used to store a language tag (such as `en-GB` or `de-CH-1996`) then this command uses `tracklang`'s interface to encapsulate $\langle text \rangle$. The field identifying the locale is given by `\GlsXtrForeignTextField`.

```
\ifdef\foreignlanguage
{
  \ifdef\GetTrackedDialectFromLanguageTag
  {
    \newcommand{\GlsXtrForeignText}[2]{%
```

In case this is used inside the argument of `\glxtrifhasfield`, save and restore `\glscurrentfieldvalue`.

```
\let\@glxtr@org@currentfieldvalue\glscurrentfieldvalue
\glxtrifhasfield{\GlsXtrForeignTextField}{#1}%
{%-
  \expandafter\GetTrackedDialectFromLanguageTag\expandafter
  {\glscurrentfieldvalue}{\@glxtr@dialect}%
  \let\@glxtr@locale\glscurrentfieldvalue
  \let\glscurrentfieldvalue\@glxtr@org@currentfieldvalue
  \ifdefempty\@glxtr@dialect
  {%-
```

An exact match hasn't been found. A partial match can only be obtained with at least `tracklang` v1.3.6.

```
\ifundef\TrackedDialectClosestSubMatch
{%-
  \GlossariesExtraWarning{Can't obtain dialect label
    (tracklang v1.3.6+ required)}%
  }%
  {\let\@glxtr@dialect\TrackedDialectClosestSubMatch}%
}%
}%%
\ifdefempty\@glxtr@dialect
{%-
```

No tracked dialect found for the root language.

```
}%
{%-
```

Check if there's a caption hook for the given dialect label.

```
\ifcsundef{captions\@glxtr@dialect}{}%
{%-
```

Dialect label not recognised. Check if there's a known mapping.

```
\IfTrackedDialectHasMapping{\@glxtr@dialect}%
{%-
  \edef\@glxtr@dialect{%
    \GetTrackedDialectToMapping{\@glxtr@dialect}}%
```

Does a caption hook exist for this?

```
\ifcsundef{captions\@glxtr@dialect}{}%
{%-
```

No mapping. Try root language label instead.

```

\ifcsundef{captions\@tracklang@lang}{}%
{%
\let\@glstr@dialect\@tracklang@lang
}%
}%
}%
{%

```

No mapping. Try root language label instead.

```

\ifcsundef{captions\@tracklang@lang}{}%
{%
\let\@glstr@dialect\@tracklang@lang
}%
}%
}%
}%
\ifdefempty\@glstr@dialect
{%
\GlsXtrUnknownDialectWarning{\@glstr@locale}{\@tracklang@lang}%
#2%
}%
{\foreignlanguage{\@glstr@dialect}{#2}}%
}%
{#2}% key not set
}
}
{
\newcommand{\GlsXtrForeignText}[2]{%
\GlossariesExtraWarning{Can't encapsulate foreign text:
tracklang v1.3.6+ required}%
#2%
}
}
}
{
\foreignlanguage isn't defined so just do text.
\newcommand{\GlsXtrForeignText}[2]{#2}
}

```

`\GlsXtrForeignTextField` This is the user2 field by default but may be redefined as required.

```
\newcommand*{\GlsXtrForeignTextField}{userii}
```

`\GlsXtrUnknownDialectWarning`

```

\newcommand*{\GlsXtrUnknownDialectWarning}[2]{%
\GlossariesExtraWarning{Can't determine valid dialect label
for locale '#1' (root language: #2)}%
}

```


`\glsxtrpageref` Like `\glsrefentry` but references the page number instead (if entry counting is on). The base glossaries package only introduced `\GlsEntryCounterLabelPrefix` in version 4.38, so it may not be defined.

```
\ifdef\GlsEntryCounterLabelPrefix
{%
  \newcommand*\glsxtrpageref}[1]{%
    \ifglsentrycounter
      \pageref{\GlsEntryCounterLabelPrefix\glsdetoklabel{#1}}%
    \else
      \ifglssubentrycounter
        \pageref{\GlsEntryCounterLabelPrefix\glsdetoklabel{#1}}%
      \else
        \gls{#1}%
      \fi
    \fi
  }
}%
{%
  \newcommand*\glsxtrpageref}[1]{%
    \ifglsentrycounter
      \pageref{glsentry-\glsdetoklabel{#1}}%
    \else
      \ifglssubentrycounter
        \pageref{glsentry-\glsdetoklabel{#1}}%
      \else
        \gls{#1}%
      \fi
    \fi
  }
}%
```

`\apptoglossarypreamble`

```
\newcommand{\apptoglossarypreamble}[2][\glsdefaulttype]{%
  \ifcsdef{glolist@#1}%
  {%
    \ifcsundef{@glossarypreamble@#1}%
    {\csdef{@glossarypreamble@#1}{}}%
  }%
  \csappto{@glossarypreamble@#1}{#2}%
}%
{%
  \GlossariesExtraWarning{Glossary ‘#1’ is not defined}%
}%
}
```

`\pretoglossarypreamble`

```
\newcommand{\pretoglossarypreamble}[2][\glsdefaulttype]{%
  \ifcsdef{glolist@#1}%
  {%
```

```

\ifcsundef{@glossarypreamble@#1}%
{\csdef{@glossarypreamble@#1}{}}%
{}%
\cspreto{@glossarypreamble@#1}{#2}%
}%
{%
\GlossariesExtraWarning{Glossary ‘#1’ is not defined}%
}%
}

```

`\preglossarypreamble` Typo in command name resulted in `\preglossarypreamble` being defined when it should have been called `\pretoglossarypreamble`. Old name retained for backward compatibility.

```
\newcommand{\preglossarypreamble}{\pretoglossarypreamble}
```

1.3 Modifications to Commands Provided by glossaries

Some of the commands provided by `glossaries` are modified to take into account new options or to change default behaviour.

`\@pglossarysection` Phantom section only needs to be added for starred section commands.

```

\renewcommand*{@pglossarysection}[2]{%
\glsclearpage
\ifdefempty{@glossarysecstar}
{%
\csname{@glossarysec}\endcsname{#2}%
}%
{%
\phantomsection
\@gls@toc{#1}{\@glossarysec}%
\csname{@glossarysec}\endcsname*{#2}%
}%
\@glossaryseclabel
}

```

The original `\@gls@entry@field` causes a problem for undefined entries when used in section headings or captions. Since entries must be defined with just the base package this isn’t a significant issue, but it will cause a problem with `bib2gls` where no entries are defined on the first `LATEX` call, so redefine `\@gls@entry@field` to use `\csuse` instead of `\csname`.

```
\@gls@entry@field{<label>}{<field>}
```

`\@gls@entry@field`

This command was introduced to `glossaries` version 4.03 but older versions are likely to be incompatible with `glossaries-extra`.

```

\ifdef\@gls@entry@field
{

```

```

\renewcommand*{\@gls@entry@field}[2]{\csuse{glo@\glsdetoklabel{#1}@#2}}
}
{}

```

`\ifglsused{<label>}{<true part>}{<false part>}`

`\ifglsused`

In the event that undefined entries should trigger a warning rather than an error, `\ifglsused` needs to be modified to check for existence. If the boolean variable is undefined, then its state is indeterminate and is neither true nor false, so neither `<true part>` nor `<false part>` will be performed if `<label>` is undefined. See also `\GlsXtrIfUnusedOrUndefined`.

```

\renewcommand*{\ifglsused}[3]{%
  \glsdoifexists{#1}{\ifbool{glo@\glsdetoklabel{#1}@flag}{#2}{#3}}%
}

```

`\@gls@noexpand@field` Add check for `encapinnerfmt`, `encapnocase` and `encapnocaseinnerfmt`

```

\renewcommand{\@gls@noexpand@field}[3]{%
  \glsifcategoryattributehasitem{\@glo@category}{encapnocaseinnerfmt}{#2}%
  {%
    \csxdef{glo@#1@#2}{\noexpand\NoCaseChange{\noexpand\glsxtrgenentrytextfmt
      {\expandonce{#3}}}}%
    \glsexclapplyinnerfmtfield{#1}{#2}%
  }%
  {%
    \glsifcategoryattributehasitem{\@glo@category}{encapnocase}{#2}%
    {%
      \glsifcategoryattributehasitem{\@glo@category}{encapinnerfmt}{#2}%
      {%
        \csxdef{glo@#1@#2}{\noexpand\NoCaseChange{\noexpand\glsxtrgenentrytextfmt
          {\expandonce{#3}}}}%
        \glsexclapplyinnerfmtfield{#1}{#2}%
      }%
    }%
    \csxdef{glo@#1@#2}{\noexpand\NoCaseChange{\expandonce{#3}}}%
  }%
  {%
    \glsifcategoryattributehasitem{\@glo@category}{encapinnerfmt}{#2}%
    {%
      \csxdef{glo@#1@#2}{\noexpand\glsxtrgenentrytextfmt{\expandonce{#3}}}%
      \glsexclapplyinnerfmtfield{#1}{#2}%
    }%
  }%
  \expandafter\global\expandafter\let\csname glo@#1@#2\endcsname#3%
}
}

```

`\@gls@expand@field` Add check for `encapinnerfmt`, `encapnocase` and `encapnocaseinnerfmt`

```
\renewcommand{\@gls@expand@field}[3]{%
\glsifcategoryattributehasitem{\@glo@category}{encapnocaseinnerfmt}{#2}%
{%
\protected@csxdef{glo@#1@#2}{\noexpand\NoCaseChange
{\noexpand\glstrgenentrytextfmt{#3}}}%
\glsexclapplyinnerfmtfield{#1}{#2}%
}%
}%
\glsifcategoryattributehasitem{\@glo@category}{encapnocase}{#2}%
{%
\glsifcategoryattributehasitem{\@glo@category}{encapinnerfmt}{#2}%
{%
\protected@csxdef{glo@#1@#2}{\noexpand\NoCaseChange
{\noexpand\glstrgenentrytextfmt{#3}}}%
\glsexclapplyinnerfmtfield{#1}{#2}%
}%
}%
\protected@csxdef{glo@#1@#2}{\noexpand\NoCaseChange{#3}}%
}%
}%
\glsifcategoryattributehasitem{\@glo@category}{encapinnerfmt}{#2}%
{%
\protected@csxdef{glo@#1@#2}{\noexpand\glstrgenentrytextfmt{#3}}%
\glsexclapplyinnerfmtfield{#1}{#2}%
}%
}%
\protected@csxdef{glo@#1@#2}{#3}%
}%
}%
}
```

Provide a starred version of `\longnewglossaryentry` that doesn't automatically insert `\leavevmode\unskip\nopostdesc` at the end of the description. The unstarred version is modified to use `\glstrpostlongdescription` instead.

`\longnewglossaryentry`

```
\renewcommand*{\longnewglossaryentry}{%
\@ifstar{\glstr@s@longnewglossaryentry}{\glstr@longnewglossaryentry}
}
```

`\glstr@s@longnewglossaryentry` Starred version.

```
\newcommand{\@glstr@s@longnewglossaryentry}[3]{%
\glsdoifnoexists{#1}%
{%
\bgroupp
```

```

\let\@org@newglossaryentryprehook\@newglossaryentryprehook
\long\def\@newglossaryentryprehook{%
  \long\def\@glo@desc{#3}%
  \@org@newglossaryentryprehook
}%
\renewcommand*{\gls@assign@desc}[1]{%
  \global\cslet{glo@\glsdetoklabel{#1}@desc}{\@glo@desc}%
  \global\cslet{glo@\glsdetoklabel{#1}@descplural}{\@glo@descplural}%
}
\gls@defglossaryentry{#1}{#2}%
\egroup
}%
}

```

`\glsxtr@longnewglossaryentry` Unstarred version.

```

\newcommand{\@glsxtr@longnewglossaryentry}[3]{%
  \glsdoifnoexists{#1}%
  {%
    \bgroup
    \let\@org@newglossaryentryprehook\@newglossaryentryprehook
    \long\def\@newglossaryentryprehook{%
      \long\def\@glo@desc{#3\glsxtrpostlongdescription}%
      \@org@newglossaryentryprehook
    }%
    \renewcommand*{\gls@assign@desc}[1]{%
      \global\cslet{glo@\glsdetoklabel{#1}@desc}{\@glo@desc}%

```

The following is different from the base glossaries.sty:

```

  \global\cslet{glo@\glsdetoklabel{#1}@descplural}{\@glo@descplural}%
  }
  \gls@defglossaryentry{#1}{#2}%
\egroup
}%
}

```

`\glsxtrpostlongdescription` Hook at the end of the description when using the unstarred `\longnewglossaryentry`.

```

\newcommand*{\glsxtrpostlongdescription}{\leavevmode\unskip\nopostdesc}

```

Provide a starred version of `\newignoredglossary` that doesn't add the glossary to the nohyperlist list.

`\newignoredglossary` Redefine to check for star.

```

\renewcommand{\newignoredglossary}{%
  \@ifstar\glsxtr@s@newignoredglossary\glsxtr@org@newignoredglossary
}

```

`\glsxtr@org@newignoredglossary` The original definition is patched to check for existence.

```

\newcommand*{\glsxtr@org@newignoredglossary}[1]{%
  \ifcsdef{glolist@#1}
  {%

```

```

\glxstrundefaction{Glossary type ‘#1’ already exists}{}%
}%
{%
\ifdefempty\@ignored@glossaries
{%
\protected@edef\@ignored@glossaries{#1}%
}%
{%
\protected@eappto\@ignored@glossaries{,#1}%
}%
\csgdef{glolist@#1}{,}%
\ifcsundef{gls@#1@entryfmt}%
{%
\defglentryfmt[#1]{\glentryfmt}%
}%
}%
\ifdefempty\@gls@nohyperlist
{%
\renewcommand*{\@gls@nohyperlist}{#1}%
}%
{%
\protected@eappto\@gls@nohyperlist{,#1}%
}%
}%
}

```

`\glxtr@s@newignoredglossary` Starred form.

```

\newcommand*{\glxtr@s@newignoredglossary}[1]{%
\ifcsdef{glolist@#1}
{%
\glxstrundefaction{Glossary type ‘#1’ already exists}{}%
}%
{%
\ifdefempty\@ignored@glossaries
{%
\protected@edef\@ignored@glossaries{#1}%
}%
{%
\protected@eappto\@ignored@glossaries{,#1}%
}%
\csgdef{glolist@#1}{,}%
\ifcsundef{gls@#1@entryfmt}%
{%
\defglentryfmt[#1]{\glentryfmt}%
}%
}%
}%
}

```

`\glstocctitle` Ignored glossaries don't have an associated title, so modify `\glstocctitle` to check for it to prevent an undefined command written to the toc file.

```
\glsifusetranslator
{%
  \renewcommand*{\glstocctitle}[1]{%
    \ifcsdef{gls@tr@set@#1@tocctitle}%
    {%
      \csuse{gls@tr@set@#1@tocctitle}%
    }%
    {%
      \ifcsdef{gls@#1@title}%
      {\def\glsentrytocctitle{\csname gls@#1@title\endcsname}}%
      {\def\glsentrytocctitle{\glsentrytitle}}%
    }%
  }%
}
{
  \renewcommand*{\glstocctitle}[1]{%
    \ifcsdef{gls@#1@title}%
    {\def\glsentrytocctitle{\csname gls@#1@title\endcsname}}%
    {\def\glsentrytocctitle{\glsentrytitle}}%
  }
}
```

`\provideignoredglossary` As above but won't do anything if the glossary already exists.

```
\newcommand{\provideignoredglossary}{%
  \@ifstar{glsxtr@s@provideignoredglossary}{glsxtr@provideignoredglossary}
}
```

`glsxtr@provideignoredglossary` Unstarred version.

```
\newcommand*{glsxtr@provideignoredglossary}[1]{%
  \ifcsdef{glolist@#1}
  {}%
  {%
    \ifdefempty\@ignored@glossaries
    {%
      \protected@edef\@ignored@glossaries{#1}%
    }%
    {%
      \protected@eappto\@ignored@glossaries{, #1}%
    }%
    \csgdef{glolist@#1}{,}%
    \ifcsundef{gls@#1@entryfmt}%
    {%
      \defglsentryfmt[#1]{\glsentryfmt}%
    }%
    {}%
    \ifdefempty\@gls@nohyperlist
    {%
```

```

\renewcommand*{\@gls@nohyperlist}{#1}%
}%
{%

\protected@eappto\@gls@nohyperlist{,#1}%
}%
}%
}

```

tr@s@provideignoredglossary Starred form.

```

\newcommand*{\glsxtr@s@provideignoredglossary}[1]{%
\ifcsdef{glolist@#1}
{}%
{%

\ifdefempty\@ignored@glossaries
{%
\protected@edef\@ignored@glossaries{#1}%
}%
{%
\protected@eappto\@ignored@glossaries{,#1}%
}%
\csgdef{glolist@#1}{,}%
\ifcsundef{gls@#1@entryfmt}%
{%
\defglsentryfmt[#1]{\glsentryfmt}%
}%
{}%
}%
}

```

`\glsxtrcopytoglossary` Adds an entry label to another glossary list. First argument is entry label. Second argument is glossary label. The starred version globally adds the entry label.

```

\newcommand*{\glsxtrcopytoglossary}{%
\ifstar\s@glsxtrcopytoglossary\@glsxtrcopytoglossary
}

```

`\@glsxtrcopytoglossary`

```

\newcommand*{\@glsxtrcopytoglossary}[2]{%
\glsdoifexists{#1}%
{%
\ifcsdef{glolist@#2}
{%
\protected@cseappto{glolist@#2}{#1,}%
}%
{%
\glsxtrundefaction{Glossary type ‘#2’ doesn’t exist}{}%
}%
}

```



```
}%
}
```

`\s@glxtrcopytoglossary`

```
\newcommand*\s@glxtrcopytoglossary}[2]{%
  \glstoifexists{#1}%
  {%
    \ifcsdef{glolist@#2}
    {%
      \protected@csxappto{glolist@#2}{#1,}%
    }%
    {%
      \glxtrundefaction{Glossary type ‘#2’ doesn’t exist}{}%
    }%
  }%
}
```

1.3.1 Existence Checks

`\glstoifexists` Modify `\glstoifexists` to take account of the undefaction setting.

```
\renewcommand{\glstoifexists}[2]{%
  \ifglstryexists{#1}{#2}{\glxtr@doifexists{#1}}%
}
```

`\glxtr@doifexists` Provide a robust command for the error/warning in case `\glstoifexists` is expanded.

```
\newrobustcmd{\glxtr@doifexists}[1]{%
  Define \glslabel in case it’s needed after this command (for example in the
  post-link hook).

  \protected@edef\glslabel{\glstetoklabel{#1}}%
  \expandafter\glxtrundefdebug\expandafter
    {\expandafter\detokenize\expandafter{\glslabel}}%
  \glxtrundefaction{Glossary entry ‘\glslabel’
    has not been defined}{You need to define a glossary entry before
    you can reference it.}%
}
```

`\glstoifnoexists` Modify `\glstoifnoexists` to take account of the undefaction setting.

```
\renewcommand{\glstoifnoexists}[2]{%
  \ifglstryexists{#1}{\glxtr@doifnoexists{#1}}{#2}%
}
```

`\glxtr@doifnoexists` Provide a robust command for the error/warning in case `\glstoifnoexists` is expanded.

```
\newrobustcmd{\glxtr@doifnoexists}[1]{%
  \glxtrundefaction{Glossary entry ‘\glstetoklabel{#1}’
    has already been defined}%
}
```

`\glsdoifexistsordo` Modify `\glsdoifexistsordo` to take account of the undefaction setting. This command was introduced in glossaries version 4.19, so check if it has been defined first.

```
\ifdef\glsdoifexistsordo
{%
  \renewcommand{\glsdoifexistsordo}[3]{%
    \ifglentryexists{#1}{#2}%
    {%
      \glstrundefaction{Glossary entry '\glsdetoklabel{#1}'
        has not been defined}{You need to define a glossary entry
        before you can use it.}%
      #3%
    }%
  }%
}
{%
  \glstr@warnonexistsordo\glsdoifexistsordo
  \newcommand{\glsdoifexistsordo}[3]{%
    \ifglentryexists{#1}{#2}%
    {%
      \glstrundefaction{Glossary entry '\glsdetoklabel{#1}'
        has not been defined}{You need to define a glossary entry
        before you can use it.}%
      #3%
    }%
  }%
}
```

`\doifglossarynoexistsordo` Similarly for `\doifglossarynoexistsordo`.

```
\ifdef\doifglossarynoexistsordo
{%
  \renewcommand{\doifglossarynoexistsordo}[3]{%
    \ifglossaryexists*{#1}%
    {%
      \glstrundefaction{Glossary type '#1' already exists}{}%
      #3%
    }%
    {#2}%
  }%
}
{%
  \glstr@warnonexistsordo\doifglossarynoexistsordo
  \newcommand{\doifglossarynoexistsordo}[3]{%
    \ifglossaryexists*{#1}%
    {%
      \glstrundefaction{Glossary type '#1' already exists}{}%
      #3%
    }%
    {#2}%
  }%
}
```

```
}%
}
```

There are now three types of cross-references: the `see` key (as original), the `alias` key (from `glossaries-extra` v1.12) and the `seealso` key (from `glossaries-extra` v1.16). The original `see` key needs to have a corresponding field (which it doesn't with the base `glossaries` package).

`\newglossaryentryposthook` Hook into end of `\newglossaryentry` to add “see” value as a field.

```
\appto\newglossaryentryposthook{%
\ifdefined\@glo@see
{\csxdef{glo@\@glo@label @see}{}}%
{%
\csxdef{glo@\@glo@label @see}{\@glo@see}%
\if@glxtr@autoseeindex
\@glxtr@autoindexcrossrefs
\fi
}%
}
\appto\@gls@keymap{,{see}{see}}
```

```
\glxtrseelistsencap{<content>}
```

`\glxtrseelistsencap`

Encapsulates cross-reference list.

```
\newcommand*{\glxtrseelistsencap}[1]{\space #1}
```

`\glxtrseelistsdelim` Delimiter in cross-reference list.

```
\newcommand*{\glxtrseelistsdelim}{, }
```

```
\glxtrseelists{<label>}
```

`\glxtrseelists`

```
\newcommand*{\glxtrseelists}[1]{%
\glsdoifexists{#1}%
{%
\def\@glxtr@seelists{%
\letcs{\@glo@see}{glo\@glsdetoklabel{#1}@see}%
\ifdefempty\@glo@see
{}%
}%
\protected@edef\@glxtr@seelists{%
\noexpand\glxtr@usesee\@glo@see\noexpand\@end@glxtr@usesee
}%
}%
\letcs{\@glo@see}{glo\@glsdetoklabel{#1}@seealso}%
\ifdefempty\@glo@see
```

```

{}%
{%
  \ifdefempty\@glxtr@seelists{%
    {\appto\@glxtr@seelists{\glxtrseelistsdelim}}%
    \protected@edef\@glxtr@seelists{%
      \noexpand\glxtruseseealsoformat{\@glo@see}%
    }%
  }%
  \letcs{\@glo@see}{glo@\glsdetoklabel{#1}@alias}%
  \ifdefempty\@glo@see
  {}%
  {%
    \ifdefempty\@glxtr@seelists{%
      {\appto\@glxtr@seelists{\glxtrseelistsdelim}}%
      \protected@edef\@glxtr@seelists{%
        \noexpand\glxtruseseeformat{\noexpand\seename}{\@glo@see}%
      }%
    }%
    \ifdefempty\@glxtr@seelists{%
      {\glxtrseelistsencap\@glxtr@seelists}%
    }%
  }
}

```

`\glxtrusesee` Apply `\glseeformat` to the see key if not empty.

```

\newcommand*{\glxtrusesee}[1]{%
  \glsdexists{#1}%
  {%
    \letcs{\@glo@see}{glo@\glsdetoklabel{#1}@see}%
    \ifdefempty\@glo@see
    {}%
    {%
      \expandafter\glxtr@usesee\@glo@see\@end@glxtr@usesee
    }%
  }%
}

```

`\glxtr@usesee`

```

\newcommand*{\glxtr@usesee}[1][\seename]{%
  \@glxtr@usesee[#1]%
}

```

`\@glxtr@usesee`

```

\def\@glxtr@usesee[#1]#2\@end@glxtr@usesee{%
  \glxtruseseeformat{#1}{#2}%
}

```

`\glxtruseseeformat` The format used by `\glxtrusesee`. The first argument is the tag (such as `\seename`). The second argument is the comma-separated list of cross-referenced labels.

```

\newcommand*{\glxtruseeformat}[2]{%
  \glseeformat{#1}{#2}{}%
}

```

`\glseeitemformat` glossaries originally defined `\glseeitemformat` to use `\glentryname` but in v3.0 this was switched to use `\glentrytext` due to problems occurring with the `name` field being sanitized. Since this is no longer a problem, `glossaries-extra` restored the original definition as it makes more sense to use the `name` in the cross-reference list. Unfortunately this doesn't take style changes into account, so as from v1.42, this now uses `\glfmttext` and `\glfmtname` instead. (The `text` field is chosen rather than the `short` field to allow for the “noshort” styles.)

```

\renewcommand*{\glseeitemformat}[1]{%
  \ifglshasshort{#1}{\glfmttext{#1}}{\glfmtname{#1}}%
}

```

`\glxtrseeitemformat`

```

\newcommand*{\glxtrseeitemformat}[1]{%
  \ifglshasparent{#1}%
  {\glxtrhiername{#1}}%
  {\ifglshasshort{#1}{\glfmttext{#1}}{\glfmtname{#1}}}%
}

```

`\glxtrhiername{<label>}`

`\glxtrhiername`

Displays the hierarchical name for the given entry. The cross-reference format `\glseeitemformat` may be redefined to use this command to show the hierarchy, if required. This now uses `\glfmttext` and `\glfmtname` instead of `\glaccessshort` and `\glaccessname` to allow for style formatting.

```

\newcommand*{\glxtrhiername}[1]{%
  \glstexorpdfstring
  {\@glxtrhiername{#1}}%
  {\glentryname{#1}}%
}

```

`\@glxtrhiername` Provide robust inner command.

```

\newrobustcmd*{\@glxtrhiername}[1]{%
  \glsoifexists{#1}%
  {%
    \glxtrifhasfield{parent}{#1}%
    {\expandafter\glxtrhiername\expandafter
      {\glcurrentfieldvalue}\glxtrhiernamesep}%
    {}%
    \ifglshasshort{#1}{\glfmttext{#1}}{\glfmtname{#1}}%
  }%
}

```

`\Glsxtrhiername{<label>}`

`\Glsxtrhiername`

As above but displays the top-level name with an initial capital.

```
\newcommand*{\Glsxtrhiername}[1]{%
  \glstexorpdfstring
  {\@Glsxtrhiername{#1}}%
  {\MFUsentencecase{\glstryname{#1}}}%
}
```

`\@Glsxtrhiername` Provide robust inner command.

```
\newrobustcmd*{\@Glsxtrhiername}[1]{%
  \glstoifexists{#1}%
  {%
    \glstrifhasfield{parent}{#1}%
    {%
      \expandafter\Glsxtrhiername\expandafter
      {\glscurrentfieldvalue}\glstrhiernamesep
      \ifglshasshort{#1}{\glsfmtext{#1}}{\glsfmname{#1}}%
    }%
    {\ifglshasshort{#1}{\glsfmtext{#1}}{\glsfmname{#1}}}%
  }%
}
```

```
\glsmfuaddmap{\glstrhiername}{\Glsxtrhiername}
```

`\GlsXtrhiername{<label>}`

`\GlsXtrhiername`

As above but converts the first letter of each name to a capital. (Note that this isn't applying title case, just capitalising the start of each hierarchical element.)

```
\newcommand*{\GlsXtrhiername}[1]{%
  \glstexorpdfstring
  {\@GlsXtrhiername{#1}}%
  {\glstryname{#1}}%
}
```

`\@GlsXtrhiername` Provide robust inner command.

```
\newrobustcmd*{\@GlsXtrhiername}[1]{%
  \glstoifexists{#1}%
  {%
    \glstrifhasfield{parent}{#1}%
    {\expandafter\GlsXtrhiername\expandafter
      {\glscurrentfieldvalue}\glstrhiernamesep}%
    {}%
    \ifglshasshort{#1}{\glsfmtext{#1}}{\glsfmname{#1}}%
  }%
}
```

```
\glsmfublocker{\GlsXtrhiername}
```

`\GLSxtrhiername{<label>}`

`\GLSxtrhiername`

As above but displays the top-level name in all-caps.

```
\newcommand*{\GLSxtrhiername}[1]{%
  \glstexorpdfstring
  {\@GLSxtrhiername{#1}}%
  {\GLSxtrusefield{#1}{name}}%
}
```

`\@GLSxtrhiername` Provide robust inner command.

```
\newrobustcmd*{\@GLSxtrhiername}[1]{%
  \glstoifexists{#1}%
  {%
    \glxtrifhasfield{parent}{#1}%
    {%
      \expandafter\GLSxtrhiername\expandafter
      {\glscurrentfieldvalue}\glxtrhiernamesep
      \ifglshasshort{#1}{\glsfmtext{#1}}{\glsfmname{#1}}%
    }%
    {\ifglshasshort{#1}{\GLSfmmtext{#1}}{\GLSfmmname{#1}}}%
  }%
}
\glsmfublocker{\GLSxtrhiername}
```

`\GLSXTRhiername{<label>}`

`\GLSXTRhiername`

As above but displays all names in all-caps.

```
\newcommand*{\GLSXTRhiername}[1]{%
  \glstexorpdfstring
  {\@GLSXTRhiername{#1}}%
  {\GLSxtrusefield{#1}{name}}%
}
```

`\@GLSXTRhiername` Provide robust inner command.

```
\newrobustcmd*{\@GLSXTRhiername}[1]{%
  \glstoifexists{#1}%
  {%
    \glxtrifhasfield{parent}{#1}%
    {\expandafter\GLSXTRhiername\expandafter
      {\glscurrentfieldvalue}\glxtrhiernamesep}%
    {}%
    \ifglshasshort{#1}{\GLSfmmtext{#1}}{\GLSfmmname{#1}}%
  }%
}
\glsmfublocker{\GLSXTRhiername}
```

`\glxtrhiernamesep` Separator used in `\glxtrhiername` and variants.

```
\newcommand*{\glxtrhiernamesep}{\,{\small$\triangleright$}\,}
```

`\glxtruseseealso` Apply `\glseeformat` to the `seealso` key if not empty. There's no optional tag to worry about here.

```
\newcommand*{\glxtruseseealso}[1]{%
  \glsdofexists{#1}%
  {%
    \letcs{\@glo@see}{glo\glsetoklabel{#1}@seealso}%
    \ifdefempty\@glo@see
    {}%
    {%
      \expandafter\glxtruseseealsoformat\expandafter{\@glo@see}%
    }%
  }%
}
```

`\glxtrusealias` Apply `\glseeformat` to the `alias` key if not empty. There's no optional tag to worry about here. The value also isn't a comma-separated list, but use the same interface.

```
\newcommand*{\glxtrusealias}[1]{%
  \glsdofexists{#1}%
  {%
    \letcs{\@glo@see}{glo\glsetoklabel{#1}@alias}%
    \ifdefempty\@glo@see
    {}%
    {%
```

Expansion isn't necessary because the value is a single label not a list.

```
\glxtruseseeformat{\seename}{\@glo@see}%
  }%
}
```

`\glxtruseseealsoformat` The format used by `\glxtruseseealso`. The argument is the comma-separated list of cross-referenced labels.

```
\newcommand*{\glxtruseseealsoformat}[1]{%
  \glseeformat[\seealso]{#1}{}%
}
```

`\glxtrseelist` Fully expands argument before passing to `\glseeelist`. (The argument to `\glseeelist` must be a comma-separated list of entry labels.)

```
\newrobustcmd{\glxtrseelist}[1]{%
  \protected@edef\@glo@tmp{\noexpand\glseeelist{#1}}\@glo@tmp
}
```

`\glseeelist` Redefine to make `\glseeelist` more flexible.

```
\renewrobustcmd*{\glseeelist}[1]{%
  \let\@gls@dolast\relax
```



```

\let\@gls@donext\relax
\let\@glsseeitem\@glsxtr@seefirstitem
\let\@glsseelastsep\glsseelastsep
\@for\@gls@thislabel:=#1\do{%
  \ifx\@xfor@nextelement\@nnil
    \gls@dolast
  \else
    \gls@donext
  \fi
  \expandafter\@glsseeitem\expandafter{\@gls@thislabel}%
  \let\@gls@dolast\glsseelastsep
  \let\@gls@donext\glsseesep
  \let\@glsseeitem\@glsxtr@seeitem
  \let\@glsseelastsep\glsseelastoxfordsep
}%
}

```

`\glsxtrtaggedlistsep` Separator between the tag and the list in `\glsxtrtaggedlist`

```
\newcommand{\glsxtrtaggedlistsep}{\space}
```

```

\glsxtrtaggedlist{\singular tag}{\plural
tag}{\label prefix}{\label list}

```

`\glsxtrtaggedlist`

Similar to the above but the tag is selected depending on how many items there are in the list.

```

\newrobustcmd*{\glsxtrtaggedlist}[4]{%
\begingroup
\protected@edef\@gls@taggedlist@labels{#4}%
\let\@gls@dolast\relax
\let\@gls@donext\relax
\let\@glsseeitem\@glsxtr@seefirstitem
\let\@glsseelastsep\glsseelastsep
\def\@gls@taggedlist@content{}%
\let\@gls@taggedlist@tag\relax
\@for\@gls@thislabel:=\@gls@taggedlist@labels\do{%
  \ifx\@xfor@nextelement\@nnil
    \ifx\@gls@dolast\relax
      \else
        \eappto\@gls@taggedlist@content{\expandonce\@gls@dolast}%
      \fi
    \else
      \ifx\@gls@dolast\relax
        \else
          \eappto\@gls@taggedlist@content{\expandonce\@gls@donext}%
        \fi
      \fi
    \protected@eappto\@gls@taggedlist@content{\noexpand\@glsseeitem
      {#3\@gls@thislabel}}%

```

```

\let\@gls@dolast\@glsseelastsep
\let\@gls@donext\glsseesep
\let\@glsseeitem\@glsxtr@seeitem
\let\@glsseelastsep\glsseelastoxfordsep
\ifx\@gls@taggedlist@tag\relax
\def\@gls@taggedlist@tag{#1\glsxtrtaggedlistsep}%
\else
\def\@gls@taggedlist@tag{#2\glsxtrtaggedlistsep}%
\fi
}%
\@gls@taggedlist@tag\@gls@taggedlist@content
\endgroup
}

\@glsxtr@seeitem
\newcommand*{\@glsxtr@seeitem}[1]{%
\glsxtrifmulti{#1}{\mglseeitem{#1}}{\glsseeitem{#1}}%
}

\@glsxtr@seefirstitem
\newcommand*{\@glsxtr@seefirstitem}[1]{%
\glsxtrifmulti{#1}{\mglseeefirstitem{#1}}{\glsseefirstitem{#1}}%
}

\mglseeitem Multi-entry cross-reference
\newcommand*{\mglseeitem}[1]{%
\mglename[all={noindex},setup={hyper=allmain}]{#1}%
}

\mglseeefirstitem Multi-entry cross-reference
\newcommand*{\mglseeefirstitem}{\mglseeitem}

\glsseeefirstitem
\newcommand*{\glsseeefirstitem}{\glsseeitem}

\glsseelastoxfordsep
\newcommand*{\glsseelastoxfordsep}{\glsseelastsep}

\seealso In case this command hasn't been defined. Languages packages actually provide
\also so use that if it's defined.
\ifdef\also
{\providecommand{\seealso}{\also}}
{\providecommand{\seealso}{see also}}

\glsxtrindexseealso If \@xdycrossrefhook is defined, provide a seealso crossref class. Otherwise
this just does \glssee with \seealso as the tag. The hook is only defined
if both xindy and glossaries v4.30+ are being used.
\ifdef\@xdycrossrefhook
{

```

Add the cross-reference class definition to the hook.

```
\appto\@xdycrossrefhook{%
  \write\glswrite{(define-crossref-class \string"seealso\string"
    :unverified )}%
  \write\glswrite{(markup-crossref-list
    :class \string"seealso\string"^^J\space\space\space
    :open \string"\string\glxtruseealsoformat\glsopenbrace\string"
    :close \string"\glsclosebrace\string")}%
}
```

Append to class list.

```
\appto\@xdylocationclassorder{\space\string"seealso\string"}
```

This essentially works like `\@do@seeglossary` but uses the `seealso` class. This doesn't increment the associated counter.

```
\newrobustcmd*{\glxtrindexseealso}[2]{%
  \glxtr@wrglossary@encap{#1}
  {%
    \ifx\@glxtr@record@setting\@glxtr@record@setting@alsoindex
      \@glxtr@recordsee{#1}{#2}%
    \fi
    \glsdoifexists{#1}%
    {%
      \@@glxtrwrglossmark
      \def\@gls@xref{#2}%
      \@onelevel@sanitize\@gls@xref
      \@gls@checkmkidxchars\@gls@xref
      \gls@glossary{\csname glo@#1@type\endcsname}{%
        (indexentry
          :tkey (\csname glo@#1@index\endcsname)
          :xref (\string"\@gls@xref\string")
          :attr \string"seealso\string"
        )
      }%
    }%
  }%
}
```

xindy not in use or glossaries version too old to support this.

```
\newrobustcmd*{\glxtrindexseealso}{\glssee[\seealsoname]}
}
```

The `alias` key should be set to the label of the synonymous entry. The `seealso` key essentially behaves like `see=[\seealsoname]{\langle xr-list \rangle}`. Neither of these new keys has the optional tag part allowed with `see`.

If `\gls@set@xr@key` has been defined (glossaries v4.30), use that, otherwise just use `\glsaddstoragekey`.

```
\ifdef\gls@set@xr@key
```

```
{
```

We have at least glossaries v4.30. This means the new keys can be governed by the same settings as the see key.

```
\define@key{glossentry}{alias}{%
  \gls@set@xr@key{alias}{\@glo@alias}{#1}%
}
\define@key{glossentry}{seealso}{%
  \gls@set@xr@key{seealso}{\@glo@seealso}{#1}%
}
```

Add to the key mappings.

```
\appto\@gls@keymap{,{alias}{alias},{seealso}{seealso}}
```

Set the default value.

```
\appto\@newglossaryentryprehook{\def\@glo@alias{}\def\@glo@seealso{}}%
```

Assign the field values.

```
\appto\@newglossaryentryposthook{%
  \ifdefvoid\@glo@seealso
    {\csxdef{glo@\@glo@label @seealso}{}}%
  {%
    \csxdef{glo@\@glo@label @seealso}{\@glo@seealso}%
    \if@glstr@autoseeindex
      \@glstr@autoindexcrossrefs
    \fi
  }%
}
```

The alias field doesn't trigger the automatic cross-reference indexing performed at the end of the document.

```
\ifdefvoid\@glo@alias
{\csxdef{glo@\@glo@label @alias}{}}%
{%
  \csxdef{glo@\@glo@label @alias}{\@glo@alias}%
  \glstr@aliashook{\@glo@label}%
}%
}
```

Provide user-level commands to access the values.

```
\glstralias
```

```
\newcommand*{\glstralias}[1]{\@gls@entry@field{#1}{alias}}
```

```
\glstrseealsolabels
```

```
\newcommand*{\glstrseealsolabels}[1]{\@gls@entry@field{#1}{seealso}}
```

Add to the \@glo@autosee hook.

```
\appto\@glo@autoseehook{%
  \ifdefvoid\@glo@alias
  {%
    \ifdefvoid\@glo@seealso
    {}%
  }%
}
```

```

        \protected@edef\@do@glsssee{\noexpand\glxtrindexseealso
        {\@glo@label}{\@glo@seealso}}}%
    \@do@glsssee
}%
}%
{%

```

Add cross-reference if see key hasn't been used.

```

    \ifdefvoid\@glo@see
    {%
        \protected@edef\@do@glsssee{\noexpand\glsssee{\@glo@label}{\@glo@alias}}}%
        \@do@glsssee
        \glxtraliashook{\@glo@label}%
    }%
    {}%
}%
}%
}
{

```

We have an older version of glossaries, so just use `\glsaddstoragekey`.

`\glxtralias`

```
\glsaddstoragekey*{alias}{\glxtralias}
```

`\glxtrseealsolabels`

```
\glsaddstoragekey*{seealso}{\glxtrseealsolabels}
```

If `\gls@set@xr@key` isn't defined, then `\@glo@autosee` won't be either, so use the post entry definition hook.

`\@newglossaryentryposthook` Append to the hook to check for the alias and seealso keys.

```

\appto\@newglossaryentryposthook{%
    \ifcsvoid{glo@\@glo@label @alias}%
    {%
        \ifcsvoid{glo@\@glo@label @seealso}%
        {}%
    }%
    {%
        \protected@edef\@do@glsssee{\noexpand\glxtrindexseealso
        {\@glo@label}{\csuse{glo@\@glo@label @seealso}}}%
        \@do@glsssee
    }%
}%
{%

```

Add cross-reference if see key hasn't been used.

```

    \ifdefvoid\@glo@see
    {%

```

```

        \protected@edef\@do@glsssee{\noexpand\glsssee
        {\@glo@label}{\csuse{glo@\@glo@label @alias}}}%
        \@do@glsssee
    }%
    {}%
}
}

```

`\glxtraliashook` Provide a hook that's used when the alias field is provided.

```
\newcommand*{\glxtraliashook}[1]{}%
```

Add all unused cross-references at the end of the document.

```
\AtEndDocument{\if@glxtrindexcrossrefs\glxtraddallcrossrefs\fi}
```

`\glxtraddallcrossrefs` Iterate through all used entries and if they have a cross-reference, make sure the cross-reference has been added.

```

\newcommand*{\glxtraddallcrossrefs}{%
  \foralloptions{\@glo@type}%
  {%
    \for@glxentries[\@glo@type]{\@glo@label}%
    {%
      \ifglxused{\@glo@label}{\glxtraddunusedxrefs{\@glo@label}}}%
    }%
  }%
}

```

`\glxtraddunusedxrefs` Added user-level command in case user wants to redefine `\glxtraddallcrossrefs`

```
\newcommand*{\glxtraddunusedxrefs}[1]{\expandafter\@glxtr@addunusedxrefs\expandafter{#1}}
```

`\@glxtr@addunusedxrefs` If the given entry has a see or seealso field add all unused cross-references. (The alias field isn't checked.)

```

\newcommand*{\@glxtr@addunusedxrefs}[1]{%
  \letcs{\@glo@see}{glo@\glxdetoklabel{#1}@see}%
  \ifvoid\@glo@see
  {}%
  {%
    \expandafter\glxtr@addunused\@glo@see\@end@glxtr@addunused
  }%
  \letcs{\@glo@seealso}{glo@\glxdetoklabel{#1}@seealso}%
  \ifvoid\@glo@see
  {}%
  {%
    \expandafter\glxtr@addunused\@glo@see\@end@glxtr@addunused
  }%
}

```

`\glsxtr@addunused` Adds all the entries if they haven't been used.

```
\newcommand*{\glsxtr@addunused}[1][]{%
  \@glsxtr@addunused
}
```

`\@glsxtr@addunused` Adds all the entries if they haven't been used.

```
\def\@glsxtr@addunused#1\endglsxtr@addunused{%
  \@for\@glsxtr@label:=#1\do
  {%
    \glsxtrifmulti\@glsxtr@label
    {%
      \letcs\@glsxtr@labellist{\@gls@combined@\@glsxtr@label @list}%
      \@for\@glsxtr@multilabel:=\@glsxtr@labellist\do
      {\@glsxtr@addunused\@glsxtr@multilabel\endglsxtr@addunused}%
    }%
    {%
      \ifglsused{\@glsxtr@label}{}%
      {%
        \glsadd[format=glsxtrunusedformat]{\@glsxtr@label}%
        \glsunset{\@glsxtr@label}%
        \expandafter\@glsxtr@addunusedxrefs\expandafter{\@glsxtr@label}%
      }%
    }%
  }%
}
```

`\glsxtrunusedformat`

```
\newcommand*{\glsxtrunusedformat}[1]{\unskip}
```

1.3.2 Document Definitions

`\gls@begindocdefs` This command was only introduced to glossaries v4.37, so it may not be defined. If it has been defined, redefine it to check `\@glsxtr@docdefval` so that it only inputs the `.glsdefs` file if `docdef=true`.

```
\ifdef\gls@begindocdefs
{%
  \renewcommand*{\gls@begindocdefs}{%
    \ifnum\@glsxtr@docdefval=1\relax
    \@gls@enablesavenonumberlist
    \edef\@gls@restoreat{%
      \noexpand\catcode'\noexpand\@=\number\catcode'\@\\relax}%
    \makeatletter
    \InputIfFileExists{\jobname.glsdefs}{-}{-}%
    \@gls@restoreat
    \undef\@gls@restoreat
    \gls@defdocnewglossaryentry
  }%
  \else
    \ifnum\@glsxtr@docdefval=3\relax
```

The `docdef=atom` package option has been set. Create the `.glsdefs` file for the autocomplete support but don't read it.

```
\@gls@enablesavenonumberlist
\let\gls@checkseeallowed\relax
\let\newglossaryentry\new@atom@glossaryentry
\global\newwrite\@gls@deffile
\immediate\openout\@gls@deffile=\jobname.glsdefs
```

Write all currently defined entries.

```
\forallglsentries{\@glsentry}{\@gls@writedef{\@glsentry}}%
\fi
\fi
}
}
{%
\ifnum\@glsxtr@docdefval=3\relax
\PackageError{glossaries-extra}{Package option
‘docdef=\@glsxtr@docdefsetting’ requires at least version 4.37
of the base glossaries.sty package}{}
\fi
}
```

`\new@atom@glossaryentry`

```
\newrobustcmd{\new@atom@glossaryentry}[2]{%
\gls@defglossaryentry{#1}{#2}%
\@gls@writedef{#1}%
}
```

`\makenoidxglossaries` Modify `\makenoidxglossaries` so that it automatically sets `docdef=false` (unless the restricted setting is on) and disables the `docdef` key. This command isn't allowed with the `record` option.

```
\let\glsxtr@orgmakenoidxglossaries\makenoidxglossaries
\renewcommand{\makenoidxglossaries}{%
\def\glsindexingsetting{noidx}%
\@domakeglossaries
{%
\ifdefequal\@glsxtr@record@setting\@glsxtr@record@setting@off
{%
\glsxtr@orgmakenoidxglossaries
```

Add marker to `\@do@seeglossary` but don't increment associated counter.

```
\renewcommand{\@do@seeglossary}[2]{%
\@glsxtrwrglossmark

\protected@edef\@gls@label{\glsdetoklabel{##1}}%
\protected@write\@auxout{}{%
\string\@gls@reference
{\csname glo@\@gls@label @type\endcsname}%
{\@gls@label}%
}%
```



```

\string\glsseeformat##2{}%
}%
}%
\@gls@noidx@addtorefs{\@gls@label}%
}%

```

Check for docdefs=restricted:

```
\if@glstrdocdefrestricted
```

If restricted document definitions allowed, adjust \@gls@reference so that it doesn't test for existence.

```

\renewcommand*\@gls@reference{%
\@glstr@reference
}%

```

Adjust hook to ensure unindexed parents are added to the referenced list, otherwise a rerun warning will keep occurring.

```

\appto\@newglossaryentryposthook{%
\@glstr@restricted@newentryhook
}%
\else

```

Disable document definitions.

```

\@glstrdocdeffalse
\fi
\disable@keys{glossaries-extra.sty}{docdef}%
}%
{%
\PackageError{glossaries-extra}{\string\makenoidxglossaries\space
not permitted\MessageBreak
with record=\@glstr@record@setting\space package option}%
{You may only use \string\makenoidxglossaries\space with the
record=off option}%
}%
\let\gls@warn@noidx@incompatible\@gls@warn@noidx@incompatible
}%
}

```

\@glstr@reference Check for new command.

```

\ExplSyntaxOn
\cs_if_exist:NTF \__glossaries_add_glsref:nnn
{
\newcommand*\@glstr@reference[3]{
\__glossaries_add_glsref:nnn { #1 } { #2 } { #3 }
}
}
{
\newcommand*\@glstr@reference[3]{
\ifcsundef{\@glsref@#1}{\csgdef{\@glsref@#1}{}}{}%
\ifinlistcs{#2}{\@glsref@#1}%
{}%
}
}

```

```

        {\listcsgadd{@glsref@#1}{#2}}%
        \ifcsundef{glo@\glsdetoklabel{#2}@loclist}%
        {\csgdef{glo@\glsdetoklabel{#2}@loclist}{}}%
        {}%
        \listcsgadd{glo@\glsdetoklabel{#2}@loclist}{#3}%
    }
}

\glsxtr@restricted@newentryhook

\cs_if_exist:NTF \__glossaries_noidx_add_parent_of_glsrefd:n
{
    \newcommand \glsxtr@restricted@newentryhook
    {
        \bool_lazy_and:nnT
        { \tl_if_exist_p:c { glo@ \glslabel @parent } }
        { \bool_not_p:n { \tl_if_empty_p:c { glo@ \glslabel @parent } } }
        {
            \exp_args:Nv \__glossaries_noidx_add_parent_of_glsrefd:n
            { glo@ \glslabel @parent }
        }
    }
}
{
    \newcommand \glsxtr@restricted@newentryhook { }
}
\ExplSyntaxOff

\@gls@noidx@addtorefs This was only added to glossaries v4.59, so provide it in case an older version is
installed.
\providecommand\@gls@noidx@addtorefs[1]{}%

\gls@warn@noidx@incompatible
\newcommand*{\gls@warn@noidx@incompatible}[2]{%

\gls@warn@noidx@incompatible
\newcommand*{\@gls@warn@noidx@incompatible}[2]{%
    #2\GlossariesExtraWarning{#1\space is incompatible with \string\makenoidxglossaries}%
}

\gls@warn@noidx@incompatible
\newcommand*{\@gls@warn@noidx@incompatible}[2]{%
    \gls@warn@noidx@incompatible{#1}{#2}%
    \gls@warn@makegloss@incompatible{#1}{#2}%
}

\gls@defdocnewglossaryentry Modify \gls@defdocnewglossaryentry so that it checks the docdef value.
\renewcommand*{\gls@defdocnewglossaryentry}{%
    \ifcase\@glsxtr@docdefval

```

docdef=false:

```
\renewcommand*{\newglossaryentry}[2]{%
  \PackageError{glossaries-extra}{Glossary entries must
    be \MessageBreak defined in the preamble with \MessageBreak
    package option 'docdef=false'\MessageBreak(consider using
    'docdef=restricted')}{Move your glossary definitions to
    the preamble. You can also put them in a \MessageBreak separate file
    and load them with \string\loadglsentries.}%
}%
```

\or

(docdef=true case.) Since the see value is now saved in a field, it can be used by entries that have been defined in the document.

```
\let\gls@checkseeallowed\relax
\let\newglossaryentry\new@glossaryentry
\else
```

Restricted mode just needs to allow the see value.

```
\let\gls@checkseeallowed\relax
\fi
}%
```

Permit a special form of document definition, but only allow it if the glossaries come at the end of the document. These commands behave a little like a combination of `\newterm` and `\gls`. This must be explicitly enabled with the following.

`\GlsXtrEnableOnTheFly`

```
\newcommand*{\GlsXtrEnableOnTheFly}{%
  \ifstar\@sGlsXtrEnableOnTheFly\@GlsXtrEnableOnTheFly
}
```

`\@sGlsXtrEnableOnTheFly` The starred version attempts to allow UTF8 characters in the label, but this may break! (Formatting commands mustn't be used in the label, but the label may be a command whose replacement text is the actual label. This doesn't take into account a command that's defined in terms of another command that may eventually expand to the label text.)

```
\newcommand*{\@sGlsXtrEnableOnTheFly}{%
  \renewcommand*{\glsdetoklabel}[1]{%
    \expandafter\@glsxtr@ifcsstart\string##1 \@glsxtr@end@
    {%
      \expandafter\detokenize\expandafter{##1}%
    }%
    {\detokenize{##1}}}%
  }%
  \@GlsXtrEnableOnTheFly
}
\def\@glsxtr@ifcsstart#1#2\@glsxtr@end@#3#4{%
  \expandafter\if\glsbackslash#1%
```

```

        #3%
    \else
        #4%
    \fi
}

\glsxtrstarflywarn
\newcommand*{\glsxtrstarflywarn}{%
  \GlossariesExtraWarning{Experimental starred version of
  \string\GlsXtrEnableOnTheFly\space in use (please ensure you have
  read the warnings in the glossaries-extra user manual)}%
}

```

`\@GlsXtrEnableOnTheFly`

```
\newcommand*{\@GlsXtrEnableOnTheFly}{%
```

Don't redefine `\glsdetoklabel` if LuaTeX or XeTeX is being used, since it's mainly to allow accented characters in the label.

These definitions are all assigned the category given by:

`\glsxtrcat`

```
\newcommand*{\glsxtrcat}{general}
```

`\glsxtr`

```

\newcommand*{\glsxtr}[1][]{%
  \def\glsxtr@keylist{##1}%
  \@glsxtr
}

```

`\@glsxtr`

```

\newcommand*{\@glsxtr}[2][]{%
  \ifglstryexists{##2}%
  {%
    \ifblank{##1}{\GlsXtrWarning{##1}{##2}}%
  }%
  {%
    \gls@defglossaryentry{##2}{name={##2},category=\glsxtrcat,
    description={\nopostdesc},##1}%
  }%
  \expandafter\gls\expandafter[\glsxtr@keylist]{##2}%
}

```

`\Glsxtr`

```

\newcommand*{\Glsxtr}[1][]{%
  \def\glsxtr@keylist{##1}%
  \@Glsxtr
}
\glsmfuaddmap{\glsxtr}{\Glsxtr}

```

```

\@Glsxtr
\newcommand*\@Glsxtr}[2][]{%
\ifglstryexists{##2}%
{%
\ifblank{##1}{-}{\GlsXtrWarning{##1}{##2}}%
}%
{%
\gls@defglossaryentry{##2}{name={##2},category=\glstrcat,
description={\nopostdesc},##1}%
}%
\expandafter\Gls\expandafter[\glstr@keylist]{##2}%
}

\glstrpl
\newcommand*\glstrpl#[1][]{%
\def\glstr@keylist{##1}%
\@glstrpl
}

\@glstrpl
\newcommand*\@glstrpl#[2][]{%
\ifglstryexists{##2}%
{%
\ifblank{##1}{-}{\GlsXtrWarning{##1}{##2}}%
}%
{%
\gls@defglossaryentry{##2}{name={##2},category=\glstrcat,
description={\nopostdesc},##1}%
}%
\expandafter\glsp\expandafter[\glstr@keylist]{##2}%
}

\Glsxtrpl
\newcommand*\Glsxtrpl#[1][]{%
\def\glstr@keylist{##1}%
\@Glsxtrpl
}
\glsmfuaddmap{\glstrpl}{\Glsxtrpl}

\@Glsxtrpl
\newcommand*\@Glsxtrpl#[2][]{%
\ifglstryexists{##2}%
{%
\ifblank{##1}{-}{\GlsXtrWarning{##1}{##2}}%
}%
{%
\gls@defglossaryentry{##2}{name={##2},category=\glstrcat,
description={\nopostdesc},##1}%
}%
}

```

```

\expandafter\Glspl\expandafter[\glxtr@keylist]{##2}%
}

\GlsXtrWarning
\newcommand*{\GlsXtrWarning}[2]{%
\def\@glxtr@optlist{##1}%
\@onelevel@sanitize\@glxtr@optlist
\GlossariesExtraWarning{The options ‘\@glxtr@optlist’ have
been ignored for entry ‘##2’ as it has already been defined}%
}

```

Disable commands after the glossary:

```

\renewcommand\@printglossary[2]{%
\def\@glxtr@printglossopts{##1}%
\@glxtr@orgprintglossary{##1}{##2}%
\def\@glxtr{\@glxtr@disabledflycommand\glxtr}%
\def\@glxtrpl{\@glxtr@disabledflycommand\glxtrpl}%
\def\@Glsxtr{\@glxtr@disabledflycommand\Glsxtr}%
\def\@Glsxtrpl{\@glxtr@disabledflycommand\Glsxtrpl}%
}

```

\@glxtr@disabledflycommand

```

\newcommand*{\@glxtr@disabledflycommand}[1]{%
\PackageError{glossaries-extra}%
{string##1\space can’t be used after any of the \MessageBreak
glossaries have been displayed}%
{The on-the-fly commands enabled by
\string\GlsXtrEnableOnTheFly\space may only be used \MessageBreak
before the glossaries. If you want to use any entries \MessageBreak
after any of the glossaries, you must use the standard \MessageBreak
method of first defining the entry and then using the \MessageBreak
entry with commands like \string\gls}%
\@glxtr@disabledflycommand
}%
\newcommand*{\@glxtr@disabledflycommand}[2][{}]{##2}

```

End of \GlsXtrEnableOnTheFly. Disable since it can only be used once.

```

\let\GlsXtrEnableOnTheFly\relax
}
\@onlypreamble\GlsXtrEnableOnTheFly

```

1.3.3 Existing Glossary Style Modifications

Modify \setglossarystyle to keep track of the current style. This allows the \glossaries-extra-stylemods package to reset the current style after the required modifications have been made.

\@glxtr@current@style Initialise the current style to the default style.

```

\newcommand*{\@glxtr@current@style}{\@glossary@default@style}

```

`\glstrpreglossarystyle` A hook to initialise default definitions for style commands.

```
\newcommand{\glstrpreglossarystyle}{%
  \renewcommand*{\glssubgroupheading}[4]{\glsgroupheading{##4}}%
}
```

Modify `\setglossarystyle` to set `\@glstr@current@style` and reset `\glssubgroupheading` in case the style doesn't support it.

`\setglossarystyle`

```
\renewcommand*{\setglossarystyle}[1]{%
  \ifcsundef{@glssstyle@#1}%
  {%
    \PackageError{glossaries-extra}{Glossary style ‘#1’ undefined}{}%
  }%
  {%
    \glstrpreglossarystyle
    \csname @glssstyle@#1\endcsname
  }
```

Only set the current style if it exists.

```
\protected@edef\@glstr@current@style{#1}%
}%
```

Set this as the default, if a default hasn't been set.

```
\ifx\@glossary@default@style\relax
\protected@edef\@glossary@default@style{#1}%
\fi
}
```

In case we have an old version of `glossaries`:

```
\ifdef\@glossary@default@style
{}
{%
  \let\@glossary@default@style\relax
}
```

`\glslistdottedwidth` If `\glslistdottedwidth` has been defined and is currently equal to `.5\hsize` then make the modification suggested in [bug report #92](#)

```
\ifdef\glslistdottedwidth
{%
  \ifdim\glslistdottedwidth=.5\hsize
    \setlength{\glslistdottedwidth}{-\dimexpr\maxdimen-1sp\relax}
    \AtBeginDocument{%
      \ifdim\glslistdottedwidth=-\dimexpr\maxdimen-1sp\relax
        \setlength{\glslistdottedwidth}{.5\columnwidth}%
      \fi
    }%
  \fi
}
```

Similarly for `\glsdescwidth`:

\glsdescwidth

```
\ifdef\glsdescwidth
{%
  \ifdim\glsdescwidth=.6\hsize
    \setlength{\glsdescwidth}{-\dimexpr\maxdimen-1sp\relax}
    \AtBeginDocument{%
      \ifdim\glsdescwidth=-\dimexpr\maxdimen-1sp\relax
        \setlength{\glsdescwidth}{.6\columnwidth}%
      \fi
    }%
  \fi
}
```

and for \glspagelistwidth:

\glspagelistwidth

```
\ifdef\glspagelistwidth
{%
  \ifdim\glspagelistwidth=.1\hsize
    \setlength{\glspagelistwidth}{-\dimexpr\maxdimen-1sp\relax}
    \AtBeginDocument{%
      \ifdim\glspagelistwidth=-\dimexpr\maxdimen-1sp\relax
        \setlength{\glspagelistwidth}{.1\columnwidth}%
      \fi
    }%
  \fi
}
```

\glossaryentrynumbers Has the nonumberlist option been used?

```
\def\org@glossaryentrynumbers#1{#1\gls@save@numberlist{#1}}%
\ifx\org@glossaryentrynumbers\glossaryentrynumbers
  \glsnonumberlistfalse
  \renewcommand*{\glossaryentrynumbers}[1]{%
    \ifglsentryexists{\glscurrententrylabel}%
    {%
      \@glsxtrpreloctag
      \GlsXtrFormatLocationList{#1}%
      \@glsxtrpostloctag
      \gls@save@numberlist{#1}%
    }{}%
  }%
\else
  \glsnonumberlisttrue
  \renewcommand*{\glossaryentrynumbers}[1]{%
    \ifglsentryexists{\glscurrententrylabel}%
    {%
      \gls@save@numberlist{#1}%
    }{}%
  }%
\fi
```



```
}%
\fi
```

`\GlsXtrFormatLocationList` Provide an easy interface to change the format of the location list without removing the save number list stuff.

```
\newcommand*{\GlsXtrFormatLocationList}[1]{#1}
```

Sometimes users want to prefix the location list with “page”/“pages”. The simplest way to determine if the location list consists of a single location is to check for instances of `\delimN` or `\delimR`, but this isn’t so easy to do as they might be embedded inside the argument of formatting commands. With a bit of trickery we can find out by adjusting `\delimN` and `\delimR` to set a flag and then save information to the auxiliary file for the next run.

`\GlsXtrEnablePreLocationTag`

```
\newcommand*{\GlsXtrEnablePreLocationTag}[2]{%
  \let\@glstrpreloctag\@glstrpreloctag
  \let\@glstrpostloctag\@glstrpostloctag
  \renewcommand*{\@glstr@pagetag}{#1}%
  \renewcommand*{\@glstr@pagetag}{#2}%
  \renewcommand*{\@glstr@savepreloctag}[2]{%
    \csgdef{\@glstr@preloctag@##1}{##2}%
  }%
  \renewcommand*{\@glstr@doloctag}{%
    \ifcsundef{\@glstr@preloctag@\glscurrententrylabel}%
    {%
      \GlossariesWarning{Missing pre-location tag for ‘\glscurrententrylabel’.
        Rerun required}%
    }%
    {%
      \csuse{\@glstr@preloctag@\glscurrententrylabel}%
    }%
  }%
}
```

```
\@onlypreamble\GlsXtrEnablePreLocationTag
```

`\@glstrpreloctag`

```
\newcommand*{\@glstrpreloctag}{%
  \let\@glstr@org@delimN\delimN
  \let\@glstr@org@delimR\delimR
  \let\@glstr@org@glignore\glignore
```

`\gdef` is required as the delimiters may occur inside a scope.

```
\gdef\@glstr@thisloctag{\@glstr@pagetag}%
\renewcommand*{\delimN}{%
  \gdef\@glstr@thisloctag{\@glstr@pagetag}%
  \@glstr@org@delimN}%
\renewcommand*{\delimR}{%
  \gdef\@glstr@thisloctag{\@glstr@pagetag}%
  \@glstr@org@delimR}%
```

```

\renewcommand*{\glsignore}[1]{%
  \gdef\@glsxtr@thisloctag{\relax}%
  \@glsxtr@org@glsignore{##1}}%
\@glsxtr@doloctag
}

\@glsxtr@preloctag
\newcommand*{\@glsxtr@preloctag}{}

\@glsxtr@pagetag
\newcommand*{\@glsxtr@pagetag}{}%

\@glsxtr@pagetag
\newcommand*{\@glsxtr@pagetag}{}%

\@glsxtr@postloctag
\newcommand*{\@glsxtr@postloctag}{%
  \let\delimN\@glsxtr@org@delimN
  \let\delimR\@glsxtr@org@delimR
  \let\glsignore\@glsxtr@org@glsignore
  \protected@write\@auxout{%
    {\string\@glsxtr@savepreloctag{\glscurrententrylabel}\@glsxtr@thisloctag}}%
  }

\@glsxtr@postloctag
\newcommand*{\@glsxtr@postloctag}{}

\@glsxtr@preloctag
\newcommand*{\@glsxtr@savepreloctag}[2]{%
  \protected@write\@auxout{%
    {\string\providecommand\string\@glsxtr@savepreloctag[2]{}}}

\@glsxtr@doloctag
\newcommand*{\@glsxtr@doloctag}{}

```

\KV@printgloss@nonumberlist Modify the nonumberlist key to use \GlsXtrFormatLocationList (and also save the number list):

```

\renewcommand*{\KV@printgloss@nonumberlist}[1]{%
  \XKV@plfalse
  \XKV@sttrue
  \XKV@checkchoice[\XKV@resa]{#1}{true,false}%
  {%
    \csname glsnonumberlist\XKV@resa\endcsname
    \ifglsnonumberlist
      \def\glossaryentrynumbers##1{\gls@save@numberlist{##1}}%
    \else
      \def\glossaryentrynumbers##1{%
        \@glsxtr@preloctag
        \GlsXtrFormatLocationList{##1}%

```

```

        \@glsxtrpostloctag
        \gls@save@numberlist{##1}}%
    \fi
}%
}

```

1.3.4 Entry Formatting, Hyperlinks and Indexing

`\glsentryfmt` Change default entry format. Use the generic format for regular terms (that is, entries that have a category with the `regular` attribute set) or non-regular terms without a short value and use the abbreviation format for non-regular terms that have a short value. If further attributes need to be checked, then `\glsentryfmt` will need redefining as appropriate (or use `\defglsentryfmt`). The abbreviation format is set here for entries that have a short form, even if they are regular entries to ensure the abbreviation fonts are correct.

```

\renewcommand*{\glsentryfmt}{%
  \ifglshasshort{\glslabel}{\glssetabbrvfmt{\glscategory{\glslabel}}}{}%
  \glsifregular{\glslabel}%
  {\glsxtrregularfont{\glsgenentryfmt}}%
  {%
    \ifglshasshort{\glslabel}%
    {\glsxtrabbreviationfont{\glsxtrgenabbrvfmt}}%
    {\glsxtrregularfont{\glsgenentryfmt}}%
  }%
}

```

`\glsxtrregularfont` Font used for regular entries.

```
\newcommand*{\glsxtrregularfont}[1]{#1}
```

`\glsxtrabbreviationfont` Font used for abbreviation entries.

```
\newcommand*{\glsxtrabbreviationfont}[1]{#1}
```

Some formatting commands (such as highlighting or letter spacing) may require expandable content in the argument, so also provide a formatting command for use within `\glsgenentryfmt` for those instances.

`\glsxtrdefaultentrytextfmt` This is the default command that `\glsxtrgenentrytextfmt` is initialised to within `\@gls@link`.

```
\newcommand{\glsxtrdefaultentrytextfmt}[1]{#1}
```

`\glsxtrattrententrytextfmt` Provide a convenient command that applies the formatting according to the category attribute. This isn't used by default as this inner formatting should rarely be needed and increases complexity.

```

\newcommand{\glsxtrattrententrytextfmt}[1]{%
  \glshasattribute{\glslabel}{innertextformat}%
  {%
    \csuse{\glsgetattribute{\glslabel}{innertextformat}}{#1}%
  }%
}

```

```
{#1}%
}
```

`\glstrgenentrytextfmt` This command is a user-level command to allow it to be included in custom formats or styles but it should not be redefined at the user level as it's redefined within `\@gls@link` (similar to other style commands, such as `\glscapscase`). Redefine `\glstrdefaultentrytextfmt` to change the default definition for this command.

```
\newcommand*\glstrgenentrytextfmt{\glstrdefaultentrytextfmt}
```

```
\glsfmtfield{<insert>}{<cs>}{<label>}{<field>}
```

`\glsfmtfield`

Provide a convenient way of applying a formatting command to the actual field contents. No check for existence.

Note this command intentionally isn't robust, as it's possible that a user may want to redefine an abbreviation command to use `\MakeLowercase`, for example, to use smallcaps when abbreviations have been defined with the short version in capitals. Using `\newrobustcmd` will break that case.

```
\newcommand*\glsfmtfield[4]{%
  \expandafter\expandafter\expandafter
  #2\expandafter\expandafter\expandafter
  {\csname glo@glsdetoklabel{#3}@#4\endcsname #1}%
}
```

```
\Glsfmtfield{<insert>}{<cs>}{<label>}{<field>}
```

`\Glsfmtfield`

As above but convert first letter to uppercase. Note that if the formatting command can go outside of `\makefirstuc` then it can simply be applied around the appropriate command that expands to the field value. For example,

```
%\emph{\Glsentrytext{label}}
%
```

instead of

```
%\Glsfmtfield{}{\emph}{sample}{text}
%
```

Note this command intentionally isn't robust for the same reason as above. The expansion allows `\makefirstuc` to pick up any mappings or blockers before the content is passed to `\MFUsentencecase`.

```
\newcommand*\Glsfmtfield[4]{%
  \ifx#2\@firstofone
  \expandafter\expandafter\expandafter
  \glssentencecase\expandafter\expandafter\expandafter
  {%
```

```

\csname glo@glstdetoklabel{#3}@#4\endcsname #1%
}%
\else
\expandafter\expandafter\expandafter
\glssentencecase\expandafter\expandafter\expandafter
{%
\expandafter\expandafter\expandafter
#2\expandafter\expandafter\expandafter
{\csname glo@glstdetoklabel{#3}@#4\endcsname #1}%
}%
\fi
}
\glsmfuaddmap{\glsfmtfield}{\Glsfmtfield}

```

`\Glsfmtfield{<insert>}{<cs>}{<label>}{<field>}`

`\Glsfmtfield`

As above but convert all to uppercase. The expansion is in case we have an older kernel.

```

\newcommand*{\Glsfmtfield}[4]{%
\ifx#2\@firstofone
\expandafter\expandafter\expandafter
\glssupercase\expandafter\expandafter\expandafter
{%
\csname glo@glstdetoklabel{#3}@#4\endcsname #1%
}%
\else
\expandafter\expandafter\expandafter
\glssupercase\expandafter\expandafter\expandafter
{%
\expandafter\expandafter\expandafter
#2\expandafter\expandafter\expandafter
{\csname glo@glstdetoklabel{#3}@#4\endcsname #1}%
}%
\fi
}
\glsmfublocker{\Glsfmtfield}

```

`\glsfmtinsert` Formats `\glsinsert`.

```

\newcommand*{\glsfmtinsert}{%
\ifdefempty\glsinsert{}%
{\expandafter\glstrgenentrytextfmt\expandafter{\glsinsert}}%
}

```

`\Glsfmtinsert` As above but all caps.

```

\newcommand*{\Glsfmtinsert}{%
\ifdefempty\glsinsert{}%
{%
\expandafter\glssupercase\expandafter

```

```

    {\expandafter\glstrgenentrytextfmt\expandafter{\glinsert}}}%
  }%
}

```

```
\glsifapplyinnerfmtfield{\label}{\field}{\true}{\false}
```

`\glsifapplyinnerfmtfield`

Does `\true` if `\glsgenentryfmt` should encapsulate the given field with the inner format otherwise does `\false`.

```

\newcommand*\glsifapplyinnerfmtfield[4]{%
\ifcsundef{@glo@\glstetoklabel{#1}@innerfmt@fields}%
{#3}%
{\xifinlistcs{#2}{@glo@\glstetoklabel{#1}@innerfmt@fields}{#4}{#3}}%
}

```

`\glsexclapplyinnerfmtfield` Adds the field to the exclusion list. This typically means that the field value already contains the inner formatting.

```

\newcommand*\glsexclapplyinnerfmtfield[2]{%
\listcseadd{@glo@\glstetoklabel{#1}@innerfmt@fields}{#2}%
}

```

`\glsgenentryfmt` Redefine to use `\glstrgenentrytextfmt`

```

\renewcommand*\glsgenentryfmt{%
\ifdefempty\glscustomtext
{%
\glsifplural
{%

```

Plural form

```

\glscapscase
{%

```

Don't adjust case

```

\ifglssused\glslabel
{%

```

Subsequent use

```

\glsifapplyinnerfmtfield{\glslabel}{plural}%
{%
\expandafter\glssaccessfmtplural\expandafter{\glinsert}%
{\glstrgenentrytextfmt}{\glslabel}%
}%
{\glssaccessplural{\glslabel}\glssfmtinsert}%
}%
{%

```

First use

```

\glsifapplyinnerfmtfield{\glslabel}{firstpl}%
{%
\expandafter\glssaccessfmtfirstplural\expandafter{\glinsert}%

```

```

        {\glstrgenentrytextfmt}{\glslabel}%
    }%
    {\glsaccessfirstplural{\glslabel}\glsfmtinsert}%
}%
}%
{%

```

Make first letter upper case

```

\ifglsused\glslabel
{%

```

Subsequent use.

```

\glsifapplyinnerfmtfield{\glslabel}{plural}%
{%
    \expandafter\Glsaccessfmtplural\expandafter
    {\glsinsert}{\glstrgenentrytextfmt}{\glslabel}%
}%
{\Glsaccessplural{\glslabel}\glsfmtinsert}%
}%
{%

```

First use

```

\glsifapplyinnerfmtfield{\glslabel}{firstpl}%
{%
    \expandafter\Glsaccessfmtfirstplural\expandafter
    {\glsinsert}{\glstrgenentrytextfmt}{\glslabel}%
}%
{\Glsaccessfirstplural{\glslabel}\glsfmtinsert}%
}%
}%
{%

```

Make all upper case

```

\ifglsused\glslabel
{%

```

Subsequent use

```

\glsifapplyinnerfmtfield{\glslabel}{plural}%
{%
    \expandafter\GLSaccessfmtplural\expandafter
    {\glsinsert}{\glstrgenentrytextfmt}{\glslabel}%
}%
{\GLSaccessplural{\glslabel}\GLSfmtinsert}%
}%
{%

```

First use

```

\glsifapplyinnerfmtfield{\glslabel}{firstpl}%
{%
    \expandafter\GLSaccessfmtfirstplural\expandafter
    {\glsinsert}{\glstrgenentrytextfmt}{\glslabel}%
}%

```

```

        {\GLSaccessfirstplural{\glslabel}\GLSfmtinsert}%
    }%
}%
}%
{%
Singular form
    \glscapscase
    {%
Don't adjust case
    \ifglssused\glslabel
    {%
Subsequent use
    \glsifapplyinnerfmtfield{\glslabel}{text}%
    {%
        \expandafter\glsaccessfmttext\expandafter
        {\glsinsert}{\glstrgenentrytextfmt}{\glslabel}%
    }%
    {\glsaccesstext{\glslabel}\glsfmtinsert}%
}%
{%
First use
    \glsifapplyinnerfmtfield{\glslabel}{first}%
    {%
        \expandafter\glsaccessfmtfirst\expandafter
        {\glsinsert}{\glstrgenentrytextfmt}{\glslabel}%
    }%
    {\glsaccessfirst{\glslabel}\glsfmtinsert}%
}%
}%
{%
Make first letter upper case
    \ifglssused\glslabel
    {%
Subsequent use
    \glsifapplyinnerfmtfield{\glslabel}{text}%
    {%
        \expandafter\Glsaccessfmttext\expandafter
        {\glsinsert}{\glstrgenentrytextfmt}{\glslabel}%
    }%
    {\Glsaccesstext{\glslabel}\glsfmtinsert}%
}%
{%
First use
    \glsifapplyinnerfmtfield{\glslabel}{first}%
    {%

```



```

\expandafter\Glsaccessfmtfirst\expandafter
{\glsinsert}{\glstrgenentrytextfmt}{\glslabel}%
}%
{\Glsaccessfirst{\glslabel}\glsfmtinsert}%
}%
}%
{%

```

Make all upper case

```

\ifglssused\glslabel
{%

```

Subsequent use

```

\glsifapplyinnerfmtfield{\glslabel}{text}%
{%
\expandafter\Glsaccessfmttext\expandafter
{\glsinsert}{\glstrgenentrytextfmt}{\glslabel}%
}%
{\Glsaccesstext{\glslabel}\Glsfmtinsert}%
}%
{%

```

First use

```

\glsifapplyinnerfmtfield{\glslabel}{first}%
{%
\expandafter\Glsaccessfmtfirst\expandafter
{\glsinsert}{\glstrgenentrytextfmt}{\glslabel}%
}%
{\Glsaccessfirst{\glslabel}\Glsfmtinsert}%
}%
}%
}%
}%
{%

```

Custom text provided in `\glstdisp`, in which case the formatting should already be applied.

```

\glscustomtext
}%
}

```

Commands like `\glsifplural` are only used by the `\gls`-like commands in the `glossaries` package, but it might be useful for the post-link hook to know if the user has used, say, `\glsfirst` or `\glsplural`. This can provide better consistency with the formatting of the `\gls`-like commands, even though they don't use `\glstryfmt`.

`\glstrifwasglslike` For use in the post-link hook, this indicates whether or not the hook follows a `\gls`-like command.

```

\newcommand*{\glstrifwasglslike}[2]{#2}

```

`\glxtrifwasglslikeandfirstuse`

```
\newcommand*\glxtrifwasglslikeandfirstuse}[2]{%
  \glxtrifwasglslike
  {%
    \glxtrifwasfirstuse{#1}{#2}%
  }{#2}%
}
```

`\glxtrifwassubsequentuse`

```
\newcommand*\glxtrifwassubsequentuse}[2]{%
  \glxtrifwasglslike
  {%
    \glxtrifwasfirstuse{#2}{#1}%
  }{#2}%
}
```

`\glxtrifallcaps` Shortcut.

```
\newcommand*\glxtrifallcaps}[2]{\glscapscase{#2}{#1}{#1}}
```

`\glxtrcurrentfield` Another placeholder to find out information about the calling command. This will be empty for the `\gls` and `\glxtrfull` set of commands and will be the singular field otherwise.

```
\newcommand*\glxtrcurrentfield){}
```

`\glxtr@shortfieldname`

```
\newcommand*\glxtr@shortfieldname){short}
```

`\glxtrifwassubsequentorshort`

```
\newcommand*\glxtrifwassubsequentorshort}[2]{%
  \glxtrifwasglslike
  {%
    \glxtrifwasfirstuse{#2}{#1}%
  }%
  {\ifdefequal\glxtrcurrentfield\glxtr@shortfieldname{#1}{#2}}%
}
```

`\@gls@field@link` Redefine `\@gls@field@link` so that commands like `\glsfirst` can setup `\glxtrifwasfirstuse` etc to allow the postlink hook to work better. This now has an optional argument that sets up the defaults.

```
\renewcommand*\@gls@field@link}[4][]{%
```

If the record option has been used, the information needs to be written to the aux file regardless of whether the entry exists (unless indexing has been switched off).

```
\@glxtr@record{#2}{#3}{glslink}%
\glsdoifexists{#3}%
{%
```

Save and restore the hyper setting (`\@gls@link` also does this, but that's too late if the optional argument of `\@gls@field@link` modifies it).

```
\let\glstrorg@ifKV@glslink@hyper\ifKV@glslink@hyper
```

Save local setting.

```
\@gls@save@glslocal
```

Initialise preunset, prereset and postunset

```
\glsinitreunsets
\let\do@gls@link@checkfirsthyper\@gls@link@nocheckfirsthyper
\def\glscustomtext{#4}%
\@glsxtr@field@linkdefs
#1%
\@gls@link[#2]{#3}{#4}%
\let\ifKV@glslink@hyper\glstrorg@ifKV@glslink@hyper
\@gls@restore@glslocal
}%
\glspostlinkhook
}
```

The commands `\gls`, `\Gls` etc don't use `\@gls@field@link`, so they need modifying as well to use `\@glsxtr@record`.

`\@gls@` Save the original definition and redefine.

```
\let\@glsxtr@org@gls@\@gls@
\def\@gls@#1#2{%
  \def\glstrcurrentfield{}%
  \@glsxtr@record{#1}{#2}{glslink}%
  \@glsxtr@org@gls@{#1}{#2}%
}%
```

`\@glspl@` Save the original definition and redefine.

```
\let\@glsxtr@org@glspl@\@glspl@
\def\@glspl@#1#2{%
  \def\glstrcurrentfield{}%
  \@glsxtr@record{#1}{#2}{glslink}%
  \@glsxtr@org@glspl@{#1}{#2}%
}%
```

`\@Gls@` Save the original definition and redefine.

```
\let\@glsxtr@org@Gls@\@Gls@
\def\@Gls@#1#2{%
  \def\glstrcurrentfield{}%
  \@glsxtr@record{#1}{#2}{glslink}%
  \@glsxtr@org@Gls@{#1}{#2}%
}%
```

`\@Glspl@` Save the original definition and redefine.

```
\let\@glsxtr@org@Glspl@\@Glspl@
\def\@Glspl@#1#2{%
```

```

\def\glxstrcurrentfield{}%
\@glxstr@record{#1}{#2}{glslink}%
\@glxstr@org@GLspl@{#1}{#2}%
}%

\@GLS@ Save the original definition and redefine.
\let\@glxstr@org@GLS@\@GLS@
\def\@GLS@#1#2{%
  \def\glxstrcurrentfield{}%
  \@glxstr@record{#1}{#2}{glslink}%
  \@glxstr@org@GLS@{#1}{#2}%
}%

\@GLSpl@ Save the original definition and redefine.
\let\@glxstr@org@GLSpl@\@GLSpl@
\def\@GLSpl@#1#2{%
  \def\glxstrcurrentfield{}%
  \@glxstr@record{#1}{#2}{glslink}%
  \@glxstr@org@GLSpl@{#1}{#2}%
}%

\@glsdisp This is redefined to allow the recording on the first run. Can't save and restore
\@glsdisp since it has an optional argument.
\renewcommand*{\@glsdisp}[3][{}]{%
  \def\glxstrcurrentfield{}%
  \@glxstr@record{#1}{#2}{glslink}%
  \glsdoifexists{#2}{%
    \let\do@gl@link@checkfirsthyper\@gl@link@checkfirsthyper
    \let\glsifplural\@secondoftwo
    \let\glscapscase\@firstofthree
    \def\glscustomtext{\glxstrgenentrytextfmt{#3}}%
    \def\glsinsert{}%
    \def\@glo@text{\cename{gls@glstype}{@entryfmt}\endcsname}%
    \@gl@link[#1]{#2}{\@glo@text}%
    \@gl@do@gl@unset{#2}%
  }%
  \glspostlinkhook
}

\@gl@link Redefine to include \@glxstr@record
\renewcommand*{\@gl@link}[3][{}]{%
  \def\glxstrcurrentfield{}%
  \@glxstr@record{#1}{#2}{glslink}%
  \glsdoifexistsordo{#2}%
  {%
    \let\do@gl@link@checkfirsthyper\relax
    Post-link hook commands need initialising.
    \def\glscustomtext{#3}%
    \def\glsinsert{}%

```

```

        \@glxtr@field@linkdefs
        \@gls@link[#1]{#2}{\glxtrgenentrytextfmt{#3}}%
    }%
    {%
        \glstextformat{#3}%
    }%
    \glspostlinkhook
}

\glxtrinitwrgloss Set the default if the wrgloss is omitted.
\newcommand*{\glxtrinitwrgloss}{%
    \glsifattribute{\glslabel}{wrgloss}{after}%
    {%
        \glxtrinitwrglossbeforefalse
    }%
    {%
        \glxtrinitwrglossbeforetrue
    }%
}

\ifglxtrwrglossbefore Conditional to determine if the indexing should be done before the link text.
\newif\ifglxtrinitwrglossbefore
\glxtrinitwrglossbeforetrue

\setupglslink Shortcut command to set glslink options.
\newcommand*{\setupglslink}[1]{\setkeys{glslink}{#1}}

\setupglsadd Shortcut command to set glsadd options.
\newcommand*{\setupglsadd}[1]{\setkeys{glsadd}{#1}}

\@gls@do@glsprereset
\newcommand*{\@gls@do@glsprereset}[1]{}

\define@choicekey{glslink}{prereset}%
[ \@glxtr@preresetval \@glxtr@preresetnr ]%
{none,local,global}[local]%
{%
    \ifcase\@glxtr@preresetnr
        \let\@gls@do@glsprereset\@gobble
    \or
        \def\@gls@do@glsprereset{%
            \let\@gls@link@postkeys@checkfirsthyper\do@gls@link@checkfirsthyper
            \let\glxtrifwasfirstuse\@firstoftwo\glslocalreset}%
        \or
        \def\@gls@do@glsprereset{%
            \let\@gls@link@postkeys@checkfirsthyper\do@gls@link@checkfirsthyper
            \let\glxtrifwasfirstuse\@firstoftwo\glsreset}%
        \fi
}

```

```

\@gls@do@glspreunset
\newcommand*{\@gls@do@glspreunset}[1]{%
\ifdefined\@gls@glslink@hyper@update@hook
This hook was only introduced to glossaries v4.50, so if isn't defined, need to
patch the hyper key.
\ifdefined\@gls@glslink@hyper@update@hook
{%
\renewcommand*{\@gls@glslink@hyper@update@hook}{%
\let\@gls@if@glslink@hyper@updated\@firstoftwo
}
}
{
\newcommand*{\@gls@glslink@hyper@update@hook}{%
\let\@gls@if@glslink@hyper@updated\@firstoftwo
}
\renewcommand*{\KV@glslink@hyper}[1]{%
\XKV@plfalse\XKV@sttrue
\XKV@checkchoice[\XKV@resa ][#1]{true,false}%
{\csname KV@glslink@hyper\XKV@resa \endcsname \@gls@glslink@hyper@update@hook}%
}
}
}

\define@choicekey{glslink}{preunset}%
[\@glsxtr@preunsetval\@glsxtr@preunsetnr]%
{none,local,global}[local]%
{%
\ifcase\@glsxtr@preunsetnr
\let\@gls@do@glspreunset\@gobble
\or
\def\@gls@do@glspreunset{%
\let\@gls@link@postkeys@checkfirsthyper\do@gls@link@checkfirsthyper
\let\glxtrifwasfirstuse\@secondoftwo\glslocalunset}%
\or
\def\@gls@do@glspreunset{%
\let\@gls@link@postkeys@checkfirsthyper\do@gls@link@checkfirsthyper
\let\glxtrifwasfirstuse\@secondoftwo\glsunset}%
\fi
}

\define@choicekey{glslink}{postunset}%
[\@glsxtr@postunsetval\@glsxtr@postunsetnr]%
{none,local,global}[global]%
{%
\ifcase\@glsxtr@postunsetnr
\let\@gls@restore@glslocal\@gls@ignore@restore@glslocal
\or
\let\@gls@restore@glslocal\@gls@default@restore@glslocal
\KV@glslink@localtrue
\or
\let\@gls@restore@glslocal\@gls@default@restore@glslocal

```

```

\KV@glslink@localfalse
\fi
}

\glsinitreunsets
\newcommand*{\glsinitreunsets}{%
\let\@gls@do@glspreunset\@gobble
\let\@gls@do@glsprereset\@gobble
\let\@gls@restore@glsllocal\@gls@default@restore@glsllocal
\@glstrbuffer@check@repeats
}

Define wrgloss key to determine whether to write the glossary information
before or after the link text.
\define@choicekey{glslink}{wrgloss}%
[\@glstr@wrglossval\@glstr@wrglossnr]%
{before,after}%
{%
\ifcase\@glstr@wrglossnr\relax
\glstrinitwrglossbeforetrue
\or
\glstrinitwrglossbeforefalse
\fi
}

\define@key{glslink}{thevalue}{\def\@glstr@thevalue{#1}}
\define@key{glslink}{theHvalue}{\def\@glstr@theHvalue{#1}}

\ifglstr@hyperoutside Define a hyperoutside key to determine whether \hyperlink should be outside
\glstextformat.
\define@boolkey{glslink}[glstr@]{hyperoutside}[true]{}
\glstr@hyperoutsidetrue

r@current@textformat@csname
\newcommand*{\@glstr@current@textformat@csname}{\glstextformat}

r@current@innertextformat@csname
\newcommand*{\@glstr@current@innertextformat@csname}{\glstrdefaultentrytextfmt}

\glstrassignlinktextfmt Used to assign \glstextformat and \glstrgenentrytextfmt in the post-link
hook for “postfootnote” abbreviation styles.
\newcommand*{\glstrassignlinktextfmt}{}

\@glstr@local@textformat Provide a key to locally change the text format.
\define@key{glslink}{textformat}{%
\ifcsdef{#1}
{%
\letcs{\@glstr@local@textformat}{#1}%

```

```

\def\@glsxtr@current@textformat@csname{#1}%
}%
{%
\PackageError{glossaries-extra}{Unknown control sequence name ‘#1’}{}%
}%
}

\glsxtr@local@innertextformat Provide a key to locally change the inner text format.
\define@key{glslink}{innertextformat}{%
\ifcsdef{#1}
{%
\letcs{\@glsxtr@local@innertextformat}{#1}%
\def\@glsxtr@current@innertextformat@csname{#1}%
}%
{%
\PackageError{glossaries-extra}{Unknown control sequence name ‘#1’}{}%
}%
}

\define@key{glslink}{prefix}{\def\glolinkprefix{#1}}

\glsxtrinithyperoutside Set the default if the hyperoutside is omitted.
\newcommand*{\glsxtrinithyperoutside}{%
\glsifattribute{\glslabel}{hyperoutside}{false}%
{%
\glsxtr@hyperoutsidefalse
}%
{%
\glsxtr@hyperoutsidetrue
}%
}

\glsxtr@inc@linkcount Does nothing by default.
\newcommand*{\glsxtr@inc@linkcount}{%

\glslinkpresetkeys User hook performed immediately before options are set. Does nothing by
default.
\newcommand*{\glslinkpresetkeys}{%

\GlsXtrExpandedFmt Helper command that (protected) fully expands second argument and then ap-
plies it to the first, which must be a command that takes a single argument.
\newrobustcmd*{\GlsXtrExpandedFmt}[2]{%
\protected@edef\@glsxtr@tmp{#2}%
\expandafter#1\expandafter{\@glsxtr@tmp}%
}

\glsxtr@use@equation@counter@or If in a numbered equation, change the counter to equation. This can be over-
ridden by explicitly setting the counter in the optional argument of commands
like \gls and \glslink.

```



```

\newcommand*{\@glstr@use@equation@counter}{%
  \@glstr@ifnum@mmode{\def\@glstr@counter{equation}}{}%
}

```

`\glstr@do@autoadd` If `\GlsXtrAutoAddOnFormat` is used, this will automatically use `\glsadd`. It's therefore only used with `\@glstr@link` not with `\glsadd` otherwise it could trigger an infinite loop. The argument indicates the key family (`glslink` or `glossadd`).

```

\newcommand*{\glstr@do@autoadd}[1]{}

```

```

\GlsXtrAutoAddOnFormat[<label>]{<format list>}{<glsadd
options>}

```

`\GlsXtrAutoAddOnFormat`

If an entry is indexed with the format set to one identified in the comma-separated list, then automatically index it using `\glsadd` with the given options, which may override the current options. Scoping is needed to prevent leakage.

```

\newcommand*{\GlsXtrAutoAddOnFormat}[3][\glstrlabel]{%
  \renewcommand*{\glstr@do@autoadd}[1]{%
    \begingroup
      \protected@edef\@glstr@do@autoadd{%
        \noexpand\ifstrequal{##1}{\glstrlink}%
        {%
          \noexpand\DTLifinlist
            {\@glstrnumberformat}{#2}%
            {\noexpand\glsadd[format={\@glstrnumberformat},#3]{#1}}{}%
        }%
      }%
    }%
  }%
  \@glstr@do@autoadd
\endgroup
}%
}

```

`\GlsXtrClearAutoAddOnFormat` Reset.

```

\newcommand\GlsXtrClearAutoAddOnFormat{%
  \renewcommand*{\glstr@do@autoadd}[1]{}%
}

```

`\glslinkwrcontent` This was defined to add grouping to resolve [issue #189](#) but had unexpected consequences ([issue #194](#)) so the grouping has been removed and transferred to `\glsencapwrcontent`.

```

\providecommand*{\glslinkwrcontent}[1]{#1}

```

`\@glstrlink@prefix@label` Hyperlink using current prefix and label.

```

\newcommand*{\@glstrlink@prefix@label}[1]{%
  \@glstrlink{\glolinkprefix\glstrlabel}{#1}}

```

`\@noglslink@prefix@label`

```
\newcommand*{\@noglslink@prefix@label}[1]{%
  \glsdonohyperlink{\glslinkprefix\glslabel}{#1}}
```

`\@gls@link` Redefine to allow the indexing to be placed after the link text. By default this is done before the link text to prevent problems that can occur from the whatsit, but there may be times when the user would like the indexing done afterwards even though it causes a whatsit.

```
\def\@gls@link[#1]#2#3{%
  \leavevmode

  \protected@edef\glslabel{\glsdetoklabel{#2}}%
  \def\@gls@link@opts{#1}%
  \let\@gls@link@label\glslabel
  \let\@glsnumberformat\@glsxtr@defaultnumberformat
  \protected@edef\@gls@counter{\csname glo@\glslabel @counter\endcsname}%
  \protected@edef\gls@type{\csname glo@\glslabel @type\endcsname}%
  \let\org@ifKV@glslink@hyper@ifKV@glslink@hyper
```

Save local setting.

```
\@gls@save@glslocal
```

Initialise preunset, prereset and postunset

```
\glsinitreunsets
```

Save current value of `\glslinkprefix`:

```
\let\@glsxtr@org@glslinkprefix\glslinkprefix
```

Initialise `\@glsxtr@local@textformat`

```
\let\@glsxtr@local@textformat\relax
\def\@glsxtr@current@textformat@csname{gls@textformat}%
```

Initialise inner text format (1.49):

```
\let\@glsxtr@local@innertextformat\glsxtr@defaultentrytextfmt
\def\@glsxtr@current@innertextformat@csname{glsxtr@defaultentrytextfmt}%
```

Initialise thevalue and theHvalue (v1.19).

```
\def\@glsxtr@thevalue{}%
\def\@glsxtr@theHvalue{\@glsxtr@thevalue}%
```

Initialise when indexing should occur (new to v1.14).

```
\glsxtrinitwrgloss
```

Initialise whether `\hyperlink` should be outside `\gls@textformat` (new to v1.21).

```
\glsxtrinithyperoutside
```

Note that the default link options may override `\glsxtrinitwrgloss`.

```
\@gls@setdefault@glslink@opts
```

Increment link counter if enabled (new to v1.26).

```
\glsxtr@inc@linkcount
```

Check if the equations option has been set (new to v1.37).

```
\if@glxtr@equations
\@glxtr@use@equation@counter
\fi
```

As the original definition.

```
\do@gl:disablehyperinlist
\do@gl:link@checkfirsthyper
```

Provide way of finding if hyper key has been explicitly set.

```
\let\@gl@if@gl:link@hyper@updated\@secondoftwo
\let\@gl:link@postkeys@checkfirsthyper\relax
```

User hook before options are set (new to v1.26):

```
\gl:link@presetkeys
```

Set options.

```
\setkeys{gl:link}{#1}%
```

Perform auto add if set (new to v1.37)

```
\glxtr@do@autoadd{gl:link}%
```

User hook after options are set:

```
\gl:link@postsetkeys
```

Reset/unset if required:

```
\@gl:do@gl:prereset{#2}%
\@gl:do@gl:spreunset{#2}%
```

If the hyper setting hasn't changed, and reset/unset option has been used, need to perform another check.

```
\@gl@if@gl:link@hyper@updated{}\@gl:link@postkeys@checkfirsthyper}%
```

Set inner text format (1.49):

```
\let\glxtr@genentrytextfmt\@glxtr@local@innertextformat
```

Check thevalue and theHvalue before saving (v1.19).

```
\ifdefempty{\@glxtr@thevalue}%
{%
\@gl:saveentrycounter
}%
{%
\let\thegl:entrycounter\@glxtr@thevalue
\def\theHgl:entrycounter{\@glxtr@theHvalue}%
}%
\@gl:setsort{\gl:label}%
```

Check if the textformat key has been used.

```
\ifx\@glxtr@local@textformat\relax
```

Check textformat attribute (new to v1.21).

```
\gl:hasattribute{\gl:label}{textformat}%
{%
\protected@edef\@glxtr@attrval{\gl:getattribute{\gl:label}{textformat}}%
```

```

\ifcsdef{\@glsxtr@attrval}%
{%
  \letcs{\@glsxtr@textformat}{\@glsxtr@attrval}%
  \let\@glsxtr@current@textformat@csname\@glsxtr@attrval
}%
{%
  \GlossariesExtraWarning{Unknown control sequence name
    '\@glsxtr@attrval' supplied in textformat attribute
    for entry '\glslabel'. Reverting to default \string\glstextformat}%
  \let\@glsxtr@textformat\glstextformat
}%
}%
{%
  \let\@glsxtr@textformat\glstextformat
}%
\else
  \let\@glsxtr@textformat\@glsxtr@local@textformat
\fi

```

Setup formatting assignments for use in post-link hook.

```

\edef\glsxtrassignlinktextfmt{%
  \noexpand\def\noexpand\glslabel{\expandonce\glslabel}%
  \noexpand\letcs\noexpand\glstextformat{\@glsxtr@current@textformat@csname}%
  \noexpand\letcs\noexpand\glsxtrgenentrytextfmt
    {\@glsxtr@current@innertextformat@csname}%
}%

```

Encapsulate link text and indexing.

```

\glslinkwrcontent
{%

```

Do write if it should occur before the link text:

```

  \ifglsxtrinitwrglossbefore
  \glsxtr@wrglossary@encap{#2}{\@do@wrglossary{#2}}%
\fi

```

Do the link text:

```

  \ifKV@glslink@hyper
  \ifglsxtr@hyperoutside
    \@glslink@prefix@label{\@glsxtr@textformat{#3}}%
  \else
    \@glsxtr@textformat{\@glslink@prefix@label{#3}}%
  \fi
\else
  \ifglsxtr@hyperoutside
    \noglslink@prefix@label{\@glsxtr@textformat{#3}}%
  \else
    \@glsxtr@textformat{\noglslink@prefix@label{#3}}%
  \fi
\fi

```

Do write if it should occur after the link text:

```

\ifglstrinitwrglossbefore
\else
\glstr@wrglossary@encap{#2}{\do@wrglossary{#2}}%
\fi
}%

Restore original value of \glolinkprefix:
\let\glolinkprefix\@glstr@org@glolinkprefix
As the original definition:
\let\ifKV@glslink@hyper\org@ifKV@glslink@hyper
\@glstr@restore@glslocal
}

\define@key{glossadd}{thevalue}{\def\@glstr@thevalue{#1}}
\define@key{glossadd}{theHvalue}{\def\@glstr@theHvalue{#1}}

\glsaddpresetkeys
\newcommand*{\glsaddpresetkeys}{}

\glsaddpostsetkeys
\newcommand*{\glsaddpostsetkeys}{}

\glsadd Redefine to include \@glstr@record and suppress in headings
\renewrobustcmd*{\glsadd}[2][\%
\glstr@trifinmark
\}%
\%
\@glstr@adjustmode
\begin@group
\@glstradd{#1}{#2}%
\end@group
\}%
}

\@glstradd
\newcommand{\@glstradd}[2]{\%
\@glstr@record{#1}{#2}{glossadd}%
\glstrdoifexists{#2}%
\%
\let\@glstrnumberformat\@glstr@defaultnumberformat

\protected@edef\@glstr@counter{\csname glo@glstrdetoklabel{#2}@counter\endcsname}%
\def\@glstr@thevalue{}%
\def\@glstr@theHvalue{\@glstr@thevalue}%

Implement any default settings (before options are set)
\glsaddpresetkeys
\setkeys{glossadd}{#1}%

```

Implement any default settings (after options are set)

```
\glsaddpostsetkeys
\ifdefempty{\@glsxtr@thevalue}%
{%
  \gls@saveentrycounter
}%
{%
  \let\theglsentrycounter\@glsxtr@thevalue
  \def\theHglentrycounter{\@glsxtr@theHvalue}%
}%
```

Define sort key if necessary (in case of sort=use):

```
\@gls@setsort{#2}%
```

Ensure that indexing occurs (since that's the point of `\glsadd`). If indexing has been switched off by default, don't want the setting to affect `\glsadd`. The ignored format `\glsignore` can be used for selection without location, but the indexing still needs to be performed.

```
\KV@glslink@noindexfalse
\glsxtr@wrglossary@encap{#2}{\@do@wrglossary{#2}}%
}%
}
```

`\glsaddeach` Performs `\glsadd` for each entry listed in the mandatory argument.

```
\newrobustcmd{\glsaddeach}[2][]{%
  \glsxtrifinmark
}%
{%
  \@gls@adjustmode
  \@for\@gls@thislabel:=#2\do{\@glsadd{#1}{\@gls@thislabel}}}%
}%
}
```

`\glsxtr@rangeformat`

```
\newcommand{\glsxtr@rangeformat}{\@glsxtr@defaultnumberformat}
```

`\GlsXtrSetDefaultRangeFormat`

```
\newcommand*{\GlsXtrSetDefaultRangeFormat}[1]{%
  \renewcommand*{\glsxtr@rangeformat}{#1}%
}%
```

`\glsstartrange` Essentially does `\glsadd[format=]{\langle label \rangle}`

```
\newrobustcmd{\glsstartrange}[2][]{%
  \glsxtrifinmark
}%
{%
  \@gls@adjustmode
  \begingroup
  \appto\glsaddpresetkeys{\protected@edef\@glsnumberformat{\glsxtr@rangeformat}}%
```

```

        \appto\glsaddpostsetkeys{\protected@edef\@glsnumberformat{\@glsnumberformat}}%
        \for\@gls@thislabel:=#2\do{\@glsadd{#1}{\@gls@thislabel}}%
        \endgroup
    }%
}

\glsendrange Essentially does \glsadd[format=)]{\langle label\rangle}
\newrobustcmd{\glsendrange}[2][\{%
    \glxtrifinmark
    {\}%
    {\%
        \@gls@adjustmode
        \begingroup
        \appto\glsaddpresetkeys{\protected@edef\@glsnumberformat{\glxtr@rangeformat}}%
        \appto\glsaddpostsetkeys{\protected@edef\@glsnumberformat{\@glsnumberformat}}%
        \for\@gls@thislabel:=#2\do{\@glsadd{#1}{\@gls@thislabel}}%
        \endgroup
    }%
}

```

`\@glxtr@field@linkdefs` Default settings for `\@gls@field@link`. Note that from v1.49, `\glsinsert` is set with `\glxtrsaveminset`.

```

\newcommand*{\@glxtr@field@linkdefs}{\%
    \let\glxtrifwasglslike\@secondoftwo
    \let\glxtrifwasfirstuse\@secondoftwo
    \let\glsifplural\@secondoftwo
    \let\glscapscase\@firstofthree
}

```

Redefine the field link commands that need to modify the above. Also add accessibility support and set the abbreviation styles if required.

`\glxtrassignfieldfont`

```

\newcommand*{\glxtrassignfieldfont}[1]{\%
    \ifglstryexists{#1}%
    {\%
        \ifglshasshort{#1}%
        {\%
            \glsetabbrvfmt{\glscategory{#1}}%
            \glsifregular{#1}%
            {\let\@gls@field@font\glxtrregularfont}%
            {\let\@gls@field@font\@firstofone}%
        }%
        {\%
            \glsifnotregular{#1}%
            {\let\@gls@field@font\@firstofone}%
            {\let\@gls@field@font\glxtrregularfont}%
        }%
    }%
    {\%

```

```

\let\@gls@field@font\@gobble
}%
}

```

```
\glsxtrsaveinsert{<entry-label>}{<insert>}
```

`\glsxtrsaveinsert`

The insert argument isn't saved in `\glsinsert` for the `\glslike` commands, but provide a way to save it if it is required for the post-link hook. The default is to set `\glsinsert` to empty. This means that the insert won't appear in the post-link hook with commands like `\glsxtrfull` for the hyphen abbreviation styles. The entry label is provided in case the insert should only be saved for certain entries, such as those with a particular category.

```
\newcommand*{\glsxtrsaveinsert}[2]{\def\glsinsert{}}
```

`\glsxtrfullsaveinsert` As above but specifically for commands like `\glsxtrfull`

```
\newcommand*{\glsxtrfullsaveinsert}{\glsxtrsaveinsert}
```

`\@glstext@` The abbreviation format may also need setting.

```

\def\@glstext@#1#2[#3]{%
  \def\glsxtrcurrentfield{text}%
  \glsxtrassignfieldfont{#2}%
  \glsxtrsaveinsert{#2}{#3}%
  \@gls@field@link{#1}{#2}%
  {%
    \glsifapplyinnerfmtfield{#2}{text}%
    {%
      \@gls@field@font{\glsaccessfmttext{#3}{\glsxtrgenentrytextfmt{#2}}}%
    }%
    {%
      \@gls@field@font{\glsaccesstext{#2}\glsxtrgenentrytextfmt{#3}}%
    }%
  }%
}

```

`\@GLStext@` All uppercase version of `\glstext`. The abbreviation format may also need setting.

```

\def\@GLStext@#1#2[#3]{%
  \def\glsxtrcurrentfield{text}%
  \glsxtrassignfieldfont{#2}%
  \glsxtrsaveinsert{#2}{#3}%
  \@gls@field@link[\let\gls@caps@case\@thirdofthree]{#1}{#2}%
  {%
    \glsifapplyinnerfmtfield{#2}{text}%
    {%
      \@gls@field@font{\@GLSaccessfmttext{#3}{\glsxtrgenentrytextfmt{#2}}}%
    }%
    {%

```



```

\ifx\glscapscase\@thirdofthree
  \@gls@field@font{\GlsAccesstext{#2}%
    \glssupercase{\glstrgenentrytextfmt{#3}}}%
\else
  \@gls@field@font{\glssaccesstext{#2}\glstrgenentrytextfmt{#3}}%
\fi
}%
}%
}

```

`\@Glsfirst@` First letter uppercase version. The abbreviation format may also need setting.

```

\def\@Glsfirst@#1#2[#3]{%
  \def\glstrcurrentfield{text}%
  \glstrassignfieldfont{#2}%
  \glstrsaveinsert{#2}{#3}%
  \@gls@field@link[\let\glscapscase\@secondofthree]{#1}{#2}%
  {%
    \glssifapplyinnerfmtfield{#2}{text}%
    {%
      \@gls@field@font{\Glsaccessfmttext{#3}{\glstrgenentrytextfmt{#2}}}%
    }%
    {%
      \@gls@field@font{\Glsaccesstext{#2}\glstrgenentrytextfmt{#3}}%
    }%
  }%
}

```

Version 1.07 ensures that `\glssfirst` etc honours the `nohyperfirst` attribute. Allow a convenient way for the user to revert to ignoring this attribute for these commands.

`\glstrchecknohyperfirst`

```

\newcommand*{\glstrchecknohyperfirst}[1]{%
  \glssifattribute{#1}{nohyperfirst}{true}{\KV@glsslink@hyperfalse}{}%
}

```

`\@glssfirst@` No case changing version. The abbreviation format may also need setting.

```

\def\@glssfirst@#1#2[#3]{%
  \def\glstrcurrentfield{first}%
  \glstrassignfieldfont{#2}%
  Ensure that \glssfirst honours the nohyperfirst attribute.
  \glstrsaveinsert{#2}{#3}%
  \@gls@field@link
  [\let\glstrifwasfirstuse\@firstoftwo
  \glstrchecknohyperfirst{#2}%
  \glstr@check@complexstyle{#2}{#3}%
  ]{#1}{#2}%
  {%
    \glssifapplyinnerfmtfield{#2}{first}%
  }%
}

```

```

    {%
      \gls@field@font{\glsaccessfmtfirst{#3}{\glsxtrgenentrytextfmt}{#2}}%
    }%
    {%
      \gls@field@font{\glsaccessfirst{#2}\glsxtrgenentrytextfmt{#3}}%
    }%
  }%
}

```

`\Glsfirst@` First letter uppercase version. The abbreviation format may also need setting.

```

\def\@Glsfirst@#1#2[#3]{%
  \def\glsxtrcurrentfield{first}%
  \glsxtrassignfieldfont{#2}%

```

Ensure that `\Glsfirst` honours the `nohyperfirst` attribute.

```

  \glsxtrsaveinsert{#2}{#3}%
  \@gls@field@link
  [\let\glsxtrifwasfirstuse\@firstoftwo
   \let\glscapscase\@secondofthree
   \glsxtrchecknohyperfirst{#2}%
   \glsxtr@check@complexstyle{#2}{#3}%
  ]%
  {#1}{#2}%
  {%
    \glsifapplyinnerfmtfield{#2}{first}%
    {%
      \gls@field@font{\Glsaccessfmtfirst{#3}{\glsxtrgenentrytextfmt}{#2}}%
    }%
    {%
      \gls@field@font{\Glsaccessfirst{#2}\glsxtrgenentrytextfmt{#3}}%
    }%
  }%
}

```

`\GLSfirst@` All uppercase version. The abbreviation format may also need setting.

```

\def\@GLSfirst@#1#2[#3]{%
  \def\glsxtrcurrentfield{first}%
  \glsxtrassignfieldfont{#2}%

```

Ensure that `\GLSfirst` honours the `nohyperfirst` attribute.

```

  \glsxtrsaveinsert{#2}{#3}%
  \@gls@field@link
  [\let\glsxtrifwasfirstuse\@firstoftwo
   \let\glscapscase\@thirdofthree
   \glsxtrchecknohyperfirst{#2}%
   \glsxtr@check@complexstyle{#2}{#3}%
  ]%
  {#1}{#2}%
  {%
    \ifx\glscapscase\@thirdofthree

```

```

\glsifapplyinnerfmtfield{#2}{first}%
{%
  \@gls@field@font{\GLSaccessfmtfirst{#3}{\glsxtrgenentrytextfmt}{#2}}%
}%
{%
  \@gls@field@font{\GLSaccessfirst{#2}%
    \glsuppercase{\glsxtrgenentrytextfmt{#3}}}%
}%
\else
\glsifapplyinnerfmtfield{#2}{first}%
{%
  \@gls@field@font{\glsaccessfmtfirst{#3}{\glsxtrgenentrytextfmt}{#2}}%
}%
{%
  \@gls@field@font{\glsaccessfirst{#2}\glsxtrgenentrytextfmt{#3}}%
}%
\fi
}%
}

```

`\@glsplural@` No case changing version. The abbreviation format may also need setting.

```

\def\@glsplural@#1#2[#3]{%
  \def\glsxtrcurrentfield{text}%
  \glsxtrassignfieldfont{#2}%
  \glsxtrsaveinsert{#2}{#3}%
  \@gls@field@link
  [\let\glsifplural\@firstoftwo
   \glsxtr@check@complexstyle{#2}{#3}%
  ]{#1}{#2}%
  {%
    \glsifapplyinnerfmtfield{#2}{plural}%
    {%
      \@gls@field@font{\glsaccessfmtpplural{#3}{\glsxtrgenentrytextfmt}{#2}}%
    }%
    {%
      \@gls@field@font{\glsaccessplural{#2}\glsxtrgenentrytextfmt{#3}}%
    }%
  }%
}

```

`\@Glsplural@` First letter uppercase version. The abbreviation format may also need setting.

```

\def\@Glsplural@#1#2[#3]{%
  \def\glsxtrcurrentfield{text}%
  \glsxtrassignfieldfont{#2}%
  \glsxtrsaveinsert{#2}{#3}%
  \@gls@field@link
  [\let\glsifplural\@firstoftwo
   \let\gls@caps@case\@secondofthree
   \glsxtr@check@complexstyle{#2}{#3}%
  ]%
}

```

```

{#1}{#2}%
{%
  \glsifapplyinnerfmtfield{#2}{plural}%
  {%
    \@gls@field@font{\Glsaccessfmtplural{#3}{\glsxtrgenentrytextfmt}{#2}}%
  }%
  {%
    \@gls@field@font{\Glsaccessplural{#2}\glsxtrgenentrytextfmt{#3}}%
  }%
}%
}

```

`\@GLSplural@` All uppercase version. The abbreviation format may also need setting.

```

\def\@GLSplural@#1#2[#3]{%
  \def\glsxtrcurrentfield{text}%
  \glsxtrassignfieldfont{#2}%
  \glsxtrsaveinsert{#2}{#3}%
  \@gls@field@link
  [\let\glsifplural\@firstoftwo
   \let\glsapscase\@thirdofthree
   \glsxtr@check@complexstyle{#2}{#3}%
  ]%
  {#1}{#2}%
  {%
    \ifx\glsapscase\@thirdofthree
      \glsifapplyinnerfmtfield{#2}{plural}%
      {%
        \@gls@field@font{\Glsaccessfmtplural{#3}{\glsxtrgenentrytextfmt}{#2}}%
      }%
      {%
        \@gls@field@font{\Glsaccessplural{#2}%
          \glsuppercase{\glsxtrgenentrytextfmt{#3}}}%
      }%
    \else
      \glsifapplyinnerfmtfield{#2}{plural}%
      {%
        \@gls@field@font{\glsaccessfmtplural{#3}{\glsxtrgenentrytextfmt}{#2}}%
      }%
      {%
        \@gls@field@font{\glsaccessplural{#2}\glsxtrgenentrytextfmt{#3}}%
      }%
    \fi
  }%
}

```

`\@glsfirstplural@` No case changing version. The abbreviation format may also need setting.

```

\def\@glsfirstplural@#1#2[#3]{%
  \def\glsxtrcurrentfield{first}%
  \glsxtrassignfieldfont{#2}%

```

Ensure that `\glsfirstplural` honours the `nohyperfirst` attribute.

```
\glsxtrsaveinsert{#2}{#3}%
\@gls@field@link
[\let\glsxtrifwasfirstuse\@firstoftwo
\let\glsifplural\@firstoftwo
\glsxtrchecknohyperfirst{#2}%
\glsxtr@check@complexstyle{#2}{#3}%
]%
{#1}{#2}%
{%
\glsifapplyinnerfmtfield{#2}{firstpl}%
{%
\@gls@field@font{\glsaccessfmtfirstplural{#3}{\glsxtrgenentrytextfmt}{#2}}%
}%
{%
\@gls@field@font{\glsaccessfirstplural{#2}\glsxtrgenentrytextfmt{#3}}%
}%
}%
}
```

`\@Glsfirstplural@` First letter uppercase version. The abbreviation format may also need setting.

```
\def\@Glsfirstplural@#1#2[#3]{%
\def\glsxtrcurrentfield{first}%
\glsxtrassignfieldfont{#2}%
```

Ensure that `\glsfirstplural` honours the `nohyperfirst` attribute.

```
\glsxtrsaveinsert{#2}{#3}%
\@gls@field@link
[\let\glsxtrifwasfirstuse\@firstoftwo
\let\glsifplural\@firstoftwo
\let\gls@capscase\@secondofthree
\glsxtrchecknohyperfirst{#2}%
\glsxtr@check@complexstyle{#2}{#3}%
]%
{#1}{#2}%
{%
\glsifapplyinnerfmtfield{#2}{firstpl}%
{%
\@gls@field@font{\Glsaccessfmtfirstplural{#3}{\glsxtrgenentrytextfmt}{#2}}%
}%
{%
\@gls@field@font{\Glsaccessfirstplural{#2}\glsxtrgenentrytextfmt{#3}}%
}%
}%
}
```

`\@GLSfirstplural@` All uppercase version. The abbreviation format may also need setting.

```
\def\@GLSfirstplural@#1#2[#3]{%
\def\glsxtrcurrentfield{first}%
\glsxtrassignfieldfont{#2}%
```

Ensure that `\glsfirstplural` honours the `nohyperfirst` attribute.

```
\glsxtrsaveinsert{#2}{#3}%
\@gls@field@link
[\let\glsxtrifwasfirstuse\@firstoftwo
\let\glsifplural\@firstoftwo
\let\gls caps case\@thirdofthree
\glsxtrchecknohyperfirst{#2}%
\glsxtr@check@complexstyle{#2}{#3}%
]%
{#1}{#2}%
{%
\ifx\gls caps case\@thirdofthree
\glsifapplyinnerfmtfield{#2}{firstpl}%
{%
\@gls@field@font{\GLSaccessfmtfirstplural{#3}{\glsxtrgenentrytextfmt}{#2}}%
}%
{%
\@gls@field@font{\GLSaccessfirstplural{#2}%
\glsuppercase{\glsxtrgenentrytextfmt{#3}}}%
}%
\else
\glsifapplyinnerfmtfield{#2}{firstpl}%
{%
\@gls@field@font{\glsaccessfmtfirstplural{#3}{\glsxtrgenentrytextfmt}{#2}}%
}%
{%
\@gls@field@font{\glsaccessfirstplural{#2}\glsxtrgenentrytextfmt{#3}}%
}%
\fi
}%
}
```

`\@glsname@` Redefine to use accessibility support. The abbreviation format may also need setting.

```
\def\@glsname@#1#2[#3]{%
\def\glsxtrcurrentfield{name}%
\glsxtrassignfieldfont{#2}%
\glsxtrsaveinsert{#2}{#3}%
\@gls@field@link{#1}{#2}%
{%
\glsifapplyinnerfmtfield{#2}{name}%
{%
\@gls@field@font{\glsaccessfmtname{#3}{\glsxtrgenentrytextfmt}{#2}}%
}%
{%
\@gls@field@font{\glsaccessname{#2}\glsxtrgenentrytextfmt{#3}}%
}%
}%
}
```

`\@Glsname@` First letter uppercase version. The abbreviation format may also need setting.

```
\def\@Glsname@#1#2[#3]{%
  \def\glstrcurrentfield{name}%
  \glstrassignfieldfont{#2}%
  \glstrsaveinsert{#2}{#3}%
  \@gls@field@link
  [\let\glscapscase\@secondofthree]{#1}{#2}%
  {%
    \gl@ifapplyinnerfmtfield{#2}{name}%
    {%
      \@gls@field@font{\Glsaccessfmtname{#3}{\glstrgenentrytextfmt}{#2}}%
    }%
    {%
      \@gls@field@font{\Glsaccessname{#2}\glstrgenentrytextfmt{#3}}%
    }%
  }%
}
```

`\@GLSname@` All uppercase version. The abbreviation format may also need setting.

```
\def\@GLSname@#1#2[#3]{%
  \def\glstrcurrentfield{name}%
  \glstrassignfieldfont{#2}%
  \glstrsaveinsert{#2}{#3}%
  \@gls@field@link[\let\glscapscase\@thirdofthree]{%
    #1}{#2}%
  {%
    \gl@ifapplyinnerfmtfield{#2}{name}%
    {%
      \@gls@field@font{\GLSaccessfmtname{#3}{\glstrgenentrytextfmt}{#2}}%
    }%
    {%
      \@gls@field@font{\GLSaccessname{#2}%
        \glssupercase{\glstrgenentrytextfmt{#3}}}%
    }%
  }%
}
```

`\@glsdesc@`

```
\def\@glsdesc@#1#2[#3]{%
  \def\glstrcurrentfield{description}%
  \glstrassignfieldfont{#2}%
  \glstrsaveinsert{#2}{#3}%
  \@gls@field@link{#1}{#2}%
  {%
    \gl@ifapplyinnerfmtfield{#2}{desc}%
    {%
      \@gls@field@font{\glsaccessfmtdesc{#3}{\glstrgenentrytextfmt}{#2}}%
    }%
    {%

```

```

        \@gls@field@font{\glsaccessdesc{#2}\glsxtrgenentrytextfmt{#3}}%
    }%
}%
}

```

\@Glsdesc@ First letter uppercase version.

```

\def\@Glsdesc@#1#2[#3]{%
  \def\glsxtrcurrentfield{description}%
  \glsxtrassignfieldfont{#2}%
  \glsxtrsaveinsert{#2}{#3}%
  \@gls@field@link
  [\let\glscapscase\@secondofthree]{#1}{#2}%
  {%
    \glsifapplyinnerfmtfield{#2}{desc}%
    {%
      \@gls@field@font{\Glsaccessfmtdesc{#3}{\glsxtrgenentrytextfmt}{#2}}%
    }%
    {%
      \@gls@field@font{\Glsaccessdesc{#2}\glsxtrgenentrytextfmt{#3}}%
    }%
  }%
}

```

\@GLSdesc@ All uppercase version.

```

\def\@GLSdesc@#1#2[#3]{%
  \def\glsxtrcurrentfield{description}%
  \glsxtrassignfieldfont{#2}%
  \glsxtrsaveinsert{#2}{#3}%
  \@gls@field@link[\let\glscapscase\@thirdofthree]{%
    {#1}{#2}%
    {%
      \glsifapplyinnerfmtfield{#2}{desc}%
      {%
        \@gls@field@font{\GLSaccessfmtdesc{#3}{\glsxtrgenentrytextfmt}{#2}}%
      }%
      {%
        \@gls@field@font{\GLSaccessdesc{#2}%
          \glsuppercase{\glsxtrgenentrytextfmt{#3}}}%
      }%
    }%
  }%
}

```

\@glsdescplural@ No case-changing version.

```

\def\@glsdescplural@#1#2[#3]{%
  \def\glsxtrcurrentfield{description}%
  \glsxtrassignfieldfont{#2}%
  \glsxtrsaveinsert{#2}{#3}%
  \@gls@field@link
  [\let\glscapscase\@secondofthree

```



```

\let\glsifplural\@firstoftwo
]{#1}{#2}%
{%
\glsifapplyinnerfmtfield{#2}{descplural}%
{%
\@gls@field@font{\glsaccessfmtdescpl{#3}{\glsxtrgenentrytextfmt}{#2}}%
}%
{%
\@gls@field@font{\glsaccessdescplural{#2}\glsxtrgenentrytextfmt{#3}}%
}%
}%
}

```

\@Glsdescplural@ First letter uppercase version.

```

\def\@Glsdescplural@#1#2[#3]{%
\def\glsxtrcurrentfield{description}%
\glsxtrassignfieldfont{#2}%
\glsxtrsaveinsert{#2}{#3}%
\@gls@field@link
[\let\glscapscase\@secondofthree
\let\glsifplural\@firstoftwo
]{#1}{#2}%
{%
\glsifapplyinnerfmtfield{#2}{descplural}%
{%
\@gls@field@font{\Glsaccessfmtdescpl{#3}{\glsxtrgenentrytextfmt}{#2}}%
}%
{%
\@gls@field@font{\Glsaccessdescplural{#2}#3}%
}%
}%
}

```

\@GLSdescplural@ All uppercase version.

```

\def\@GLSdescplural@#1#2[#3]{%
\def\glsxtrcurrentfield{description}%
\glsxtrassignfieldfont{#2}%
\glsxtrsaveinsert{#2}{#3}%
\@gls@field@link
[\let\glscapscase\@thirdofthree
\let\glsifplural\@firstoftwo
]%
]{#1}{#2}%
{%
\glsifapplyinnerfmtfield{#2}{descplural}%
{%
\@gls@field@font{\GLSaccessfmtdescplural{#3}{\glsxtrgenentrytextfmt}{#2}}%
}%
{%
\@gls@field@font{\GLSaccessdescplural{#2}}%
}
}

```

```

        \glssupercase{\glstrgenentrytextfmt{#3}}}%
    }%
}

\@glssymbol@
\def\@glssymbol@#1#2[#3]{%
  \def\glstrcurrentfield{symbol}%
  \glstrassignfieldfont{#2}%
  \glstrsaveinsert{#2}{#3}%
  \@gls@field@link{#1}{#2}%
  {%
    \gl@ifapplyinnerfmtfield{#2}{symbol}%
    {%
      \@gls@field@font{\glaccessfmtsymboll{#3}{\glstrgenentrytextfmt}{#2}}%
    }%
    {%
      \@gls@field@font{\glaccesssymboll{#2}\glstrgenentrytextfmt{#3}}%
    }%
  }%
}

\@Glsymbol@ First letter uppercase version.
\def\@Glsymbol@#1#2[#3]{%
  \def\glstrcurrentfield{symbol}%
  \glstrassignfieldfont{#2}%
  \glstrsaveinsert{#2}{#3}%
  \@gls@field@link
  [\let\glscapscase\@secondofthree]%
  {#1}{#2}%
  {%
    \gl@ifapplyinnerfmtfield{#2}{symbol}%
    {%
      \@gls@field@font{\Glsaccessfmtsymboll{#3}{\glstrgenentrytextfmt}{#2}}%
    }%
    {%
      \@gls@field@font{\Glsaccesssymboll{#2}\glstrgenentrytextfmt{#3}}%
    }%
  }%
}

\@GLSsymbol@ All uppercase version.
\def\@GLSsymbol@#1#2[#3]{%
  \def\glstrcurrentfield{symbol}%
  \glstrassignfieldfont{#2}%
  \glstrsaveinsert{#2}{#3}%
  \@gls@field@link[\let\glscapscase\@thirdofthree]%
  {#1}{#2}%
  {%

```

```

\glsifapplyinnerfmtfield{#2}{symbol}%
{%
  \@gls@field@font{\GLSaccessfmtsymbol{#3}{\glsxtrgenentrytextfmt}{#2}}%
}%
{%
  \@gls@field@font{\GLSaccesssymbol{#2}%
    \glsuppercase{\glsxtrgenentrytextfmt{#3}}}%
}%
}%
}

```

\@Glsymbolplural@ No case-changing version.

```

\def\@Glsymbolplural@#1#2[#3]{%
  \def\glsxtrcurrentfield{symbol}%
  \glsxtrassignfieldfont{#2}%
  \glsxtrsaveinsert{#2}{#3}%
  \@gls@field@link
  [\let\glscapscase\@secondofthree
  \let\glsifplural\@firstoftwo
  ]{#1}{#2}%
  {%
    \glsifapplyinnerfmtfield{#2}{symbolplural}%
    {%
      \@gls@field@font{\glsaccessfmtsymbolplural{#3}{\glsxtrgenentrytextfmt}{#2}}%
    }%
    {%
      \@gls@field@font{\glsaccesssymbolplural{#2}\glsxtrgenentrytextfmt{#3}}%
    }%
  }%
}

```

\@Glsymbolplural@ First letter uppercase version.

```

\def\@Glsymbolplural@#1#2[#3]{%
  \def\glsxtrcurrentfield{symbol}%
  \glsxtrassignfieldfont{#2}%
  \glsxtrsaveinsert{#2}{#3}%
  \@gls@field@link
  [\let\glsapsacase\@secondofthree
  \let\glsifplural\@firstoftwo
  ]{#1}{#2}%
  {%
    \glsifapplyinnerfmtfield{#2}{symbolplural}%
    {%
      \@gls@field@font{\Glsaccessfmtsymbolplural{#3}{\glsxtrgenentrytextfmt}{#2}}%
    }%
    {%
      \@gls@field@font{\Glsaccesssymbolplural{#2}\glsxtrgenentrytextfmt{#3}}%
    }%
  }%
}

```

\@GLSsymbolplural@ All uppercase version.

```

\def\@GLSsymbolplural@#1#2[#3]{%
  \def\glstrcurrentfield{symbol}%
  \glstrassignfieldfont{#2}%
  \glstrsaveinsert{#2}{#3}%
  \@gls@field@link
  [\let\glscapscase\@thirdofthree
   \let\glsifplural\@firstoftwo
  ]%
  {#1}{#2}%
  {%
    \glsifapplyinnerfmtfield{#2}{symbolplural}%
    {%
      \@gls@field@font{\GLSaccessfmtsymbolplural{#3}{\glstrgenentrytextfmt}{#2}}%
    }%
    {%
      \@gls@field@font{\GLSaccesssymbolplural{#2}%
        \glssupercase{\glstrgenentrytextfmt{#3}}}%
    }%
  }%
}

```

\@glsuseri@ User 1 field.

```

\def\@glsuseri@#1#2[#3]{%
  \def\glstrcurrentfield{user1}%
  \glstrassignfieldfont{#2}%
  \glstrsaveinsert{#2}{#3}%
  \@gls@field@link
  {#1}{#2}%
  {%
    \glsifapplyinnerfmtfield{#2}{useri}%
    {%
      \@gls@field@font{\glsaccessfmtuseri{#3}{\glstrgenentrytextfmt}{#2}}%
    }%
    {%
      \@gls@field@font{\glsaccessuseri{#2}\glstrgenentrytextfmt{#3}}%
    }%
  }%
}

```

\@Glsuseri@ First letter uppercase version.

```

\def\@Glsuseri@#1#2[#3]{%
  \def\glstrcurrentfield{user1}%
  \glstrassignfieldfont{#2}%
  \glstrsaveinsert{#2}{#3}%
  \@gls@field@link
  [\let\glscapscase\@secondofthree]{#1}{#2}%
  {%
    \glsifapplyinnerfmtfield{#2}{useri}%
  }

```

```

    {%
      \gls@field@font{\Glsaccessfmtuseri{#3}{\glsxtrgenentrytextfmt}{#2}}%
    }%
    {%
      \gls@field@font{\Glsaccessuseri{#2}\glsxtrgenentrytextfmt{#3}}%
    }%
  }%
}

```

\@GLSuseri@ All uppercase version.

```

\def\@GLSuseri@#1#2[#3]{%
  \def\glsxtrcurrentfield{user1}%
  \glsxtrassignfieldfont{#2}%
  \glsxtrsaveinsert{#2}{#3}%
  \@gls@field@link[\let\glscapscase\@thirdofthree]%
  {#1}{#2}%
  {%
    \glsifapplyinnerfmtfield{#2}{useri}%
    {%
      \gls@field@font{\Glsaccessfmtuseri{#3}{\glsxtrgenentrytextfmt}{#2}}%
    }%
    {%
      \ifx\glscapscase\@thirdofthree
        \gls@field@font{\Glsaccessuseri{#2}}%
        \glssupercase{\glsxtrgenentrytextfmt{#3}}}%
      \else
        \gls@field@font{\glsaccessuseri{#2}\glsxtrgenentrytextfmt{#3}}%
      \fi
    }%
  }%
}

```

\@glsuserii@ User 2 field.

```

\def\@glsuserii@#1#2[#3]{%
  \def\glsxtrcurrentfield{user2}%
  \glsxtrassignfieldfont{#2}%
  \glsxtrsaveinsert{#2}{#3}%
  \@gls@field@link
  {#1}{#2}%
  {%
    \glsifapplyinnerfmtfield{#2}{userii}%
    {%
      \gls@field@font{\glsaccessfmtuserii{#3}{\glsxtrgenentrytextfmt}{#2}}%
    }%
    {%
      \gls@field@font{\glsaccessuserii{#2}\glsxtrgenentrytextfmt{#3}}%
    }%
  }%
}

```

\@Glsuserii@ First letter uppcase version.

```

\def\@Glsuserii@#1#2[#3]{%
  \def\glstrcurrentfield{user2}%
  \glstrassignfieldfont{#2}%
  \glstrsaveinsert{#2}{#3}%
  \@gls@field@link
  [\let\glscapscase\@secondofthree]%
  {#1}{#2}%
  {%
    \gl@ifapplyinnerfmtfield{#2}{userii}%
    {%
      \@gls@field@font{\Glsaccessfmtuserii{#3}{\glstrgenentrytextfmt}{#2}}%
    }%
    {%
      \@gls@field@font{\Glsaccessuserii{#2}\glstrgenentrytextfmt{#3}}%
    }%
  }%
}
```

\@GLSuserii@ All uppcase version.

```

\def\@GLSuserii@#1#2[#3]{%
  \def\glstrcurrentfield{user2}%
  \glstrassignfieldfont{#2}%
  \glstrsaveinsert{#2}{#3}%
  \@gls@field@link[\let\glscapscase\@thirdofthree]%
  {#1}{#2}%
  {%
    \gl@ifapplyinnerfmtfield{#2}{userii}%
    {%
      \@gls@field@font{\GLSaccessfmtuserii{#3}{\glstrgenentrytextfmt}{#2}}%
    }%
    {%
      \ifx\glscapscase\@thirdofthree
        \@gls@field@font{\GLSaccessuserii{#2}%
          \glssupercase{\glstrgenentrytextfmt{#3}}}%
      \else
        \@gls@field@font{\glssaccessuserii{#2}\glstrgenentrytextfmt{#3}}%
      \fi
    }%
  }%
}
```

\@glsuseriii@ User 3 field.

```

\def\@glsuseriii@#1#2[#3]{%
  \def\glstrcurrentfield{user3}%
  \glstrassignfieldfont{#2}%
  \glstrsaveinsert{#2}{#3}%
  \@gls@field@link
  {#1}{#2}%
}
```

```

    {%
      \glsifapplyinnerfmtfield{#2}{useriii}%
      {%
        \@gls@field@font{\glsaccessfmtuseriii{#3}{\glsxtrgenentrytextfmt}{#2}}%
      }%
      {%
        \@gls@field@font{\glsaccessuseriii{#2}\glsxtrgenentrytextfmt{#3}}%
      }%
    }%
  }

\@Glsuseriii@ First letter uppercase version.
\def\@Glsuseriii@#1#2[#3]{%
  \def\glsxtrcurrentfield{user3}%
  \glsxtrassignfieldfont{#2}%
  \glsxtrsaveinsert{#2}{#3}%
  \@gls@field@link
  [\let\glsupercase\@secondofthree]%
  {#1}{#2}%
  {%
    \glsifapplyinnerfmtfield{#2}{useriii}%
    {%
      \@gls@field@font{\Glsaccessfmtuseriii{#3}{\glsxtrgenentrytextfmt}{#2}}%
    }%
    {%
      \@gls@field@font{\Glsaccessuseriii{#2}\glsxtrgenentrytextfmt{#3}}%
    }%
  }%
}

\@GLSuseriii@ All uppercase version.
\def\@GLSuseriii@#1#2[#3]{%
  \def\glsxtrcurrentfield{user3}%
  \glsxtrassignfieldfont{#2}%
  \glsxtrsaveinsert{#2}{#3}%
  \@gls@field@link[\let\glsupercase\@thirdofthree]%
  {#1}{#2}%
  {%
    \glsifapplyinnerfmtfield{#2}{useriii}%
    {%
      \@gls@field@font{\GLSaccessfmtuseriii{#3}{\glsxtrgenentrytextfmt}{#2}}%
    }%
    {%
      \ifx\glsupercase\@thirdofthree
        \@gls@field@font{\GLSaccessuseriii{#2}%
          \glsupercase{\glsxtrgenentrytextfmt{#3}}}%
      \else
        \@gls@field@font{\glsaccessuseriii{#2}\glsxtrgenentrytextfmt{#3}}%
      \fi
    }%
  }%
}

```

```

    }%
  }

\@glsuseriv@ User 4 field.
\def\@glsuseriv@#1#2[#3]{%
  \def\glsxtrcurrentfield{user4}%
  \glsxtrassignfieldfont{#2}%
  \glsxtrsaveinsert{#2}{#3}%
  \@gls@field@link
  {#1}{#2}%
  {%
    \glsifapplyinnerfmtfield{#2}{useriv}%
    {%
      \@gls@field@font{\glsaccessfmtuseriv{#3}{\glsxtrgenentrytextfmt}{#2}}%
    }%
    {%
      \@gls@field@font{\glsaccessuseriv{#2}\glsxtrgenentrytextfmt{#3}}%
    }%
  }%
}

\@Glsuseriv@ First letter uppercase version.
\def\@Glsuseriv@#1#2[#3]{%
  \def\glsxtrcurrentfield{user4}%
  \glsxtrassignfieldfont{#2}%
  \glsxtrsaveinsert{#2}{#3}%
  \@gls@field@link
  [\let\glsupcase\@secondofthree]%
  {#1}{#2}%
  {%
    \glsifapplyinnerfmtfield{#2}{useriv}%
    {%
      \@gls@field@font{\Glsaccessfmtuseriv{#3}{\glsxtrgenentrytextfmt}{#2}}%
    }%
    {%
      \@gls@field@font{\Glsaccessuseriv{#2}{#3}}%
    }%
  }%
}

\@GLSuseriv@ All uppercase version.
\def\@GLSuseriv@#1#2[#3]{%
  \def\glsxtrcurrentfield{user4}%
  \glsxtrassignfieldfont{#2}%
  \glsxtrsaveinsert{#2}{#3}%
  \@gls@field@link[\let\glsupcase\@thirdofthree]%
  {#1}{#2}%
  {%
    \glsifapplyinnerfmtfield{#2}{useriv}%

```



```

    {%
      \@gls@field@font{\GLSaccessfmtuseriv{#3}{\glstrgenentrytextfmt}{#2}}%
    }%
    {%
      \ifx\glscapscase\@thirdofthree
        \@gls@field@font{\GLSaccessuseriv{#2}%
          \glssupercase{\glstrgenentrytextfmt{#3}}}%
      \else
        \@gls@field@font{\glsaccessuseriv{#2}\glstrgenentrytextfmt{#3}}%
      \fi
    }%
  }%
}

\@glsuserv@ User 5 field.
\def\@glsuserv@#1#2[#3]{%
  \def\glstrcurrentfield{user5}%
  \glstrassignfieldfont{#2}%
  \glstrsaveinsert{#2}{#3}%
  \@gls@field@link
  {#1}{#2}%
  {%
    \glsifapplyinnerfmtfield{#2}{userv}%
    {%
      \@gls@field@font{\glsaccessfmtuserv{#3}{\glstrgenentrytextfmt}{#2}}%
    }%
    {%
      \@gls@field@font{\glsaccessuserv{#2}\glstrgenentrytextfmt{#3}}%
    }%
  }%
}

\@Glsuserv@ First letter uppercase version.
\def\@Glsuserv@#1#2[#3]{%
  \def\glstrcurrentfield{user5}%
  \glstrassignfieldfont{#2}%
  \glstrsaveinsert{#2}{#3}%
  \@gls@field@link
  [\let\glscapscase\@secondofthree]%
  {#1}{#2}%
  {%
    \glsifapplyinnerfmtfield{#2}{userv}%
    {%
      \@gls@field@font{\Glsfmtfield{#3}{\glstrgenentrytextfmt}{#2}{userv}}%
    }%
    {%
      \@gls@field@font{\Glsentryuserv{#2}\glstrgenentrytextfmt{#3}}%
    }%
  }%
}

```

\@GLSuserv@ All uppercase version.

```

\def\@GLSuserv@#1#2[#3]{%
  \def\glstrcurrentfield{user5}%
  \glstrassignfieldfont{#2}%
  \glstrsaveinsert{#2}{#3}%
  \@gls@field@link[\let\glscapscase\@thirdofthree]%
  {#1}{#2}%
  {%
    \glrifapplyinnerfmtfield{#2}{userv}%
    {%
      \@gls@field@font{\GLSaccessfmtuserv{#3}\glstrgenentrytextfmt}{#2}}%
    }%
    {%
      \ifx\glscapscase\@thirdofthree
        \@gls@field@font{\GLSaccessuserv{#2}%
          \glssupercase{\glstrgenentrytextfmt{#3}}}%
      \else
        \@gls@field@font{\glssaccessuserv{#2}\glstrgenentrytextfmt{#3}}%
      \fi
    }%
  }%
}

```

\@glsuservi@ User 6 field.

```

\def\@glsuservi@#1#2[#3]{%
  \def\glstrcurrentfield{user6}%
  \glstrassignfieldfont{#2}%
  \glstrsaveinsert{#2}{#3}%
  \@gls@field@link
  {#1}{#2}%
  {%
    \glrifapplyinnerfmtfield{#2}{uservi}%
    {%
      \@gls@field@font{\glssaccessfmtuservi{#3}\glstrgenentrytextfmt}{#2}}%
    }%
    {%
      \@gls@field@font{\glssaccessuservi{#2}\glstrgenentrytextfmt{#3}}%
    }%
  }%
}

```

\@Glsuservi@ First letter uppercase version.

```

\def\@Glsuservi@#1#2[#3]{%
  \def\glstrcurrentfield{user6}%
  \glstrassignfieldfont{#2}%
  \glstrsaveinsert{#2}{#3}%
  \@gls@field@link
  [\let\glscapscase\@secondofthree]%
  {#1}{#2}%
}

```

```

{%
  \glsifapplyinnerfmtfield{#2}{uservi}%
  {%
    \@gls@field@font{\Glsaccessfmtuservi{#3}{\glsxtrgenentrytextfmt}{#2}}%
  }%
  {%
    \@gls@field@font{\Glsaccessuservi{#2}\glsxtrgenentrytextfmt{#3}}%
  }%
}%
}

```

\@GLSuservi@ All uppercase version.

```

\def\@GLSuservi@#1#2[#3]{%
  \def\glsxtrcurrentfield{user6}%
  \glsxtrassignfieldfont{#2}%
  \glsxtrsaveinsert{#2}{#3}%
  \@gls@field@link[\let\glscapscase\@thirdofthree]%
  {#1}{#2}%
  {%
    \glsifapplyinnerfmtfield{#2}{uservi}%
    {%
      \@gls@field@font{\Glsaccessfmtuservi{#3}{\glsxtrgenentrytextfmt}{#2}}%
    }%
    {%
      \ifx\glscapscase\@thirdofthree
        \@gls@field@font{\Glsaccessuservi{#2}%
          \glsuppercase{\glsxtrgenentrytextfmt{#3}}}%
      \else
        \@gls@field@font{\glsaccessuservi{#2}\glsxtrgenentrytextfmt{#3}}%
      \fi
    }%
  }%
}

```

Commands like `\acrshort` already set `\glsifplural`, but they don't set `\glsxtrifwasfirstuse` so they need adjusting. These commands shouldn't be used with `\newabbreviation`, but the redefinitions below allow for users reverting `\newacronym` back to its base definition.

\@@glsxtr@base@acrcmd@warn Warn user that they need to use to new abbreviation commands.

```

\newcommand*{\@@glsxtr@base@acrcmd@warn}[2]{%
  \GlossariesExtraWarning{Base acronym command \string#1\space
    should not be used with new abbreviation definitions. Use
    \string#2\space instead}%
}

```

\@glsxtr@base@acrcmd Warn user that they need to use to new abbreviation commands.

```

\let\@glsxtr@base@acrcmd\@@glsxtr@base@acrcmd@warn

```

The following `acr` commands don't support `innertextformat`.

\@acrshort No case change.

```
\def\@acrshort#1#2[#3]{%
  \def\glxtrcurrentfield{short}%
  \@glxtr@base@acrcmd\acrshort\glxtrshort
  \glsdoifexists{#2}%
  {%
    \let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
    \let\glxtrifwasglslike\@secondoftwo
    \let\glxtrifwasfirstuse\@secondoftwo
    \let\glsifplural\@secondoftwo
    \let\glscapscase\@firstofthree
    \let\glsinsert\@empty
    \def\glscustomtext{%
      \acronymfont{\glsaccessshort{#2}}#3%
    }%
    \@gl@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
  }%
  \glspostlinkhook
}
```

\@Acrshort First letter uppercase.

```
\def\@Acrshort#1#2[#3]{%
  \def\glxtrcurrentfield{short}%
  \@glxtr@base@acrcmd\Acrshort\Glsxtrshort
  \glsdoifexists{#2}%
  {%
    \let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
    \let\glxtrifwasglslike\@secondoftwo
    \let\glxtrifwasfirstuse\@secondoftwo
    \let\glsifplural\@secondoftwo
    \let\glscapscase\@secondofthree
    \let\glsinsert\@empty
    \def\glscustomtext{%
      \acronymfont{\Glsaccessshort{#2}}#3%
    }%
    \@gl@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
  }%
  \glspostlinkhook
}
```

\@ACRshort All uppercase.

```
\def\@ACRshort#1#2[#3]{%
  \def\glxtrcurrentfield{short}%
  \@glxtr@base@acrcmd\ACRshort\GLSxtrshort
  \glsdoifexists{#2}%
  {%
    \let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
    \let\glxtrifwasglslike\@secondoftwo
    \let\glxtrifwasfirstuse\@secondoftwo
  }
```

```

\let\glsifplural\@secondoftwo
\let\glscapscase\@thirdofthree
\let\glsinsert\@empty
\def\glscustomtext{%
  \glsuppercase{\acronymfont{\glsaccessshort{#2}}#3}%
}%
\@gls@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
}%
\glspostlinkhook
}

\@acrshortpl No case change.
\def\@acrshortpl#1#2[#3]{%
  \def\glstrcurrentfield{short}%
  \@glstr@base@acrcmd\acrshortpl\glstrshortpl
  \glsdoifexists{#2}%
  {%
    \let\do@gls@link@checkfirsthyper\@gls@link@nocheckfirsthyper
    \let\glstrifwasglslike\@secondoftwo
    \let\glstrifwasfirstuse\@secondoftwo
    \let\glsifplural\@firstoftwo
    \let\glscapscase\@firstofthree
    \let\glsinsert\@empty
    \def\glscustomtext{%
      \acronymfont{\glsaccessshortpl{#2}}#3%
    }%
    \@gls@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
  }%
  \glspostlinkhook
}

\@Acrshortpl First letter uppercase.
\def\@Acrshortpl#1#2[#3]{%
  \def\glstrcurrentfield{short}%
  \@glstr@base@acrcmd\Acrshortpl\Glsxtrshortpl
  \glsdoifexists{#2}%
  {%
    \let\do@gls@link@checkfirsthyper\@gls@link@nocheckfirsthyper
    \let\glstrifwasglslike\@secondoftwo
    \let\glstrifwasfirstuse\@secondoftwo
    \let\glsifplural\@firstoftwo
    \let\glscapscase\@secondofthree
    \let\glsinsert\@empty
    \def\glscustomtext{%
      \acronymfont{\Glsaccessshortpl{#2}}#3%
    }%
    \@gls@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
  }%
  \glspostlinkhook
}

```

\@ACRshortpl All uppercase.

```
\def\@ACRshortpl#1#2[#3]{%
\def\glstrcurrentfield{short}%
\@glstr@base@acrcmd\ACRshortpl\GLSxtrshortpl
\glsdoifexists{#2}%
{%
\let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
\let\glstrifwasglslike\@secondoftwo
\let\glstrifwasfirstuse\@secondoftwo
\let\glsifplural\@firstoftwo
\let\glscapscase\@thirdofthree
\let\glsinsert\@empty
\def\glscustomtext{%
\glsuppercase{\acronymfont{\glsaccessshortpl{#2}}#3}%
}%
\@gl@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
}%
\glspostlinkhook
}
```

\@acrlong No case change.

```
\def\@acrlong#1#2[#3]{%
\def\glstrcurrentfield{long}%
\@glstr@base@acrcmd\acrlong\glxtrlong
\glsdoifexists{#2}%
{%
\let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
\let\glstrifwasglslike\@secondoftwo
\let\glstrifwasfirstuse\@secondoftwo
\let\glsifplural\@secondoftwo
\let\glscapscase\@firstofthree
\let\glsinsert\@empty
\def\glscustomtext{%
\acronymfont{\glsaccesslong{#2}}#3%
}%
\@gl@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
}%
\glspostlinkhook
}
```

\@Acrlong First letter uppercase.

```
\def\@Acrlong#1#2[#3]{%
\def\glstrcurrentfield{long}%
\@glstr@base@acrcmd\Acrlong\Glsxtrlong
\glsdoifexists{#2}%
{%
\let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
\let\glstrifwasglslike\@secondoftwo
\let\glstrifwasfirstuse\@secondoftwo
}
```

```

\let\glsifplural\@secondoftwo
\let\glscapscase\@secondofthree
\let\glsinsert\@empty
\def\glscustomtext{%
  \acronymfont{\Glsaccesslong{#2}}#3%
}%
\@gls@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
}%
\glspostlinkhook
}

\@ACRlong All uppercase.
\def\@ACRlong#1#2[#3]{%
  \def\glstrcurrentfield{long}%
  \@glsxtr@base@acrcmd\ACRlong\GLSxtrlong
  \glsdoifexists{#2}%
  {%
    \let\do@gls@link@checkfirsthyper\@gls@link@nocheckfirsthyper
    \let\glstrifwasglslike\@secondoftwo
    \let\glstrifwasfirstuse\@secondoftwo
    \let\glsifplural\@secondoftwo
    \let\glscapscase\@thirdofthree
    \let\glsinsert\@empty
    \def\glscustomtext{%
      \glsuppercase{\acronymfont{\Glsaccesslong{#2}}#3}%
    }%
    \@gls@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
  }%
  \glspostlinkhook
}

\@acrlongpl No case change.
\def\@acrlongpl#1#2[#3]{%
  \def\glstrcurrentfield{long}%
  \@glsxtr@base@acrcmd\acrlongpl\glxtrlongpl
  \glsdoifexists{#2}%
  {%
    \let\do@gls@link@checkfirsthyper\@gls@link@nocheckfirsthyper
    \let\glstrifwasglslike\@secondoftwo
    \let\glstrifwasfirstuse\@secondoftwo
    \let\glsifplural\@firstoftwo
    \let\glscapscase\@firstofthree
    \let\glsinsert\@empty
    \def\glscustomtext{%
      \acronymfont{\Glsaccesslongpl{#2}}#3%
    }%
    \@gls@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
  }%
  \glspostlinkhook
}

```

\@Acrlongpl First letter uppercase.

```
\def\@Acrlongpl#1#2[#3]{%
  \def\glstrcurrentfield{long}%
  \@glstr@base@acrcmd\Acrlongpl\Glsxtrlongpl
  \glsdoifexists{#2}%
  {%
    \let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
    \let\glstrifwasglslike\@secondoftwo
    \let\glstrifwasfirstuse\@secondoftwo
    \let\glsifplural\@firstoftwo
    \let\glscapscase\@secondofthree
    \let\glsinsert\@empty
    \def\glscustomtext{%
      \acronymfont{\Glsaccesslongpl{#2}}#3}%
    }%
    \@gl@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
  }%
  \glspostlinkhook
}
```

\@ACRlongpl All uppercase.

```
\def\@ACRlongpl#1#2[#3]{%
  \def\glstrcurrentfield{long}%
  \@glstr@base@acrcmd\ACRlongpl\GLSxtrlongpl
  \glsdoifexists{#2}%
  {%
    \let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
    \let\glstrifwasglslike\@secondoftwo
    \let\glstrifwasfirstuse\@secondoftwo
    \let\glsifplural\@firstoftwo
    \let\glscapscase\@thirdofthree
    \let\glsinsert\@empty
    \def\glscustomtext{%
      \glssupercase{\acronymfont{\Glsaccesslongpl{#2}}#3}%
    }%
    \@gl@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
  }%
  \glspostlinkhook
}
```

The full formats use the internal long and short commands (such as \@acrshort and \@acrlong). Therefore they don't need adjustments, but they do need clearer warnings. This means three warnings per use (once for the full command and once each for the short and long commands), but at least this way the most important warning (replace \acrfull with \glstrfull etc) is present.

\@acrfull

```
\def\@acrfull#1#2[#3]{%
```



```

\def\glstrcurrentfield{%
\glstr@base@acrcmd\acrfull\glstrfull
\acrfullfmt{#1}{#2}{#3}%
}

\@Acrfull
\def\@Acrfull#1#2[#3]{%
\def\glstrcurrentfield{%
\glstr@base@acrcmd\Acrfull\Glsxtrfull
\Acrfullfmt{#1}{#2}{#3}%
}

\@ACRfull
\def\@ACRfull#1#2[#3]{%
\def\glstrcurrentfield{%
\glstr@base@acrcmd\ACRfull\GLSxtrfull
\ACRfullfmt{#1}{#2}{#3}%
}

\@acrfullpl
\def\@acrfullpl#1#2[#3]{%
\def\glstrcurrentfield{%
\glstr@base@acrcmd\acrfullpl\glstrfullpl
\acrfullplfmt{#1}{#2}{#3}%
}

\@Acrfullpl
\def\@Acrfullpl#1#2[#3]{%
\def\glstrcurrentfield{%
\glstr@base@acrcmd\Acrfullpl\Glsxtrfullpl
\Acrfullplfmt{#1}{#2}{#3}%
}

\@ACRfullpl
\def\@ACRfullpl#1#2[#3]{%
\def\glstrcurrentfield{%
\glstr@base@acrcmd\ACRfullpl\GLSxtrfullpl
\ACRfullplfmt{#1}{#2}{#3}%
}

```

Modify \@glsaddkey so additional keys provided by the user can be treated in a similar way.

```

\@glsaddkey
\renewcommand*{\@glsaddkey}[7]{%
\key@ifundefined{glossentry}{#1}%
{%
\define@key{glossentry}{#1}{\csdef{@glo@#1}{##1}}%
\appto\@gls@keymap{,{#1}{#1}}%
}

```

```

\appto\@newglossaryentryprehook{\csdef{@glo@#1}{#2}}%
\appto\@newglossaryentryposthook{%
  \letcs{@glo@tmp}{@glo@#1}%
  \gls@assign@field{#2}{\@glo@label}{#1}{\@glo@tmp}%
}%
\newcommand*{#3}[1]{\@gls@entry@field{##1}{#1}}%
\newcommand*{#4}[1]{\@Gls@entry@field{##1}{#1}}%

```

Now for the commands with links. These currently don't support the inner text format. First the version with no case change:

```

\ifcsdef{@gls@user@#1@}%
{%
  \PackageError{glossaries}%
  {Can't define '\string#5' as helper command
   '\expandafter\string\csname @gls@user@#1\endcsname' already
   exists}%
  {}%
}%
{%
  \expandafter\newcommand\expandafter*\expandafter
  {\csname @gls@user@#1\endcsname}[2][\{%
    \new@ifnextchar[%
      {\csuse{@gls@user@#1@}{##1}{##2}}%
      {\csuse{@gls@user@#1@}{##1}{##2}[]}%
    \csdef{@gls@user@#1@}##1##2[##3]{%
      \def\glsxtrcurrentfield{#1}%
      \glsxtrassignfieldfont{##2}%
      \glsxtrsaveinsert{##2}{##3}%
      \@gls@field@link{##1}{##2}{\@gls@field@font{#3{##2}##3}}%
    }%
    \newrobustcmd*{#5}{%
      \expandafter\@gls@hyp@opt\csname @gls@user@#1\endcsname}%
    }%
  }%

```

Next the version with the first letter converted to upper case (modified):

```

\ifcsdef{@Gls@user@#1@}%
{%
  \PackageError{glossaries}%
  {Can't define '\string#6' as helper command
   '\expandafter\string\csname @Gls@user@#1\endcsname' already
   exists}%
  {}%
}%
{%
  \expandafter\newcommand\expandafter*\expandafter
  {\csname @Gls@user@#1\endcsname}[2][\{%
    \new@ifnextchar[%
      {\csuse{@Gls@user@#1@}{##1}{##2}}%
      {\csuse{@Gls@user@#1@}{##1}{##2}[]}%
    \csdef{@Gls@user@#1@}##1##2[##3]{%
      \def\glsxtrcurrentfield{#1}%

```

```

\glstrassignfieldfont{##2}%
\glstrsaveinsert{##2}{##3}%
\@gls@field@link[\let\glscapscase\@secondofthree]%
{##1}{##2}{\@gls@field@font{#4{##2}##3}}%
}%
\newrobustcmd*{#6}{%
\expandafter\@gls@hyp@opt\csname @Gls@user@#1\endcsname}%
}%

```

Finally the all caps version (modified):

```

\ifcsdef{@GLS@user@#1@}%
{%
\PackageError{glossaries}%
{Can't define '\string#7' as helper command
'\expandafter\string\csname @GLS@user@#1\endcsname' already
exists}%
}%
}%
{%
\expandafter\newcommand\expandafter*\expandafter
{\csname @GLS@user@#1\endcsname}[2][]{%
\new@ifnextchar[%
{\csuse{@GLS@user@#1@}{##1}{##2}}%
{\csuse{@GLS@user@#1@}{##1}{##2}[]}%
\csdef{@GLS@user@#1@}##1##2[##3]{%
\def\glstrcurrentfield{#1}%
\glstrassignfieldfont{##2}%
\glstrsaveinsert{##2}{##3}%
\@gls@field@link[\let\glscapscase\@thirdofthree]%
{##1}{##2}{\@gls@field@font{\glssupercase{#3{##2}##3}}}%
}%
\newrobustcmd*{#7}{%
\expandafter\@gls@hyp@opt\csname @GLS@user@#1\endcsname}%
}%

```

Add mappings.

```

\glsmfuaddmap{#3}{#4}%
\glsmfuaddmap{#5}{#6}%
\glsmfublocker{#7}%
}%
{%
\PackageError{glossaries-extra}{Key '#1' already exists}{}%
}%
}

```

`\@gls@link@nocheckfirsthyper` Old versions of glossaries don't define this, so provide it just in case it hasn't been defined.

```
\providecommand*{\@gls@link@nocheckfirsthyper}{}
```

`\@gls@link@postkeys@checkfirsthyper` Need another check after preunset and postunset options have been applied.

```
\newcommand*{\@gls@link@postkeys@checkfirsthyper}{}
```

`\@gls@link@checkfirsthyper` Modify check to determine if the hyperlink should be automatically suppressed, but save the original in case the acronyms are restored.

```
\let\@glsxtr@org@checkfirsthyper\@gls@link@checkfirsthyper
\renewcommand*{\@gls@link@checkfirsthyper}{%
```

`\ifglsused` isn't useful in the post link hook as it's already been unset by then, so define a command that can be used in the post link hook. Since `\@gls@link@checkfirsthyper` is only used by commands like `\gls` but not by other commands, this seems the best place to put it to automatically set the value for the commands that change the first use flag. The other commands should set `\glsxtrifwasfirstuse` to `\@secondoftwo` (which is done in `\@glsxtr@field@linkdefs`). Note that if the entry is undefined (as with `bib2gls` on the first \LaTeX run), `\ifglsused` does neither true nor false parts. However, in that case, this macro won't be called anyway (since it's used in the argument of `\glsdoifexistsordo`).

```
\ifglsused{\glslabel}%
{\let\glsxtrifwasfirstuse\@secondoftwo}
{\let\glsxtrifwasfirstuse\@firstoftwo}%
```

Similarly for `\glsxtrifwasglslike`

```
\let\glsxtrifwasglslike\@firstoftwo
```

Store the category label for convenience.

```
\protected@edef\glscategorylabel{\glscategory{\glslabel}}%
\glsxtrifwasfirstuse
{%
\glsifcategoryattribute{\glscategorylabel}{nohyperfirst}{true}%
{\KV@glslink@hyperfalse}{}%
}%
{%
\glsifcategoryattribute{\glscategorylabel}{nohypernext}{true}%
{\KV@glslink@hyperfalse}{}%
}%
\glslinkcheckfirsthyperhook
}
```

`\do@gl:disablehyperinlist` This command was introduced in glossaries v4.19. If it hasn't been defined, we're using an earlier version, in which case the `nohyper` attribute can't be implemented.

```
\ifdef\do@gl:disablehyperinlist
{%
\let\@glsxtr@do@gl:disablehyperinlist\do@gl:disablehyperinlist
\renewcommand*{\do@gl:disablehyperinlist}{%
\@glsxtr@do@gl:disablehyperinlist
\glsifattribute{\glslabel}{nohyper}{true}{\KV@glslink@hyperfalse}{}%
}
}
{}
```

```

        Define a noindex key to prevent writing information to the external file.
        \define@boolkey{glslink}{noindex}[true]{}
        \KV@glslink@noindexfalse

\@gls@save@glslocal Defined in glossaries v4.50 so may not be defined.
    \providecommand*{\@gls@save@glslocal}{%
        \let\if@org@KV@glslink@local\ifKV@glslink@local
    }

\@gls@restore@glslocal Defined in glossaries v4.50 so may not be defined.
    \providecommand*{\@gls@restore@glslocal}{%
        \ifKV@glslink@local
            \let\@gls@do@glsunset@glslocalunset
        \else
            \let\@gls@do@glsunset@glsunset
        \fi
        \let\ifKV@glslink@local\if@org@KV@glslink@local
    }

\@gls@default@restore@glslocal Save default definition of \@gls@restore@glslocal
    \let\@gls@default@restore@glslocal\@gls@restore@glslocal

\@gls@ignore@restore@glslocal
    \newcommand*{\@gls@ignore@restore@glslocal}{%
        \let\@gls@do@glsunset@gobble
        \let\ifKV@glslink@local\if@org@KV@glslink@local
    }

\@gls@do@glsunset Defined in glossaries v4.50 so may not be defined.
    \providecommand*{\@gls@do@glsunset}[1]{\@glsunset{#1}}

\@gls@default@glslink@opts The noindex setting needs to be initialised, so it's now always set to false first
                           before applying the default options. Otherwise, if noindex is explicitly set in a
                           command like \gls then it won't get reset if the default option list doesn't set
                           it.
    \newcommand*{\@gls@default@glslink@opts}{}

    If \@gls@setdefault@glslink@opts has been defined (glossaries v4.20) use
    it to set the default keys in \@glslink.

\@gls@setdefault@glslink@opts
    \ifdef\@gls@setdefault@glslink@opts
    {
        \renewcommand*{\@gls@setdefault@glslink@opts}{%
            \KV@glslink@noindexfalse
            \expandafter\setupglslink\expandafter{\@gls@default@glslink@opts}%
            \@glsxtrsetaliasnoindex
        }
    }
    {

```

Not defined so prepend it to `\do@glsglslDisableHyperinlist` to achieve the same effect.

```
\newcommand*{\@gls@setdefault@glslink@opts}{%
  \KV@glslink@noindexfalse
  \expandafter\setupglslink\expandafter{\@gls@default@glslink@opts}%
  \@glstrsetaliasnoindex
}
\preto\do@glsglslDisableHyperinlist{\@gls@setdefault@glslink@opts}
}
```

`\glstrsetaliasnoindex` Allow user to hook into the alias noindex setting. Default behaviour switches off indexing for aliases. If the record option is on, this will have been defined to do nothing. (bib2gls will deal with records for aliased entries.)

```
\providecommand*{\glstrsetaliasnoindex}{%
  \KV@glslink@noindextrue
}
```

`\@glstrsetaliasnoindex` The change made in v1.46 to remove the grouping has had the knock-on effect of redefining `\glscurrentfieldvalue`, which may be a problem, so v1.47 has changed this to use `\ifcvoid`.

```
\newcommand*{\@glstrsetaliasnoindex}{%
  \ifcvoid{glo@glsglslDetoklabel{\glslabel}@alias}%
  {}%
  {%
    \let\glstrindexaliased\glstrindexaliased
    \glstrsetaliasnoindex
    \let\glstrindexaliased\@no@glstrindexaliased
  }%
}
```

`\@glstrindexaliased`

```
\newcommand{\@glstrindexaliased}{%
  \ifKV@glslink@noindex
  \else
    \begingroup
    \let\@glsnumberformat\@glstr@defaultnumberformat

    \protected@edef\@gls@counter{\csname glo@glsglslDetoklabel{\glslabel}@counter\endcsname}%
    \glstr@saveentrycounter
    \glstr@wrglossary@encap{\glstralias{\glslabel}}{\@do@wrglossary{\glstralias{\glslabel}}}%
    \endgroup
  \fi
}
```

`\@no@glstrindexaliased`

```
\newcommand{\@no@glstrindexaliased}{%
  \PackageError{glossaries-extra}{\string\glstrindexaliased\space
    not permitted outside definition of \string\glstrsetaliasnoindex}%
  {}%
}
```

`\glxtrindexaliased` Provide a command to redirect alias indexing, but only allow it to be used within `\glxtrsetaliasnoindex`.

```
\let\glxtrindexaliased\@no@glxtrindexaliased
```

`\GlsXtrSetDefaultGlsOpts` Set the default options for `\glslink` etc.

```
\newcommand*{\GlsXtrSetDefaultGlsOpts}[1]{%
  \renewcommand*{\@gls@default@glslink@opts}{#1}%
}
```

`\GlsXtrAppToDefaultGlsOpts`

```
\newcommand*{\GlsXtrAppToDefaultGlsOpts}[1]{%
  \appto\@gls@default@glslink@opts{,#1}%
}
```

`\GlsXtrPreToDefaultGlsOpts`

```
\newcommand*{\GlsXtrPreToDefaultGlsOpts}[1]{%
  \preto\@gls@default@glslink@opts{#1,}%
}
```

`\glxtrifindexing` Provide user level command to access it in `\glswriteentry`.

```
\newcommand*{\glxtrifindexing}[2]{%
  \ifKV@glslink@noindex #2\else #1\fi
}
```

```
\glxtr@wrglossary@encap{\label}{\whatsit}
```

`\glxtr@wrglossary@encap`

Encapsulate indexing `whatsit` and increment indexed count. See also `\glxtrdowrglossaryhook`

```
\newcommand*{\glxtr@wrglossary@encap}[2]{\glsencapwrcontent{#2\@glxtr@inc@indexcount{#1}}}
```

Keep track of how many times an entry has been indexed. This doesn't test if the entry has been defined to allow for the first L^AT_EX run before calling `bib2gls`.

`\@glxtr@inc@indexcount`

```
\newcommand*{\@glxtr@inc@indexcount}[1]{%
  \ifcsdef{glo@\glsdetoklabel{#1}@indexed}%
  {%
    \csxdef{glo@\glsdetoklabel{#1}@indexed}{%
      \expandafter\number\expandafter\numexpr\csname glo@\glsdetoklabel{#1}@indexed\endcsname+1}%
    }%
  }%
  \csgdef{glo@\glsdetoklabel{#1}@indexed}{1}%
}
```

```

\glsentryindexcount
\newcommand*\glsentryindexcount[1]{%
  \ifcsdef{glo@\glsdetoklabel{#1}@indexed}%
  {\csuse{glo@\glsdetoklabel{#1}@indexed}}%
  {0}%
}

\glsifindexed
\newcommand*\glsifindexed[3]{%
  \ifcsdef{glo@\glsdetoklabel{#1}@indexed}%
  {\expandafter\ifnum\csname glo@\glsdetoklabel{#1}@indexed\endcsname>0 #2\else#3\fi}%
  {#3}%
}

\glsaddallunindexed
\newcommand*\glsaddallunindexed[1][\@glo@types]{%
  \forallglsentries[1]{\@glo@entry}%
  {%
    \glsifindexed{\@glo@entry}{\glsadd[format=glsignore]{\@glo@entry}}%
  }%
}

\glsencapwrcontent This command was added to glossaries v4.50 so may not be defined.
\providecommand*\glsencapwrcontent[1]{#1}

\glswriteentry Redefine to test for indexonlyfirst category attribute. This needs to use
\GlsXtrIfUnusedOrUndefined instead of \ifglsused to allow it to work with
bib2gls.
\renewcommand*\glswriteentry[2]{%
  \glsxtrifindexing
  {%
    \ifglsindexonlyfirst
      \GlsXtrIfUnusedOrUndefined{#1}
      {#2}%
      {\glsxtrdoautoindexname{#1}{dualindex}}%
    \else
      \glsifattribute{#1}{indexonlyfirst}{true}%
      {%
        \GlsXtrIfUnusedOrUndefined{#1}%
        {#2}%
        {\glsxtrdoautoindexname{#1}{dualindex}}%
      }%
      {#2}%
    \fi
  }%
  {}%
}

```


`\@@do@@wrglossary` Hook into glossary indexing command so that it can also use `\index` at the same time if required and add user hook.

```
\appto\@@do@@wrglossary{\@glstr@do@@wrindex
\glstrdowrglossaryhook{\@gls@label}%
}
```

(The label can be obtained from `\@gls@label` at this point.)

Similarly for the “noidx” version:

`\gls@noidxglossary`

```
\appto\gls@noidxglossary{\@glstr@do@@wrindex
\glstrdowrglossaryhook{\@gls@label}%
}
```

`\@glstr@do@@wrindex`

```
\newcommand*{\@glstr@do@@wrindex}{%
\glstrdoautoindexname{\@gls@label}{dualindex}%
}
```

`\glstrdowrglossaryhook` Allow user to hook into indexing code. (Always used by `\glsadd`. Used by `\gls` when indexing, which may or may not occur depending on the indexing settings.)

```
\newcommand*{\glstrdowrglossaryhook}[1]{}
```

`\@gls@alt@hyp@opt` Commands like `\gls` have a star or plus version. Provide a third symbol that the user can adapt for convenience.

```
\newcommand*{\@gls@alt@hyp@opt}[1]{%
\let\glslinkvar\@firstofthree

\def\@gls@hyp@opt@cs{#1}%
\@ifstar{\s@gls@hyp@opt}%
{\@ifnextchar{%
{\@firstoftwo{\p@gls@hyp@opt}}%
{%
\expandafter\@ifnextchar\@gls@alt@hyp@opt@char
{\@firstoftwo{\@alt@gls@hyp@opt}}%
{#1}%
}%
}%
}
```

`\@alt@gls@hyp@opt` User version

```
\newcommand*{\@alt@gls@hyp@opt}[1][\@firstofthree]{%
\let\glslinkvar\@firstofthree
\expandafter\@gls@hyp@opt@cs\expandafter[\@gls@alt@hyp@opt@keys,#1]}
```

`\@gls@alt@hyp@opt@char` Contains the character used as the command modifier.

```
\newcommand*{\@gls@alt@hyp@opt@char}{}
```

```

\@gls@alt@hyp@opt@keys Contains the option list used as the command modifier.
    \newcommand*{\@gls@alt@hyp@opt@keys}{}

\GlsXtrSetAltModifier
    \newcommand*{\GlsXtrSetAltModifier}[2]{%
        \let\@gls@hyp@opt\@gls@alt@hyp@opt
    Check that the supplied character isn't "+" or "*"
        \ifstrequal{#1}{+}%
        {\PackageError{glossaries-extra}%
            {Can't use '+' as modifier (it's already in use)}{}}%
        {%
            \ifstrequal{#1}{*}%
            {\PackageError{glossaries-extra}%
                {Can't use '*' as modifier (it's already in use)}{}}%
            {%
            }%
        }%
        \def\@gls@alt@hyp@opt@char{#1}%
        \def\@gls@alt@hyp@opt@keys{#2}%
        \ifdefequal\@glsxtr@record@setting\@glsxtr@record@setting@off
        {%
        }%
    Let bib2gls know the modifier.
        \protected@write\@auxout{}{\string\providecommand{\string\@glsxtr@altmodifier}[1]{}}%
        \protected@write\@auxout{}{\string\@glsxtr@altmodifier{#1}}%
    }%
}

\GlsXtrSetPlusModifier Allow user to override the plus modifier.
    \newcommand*{\GlsXtrSetPlusModifier}[1]{%
        \renewcommand*{\p@gls@hyp@opt}[1][]{%
            \let\glslinkvar\@thirdofthree
            \@gls@hyp@opt@cs[#1,##1]%
        }%
    }

\GlsXtrSetStarModifier Allow user to override the star modifier.
    \newcommand*{\GlsXtrSetStarModifier}[1]{%
        \renewcommand*{\s@gls@hyp@opt}[1][]{%
            \let\glslinkvar\@secondofthree
            \@gls@hyp@opt@cs[#1,##1]%
        }
    }

\glsxtr@org@dohyperlink
    \let\glsxtr@org@dohyperlink\glsdohyperlink

```

`\glsnavhyperlink` Since `\glsnavhyperlink` uses `\@glslink`, it's necessary to patch it uses `\glsdohyperlink` instead of `\glsxtrdohyperlink`. The simplest way to achieve this is to locally let `\glsxtrdohyperlink` to `\glsdohyperlink`.

This command is provided by `glossary-hypernav` so it may not exist.

```
\ifdef\glsnavhyperlink
{
  \renewcommand*{\glsnavhyperlink}[3][\@glo@type]{%
    \protected@edef\gls@grplabel{#2}\protected@edef\gls@grptitle{#3}%
```

Scope:

```
{%
  \let\glsxtrdohyperlink\glsxtr@org@dohyperlink
  \@glslink{\glsnavhyperlinkname{#1}{#2}}{#3}%
}%
}%
}
```

Patch if glossaries pre 4.50.

```
\ifdef\@gls@navhypertarget
{}
{%
```

`\glsnavhypertarget`

```
\renewcommand*{\glsnavhypertarget}{\protect\@gls@navhypertarget}
```

`\@gls@navhypertarget`

```
\newcommand*{\@gls@navhypertarget}[3][\@glo@type]{%
  \@glsnavhypertarget{#1}{#2}{#3}%
}
}%
```

NB `glossary-hypernav` v4.53 switched to L^AT_EX3 sequences, so check for the existence of `\glsnavhypergroupdotarget`:

```
\ifdef\glsnavhypergroupdotarget
{
```

`\glsnavhypergroupdotarget`

```
\renewcommand\glsnavhypergroupdotarget[3]{%
  \@glsxtr@do@org@target{\glsnavhyperlinkname{#1}{#2}}{#3}%
}
}
{
```

`\@glsnavhypertarget` Similarly for `\@glsnavhypertarget`. (NB this patch should not be used with glossaries v4.53+)

```
\ifdef\@glsnavhypertarget
```

```

{%
\renewcommand*{\@glsnavhypertarget}[3]{%
\protected@write\@auxout{}\string\@gls@hypergroup{#1}{#2}}%
\@glsxtr@do@org@target{\glsnavhyperlinkname{#1}{#2}}{#3}%
\ifcsdef{\gls@hypergrouplist@#1}%
{%
\letcs\@gls@list{\gls@hypergrouplist@#1}%
\protected@edef\@gls@thishypernavlabel{#2}%
\expandafter\DTLifinlist\expandafter{\@gls@thishypernavlabel}\@gls@list{}%
}%
\GlossariesWarningNoLine{Navigation panel
for glossary type ‘#1’^^Jmissing group ‘#2’}%
\gdef\gls@hypergroup@prerun{%
\GlossariesWarningNoLine{Navigation panel
has changed. Rerun LaTeX}}%
}%
}%
{%
\GlossariesWarningNoLine{Navigation panel
for glossary type ‘#1’^^Jmissing group ‘#2’}%
\gdef\gls@hypergroup@prerun{%
\GlossariesWarningNoLine{Navigation panel
has changed. Rerun LaTeX}}%
}%
}%
}
{}
}

```

The redefinition of `\glsdohyperlink` has been causing problems so introduce a new command instead.

`\glsxtrdohyperlink` Unpleasant complications can occur if the text or first key etc contains `\gls`, particularly if there are hyperlinks. To get around this problem, patch `\glsdohyperlink` so that it temporarily makes `\gls` behave like `\glstext` [*hyper=false,noindex*]. (This will be overridden if the user explicitly cancels either of those options in the optional argument of `\gls` or using the plus version.) This also patches the short form commands like `\acrshort` and `\glsxtrshort` to use `\glsentryshort` and, similarly, the long form commands like `\acrlong` and `\glsxtrlong` to use `\glsentrylong`. Added attribute check.

```

\newcommand*{\glsxtrdohyperlink}[2]{%
\gls@hasattribute{\glslabel}{targeturl}%
{%
\gls@hasattribute{\glslabel}{targetname}%
{%
\gls@hasattribute{\glslabel}{targetcategory}%
{%
\hyperref{\gls@getattribute{\glslabel}{targeturl}}%

```

```

        {\glsgetattribute{\glslabel}{targetcategory}}}%
        {\glsgetattribute{\glslabel}{targetname}}}%
        {\{\glsxtrprotectlinks#2}}}%
    }%
    {%
        \hyperref{\glsgetattribute{\glslabel}{targeturl}}}%
        {}%
        {\glsgetattribute{\glslabel}{targetname}}}%
        {\{\glsxtrprotectlinks#2}}}%
    }%
}%
{%
    \href{\glsgetattribute{\glslabel}{targeturl}}}%
    {\{\glsxtrprotectlinks#2}}}%
}%
}%
{%

```

Check for alias.

```

    \glsfieldfetch{\glslabel}{alias}{\gloaliaslabel}%
    \ifdefvoid\gloaliaslabel
    {%
        \glsxtrhyperlink{#1}{\{\glsxtrprotectlinks#2}}}%
    }%
    {%

```

Is the alias a multi-entry?

```

    \glsxtrifmulti\gloaliaslabel
    {%

```

Get the main target.

```

    \letcs\gloaliaslabel{@gls@combined@\gloaliaslabel @main}%
    }%
    {}%

```

Redirect link to the alias target.

```

    \glsxtrhyperlink
    {\glolinkprefix\glsdetoklabel{\gloaliaslabel}}%
    {\{\glsxtrprotectlinks#2}}}%
    }%
}%
}

```

`\glsxtrhyperlink` Allows integration with the base glossaries package's `debug=showtargets` option.

```

\ifdef\glsdohyperlinkhook
{
    \newcommand{\glsxtrhyperlink}[2]{%
        \glsdoshowtarget{#1}{\glsdohyperlinkhook{#1}{#2}\hyperlink{#1}{#2}}%
    }%
}
{

```

```

\newcommand{\glxtrhyperlink}[2]{%
  \glsdoshowtarget{#1}{\hyperlink{#1}{#2}}%
}%
}

```

\glisablehyper Redefine to set `\glslabel` (to allow it to be picked up by `\glsdohyperlink`). Also made it robust and added grouping to localise the definition of `\glslabel`. The original internal command `@glo@label` could probably be simply replaced with `\glslabel`, but it's retained in case its removal causes unexpected problems.

```

\renewrobustcmd*{\glshyperlink}[2][\glstrytext{\@glo@label}]{%
  \glsdifexists{#2}%
  {%
    \def\@glo@label{#2}%

    {\protected@edef\glslabel{#2}%
     \@glslink{\glslinkprefix\glslabel}{#1}}%
  }%
}

```

\glisablehyper Redefine in case we have an old version of `glossaries`. This now uses `\def` rather than `\let` to allow for redefinitions of `\glsdonohyperlink`.

```

\renewcommand{\glisablehyper}{%
  \KV@glslink@hyperfalse
  \def\@glslink{\glsdonohyperlink}%
  \let\@glstarget\@secondoftwo
}

```

\glisablehyper This now uses `\def` rather than `\let` to allow for redefinitions of `\glsdohypertarget` and `\glsdohyperlink`.

```

\renewcommand{\glisablehyper}{%
  \KV@glslink@hypertrue
  \def\@glslink{\glxtrdohyperlink}%
  \def\@glstarget{\glsdohypertarget}%
}

```

\glsdonohyperlink This command was only introduced in `glossaries v4.20`, so it may not be defined (therefore use `\def`). For older `glossaries` versions, this won't be used if `hyperref` hasn't been loaded, which means the indexing will still take place. The generated text is scoped (the link text in `\hyperlink` is also scoped, so it's consistent).

```

\def\glsdonohyperlink#1#2{\glxtrprotectlinks #2}

```

\@glslink Reset `\@glslink` with patched versions:

```

\ifcsundef{hyperlink}%
{%
  \def\@glslink{\glsdonohyperlink}
}%
{%
  \def\@glslink{\glxtrdohyperlink}
}

```

`\glstrprotectlinks` Make `\gls` (and variants) behave like the corresponding `\glstext` (and variants) with hyperlinking and indexing off.

```
\newcommand*{\glstrprotectlinks}{%
  \KV@glslink@hyperfalse
  \KV@glslink@noindextrue
  \let\@gls@\@glstr@p@text@
  \let\@Gls@\@Glsxtr@p@text@
  \let\@GLS@\@GLSxtr@p@text@
  \let\@glspl@\@glstr@p@plural@
  \let\@Glspl@\@Glsxtr@p@plural@
  \let\@GLSpl@\@GLSxtr@p@plural@
  \let\@glstrshort@\@glstr@p@short@
  \let\@Glsxtrshort@\@Glsxtr@p@short@
  \let\@GLSxtrshort@\@GLSxtr@p@short@
  \let\@glstrlong@\@glstr@p@long@
  \let\@Glsxtrlong@\@Glsxtr@p@long@
  \let\@GLSxtrlong@\@GLSxtr@p@long@
  \let\@glstrshortpl@\@glstr@p@shortpl@
  \let\@Glsxtrshortpl@\@Glsxtr@p@shortpl@
  \let\@GLSxtrshortpl@\@GLSxtr@p@shortpl@
  \let\@glstrlongpl@\@glstr@p@longpl@
  \let\@Glsxtrlongpl@\@Glsxtr@p@longpl@
  \let\@GLSxtrlongpl@\@GLSxtr@p@longpl@
  \let\@acrshort@\@glstr@p@acrshort@
  \let\@Acrshort@\@Glsxtr@p@acrshort@
  \let\@ACRshort@\@GLSxtr@p@acrshort@
  \let\@acrshortpl@\@glstr@p@acrshortpl@
  \let\@Acrshortpl@\@Glsxtr@p@acrshortpl@
  \let\@ACRshortpl@\@GLSxtr@p@acrshortpl@
  \let\@acrlong@\@glstr@p@acrlong@
  \let\@Acrlong@\@Glsxtr@p@acrlong@
  \let\@ACRlong@\@GLSxtr@p@acrlong@
  \let\@acrlongpl@\@glstr@p@acrlongpl@
  \let\@Acrlongpl@\@Glsxtr@p@acrlongpl@
  \let\@ACRlongpl@\@GLSxtr@p@acrlongpl@
}
```

These protected versions need grouping to prevent the label from getting confused.

```
\@glstr@p@text@
\def\@glstr@p@text@#1#2[#3]{\@glstext@{#1}{#2}[#3]}}

\@Glsxtr@p@text@
\def\@Glsxtr@p@text@#1#2[#3]{\@Glsxtr@p@text@{#1}{#2}[#3]}}

\@GLSxtr@p@text@
\def\@GLSxtr@p@text@#1#2[#3]{\@GLSxtr@p@text@{#1}{#2}[#3]}}
```

```

\@glsxtr@p@plural@
\def\@glsxtr@p@plural@#1#2[#3]{\@glsplural@{#1}{#2}[#3]}}

\@Glsxtr@p@plural@
\def\@Glsxtr@p@plural@#1#2[#3]{\@Glsplural@{#1}{#2}[#3]}}

\@GLSxtr@p@plural@
\def\@GLSxtr@p@plural@#1#2[#3]{\@GLSplural@{#1}{#2}[#3]}}

\@glsxtr@p@short@
\def\@glsxtr@p@short@#1#2[#3]{%
{%
\glssetabbrvfmt{\glscategory{#2}}%
\glsabbrvfont{\glstryshort{#2}}#3%
}%
}

\@Glsxtr@p@short@
\def\@Glsxtr@p@short@#1#2[#3]{%
{%
\glssetabbrvfmt{\glscategory{#2}}%
\glsabbrvfont{\Glsentryshort{#2}}#3%
}%
}

\@GLSxtr@p@short@
\def\@GLSxtr@p@short@#1#2[#3]{%
{%
\glssetabbrvfmt{\glscategory{#2}}%
\glsupercase{\glsabbrvfont{\glstryshort{#2}}#3}%
}%
}

\@glsxtr@p@shortpl@
\def\@glsxtr@p@shortpl@#1#2[#3]{%
{%
\glssetabbrvfmt{\glscategory{#2}}%
\glsabbrvfont{\glstryshortpl{#2}}#3%
}%
}

\@Glsxtr@p@shortpl@
\def\@Glsxtr@p@shortpl@#1#2[#3]{%
{%
\glssetabbrvfmt{\glscategory{#2}}%
\glsabbrvfont{\Glsentryshortpl{#2}}#3%
}%
}

```



```

\@GLSxtr@p@shortpl@
\def\@GLSxtr@p@shortpl@#1#2[#3]{%
  {%
    \glsetabbrvfmt{\glscategory{#2}}%
    \glsupercase{\glsabbrvfont{\glsentryshortpl{#2}}#3}%
  }%
}

\@glsxtr@p@long@
\def\@glsxtr@p@long@#1#2[#3]{\{\glsentrylong{#2}#3}\}

\@Glsxtr@p@long@
\def\@Glsxtr@p@long@#1#2[#3]{\{\Glsentrylong{#2}#3}\}

\@GLSxtr@p@long@
\def\@GLSxtr@p@long@#1#2[#3]{%
  {\glsupercase{\glslongfont{\glsentrylong{#2}}#3}}
}

\@glsxtr@p@longpl@
\def\@glsxtr@p@longpl@#1#2[#3]{\{\glsentrylongpl{#2}#3}\}

\@Glsxtr@p@longpl@
\def\@Glsxtr@p@longpl@#1#2[#3]{\{\glslongfont{\Glsentrylongpl{#2}}#3}\}

\@GLSxtr@p@longpl@
\def\@GLSxtr@p@longpl@#1#2[#3]{%
  {\glsupercase{\glslongfont{\glsentrylongpl{#2}}#3}}
}

\@glsxtr@p@acrshort@
\def\@glsxtr@p@acrshort@#1#2[#3]{\{\acronymfont{\glsentryshort{#2}}#3}\}

\@Glsxtr@p@acrshort@
\def\@Glsxtr@p@acrshort@#1#2[#3]{\{\acronymfont{\Glsentryshort{#2}}#3}\}

\@GLSxtr@p@acrshort@
\def\@GLSxtr@p@acrshort@#1#2[#3]{%
  {\glsupercase{\acronymfont{\glsentryshort{#2}}#3}}
}

\@glsxtr@p@acrshortpl@
\def\@glsxtr@p@acrshortpl@#1#2[#3]{\{\acronymfont{\glsentryshortpl{#2}}#3}\}

\@Glsxtr@p@acrshortpl@
\def\@Glsxtr@p@acrshortpl@#1#2[#3]{\{\acronymfont{\Glsentryshortpl{#2}}#3}\}

\@GLSxtr@p@acrshortpl@
\def\@GLSxtr@p@acrshortpl@#1#2[#3]{%
  {\glsupercase{\acronymfont{\glsentryshortpl{#2}}#3}}
}

```

```

\@glxtrp@acrlong@
\def\@glxtrp@acrlong@#1#2[#3]{\@glstrylong{#2}#3}}

\@Glsxtrp@acrlong@
\def\@Glsxtrp@acrlong@#1#2[#3]{\@Glsstrylong{#2}#3}}

\@GLSxtrp@acrlong@
\def\@GLSxtrp@acrlong@#1#2[#3]{%
{\@glssuppercase{\@glstrylong{#2}#3}}}

\@glxtrp@acrlongpl@
\def\@glxtrp@acrlongpl@#1#2[#3]{\@glstrylongpl{#2}#3}}

\@Glsxtrp@acrlongpl@
\def\@Glsxtrp@acrlongpl@#1#2[#3]{\@Glsstrylongpl{#2}#3}}

\@GLSxtrp@acrlongpl@
\def\@GLSxtrp@acrlongpl@#1#2[#3]{%
{\@glssuppercase{\@glstrylongpl{#2}#3}}}

Commands to minimise conflict.

\@glxtrp@opt
\newcommand*{\@glxtrp@opt}{hyper=false,noindex}

\glxtrsetpopts Used in glossary to switch hyperlinks on for the \glxtrp type of commands.
\newcommand*{\glxtrsetpopts}[1]{%
\renewcommand*{\@glxtrp@opt}{#1}%
}

\glossxtrsetpopts Used in glossary to switch hyperlinks on for the \glxtrp type of commands.
\newcommand*{\glossxtrsetpopts}{%
\glxtrsetpopts{noindex}%
}

\glxtrpInit Initialisation code at the start of the group inserted by \@@glxtrp.
\newcommand{\glxtrpInit}[2]{\let\glspostlinkhook\relax}

\@@glxtrp
\newrobustcmd*{\@@glxtrp}[2]{%
Add scope.
{%
\glxtrpInit{#1}{#2}%
\csname#1\expandafter\endcsname\expandafter[\@glxtrp@opt]{#2}[]%
}%
}

```

```

\@glsxtrp
\newrobustcmd*{\@glsxtrp}[2]{%
  \ifcsdef{gls#1}%
  {%
    \@glsxtrp{gls#1}{#2}%
  }%
  {%
    \ifcsdef{glsxtr#1}%
    {%
      \@glsxtrp{glsxtr#1}{#2}%
    }%
    {%
      \PackageError{glossaries-extra}{‘#1’ not recognised by
        \string\glsxtrp}{}%
    }%
  }%
}

```

```

\@Glsxtrp
\newrobustcmd*{\@Glsxtrp}[2]{%
  \ifcsdef{Gls#1}%
  {%
    \@glsxtrp{Gls#1}{#2}%
  }%
  {%
    \ifcsdef{Glsxtr#1}%
    {%
      \@glsxtrp{Glsxtr#1}{#2}%
    }%
    {%
      \PackageError{glossaries-extra}{‘#1’ not recognised by
        \string\Glsxtrp}{}%
    }%
  }%
}

```

```

\@GLSxtrp
\newrobustcmd*{\@GLSxtrp}[2]{%
  \ifcsdef{GLS#1}%
  {%
    \@glsxtrp{GLS#1}{#2}%
  }%
  {%
    \ifcsdef{GLSxtr#1}%
    {%
      \@glsxtrp{GLSxtr#1}{#2}%
    }%
    {%
      \PackageError{glossaries-extra}{‘#1’ not recognised by

```

```

        \string\GLSxtrp}{}%
    }%
}

\glxtrifintoc
\newcommand{\glxtrifintoc}[2]{#2}

\glxtrifheaduc
\newcommand*{\glxtrifheaduc}[3]{%
\glxtrifintoc{#3}{\glxifattribute{#1}{headuc}{true}{#2}{#3}}%
}

\glxtr@entry@p
\newrobustcmd*{\glxtr@headentry@p}[2]{%
\glxtrifheaduc{#1}%
{%
\glssupercase{\@glx@entry@field{#1}{#2}}%
}%
{%
\@glx@entry@field{#1}{#2}%
}%
}

\glxtrp Not robust as it needs to expand somewhat.
\newcommand{\glxtrp}[2]{%
\protect\NoCaseChange
{%
\protect\glstexorpdfstring
{%
\protect\glxtrifinmark
{%
\ifcsdef{glxtrhead#1}%
{%
{\protect\cuse{glxtrhead#1}{#2}}%
}%
{%
\glxtr@headentry@p{#2}{#1}%
}%
}%
}%
\@glxtrp{#1}{#2}%
}%
{%
\protect\@glx@entry@field{#2}{#1}%
}%
}%
}

```

Provide short synonyms for the most common option.

```

\glsps
\newcommand*{\glsps}{\glsxtrp{short}}

\glspt
\newcommand*{\glspt}{\glsxtrp{text}}

\Glsxtrp As above but use first letter upper case.
\newcommand{\Glsxtrp}[2]{%
  \protect\NoCaseChange
  {%
    \protect\glstexorpdfstring
    {%
      \protect\glsxtrifinmark
      {%
        \ifcsdef{Glsxtrhead#1}%
        {%
          {\protect\csuse{Glsxtrhead#1}{#2}}%
        }%
      }%
    }%
  }%

  \@Gls@entry@field is robust as from glossaries v4.50, but continue to use
  \protect in case an older version is installed.
  \protect\@Gls@entry@field{#2}{#1}%
  }%
  }%
  {%
    \@Glsxtrp{#1}{#2}%
  }%
  }%
  {%
    \MFUsentencecase{\@Gls@entry@field{#2}{#1}}%
  }%
  }%
}
\glsmfuaddmap{\glsxtrp}{\Glsxtrp}

\GLSxtrp As above but all upper case. The bookmarks use \glsuppercase, which is
expandable as from mfirstuc v2.08+.
\newcommand{\GLSxtrp}[2]{%
  \protect\NoCaseChange
  {%
    \protect\glstexorpdfstring
    {%
      \protect\glsxtrifinmark
      {%
        \ifcsdef{GLSxtr#1}%
        {%
          {\protect\GLSxtrshort[noindex,hyper=false]{#1}[]}%
        }%
      }%
    }%
  }%
}

```

```

    }%
    {%
      \protect\glsupercase
      {%
        \protect\@gls@entry@field{#2}{#1}%
      }%
    }%
  }%
  {%
    \@GLSxtrp{#1}{#2}%
  }%
  }%
  {%
    \protect\GLSxtrusefield{#2}{#1}%
  }%
}%
}
\glsmfublocker{\GLSxtrp}

```

Provide case-changing versions of synonyms.

```

\Glsps
\newcommand*{\Glsps}{\GLSxtrp{short}}
\glsmfuaddmap{\glsps}{\Glsps}

\GLSps
\newcommand*{\GLSps}{\GLSxtrp{short}}
\glsmfublocker{\GLSps}

\Glspt
\newcommand*{\Glspt}{\GLSxtrp{text}}
\glsmfuaddmap{\glspt}{\Glspt}

\GLSpt
\newcommand*{\GLSpt}{\GLSxtrp{text}}
\glsmfublocker{\GLSpt}

```

1.3.5 Entry Counting

The (use) entry counting mechanism from `glossaries` is adjusted here to work with category attributes. Provide a convenient command to enable entry counting, set the `entrycount` attribute for given categories and redefine `\gls` etc to use `\cgl`s instead. This form of entry counting is provided to adjust the formatting if the number of times an entry has been used (through commands that unset the first use flag) doesn't exceeding the specified threshold. For link counting, see §1.4.

First adjust definitions of the unset and reset commands to provide a hook, but changing the flag can cause problems in certain situations, so to allow the normal unsetting to be temporarily disabled, `\@glsunset` is let to

`\@glxtr@unset`, which performs the actual unsetting through `\@@glunset` and then does the hook. This means that the unsetting (and the hook) can be switched off by redefining `\@glunset` and then switched back on again by changing the definition back to `\@glxtr@unset`.

`\@glxtr@unset` Global unset.

```
\newcommand*{\@glxtr@unset}[1]{%
  \@@glunset{#1}%
  \glxtrpostunset{#1}%
}%
```

`\@glunset` Global unset.

```
\let\@glunset\@glxtr@unset
```

`\glxtrpostunset`

```
\newcommand*{\glxtrpostunset}[1]{}
```

Provide a command to store a list of labels that will need unsetting.

`\GlsXtrStartUnsetBuffering`

```
\newcommand*{\GlsXtrStartUnsetBuffering}{%
  \@ifstar\s@GlsXtrStartUnsetBuffering\@GlsXtrStartUnsetBuffering
}
```

`\@GlsXtrStartUnsetBuffering` Unstarred version doesn't check for duplicates.

```
\newcommand*{\@GlsXtrStartUnsetBuffering}{%
  \let\@glxtr@org@unset@buffer\@glxtr@unset@buffer
  \GlsXtrClearUnsetBuffer
  \let\@glunset\@glxtrbuffer@unset
  \let\org@glxtrbuffer@check@repeats\@glxtrbuffer@check@repeats
  \renewcommand*{\@glxtrbuffer@check@repeats}{%
    \@@glxtrbuffer@check@repeats
  }%
}
```

`\s@GlsXtrStartUnsetBuffering` Starred version checks for duplicates.

```
\newcommand*{\s@GlsXtrStartUnsetBuffering}{%
  \let\@glxtr@org@unset@buffer\@glxtr@unset@buffer
  \GlsXtrClearUnsetBuffer
  \let\@glunset\@glxtrbuffer@nodup@unset
  \let\org@glxtrbuffer@check@repeats\@glxtrbuffer@check@repeats
  \renewcommand*{\@glxtrbuffer@check@repeats}{%
    \@@glxtrbuffer@check@repeats
  }%
}
```

`\@glxtrbuffer@unset` This must use a global change since `\gl`s may have to be placed inside `\mbox` (for example, with `soul` commands).

```
\newcommand*{\@glxtrbuffer@unset}[1]{%
```

```

\listxadd\@glxtr@unset@buffer{#1}%
}

\@glxtrbuffer@nodup@unset Alternative version that avoids duplicates. One level of expansion is performed
on the argument in case it's a control sequence containing the label. (Not using
\xifinlist as the added complexity might cause problems that the buffering
is trying to overcome.)
\newcommand*{\@glxtrbuffer@nodup@unset}[1]{%
\expandafter\xifinlist\expandafter{#1}{\@glxtr@unset@buffer}{}%
{\listxadd\@glxtr@unset@buffer{#1}}%
}

\@glxtrbuffer@check@repeats
\newcommand*{\@glxtrbuffer@check@repeats}{}

\@glxtrbuffer@check@repeats
\newcommand*{\@glxtrbuffer@check@repeats}{}

\@glxtrbuffer@check@repeats@notused
\newcommand*{\@glxtrbuffer@check@repeats@notused}{}

\@glxtrbuffer@do@check@repeat
\newrobustcmd*{\@glxtrbuffer@do@check@repeat}{%
\expandafter\xifinlist\expandafter{\glslabel}{\@glxtr@unset@buffer}%
{\@glslocalunset{\glslabel}}%
{\GlsXtrIfUnusedOrUndefined\glslabel
{\listxadd\@glxtrbuffer@check@repeats@notused{\glslabel}}{}}%
}

\GlsXtrUnsetBufferEnableRepeatLocal
\newcommand*{\GlsXtrUnsetBufferEnableRepeatLocal}{%
\def\@glxtrbuffer@check@repeats{\@glxtrbuffer@do@check@repeat}%
\def\@glxtrbuffer@check@repeats@notused{}%
}

\GlsXtrUnsetBufferDisableRepeatLocal
\newcommand*{\GlsXtrUnsetBufferDisableRepeatLocal}{%
\def\@glxtrbuffer@check@repeats{}%
\def\@glxtrbuffer@check@repeats@notused{}%
}

\GlsXtrResetLocalBuffer
\newcommand*{\GlsXtrResetLocalBuffer}{%
\forlistloop\@glslocalreset\@glxtrbuffer@check@repeats@notused
\GlsXtrClearUnsetBuffer
}

```



```

\GlsXtrClearUnsetBuffer
    \newcommand*{\GlsXtrClearUnsetBuffer}{%
        \def\@glsxtrbuffer@check@repeats@notused{}%
        \def\@glsxtr@unset@buffer{}%
    }

\GlsXtrStopUnsetBuffering
    \newcommand*{\GlsXtrStopUnsetBuffering}{%
        \ifstar\s@GlsXtrStopUnsetBuffering\@GlsXtrStopUnsetBuffering
    }

\@GlsXtrStopUnsetBuffering Unstarred form (global unset).
    \newcommand*{\@GlsXtrStopUnsetBuffering}{%
        \let\@glsunset\@glsxtr@unset
        \forlistloop\@glsunset\@glsxtr@unset@buffer
        \let\@glsxtr@unset@buffer\@glsxtr@org@unset@buffer
        \let\@glsxtrbuffer@check@repeats\org@glsxtrbuffer@check@repeats
    }

\s@GlsXtrStopUnsetBuffering Starred form (local unset).
    \newcommand*{\s@GlsXtrStopUnsetBuffering}{%
        \forlistloop\@glslocalunset\@glsxtr@unset@buffer
        \let\@glsunset\@glsxtr@unset
        \let\@glsxtrbuffer@check@repeats\org@glsxtrbuffer@check@repeats
    }

\GlsXtrDiscardUnsetBuffering Discards pending buffer and restores \glsunset.
    \newcommand*{\GlsXtrDiscardUnsetBuffering}{%
        \let\@glsunset\@glsxtr@unset
        \let\@glsxtr@unset@buffer\@glsxtr@org@unset@buffer
        \let\@glsxtrbuffer@check@repeats\org@glsxtrbuffer@check@repeats
    }

\GlsXtrForUnsetBufferedList Iterate over labels stored in the current buffer. The argument is the handler
macro.
    \newcommand*{\GlsXtrForUnsetBufferedList}[1]{%
        \forlistloop#1\@glsxtr@unset@buffer
    }

\@glslocalunset Local unset.
    \renewcommand*{\@glslocalunset}[1]{%
        \@glslocalunset{#1}%
        \glsxtrpostlocalunset{#1}%
    }%

\glsxtrpostlocalunset
    \newcommand*{\glsxtrpostlocalunset}[1]{}

```

`\@glsreset` Global reset.

```
\renewcommand*{\@glsreset}[1]{%  
  \@glsreset{#1}%  
  \glstrpostreset{#1}%  
}%
```

`\glstrpostreset`

```
\newcommand*{\glstrpostreset}[1]{}
```

`\@glslocalreset` Local reset.

```
\renewcommand*{\@glslocalreset}[1]{%  
  \@glslocalreset{#1}%  
  \glstrpostlocalreset{#1}%  
}%
```

`\glstrpostlocalreset`

```
\newcommand*{\glstrpostlocalreset}[1]{}
```

`\glslocalreseteach` Locally reset a list of entries.

```
\newcommand*{\glslocalreseteach}[1]{%  
  \gls@ifnotmeasuring  
  {%  
    \@for\@gls@thislabel:=#1\do{%  
      \glsdoifexists{\@gls@thislabel}%  
      {%  
        \@glslocalreset{\@gls@thislabel}%  
      }%  
    }%  
  }%  
}
```

`\glslocalunseteach` Locally unset a list of entries.

```
\newcommand*{\glslocalunseteach}[1]{%  
  \gls@ifnotmeasuring  
  {%  
    \@for\@gls@thislabel:=#1\do{%  
      \glsdoifexists{\@gls@thislabel}%  
      {%  
        \@glslocalunset{\@gls@thislabel}%  
      }%  
    }%  
  }%  
}
```

`\GlsXtrEnableEntryCounting` The first argument is the list of categories and the second argument is the value of the `entrycount` attribute.

```
\newcommand*{\GlsXtrEnableEntryCounting}[2]{%
```

Enable entry counting:

```
\glsenableentrycount
```

Redefine `\gls` etc:

```
\renewcommand*{\gls}{\cglsl}%
\renewcommand*{\Gls}{\cGls}%
\renewcommand*{\glspl}{\cglspl}%
\renewcommand*{\Glspl}{\cGlspl}%
\renewcommand*{\GLS}{\cGLS}%
\renewcommand*{\GLSpl}{\cGLSpl}%
```

Set the entrycount attribute:

```
\@glstr@setentrycountunsetattr{#1}{#2}%
```

In case this command is used again:

```
\let\GlsXtrEnableEntryCounting\@glstr@setentrycountunsetattr
\renewcommand*{\GlsXtrEnableEntryUnitCounting}[3]{%
\PackageError{glossaries-extra}{\string\GlsXtrEnableEntryUnitCounting\space
can't be used with \string\GlsXtrEnableEntryCounting}%
{Use one or other but not both commands}}%
}
```

`\@glstr@setentrycountunsetattr`

```
\newcommand*{\@glstr@setentrycountunsetattr}[2]{%
\@for\@glstr@cat:=#1\do
{%
\ifdefempty{\@glstr@cat}{}%
{%
\glssetcategoryattribute{\@glstr@cat}{entrycount}{#2}%
}%
}%
}
```

`\ifglrsresetcurrcount` Determine whether or not to reset the entry counter when the first use flag is reset. This conditional will already be defined with glossaries v4.50+.

```
\ifdef\glrsresetcurrcountfalse{\newif\ifglrsresetcurrcount}
\glrsresetcurrcountfalse
```

Redefine the entry counting commands to take into account the entrycount attribute.

`\glsenableentrycount`

```
\renewcommand*{\glsenableentrycount}{%
```

Enable new fields:

```
\appto\@newglossaryentry@defcounters{\@@newglossaryentry@defcounters}%
```

Just in case the user has switched on the docdef option.

```
\renewcommand*{\gls@defdocnewglossaryentry}{%
\renewcommand*\newglossaryentry[2]{%
\PackageError{glossaries}{\string\newglossaryentry\space
may only be used in the preamble when entry counting has
been activated}{If you use \string\glsenableentrycount\space
you must place all entry definitions in the preamble not in
```

```

        the document environment}%
    }%
}%

```

New commands to access new fields:

```

\newcommand*{\glsentrycurrcount}[1]{%
\ifcsundef{glo@\glsdetoklabel{##1}@currcount}%
{0}{\@gls@entry@field{##1}{currcount}}%
}%
\newcommand*{\glsentryprevcount}[1]{%
\ifcsundef{glo@\glsdetoklabel{##1}@prevcount}%
{0}{\@gls@entry@field{##1}{prevcount}}%
}%

```

Adjust post unset and reset:

```

\let\@glsxtr@entrycount@org@unset\glsxtrpostunset
\renewcommand*{\glsxtrpostunset}[1]{%
\@glsxtr@entrycount@org@unset{##1}%
\@gls@increment@currcount{##1}%
}%
\let\@glsxtr@entrycount@org@localunset\glsxtrpostlocalunset
\renewcommand*{\glsxtrpostlocalunset}[1]{%
\@glsxtr@entrycount@org@localunset{##1}%
\@gls@local@increment@currcount{##1}%
}%
\let\@glsxtr@entrycount@org@reset\glsxtrpostreset
\renewcommand*{\glsxtrpostreset}[1]{%
\@glsxtr@entrycount@org@reset{##1}%
\ifglsresetcurrcount
\csdef{glo@\glsdetoklabel{##1}@currcount}{0}%
\fi
}%
\let\@glsxtr@entrycount@org@localreset\glsxtrpostlocalreset
\renewcommand*{\glsxtrpostlocalreset}[1]{%
\@glsxtr@entrycount@org@localreset{##1}%
\ifglsresetcurrcount
\csdef{glo@\glsdetoklabel{##1}@currcount}{0}%
\fi
}%

```

Modifications to take into account the attributes that govern whether the entry should be unset.

```

\let\@cgls@\@cgls@
\let\@cglspl@\@cglspl@

\let\@cGls@\@cGls@
\let\@cGlspl@\@cGlspl@
\let\@cGLS@\@cGLS@
\let\@cGLSpl@\@cGLSpl@

```

The rest is as the original definition.

```

\AtEndDocument{\@gls@write@entrycounts}%
\renewcommand*{\@gls@entry@count}[2]{%
  \csgdef{glo@\glsdetoklabel{##1}@prevcount}{##2}%
}%
\let\glsenableentrycount\relax
\renewcommand*{\glsenableentryunitcount}{%
  \PackageError{glossaries-extra}{\string\glsenableentryunitcount\space
    can't be used with \string\glsenableentrycount}%
  {Use one or other but not both commands}%
}%
}

newglossaryentry@defcounters Allow for docdef=restricted.
\renewcommand*{\@newglossaryentry@defcounters}{%
  \csdef{glo@\@glo@label @currcount}{0}%
  \ifnum\@glsxtr@docdefval=2\relax
    \ifcsdef{glo@\@glo@label @prevcount}{\csdef{glo@\@glo@label @prevcount}{0}}%
  \else
    \csdef{glo@\@glo@label @prevcount}{0}%
  \fi
}

\@gls@write@entrycounts Modify this command so that it only writes the information for entries with the
entrycount attribute and issue warning if no entries have this attribute set.
\renewcommand*{\@gls@write@entrycounts}{%
  \immediate\write\@auxout
    {\string\providecommand*{\string\@gls@entry@count}[2]{}}%
  \count@=0\relax
  \forallglsentries{\@glsentry}{%
    \gls@hasattribute{\@glsentry}{entrycount}%
    {%
      \ifglsused{\@glsentry}%
      {%
        \immediate\write\@auxout
          {\string\@gls@entry@count{\@glsentry}{\glsentrycurrcount{\@glsentry}}}%
      }%
    }%
    \advance\count@ by \@ne
  }%
  {%
  }%
}%
\ifnum\count@=0
  \GlossariesExtraWarningNoLine{Entry counting has been enabled
    \MessageBreak with \string\glsenableentrycount\space but the
    \MessageBreak attribute 'entrycount' hasn't
    \MessageBreak been assigned to any of the defined
    \MessageBreak entries}%
\fi
}

```

`\glstrifcounttrigger{<label>}{<trigger format>}{<normal>}`

`\glstrifcounttrigger`

```
\newcommand*\glstrifcounttrigger}[3]{%
\glshasattribute{#1}{entrycount}%
{%
\ifnum\glsentryprevcount{#1}>\glsggetattribute{#1}{entrycount}\relax
#3%
\else
#2%
\fi
}%
{#3}%
}
```

Actual internal definitions of `\cgl`s used when entry counting is enabled.

`\@@cgl@s@`

```
\def\@@cgl@s@#1#2[#3]{%
\glstrifcounttrigger{#2}%
{%
\cglformat{#2}{#3}%
\glunset{#2}%
}%
{%
\@cgl@s@{#1}{#2}[#3]%
}%
}%
```

`\@@cgl spl@`

```
\def\@@cgl spl@#1#2[#3]{%
\glstrifcounttrigger{#2}%
{%
\cgl spl format{#2}{#3}%
\glunset{#2}%
}%
{%
\@cgl spl@{#1}{#2}[#3]%
}%
}%
```

`\@@cGls@`

```
\def\@@cGls@#1#2[#3]{%
\glstrifcounttrigger{#2}%
{%
\cGlsformat{#2}{#3}%
\glunset{#2}%
}%
}%
```

```

        {%
        \@Gls@{#1}{#2}[#3]%
        }%
    }%

\@@cGlspl@
\def\@@cGlspl@#1#2[#3]{%
    \glstrifcounttrigger{#2}%
    {%
        \cGlsplformat{#2}{#3}%
        \glunset{#2}%
    }%
    {%
        \@Glspl@{#1}{#2}[#3]%
    }%
}%

\@@cGLS@
\def\@@cGLS@#1#2[#3]{%
    \glstrifcounttrigger{#2}%
    {%
        \cGLSformat{#2}{#3}%
        \glunset{#2}%
    }%
    {%
        \@GLS@{#1}{#2}[#3]%
    }%
}%

\@@cGLSpl@
\def\@@cGLSpl@#1#2[#3]{%
    \glstrifcounttrigger{#2}%
    {%
        \cGLSplformat{#2}{#3}%
        \glunset{#2}%
    }%
    {%
        \@GLSpl@{#1}{#2}[#3]%
    }%
}%

```

Remove default warnings from \cgl's etc so that it can be used interchangeably with \gl's etc.

```

\@cgl's@
\def\@cgl's@#1#2[#3]{\@gl's@{#1}{#2}[#3]}

\@cGls@
\def\@cGls@#1#2[#3]{\@Gls@{#1}{#2}[#3]}

```

```

\@cglsp1@
\def\@cglsp1@#1#2[#3]{\@glsp1@{#1}{#2} [#3]}

\@cGlsp1@
\def\@cGlsp1@#1#2[#3]{\@Glspl@{#1}{#2} [#3]}

Add all upper case versions not provided by glossaries.

\cGLS
\newrobustcmd*\cGLS{\@gls@hyp@opt\@cGLS}
\glsmfublocker{\cGLS}

\@cGLS Defined the un-starred form. Need to determine if there is a final optional
argument
\newcommand*\@cGLS}[2] [] {%
  \new@ifnextchar[{\@cGLS@{#1}{#2}}{\@cGLS@{#1}{#2} []}%
}

\@cGLS@
\def\@cGLS@#1#2[#3]{\@GLS@{#1}{#2} [#3]}

\cGLSformat Format used by \cGLS if entry only used once on previous run. The first argu-
ment is the label, the second argument is the insert text.
\newcommand*\cGLSformat}[2] {%
  \expandafter\glssupercase\expandafter{\cglformat{#1}{#2}}%
}

\cGLSpl
\newrobustcmd*\cGLSpl{\@gls@hyp@opt\@cGLSpl}
\glsmfublocker{\cGLSpl}

\@cGLSpl Defined the un-starred form. Need to determine if there is a final optional
argument
\newcommand*\@cGLSpl}[2] [] {%
  \new@ifnextchar[{\@cGLSpl@{#1}{#2}}{\@cGLSpl@{#1}{#2} []}%
}

\@cGLSpl@
\def\@cGLSpl@#1#2[#3]{\@GLSpl@{#1}{#2} [#3]}

\cGLSplformat Format used by \cGLSpl if entry only used once on previous run. The first
argument is the label, the second argument is the insert text.
\newcommand*\cGLSplformat}[2] {%
  \expandafter\glssupercase\expandafter{\cglsplformat{#1}{#2}}%
}

Modify the trigger formats to check for the regular attribute.

```



```
\cglformat
\renewcommand*\cglformat}[2]{%
  \glsifregular{#1}
  {\glsentryfirst{#1}}%
  {\ifglshaslong{#1}{\glsentrylong{#1}}{\glsentryfirst{#1}}}\#2%
}
```

```
\cGlsformat
\renewcommand*\cGlsformat}[2]{%
  \glsifregular{#1}
  {\Glsentryfirst{#1}}%
  {\ifglshaslong{#1}{\Glsentrylong{#1}}{\Glsentryfirst{#1}}}\#2%
}
```

```
\cglsplformat
\renewcommand*\cglsplformat}[2]{%
  \glsifregular{#1}
  {\glsentryfirstplural{#1}}%
  {\ifglshaslong{#1}{\glsentrylongpl{#1}}{\glsentryfirstplural{#1}}}\#2%
}
```

```
\cGlsplformat
\renewcommand*\cGlsplformat}[2]{%
  \glsifregular{#1}
  {\Glsentryfirstplural{#1}}%
  {\ifglshaslong{#1}{\Glsentrylongpl{#1}}{\Glsentryfirstplural{#1}}}\#2%
}
```

New code similar to above for unit counting.

`\glossaryentry@defunitcounters`

```
\newcommand*\@newglossaryentry@defunitcounters{%
  \protected@edef\@glo@countunit{\csuse{@glsxtr@categoryattr@ \@glo@category @unitcount}}%
  \ifdefvoid\@glo@countunit
  {}%
  {%
    \@glsxtr@ifunitcounter{\@glo@countunit}%
    {}%
    {\expandafter\@glsxtr@addunitcounter\expandafter{\@glo@countunit}}%
  }%
}
```

`\@glsxtr@unitcountlist` List to keep track of which counters are being used by the entry unit count facility.

```
\newcommand*\@glsxtr@unitcountlist{}
```

`\@glsxtr@addunitcounter`

```
\newcommand*\@glsxtr@addunitcounter}[1]{%
  \listadd{\@glsxtr@unitcountlist}{#1}%
}
```

```

\ifcsundef{glsxtr@theunit@#1}
{%
  \ifcsdef{theH#1}%
  {\csdef{glsxtr@theunit@#1}{\csuse{theH#1}}}%
  {\csdef{glsxtr@theunit@#1}{\csuse{the#1}}}%
}%
{}%
}

\@glsxtr@ifunitcounter

\newcommand*{\@glsxtr@ifunitcounter}[3]{%
  \xifinlist{#1}{\@glsxtr@unitcountlist}{#2}{#3}%
}

\@glsxtr@currentunitcount

\newcommand*\@glsxtr@currentunitcount[1]{%
  glo@glsdetoklabel{#1}@currunit@glsgetattribute{#1}{unitcount}.%
  \csuse{glsxtr@theunit@\glsgetattribute{#1}{unitcount}}%
}

\@glsxtr@previousunitcount

\newcommand*\@glsxtr@previousunitcount[1]{%
  glo@glsdetoklabel{#1}@prevunit@glsgetattribute{#1}{unitcount}.%
  \csuse{glsxtr@theunit@\glsgetattribute{#1}{unitcount}}%
}

\@gls@increment@currunitcount

\newcommand*{\@gls@increment@currunitcount}[1]{%
  \glshasattribute{#1}{unitcount}%
  {%
    \protected@edef\@glsxtr@csname{\@glsxtr@currentunitcount{#1}}%
    \ifcsundef{\@glsxtr@csname}%
    {%
      \csgdef{\@glsxtr@csname}{1}%
      \listcsxadd
      {glo@glsdetoklabel{#1}@unitlist}%
      {\glsgetattribute{#1}{unitcount}.%
        \csuse{glsxtr@theunit@\glsgetattribute{#1}{unitcount}}}%
      }%
    }%
    {%
      \csxdef{\@glsxtr@csname}%
      {\number\numexpr\csname\@glsxtr@csname\endcsname+1}%
    }%
  }%
  {}%
}

\@gls@increment@currunitcount

```

```

\newcommand*{\@gls@local@increment@currunitcount}[1]{%
  \gls@hasattribute{#1}{unitcount}%
  {%
    \protected@edef\@glsxtr@csname{\@glsxtr@currentunitcount{#1}}%
    \ifcsundef{\@glsxtr@csname}%
    {%
      \csdef{\@glsxtr@csname}{1}%
      \listcseadd
        {glo@\glsdetoklabel{#1}@unitlist}%
        {\glsgetattribute{#1}{unitcount}.%
          \csuse{glsxtr@theunit@\glsgetattribute{#1}{unitcount}}}%
    }%
  }%
  {%
    \csedef{\@glsxtr@csname}%
      {\number\numexpr\csname\@glsxtr@csname\endcsname+1}%
  }%
}%
}

```

\@glsxtr@currunitcount

```

\newcommand*{\@glsxtr@currunitcount}[2]{%
  \ifcsundef
    {glo@\glsdetoklabel{#1}@currunit@#2}%
    {0}%
    {\csuse{glo@\glsdetoklabel{#1}@currunit@#2}}%
  }%

```

\@glsxtr@prevunitcount

```

\newcommand*{\@glsxtr@prevunitcount}[2]{%
  \ifcsundef
    {glo@\glsdetoklabel{#1}@prevunit@#2}%
    {0}%
    {\csuse{glo@\glsdetoklabel{#1}@prevunit@#2}}%
  }%

```

\glsenableentryunitcount

```

\newcommand*{\glsenableentryunitcount}{%

```

Enable new fields:

```

  \appto\@newglossaryentry@defcounters{\@@newglossaryentry@defunitcounters}%

```

Just in case the user has switched on the docdef option.

```

  \renewcommand*{\gls@defdocnewglossaryentry}{%
    \renewcommand*{\newglossaryentry}[2]{%
      \PackageError{glossaries}{\string\newglossaryentry\space
        may only be used in the preamble when entry counting has
        been activated}{If you use \string\glsenableentryunitcount\space
        you must place all entry definitions in the preamble not in

```

```

        the document environment}%
    }%
}%

```

New commands to access new fields:

```

\newcommand*{\glentrycurrcount}[1]{%
  \@glxtr@currunitcount{##1}{\glsetattribute{##1}{unitcount}.%
  \csuse{glxtr@theunit@\glsetattribute{##1}{unitcount}}}%
}%
\newcommand*{\glentryprevcount}[1]{%
  \@glxtr@prevunitcount{##1}{\glsetattribute{##1}{unitcount}.%
  \csuse{glxtr@theunit@\glsetattribute{##1}{unitcount}}}%
}%

```

Access total count:

```

\newcommand*{\glentryprevtotalcount}[1]{%
  \ifcsundef{glo@\glsetoklabel{##1}@prevunittotal}%
  {0}%
  {%
    \number\csuse{glo@\glsetoklabel{##1}@prevunittotal}
  }%
}%

```

Access max value:

```

\newcommand*{\glentryprevmaxcount}[1]{%
  \ifcsundef{glo@\glsetoklabel{##1}@prevunitmax}%
  {0}%
  {%
    \number\csuse{glo@\glsetoklabel{##1}@prevunitmax}
  }%
}%

```

Adjust post unset and reset:

```

\let\@glxtr@entryunitcount@org@unset\glxtrpostunset
\renewcommand*{\glxtrpostunset}[1]{%
  \@glxtr@entryunitcount@org@unset{##1}%
  \@gl@increment@currunitcount{##1}%
}%
\let\@glxtr@entryunitcount@org@localunset\glxtrpostlocalunset
\renewcommand*{\glxtrpostlocalunset}[1]{%
  \@glxtr@entryunitcount@org@localunset{##1}%
  \@gl@local@increment@currunitcount{##1}%
}%
\let\@glxtr@entryunitcount@org@reset\glxtrpostreset
\renewcommand*{\glxtrpostreset}[1]{%
  \glshasattribute{##1}{unitcount}%
  {%
    \protected@edef\@glxtr@curname{\@glxtr@currentunitcount{##1}}%
    \ifcsundef{\@glxtr@curname}%
    {}%
    {\ifglresetcurrcount\csgdef{\@glxtr@curname}{0}\fi}%
  }%
}%

```

```

}%
{}%
}%
\let\@glxstr@entryunitcount@org@localreset\glxstrpostlocalreset
\renewcommand*{\glxstrpostlocalreset}[1]{%
  \@glxstr@entryunitcount@org@localreset{##1}%
  \glshasattribute{##1}{unitcount}%
  {%
    \protected@edef\@glxstr@csname{\@glxstr@currentunitcount{##1}}%
    \ifcsundef{\@glxstr@csname}%
    {}%
    {\ifglresetcurrcount\csdef{\@glxstr@csname}{0}\fi}%
  }%
  {}%
}%

```

Modifications to take into account the attributes that govern whether the entry should be unset.

```

\let\@cgl@\@cgl@
\let\@cgl@sp\@cgl@sp

\let\@cgl@G\@cgl@G
\let\@cgl@spG\@cgl@spG
\let\@cgl@S\@cgl@S
\let\@cgl@spS\@cgl@spS

```

Write information to the aux file.

```

\AtEndDocument{\@gl@write@entryunitcounts}%
\renewcommand*{\@gl@entry@unitcount}[3]{%
  \csgdef{glo@\gl@detoklabel{##1}@prevunit@##3}{##2}%
  \ifcsundef{glo@\gl@detoklabel{##1}@prevunittotal}%
  {\csgdef{glo@\gl@detoklabel{##1}@prevunittotal}{##2}}%
  {%
    \csxdef{glo@\gl@detoklabel{##1}@prevunittotal}{%
      \number\numexpr\csuse{glo@\gl@detoklabel{##1}@prevunittotal}+##2}%
    }%
    \ifcsundef{glo@\gl@detoklabel{##1}@prevunitmax}%
    {\csgdef{glo@\gl@detoklabel{##1}@prevunitmax}{##2}}%
    {%
      \ifnum\csuse{glo@\gl@detoklabel{##1}@prevunitmax}<##2
      \csgdef{glo@\gl@detoklabel{##1}@prevunitmax}{##2}%
      \fi
    }%
  }%
  \let\gl@enableentryunitcount\relax
  \renewcommand*{\gl@enableentrycount}{%
    \PackageError{glossaries-extra}{\string\gl@enableentrycount\space
      can't be used with \string\gl@enableentryunitcount}%
    {Use one or other but not both commands}%
  }%
}

```

```

    }
    \@onlypreamble\glsenableentryunitcount

\@gls@entry@unitcount
    \newcommand*{\@gls@entry@unitcount}[3]{}

\gls@write@entryunitcounts@do
    \newcommand*{\@gls@write@entryunitcounts@do}[1]{%
        \immediate\write\@auxout
        {\string\@gls@entry@unitcount
         {\@glsentry}%
         {\@glsxtr@currunitcount{\@glsentry}{#1}%
          }%
         {#1}}%
    }

\@gls@write@entryunitcounts
    \newcommand*{\@gls@write@entryunitcounts}{%
        \immediate\write\@auxout
        {\string\providecommand*{\string\@gls@entry@unitcount}[3]{}%
         \count@=0\relax
         \forallglsentries{\@glsentry}{%
             \glshasattribute{\@glsentry}{unitcount}%
             {%
                 \ifglsused{\@glsentry}%
                 {%
                     \forlistcsloop
                     {\@gls@write@entryunitcounts@do}%
                     {\glo@\@glsdetoklabel{\@glsentry}@unitlist}%
                 }%
             }%
             \advance\count@ by \@ne
         }%
         {}%
     }%
    \ifnum\count@=0
        \GlossariesExtraWarningNoLine{Entry counting has been enabled
        \MessageBreak with \string\glsenableentryunitcount\space but the
        \MessageBreak attribute ‘unitcount’ hasn’t
        \MessageBreak been assigned to any of the defined
        \MessageBreak entries}%
    \fi
}

```

`\glsXtrEnableEntryUnitCounting` The first argument is the list of categories, the second argument is the value of the entrycount attribute and the third is the counter name.

```
\newcommand*{\GlsXtrEnableEntryUnitCounting}[3]{%
```

Enable entry counting:

```
\glsenableentryunitcount
```

Redefine `\gls` etc:

```
\renewcommand*{\gls}{\cglsl}%
\renewcommand*{\Gls}{\cGls}%
\renewcommand*{\glspl}{\cglspl}%
\renewcommand*{\Glspl}{\cGlspl}%
\renewcommand*{\GLS}{\cGLS}%
\renewcommand*{\GLSpl}{\cGLSpl}%
```

Set the entrycount attribute:

```
\@glstr@setentryunitcountunsetattr{#1}{#2}{#3}%
```

In case this command is used again:

```
\let\GlsXtrEnableEntryUnitCounting\@glstr@setentryunitcountunsetattr
\renewcommand*{\GlsXtrEnableEntryUnitCounting}[2]{%
\PackageError{glossaries-extra}{\string\GlsXtrEnableEntryUnitCounting\space
can't be used with \string\GlsXtrEnableEntryUnitCounting}%
{Use one or other but not both commands}}%
}
```

`@setentryunitcountunsetattr`

```
\newcommand*{\@glstr@setentryunitcountunsetattr}[3]{%
\@for\@glstr@cat:=#1\do
{%
\ifdefempty{\@glstr@cat}{}%
{%
\glssetcategoryattribute{\@glstr@cat}{entrycount}{#2}%
\glssetcategoryattribute{\@glstr@cat}{unitcount}{#3}%
}%
}%
}
```

1.3.6 Acronym Modifications

It's more consistent to use the abbreviation code for acronyms, but make some adjustments to allow for continued use of the `glossaries` package's custom acronym format. (For example, user may already have defined some acronym styles with `\newacronymstyle` which they would like to continue to use.) The original `glossaries` acronym code can be restored with `\RestoreAcronyms`, but adjust `\SetGenericNewAcronym` so that `\newacronym` adds the category.

`\SetGenericNewAcronym`

```
\renewcommand*{\SetGenericNewAcronym}{%
```

Make sure `\RestoreAcronyms` has been used.

```
\ifdefequal\@addtoacronymlists\@glstr@org@addtoacronymlists
{%
{%
\GlossariesWarning{\string\SetGenericNewAcronym\space used
without restoring base acronym functions with
\string\RestoreAcronyms}%
```

```

}%
\let\@Gls@entryname\@Gls@acrenentryname
Redefine \newacronym:
\renewcommand{\newacronym}[4][]{%
\ifdefempty{\@glsacronymlists}%
{%
\def\@glo@type{\acronymtype}%
\setkeys{glossentry}{##1}%
\DeclareAcronymList{\@glo@type}%
}%
}%
\glskeylisttok{##1}%
\glslabeltok{##2}%
\glsshorttok{##3}%
\glslongtok{##4}%
\newacronymhook
\protected@edef\@do@newglossaryentry{%
\noexpand\newglossaryentry{\the\glslabeltok}%
{%
type=\acronymtype,%
name={\expandonce{\acronymentry{##2}}},%
sort={\acronymsort{\the\glsshorttok}{\the\glslongtok}},%
text={\the\glsshorttok},%
short={\the\glsshorttok},%
shortplural={\the\glsshorttok\noexpand\acrpluralsuffix},%
long={\the\glslongtok},%
longplural={\the\glslongtok\noexpand\acrpluralsuffix},%
category=acronym,%
\GenericAcronymFields,%
\the\glskeylisttok
}%
}%
\@do@newglossaryentry
}%
\renewcommand*{\acrfullfmt}[3]{%
\glslink[##1]{##2}{\genacrfullformat{##2}{##3}}}%
\renewcommand*{\Acrfullfmt}[3]{%
\glslink[##1]{##2}{\Genacrfullformat{##2}{##3}}}%
\renewcommand*{\ACRfullfmt}[3]{%
\glslink[##1]{##2}{%
\glssupercase{\genacrfullformat{##2}{##3}}}%
}%
\renewcommand*{\acrfullplfmt}[3]{%
\glslink[##1]{##2}{\genplacrfullformat{##2}{##3}}}%
\renewcommand*{\Acrfullplfmt}[3]{%
\glslink[##1]{##2}{\Genplacrfullformat{##2}{##3}}}%
\renewcommand*{\ACRfullplfmt}[3]{%
\glslink[##1]{##2}{%
\glssupercase{\genplacrfullformat{##2}{##3}}}%
}%
\renewcommand*{\glsentryfull}[1]{\genacrfullformat{##1}{}}%

```



```

\renewcommand*{\Glsentryfull}[1]{\Genacrformat{##1}{}}%
\renewcommand*{\glsentryfullpl}[1]{\genplacrformat{##1}{}}%
\renewcommand*{\Glsentryfullpl}[1]{\Genplacrformat{##1}{}}%
}

```

This will cause a problem for glossaries that contain a mixture of acronyms and abbreviations, so redefine `\newacronym` to use the new abbreviation interface.

First save the original definitions:

```

\let\@glstr@org@setacronymstyle\setacronymstyle
\let\@glstr@org@newacronymstyle\newacronymstyle

```

Save the list of acronyms in case they are required.

```

\@glstr@acronymlists

```

```

\let\@glstr@acronymlists\@glstr@acronymlists

```

```

\glstr@org@addtoacronymlists

```

```

\let\@glstr@org@addtoacronymlists\@addtoacronymlists

```

```

\@glstr@org@setacronymlists

```

```

\let\@glstr@org@setacronymlists\SetAcronymLists

```

Need to provide a replacement for `\forallacronyms` since `\@glstr@acronymlists` isn't available.

```

\@glstr@abbrlists

```

```

\newcommand{\@glstr@abbrlists}{}

```

```

\forallabbreviationlists

```

```

\newcommand*{\forallabbreviationlists}[2]{%
  \@for#1:=\@glstr@abbrlists\do{\ifdefempty{#1}{#2}}%
}

```

```

\@glstr@addabbreviationlist

```

```

\newcommand*{\@glstr@addabbreviationlist}[1]{%
  \protected@edef\@glo@type{#1}%
  \ifdefempty\@glstr@abbrlists
  {\let\@glstr@abbrlists\@glo@type}%
  {%
    \ifdefequal\@glstr@abbrlists\@glo@type
    {}%
    {%
      \expandafter\DTLifinlist\expandafter{\@glo@type}{\@glstr@abbrlists}{}%
      {\protected@eappto\@glstr@abbrlists{,\@glo@type}}%
    }%
  }%
}

```

`\forallacronyms` Modify to add warning.

```
\renewcommand*{\forallacronyms}[2]{%
  \@glsxtr@base@acrcmd\forallacronyms\forallabbreviationlists
  \@for#1:=\glsacronymlists\do{\ifx#1@empty\else#2\fi}%
}
```

`\MakeAcronymsAbbreviations` Make acronyms use the same interface as abbreviations. Note that `\newacronymstyle` has a different implementation to `\newabbreviationstyle` so disable `\newacronymstyle` and `\setacronymstyle`.

```
\newcommand*{\MakeAcronymsAbbreviations}{%
```

Undo acronym display style:

```
\@for\@gls@type:=\glsacronymlists\do{%
  \csgdef{gls@\@gls@type @entryfmt}{\glentryfmt}%
}%
```

Save and clear acronym list.

```
\let\@glsxtr@acronymlists\@glsacronymlists
\let\@glsacronymlists@empty
\let\@addtoacronymlists@gobble
\let\SetAcronymLists@gobble
```

Warn if `\acrshort` etc are used.

```
\let\@glsxtr@base@acrcmd\@glsxtr@base@acrcmd@warn
```

Redefine `\newacronym` to use same interface as `\newabbreviation`.

```
\renewcommand*{\newacronym}[4][{}]{%
  \glsxtr@newabbreviation{type=acronymtype,category=acronym,##1}{##2}{##3}{##4}%
}%
\renewcommand*{\firstacronymfont}[1]{\glsfirstabbrvfont{##1}}%
\renewcommand*{\acronymfont}[1]{\glsabbrvfont{##1}}%
\renewcommand*{\setacronymstyle}[1]{%
  \PackageError{glossaries-extra}{\string\setacronymstyle{##1}
  unavailable.
  Use \string\setabbreviationstyle[acronym]\space instead.
  The original acronym interface can be restored with
  \string\RestoreAcronyms}{}%
}%
\renewcommand*{\newacronymstyle}[1]{%
  \GlossariesExtraWarning{New acronym style ‘##1’ won’t be
  available unless you restore the original acronym interface with
  \string\RestoreAcronyms}%
  \@glsxtr@org@newacronymstyle{##1}%
}%
}
```

Switch acronyms to abbreviations:

```
\MakeAcronymsAbbreviations
```

`\RestoreAcronyms` Restore acronyms to glossaries interface.

```
\newcommand*{\RestoreAcronyms}{%
```

Restore acronym list.

```
\let\@glsacronymlists\@glsxtr@acronymlists
\let\@addtoacronymlists\@glsxtr@org@addtoacronymlists
\let\SetAcronymLists\@glsxtr@org@setacronymlists
```

Suppress warnings if \acrshort etc are used.

```
\let\@glsxtr@base@acrcmd\@gobbletwo
```

Restore acronym display style:

```
\@for\@gls@type:=\@glsacronymlists\do{%
  \SetDefaultAcronymDisplayStyle{\@gls@type}%
}%
```

Switch to the generic acronym mechanism.

```
\SetGenericNewAcronym
\renewcommand{\firstacronymfont}[1]{\acronymfont{##1}}%
\renewcommand{\acronymfont}[1]{##1}%
\let\setacronymstyle\@glsxtr@org@setacronymstyle
\let\newacronymstyle\@glsxtr@org@newacronymstyle
```

Need to restore the original definition of \@gls@link@checkfirsthyper but \glsxtrifwasfirstuse still needs setting for the benefit of the post-link hook.

```
\renewcommand*\@gls@link@checkfirsthyper{%
  \ifglsused{\glslabel}%
  {\let\glsxtrifwasfirstuse\@secondoftwo}
  {\let\glsxtrifwasfirstuse\@firstoftwo}%
  \@glsxtr@org@checkfirsthyper
}
\glssetcategoryattribute{acronym}{regular}{false}%
\setacronymstyle{long-short}%
}
```

\glsacspace Allow the user to customise the maximum value.

```
\renewcommand*\@glsacspace}[1]{%
  \glsmeasurewidth{\dimen@}{(\@firstacronymfont{\glsentryshort{#1}})}%
  \ifdim\dimen@<\glsacspacemax~\else\space\fi
}
```

\glsacspacemax Value used in the above.

```
\newcommand*\@glsacspacemax{3em}
```

\glsabspace Similar to \glsacspace but includes inner formatting.

```
\newrobustcmd*\@glsabspace}[1]{%
  \glsmeasurewidth{\dimen@}{(\@glsfirstabbrvfont{\glsentryshort{#1}})}%
  \ifdim\dimen@<\glsacspacemax
    \glsxtrgenentrytextfmt{~}%
  \else
    \glsxtrgenentrytextfmt{ }%
  \fi
}
```

1.3.7 Indexing and Displaying Glossaries

From time-to-time users ask if they can have one glossary sorted normally and another sorted by definition or usage. With the base `glossaries` package this can only be achieved with the “`noidx`” commands (Option 1). This is an attempt to mix and match.

First we need a list of the glossaries that require `makeindex`/`xindy`.

```
\@glstr@reg@glosslist
```

```
\newcommand*{\@glstr@reg@glosslist}{}
```

Save the original definition of `\makeglossaries`:

```
\let\@glstr@org@makeglossaries\makeglossaries
```

`saries@warn@noprintglossary` This command was only introduced to `glossaries` v4.47 so it may not be defined.

```
\providecommand\@makeglossaries@warn@noprintglossary{%
  \ifdefstring{\@glo@types}{,}%
  {%
    \GlossariesWarningNoLine{No glossaries have been defined}%
  }%
  {%
    \GlossariesWarningNoLine{No \string\printglossary\space
      or \string\printglossaries\space
      found. ^^J(Remove \string\makeglossaries\space if you
      don't want any glossaries.) ^^JThis document will not
      have a glossary}%
  }%
}%
```

`\@domakeglossaries` `glossaries` v4.45 introduced `\@domakeglossaries` to provide a way of disabling `\makeglossaries`. If it hasn't been defined, define here to do its argument:

```
\providecommand{\@domakeglossaries}[1]{#1}
```

`\@gls@automake@types` Added to `glossaries` v4.50 so may not be defined.

```
\providecommand{\@gls@automake@types}{\@glo@types}
```

Redefine `\makeglossaries` to take an optional argument. This should be empty for the usual behaviour (all glossaries need processing with an indexing application) or a comma-separated list of glossary labels indicating those glossaries that should be processed with an indexing application. The optional argument version shouldn't be used with `record`.

```
\makeglossaries
```

```
\renewcommand*{\makeglossaries}[1][]{%
  \ifx\@glstr@record@setting\@glstr@record@setting@alsoindex
    \edef\glsindexingsetting{bib2gls-\ifglxindy xindy\else makeindex\fi}%
  \else
    \ifglxindy
      \def\glsindexingsetting{xindy}%
    \fi
  }
```

```

\else
\def\glsindexingsetting{makeindex}%
\fi
\fi
\@domakeglossaries
{%
\@glsxtr@if@record@only
{%
\PackageError{glossaries-extra}{\string\makeglossaries\space
not permitted\MessageBreak with record=\@glsxtr@record@setting\space
package option}%
{You may only use \string\makeglossaries\space with
record=off or record=hybrid options}%
}%
{%
\ifblank{#1}%
{%
\@glsxtr@org@makeglossaries

\ifx\@glsxtr@record@setting\@glsxtr@record@setting@alsoindex
\let\warn@noprntglossary\@glsxtr@warn@hybrid@noprntgloss
\fi
}%
{%
\ifx\@glsxtr@record@setting\@glsxtr@record@setting@alsoindex
\PackageError{glossaries-extra}{\string\makeglossaries[#1]\space
not permitted\MessageBreak with record=\@glsxtr@record@setting\space package option}%
{You may only use the hybrid \string\makeglossaries[...]\space with
record=off option}%
\else
\appto\glsindexingsetting{-noidx}%
\@gls@@automake@immediate was introduced to glossaries v4.42 so it may not
be defined.

\protected@edef\@glsxtr@reg@glosslist{#1}%
\@gls@@automake@immediate uses \@gls@automake@types as from v4.50. Older
versions use \@glo@types which will include the noidx glossaries.

\let\@gls@automake@types\@glsxtr@reg@glosslist
\ifdef\@gls@@automake@immediate{\@gls@@automake@immediate}{}%
\ifundef{\glswrite}{\newwrite\glswrite}{}%
\protected@write\@auxout{}{\string\providecommand
\string\@glsorder[1]{} }
\protected@write\@auxout{}{\string\providecommand
\string\@istfilename[1]{} }
\protected@write\@auxout{}{\string\@istfilename{\istfilename}}%
\protected@write\@auxout{}{\string\@glsorder{\glsorder}}
\protected@write\@auxout{}{\string\glsxtr@makeglossaries{#1}}
\write\@auxout{\string\providecommand\string\@gls@reference[3]{} }%

```

Iterate through each supplied glossary type and activate it.

```

\@for\@glo@type:=#1\do{%
\ifdefempty{\@glo@type}{\@makeglossary{\@glo@type}}%
}%

```

New glossaries must be created before `\makeglossaries`:

```

\renewcommand*\newglossary[4][]{%
\PackageError{glossaries}{New glossaries
must be created before \string\makeglossaries}{You need
to move \string\makeglossaries\space after all your
\string\newglossary\space commands}}%

```

Any subsequent instances of this command should have no effect.

```

\let\@makeglossary\gobble

```

Version 1.42 removed letting `\makeglossary` to `\relax` (no kernel redefs may be in effect).

```

\renewcommand\makeglossaries[1][]{}%

```

Disable all commands that have no effect after `\makeglossaries`

```

\@disable@onlypremakeg

```

Allow see key:

```

\let\gls@checkseeallowed\relax

```

Adjust `\@do@seeglossary`. This needs to check for the entry's existence but don't increment associated counter.

```

\renewcommand*\@do@seeglossary}[2]{%
\glsdoifexists{##1}%
{%
\protected@edef\@gls@label{\glsdetoklabel{##1}}%
\protected@edef\@gls@type{\csname glo@\@gls@label @type\endcsname}%
\expandafter\DTLifinlist\expandafter{\@gls@type}{\@glsxtr@reg@glosslist}%
{\@glsxtr@org@doseeglossary{##1}{##2}}%
}%
\@glsxtrwrglossmark
\protected@write\@auxout{}{%
\string\@gls@reference
{\@gls@type}{\@gls@label}{\string\glsseeformat##2}}%
}%
\@gls@noidx@addtorefs{\@gls@label}%
}%
}%

```

Adjust `\@do@wrglossary`

```

\let\@glsxtr@do@wrglossary\@do@wrglossary
\def\@do@wrglossary{%
\protected@edef\@gls@type{\csname glo@\@gls@label @type\endcsname}%
\expandafter\DTLifinlist\expandafter{\@gls@type}{\@glsxtr@reg@glosslist}%
{\@glsxtr@do@wrglossary}%
{\@gls@noidx@glossary}%
}%

```

Suppress warning about no `\makeglossaries`

```
\let\warn@nomakeglossaries\relax
\let\warn@noprintglossary\@makeglossaries@warn@noprintglossary
```

Only warn for glossaries not listed.

```
\renewcommand{\@gls@noref@warn}[1]{%

\protected@edef\@gls@type{##1}%
\expandafter\DTLifinlist\expandafter{\@gls@type}{\@glsxtr@reg@glosslist}%
{%
\GlossariesExtraWarning{Can't use
\string\printnoidxglossary[type={\@gls@type}]
when '\@gls@type' is listed in the optional argument of
\string\makeglossaries}%
}%
}%
\GlossariesWarning{Empty glossary for
\string\printnoidxglossary[type={##1}].
Rerun may be required (or you may have forgotten to use
commands like \string\gls)}%
}%
}%
```

Adjust display number list to check for type:

```
\renewcommand*{\glsdisplaynumberlist}[1]{%
\expandafter\DTLifinlist\expandafter{##1}{\@glsxtr@reg@glosslist}%
{\@glsxtr@idx@displaynumberlist{##1}}%
{\@glsxtr@noidx@displaynumberlist{##1}}%
}%
```

Adjust entry list:

```
\renewcommand*{\glsentrynumberlist}[1]{%
\expandafter\DTLifinlist\expandafter{##1}{\@glsxtr@reg@glosslist}%
{\@glsxtr@idx@entrynumberlist{##1}}%
{\@glsxtr@noidx@entrynumberlist{##1}}%
}%
```

Adjust number list loop

```
\renewcommand*{\glsnumberlistloop}[2]{%
\expandafter\DTLifinlist\expandafter{##1}{\@glsxtr@reg@glosslist}%
{%
\PackageError{glossaries-extra}{\string\glsnumberlistloop\space
not available for glossary '##1'}{%
}%
{\@glsxtr@noidx@numberlistloop{##1}{##2}}%
}%
```

Only sanitize sort for normal indexing glossaries.

```
\renewcommand*{\glsprestandardsort}[3]{%
\expandafter\DTLifinlist\expandafter{##2}{\@glsxtr@reg@glosslist}%
{%
\glsdosanitizesort
```

```

}%
{%
  \ifglssanitizesort
  \@gls@noidx@sanitizesort
  \else

  \@@gls@noidx@nosanitizesort
  \fi
}%
}%

```

Unlike `\makenoidxglossaries` we can't automatically set `sanitizesort=false`. All entries must be defined in the preamble.

```

\renewcommand*\new@glossaryentry[2]{%
  \PackageError{glossaries-extra}{Glossary entries must be defined
    in the preamble\MessageBreak when you use the optional argument
    of \string\makeglossaries}{Either move your definitions to the
    preamble or don't use the optional argument of
    \string\makeglossaries}%
}%

```

Only activate sort key for glossaries that aren't listed in #1 (glossary label is stored in `\@glo@type` but this defaults to `\glsdefaulttype` so some expansion is required).

```

\let\@glo@assign@sortkey\@glxtr@mixed@assign@sortkey
\renewcommand*\@printgloss@setsort{%

```

Need to extract just the type value.

```

\expandafter\@glxtr@gettype\expandafter,\@glxtr@printglossopts,%
  type=\glsdefaulttype,\@end@glxtr@gettype
\def\@glo@sorttype{\@glo@default@sorttype}%
}%

```

Check automake setting:

```

\ifglsautomake
\renewcommand*\@gls@doautomake{%
  \for\@gls@type:=\@glxtr@reg@glosslist\do{%
    \ifdefempty{\@gls@type}{\@gls@automake{\@gls@type}}%
  }%
}%
\fi

```

Check the sort setting (glossaries v4.30 onwards):

```

\ifdef\@glo@check@sortallowed{\@glo@check@sortallowed\makeglossaries}{}%

```

Version 1.6: add rerun check if it's defined.

```

\ifdef\GlsNoIdxDoRerunCheck
{\AtEndDocument{\GlsNoIdxDoRerunCheck}}%
}%
\fi
}%

```


Prohibit the use of `\glxtrnoidxgroups`.

```
\prohibit@glxtrnoidxgroups
```

Activate warnings for incompatible options.

```
\let\gls@warn@makegloss@incompatible\@gls@warn@makegloss@incompatible
}%
}%
}
```

```
@warn@makegloss@incompatible
```

```
\newcommand*{\gls@warn@makegloss@incompatible}[2]{}
```

```
@warn@makegloss@incompatible
```

```
\newcommand*{\@gls@warn@makegloss@incompatible}[2]{%
#2\GlossariesExtraWarning{#1\space is incompatible with \string\makeglossaries}%
}
```

The optional argument version of `\makeglossaries` needs an adjustment to `\@printglossary` to allow `\@glo@assign@sortkey` to pick up the glossary type.

Earlier versions of `glossaries-extra` simply saved the original version of `\@printglossary` with `\let \@glxtr@orgprintglossary`. This was later changed to actually defining `\@glxtr@orgprintglossary` to something similar with some alterations to allow for ignored glossaries, which don't have an associated title and to by-pass the existence check with `\ifglossaryexists` which doesn't recognise ignored glossaries. (`bib2gls` writes `\provideignoredglossary` to the `glstex` file for some settings, so the glossary might not been defined on the first `LATEX` run and it needs to be allowed with `\printunsrtglossary` on subsequent runs.)

Unfortunately, removing the existence check will cause an error if `\printglossary` is used with an ignored glossary.

As from `glossaries` v4.46, some new commands have been included to allow the existence check to be varied depending on whether or not ignored glossaries should be allowed, so check for them:

```
@glxtr@printgloss@checkexists
```

```
\ifdef\@printgloss@checkexists
{\newcommand{\glxtr@printgloss@checkexists}{\@printgloss@checkexists}}
{\newcommand{\glxtr@printgloss@checkexists}[2]{#2}}
```

`\@glxtr@orgprintglossary` (This command is also used for on-the-fly setting.)

```
\newcommand*{\@glxtr@orgprintglossary}[2]{%
\def\@glo@type{\glsdefaulttype}%
```

Add check here.

```
\def\glossarytitle{%
\ifcsdef{@glo@type@\@glo@type @title}%
{\csuse{@glo@type@\@glo@type @title}}%
```

```

    {\glossaryname}}}%
\def\glossarytoctitle{\glossarytitle}%
\let\org@glossarytitle\glossarytitle
\def\@glossarystyle{%
  \ifx\@glossary@default@style\relax
    \GlossariesWarning{No default glossary style provided \MessageBreak
      for the glossary '\@glo@type'. \MessageBreak
      Using fallback. \MessageBreak
      To fix this set the style with \MessageBreak
      \string\setglossarystyle\space or use the \MessageBreak
      style key=value option}%
  \fi
}%
\def\gls@dotoc{title{\glssettoctitle{\@glo@type}}}%
\let\org@glossaryentrynumbers\glossaryentrynumbers
\bgroup
  \@printgloss@setsort
  \setkeys{printgloss}{#1}%
  \ifx\glossarytitle\org@glossarytitle
  \else
    \cslet{\@glo@type@\@glo@type @title}{\glossarytitle}%
  \fi
  \let\currentglossary\@glo@type
  \let\org@glossaryentrynumbers\glossaryentrynumbers
  \let\glsnonextpages\@glsnonextpages
  \let\glsnextpages\@glsnextpages

  \glsxtractivatenopost
  \gls@dotoc{title
  \@glossarystyle
  \let\gls@org@glossaryentryfield\glossentry
  \let\gls@org@glossarysubentryfield\subglossentry
  \renewcommand{\glossentry}[1]{%
    \protected@xdef\glscurrententrylabel{\glsdetoklabel{##1}}%
    \gls@org@glossaryentryfield{##1}%
  }%
  \renewcommand{\subglossentry}[2]{%
    \protected@xdef\glscurrententrylabel{\glsdetoklabel{##2}}%
    \gls@org@glossarysubentryfield{##1}{##2}%
  }%
  \@gls@preglossaryhook
  \glsxtr@printgloss@checkexists{\@glo@type}{#2}%
\egroup
\global\let\glossaryentrynumbers\org@glossaryentrynumbers
\global\let\warn@noprintglossary\relax
}

```

\glsxtractivatenopost Change \nopostdesc and \glsxtrnopostpunc to behave as they do in the glossary.

```
\newcommand*{\glsxtractivatenopost}{%
```

```

\let\nopostdesc\@nopostdesc
\let\glxtrnopostpunc\@glxtrnopostpunc
}

\glxtrnopostpunc
\newrobustcmd*{\glxtrnopostpunc}{%

\@glxtrnopostpunc Provide a command that works like \nopostdesc but only switches off the
punctuation without suppressing the post-description hook.
\newcommand{\@glxtrnopostpunc}{%
\let\@glxtr@org@postdescription\glspostdescription
\ifglsnopostdot
\renewcommand{\glspostdescription}{%
\glsnopostdottrue
\let\glspostdescription\@glxtr@org@postdescription
\let\glxtrrestorepostpunc\@glxtr@restore@postpunc
\glxtrpostdescription
\@glxtrnopostpunc@postdesc}%
\else
\renewcommand{\glspostdescription}{%
\let\glspostdescription\@glxtr@org@postdescription
\let\glxtrrestorepostpunc\@glxtr@restore@postpunc
\glxtrpostdescription
\@glxtrnopostpunc@postdesc}%
\fi
\glsnopostdotfalse
}

\@glxtrnopostpunc@postdesc
\newcommand*{\@glxtrnopostpunc@postdesc}{%

\@glxtr@restore@postpunc
\newcommand*{\@glxtr@restore@postpunc}{%
\def\@glxtrnopostpunc@postdesc{%
\@glxtr@org@postdescription
\let\@glxtrnopostpunc@postdesc\@empty
\let\glxtrrestorepostpunc\@empty
}%
}

\glxtrrestorepostpunc Does nothing outside of glossary.
\newcommand*{\glxtrrestorepostpunc}{%

\@printglossary Redefine.
\renewcommand{\@printglossary}[2]{%
\def\@glxtr@printglossopts{#1}%
\@glxtr@orgprintglossary{#1}{#2}%
}

```

Add a key that switches off the entry targets:

```
\define@choicekey{printgloss}{target}
[{\@glxtr@printglossval\@glxtr@printglossnr}]%
{true,false}[true]%
{%
  \ifcase\@glxtr@printglossnr
    \def\@glstarget{\@glsdohypertarget}%
  \else
    \let\@glstarget\@secondoftwo
  \fi
}
```

`\@glxtrhypernameprefix`

```
\newcommand{\@glxtrhypernameprefix}{}

New to v1.20:
\define@key{printgloss}{targetnameprefix}{%
  \renewcommand{\@glxtrhypernameprefix}{#1}%
}

\define@key{printgloss}{prefix}{%
  \renewcommand{\@glolinkprefix}{#1}%
}

\define@key{printgloss}{label}{%
  \glxtrsetglossarylabel{#1}%
}

\define@key{printgloss}{preamble}{%
  \renewcommand{\@glossarypreamble}{#1}%
}

\define@key{printgloss}{postamble}{%
  \renewcommand{\@glossarypostamble}{#1}%
}
```

`\glxtrsetglossarylabel` Set the label for subsequent glossaries. If the label is fixed (that is, doesn't change with each glossary) this will need to be scoped or changed again to prevent duplicate labels.

```
\newcommand{\glxtrsetglossarylabel}[1]{%
  \ifstrepty{#1}%
  {%
    \renewcommand*{\@glossaryseclabel}{}%
  }%
  {%
    \renewcommand*{\@glossaryseclabel}{%
      \protected@edef\@currentlabelname{\glossarytoctitle}%
      \label{#1}%
    }%
  }%
}
```

\@glxtr@leveloffset

\newcount\@glxtr@leveloffset

New to v1.44:

```
\define@key{printgloss}{leveloffset}{%
  \@glxtr@assign@leveloffset#1\relax
  \gls@warn@noidxmakegloss@incompatible{option 'leveloffset'}
  {\@glxtr@leveloffset=0\relax}%
}
```

\@glxtr@assign@leveloffset

```
\newcommand*{\@glxtr@assign@leveloffset}{%
  \@ifnextchar+{\p@glxtr@assign@leveloffset}{\np@glxtr@assign@leveloffset}%
}
```

\p@glxtr@assign@leveloffset Discard initial "+" character.

```
\newcommand*{\p@glxtr@assign@leveloffset}[1]{%
  \@ifnextchar+{\pp@glxtr@assign@leveloffset}{\np@glxtr@assign@leveloffset}%
}
```

\np@glxtr@assign@leveloffset

```
\def\np@glxtr@assign@leveloffset#1\relax{\@glxtr@leveloffset=#1\relax}
```

\pp@glxtr@assign@leveloffset

```
\def\pp@glxtr@assign@leveloffset#1\relax{\advance\@glxtr@leveloffset by #1\relax}
```

```
\define@boolkey{printgloss}[glxtr@printgloss@]{groups}[true]{%
  \ifglxtr@printgloss@groups
  \else
    \gls@warn@noidxmakegloss@incompatible{option 'groups'}%
    {\glxtr@printgloss@groupstrue}%
  \fi
}
\glxtr@printgloss@groupstrue

\define@boolkey{printgloss}[glxtr@printgloss@]{flatten}[true]{%
  \ifglxtr@printgloss@flatten
  \gls@warn@noidxmakegloss@incompatible{option 'flatten'}%
  {\glxtr@printgloss@flattenfalse}%
  \fi
}
\glxtr@printgloss@flattenfalse
```

\glsdohypertarget Redefine to insert \@glxtrhypertextprefix before the target name.

```
\let\@glxtr@org@glsdohypertarget\glsdohypertarget
\renewcommand{\glsdohypertarget}[2]{%
  \@glxtr@org@glsdohypertarget{\@glxtrhypertextprefix#1}{#2}%
}
```

Update `\@glstarget` to use `\def` instead being assigned with `\let` so that it can pick up the new definition and allow any further redefinitions:

```
\ifx\@glstarget\@glxtr@org@glsdohypertarget
\def\@glstarget{\glsdohypertarget}%
\fi
```

`\@glxtr@do@org@target` Provide a way to locally do the original.

```
\newcommand{\@glxtr@do@org@target}[2]{%
{%
\let\glsdohypertarget\@glxtr@org@glsdohypertarget
\@glstarget{#1}{#2}%
}%
}
```

`\glxtr@makeglossaries` For the benefit of `makeglossaries`

```
\newcommand*{\glxtr@makeglossaries}[1]{}
```

`\@glxtr@gettype` Get just the type.

```
\def\@glxtr@gettype#1,type=#2,#3\end@glxtr@gettype{%
\def\@glo@type{#2}%
}
```

`\@glxtr@mixed@assign@sortkey` Assign the sort key.

```
\newcommand\@glxtr@mixed@assign@sortkey[1]{%
\protected@edef\@glo@type{\@glo@type}%
\expandafter\DTLifinlist\expandafter{\@glo@type}{\@glxtr@reg@glosslist}%
{%
\@glo@no@assign@sortkey{#1}%
}%
{%
\@glo@assign@sortkey{#1}%
}%
}%
```

Display number list for the regular version:

`\glxtr@idx@displaynumberlist`

```
\let\@glxtr@idx@displaynumberlist\glstdisplaynumberlist
```

Display number list for the “noidx” version:

`\@glxtr@noidx@displaynumberlist`

```
\newcommand*{\@glxtr@noidx@displaynumberlist}[1]{%
\letcs{\@gls@loclist}{glo@\glstdetoklabel{#1}@loclist}%
\ifdef\@gls@loclist
{%
\def\@gls@noidxloclist@sep{%
\def\@gls@noidxloclist@sep{%
\def\@gls@noidxloclist@sep{%
```

```

        \glsnumlistsep
    }%
    \def\@gls@noidxloclist@finalsep{\glsnumlistlastsep}%
}%
}%
\def\@gls@noidxloclist@finalsep{}%
\def\@gls@noidxloclist@prev{}%
\forlistloop{\glsnoidxdisplayloclisthandler}{\@gls@loclist}%
\@gls@noidxloclist@finalsep
\@gls@noidxloclist@prev
}%
{%

    \glsxtrundefrag
    \glsdoifexists{#1}%
    {%
        \GlossariesWarning{Missing location list for ‘#1’. Either
            a rerun is required or you haven’t referenced the entry.}%
    }%
}%
}%

```

And for the number list loop:

`\glsxtr@noidx@numberlistloop`

```

\newcommand*{\@glsxtr@noidx@numberlistloop}[3]{%
    \letcs{\@gls@loclist}{glo\@glsdetoklabel{#1}@loclist}%
    \let\@gls@org@glsnoidxdisplayloc\glsnoidxdisplayloc
    \let\@gls@org@glsseeformat\glsseeformat
    \let\@glsnoidxdisplayloc#2\relax
    \let\@glsseeformat#3\relax
    \ifdef\@gls@loclist
    {%
        \forlistloop{\glsnoidxnumberlistloophandler}{\@gls@loclist}%
    }%
    {%

        \glsxtrundefrag
        \glsdoifexists{#1}%
        {%
            \GlossariesWarning{Missing location list for ‘##1’. Either
                a rerun is required or you haven’t referenced the entry.}%
        }%
    }%
    \let\@glsnoidxdisplayloc\@gls@org@glsnoidxdisplayloc
    \let\@glsseeformat\@gls@org@glsseeformat
}%

```

Same for entry number list.

\glstr@noidx@entrynumberlist

```
\newcommand*{\@glstr@noidx@entrynumberlist}[1]{%
  \letcs{\@gls@loclist}{glo\@glsdetoklabel{#1}@loclist}%
  \ifdef\@gls@loclist
  {%
    \glsnoidxloclist{\@gls@loclist}%
  }%
  {%

    \glstrundeftag
    \glsdoifexists{#1}%
    {%
      \GlossariesWarning{Missing location list for ‘#1’. Either
        a rerun is required or you haven’t referenced the entry.}%
    }%
  }%
}%
```

\@glstr@idx@entrynumberlist

```
\newcommand*{\@glstr@idx@entrynumberlist}[1]{\glsentrynumberlist{#1}}
```

\@gls@noidx@getgrouptitle Patch. Need to take into account new internal token list variable used with new datatool integration.

```
\renewcommand*{\@gls@noidx@getgrouptitle}[2]{%
  \protected@edef\@glstr@titlelabel{#1}%
  \ifvoid\@glstr@titlelabel
  {}%
  {%
    \protected@edef\@glstr@titlelabel{\csuse{glstr@grouptitle@#1}}%
  }%
  \ifvoid{\@glstr@titlelabel}%
  {%
    \ifcsvoid{l__glossaries_noidx_#1_grouptitle_tl}%
    {%
```

Use old method.

```
\DTLifint{#1}%
{%
  \ifnum#1<256\relax
    \edef#2{\char#1\relax}%
  \else
    \edef#2{#1}%
  \fi
}%
{%
  \ifcsundef{#1groupname}%
  {\def#2{#1}}%
  {\letcs#2{#1groupname}}%
}%
}%
```



```

        {%
        \letcs#2{1__glossaries_noidx_#1_grouptitle_tl}%
        }%
    }%
    {%
    \let#2\@glxtr@titlelabel
    }%
}

\glxtr@org@getgrouptitle Save original definition of \@gls@getgrouptitle
\let\glxtr@org@getgrouptitle\@gls@getgrouptitle

\glxtrnoidxgroups Provide the ability to switch from unsrt to noidx code, but only for record=off.
\newcommand*{\glxtrnoidxgroups}{%
\ifdefequal\@glxtr@record@setting\@glxtr@record@setting@off
{%
\let\@gls@getgrouptitle\@gls@noidx@getgrouptitle
\let\glxtr@org@getgrouptitle\@gls@getgrouptitle
}%
{\PackageError{glossaries-extra}{Can't use
\string\glxtrunsrtgrouptonoidx\space with record=\@glxtr@record@setting}
{\string\glxtrunsrtgrouptonoidx\space is only available with record=off}}%
\global\let\prohibit@glxtrnoidxgroups\@glxtrnoidxgroups@nomakegloss
}

sxnoidxgroups@nomakegloss
\newcommand{\@glxtrnoidxgroups@nomakegloss}{%
\PackageError{glossaries-extra}{Can't use
\string\glxtrunsrtgrouptonoidx\space with \string\makeglossaries}{%
}

\prohibit@glxtrnoidxgroups
\newcommand{\prohibit@glxtrnoidxgroups}{%
\global\let\glxtrnoidxgroups\@glxtrnoidxgroups@nomakegloss
}

\glxtrgetgrouptitle Provide a user-level command to fetch the group title. The first argument is
the group label. The second argument is a control sequence in which to store
the title.
\newrobustcmd{\glxtrgetgrouptitle}[2]{%
\protected@edef\@glxtr@titlecsname{\glxtr@grouptitle@#1}%
\@onelevel@sanitize\@glxtr@titlecsname
\ifcsdef{\@glxtr@titlecsname}
{\letcs{#2}{\@glxtr@titlecsname}}%
{\glxtr@org@getgrouptitle{#1}{#2}}%
}
\let\@gls@getgrouptitle\glxtrgetgrouptitle

```

`\glstrsetgrouptitle` Sets the title for the given group label.

```
\newcommand{\glstrsetgrouptitle}[2]{%
  \protected@edef\@glstr@titlelabel{\glstr@grouptitle@#1}%
  \@onelevel@sanitize\@glstr@titlelabel
  \protected@csxdef{\@glstr@titlelabel}{#2}%
}
```

`\glstrlocalsetgrouptitle` As above put only locally defines the title.

```
\newcommand{\glstrlocalsetgrouptitle}[2]{%
  \protected@edef\@glstr@titlelabel{\glstr@grouptitle@#1}%
  \@onelevel@sanitize\@glstr@titlelabel
  \protected@csedef{\@glstr@titlelabel}{#2}%
}
```

```
\ifdef\glsnavigationitem
{
```

`\glsnavigationitem`

```
\renewcommand\glsnavigationitem[1]{%
  \glstrgetgrouptitle{#1}{\@gls@grptitle}%
  \glsnavhyperlink{#1}{\@gls@grptitle}%
}
```

```
}
{
```

`\glsnavigation` Redefine to use new user-level command. This patch should not be used with glossaries v4.53+.

```
\renewcommand*{\glsnavigation}{%
  \def\@gls@between{}%
  \ifcsundef\@gls@hypergroup\list\@gls@type{%
    {%
      \def\@gls@list{}%
    }%
    {%
      \expandafter\let\expandafter\@gls@list
      \csname @gls@hypergroup\list\@gls@type\endcsname
    }%
    \@for\@gls@tmp:=\@gls@list\do{%
      \@gls@between
      \glstrgetgrouptitle{\@gls@tmp}{\@gls@grptitle}%
      \glsnavhyperlink{\@gls@tmp}{\@gls@grptitle}%
      \let\@gls@between\glsnavsep
    }%
  }
}
```

`\@print@noidx@glossary` Only redefine if old version (pre v4.57) of glossaries.

```
\ExplSyntaxOn
```

```

\cs_if_exist:NF \__glossaries_print_noidx:
{
  \renewcommand*{\@print@noidx@glossary}{%
    \ifcsdef{@glsref@{\@glo@type}%
      {%
        \ifcsdef{@glo@sortmacro@{\@glo@sorttype}%
          {%
            \csuse{@glo@sortmacro@{\@glo@sorttype}}{\@glo@type}%
          }%
        }%
      }%
      \PackageError{glossaries}{Unknown ~ sort ~ handler ~ ‘\@glo@sorttype’}{}%
    }%
    \glossarysection[\glossarytoctitle]{\glossarytitle}%
    \glossarypreamble
  }

```

Moved this command definition outside of environment in case of scoping issues (e.g. in tabular-like styles).

```

\def\@gls@currentlettergroup{}%
\begin{theglossary}%
\glossaryheader
\glsresetentrylist
\forlistcsloop{\@gls@noidx@do}{\@glsref@{\@glo@type}%
\end{theglossary}%
\glossarypostamble
}%
{}

```

Add section header if there are actually entries defined in this glossary as the document is likely pending a re-run.

```

\glsxtrifemptyglossary{\@glo@type}%
{}%
{\glossarysection[\glossarytoctitle]{\glossarytitle}}%
\@gls@noref@warn{\@glo@type}%
}%
}
}
\ExplSyntaxOff

```

`\glsnoidxdisplayloc` Patch to check for range formations.

```

\renewcommand*{\glsnoidxdisplayloc}[4]{%
  \setentrycounter[#1]{#2}%
  \@glsxtr@display@loc#3\empty\end@glxtr@display@loc{#4}%
}

```

`\@glsxtr@display@loc` Patch to check for range formations.

```

\def\@glsxtr@display@loc#1#2\end@glxtr@display@loc#3{%
  \ifx#1\relax
    \glsxtrdisplaystartloc{#2}{#3}%
  \else
    \ifx#1)\relax

```

```

\glxtrdisplayendloc{#2}{#3}%
\else
\glxtrdisplaysingleloc{#1#2}{#3}%
\fi
\fi
}

```

`\glxtrdisplaysingleloc` Single location.

```

\newcommand*{\glxtrdisplaysingleloc}[2]{%
\csuse{#1}{#2}%
}

```

By default the range identifiers are simply ignored. A custom list loop handler can be defined by the user to test for ranges by checking the definition of `\glxtrlocrangefmt`.

`\glxtrdisplaystartloc` Start of a location range.

```

\newcommand*{\glxtrdisplaystartloc}[2]{%
\protected@edef\glxtrlocrangefmt{#1}%
\ifx\glxtrlocrangefmt\empty
\def\glxtrlocrangefmt{glsnumberformat}%
\fi
\expandafter\glxtrdisplaysingleloc
\expandafter{\glxtrlocrangefmt}{#2}%
}

```

`\glxtrdisplayendloc` End of a location range.

```

\newcommand*{\glxtrdisplayendloc}[2]{%
\protected@edef\@glxtr@tmp{#1}%
\ifdefempty{\@glxtr@tmp}{\def\@glxtr@tmp{glsnumberformat}}{}%
\ifx\glxtrlocrangefmt\@glxtr@tmp
\else
\GlossariesExtraWarning{Mismatched end location range
(start=\glxtrlocrangefmt, end=\@glxtr@tmp)}%
\fi
\expandafter\glxtrdisplayendloohook\expandafter{\@glxtr@tmp}{#2}%
\expandafter\glxtrdisplaysingleloc
\expandafter{\glxtrlocrangefmt}{#2}%
\def\glxtrlocrangefmt{}%
}

```

`\glxtrdisplayendloohook` Allow the user to hook into the end of range command.

```

\newcommand*{\glxtrdisplayendloohook}[2]{}

```

`\glxtrlocrangefmt` Current range format. Empty if not in a range.

```

\newcommand*{\glxtrlocrangefmt}{}

```

`\setentrycounter` Adjust `\setentrycounter` to save the original prefix.

```

\renewcommand*{\setentrycounter}[2][{}]{%

```

```

\def\glxstrcounterprefix{#1}%
\ifx\glxstrcounterprefix\@empty
  \def\@glo@counterprefix{.}%
\else
  \def\@glo@counterprefix{.#1.}%
\fi
\def\gl Sentrycounter{#2}%
}

```

`\@gls@removespaces` Redefine to allow adjustments to location hyperlink.

```

\def\@gls@removespaces#1 #2\@nil{%
  \toks@=\expandafter{\the\toks@#1}%
  \ifx\#2\%

    \edef\@glo@tmp{\the\toks@}%
    \ifx\@glo@tmp\empty
      \else

```

Expand location (just in case `\toks@` is needed for something else).

```

    \expandafter\glxstrlocationhyperlink\expandafter
    \gl Sentrycounter\expandafter\@glo@counterprefix\expandafter{\the\toks@}%
  \fi
\else
  \@gls@ReturnAfterFi{%
    \@gls@removespaces#2\@nil
  }%
\fi
}

```

`\glxstrlocationhyperlink{<counter>}{<prefix>}{<location>}`

`\glxstrlocationhyperlink`

```

\newcommand*{\glxstrlocationhyperlink}[3]{%
  \ifdefined\glxstrsupplocationurl
  {%
    \GlsXtrInternalLocationHyperlink{#1}{#2}{#3}%
  }%
  {%
    \hyperref{\glxstrsupplocationurl}{#1#2#3}{#3}%
  }%
}

```

`\glxstrsupphypernumber`

```

\newcommand*{\glxstrsupphypernumber}[1]{%
  {%
    \glshasattribute{\glscurrententrylabel}{externalallocation}%
  }%
  \def\glxstrsupplocationurl{%
    \glsgetaattribute{\glscurrententrylabel}{externalallocation}}%
}

```

```

}%
{%
\def\glxtrsupplocationurl{%
}%
\glshypernumber{#1}%
}%
}

```

Give a bit of assistance to new users who are confused and don't know how to read transcript messages.

\@print@glossary

```

\renewcommand{\@print@glossary}{%
\makeatletter
\input@{\jobname.\csname @glo@type@\glo@type @in\endcsname}%
\IfFileExists{\jobname.\csname @glo@type@\glo@type @in\endcsname}%
{}%
{\glxtrNoGlossaryWarning{\glo@type}}%
\ifglxindy
\ifcsundef{xdy@\glo@type @language}%
{%
\edef\@do@auxoutstuff{%
\noexpand\AtEndDocument{%
\noexpand\immediate\noexpand\write\@auxout{%
\string\providecommand\string\@xdylanguage[2]{}%
\noexpand\immediate\noexpand\write\@auxout{%
\string\@xdylanguage{\glo@type}{\@xdy@main@language}}%
}%
}%
}%
}%
{\edef\@do@auxoutstuff{%
\noexpand\AtEndDocument{%
\noexpand\immediate\noexpand\write\@auxout{%
\string\providecommand\string\@xdylanguage[2]{}%
\noexpand\immediate\noexpand\write\@auxout{%
\string\@xdylanguage{\glo@type}{\csname @xdy@\glo@type
@language\endcsname}}%
}%
}%
}%
\@do@auxoutstuff
\edef\@do@auxoutstuff{%
\noexpand\AtEndDocument{%
\noexpand\immediate\noexpand\write\@auxout{%
\string\providecommand\string\gls@codepage[2]{}%
\noexpand\immediate\noexpand\write\@auxout{%
\string\gls@codepage{\glo@type}{\gls@codepage}}%
}%
}%
}%
}

```

```

\do@auxoutstuff
\fi
\renewcommand*{\@warn@nomakeglossaries}{%
\GlossariesWarningNoLine{\string\makeglossaries\space
hasn't been used,^^Jthe glossaries will not be updated}%
}%
}

```

Setup the warning text to display if the external file for the given glossary is missing.

`\GlsXtrNoGlsWarningHead` Header message.

```

\newcommand{\GlsXtrNoGlsWarningHead}[2]{%
This document is incomplete. The external file associated with
the glossary ‘#1’ (which should be called \texttt{#2})
hasn't been created.%
}

```

`\GlsXtrNoGlsWarningEmptyStart` No entries have been added to the glossary.

```

\newcommand{\GlsXtrNoGlsWarningEmptyStart}{%
This has probably happened because there are no entries defined
in this glossary.%
}

```

`\GlsXtrNoGlsWarningEmptyMain` The default “main” glossary is empty.

```

\newcommand{\GlsXtrNoGlsWarningEmptyMain}{%
If you don't want this glossary,
add \texttt{nomain} to your package option list when you load
\texttt{glossaries-extra.sty}. For example:%
}

```

`\GlsXtrNoGlsWarningEmptyNotMain` A glossary that isn't the default “main” glossary is empty.

```

\newcommand{\GlsXtrNoGlsWarningEmptyNotMain}[1]{%
Did you forget to use \texttt{type=#1} when you defined your
entries? If you tried to load entries into this glossary with
\texttt{\string\loadglsentries} did you remember to use
\texttt{[#1]} as the optional argument? If you did, check that
the definitions in the file you loaded all had the type set
to \texttt{\string\glsdefaulttype}.%
}

```

`\GlsXtrNoGlsWarningCheckFile` Advisory message to check the file contents.

```

\newcommand{\GlsXtrNoGlsWarningCheckFile}[1]{%
Check the contents of the file \texttt{#1}. If
it's empty, that means you haven't indexed any of your entries in this
glossary (using commands like \texttt{\string\gls} or
\texttt{\string\glsadd}) so this list can't be generated.
If the file isn't empty, the document build process hasn't been
completed.%
}

```

`\GlsXtrNoGlsWarningAutoMake` Message when automake option has been used.

```
\newcommand{\GlsXtrNoGlsWarningAutoMake}[1]{%
  You may need to rerun \LaTeX. If you already have, it may be that
  \TeX's shell escape doesn't allow you to run
  \ifglxindy xindy\else makeindex\fi. Check the
  transcript file \texttt{\jobname.log}. If the shell escape is
  disabled, try one of the following:

  \begin{itemize}
    \item Run the external (Lua) application:

      \texttt{makeglossaries-lite \string\jobname\string}

    \item Run the external (Perl) application:

      \texttt{makeglossaries \string\jobname\string}
  \end{itemize}

  Then rerun \LaTeX\ on this document.
  \GlossariesExtraWarning{Rerun required to build the
  glossary '#1' or check TeX's shell escape allows
  you to run \ifglxindy xindy\else makeindex\fi}%
}
```

`\GlsXtrNoGlsWarningMisMatch` Mismatching `\makenoidxglossaries`.

```
\newcommand{\GlsXtrNoGlsWarningMisMatch}{%
  You need to either replace \texttt{\string\makenoidxglossaries}
  with \texttt{\string\makeglossaries} or replace
  \texttt{\string\printglossary} (or \texttt{\string\printglossaries}) with
  \texttt{\string\printnoidxglossary}
  (or \texttt{\string\printnoidxglossaries}) and then rebuild
  this document.%
}
```

`\GlsXtrNoGlsWarningBuildInfo` Build advice.

```
\newcommand{\GlsXtrNoGlsWarningBuildInfo}{%
  Try one of the following:
  \begin{itemize}
    \item Add \texttt{automake} to your package option list when you load
      \texttt{glossaries-extra.sty}. For example:

      \texttt{\string\usepackage[automake]%
      \glsoverbrace glossaries-extra\glsclosebrace}

    \item Run the external (Lua) application:

      \texttt{makeglossaries-lite.lua \string\jobname\string}

    \item Run the external (Perl) application:
```



```

\texttt{makeglossaries \string\jobname\string"}
\end{itemize}

```

```

Then rerun \LaTeX\ on this document.%
}

```

`\GlsXtrRecordWarning` Paragraph for record=only.

```

\newcommand{\GlsXtrRecordWarning}[1]{%
\texttt{\string\printglossary} doesn't work
with the \texttt{record=\@glxtr@record@setting} package option
use\par\texttt{\string\printunsrtglossary[type=#1]}\par
instead (or change the package option).%
}

```

`\GlsXtrNoGlsWarningTail` Final paragraph.

```

\newcommand{\GlsXtrNoGlsWarningTail}{%
This message will be removed once the problem has been fixed.%
}

```

`\GlsXtrNoGlsWarningNoOut` No out file created. Build advice.

```

\newcommand{\GlsXtrNoGlsWarningNoOut}[1]{%
The file \texttt{#1} doesn't exist. This most likely means you haven't used
\texttt{\string\makeglossaries} or you have used
\texttt{\string\nofiles}. If this is just a draft version of the
document, you can suppress this message using the
\texttt{nomissingglsText} package option.%
}

```

`\GlsXtr@defaultnoglossarywarning`

```

\newcommand*{\@glxtr@defaultnoglossarywarning}[1]{%
\glossarysection[\glossarytoctitle]{\glossarytitle}
\GlsXtrNoGlsWarningHead{#1}{\jobname.\csname @glotype@\@glo@type @in\endcsname}
\par
\glxtrifemptyglossary{#1}%
{%
\GlsXtrNoGlsWarningEmptyStart\space
\ifthenelse{\equal{#1}{main}}{\GlsXtrNoGlsWarningEmptyMain\par
\medskip
\noindent\texttt{\string\usepackage[nomain\ifglacronym ,acronym\fi]}%
\glsopenbrace glossaries-extra\glsclosebrace}
\medskip
}%
{\GlsXtrNoGlsWarningEmptyNotMain{#1}}%
}%
{%
\IfFileExists{\jobname.\csname @glotype@\@glo@type @out\endcsname}
{%
\GlsXtrNoGlsWarningCheckFile

```

```

        {\jobname.\csname @glotype@\@glo@type @out\endcsname}

\ifglautomake

\GlsXtrNoGlsWarningAutoMake{#1}

\else

\ifthenelse{\equal{#1}{main}}{%
  {%
    \GlsXtrNoGlsWarningEmptyMain\par
    \medskip
    \noindent\texttt{\string\usepackage[nomain]%
      \glsoopenbrace glossaries-extra\glsclosebrace}
    \medskip
  }%
  {%
    \ifdefequal\makeglossaries\@no@makeglossaries
    {%
      \GlsXtrNoGlsWarningMisMatch
    }%
    {%
      \GlsXtrNoGlsWarningBuildInfo
    }%
  }%
\fi
}%
{%
  \GlsXtrNoGlsWarningNoOut
  {\jobname.\csname @glotype@\@glo@type @out\endcsname}%
}%
\par
\GlsXtrNoGlsWarningTail
}

\tr@record@noglossarywarning Warn about using \printglossary with record
\newcommand*{\@glxtr@record@noglossarywarning}[1]{%
  \GlossariesExtraWarning{\string\printglossary\space doesn't work\MessageBreak
    with record=\@glxtr@record@setting\space package option\MessageBreak(use
    \string\printunsrtglossary[type=#1])\MessageBreak
    instead (or change the package option)}%
  \glossarysection[\glossarytoctitle]{\glossarytitle}
  \GlsXtrRecordWarning{#1}
  \GlsXtrNoGlsWarningTail
}

```

Provide some commands to accompany the record option for use with **bib2gls**.

\GlsXtrDefaultResourceOptions Default resource options.

```
\newcommand*{\GlsXtrDefaultResourceOptions}{}%
```

`\BibGlsOptions` Supply global `bib2gls` options. Provided as an alternative to using the command line switches, except for those that must be set on startup.

```
\NewDocumentCommand\BibGlsOptions{m}{%
  \protected@write\@auxout{}{\string\bibgls@options{#1}}%
}
\newcommand{\bibgls@options}[1]{%
\@onlypreamble\BibGlsOptions
```

Allowing arbitrary basename for the `.glstex` file can cause conflict if multiple documents use the same basename. This is most likely to occur because the user is simply using `\glstxrresourcefile` as a convenient shortcut to avoid the more lengthy `\GlsXtrLoadResources[src=<bibname>]`. NB if multiple documents need to share the same resource set (including locations), then they should be using the "master" setting.

Therefore, as from v1.55, `\glstxrresourcefile` is deprecated. A new shortcut command is provided as a drop-in replacement and the original `\glstxrresourcefile` is changed to an internal command.

`\glstxrresourcefile` Since it's dangerous for an external application to create a file with a `.tex` extension, as from v1.11 this enforces a `.glstex` extension to avoid conflict.

```
\newcommand*{\glstxrresourcefile}[2][]{%
  \GlossariesExtraWarning{\string\glstxrresourcefile\space is now deprecated
    use \string\glsbibdata[...]{#2} instead}%
  \@glstxr@resourcefile{#1}{#2}%
}
\@onlypreamble\glstxrresourcefile
```

`\glsbibdata`

```
\NewDocumentCommand\glsbibdata{om}{%
  \IfValueTF{#1}{%
    {\GlsXtrLoadResources[src={#2},#1]}%
    {\GlsXtrLoadResources[src={#2}]}%
  }
\@onlypreamble\glsbibdata
```

`\@glstxr@resourcefile` This was the old `\glstxrresourcefile` command.

```
\newcommand*{\@glstxr@resourcefile}[2]{%
  \@glstxr@if@record@only
  {\renewcommand{\glsindexingsetting}{bib2gls}}%
  {\edef\glsindexingsetting{bib2gls-\ifglxindy xindy\else makeindex\fi}}%
```

The record option can't be set after this command.

```
\disable@keys{glossaries-extra.sty}{record}%
\glstxr@writefields
\glstxr@save@mfu
\ifdefempty\GlsXtrDefaultResourceOptions
{%
```

```

\protected@write\@auxout{\glxtrresourceinit}%
{\string\glxtr@resource{#1}{#2}}%
}%
{%
\protected@write\@auxout{\glxtrresourceinit}%
{\string\glxtr@resource{\GlsXtrDefaultResourceOptions,#1}{#2}}%
}%
\let\@glxtr@org@see@noindex\@gl@see@noindex
\let\@gl@see@noindex\relax
\IfFileExists{#2.glstex}%
{%

```

Can't scope `\@input` so save and restore the category code of `@` to allow for internal commands in the location list.

```

\edef\@bibgl@restoreat{\noexpand\catcode\noexpand'\noexpand\@=\number\catcode'\@}%
\makeatletter
\@input{#2.glstex}%
\@bibgl@restoreat

```

If the `record=nameref` option has been set, check if this is supported by the installed version of `bib2gls`.

```

\@glxtr@check@bibgl@nameref
}%
{%
\GlossariesExtraWarning{No file '#2.glstex'}%
}%
\let\@gl@see@noindex\@glxtr@org@see@noindex
}

```

`\@glxtr@check@bibgl@nameref` This will only warn after `bib2gls` has created the `.glstex` file, but there's way to check before.

```

\newcommand{\@glxtr@check@bibgl@nameref}{%
\ifx\@glxtr@record@setting\@glxtr@record@setting@nameref
\ifdef\bibglshrefchar
{}%
{%
\GlossariesExtraWarning{record=nameref requires at least
version 1.8 of bib2gls}%
}%
\fi
\let\@glxtr@check@bibgl@nameref\relax
}

```

`\glxtrresourceinit` Code used during the protected write operation.

```

\newcommand*{\glxtrresourceinit}{}

```

`\glxtrresourcecount`

```

\newcount\glxtrresourcecount

```

`\GlsXtrLoadResources` Short cut that uses `\@glsxtr@resourcefile` with `\jobname` as the mandatory argument.

```
\NewDocumentCommand\GlsXtrLoadResources{0{}}{%
  \ifnum\glsxtrresourcecount=0\relax
    \@glsxtr@resourcefile{#1}{\jobname}%
  \else
    \@glsxtr@resourcefile{#1}{\jobname-\the\glsxtrresourcecount}%
  \fi
  \advance\glsxtrresourcecount by 1\relax
}
\@onlypreamble\GlsXtrLoadResources
```

`\glsxtr@resource`

```
\newcommand*{\glsxtr@resource}[2]{}
```

`\glsxtrMFUsave`

```
\newcommand*{\glsxtrMFUsave}{%
  \ifdef\MFUsave
  {%
    \AtBeginDocument{\MFUsave}%
  }%
  {%
    \GlossariesExtraWarning{mfirstuc.sty too old,
      \string\glsxtrMFUsave\space has no effect. You need to upgrade
      to mfirstuc v2.08}%
  }%
  \let\glsxtrMFUsave\relax
}
```

`\glsxtr@save@mfu`

```
\ifdef\MFUsave
{
  \newcommand*{\glsxtr@save@mfu}{%
    \glsxtrMFUsave
    \let\glsxtr@save@mfu\relax
  }
}
{
  \newcommand*{\glsxtr@save@mfu}{}
}
```

`\glsxtr@fields`

```
\newcommand*{\glsxtr@fields}[1]{}
```

`\glsxtr@texencoding`

```
\newcommand*{\glsxtr@texencoding}[1]{}
```

`\glsxtr@locale` Used to identify all languages tracked in the document.

```
\newcommand*{\glsxtr@locale}[1]{}
```

`\glsxtr@langtag` Identifies the current language at the time `\glsxtr@writefields` is used.

```
\newcommand*\glsxtr@langtag}[1]{}
```

`\glsxtr@pluralsuffixes`

```
\newcommand*\glsxtr@pluralsuffixes}[4]{}
```

`\glsxtr@shortcutsval`

```
\newcommand*\glsxtr@shortcutsval}[1]{}
```

`\glsxtr@linkprefix`

```
\newcommand*\glsxtr@linkprefix}[1]{}
```

`\@gls@runshell` and `\@gls@run@output@dir` new to glossaries v4.55 so may not be defined. If they haven't been defined, provide definitions which will match old behaviour.

```
\ifglsautomake
  \providecommand*\@gls@run@unrestricted@shell}[1]{\immediate\write18{#1}}
  \providecommand*\@gls@run@output@dir}[1]{}
```

`\fi`

`\glsxtr@writefields` This information only needs to be written once, so disable it after it's been used.

```
\newcommand*\glsxtr@writefields{%

  \protected@write\@auxout{%
    {\string\providecommand*\string\glsxtr@fields}[1]{}}%
  \protected@write\@auxout{%
    {\string\providecommand*\string\glsxtr@resource}[2]{}}%
  \protected@write\@auxout{%
    {\string\providecommand*\string\glsxtr@pluralsuffixes}[4]{}}%
  \protected@write\@auxout{%
    {\string\providecommand*\string\glsxtr@shortcutsval}[1]{}}%
  \protected@write\@auxout{%
    {\string\providecommand*\string\glsxtr@linkprefix}[1]{}}%
  \protected@write\@auxout{{\string\glsxtr@fields{\@gls@keymap}}}%

  \protected@write\@auxout{%
    {\string\providecommand*\string\glsxtr@record}[5]{}}%

  \ifx\@glsxtr@record@setting\@glsxtr@record@setting@nameref
    \protected@write\@auxout{%
      {\string\providecommand*\string\glsxtr@record@nameref}[8]{}}%
  \fi
```

If any languages have been loaded, the language tag will be available in `\CurrentTrackedLanguageTag` (provided by `tracklang`). For multilingual documents, the required locale will have to be indicated in the "sort" key when using `\GlsXtrLoadResources`.

```
\ifdef\CurrentTrackedLanguageTag
{%
```

```

\ForEachTrackedDialect{\@glsxtr@currentdialect}{%
  \protected@write\@auxout{}{%
    \string\glsxtr@locale{\GetTrackedLanguageTag\@glsxtr@currentdialect}}%
  }%
  \protected@write\@auxout{}{%
    \string\glsxtr@langtag{\CurrentTrackedLanguageTag}}%
  }%
}%
\protected@write\@auxout{}{\string\glsxtr@pluralsuffixes
  {\glspluralsuffix}{\abbrvpluralsuffix}{\acrpluralsuffix}%
  {\glsxtrabbrvpluralsuffix}}%

\ifvoid\inputencodingname
{%

```

Assume UTF-8.

```

  \protected@write\@auxout{}{\string\glsxtr@texencoding{utf8}}%
}%
}%
  \protected@write\@auxout{}{\string\glsxtr@texencoding{\inputencodingname}}%
}%
  \protected@write\@auxout{}{\string\glsxtr@shortcutsval{\@glsxtr@shortcutsval}}%

```

Prefix deferred until the beginning of the document in case it's redefined later in the preamble. This is picked up by bib2gls when the external option is used.

```

\AtBeginDocument
  {\protected@write\@auxout{}{\string\glsxtr@linkprefix{\glslinkprefix}}}%
\let\glsxtr@writefields\relax

```

If the `automake` option is on, try running bib2gls if the aux file exists. This has to be done before the aux file is opened (so package options `automake=immediate` and `automake=true` are identical if just bib2gls is used). The double-quotes around `\jobname` have been removed (v1.19) since `\jobname` will include double-quotes if the file name has spaces.

```

\ifglsautomake
  \IfFileExists{\jobname.aux}%
  {%
    \@gls@run@unrestricted@shell{bib2gls \@gls@run@output@dir{--dir} \jobname}%
  }%

```

If `\makeglossaries` is also used, allow `makeindex/xindy` to also be run, otherwise disable the error message about requiring `\makeglossaries` with `automake`.

```

  \ifx\@gls@doautomake\@gls@doautomake@err
    \let\@gls@doautomake\relax
  \fi
\fi

```

Check if `order=letter` has been used by mistake (but not if `record=alsoindex` has been used).

```

\@glsxtr@if@record@only
{\ifdefstring{\glsorder}{letter}%

```

```

{\GlossariesExtraWarningNoLine{Package option ‘order=letter’ isn’t
supported with ‘record=\glsxtr@record@setting’. Use ‘break-at=none’
resource option instead}}%
}%
}%
}%
}

```

`\glsxtr@do@automake@err` glossaries v4.50+ now provides `\@gls@do@automake@err` so use that if defined.

```

\ifdef{\@gls@do@automake@err}
{
  \let\@gls@doautomake@err\@gls@do@automake@err
}
{
  \newcommand*{\@gls@doautomake@err}{%
    \PackageError{glossaries}{You must use
    \string\makeglossaries\space with automake=true}
    {%
      Either remove the automake=true setting or
      add \string\makeglossaries\space to your document preamble.%
    }%
  }
}
}

```

Allow locations specific to a particular counter to be recorded.

```

\glsxtr@record
\newcommand*{\glsxtr@record}[5]{%

```

`\glsxtr@record@nameref` Used with `record=nameref` to include current label information.

```

\newcommand*{\glsxtr@record@nameref}[8]{%

```

`\glsxtr@counterrecord` Aux file command.

```

\newcommand*{\glsxtr@counterrecord}[3]{%
  \glsxtrfieldlistgadd{#1}{record.#2}{#3}%
  \glsxtrAddCounterRecordHook{#1}{#2}{#3}%
}

```

`\glsxtrAddCounterRecordHook` User hook.

```

\newcommand*{\glsxtrAddCounterRecordHook}[3]{%

```

`\@glsxtr@counterrecordhook` Hook used by `\@glsxtr@dorecord`.

```

\newcommand*{\@glsxtr@counterrecordhook}{%

```

`\GlsXtrRecordCounter` Activate recording for a particular counter (identified in the argument).

```

\newcommand*{\GlsXtrRecordCounter}[1]{%
  \@glsxtr@recordcounter{#1}%
}
\@onlypreamble\GlsXtrRecordCounter

```


`\@glxtr@docounterrecord`

```
\newcommand*{\@glxtr@docounterrecord}[1]{%
  \@bibgls@write@aux{}\string\glxtr@counterrecord
  {\@glx@label}{#1}{\csuse{the#1}}}%
}
```

`\glxtrglossentry` Users may prefer to have entries displayed throughout the document rather than gathered together in a list. This command emulates the way `\glossentry` behaves (without the style formatting commands like `\item`). This needs to define `\currentglossary` to the current glossary type (normally set at the start of `\@printglossary`) and needs to define `\glscurrententrylabel` to the entry's label (normally set before `\glossentry` and `\subglossentry`). This needs some protection in case it's used in a section heading.

```
\newcommand*{\glxtrglossentry}[1]{%
  \glxtrtitleorpdforheading
  {\@glxtrglossentry{#1}}%
  {\GlsXtrStandaloneEntryPdfName{#1}}%
  {\GlsXtrStandaloneEntryHeadName{#1}}%
}
```

`\@glxtrglossentry` Another test is needed in case `\@glxtrglossentry` has been written to the table of contents.

```
\newrobustcmd*{\@glxtrglossentry}[1]{%
  \glxtrtitleorpdforheading
  {%
    \glsdofexists{#1}%
    {%
      \begingroup

      \protected@edef\glscurrententrylabel{\glsetoklabel{#1}}%
      \protected@edef\currentglossary{\GlsXtrStandaloneGlossaryType}%
      \ifglshasparent{#1}%
        {\GlsXtrStandaloneSubEntryItem{#1}}%
        {\glsentryitem{#1}}%
        \GlsXtrStandaloneEntryName{#1}%
      \endgroup
    }%
  }%
  {\GlsXtrStandaloneEntryPdfName{#1}}%
  {\GlsXtrStandaloneEntryHeadName{#1}}%
}
```

`\GlsXtrStandaloneEntryHeadName`

```
\newcommand*{\GlsXtrStandaloneEntryHeadName}[1]{%
  \glxtrheadname{#1}%
}
```

`\GlsXtrStandaloneEntryPdfName`

```
\newcommand*{\GlsXtrStandaloneEntryPdfName}[1]{%
```

```

        \glsentryname{#1}%
    }

\GlsXtrStandaloneEntryName
    \newcommand*{\GlsXtrStandaloneEntryName}[1]{%
        \glstarget{#1}{\glossentryname{#1}}%
    }

\Glsxtrglossentry As \glsxtrglossentry but sentence case.
    \newcommand*{\Glsxtrglossentry}[1]{%
        \glsxtrtitleorpdforheading
        {\@Glsxtrglossentry{#1}}%
        {\GlsXtrStandaloneEntryPdfNameFirstUc{#1}}%
        {\GlsXtrStandaloneEntryHeadNameFirstUc{#1}}%
    }

\@Glsxtrglossentry
    \newrobustcmd*{\@Glsxtrglossentry}[1]{%
        \glsxtrtitleorpdforheading
        {%
            \glsdoifexists{#1}%
            {%
                \begingroup
                    \protected@edef\glscurrententrylabel{\glsdetoklabel{#1}}%
                    \protected@edef\currentglossary{\GlsXtrStandaloneGlossaryType}%
                    \ifglshasparent{#1}%
                        {\GlsXtrStandaloneSubEntryItem{#1}}%
                        {\glsentryitem{#1}}%
                    \GlsXtrStandaloneEntryNameFirstUc{#1}%
                \endgroup
            }%
        }%
        {\GlsXtrStandaloneEntryPdfNameFirstUc{#1}}%
        {\GlsXtrStandaloneEntryHeadNameFirstUc{#1}}%
    }

\GlsXtrStandaloneEntryHeadNameFirstUc
    \newcommand*{\GlsXtrStandaloneEntryHeadNameFirstUc}[1]{%
        \Glsxtrheadname{#1}%
    }

\GlsXtrStandaloneEntryPdfNameFirstUc Requires new expandable version of \Glsentryname.
    \newcommand*{\GlsXtrStandaloneEntryPdfNameFirstUc}[1]{%
        \Glsentryname{#1}%
    }

\GlsXtrStandaloneEntryNameFirstUc
    \newcommand*{\GlsXtrStandaloneEntryNameFirstUc}[1]{%
        \glstarget{#1}{\Glossentryname{#1}}%
    }

```

`\GlsXtrStandaloneGlossaryType` To make it easier to adjust the definition of `\currentglossary` within `\glstrglossentry`, this expands to the default definition. (If redefined, it must fully expand to the appropriate label.)

```
\newcommand{\GlsXtrStandaloneGlossaryType}{\glsenentrytype{\glscurrententrylabel}}
```

`\GlsXtrStandaloneSubEntryItem` Used for sub-entries in standalone format. The argument is the entry's label.

```
\newcommand*{\GlsXtrStandaloneSubEntryItem}[1]{%
  \GlsXtrIfFieldEqNum{level}{#1}{1}{\glssubentryitem{#1}}{}%
}
```

`\glstrglossentryother` As `\glstrglossentry` but uses a different field. First argument is code to use in the header. The second argument is the entry's label. The third argument is the internal field label. This needs to be expandable in case it occurs in a sectioning command so it can't have an optional argument.

```
\newcommand*{\glstrglossentryother}[3]{%
  \ifstrempy{#1}%
  {%
    \glstrtitleorpdforheading
    {\@glstrglossentryother{#2}{#3}{\GlsXtrStandaloneEntryHeadOther{#3}{#2}}}%
    {\GlsXtrStandaloneEntryPdfOther{#2}{#3}}%
    {\GlsXtrStandaloneEntryHeadOther{#3}{#2}}%
  }%
  {%
    \glstrtitleorpdforheading
    {\@glstrglossentryother{#2}{#3}{#1}}%
    {\GlsXtrStandaloneEntryPdfOther{#2}{#3}}%
    {#1}%
  }%
}
```

```
\glstrglossentryother{<entry-label>}{<field>}{<header>}
```

`\@glstrglossentryother`

As `\@glstrglossentry` but uses a different field.

```
\newrobustcmd*{\@glstrglossentryother}[3]{%
  \glstrtitleorpdforheading
  {%
    \glsoifexists{#1}%
    {%
      \begingroup

      \protected@edef\glscurrententrylabel{\glsetoklabel{#1}}%
      \protected@edef\currentglossary{\GlsXtrStandaloneGlossaryType}%
      \ifglshasparent{#1}%
      {\GlsXtrStandaloneSubEntryItem{#1}}%
      {\glsenentryitem{#1}}%
    }%
  }%
}
```

```

        \GlsXtrStandaloneEntryOther{#1}{#2}%
    \endgroup
}%
}%
{\GlsXtrStandaloneEntryPdfOther{#1}{#2}}%
{#3}%
}

```

sXtrStandaloneEntryHeadOther

```

\newcommand*{\GlsXtrStandaloneEntryHeadOther}[2]{%
  \ifcsdef{glxstrhead#2}%
  {\csuse{glxstrhead#2}{#1}}%
  {\@gls@entry@field{\NoCaseChange{#1}}{#2}}%
}

```

sXtrStandaloneEntryPdfOther

```

\newcommand*{\GlsXtrStandaloneEntryPdfOther}[2]{%
  \@gls@entry@field{#1}{#2}%
}

```

\GlsXtrStandaloneEntryOther

```

\newcommand*{\GlsXtrStandaloneEntryOther}[2]{%
  \glstarget{#1}{\glossentrynameother{#1}{#2}}%
}

```

\Glsxtrglossentryother As \glsxtrglossentryother but sentence-case.

```

\newcommand*{\Glsxtrglossentryother}[3]{%
  \ifstrempy{#1}%
  {%
    \glxstrtitleorpdforheading
    {\@Glsxtrglossentryother{#2}{#3}{\GlsXtrStandaloneEntryHeadOtherFirstUc{#3}{#2}}}%
    {\GlsXtrStandaloneEntryPdfOtherFirstUc{#2}{#3}}%
    {\GlsXtrStandaloneEntryHeadOtherFirstUc{#3}{#2}}%
  }%
  {%
    \glxstrtitleorpdforheading
    {\@Glsxtrglossentryother{#2}{#3}{#1}}%
    {\GlsXtrStandaloneEntryPdfOtherFirstUc{#2}{#3}}%
    {#1}%
  }%
}

```

\Glsxtrglossentryother{<entry-label>}{<field>}{<header>}

\@Glsxtrglossentryother

As \@glsxtrglossentry but uses a different field.

```

\newrobustcmd*{\@Glsxtrglossentryother}[3]{%
  \glxstrtitleorpdforheading
  {%

```

```

\glsdoifexists{#1}%
{%
  \begingroup
    \protected@edef\glscurrententrylabel{\glsdetoklabel{#1}}%
    \protected@edef\currentglossary{\GlsXtrStandaloneGlossaryType}%
    \ifglshasparent{#1}%
      {\GlsXtrStandaloneSubEntryItem{#1}}%
      {\glsentryitem{#1}}%
    \GlsXtrStandaloneEntryOtherFirstUc{#1}{#2}%
  \endgroup
}%
}%
{\GlsXtrStandaloneEntryPdfOtherFirstUc{#1}{#2}}%
{#3}%
}

```

ndaloneEntryHeadOtherFirstUc

```

\newcommand*{\GlsXtrStandaloneEntryHeadOtherFirstUc}[2]{%
  \ifcsdef{glxtrhead#2}%
    {\csuse{glxtrhead#2}{#1}}%
    {\@Gls@entry@field{\NoCaseChange{#1}}{#2}}%
}

```

ndaloneEntryPdfOtherFirstUc

```

\newcommand*{\GlsXtrStandaloneEntryPdfOtherFirstUc}[2]{%
  \MFUsentencecase{\@Gls@entry@field{#1}{#2}}%
}

```

StandaloneEntryOtherFirstUc

```

\newcommand*{\GlsXtrStandaloneEntryOtherFirstUc}[2]{%
  \glstarget{#1}{\Glossentrynameother{#1}{#2}}%
}

```

`\glxtrtarget` Similar to `\glstarget` but will only create the target if the field identified by `\glxtrtargetfield` has been defined. If the target hasn't been defined, the target is created and the target name is saved in the given field. If `\glstarget` is redefined to use this command then duplicate targets can be avoid if the same entry appears in multiple glossaries. TODO: possibly extend this to allow a comma-separated list of targets in the field?

```

\newcommand{\glxtrtarget}[2]{%
  \GlsXtrIfFieldUndef{\glxtrtargetfield}{#1}%
  {%
    \@glstarget{\glolinkprefix #1}{#2}%
    \xGlsXtrSetField{#1}{\glxtrtargetfield}{\glolinkprefix #1}%
  }%
  {\glxtrtargetdup{#1}{#2}}%
}

```

`\glxtrtargetdup`

```

\newcommand{\glxtrtargetdup}[2]{#2}

```

`\glxtrtargetfield` The field name used by `\glxtrtarget`.
`\newcommand{\glxtrtargetfield}{target}`

`\printunsrtglossary` Similar to `\printnoidxglossary` but it displays all entries defined for the given glossary without sorting. Check for `\@printgloss@checkexists` which was introduced to glossaries v4.46.

```

\ifdef\@printgloss@checkexists
{
  \newcommand*\@printunsrtglossary{%
    \let\@printgloss@checkexists\@printgloss@checkexists@allowignored
    \ifstar\s@printunsrtglossary\@printunsrtglossary
  }
}
{
  \newcommand*\@printunsrtglossary{%
    \ifstar\s@printunsrtglossary\@printunsrtglossary
  }
}

```

`\@printunsrtglossary` Unstarred version.

```

\newcommand*\@printunsrtglossary[1][{}]{%
  \@printglossary{type=\glsdefaulttype,#1}{\@print@unsrt@glossary}%
}

```

`\s@printunsrtglossary` Starred version.

```

\newcommand*\s@printunsrtglossary[2][{}]{%
  \begingroup
    #2%
    \@printglossary{type=\glsdefaulttype,#1}{\@print@unsrt@glossary}%
  \endgroup
}

```

`\printunsrtglossaries` Similar to `\printnoidxglossaries` but it displays all entries defined for the given glossary without sorting.

```

\newcommand*\@printunsrtglossaries{%
  \forallglossaries{\@glo@type}{\printunsrtglossary[type=\@glo@type]}%
}

```

`\@print@unsrt@glossary`

```

\newcommand*\@print@unsrt@glossary{%
  \glossarysection[\glossarytoctitle]{\glossarytitle}%
  \glossarypreamble
  check for empty list
  \glxtrifemptyglossary{\@glo@type}%
  {%
    \GlossariesExtraWarning{No entries defined in glossary ‘\@glo@type’}%
  }%
  {%

```

Setup local commands.

```
\@glxtr@unsrt@gloss@init
```

A loop within the tabular-like styles can cause problems, so move the loop outside. The entire glossary will be saved in `\@glxtr@doglossary`, which will be built up in the loop. Note that v1.50 has removed `\glsresetentrylist`.

```
\def\@glxtr@doglossary{%
  \begin{theglossary}%
  \glossaryheader
}%
```

Apply the post-begin hook.

```
\printunsrtglossarypostbegin{\@glxtr@doglossary}%
```

Iterate over all entries in the current glossary and add the relevant commands to `\@glxtr@doglossary`.

```
\expandafter\@for\expandafter\glscurrententrylabel\expandafter
:\expandafter=\csname glolist@\@glo@type\endcsname\do{%
  \ifdefempty{\glscurrententrylabel}
  {}%
  {%
```

Initialise hooks

```
\@gls@xtr@initprocess
```

Process this entry (unless it has been skipped).

```
\glxtr@process
{%
  \ifglxtr@printgloss@groups
```

Check if the group heading should be added and, if so, add it. `\@glxtr@groupheading` will be empty if no group heading.

```
\glxtraddgroup\glscurrententrylabel
{%
  \@glxtr@checkgroup\glscurrententrylabel
  \expandafter\appto\expandafter\@glxtr@doglossary\expandafter
  {\@glxtr@groupheading}%
}%
\fi
```

Apply the pre-entry hook.

```
\printunsrtglossarypreentryprocesshook{\@glxtr@doglossary}%

\protected@eappto\@glxtr@doglossary{%
  \noexpand\@printunsrt@glossary@handler{\glscurrententrylabel}}%
```

Apply the post-entry hook.

```
\printunsrtglossarypostentryprocesshook{\@glxtr@doglossary}%
}%
}%
}%
```

Apply the pre-end hook.

```
\printunsrtglossarypreend{\@glsxtr@doglossary}%
\appto\@glsxtr@doglossary{\end{theglossary}}%
\printunsrtglossarypredoglossary
\@glsxtr@doglossary
}%
\glossarypostamble
}
```

`\@glsxtr@unsrt@gloss@init` Initialise hooks needed at the start.

```
\newcommand*{\@glsxtr@unsrt@gloss@init}{%
```

Determine how to obtain the group information.

```
\key@ifundefined{glossentry}{group}%
{\let\@gls@getgrouptitle\@gls@noidx@getgrouptitle}%
{\let\@gls@getgrouptitle\@glsxtr@unsrt@getgrouptitle}%
```

Initialise current group information.

```
\def\@gls@currentlettergroup{}%
```

Need to keep track of the current group hierarchical level

```
\def\@gls@currentlettergroup@level{-1}%
```

and the current entry hierarchical level.

```
\def\glscurrententrylevel{-1}%
```

Initialise the root entry. This will be the most recent entry that doesn't have a parent.

```
\def\glscurrentrootentry{}%
```

Initialise the top-level entry. This will be the most recent entry that had level=0 (after adjustment).

```
\def\glscurrenttoplevelentry{}%
}
```

`\@gls@xtr@initprocess` Initialise hooks needed for each iteration of the process loop.

```
\newcommand*{\@gls@xtr@initprocess}{%
```

Save the current hierarchical level (adjusted).

```
\ifglsxtrprintglossflatten
\edef\glscurrententrylevel{\number\@glsxtr@leveloffset}%
\else
\edef\glscurrententrylevel{%
\number\numexpr\csname glo@\glscurrententrylabel @level\endcsname
+ \@glsxtr@leveloffset}%
\fi
```

If this level 0, update `\glscurrenttoplevelentry`

```
\ifnum\glscurrententrylevel=0\relax
\let\glscurrenttoplevelentry\glscurrententrylabel
\fi
```


If this entry doesn't have a parent, update `\glscurrentrootentry`

```
\ifglstrprintglossflatten
  \let\glscurrentrootentry\glscurrententrylabel
\else
  \ifglshasparent{\glscurrententrylabel}{}%
    {\let\glscurrentrootentry\glscurrententrylabel}%
  \fi
```

Initialise to do the current entry.

```
\let\glstr@process\@firstofone
```

Provide a way to skip the current entry. This will redefine `\glstr@process` to ignore its argument.

```
\let\printunsrtglossaryskipentry\glstr@printunsrtglossaryskipentry
\printunsrtglossaryentryprocesshook{\glscurrententrylabel}%
}
```

`\printunsrtinnerglossary` Similar to `\printunsrtglossary` but doesn't add the section heading, preamble, postamble or start and end of the glossary. Grouping is automatically applied so it may cause a problem within tabular-like environments. The beginning and ending of the glossary should be added around this command (but ensure the style has been set first). The simplest way of doing this is to place `\printunsrtinnerglossary` inside the `printunsrtglossarywrap` environment.

```
\newcommand*\printunsrtinnerglossary}[3][]{%
  \begingroup
    \def\glstr@printglossopts{#1}%
    \def\@glo@type{\glsdefaulttype}%
    \setkeys{printgloss}[title,toctitle,style,numberedsection,sort,label]{#1}%
    \let\currentglossary\@glo@type
    #2%
    \@print@unsrt@innerglossary
    #3%
  \endgroup
}
```

`printunsrtglossarywrap` (*env.*)

```
\newenvironment{printunsrtglossarywrap}[1][]{%
  {%
    \def\glstr@printglossopts{#1}%
    \def\@glo@type{\glsdefaulttype}%
    \def\glossarytitle{\csname \@glo@type\@glo@type @title\endcsname}%
    \def\glossarytoctitle{\glossarytitle}%
    \let\org@glossarytitle\glossarytitle
    \def\@glossarystyle{%
      \ifx\@glossary@default@style\relax
        \GlossariesWarning{No default glossary style provided \MessageBreak
          for the glossary '@@glo@type'. \MessageBreak
          Using fallback. \MessageBreak
          To fix this set the style with \MessageBreak
          \string\setglossarystyle\space or use the \MessageBreak
```

```

        style key=value option}%
    \fi
}%
\def\gls@dotoc{title{\glssettoctitle{\@glo@type}}}%
\let\@org@glossaryentrynumbers\glossaryentrynumbers
\@printgloss@setsort
\setkeys{printgloss}{#1}%

```

The type key simply allows the title to be set if the title key isn't supplied.

```

\ifglossaryexists*{\@glo@type}%
{%
    \ifx\glossarytitle\org@glossarytitle
    \else
        \expandafter\let\csname @glo@type\@glo@type @title\endcsname
        \glossarytitle
    \fi
    \let\currentglossary\@glo@type
}%
}%
\let\org@glossaryentrynumbers\glossaryentrynumbers
\let\glsnonextpages\@glsnonextpages
\let\glsnextpages\@glsnextpages
\let\nopostdesc\@nopostdesc
\gls@dotoc{title}
\@glossarystyle
\let\gls@org@glossaryentryfield\glossentry
\let\gls@org@glossarysubentryfield\subglossentry

\renewcommand{\glossentry}[1]{%
    \protected@xdef\glscurrententrylabel{\glsdetoklabel{##1}}%
    \gls@org@glossaryentryfield{##1}%
}%
\renewcommand{\subglossentry}[2]{%
    \protected@xdef\glscurrententrylabel{\glsdetoklabel{##2}}%
    \gls@org@glossarysubentryfield{##1}{##2}%
}%
\@gls@preglossaryhook
\glossarysection[\glossarytoctitle]{\glossarytitle}%
\glossarypreamble
\begin{theglossary}%
\glossaryheader
\glsresetentrylist
}%
{%
    \end{theglossary}%
\glossarypostamble
\global\let\glossaryentrynumbers\@org@glossaryentrynumbers
\global\let\warn@noprntglossary\relax
}

```

```

\@print@unsrt@innnerglossary This is much like \@print@unsrt@innnerglossary but only contains what would
normally be the content of the theglossary.
\newcommand*{\@print@unsrt@innnerglossary}{%
No section header or preamble.
\glstrifemptyglossary{\@glo@type}%
{%
\GlossariesExtraWarning{No entries defined in glossary ‘\@glo@type’}%
}%
}%
}%
Setup local commands.
\@glstr@unsrt@gloss@init
No header or reset.
\def\@glstr@doglossary{%
Iterate over all entries in the current glossary and add the relevant commands
to \@glstr@doglossary.
\expandafter\@for\expandafter\glscurrententrylabel\expandafter
:\expandafter=\csname glo@list@\@glo@type\endcsname\do{%
\ifdefempty{\glscurrententrylabel}
{}%
}%
}%
Initialise hooks
\@glstr@initprocess
Process this entry (unless it has been skipped).
\glstr@process
{%
\ifglstr@printgloss@groups
Check if the group heading should be added and, if so, add it. \@glstr@groupheading
will be empty if no group heading.
\glstr@addgroup\glscurrententrylabel
{%
\@glstr@checkgroup\glscurrententrylabel
\expandafter\appto\expandafter\@glstr@doglossary\expandafter
{\@glstr@groupheading}%
}%
\fi
Apply the pre-entry hook.
\printunsrtglossarypreentryprocesshook{\@glstr@doglossary}%
\protected@eappto\@glstr@doglossary{%
\noexpand\@printunsrt@glossary@handler{\glscurrententrylabel}}%
Apply the post-entry hook.
\printunsrtglossarypostentryprocesshook{\@glstr@doglossary}%
}%
}%
}%

```

```

\printunsrtglossarypreend not used.
    \printunsrtglossarypredoglossary
    \@glxtr@doglossary
}%
No postamble.
}

\glxtraddgroup Now that bib2gls v3.0+ has the ability to store group labels for sub-levels,
provide a way to allow for this. This checks if the entry has a parent, which was
used originally, unless the flatten option has been used. bib2gls will redefine
this in the .gls.tex file if the group-level setting is used.
    \newcommand*{\glxtraddgroup}[2]{%
        \ifglxtrprintglossflatten
            #2%
        \else
            \ifglshasparent{#1}{-}{#2}%
        \fi
    }

\printunsrtglossaryentryprocesshook
    \newcommand*{\printunsrtglossaryentryprocesshook}[1]{}

\printunsrtglossarypreentryprocesshook This hook is performed before the entry line has been added to \@glxtr@do@glossary.
The argument will be \@glxtr@do@glossary so that content can be appended
to it. The current entry can be referenced with \glscurrententrylabel. The
current level can be referenced with \glscurrententrylevel, etc.
    \newcommand*{\printunsrtglossarypreentryprocesshook}[1]{}

\printunsrtglossarypostentryprocesshook This hook is performed after the entry line has been added to \@glxtr@do@glossary.
The argument will be \@glxtr@do@glossary so that content can be appended
to it. The current entry can be referenced with \glscurrententrylabel. The
current level can be referenced with \glscurrententrylevel, etc.
    \newcommand*{\printunsrtglossarypostentryprocesshook}[1]{}

\printunsrtglossarygrouphook Similar hook used when the group heading added. In this case the argument
will be \@glxtr@groupheading.
    \newcommand*{\printunsrtglossarygrouphook}[1]{}

\printunsrtglossaryskipentry
    \newcommand*{\printunsrtglossaryskipentry}{%
        \PackageError{glossaries-extra}{\string\printunsrtglossaryskipentry\space
can only be used within \string\printunsrtglossaryentryprocesshook}{}%
    }

\printunsrtglossaryskipentry
    \newcommand*{\@glxtr@printunsrtglossaryskipentry}{%
        \let\glxtr@process\@gobble
    }

```

\printunsrtglossarypredoglossary

```
\newcommand*\printunsrtglossarypredoglossary{}{}
```

\printunsrtglossarypreend

```
\newcommand*\printunsrtglossarypreend}[1]{}{}
```

\printunsrtglossarypostbegin

```
\newcommand*\printunsrtglossarypostbegin}[1]{}{}
```

\printunsrt@glossary@handler

```
\newcommand*\printunsrt@glossary@handler}[1]{%
  \protected@xdef\glscurrententrylabel{#1}%
  \printunsrtglossaryhandler\glscurrententrylabel
}
```

\printunsrtglossaryhandler

```
\newcommand*\printunsrtglossaryhandler}[1]{%
  \glsxtrunsrtdo{#1}%
}
```

\glsxtriflabelinlist

```
\glsxtriflabelinlist{<label>}{<list>}{<true>}{<false>}
```

Might be useful for the handler to check if an entry label or category label is contained in a list, so provide a user-level version of `\@gls@ifinlist` which ensures the label and list are fully expanded.

```
\newrobustcmd*\glsxtriflabelinlist[4]{%
  \protected@edef\glsxtr@doiflabelinlist{\noexpand\@gls@ifinlist{#1}{#2}}%
  \@glxtr@doiflabelinlist{#3}{#4}%
}
```

\print@op@unsrtglossaryunit

```
\newcommand*\print@op@unsrtglossaryunit}[2][ ]{%
  \s@printunsrtglossary[type=\glstypedefaulttype,#1]{%
    \printunsrtglossaryunitsetup{#2}%
  }%
}
```

\printunsrtglossaryunitsetup

```
\newcommand*\printunsrtglossaryunitsetup}[1]{%
  \renewcommand*\printunsrtglossaryhandler}[1]{%
    \glsxtrfieldxifinlist{##1}{record.#1}{\csuse{the#1}}
    {\glsxtrunsrtdo{##1}}%
  }%
}
```

Only the target names should have the prefixes adjusted as `\gls` etc need the original `\glolinkprefix`. The `\@gobble` part discards `\glolinkprefix`.

```
\ifcsundef{theH#1}%
{%
  \renewcommand*{\@glxtrhypernameprefix}{record.#1.\csuse{theH#1}.\@gobble}%
}%
{%
  \renewcommand*{\@glxtrhypernameprefix}{record.#1.\csuse{theH#1}.\@gobble}%
}%
\@printunsrtglossary@unit@nosec
\appto\glossarypostamble{\printunsrtglossaryunitpostskip}%
}
```

`\printunsrtglossary@unit@nosec` glossaries v4.9+ now defines `\glossarysection` with `\NewDocumentCommand` rather than `\newcommand` and has introduced a new `section=none` option to suppress the section heading. The simplest way to check for this is to test for the new command that's now used by `\glossarysection`:

```
\ExplSyntaxOn
\cs_if_exist:NTF \glossaries_section:nn
{
  \newcommand \@printunsrtglossary@unit@nosec
  {
    \setglossarysection { none }
  }
}
{
  \newcommand \@printunsrtglossary@unit@nosec
  {
    \renewcommand*{\glossarysection}[2] [] {}
  }
}
\ExplSyntaxOff
```

`\printunsrtglossaryunitpostskip`

```
\newcommand*{\printunsrtglossaryunitpostskip}{\glspare\medskip\glspare}
```

`\print@noop@unsrtglossaryunit`

```
\newcommand{\print@noop@unsrtglossaryunit}[2] [] {%
  \PackageError{glossaries-extra}{\string\printunsrtglossaryunit\space
    requires the record=only or record=alsoindex package option}{}%
}
```

`\@glxtr@unsrt@getgrouptitle`

```
\newrobustcmd*{\@glxtr@unsrt@getgrouptitle}[2] {%
  \protected@edef\@glxtr@titlelabel{\glxtr@grouptitle@#1}%
  \onelevel@sanitize\@glxtr@titlelabel
  \ifcsdef{\@glxtr@titlelabel}
  {\letcs{#2}{\@glxtr@titlelabel}}%
  {\def#2{#1}}%
}
```

}

`\glxtrunsrtdo` Provide a user-level call to `\@glxtr@noidx@do` to make it easier to define a new handler.

```
\newcommand{\glxtrunsrtdo}{\@glxtr@noidx@do}
```

`\glxtrgroupfield` `bib2gls` provides a supplementary field labelled `secondarygroup` for secondary glossaries, so provide a way of switching to that field. (The `group` key still needs checking. There's no associated key with the internal field).

```
\newcommand*{\glxtrgroupfield}{group}
```

The `tabular`-like glossary styles cause quite a problem with the iterative approach. In particular for the `group skip`. To compensate for this, the groups are now determined while `\@glxtr@doglossary` is being constructed rather than in the handler.

`\@glxtr@checkgroup` The argument is the entry's label. (This block of code was formerly in `\@glxtr@noidx@do`.) Now that this is no longer within a `tabular` environment, the global definitions aren't needed. The result is now stored in `\@glxtr@groupheading`, which will be empty if no heading is required. The current hierarchical level must have first been saved to `\glscurrententrylevel`.

```
\newcommand*{\@glxtr@checkgroup}[1]{%
  \def\@glxtr@groupheading{}%
  \key@ifundefined{glossentry}{group}%
  {%
    \letcs{\@glx@sort}{glo@\glstdetoklabel{#1}@sort}%
    \expandafter\glo@grabfirst\@glx@sort{}{}\@nil
  }%
  {%

    \protected@edef\@glo@thislettergrp{%
      \csuse{glo@\glstdetoklabel{#1}@\glxtrgroupfield}}%
  }%
}
```

Need to keep track of the current group for the current level.

```
\ifcsundef{@glx@currentlettergroup\romannumeral\glscurrententrylevel}%
{\csdef{@glx@currentlettergroup\romannumeral\glscurrententrylevel}{}}%
```

Has the group label changed for the current level?

```
\ifcsequal{@glo@thislettergrp}{@glx@currentlettergroup\romannumeral\glscurrententrylevel}%
{}%
{%
  \ifdefempty{@glo@thislettergrp}
  {}%
  {%

```

Check the hierarchical level.

```
\ifnum\glscurrententrylevel>0\relax
  \protected@eappto{@glxtr@groupheading{%
    \noexpand\glssubgroupheading
```

```

        {\@gls@currentlettergroup@level}{\glscurrententrylevel}%
        {\csuse{glo@glsdetoklabel{#1}@parent}}}%
        {\expandonce\@glo@thislettergrp}%
    }%
\else
    \ifdefempty{\@gls@currentlettergroup}{}%
    {%

```

Don't add `\glsgroupskip` if `nogroupskip` setting is on.

```

        \ifglsgroupskip
        \else
            \def\@glsxtr@groupheading{\glsgroupskip}%
        \fi
    }%
    \protected@eappto\@glsxtr@groupheading{%
        \noexpand\glsgroupheading{\expandonce\@glo@thislettergrp}%
    }%
\fi
\let\@gls@currentlettergroup@level\glscurrententrylevel
\cslet\@gls@currentlettergroup\romannumeral\glscurrententrylevel\@glo@thislettergrp

```

Perform the group hook, which can be used to add content.

```

        \printunsrtglossarygrouphook{\@glsxtr@groupheading}%
    }%
}%
}

```

```

\glssubgroupheading{<previous level>}{<level>}{<parent>}}
{<group label>}}

```

`\glssubgroupheading`

Default definition uses the same format as the top-level heading. Note that this won't include the group skip.

```

\newcommand*{\glssubgroupheading}[4]{\glsgroupheading{#4}}

```

`\GlsXtrLocationField` Stores the internal name of the location field.

```

\newcommand*{\GlsXtrLocationField}{location}

```

`\@glsxtr@noidx@do` Minor modification of `\@gls@noidx@do` to check for location field if present, but also need to check for the group field and flatten option.

```

\newcommand{\@glsxtr@noidx@do}[1]{%
    \ifglsentryexists{#1}%
    {%
        \global\letcs{\@gls@loclist}{glo@glsdetoklabel{#1}@loclist}%
        \global\letcs{\@gls@location}{glo@glsdetoklabel{#1}@GlsXtrLocationField}%
    }
}

```

Use level number to determine whether or not this entry has a parent.

```

    \ifglsxtrprintglossflatten
        \gls@level=\@glsxtr@leveloffset\relax
    \else

```



```

\gls@level=\numexpr\csuse{gls@glstoklabel{#1}@level}+\@glsxtr@leveloffset\relax
\fi
\ifnum\gls@level>0
\let\@glsxtr@ifischild\@firstoftwo
\else
\let\@glsxtr@ifischild\@secondoftwo
\fi

```

Some glossary styles (such as topicmcols) save the level using `\def` so make sure `\gls@level` is expanded before being passed to `\subglossentry`.

```

\@glsxtr@ifischild
{%
\ifdefvoid{\@gls@location}%
{%

```

If `\GlsXtrLocationField` has been changed then don't fallback on `loclist`.

```

\ifdefstring{\GlsXtrLocationField}{location}%
{%
\ifdefvoid{\@gls@loclist}%
{%
\expandafter\subglossentry\expandafter{\number\gls@level}{#1}{}%
}%
{%
\expandafter\subglossentry\expandafter{\number\gls@level}{#1}%
{%
\glossaryentrynumbers{\glsnoidxloclist{\@gls@loclist}}%
}%
}%
}%
{%
\expandafter\subglossentry\expandafter{\number\gls@level}{#1}{}%
}%
}%
{%
\expandafter\subglossentry\expandafter
{\number\gls@level}{#1}{\glossaryentrynumbers{\@gls@location}}%
}%
}%
{%
\ifdefvoid{\@gls@location}%
{%

```

If `\GlsXtrLocationField` has been changed then don't fallback on `loclist`.

```

\ifdefstring{\GlsXtrLocationField}{location}%
{%
\ifdefvoid{\@gls@loclist}
{%
\glossentry{#1}{}%
}%
{%

```

```

        \glossentry{#1}%
        {%
        \glossaryentrynumbers{\glsnoidxloclist{\@gls@loclist}}}%
        }%
    }%
}%
{%
    \glossentry{#1}{}%
}%
}%
{%
    \glossentry{#1}%
    {%
    \glossaryentrynumbers{\@gls@location}%
    }%
}%
}%
}%
{%
}

```

Provide a way to conveniently define commands that behaves like `\gls` with a label prefix.

It's possible that the user might want minor variations with the same prefix but different default options, so use a counter to provide unique inner commands.

`\glstrnewgls`

```
\newcount\@glstrnewgls@inner
```

(The default options supplied in *<options>* below could possibly be used to form the inner control sequence name to help make it unique, but it might feasibly contain thevalue where the value might contain commands.)

`\glstrdoidentify`

```

\newcommand*{\glstrdoidentify}[1]{%
\ifdefequal\@glstr@record@setting\@glstr@record@setting@off{}\@glstr@record@setting@off{#1}%
}

```

`\@glstr@providenewgls`

```

\newcommand*{\@glstr@providenewgls}{%
    \protected@write\@auxout{}\@string\providecommand{\@string\@glstr@newglslike}[2]{}%
    \let\@glstr@providenewgls\relax
}

```

`\glstridentifyglslike` Identify the command given in the second argument for the benefit of `bib2gls` and also identify command as a blocker for `\makefirstuc`.

```

\newcommand{\glstridentifyglslike}[2]{%
    \glsmfublocker{#2}%
    \glstrdoidentify
}

```

```
{%
  \@glstr@providenewgls
  \protected@write\@auxout{}\string\@glstr@newglslike{#1}\string#2}}%
}%
}
```

\@glstr@providenewglsfamily

```
\newcommand*\@glstr@providenewglsfamily{%
  \protected@write\@auxout{}\string\providecommand\string\@glstr@newglslikefamily}[8]{}%
  \let\@glstr@providenewglsfamily\relax
}
```

```
\glstridentifyglsfamily{<options>}{<prefix>}{<gls>}
{<glspl>}{<Gls>}{<Glspl>}{<GLS>}{<GLSpl>}
```

\glstridentifyglsfamily

Identify the family of commands for the benefit of bib2gls and also establishes a sentence-case mapping.

```
\newcommand{\glstridentifyglsfamily}[8]{%
  \glsmfuaddmap{#3}{#5}%
  \glsmfuaddmap{#4}{#6}%
  \glsmfublocker{#7}%
  \glsmfublocker{#8}%
  \glstrdoidentify
  {%
    \@glstr@providenewglsfamily
    \protected@write\@auxout{}\string\@glstr@newglslikefamily{\detokenize{#1}}{\detokenize{#2}}{\detokenize{#3}}{\detokenize{#4}}{\detokenize{#5}}{\detokenize{#6}}{\detokenize{#7}}{\detokenize{#8}}%
  }%
}
```

\@glstr@providenewglslink

```
\newcommand*\@glstr@providenewglslink{%
  \protected@write\@auxout{}\string\providecommand\string\@glstr@newglslink}[2]{}%
  \let\@glstr@providenewglslink\relax
}
```

\glstridentifyglslink Identify the command given in the second argument for the benefit of bib2gls and identify the command as a blocker for \makefirstuc.

```
\newcommand{\glstridentifyglslink}[2]{%
  \glsmfublocker{#2}%
  \glstrdoidentify
  {%
    \@glstr@providenewglslink
    \protected@write\@auxout{}\string\@glstr@newglslink{#1}\string#2}}%
}%
}
```

```
\@glstrnewglslink[<options>]{<prefix>}{<cs>}{<inner cs
name>}
```

\@glstrnewglslink

```
\newcommand*{\@glstrnewglslink}[4]{%
\ifdef{#3}%
{%
\PackageError{glossaries-extra}{Command \string#3\space already
defined}{}%
}%
{%
```

Write information to the aux file for bib2gls.

```
\glstridentifyglslink{#2}{#3}%
\ifcsdef{@#4link@#2}%
{%
\advance\@glstrnewgls@inner by \@ne
\def\@glstrnewgls@innercsname{@#4link\number\@glstrnewgls@inner @#2}%
}%
{\def\@glstrnewgls@innercsname{@#4link@#2}}%
\expandafter\newrobustcmd\expandafter*\expandafter
#3\expandafter{\expandafter\@glshyp@opt\csname\@glstrnewgls@innercsname\endcsname}%
\ifstrempy{#1}%
{%
\expandafter\newcommand\expandafter*\csname\@glstrnewgls@innercsname\endcsname[2][]{%
\csname #4\endcsname{##1}{#2##2}%
}%
}%
}%
\expandafter\newcommand\expandafter*\csname\@glstrnewgls@innercsname\endcsname[2][]{%
\csname #4\endcsname{#1,##1}{#2##2}%
}%
}%
}%
}
```

```
\glstrnewglslink[<options>]{<prefix>}{<cs>}
```

\glstrnewglslink

The first argument prepends to the options and the second argument is the prefix.

```
\newrobustcmd*{\glstrnewglslink}[3][]{%
\@glstrnewglslink{#1}{#2}{#3}{@gls@link}%
}
```

```
\glstrnewglsdisp[<options>]{<prefix>}{<cs>}
```

\glstrnewglsdisp

The first argument prepends to the options and the second argument is the prefix.

```
\newrobustcmd*{\glxstrnewglsdisp}[3][\%
  \glxstrnewglslink{#1}{#2}{#3}{\glsdisp}%
}
```

```
\@glxstrnewgls[\<options>]{\<prefix>}{\<cs>}{\<inner cs
name>}
```

\glxstrnewgls

```
\newcommand*{\@glxstrnewgls}[4]{\%
  \ifdef{#3}%
  {%
    \PackageError{glossaries-extra}{Command \string#3\space already
defined}{}%
  }%
  {%
```

Write information to the aux file for bib2gls.

```
  \glxstridentifyglslike{#2}{#3}%
  \ifcsdef{@#4like@#2}%
  {%
    \advance\@glxstrnewgls@inner by \@ne
    \def\@glxstrnewgls@innercsname{@#4like\number\@glxstrnewgls@inner @#2}%
  }%
  {\def\@glxstrnewgls@innercsname{@#4like@#2}}%
  \expandafter\newrobustcmd\expandafter*\expandafter
  #3\expandafter{\expandafter\@gls@hyp@opt\csname\@glxstrnewgls@innercsname\endcsname}%
  \ifstrempy{#1}%
  {%
    \expandafter\newcommand\expandafter*\csname\@glxstrnewgls@innercsname\endcsname[2][\%
      \new@ifnextchar[\%
        {\csname @#4@\endcsname{##1}{#2##2}}}%
        {\csname @#4@\endcsname{##1}{#2##2}[]}%
      }%
    }%
  {%
    \expandafter\newcommand\expandafter*\csname\@glxstrnewgls@innercsname\endcsname[2][\%
      \new@ifnextchar[\%
        {\csname @#4@\endcsname{#1,##1}{#2##2}}}%
        {\csname @#4@\endcsname{#1,##1}{#2##2}[]}%
      }%
    }%
  }%
}
```

```
\glxstrnewgls[\<options>]{\<prefix>}{\<cs>}
```

\glxstrnewgls

The first argument prepends to the options and the second argument is the prefix.

```
\newrobustcmd*\glsxtrnewgls}[3][]{%
  \@glsxtrnewgls{#1}{#2}{#3}{gls}%
}
```

`\glsxtrnewglslike` Provide a way to conveniently define commands that behave like `\gls`, `\glspl`, `\Gls` and `\Glspl` with a label prefix. The first argument prepends to the options and the second argument is the prefix.

```
\newrobustcmd*\glsxtrnewglslike}[6][]{%
  \glsxtridentifyglsfamily{#1}{#2}{#3}{#4}{#5}{#6}{-}{-}%
  \@glsxtrnewgls{#1}{#2}{#3}{gls}%
  \@glsxtrnewgls{#1}{#2}{#4}{glspl}%
  \@glsxtrnewgls{#1}{#2}{#5}{Gls}%
  \@glsxtrnewgls{#1}{#2}{#6}{Glspl}%
}
```

`\glsxtrnewGLSlike` Provide a way to conveniently define commands that behave like `\GLS`, `\GLSpl` with a label prefix. The first argument prepends to the options and the second argument is the prefix.

```
\newrobustcmd*\glsxtrnewGLSlike}[4][]{%
  \glsxtridentifyglsfamily{#1}{#2}{-}{-}{-}{-}{#3}{#4}%
  \@glsxtrnewgls{#1}{#2}{#3}{GLS}%
  \@glsxtrnewgls{#1}{#2}{#4}{GLSpl}%
}
```

`\glsxtrnewrgls` As `\glsxtrnewgls` but for `\rgls`.

```
\newrobustcmd*\glsxtrnewrgls}[3][]{%
  \@glsxtrnewgls{#1}{#2}{#3}{rgls}%
}
```

`\glsxtrnewrglslike` As `\glsxtrnewglslike` but for `\rgls` etc.

```
\newrobustcmd*\glsxtrnewrglslike}[6][]{%
  \glsxtridentifyglsfamily{#1}{#2}{#3}{#4}{#5}{#6}{-}{-}%
  \@glsxtrnewgls{#1}{#2}{#3}{rgls}%
  \@glsxtrnewgls{#1}{#2}{#4}{rglspl}%
  \@glsxtrnewgls{#1}{#2}{#5}{rGls}%
  \@glsxtrnewgls{#1}{#2}{#6}{rGlspl}%
}
```

`\glsxtrnewrGLSlike` As `\glsxtrnewGLSlike` but for `\rGLS` etc.

```
\newrobustcmd*\glsxtrnewrGLSlike}[4][]{%
  \glsxtridentifyglsfamily{#1}{#2}{-}{-}{-}{-}{#3}{#4}%
  \@glsxtrnewgls{#1}{#2}{#3}{rGLS}%
  \@glsxtrnewgls{#1}{#2}{#4}{rGLSpl}%
}
```

Provide easy access to record count fields.

`\GlsXtrTotalRecordCount` Access total record count. This is designed to be expandable. The argument is the label.

```
\newcommand*{\GlsXtrTotalRecordCount}[1]{%
\ifcsdef{glo@\glsdetoklabel{#1}@recordcount}%
{\csname glo@\glsdetoklabel{#1}@recordcount\endcsname}%
{0}%
}
```

`\GlsXtrRecordCount` Access record count for a particular counter. The first argument is the label. The second argument is the counter name.

```
\newcommand*{\GlsXtrRecordCount}[2]{%
\ifcsdef{glo@\glsdetoklabel{#1}@recordcount.#2}%
{\csname glo@\glsdetoklabel{#1}@recordcount.#2\endcsname}%
{0}%
}
```

`\GlsXtrLocationRecordCount` Access record count for a particular counter and location. The first argument is the label. The second argument is the counter name. The third argument is the location. This command shouldn't be used if the location doesn't fully expand unless `\glsxtrdetoklocation` can be set to something sensible.

```
\newcommand*{\GlsXtrLocationRecordCount}[3]{%
\ifcsdef{glo@\glsdetoklabel{#1}@recordcount.#2.\glsxtrdetoklocation{#3}}%
{\csname glo@\glsdetoklabel{#1}@recordcount.#2.\glsxtrdetoklocation{#3}\endcsname}%
{0}%
}
```

`\glsxtrdetoklocation`

```
\newcommand*{\glsxtrdetoklocation}[1]{#1}
```

`\glsxtrenablerecordcount`

```
\newcommand*{\glsxtrenablerecordcount}{%
\renewcommand*{\gls}{\rgls}%
\renewcommand*{\Gls}{\rGls}%
\renewcommand*{\glspl}{\rglspl}%
\renewcommand*{\Glspl}{\rGlspl}%
\renewcommand*{\GLS}{\rGLS}%
\renewcommand*{\GLSpl}{\rGLSpl}%
\renewcommand{\shortcut@gls}{\rgls}%
\renewcommand{\shortcut@glspl}{\rglspl}%
\renewcommand{\shortcut@Gls}{\rGls}%
\renewcommand{\shortcut@Glspl}{\rGlspl}%
\renewcommand{\shortcut@GLS}{\rGLS}%
\renewcommand{\shortcut@GLSpl}{\rGLSpl}%
}
```

`\glsxtrrecordtriggervalue` The value used by the record trigger test. The argument is the entry's label.

```
\newcommand*{\glsxtrrecordtriggervalue}[1]{%
\GlsXtrTotalRecordCount{#1}%
}
```

sXtrSetRecordCountAttribute

```
\newcommand*{\GlsXtrSetRecordCountAttribute}[2]{%
  \@for\@glstr@cat:=#1\do
  {%
    \ifdefempty{\@glstr@cat}{}%
    {%
      \glsssetcategoryattribute{\@glstr@cat}{recordcount}{#2}%
    }%
  }%
}
```

\glstriferecordtrigger

`\glstriferecordtrigger{<label>}{<trigger format>}{<normal>}`

```
\newcommand*{\glstriferecordtrigger}[3]{%
  \glshasattribute{#1}{recordcount}%
  {%
    \ifnum\glstrrecordtriggervalue{#1}>\glsggetattribute{#1}{recordcount}\relax
    #3%
    \else
    #2%
    \fi
  }%
  {#3}%
}
```

\@glstr@rglstrigger@record Still need a record to ensure that bib2gls selects the entry.

```
\newcommand*{\@glstr@rglstrigger@record}[3]{%
  \protected@edef\glslabel{\glstetoklabel{#2}}%
  \let\@gls@link@label\glslabel
  \def\@glstr@thevalue{%
    \def\@glstr@theHvalue{\@glstr@thevalue}%
    \def\@glsnumberformat{glstriggerrecordformat}%
    \protected@edef\@gls@counter{\csname glo@\glslabel @counter\endcsname}%
    \protected@edef\glstype{\csname glo@\glslabel @type\endcsname}%
    \def\@glstr@thevalue{%
      \def\@glstr@theHvalue{\@glstr@thevalue}%
    }%
  }
```

Save local setting.

```
\@gls@save@glslocal
```

Initialise preunset, prereset and postunset

```
\glsinitreunsets
\glstrinitwrgloss
\glslinkpresetkeys
\setkeys{glslink}{#1}%
\glslinkpostsetkeys
\ifdefempty{\@glstr@thevalue}%
```



```

{%
  \@gls@saveentrycounter
}%
{%
  \let\theglsentrycounter\@glsxtr@thevalue
  \def\theHglsentrycounter{\@glsxtr@theHvalue}%
}%
\glslinkwrcontent
{%
  \ifglsxtrinitwrglossbefore
    \glsxtr@wrglossary@encap{#2}{\@do@wrglossary{#2}}%
  \fi
  #3%
  \ifglsxtrinitwrglossbefore
  \else
    \glsxtr@wrglossary@encap{#2}{\@do@wrglossary{#2}}%
  \fi
}%
\@gls@restore@glslocal
\@gls@do@glsunset{#2}%
}

```

`\glstriggerrecordformat` Typically won't be used as it should be recognised as a special type of ignored location by `bib2gls`.

```

\newcommand*{\glstriggerrecordformat}[1]{%

```

```

\rgls

```

```

\newrobustcmd*{\rgls}{\@gls@hyp@opt\@rgls}

```

```

\@rgls

```

```

\newcommand*{\@rgls}[2][{}]{%
  \new@ifnextchar[{\@rgls@{#1}{#2}}{\@rgls@{#1}{#2}[]}%
}

```

```

\@rgls@

```

```

\def\@rgls@#1#2[#3]{%
  \glsxtrifrecordtrigger{#2}%
  {%
    \@glsxtr@rglstrigger@record{#1}{#2}{\rglsformat{#2}{#3}}%
  }%
  {%
    \@gls@{#1}{#2}[#3]%
  }%
}%

```

```

\rglspl

```

```

\newrobustcmd*{\rglspl}{\@gls@hyp@opt\@rglspl}

```

```

\@rglsp1
\newcommand*{\@rglsp1}[2][{}]{%
  \new@ifnextchar[{\@rglsp1@{#1}{#2}}{\@rglsp1@{#1}{#2}[]}%
}

\@rglsp1@
\def\@rglsp1@#1#2[#3]{%
  \glstriferecordtrigger{#2}%
  {%
    \glstr@rglstrigger@record{#1}{#2}{\rglsp1format{#2}{#3}}%
  }%
  {%
    \@rglsp1@{#1}{#2}[#3]%
  }%
}%

\rgls
\newrobustcmd*{\rgls}{\@gls@hyp@opt\@rgls}
\glsmfuaddmap{\rgls}{\rgls}

\@rgls
\newcommand*{\@rgls}[2][{}]{%
  \new@ifnextchar[{\@rgls@{#1}{#2}}{\@rgls@{#1}{#2}[]}%
}

\@rgls@
\def\@rgls@#1#2[#3]{%
  \glstriferecordtrigger{#2}%
  {%
    \glstr@rglstrigger@record{#1}{#2}{\rglsformat{#2}{#3}}%
  }%
  {%
    \@rgls@{#1}{#2}[#3]%
  }%
}%

\rglsp1
\newrobustcmd*{\rglsp1}{\@gls@hyp@opt\@rglsp1}
\glsmfuaddmap{\rglsp1}{\rglsp1}

\@rglsp1
\newcommand*{\@rglsp1}[2][{}]{%
  \new@ifnextchar[{\@rglsp1@{#1}{#2}}{\@rglsp1@{#1}{#2}[]}%
}

\@rglsp1@
\def\@rglsp1@#1#2[#3]{%
  \glstriferecordtrigger{#2}%

```

```

        {%
        \glstr@r@glstrtrigger@record{#1}{#2}{\rGLsplformat{#2}{#3}}%
        }%
        {%
        \@GLspl@{#1}{#2}[#3]%
        }%
    }%

\rGLS

\newrobustcmd*{\rGLS}{\@gls@hyp@opt\rGLS}
\glsmfublocker{\rGLS}%

\@rGLS

\newcommand*{\@rGLS}[2][{}]{%
    \new@ifnextchar[{\@rGLS@{#1}{#2}}{\@rGLS@{#1}{#2}[]}%
}

\rGLS@

\def\rGLS@#1#2[#3]{%
    \glstr@r@glstrtrigger@record{#2}%
    {%
        \glstr@r@glstrtrigger@record{#1}{#2}{\rGLSformat{#2}{#3}}%
    }%
    {%
        \@GLS@{#1}{#2}[#3]%
    }%
}%

\rGLSpl

\newrobustcmd*{\rGLSpl}{\@gls@hyp@opt\rGLSpl}
\glsmfublocker{\rGLSpl}%

\@rGLSpl

\newcommand*{\@rGLSpl}[2][{}]{%
    \new@ifnextchar[{\@rGLSpl@{#1}{#2}}{\@rGLSpl@{#1}{#2}[]}%
}

\rGLSpl@

\def\rGLSpl@#1#2[#3]{%
    \glstr@r@glstrtrigger@record{#2}%
    {%
        \glstr@r@glstrtrigger@record{#1}{#2}{\rGLSplformat{#2}{#3}}%
    }%
    {%
        \@GLSpl@{#1}{#2}[#3]%
    }%
}%

```

```

\rglsformat
\newcommand*{\rglsformat}[2]{%
  \glsifregular{#1}
  {\glsentryfirst{#1}}%
  {\ifglshaslong{#1}{\glsentrylong{#1}}{\glsentryfirst{#1}}}\#2%
}

\rglsplformat
\newcommand*{\rglsplformat}[2]{%
  \glsifregular{#1}
  {\glsentryfirstplural{#1}}%
  {\ifglshaslong{#1}{\glsentrylongpl{#1}}{\glsentryfirstplural{#1}}}\#2%
}

\rGlsformat
\newcommand*{\rGlsformat}[2]{%
  \glsifregular{#1}
  {\Glsentryfirst{#1}}%
  {\ifglshaslong{#1}{\Glsentrylong{#1}}{\Glsentryfirst{#1}}}\#2%
}

\rGlsplformat
\newcommand*{\rGlsplformat}[2]{%
  \glsifregular{#1}
  {\Glsentryfirstplural{#1}}%
  {\ifglshaslong{#1}{\Glsentrylongpl{#1}}{\Glsentryfirstplural{#1}}}\#2%
}

\rGLSformat
\newcommand*{\rGLSformat}[2]{%
  \expandafter\glsupercase\expandafter{\rglsformat{#1}{#2}}%
}

\rGLSplformat
\newcommand*{\rGLSplformat}[2]{%
  \expandafter\glsupercase\expandafter{\rglsplformat{#1}{#2}}%
}

```

1.4 Link Counting

This is different to the entry counting provided by the base package (which counts the number of times the first use flag is unset). Instead, this method hooks into `\@gls@link` (through `\glsxtr@inc@linkcount`) to increment an associated counter. To preserve resources, the counter is only defined if it needs to be incremented. This method is independent of the presence of hyperlinks. (The “link” part of the name refers to `\@gls@link` not `\hyperlink`.)

`\@glstr@do@inc@linkcount` This performs the actual incrementing and counter definition. The counter is given by `\c@glstr@linkcount@label` where *label* is the entry's label. Since this is performed within `\@glsl@link` the label can be accessed with `\glslabel`.

```

\newcommand{\@glstr@do@inc@linkcount}{%
Does this entry have the linkcount attribute set?
\gl@ifattribute{\glslabel}{linkcount}{true}%
{%
Does the counter exist?
\ifcsdef{c@glstr@linkcount@\glslabel}{}%
{%
Counter doesn't exist, so define it.
\newcounter{glstr@linkcount@\glslabel}%
If linkcountmaster is set, add to counter reset.
\glshasattribute{\glslabel}{linkcountmaster}%
{%
Need to ensure values are fully expanded.
\begingroup
\edef\@glo@tmp{\endgroup\noexpand\@addtoreset{glstr@linkcount@\glslabel}%
{\glsggetattribute{\glslabel}{linkcountmaster}}}%
\@glo@tmp
}%
{}%
}%
Increment counter:
\glstrinlinkcounter{glstr@linkcount@\glslabel}%
}%
{}%
}

```

`\glstrinlinkcounter` May be redefined to use `\refstepcounter` if required.

```

\newcommand*{\glstrinlinkcounter}[1]{\stepcounter{#1}}

```

`\GlsXtrLinkCounterValue` Expands to the associated link counter register or 0 if not defined.

```

\newcommand*{\GlsXtrLinkCounterValue}[1]{%
\ifcsundef{c@glstr@linkcount@#1}{0}{\csname c@glstr@linkcount@#1\endcsname}%
}

```

`\GlsXtrTheLinkCounter` Expands to the display value of the associated link counter or 0 if not defined.

```

\newcommand*{\GlsXtrTheLinkCounter}[1]{%
\ifcsundef{theglstr@linkcount@#1}{0}%
{\csname theglstr@linkcount@#1\endcsname}%
}

```

`\GlsXtrIfLinkCounterDef` Tests if the counter has been defined

```

\newcommand*\GlsXtrIfLinkCounterDef}[3]{%
\ifcsundef{theglsxtr@linkcount@#1}{#3}{#2}%
}

\GlsXtrLinkCounterName Expands to the associated link counter name. (No check for existence.)
\newcommand*\GlsXtrLinkCounterName}[1]{glsextr@linkcount@#1}

```

`\GlsXtrEnableLinkCounting[<master counter>]{<categories>}`

`\GlsXtrEnableLinkCounting` Enable link counting for the given categories.

```

\newcommand*\GlsXtrEnableLinkCounting}[2][{}]{%
\let\glsextr@inc@linkcount\@glsextr@do@inc@linkcount
\@for\@glsextr@label:=#2\do
{%
\glsssetcategoryattribute{\@glsextr@label}{linkcount}{true}%
\ifstrempy{#1}{}%
}%
\ifcsundef{c@#1}%
{\@nocounterr{#1}}%
{\glsssetcategoryattribute{\@glsextr@label}{linkcountmaster}{#1}}%
}%
}%
}
\@onlypreamble\GlsXtrEnableLinkCounting

```

1.5 Integration with glossaries-accsupp

Provide better integration with the glossaries-accsupp package. (Must be loaded before the main code of glossaries-extra either explicitly or through the accsupp package option.)

These commands have their definitions set according to whether or not glossaries-extra has been loaded.

To allow for formatting commands that need to go inside all other commands (such as the commands provided by soul), also add version of each command that takes a text-block command as an argument.

```

\@ifpackageloaded{glossaries-accsupp}
{

```

Define (or redefine) commands to use the accessibility information.

`\glsaccessname` Display the name value (no link and no check for existence).

```

\newcommand*\glsaccessname}[1]{%
\glsnameaccessdisplay
{%
\glstryname{#1}%
}%
}

```

```
{#1}%  
}
```

```
\glsaccessfmtname{<insert>}{<cs>}{<label>}
```

\glsaccessfmtname

```
\newcommand*{\glsaccessfmtname}[3]{%  
  \glsnameaccessdisplay  
  {%  
    \glsfmtfield{#1}{#2}{#3}{name}%  
  }%  
  {#3}%  
}
```

\Glsaccessname Display the name value (no link and no check for existence) with the first letter converted to upper case.

```
\newcommand*{\Glsaccessname}[1]{%  
  \glsnameaccessdisplay  
  {%  
    \Glsentryname{#1}%  
  }%  
  {#1}%  
}
```

```
\Glsaccessfmtname{<insert>}{<cs>}{<label>}
```

\Glsaccessfmtname

```
\newcommand*{\Glsaccessfmtname}[3]{%  
  \glsnameaccessdisplay  
  {%  
    \Glsfmtfield{#1}{#2}{#3}{name}%  
  }%  
  {#3}%  
}
```

\GLSaccessname Display the name value (no link and no check for existence) converted to upper case.

```
\newcommand*{\GLSaccessname}[1]{%  
  \glsnameaccessdisplay  
  {%  
    \glsuppercase{\Glsentryname{#1}}%  
  }%  
  {#1}%  
}
```

`\GLSaccessfmtname{\insert}\langle cs \rangle\langle label \rangle`

`\GLSaccessfmtname`

```
\newcommand*\GLSaccessfmtname}[3]{%
  \glsnameaccessdisplay
  {%
    \GLSfmtfield{#1}{#2}{#3}{name}%
  }%
  {#3}%
}
```

`\glsaccesstext` Display the text value (no link and no check for existence).

```
\newcommand*\glsaccesstext}[1]{%
  \glstextaccessdisplay
  {%
    \glsentrytext{#1}%
  }%
  {#1}%
}
```

`\glsaccessfmtttext{\insert}\langle cs \rangle\langle label \rangle`

`\glsaccessfmtttext`

```
\newcommand*\glsaccessfmtttext}[3]{%
  \glstextaccessdisplay
  {%
    \glsfmtfield{#1}{#2}{#3}{text}%
  }%
  {#3}%
}
```

`\Glsaccesstext` Display the text value (no link and no check for existence) with the first letter converted to upper case.

```
\newcommand*\Glsaccesstext}[1]{%
  \glstextaccessdisplay
  {%
    \Glsentrytext{#1}%
  }%
  {#1}%
}
```

`\Glsaccessfmtttext{\insert}\langle cs \rangle\langle label \rangle`

`\Glsaccessfmtttext`

```
\newcommand*\Glsaccessfmtttext}[3]{%
```



```

\glstextaccessdisplay
{%
  \Glsfmtfield{#1}{#2}{#3}{text}%
}%
{#3}%
}

```

`\GLSaccesstext` Display the text value (no link and no check for existence) converted to upper case.

```

\newcommand*{\GLSaccesstext}[1]{%
  \glstextaccessdisplay
  {%
    \glssupercase{\glentrytext{#1}}%
  }%
  {#1}%
}

```

`\GLSaccessfmttext{<insert>}{<cs>}{<label>}`

`\GLSaccessfmttext`

```

\newcommand*{\GLSaccessfmttext}[3]{%
  \glstextaccessdisplay
  {%
    \Glsfmtfield{#1}{#2}{#3}{text}%
  }%
  {#3}%
}

```

`\glsaccessplural` Display the plural value (no link and no check for existence).

```

\newcommand*{\glsaccessplural}[1]{%
  \glspluralaccessdisplay
  {%
    \glentryplural{#1}%
  }%
  {#1}%
}

```

`\glsaccessfmtplural{<insert>}{<cs>}{<label>}`

`\glsaccessfmtplural`

```

\newcommand*{\glsaccessfmtplural}[3]{%
  \glspluralaccessdisplay
  {%
    \glsfmtfield{#1}{#2}{#3}{plural}%
  }%
  {#3}%
}

```

`\Glsaccessplural` Display the plural value (no link and no check for existence) with the first letter converted to upper case.

```
\newcommand*\Glsaccessplural}[1]{%
  \glspluralaccessdisplay
  {%
    \Glsentryplural{#1}%
  }%
  {#1}%
}
```

`\Glsaccessfmtplural{<insert>}{<cs>}{<label>}`

`\Glsaccessfmtplural`

```
\newcommand*\Glsaccessfmtplural}[3]{%
  \glspluralaccessdisplay
  {%
    \Glsfmtfield{#1}{#2}{#3}{plural}%
  }%
  {#3}%
}
```

`\GLSaccessplural` Display the plural value (no link and no check for existence) converted to upper case.

```
\newcommand*\GLSaccessplural}[1]{%
  \glspluralaccessdisplay
  {%
    \glsuppercase{\Glsentryplural{#1}}%
  }%
  {#1}%
}
```

`\GLSaccessfmtplural{<insert>}{<cs>}{<label>}`

`\GLSaccessfmtplural`

```
\newcommand*\GLSaccessfmtplural}[3]{%
  \glspluralaccessdisplay
  {%
    \GLSfmtfield{#1}{#2}{#3}{plural}%
  }%
  {#3}%
}
```

`\glsaccessfirst` Display the first value (no link and no check for existence).

```
\newcommand*\glsaccessfirst}[1]{%
  \glsfirstaccessdisplay
  {%
```

```

\glentryfirst{#1}%
}%
{#1}%
}

```

```
\glsaccessfmtfirst{<insert>}{<cs>}{<label>}
```

\glsaccessfmtfirst

```

\newcommand*{\glsaccessfmtfirst}[3]{%
\glsfirstaccessdisplay
{%
\glsfmtfield{#1}{#2}{#3}{first}%
}%
{#3}%
}

```

\Glsaccessfirst Display the first value (no link and no check for existence) with the first letter converted to upper case.

```

\newcommand*{\Glsaccessfirst}[1]{%
\glsfirstaccessdisplay
{%
\glentryfirst{#1}%
}%
{#1}%
}

```

```
\Glsaccessfmtfirst{<insert>}{<cs>}{<label>}
```

\Glsaccessfmtfirst

```

\newcommand*{\Glsaccessfmtfirst}[3]{%
\glsfirstaccessdisplay
{%
\Glsfmtfield{#1}{#2}{#3}{first}%
}%
{#3}%
}

```

\GLSaccessfirst Display the first value (no link and no check for existence) converted to upper case.

```

\newcommand*{\GLSaccessfirst}[1]{%
\glsfirstaccessdisplay
{%
\glsupercase{\glentryfirst{#1}}%
}%
{#1}%
}

```

`\GLSaccessfmtfirst`

`\GLSaccessfmtfirst{<insert>}{<cs>}{<label>}`

```
\newcommand*{\GLSaccessfmtfirst}[3]{%
  \glsfirstaccessdisplay
  {%
    \GLSfmtfield{#1}{#2}{#3}{first}%
  }%
  {#3}%
}
```

`\glsaccessfirstplural` Display the firstplural value (no link and no check for existence).

```
\newcommand*{\glsaccessfirstplural}[1]{%
  \glsfirstpluralaccessdisplay
  {%
    \glentryfirstplural{#1}%
  }%
  {#1}%
}
```

`\glsaccessfmtfirstplural{<insert>}{<cs>}{<label>}`

`\glsaccessfmtfirstplural`

```
\newcommand*{\glsaccessfmtfirstplural}[3]{%
  \glsfirstpluralaccessdisplay
  {%
    \glsfmtfield{#1}{#2}{#3}{firstpl}%
  }%
  {#3}%
}
```

`\Glsaccessfirstplural` Display the firstplural value (no link and no check for existence) with the first letter converted to upper case.

```
\newcommand*{\Glsaccessfirstplural}[1]{%
  \glsfirstpluralaccessdisplay
  {%
    \Glsentryfirstplural{#1}%
  }%
  {#1}%
}
```

`\Glsaccessfmtfirstplural{<insert>}{<cs>}{<label>}`

`\Glsaccessfmtfirstplural`

```
\newcommand*{\Glsaccessfmtfirstplural}[3]{%
```

```

\glsfirstpluralaccessdisplay
{%
  \Glsfmtfield{#1}{#2}{#3}{firstpl}%
}%
{#3}%
}

```

`\GLSaccessfirstplural` Display the firstplural value (no link and no check for existence) converted to upper case.

```

\newcommand*{\GLSaccessfirstplural}[1]{%
  \glsfirstpluralaccessdisplay
  {%
    \glssupercase{\glsentryfirstplural{#1}}%
  }%
  {#1}%
}

```

`\GLSaccessfmtfirstplural{<insert>}{<cs>}{<label>}`

`\GLSaccessfmtfirstplural`

```

\newcommand*{\GLSaccessfmtfirstplural}[3]{%
  \glsfirstpluralaccessdisplay
  {%
    \Glsfmtfield{#1}{#2}{#3}{firstpl}%
  }%
  {#3}%
}

```

`\glsaccesssymbol` Display the symbol value (no link and no check for existence).

```

\newcommand*{\glsaccesssymbol}[1]{%
  \glssymbolaccessdisplay
  {%
    \glsentrysymbol{#1}%
  }%
  {#1}%
}

```

`\glsaccessfmtymsymbol{<insert>}{<cs>}{<label>}`

`\glsaccessfmtymsymbol`

```

\newcommand*{\glsaccessfmtymsymbol}[3]{%
  \glssymbolaccessdisplay
  {%
    \glsfmtfield{#1}{#2}{#3}{symbol}%
  }%
  {#3}%
}

```

`\Glsaccesssymbol` Display the symbol value (no link and no check for existence) with the first letter converted to upper case.

```
\newcommand*\Glsaccesssymbol}[1]{%
  \glssymbolaccessdisplay
  {%
    \Glsentrysymbol{#1}%
  }%
  {#1}%
}
```

`\Glsaccessfmtsymbol{<insert>}{<cs>}{<label>}`

`\Glsaccessfmtsymbol`

```
\newcommand*\Glsaccessfmtsymbol}[3]{%
  \glssymbolaccessdisplay
  {%
    \Glsfmtfield{#1}{#2}{#3}{symbol}%
  }%
  {#3}%
}
```

`\GLSaccesssymbol` Display the symbol value (no link and no check for existence) converted to upper case.

```
\newcommand*\GLSaccesssymbol}[1]{%
  \glssymbolaccessdisplay
  {%
    \glssupercase{\Glsentrysymbol{#1}}%
  }%
  {#1}%
}
```

`\GLSaccessfmtsymbol{<insert>}{<cs>}{<label>}`

`\GLSaccessfmtsymbol`

```
\newcommand*\GLSaccessfmtsymbol}[3]{%
  \glssymbolaccessdisplay
  {%
    \GLSfmtfield{#1}{#2}{#3}{symbol}%
  }%
  {#3}%
}
```

`\glsaccesssymbolplural` Display the symbolplural value (no link and no check for existence).

```
\newcommand*\glsaccesssymbolplural}[1]{%
  \glssymbolpluralaccessdisplay
  {%
```

```

\glentrysymbolplural{#1}%
}%
{#1}%
}

```

```
\glsaccessfmtsymbolplural{<insert>}{<cs>}{<label>}
```

\glsaccessfmtsymbolplural

```

\newcommand*{\glsaccessfmtsymbolplural}[3]{%
\glssymbolpluralaccessdisplay
{%
\glfmtfield{#1}{#2}{#3}{symbolplural}%
}%
{#3}%
}

```

\Glsaccesssymbolplural Display the symbolplural value (no link and no check for existence) with the first letter converted to upper case.

```

\newcommand*{\Glsaccesssymbolplural}[1]{%
\glssymbolpluralaccessdisplay
{%
\glentrysymbolplural{#1}%
}%
{#1}%
}

```

```
\Glsaccessfmtsymbolplural{<insert>}{<cs>}{<label>}
```

\Glsaccessfmtsymbolplural

```

\newcommand*{\Glsaccessfmtsymbolplural}[3]{%
\glssymbolpluralaccessdisplay
{%
\glfmtfield{#1}{#2}{#3}{symbolplural}%
}%
{#3}%
}

```

\GLSaccesssymbolplural Display the symbolplural value (no link and no check for existence) converted to upper case.

```

\newcommand*{\GLSaccesssymbolplural}[1]{%
\glssymbolpluralaccessdisplay
{%
\glsupercase{\glentrysymbolplural{#1}}%
}%
{#1}%
}

```

`\GLSaccessfmtsymbolplural`

`\GLSaccessfmtsymbolplural{<insert>}{<cs>}{<label>}`

```
\newcommand*{\GLSaccessfmtsymbolplural}[3]{%
  \glsymbolpluralaccessdisplay
  {%
    \GLSfmtfield{#1}{#2}{#3}{symbolplural}%
  }%
  {#3}%
}
```

`\glsaccessdesc` Display the desc value (no link and no check for existence).

```
\newcommand*{\glsaccessdesc}[1]{%
  \glsdescriptionaccessdisplay
  {%
    \glsentrydesc{#1}%
  }%
  {#1}%
}
```

`\glsaccessfmtdesc`

`\glsaccessfmtdesc{<insert>}{<cs>}{<label>}`

```
\newcommand*{\glsaccessfmtdesc}[3]{%
  \glsdescaccessdisplay
  {%
    \glsfmtfield{#1}{#2}{#3}{desc}%
  }%
  {#3}%
}
```

`\Glsaccessdesc` Display the desc value (no link and no check for existence) with the first letter converted to upper case.

```
\newcommand*{\Glsaccessdesc}[1]{%
  \glsdescriptionaccessdisplay
  {%
    \Glsentrydesc{#1}%
  }%
  {#1}%
}
```

`\Glsaccessfmtdesc`

`\Glsaccessfmtdesc{<insert>}{<cs>}{<label>}`

```
\newcommand*{\Glsaccessfmtdesc}[3]{%
```



```

\glsdescaccessdisplay
{%
  \Glsfmtfield{#1}{#2}{#3}{desc}%
}%
{#3}%
}

```

`\GLSaccessdesc` Display the desc value (no link and no check for existence) converted to upper case.

```

\newcommand*\GLSaccessdesc[1]{%
  \glsdescriptionaccessdisplay
  {%
    \glsuppercase{\glsentrydesc{#1}}%
  }%
  {#1}%
}

```

```
\GLSaccessfmtdesc{<insert>}{<cs>}{<label>}
```

`\GLSaccessfmtdesc`

```

\newcommand*\GLSaccessfmtdesc[3]{%
  \glsdescaccessdisplay
  {%
    \Glsfmtfield{#1}{#2}{#3}{desc}%
  }%
  {#3}%
}

```

`\glsaccessdescplural` Display the descplural value (no link and no check for existence).

```

\newcommand*\glsaccessdescplural[1]{%
  \glsdescriptionpluralaccessdisplay
  {%
    \glsentrydescplural{#1}%
  }%
  {#1}%
}

```

```
\glsaccessfmtdescplural{<insert>}{<cs>}{<label>}
```

`\glsaccessfmtdescplural`

```

\newcommand*\glsaccessfmtdescplural[3]{%
  \glsdescpluralaccessdisplay
  {%
    \glsfmtfield{#1}{#2}{#3}{descplural}%
  }%
  {#3}%
}

```

`\Glsaccessdescplural` Display the descplural value (no link and no check for existence) with the first letter converted to upper case.

```
\newcommand*\Glsaccessdescplural[1]{%
  \glsdescriptionpluralaccessdisplay
  {%
    \Glsentrydescplural{#1}%
  }%
  {#1}%
}
```

`\Glsaccessfmtdescplural{<insert>}{<cs>}{<label>}`

`\Glsaccessfmtdescplural`

```
\newcommand*\Glsaccessfmtdescplural[3]{%
  \glsdescpluralaccessdisplay
  {%
    \Glsfmtfield{#1}{#2}{#3}{descplural}%
  }%
  {#3}%
}
```

`\GLSaccessdescplural` Display the descplural value (no link and no check for existence) converted to upper case.

```
\newcommand*\GLSaccessdescplural[1]{%
  \glsdescriptionpluralaccessdisplay
  {%
    \glsuppercase{\Glsentrydescplural{#1}}%
  }%
  {#1}%
}
```

`\GLSaccessfmtdescplural{<insert>}{<cs>}{<label>}`

`\GLSaccessfmtdescplural`

```
\newcommand*\GLSaccessfmtdescplural[3]{%
  \glsdescpluralaccessdisplay
  {%
    \GLSfmtfield{#1}{#2}{#3}{descplural}%
  }%
  {#3}%
}
```

`\glsaccessshort` Display the short form (no link and no check for existence).

```
\newcommand*\glsaccessshort[1]{%
  \glsshortaccessdisplay
  {%
```

```

\glentryshort{#1}%
}%
{#1}%
}

```

```
\glsaccessfmtshort{<insert>}{<cs>}{<label>}
```

\glsaccessfmtshort

```

\newcommand*{\glsaccessfmtshort}[3]{%
\glsshortaccessdisplay
{%
\glsfmtfield{#1}{#2}{#3}{short}%
}%
{#3}%
}

```

\Glsaccessshort Display the short form with first letter converted to uppercase (no link and no check for existence).

```

\newcommand*{\Glsaccessshort}[1]{%
\glsshortaccessdisplay
{%
\glentryshort{#1}%
}%
{#1}%
}

```

```
\Glsaccessfmtshort{<insert>}{<cs>}{<label>}
```

\Glsaccessfmtshort

```

\newcommand*{\Glsaccessfmtshort}[3]{%
\glsshortaccessdisplay
{%
\Glsfmtfield{#1}{#2}{#3}{short}%
}%
{#3}%
}

```

\GLSaccessshort Display the short value (no link and no check for existence) converted to upper case.

```

\newcommand*{\GLSaccessshort}[1]{%
\glsshortaccessdisplay
{%
\glssupercase{\glentryshort{#1}}%
}%
{#1}%
}

```

`\GLSaccessfmtshort`

`\GLSaccessfmtshort{<insert>}{<cs>}{<label>}`

```
\newcommand*{\GLSaccessfmtshort}[3]{%
  \glsshortaccessdisplay
  {%
    \GLSfmtfield{#1}{#2}{#3}{short}%
  }%
  {#3}%
}
```

`\glsaccessshortpl` Display the short plural form (no link and no check for existence).

```
\newcommand*{\glsaccessshortpl}[1]{%
  \glsshortpluralaccessdisplay
  {%
    \glstryshortpl{#1}%
  }%
  {#1}%
}
```

`\glsaccessfmtshortpl`

`\glsaccessfmtshortpl{<insert>}{<cs>}{<label>}`

```
\newcommand*{\glsaccessfmtshortpl}[3]{%
  \glsshortpluralaccessdisplay
  {%
    \glsfmtfield{#1}{#2}{#3}{shortpl}%
  }%
  {#3}%
}
```

`\Glsaccessshortpl` Display the short plural form with first letter converted to uppercase (no link and no check for existence).

```
\newcommand*{\Glsaccessshortpl}[1]{%
  \glsshortpluralaccessdisplay
  {%
    \Glsentryshortpl{#1}%
  }%
  {#1}%
}
```

`\Glsaccessfmtshortpl`

`\Glsaccessfmtshortpl{<insert>}{<cs>}{<label>}`

```
\newcommand*{\Glsaccessfmtshortpl}[3]{%
  \glsshortpluralaccessdisplay
  {%
    \Glsentryshortpl{#1}%
  }%
  {#3}%
}
```

```

\glsshortpluralaccessdisplay
{%
  \Glsfmtfield{#1}{#2}{#3}{shortpl}%
}%
{#3}%
}

```

`\GLSaccessshortpl` Display the shortplural value (no link and no check for existence) converted to upper case.

```

\newcommand*{\GLSaccessshortpl}[1]{%
  \glsshortpluralaccessdisplay
  {%
    \glssuppercase{\glentryshortpl{#1}}%
  }%
  {#1}%
}

```

`\GLSaccessfmtshortpl{<insert>}{<cs>}{<label>}`

`\GLSaccessfmtshortpl`

```

\newcommand*{\GLSaccessfmtshortpl}[3]{%
  \glsshortpluralaccessdisplay
  {%
    \Glsfmtfield{#1}{#2}{#3}{shortpl}%
  }%
  {#3}%
}

```

`\glsaccesslong` Display the long form (no link and no check for existence).

```

\newcommand*{\glsaccesslong}[1]{%
  \glslongaccessdisplay{\glentrylong{#1}}{#1}%
}

```

`\glsaccessfmtlong{<insert>}{<cs>}{<label>}`

`\glsaccessfmtlong`

```

\newcommand*{\glsaccessfmtlong}[3]{%
  \glslongaccessdisplay
  {%
    \glsfmtfield{#1}{#2}{#3}{long}%
  }%
  {#3}%
}

```

`\Glsaccesslong` Display the long form (no link and no check for existence).

```

\newcommand*{\Glsaccesslong}[1]{%

```

```
\glslongaccessdisplay{\Glsentrylong{#1}}{#1}%
}
```

```
\Glsaccessfmtlong{<insert>}{<cs>}{<label>}
```

\Glsaccessfmtlong

```
\newcommand*\Glsaccessfmtlong[3]{%
  \glslongaccessdisplay
  {%
    \Glsfmtfield{#1}{#2}{#3}{long}%
  }%
  {#3}%
}
```

\GLSaccesslong Display the long value (no link and no check for existence) converted to upper case.

```
\newcommand*\GLSaccesslong[1]{%
  \glslongaccessdisplay
  {%
    \glsuppercase{\Glsentrylong{#1}}%
  }%
  {#1}%
}
```

```
\GLSaccessfmtlong{<insert>}{<cs>}{<label>}
```

\GLSaccessfmtlong

```
\newcommand*\GLSaccessfmtlong[3]{%
  \glslongaccessdisplay
  {%
    \GLSfmtfield{#1}{#2}{#3}{long}%
  }%
  {#3}%
}
```

\glsaccesslongpl Display the long plural form (no link and no check for existence).

```
\newcommand*\glsaccesslongpl[1]{%
  \glslongpluralaccessdisplay{\Glsentrylongpl{#1}}{#1}%
}
```

```
\glsaccessfmtlongpl{<insert>}{<cs>}{<label>}
```

\glsaccessfmtlongpl

```
\newcommand*\glsaccessfmtlongpl[3]{%
  \glsaccesslongpl{#1}{#2}{#3}%
}
```

```

\glslongpluralaccessdisplay
{%
  \glsfmtfield{#1}{#2}{#3}{longpl}%
}%
{#3}%
}

```

`\Glsaccesslongpl` Display the long plural form (no link and no check for existence).

```

\newcommand*{\Glsaccesslongpl}[1]{%
  \glslongpluralaccessdisplay{\Glsentrylongpl{#1}}{#1}%
}

```

```

\Glsaccessfmtlongpl{<insert>}{<cs>}{<label>}

```

`\Glsaccessfmtlongpl`

```

\newcommand*{\Glsaccessfmtlongpl}[3]{%
  \glslongpluralaccessdisplay
  {%
    \Glsfmtfield{#1}{#2}{#3}{longpl}%
  }%
  {#3}%
}

```

`\GLSaccesslongpl` Display the longplural value (no link and no check for existence) converted to upper case.

```

\newcommand*{\GLSaccesslongpl}[1]{%
  \glslongpluralaccessdisplay
  {%
    \glsuppercase{\Glsentrylongpl{#1}}%
  }%
  {#1}%
}

```

```

\GLSaccessfmtlongpl{<insert>}{<cs>}{<label>}

```

`\GLSaccessfmtlongpl`

```

\newcommand*{\GLSaccessfmtlongpl}[3]{%
  \glslongpluralaccessdisplay
  {%
    \GLSfmtfield{#1}{#2}{#3}{longpl}%
  }%
  {#3}%
}

```

The user accessibility fields were added to glossaries-accsupp v4.45 so these may not be defined.

USER1

`\glsaccessuseri` Display the `user1` value (no link and no check for existence).

```
\ifdef\glsuseriaccessdisplay
{
  \newcommand*{\glsaccessuseri}[1]{%
    \glsuseriaccessdisplay
    {%
      \glsentryuseri{#1}%
    }%
    {#1}%
  }
}
{
  \newcommand*{\glsaccessuseri}[1]{%
    \glsentryuseri{#1}%
  }
}
```

`\glsaccessfmtuseri{<insert>}{<cs>}{<label>}`

`\glsaccessfmtuseri`

```
\ifdef\glsuseriaccessdisplay
{
  \newcommand*{\glsaccessfmtuseri}[3]{%
    \glsuseriaccessdisplay
    {%
      \glsfmtfield{#1}{#2}{#3}{useri}%
    }%
    {#3}%
  }
}
{
  \newcommand*{\glsaccessfmtuseri}[3]{%
    \glsfmtfield{#1}{#2}{#3}{useri}%
  }
}
```

`\Glsaccessuseri` Display the `user1` value (no link and no check for existence) with the first letter converted to upper case.

```
\ifdef\glsuseriaccessdisplay
{
  \newcommand*{\Glsaccessuseri}[1]{%
    \glsuseriaccessdisplay
    {%
      \Glsentryuseri{#1}%
    }
  }
}
```



```

    }%
    {#1}%
  }
}
{
  \newcommand*{\Glsaccessuseri}[1]{%
    \Glsentryuseri{#1}%
  }
}

```

```
\Glsaccessfmtuseri{<insert>}{<cs>}{<label>}
```

\Glsaccessfmtuseri

```

\ifdef\glsuseriaccessdisplay
{
  \newcommand*{\Glsaccessfmtuseri}[3]{%
    \glsuseriaccessdisplay
    {%
      \Glsfmtfield{#1}{#2}{#3}{useri}%
    }%
    {#3}%
  }
}
{
  \newcommand*{\Glsaccessfmtuseri}[3]{%
    \Glsfmtfield{#1}{#2}{#3}{useri}%
  }
}

```

\GLSaccessuseri Display the user1 value (no link and no check for existence) converted to upper case.

```

\ifdef\glsuseriaccessdisplay
{
  \newcommand*{\GLSaccessuseri}[1]{%
    \glsuseriaccessdisplay
    {%
      \glsuppercase{\glsentryuseri{#1}}%
    }%
    {#1}%
  }
}
{
  \newcommand*{\GLSaccessuseri}[1]{%
    \glsuppercase{\glsentryuseri{#1}}%
  }
}

```

`\GLSaccessfmtuseri{<insert>}{<cs>}{<label>}`

`\GLSaccessfmtuseri`

```
\ifdef\glsuseriaccessdisplay
{
  \newcommand*{\GLSaccessfmtuseri}[3]{%
    \glsuseriaccessdisplay
    {%
      \GLSfmtfield{#1}{#2}{#3}{useri}%
    }%
    {#3}%
  }
}
{
  \newcommand*{\GLSaccessfmtuseri}[3]{%
    \GLSfmtfield{#1}{#2}{#3}{useri}%
  }
}
```

USER2

`\glsaccessuserii` Display the user2 value (no link and no check for existence).

```
\ifdef\glsuseriiaccessdisplay
{
  \newcommand*{\glsaccessuserii}[1]{%
    \glsuseriiaccessdisplay
    {%
      \glsentryuserii{#1}%
    }%
    {#1}%
  }
}
{
  \newcommand*{\glsaccessuserii}[1]{%
    \glsentryuserii{#1}%
  }
}
```

`\glsaccessfmtuserii{<insert>}{<cs>}{<label>}`

`\glsaccessfmtuserii`

```
\ifdef\glsuseriiaccessdisplay
{
  \newcommand*{\glsaccessfmtuserii}[3]{%
    \glsuseriiaccessdisplay
    {%
      \glsfmtfield{#1}{#2}{#3}{userii}%
    }%
    {#3}%
  }
}
```

```

    }%
    {#3}%
  }
}
{
  \newcommand*{\Glsaccessfmtuserii}[3]{%
    \Glsfmtfield{#1}{#2}{#3}{userii}%
  }
}

```

`\Glsaccessuserii` Display the user2 value (no link and no check for existence) with the first letter converted to upper case.

```

\ifdef\glsuseriiaccessdisplay
{
  \newcommand*{\Glsaccessuserii}[1]{%
    \glsuseriiaccessdisplay
    {%
      \Glsentryuserii{#1}%
    }%
    {#1}%
  }
}
{
  \newcommand*{\Glsaccessuserii}[1]{%
    \Glsentryuserii{#1}%
  }
}

```

`\Glsaccessfmtuserii{<insert>}{<cs>}{<label>}`

`\Glsaccessfmtuserii`

```

\ifdef\glsuseriiaccessdisplay
{
  \newcommand*{\Glsaccessfmtuserii}[3]{%
    \glsuseriiaccessdisplay
    {%
      \Glsfmtfield{#1}{#2}{#3}{userii}%
    }%
    {#3}%
  }
}
{
  \newcommand*{\Glsaccessfmtuserii}[3]{%
    \Glsfmtfield{#1}{#2}{#3}{userii}%
  }
}

```

`\Glsaccessuserii` Display the user2 value (no link and no check for existence) converted to upper

case.

```
\ifdef\glsuseriiaccessdisplay
{
  \newcommand*\GLSaccessuserii[1]{%
    \glsuseriiaccessdisplay
    {%
      \glssupercase{\glsentryuserii{#1}}%
    }%
    {#1}%
  }
}
{
  \newcommand*\GLSaccessuserii[1]{%
    \glssupercase{\glsentryuserii{#1}}%
  }
}
```

`\GLSaccessfmtuserii{<insert>}{<cs>}{<label>}`

`\GLSaccessfmtuserii`

```
\ifdef\glsuseriiaccessdisplay
{
  \newcommand*\GLSaccessfmtuserii[3]{%
    \glsuseriiaccessdisplay
    {%
      \GLSfmtfield{#1}{#2}{#3}{userii}%
    }%
    {#3}%
  }
}
{
  \newcommand*\GLSaccessfmtuserii[3]{%
    \GLSfmtfield{#1}{#2}{#3}{userii}%
  }
}
```

USER3

`\glsaccessuseriii` Display the user3 value (no link and no check for existence).

```
\ifdef\glsuseriiiaccessdisplay
{
  \newcommand*\glsaccessuseriii[1]{%
    \glsuseriiiaccessdisplay
    {%
      \glsentryuseriii{#1}%
    }%
    {#1}%
  }
}
```

```

}
{
  \newcommand*{\glsaccessuseriii}[1]{%
    \glsentryuseriii{#1}%
  }
}

```

```
\glsaccessfmtuseriii{<insert>}{<cs>}{<label>}
```

\glsaccessfmtuseriii

```

\ifdef\glsuseriiiaccessdisplay
{
  \newcommand*{\glsaccessfmtuseriii}[3]{%
    \glsuseriiiaccessdisplay
    {%
      \glsfmtfield{#1}{#2}{#3}{useriii}%
    }%
    {#3}%
  }
}
{
  \newcommand*{\glsaccessfmtuseriii}[3]{%
    \glsfmtfield{#1}{#2}{#3}{useriii}%
  }
}

```

\Glsaccessuseriii Display the user3 value (no link and no check for existence) with the first letter converted to upper case.

```

\ifdef\glsuseriiiaccessdisplay
{
  \newcommand*{\Glsaccessuseriii}[1]{%
    \glsuseriiiaccessdisplay
    {%
      \Glsentryuseriii{#1}%
    }%
    {#1}%
  }
}
{
  \newcommand*{\Glsaccessuseriii}[1]{%
    \Glsentryuseriii{#1}%
  }
}

```

```
\Glsaccessfmtuseriii{<insert>}{<cs>}{<label>}
```

\Glsaccessfmtuseriii

```

\ifdef\glsuseriiiaccessdisplay
{
  \newcommand*\Glsaccessfmtuseriii}[3]{%
    \glsuseriiiaccessdisplay
    {%
      \Glsfmtfield{#1}{#2}{#3}{useriii}%
    }%
    {#3}%
  }
}
{
  \newcommand*\Glsaccessfmtuseriii}[3]{%
    \Glsfmtfield{#1}{#2}{#3}{useriii}%
  }
}

```

`\GLSaccessuseriii` Display the user3 value (no link and no check for existence) converted to upper case.

```

\ifdef\glsuseriiiaccessdisplay
{
  \newcommand*\GLSaccessuseriii}[1]{%
    \glsuseriiiaccessdisplay
    {%
      \glsuppercase{\glentryuseriii{#1}}%
    }%
    {#1}%
  }
}
{
  \newcommand*\GLSaccessuseriii}[1]{%
    \glsuppercase{\glentryuseriii{#1}}%
  }
}

```

```
\GLSaccessfmtuseriii{\<insert>}{\<cs>}{\<label>}
```

`\GLSaccessfmtuseriii`

```

\ifdef\glsuseriiiaccessdisplay
{
  \newcommand*\GLSaccessfmtuseriii}[3]{%
    \glsuseriiiaccessdisplay
    {%
      \GLSfmtfield{#1}{#2}{#3}{useriii}%
    }%
    {#3}%
  }
}

```

```

{
  \newcommand*{\GLSaccessfmtuseriii}[3]{%
    \GLSfmtfield{#1}{#2}{#3}{useriii}%
  }
}

```

USER4

`\glsaccessuseriv` Display the user4 value (no link and no check for existence).

```

\ifdef\glsuserivaccessdisplay
{
  \newcommand*{\glsaccessuseriv}[1]{%
    \glsuserivaccessdisplay
    {%
      \glsentryuseriv{#1}%
    }%
    {#1}%
  }
}
{
  \newcommand*{\glsaccessuseriv}[1]{%
    \glsentryuseriv{#1}%
  }
}

```

`\glsaccessfmtuseriv{<insert>}{<cs>}{<label>}`

`\glsaccessfmtuseriv`

```

\ifdef\glsuserivaccessdisplay
{
  \newcommand*{\glsaccessfmtuseriv}[3]{%
    \glsuserivaccessdisplay
    {%
      \glsfmtfield{#1}{#2}{#3}{useriv}%
    }%
    {#3}%
  }
}
{
  \newcommand*{\glsaccessfmtuseriv}[3]{%
    \glsfmtfield{#1}{#2}{#3}{useriv}%
  }
}

```

`\Glsaccessuseriv` Display the user4 value (no link and no check for existence) with the first letter converted to upper case.

```

\ifdef\glsuserivaccessdisplay
{

```

```

\newcommand*\Glsaccessuseriv}[1]{%
  \glsuserivaccessdisplay
  {%
    \Glsentryuseriv{#1}%
  }%
  {#1}%
}
}
{
  \newcommand*\Glsaccessuseriv}[1]{%
    \Glsentryuseriv{#1}%
  }
}

```

```
\Glsaccessfmtuseriv{<insert>}{<cs>}{<label>}
```

\Glsaccessfmtuseriv

```

\ifdef\glsuserivaccessdisplay
{
  \newcommand*\Glsaccessfmtuseriv}[3]{%
    \glsuserivaccessdisplay
    {%
      \Glsfmtfield{#1}{#2}{#3}{useriv}%
    }%
    {#3}%
  }
}
{
  \newcommand*\Glsaccessfmtuseriv}[3]{%
    \Glsfmtfield{#1}{#2}{#3}{useriv}%
  }
}

```

\GLSaccessuseriv Display the user4 value (no link and no check for existence) converted to upper case.

```

\ifdef\glsuserivaccessdisplay
{
  \newcommand*\GLSaccessuseriv}[1]{%
    \glsuserivaccessdisplay
    {%
      \glsuppercase{\Glsentryuseriv{#1}}%
    }%
    {#1}%
  }
}
{
  \newcommand*\GLSaccessuseriv}[1]{%
    \glsuppercase{\Glsentryuseriv{#1}}%
  }
}

```



```

    }
}

```

```
\GLSaccessfmtuseriv{<insert>}{<cs>}{<label>}
```

\GLSaccessfmtuseriv

```

\ifdef\glsuserivaccessdisplay
{
  \newcommand*{\GLSaccessfmtuseriv}[3]{%
    \glsuserivaccessdisplay
    {%
      \GLSfmtfield{#1}{#2}{#3}{useriv}%
    }%
    {#3}%
  }
}
{
  \newcommand*{\GLSaccessfmtuseriv}[3]{%
    \GLSfmtfield{#1}{#2}{#3}{useriv}%
  }
}

```

USER5

\glsaccessuserv Display the user5 value (no link and no check for existence).

```

\ifdef\glsuservaccessdisplay
{
  \newcommand*{\glsaccessuserv}[1]{%
    \glsuservaccessdisplay
    {%
      \glsentryuserv{#1}%
    }%
    {#1}%
  }
}
{
  \newcommand*{\glsaccessuserv}[1]{%
    \glsentryuserv{#1}%
  }
}

```

```
\glsaccessfmtuserv{<insert>}{<cs>}{<label>}
```

\glsaccessfmtuserv

```

\ifdef\glsuservaccessdisplay
{
  \newcommand*{\glsaccessfmtuserv}[3]{%

```

```

\glsuservaccessdisplay
{%
\glsfmtfield{#1}{#2}{#3}{userv}%
}%
{#3}%
}
}
{
\newcommand*{\glsaccessfmtuserv}[3]{%
\glsfmtfield{#1}{#2}{#3}{userv}%
}
}

```

`\Glsaccessuserv` Display the `user5` value (no link and no check for existence) with the first letter converted to upper case.

```

\ifdef\glsuservaccessdisplay
{
\newcommand*{\Glsaccessuserv}[1]{%
\glsuservaccessdisplay
{%
\Glsentryuserv{#1}%
}%
{#1}%
}
}
{
\newcommand*{\Glsaccessuserv}[1]{%
\Glsentryuserv{#1}%
}
}

```

```
\Glsaccessfmtuserv{\insert}{\cs}{\label}}
```

`\Glsaccessfmtuserv`

```

\ifdef\glsuservaccessdisplay
{
\newcommand*{\Glsaccessfmtuserv}[3]{%
\glsuservaccessdisplay
{%
\Glsfmtfield{#1}{#2}{#3}{userv}%
}%
{#3}%
}
}
{
\newcommand*{\Glsaccessfmtuserv}[3]{%
\Glsfmtfield{#1}{#2}{#3}{userv}%
}
}

```

}

\GLSaccessuserv Display the user5 value (no link and no check for existence) converted to upper case.

```
\ifdef\glsuservaccessdisplay
{
  \newcommand*{\GLSaccessuserv}[1]{%
    \glsuservaccessdisplay
    {%
      \glsuppercase{\glsentryuserv{#1}}%
    }%
    {#1}%
  }
}
{
  \newcommand*{\GLSaccessuserv}[1]{%
    \glsuppercase{\glsentryuserv{#1}}%
  }
}
```

\GLSaccessfmtuserv{<insert>}{<cs>}{<label>}

\GLSaccessfmtuserv

```
\ifdef\glsuservaccessdisplay
{
  \newcommand*{\GLSaccessfmtuserv}[3]{%
    \glsuservaccessdisplay
    {%
      \GLSfmtfield{#1}{#2}{#3}{userv}%
    }%
    {#3}%
  }
}
{
  \newcommand*{\GLSaccessfmtuserv}[3]{%
    \GLSfmtfield{#1}{#2}{#3}{userv}%
  }
}
```

USER6

\glsaccessuservi Display the user6 value (no link and no check for existence).

```
\ifdef\glsuserviaccessdisplay
{
  \newcommand*{\glsaccessuservi}[1]{%
    \glsuserviaccessdisplay
    {%
      \glsentryuservi{#1}%
    }
```

```

    }%
    {#1}%
  }
}
{
  \newcommand*{\glsaccessuservi}[1]{%
    \glsentryuservi{#1}%
  }
}

```

```
\glsaccessfmtuservi{<insert>}{<cs>}{<label>}
```

\glsaccessfmtuservi

```

\ifdef\glsuserviaccessdisplay
{
  \newcommand*{\glsaccessfmtuservi}[3]{%
    \glsuserviaccessdisplay
    {%
      \glsfmtfield{#1}{#2}{#3}{uservi}%
    }%
    {#3}%
  }
}
{
  \newcommand*{\glsaccessfmtuservi}[3]{%
    \glsfmtfield{#1}{#2}{#3}{uservi}%
  }
}

```

\Glsaccessuservi Display the user6 value (no link and no check for existence) with the first letter converted to upper case.

```

\ifdef\glsuserviaccessdisplay
{
  \newcommand*{\Glsaccessuservi}[1]{%
    \glsuserviaccessdisplay
    {%
      \Glsentryuservi{#1}%
    }%
    {#1}%
  }
}
{
  \newcommand*{\Glsaccessuservi}[1]{%
    \Glsentryuservi{#1}%
  }
}

```

```
\Glsaccessfmtuservi{<insert>}{<cs>}{<label>}
```

\Glsaccessfmtuservi

```
\ifdef\glsuserviaccessdisplay
{
  \newcommand*{\Glsaccessfmtuservi}[3]{%
    \glsuserviaccessdisplay
    {%
      \Glsfmtfield{#1}{#2}{#3}{uservi}%
    }%
    {#3}%
  }
}
{
  \newcommand*{\Glsaccessfmtuservi}[3]{%
    \Glsfmtfield{#1}{#2}{#3}{uservi}%
  }
}
```

\GLSaccessuservi Display the user6 value (no link and no check for existence) converted to upper case.

```
\ifdef\glsuserviaccessdisplay
{
  \newcommand*{\GLSaccessuservi}[1]{%
    \glsuserviaccessdisplay
    {%
      \glsuppercase{\glsentryuservi{#1}}%
    }%
    {#1}%
  }
}
{
  \newcommand*{\GLSaccessuservi}[1]{%
    \glsuppercase{\glsentryuservi{#1}}%
  }
}
```

```
\GLSaccessfmtuservi{<insert>}{<cs>}{<label>}
```

\GLSaccessfmtuservi

```
\ifdef\glsuserviaccessdisplay
{
  \newcommand*{\GLSaccessfmtuservi}[3]{%
    \glsuserviaccessdisplay
    {%
      \GLSfmtfield{#1}{#2}{#3}{uservi}%
    }%
  }
}
```

```

    {#3}%
  }
}
{
  \newcommand*{\GLSaccessfmtuservi}[3]{%
    \GLSfmtfield{#1}{#2}{#3}{uservi}%
  }
}

```

Keys for accessibility support while pre-parsing in \newabbreviation.

```

\define@key{glstrabbrv}{access}{%
  \def\@gls@nameaccess{#1}%
}

\define@key{glstrabbrv}{textaccess}{%
  \def\@gls@textaccess{#1}%
}

\define@key{glstrabbrv}{pluralaccess}{%
  \def\@gls@pluralaccess{#1}%
}

\define@key{glstrabbrv}{firstaccess}{%
  \def\@gls@firstaccess{#1}%
}

\define@key{glstrabbrv}{firstpluralaccess}{%
  \def\@gls@firstpluralaccess{#1}%
}

\define@key{glstrabbrv}{shortaccess}{%
  \def\@gls@shortaccess{#1}%
}

\define@key{glstrabbrv}{shortpluralaccess}{%
  \def\@gls@shortaccesspl{#1}%
}

\define@key{glstrabbrv}{longaccess}{%
  \def\@gls@longaccess{#1}%
}

\define@key{glstrabbrv}{longpluralaccess}{%
  \def\@gls@longaccesspl{#1}%
}

```

\@gls@initaccesskeys

```

\newcommand*{\@gls@initaccesskeys}{%
  \def\@gls@nameaccess{}%
  \def\@gls@textaccess{}%
  \def\@gls@pluralaccess{}%
  \def\@gls@firstaccess{}%
  \def\@gls@firstpluralaccess{}%
  \def\@gls@shortaccess{}%
}

```

```

\def\@gls@shortaccesspl{}%
\def\@gls@longaccess{}%
\def\@gls@longaccesspl{}%
}

```

```
\gls@ifaccessattribute@set{<attribute>}{<true>}{<false>}
```

```
\@gls@ifaccessattribute@set
```

```

\newcommand*{\@gls@ifaccessattribute@set}[3]{%
\glsifcategoryattribute{\glscategorylabel}{access#1}{true}%
{#2}%
{%
\glsifcategoryattribute{\glscategorylabel}{access#1}{false}%
{#3}%
{%
\glsifcategoryattribute{\glscategorylabel}{#1}{true}%
{#2}%
{#3}%
}%
}%
}

```

As from glossaries v4.45, the replacement text support has been corrected so that the accessibility support for abbreviations use the “E” (expanded value) element. This should actually contain the long form since it’s supposed to explain the abbreviation. This is a bit redundant on first use for styles like long-short.

```
\glsdefaultshortaccess{<long>}{<short>}
```

```
\glsdefaultshortaccess
```

This command was only introduced to glossaries-accsupp 4.45 so it may not be defined. This was defined to do #1 (#2) but the original definition is more appropriate, so has been reverted back to the definition provided by glossaries-accsupp.

```
\providecommand*{\glsdefaultshortaccess}[2]{#1}
```

```
\glsxtrassignactualsetup
```

```

\newcommand{\glsxtrassignactualsetup}{%
\let\@empty
\let\emph\@firstofone
\let\textbf\@firstofone
\let\textmd\@firstofone
\let\textit\@firstofone
\let\textsl\@firstofone
\let\textsc\@firstofone
\let\textrm\@firstofone
}

```

```

\let\textsf\@firstofone
\let\texttt\@firstofone
\let\glstextup\@firstofone
}

```

\@gls@assign@actual

```

\newcommand{\@gls@assign@actual}{%
\begingroup
\glstrassignactualsetup
\protected@edef\@gls@tmp{\endgroup
\def\noexpand\@gls@actualshort{\glstrorgshort}%
\def\noexpand\@gls@actuallong{\glstrorglong}%
\def\noexpand\@gls@actualshortpl{\@gls@shortpl}%
\def\noexpand\@gls@actuallongpl{\@gls@longpl}%
}%
\@gls@tmp
}

```

\@setup@default@short@access Renamed \@gls@setup@default@access and removed argument since it can be obtained from \glstrorgshort.

\@gls@setup@default@access Assign the default value of the shortaccess key. The argument is the short value passed to \newabbreviation. The shortaccess value should explain the abbreviation.

```

\newcommand{\@gls@setup@default@access}{%
\@gls@assign@actual
\ifdefempty\@gls@shortaccess
{%

```

Check if the accessinsertdots attribute has been set but only if shortaccess hasn't been set.

```

\@gls@ifaccessattribute@set{insertdots}%
{%
\expandafter\@glstr@insertdots\expandafter\@gls@actualshort\expandafter
{\@gls@actualshort}%
}%
}%
\ifdefempty\@gls@longaccess
{%
\protected@edef\@gls@shortaccess{\glsdefaultshortaccess
{\expandonce\@gls@actuallong}{\expandonce\@gls@actualshort}}%
}%
{%
\protected@edef\@gls@shortaccess{\glsdefaultshortaccess
{\expandonce\@gls@longaccess}{\expandonce\@gls@actualshort}}%
}%
\ea\ppto\ExtraCustomAbbreviationFields{shortaccess={\@gls@shortaccess},}%

```

If shortaccessplural hasn't been set, assign plural form.


```

\ifdefempty\@gls@shortaccesspl
{%
  \@gls@ifaccessattribute@set{aposplural}%
  {%
    \expandafter\def\expandafter\@gls@shortaccesspl\expandafter{%
      \@gls@actualshort'\glsextrabrvpluralsuffix}%
    }%
    {%
      \@gls@ifaccessattribute@set{noshortplural}%
      {%
        \let\@gls@shortaccesspl\@gls@shortaccess
      }%
      {%
        \let\@gls@shortaccesspl\@gls@actualshortpl
      }%
    }%
  }%
\ifdefempty\@gls@longaccesspl
{%
  \protected@edef\@gls@shortaccesspl{\glsdefaultshortaccess
    {\expandonce\@gls@actualallongpl}{\expandonce\@gls@actualshortpl}}%
  }%
  {%
    \protected@edef\@gls@shortaccesspl{\glsdefaultshortaccess
      {\expandonce\@gls@longaccesspl}{\expandonce\@gls@actualshort}}%
    }%
  \eappto\ExtraCustomAbbreviationFields{shortpluralaccess={\@gls@shortaccesspl},}%
  }%
  {}%
}%
{%
  \ifdefempty\@gls@shortaccesspl
  {\let\@gls@shortaccesspl\@gls@shortaccess}%
  {}%
}%

```

If access key hasn't been set, check if the nameshortaccess attribute has been set.

```

\ifdefempty\@gls@nameaccess
{%
  \glsifcategoryattribute{\glscategorylabel}{nameshortaccess}{true}%
  {%
    \eappto\ExtraCustomAbbreviationFields{access={\@gls@shortaccess},}%
    }%
    {}%
  }%
  {}%

```

If textaccess key hasn't been set, check if the textshortaccess attribute has been set.

```

\ifdefempty\@gls@textaccess

```

```

{%
  \glsifcategoryattribute{\glscategorylabel}{textshortaccess}{true}%
  {%
    \eappto\ExtraCustomAbbreviationFields{textaccess={\@gls@shortaccess},}%
  }%
  {}%
}%
{}%
\ifdefempty\@gls@pluralaccess
{%
  \glsifcategoryattribute{\glscategorylabel}{textshortaccess}{true}%
  {%
    \eappto\ExtraCustomAbbreviationFields{%
      pluralaccess={\@gls@shortaccesspl},%
    }%
  }%
  {}%
}%
{}%

```

If firstaccess key hasn't been set, check if the firstshortaccess attribute has been set.

```

\ifdefempty\@gls@firstaccess
{%
  \glsifcategoryattribute{\glscategorylabel}{firstshortaccess}{true}%
  {%
    \eappto\ExtraCustomAbbreviationFields{firstaccess={\@gls@shortaccess},}%
  }%
  {}%
}%
{}%
\ifdefempty\@gls@firstpluralaccess
{%
  \glsifcategoryattribute{\glscategorylabel}{firstshortaccess}{true}%
  {%
    \eappto\ExtraCustomAbbreviationFields{%
      firstpluralaccess={\@gls@shortaccesspl},%
    }%
  }%
  {}%
}%
{}%
}

```

Provide hooks for `\setabbreviationstyle` that automatically set the attributes appropriate for the style. If the name is just the short form and the description contains the long form, then it may not be necessary to set `nameshortaccess` but it would depend on the glossary style.

Need to provide `\glsxtr<category>\<field>accsupp` if not already defined.

`\glxtrprovideaccsuppcmd`

```
\newcommand*{\glxtrprovideaccsuppcmd}[2]{%
  \ifcsundef{glxtr#1#2accsup}%
  {\csdef{glxtr#1#2accsup}{\glsshortaccsup}}%
  {}%
}
```

`trAccSuppAbbrSetNoLongAttrs` For styles where the name, first and text are just the abbreviation.

```
\newcommand*{\glxtrAccSuppAbbrSetNoLongAttrs}[1]{%
  \glssetcategoryattribute{#1}{nameshortaccess}{true}%
  \glssetcategoryattribute{#1}{firstshortaccess}{true}%
  \glssetcategoryattribute{#1}{textshortaccess}{true}%
  \glxtrprovideaccsuppcmd{#1}{name}%
  \glxtrprovideaccsuppcmd{#1}{first}%
  \glxtrprovideaccsuppcmd{#1}{firstpl}%
  \glxtrprovideaccsuppcmd{#1}{text}%
  \glxtrprovideaccsuppcmd{#1}{plural}%
}
```

`ccSuppAbbrSetFirstLongAttrs` For styles where the name and text are just the abbreviation. The first form may just be long or may be short and long.

```
\newcommand*{\glxtrAccSuppAbbrSetFirstLongAttrs}[1]{%
  \glssetcategoryattribute{#1}{nameshortaccess}{true}%
  \glssetcategoryattribute{#1}{textshortaccess}{true}%
  \glxtrprovideaccsuppcmd{#1}{name}%
  \glxtrprovideaccsuppcmd{#1}{text}%
  \glxtrprovideaccsuppcmd{#1}{plural}%
}
```

`ccSuppAbbrSetTextShortAttrs` For styles where only the text is just the abbreviation. The name and first form may just be long or may be short and long. The name may also be short but followed by the long form in the description.

```
\newcommand*{\glxtrAccSuppAbbrSetTextShortAttrs}[1]{%
  \glssetcategoryattribute{#1}{textshortaccess}{true}%
  \glxtrprovideaccsuppcmd{#1}{text}%
  \glxtrprovideaccsuppcmd{#1}{plural}%
}
```

`ccSuppAbbrSetNameShortAttrs` For styles where only the name is just the abbreviation. The first and subsequent form may just be long or may be short and long.

```
\newcommand*{\glxtrAccSuppAbbrSetNameShortAttrs}[1]{%
  \glssetcategoryattribute{#1}{nameshortaccess}{true}%
  \glxtrprovideaccsuppcmd{#1}{name}%
}
```

`AccSuppAbbrSetNameLongAttrs` For styles where the first and text are just the abbreviation. The name may just be long or may be short and long or the name may be short.

```
\newcommand*{\glxtrAccSuppAbbrSetNameLongAttrs}[1]{%
```

```

\glsetcategoryattribute{#1}{firstshortaccess}{true}%
\glsetcategoryattribute{#1}{textshortaccess}{true}%
\glxtrprovideaccsuppcmd{#1}{first}%
\glxtrprovideaccsuppcmd{#1}{firstpl}%
\glxtrprovideaccsuppcmd{#1}{text}%
\glxtrprovideaccsuppcmd{#1}{plural}%
}

```

End of if accsupp part

```

}
{

```

No accessibility support. Just define these commands to do `\glentry<xxx>`

`\glsaccessname` Display the name value (no link and no check for existence).

```

\newcommand*{\glsaccessname}[1]{\glentryname{#1}}

```

`\glsaccessfmtname`

```

\glsaccessfmtname{<insert>}{<cs>}{<label>}

```

```

\newcommand*{\glsaccessfmtname}[3]{%
\glsfmtfield{#1}{#2}{#3}{name}%
}

```

`\Glsaccessname` Display the name value (no link and no check for existence) with the first letter converted to upper case.

```

\newcommand*{\Glsaccessname}[1]{\glentryname{#1}}

```

`\Glsaccessfmtname`

```

\Glsaccessfmtname{<insert>}{<cs>}{<label>}

```

```

\newcommand*{\Glsaccessfmtname}[3]{%
\Glsfmtfield{#1}{#2}{#3}{name}%
}

```

`\GLSaccessname` Display the name value (no link and no check for existence). converted to upper case.

```

\newcommand*{\GLSaccessname}[1]{%
\protect\glsuppercase{\glentryname{#1}}}

```

`\GLSaccessfmtname`

```

\GLSaccessfmtname{<insert>}{<cs>}{<label>}

```

```

\newcommand*{\GLSaccessfmtname}[3]{%
\GLSfmtfield{#1}{#2}{#3}{name}%
}

```

`\glsaccesstext` Display the text value (no link and no check for existence).

```
\newcommand*{\glsaccesstext}[1]{\glsentrytext{#1}}
```

`\glsaccessfmttext`

```
\glsaccessfmttext{<insert>}{<cs>}{<label>}
```

```
\newcommand*{\glsaccessfmttext}[3]{%  
  \glsfmtfield{#1}{#2}{#3}{text}%  
}
```

`\Glsaccesstext` Display the text value (no link and no check for existence) with the first letter converted to upper case.

```
\newcommand*{\Glsaccesstext}[1]{\Glsentrytext{#1}}
```

`\Glsaccessfmttext`

```
\Glsaccessfmttext{<insert>}{<cs>}{<label>}
```

```
\newcommand*{\Glsaccessfmttext}[3]{%  
  \Glsfmtfield{#1}{#2}{#3}{text}%  
}
```

`\GLSaccesstext` Display the text value (no link and no check for existence). converted to upper case.

```
\newcommand*{\GLSaccesstext}[1]{%  
  \protect\glsuppercase{\glsentrytext{#1}}}
```

`\GLSaccessfmttext`

```
\GLSaccessfmttext{<insert>}{<cs>}{<label>}
```

```
\newcommand*{\GLSaccessfmttext}[3]{%  
  \GLSfmtfield{#1}{#2}{#3}{text}%  
}
```

`\glsaccessplural` Display the plural value (no link and no check for existence).

```
\newcommand*{\glsaccessplural}[1]{\glsentryplural{#1}}
```

`\glsaccessfmtplural`

```
\glsaccessfmtplural{<insert>}{<cs>}{<label>}
```

```
\newcommand*{\glsaccessfmtplural}[3]{%  
  \glsfmtfield{#1}{#2}{#3}{plural}%  
}
```

`\Glsaccessplural` Display the plural value (no link and no check for existence) with the first letter converted to upper case.

```
\newcommand*\Glsaccessplural}[1]{\Glsentryplural{#1}}
```

```
\Glsaccessfmtplural{<insert>}{<cs>}{<label>}
```

`\Glsaccessfmtplural`

```
\newcommand*\Glsaccessfmtplural}[3]{%
  \Glsfmtfield{#1}{#2}{#3}{plural}%
}
```

`\GLSaccessplural` Display the plural value (no link and no check for existence). converted to upper case.

```
\newcommand*\GLSaccessplural}[1]{%
  \protect\glsuppercase{\glsentryplural{#1}}}
```

```
\GLSaccessfmtplural{<insert>}{<cs>}{<label>}
```

`\GLSaccessfmtplural`

```
\newcommand*\GLSaccessfmtplural}[3]{%
  \GLSfmtfield{#1}{#2}{#3}{plural}%
}
```

`\glsaccessfirst` Display the first value (no link and no check for existence).

```
\newcommand*\glsaccessfirst}[1]{\glsentryfirst{#1}}
```

```
\glsaccessfmtfirst{<insert>}{<cs>}{<label>}
```

`\glsaccessfmtfirst`

```
\newcommand*\glsaccessfmtfirst}[3]{%
  \glsfmtfield{#1}{#2}{#3}{first}%
}
```

`\Glsaccessfirst` Display the first value (no link and no check for existence) with the first letter converted to upper case.

```
\newcommand*\Glsaccessfirst}[1]{\Glsentryfirst{#1}}
```

```
\Glsaccessfmtfirst{<insert>}{<cs>}{<label>}
```

`\Glsaccessfmtfirst`

```
\newcommand*\Glsaccessfmtfirst}[3]{%
  \Glsfmtfield{#1}{#2}{#3}{first}%
}
```

`\GLSaccessfirst` Display the first value (no link and no check for existence). converted to upper case.

```
\newcommand*{\GLSaccessfirst}[1]{%
\protect\glssupercase{\glstentryfirst{#1}}}
```

```
\GLSaccessfmtfirst{<insert>}{<cs>}{<label>}
```

`\GLSaccessfmtfirst`

```
\newcommand*{\GLSaccessfmtfirst}[3]{%
\GLSfmtfield{#1}{#2}{#3}{first}%
}
```

`\glsaccessfirstplural` Display the firstplural value (no link and no check for existence).

```
\newcommand*{\glsaccessfirstplural}[1]{\glstentryfirstplural{#1}}
```

```
\glsaccessfmtfirstplural{<insert>}{<cs>}{<label>}
```

`\glsaccessfmtfirstplural`

```
\newcommand*{\glsaccessfmtfirstplural}[3]{%
\glsfmtfield{#1}{#2}{#3}{firstpl}%
}
```

`\Glsaccessfirstplural` Display the firstplural value (no link and no check for existence) with the first letter converted to upper case.

```
\newcommand*{\Glsaccessfirstplural}[1]{\Glstentryfirstplural{#1}}
```

```
\Glsaccessfmtfirstplural{<insert>}{<cs>}{<label>}
```

`\Glsaccessfmtfirstplural`

```
\newcommand*{\Glsaccessfmtfirstplural}[3]{%
\Glsfmtfield{#1}{#2}{#3}{firstpl}%
}
```

`\GLSaccessfirstplural` Display the firstplural value (no link and no check for existence). converted to upper case.

```
\newcommand*{\GLSaccessfirstplural}[1]{%
\protect\glssupercase{\glstentryfirstplural{#1}}}
```

```
\GLSaccessfmtfirstplural{<insert>}{<cs>}{<label>}
```

`\GLSaccessfmtfirstplural`

```
\newcommand*{\GLSaccessfmtfirstplural}[3]{%
\GLSfmtfield{#1}{#2}{#3}{firstpl}%
}
```

`\glsaccesssymbol` Display the symbol value (no link and no check for existence).

```
\newcommand*{\glsaccesssymbol}[1]{\glsentrysymbol{#1}}
```

`\glsaccessfmtsymb`

```
\glsaccessfmtsymb{\insert}{\cs}{\label}
```

```
\newcommand*{\glsaccessfmtsymb}[3]{%  
  \glsfmtfield{#1}{#2}{#3}{symbol}%  
}
```

`\Glsaccesssymbol` Display the symbol value (no link and no check for existence) with the first letter converted to upper case.

```
\newcommand*{\Glsaccesssymbol}[1]{\Glsentrysymbol{#1}}
```

`\Glsaccessfmtsymb`

```
\Glsaccessfmtsymb{\insert}{\cs}{\label}
```

```
\newcommand*{\Glsaccessfmtsymb}[3]{%  
  \Glsfmtfield{#1}{#2}{#3}{symbol}%  
}
```

`\GLSaccesssymbol` Display the symbol value (no link and no check for existence). converted to upper case.

```
\newcommand*{\GLSaccesssymbol}[1]{%  
  \protect\glsuppercase{\glsentrysymbol{#1}}}
```

`\GLSaccessfmtsymb`

```
\GLSaccessfmtsymb{\insert}{\cs}{\label}
```

```
\newcommand*{\GLSaccessfmtsymb}[3]{%  
  \GLSfmtfield{#1}{#2}{#3}{symbol}%  
}
```

`\glsaccesssymbolplural` Display the symbolplural value (no link and no check for existence).

```
\newcommand*{\glsaccesssymbolplural}[1]{\glsentrysymbolplural{#1}}
```

`\glsaccessfmtsymbolplural`

```
\glsaccessfmtsymbolplural{\insert}{\cs}{\label}
```

```
\newcommand*{\glsaccessfmtsymbolplural}[3]{%  
  \glsfmtfield{#1}{#2}{#3}{symbolplural}%  
}
```


`\Glsaccesssymbolplural` Display the symbolplural value (no link and no check for existence) with the first letter converted to upper case.

```
\newcommand*\Glsaccesssymbolplural[1]{\Glsentrysymbolplural{#1}}
```

```
\Glsaccessfmtsymbolplural{<insert>}{<cs>}{<label>}
```

`\Glsaccessfmtsymbolplural`

```
\newcommand*\Glsaccessfmtsymbolplural[3]{%
  \Glsfmtfield{#1}{#2}{#3}{symbolplural}%
}
```

`\GLSaccesssymbolplural` Display the symbolplural value (no link and no check for existence). converted to upper case.

```
\newcommand*\GLSaccesssymbolplural[1]{%
  \protect\glsuppercase{\glsentrysymbolplural{#1}}}
```

```
\GLSaccessfmtsymbolplural{<insert>}{<cs>}{<label>}
```

`\GLSaccessfmtsymbolplural`

```
\newcommand*\GLSaccessfmtsymbolplural[3]{%
  \GLSfmtfield{#1}{#2}{#3}{symbolplural}%
}
```

`\glsaccessdesc` Display the desc value (no link and no check for existence).

```
\newcommand*\glsaccessdesc[1]{\glsentrydesc{#1}}
```

```
\glsaccessfmtdesc{<insert>}{<cs>}{<label>}
```

`\glsaccessfmtdesc`

```
\newcommand*\glsaccessfmtdesc[3]{%
  \glsfmtfield{#1}{#2}{#3}{desc}%
}
```

`\Glsaccessdesc` Display the desc value (no link and no check for existence) with the first letter converted to upper case.

```
\newcommand*\Glsaccessdesc[1]{\Glsentrydesc{#1}}
```

```
\Glsaccessfmtdesc{<insert>}{<cs>}{<label>}
```

`\Glsaccessfmtdesc`

```
\newcommand*\Glsaccessfmtdesc[3]{%
  \Glsfmtfield{#1}{#2}{#3}{desc}%
}
```

`\GLSaccessdesc` Display the desc value (no link and no check for existence). converted to upper case.

```
\newcommand*{\GLSaccessdesc}[1]{%
\protect\glsuppercase{\glsentrydesc{#1}}}
```

`\GLSaccessfmtdesc`

```
\GLSaccessfmtdesc{<insert>}{<cs>}{<label>}
```

```
\newcommand*{\GLSaccessfmtdesc}[3]{%
\GLSfmtfield{#1}{#2}{#3}{desc}%
}
```

`\glsaccessdescplural` Display the descplural value (no link and no check for existence).

```
\newcommand*{\glsaccessdescplural}[1]{\glsentrydescplural{#1}}
```

`\glsaccessfmtdescplural`

```
\glsaccessfmtdescplural{<insert>}{<cs>}{<label>}
```

```
\newcommand*{\glsaccessfmtdescplural}[3]{%
\glsfmtfield{#1}{#2}{#3}{descplural}%
}
```

`\Glsaccessdescplural` Display the descplural value (no link and no check for existence) with the first letter converted to upper case.

```
\newcommand*{\Glsaccessdescplural}[1]{\Glsentrydescplural{#1}}
```

`\Glsaccessfmtdescplural`

```
\Glsaccessfmtdescplural{<insert>}{<cs>}{<label>}
```

```
\newcommand*{\Glsaccessfmtdescplural}[3]{%
\Glsfmtfield{#1}{#2}{#3}{descplural}%
}
```

`\GLSaccessdescplural` Display the descplural value (no link and no check for existence). converted to upper case.

```
\newcommand*{\GLSaccessdescplural}[1]{%
\protect\glsuppercase{\glsentrydescplural{#1}}}
```

`\GLSaccessfmtdescplural`

```
\GLSaccessfmtdescplural{<insert>}{<cs>}{<label>}
```

```
\newcommand*{\GLSaccessfmtdescplural}[3]{%
\GLSfmtfield{#1}{#2}{#3}{descplural}%
}
```

`\glsaccesssshort` Display the short form (no link and no check for existence).

```
\newcommand*{\glsaccesssshort}[1]{\glsentryshort{#1}}
```

`\glsaccessfmtshort`

```
\glsaccessfmtshort{<insert>}{<cs>}{<label>}
```

```
\newcommand*{\glsaccessfmtshort}[3]{%  
  \glsfmtfield{#1}{#2}{#3}{short}%  
}
```

`\Glsaccesssshort` Display the short form with first letter converted to uppercase (no link and no check for existence).

```
\newcommand*{\Glsaccesssshort}[1]{\Glsentryshort{#1}}
```

`\Glsaccessfmtshort`

```
\Glsaccessfmtshort{<insert>}{<cs>}{<label>}
```

```
\newcommand*{\Glsaccessfmtshort}[3]{%  
  \Glsfmtfield{#1}{#2}{#3}{short}%  
}
```

`\GLSaccesssshort` Display the short value (no link and no check for existence). converted to upper case.

```
\newcommand*{\GLSaccesssshort}[1]{%  
  \protect\glsuppercase{\glsentryshort{#1}}}
```

`\GLSaccessfmtshort`

```
\GLSaccessfmtshort{<insert>}{<cs>}{<label>}
```

```
\newcommand*{\GLSaccessfmtshort}[3]{%  
  \GLSfmtfield{#1}{#2}{#3}{short}%  
}
```

`\glsaccesssshortpl` Display the short plural form (no link and no check for existence).

```
\newcommand*{\glsaccesssshortpl}[1]{\glsentryshortpl{#1}}
```

`\glsaccessfmtshortpl`

```
\glsaccessfmtshortpl{<insert>}{<cs>}{<label>}
```

```
\newcommand*{\glsaccessfmtshortpl}[3]{%  
  \glsfmtfield{#1}{#2}{#3}{shortpl}%  
}
```

`\Glsaccessshortpl` Display the short plural form with first letter converted to uppercase (no link and no check for existence).

```
\newcommand*\Glsaccessshortpl[1]{\Glsentryshortpl{#1}}
```

`\Glsaccessfmtshortpl`

```
\Glsaccessfmtshortpl{<insert>}{<cs>}{<label>}
```

```
\newcommand*\Glsaccessfmtshortpl[3]{%
  \Glsfmtfield{#1}{#2}{#3}{shortpl}%
}
```

`\GLSaccessshortpl` Display the shortplural value (no link and no check for existence). converted to upper case.

```
\newcommand*\GLSaccessshortpl[1]{%
  \protect\glsuppercase{\Glsentryshortpl{#1}}
```

`\GLSaccessfmtshortpl`

```
\GLSaccessfmtshortpl{<insert>}{<cs>}{<label>}
```

```
\newcommand*\GLSaccessfmtshortpl[3]{%
  \GLSfmtfield{#1}{#2}{#3}{shortpl}%
}
```

`\glsaccesslong` Display the long form (no link and no check for existence).

```
\newcommand*\glsaccesslong[1]{\Glsentrylong{#1}}
```

`\glsaccessfmtlong`

```
\glsaccessfmtlong{<insert>}{<cs>}{<label>}
```

```
\newcommand*\glsaccessfmtlong[3]{%
  \glsfmtfield{#1}{#2}{#3}{long}%
}
```

`\Glsaccesslong` Display the long form (no link and no check for existence).

```
\newcommand*\Glsaccesslong[1]{\Glsentrylong{#1}}
```

`\Glsaccessfmtlong`

```
\Glsaccessfmtlong{<insert>}{<cs>}{<label>}
```

```
\newcommand*\Glsaccessfmtlong[3]{%
  \Glsfmtfield{#1}{#2}{#3}{long}%
}
```

`\GLSaccesslong` Display the long value (no link and no check for existence). converted to upper case.

```
\newcommand*{\GLSaccesslong}[1]{%
\protect\glsuppercase{\glsentrylong{#1}}}
```

`\GLSaccessfmtlong`

```
\GLSaccessfmtlong{<insert>}{<cs>}{<label>}
```

```
\newcommand*{\GLSaccessfmtlong}[3]{%
\GLSfmtfield{#1}{#2}{#3}{long}%
}
```

`\glsaccesslongpl` Display the long plural form (no link and no check for existence).

```
\newcommand*{\glsaccesslongpl}[1]{\glsentrylongpl{#1}}
```

`\glsaccessfmtlongpl`

```
\glsaccessfmtlongpl{<insert>}{<cs>}{<label>}
```

```
\newcommand*{\glsaccessfmtlongpl}[3]{%
\glsfmtfield{#1}{#2}{#3}{longpl}%
}
```

`\Glsaccesslongpl` Display the long plural form (no link and no check for existence).

```
\newcommand*{\Glsaccesslongpl}[1]{\Glsentrylongpl{#1}}
```

`\Glsaccessfmtlongpl`

```
\Glsaccessfmtlongpl{<insert>}{<cs>}{<label>}
```

```
\newcommand*{\Glsaccessfmtlongpl}[3]{%
\Glsfmtfield{#1}{#2}{#3}{longpl}%
}
```

`\GLSaccesslongpl` Display the longplural value (no link and no check for existence). converted to upper case.

```
\newcommand*{\GLSaccesslongpl}[1]{%
\protect\glsuppercase{\glsentrylongpl{#1}}}
```

`\GLSaccessfmtlongpl`

```
\GLSaccessfmtlongpl{<insert>}{<cs>}{<label>}
```

```
\newcommand*{\GLSaccessfmtlongpl}[3]{%
\GLSfmtfield{#1}{#2}{#3}{longpl}%
}
```

USER1

`\glsaccessuseri` Display the user1 value (no link and no check for existence).

`\newcommand*\glsaccessuseri}[1]{\glsentryuseri{#1}}`

`\glsaccessfmtuseri{<insert>}{<cs>}{<label>}`

`\glsaccessfmtuseri`

`\newcommand*\glsaccessfmtuseri}[3]{%
 \glsfmtfield{#1}{#2}{#3}{useri}%
}`

`\Glsaccessuseri` Display the user1 value (no link and no check for existence) with the first letter converted to upper case.

`\newcommand*\Glsaccessuseri}[1]{\Glsentryuseri{#1}}`

`\Glsaccessfmtuseri{<insert>}{<cs>}{<label>}`

`\Glsaccessfmtuseri`

`\newcommand*\Glsaccessfmtuseri}[3]{%
 \Glsfmtfield{#1}{#2}{#3}{useri}%
}`

`\GLSaccessuseri` Display the user1 value (no link and no check for existence). converted to upper case.

`\newcommand*\GLSaccessuseri}[1]{%
 \protect\glsuppercase{\glsentryuseri{#1}}}`

`\GLSaccessfmtuseri{<insert>}{<cs>}{<label>}`

`\GLSaccessfmtuseri`

`\newcommand*\GLSaccessfmtuseri}[3]{%
 \GLSfmtfield{#1}{#2}{#3}{useri}%
}`

USER2

`\glsaccessuserii` Display the user2 value (no link and no check for existence).

`\newcommand*\glsaccessuserii}[1]{\glsentryuserii{#1}}`

`\glsaccessfmtuserii{<insert>}{<cs>}{<label>}`

`\glsaccessfmtuserii`

```
\newcommand*{\glsaccessfmtuserii}[3]{%
  \glsfmtfield{#1}{#2}{#3}{userii}%
}
```

\Glsaccessuserii Display the user2 value (no link and no check for existence) with the first letter converted to upper case.

```
\newcommand*{\Glsaccessuserii}[1]{\Glsentryuserii{#1}}
```

```
\Glsaccessfmtuserii{<insert>}{<cs>}{<label>}
```

\Glsaccessfmtuserii

```
\newcommand*{\Glsaccessfmtuserii}[3]{%
  \Glsfmtfield{#1}{#2}{#3}{userii}%
}
```

\GLSaccessuserii Display the user2 value (no link and no check for existence). converted to upper case.

```
\newcommand*{\GLSaccessuserii}[1]{%
  \protect\glsuppercase{\glsentryuserii{#1}}}
```

```
\GLSaccessfmtuserii{<insert>}{<cs>}{<label>}
```

\GLSaccessfmtuserii

```
\newcommand*{\GLSaccessfmtuserii}[3]{%
  \GLSfmtfield{#1}{#2}{#3}{userii}%
}
```

USER3

\glsaccessuseriii Display the user3 value (no link and no check for existence).

```
\newcommand*{\glsaccessuseriii}[1]{\glsentryuseriii{#1}}
```

```
\glsaccessfmtuseriii{<insert>}{<cs>}{<label>}
```

\glsaccessfmtuseriii

```
\newcommand*{\glsaccessfmtuseriii}[3]{%
  \glsfmtfield{#1}{#2}{#3}{useriii}%
}
```

\Glsaccessuseriii Display the user3 value (no link and no check for existence) with the first letter converted to upper case.

```
\newcommand*{\Glsaccessuseriii}[1]{\Glsentryuseriii{#1}}
```

\Glsaccessfmtuseriii

```
\Glsaccessfmtuseriii{\insert}{\cs}{\label}
```

```
\newcommand*\Glsaccessfmtuseriii[3]{%  
  \Glsfmtfield{#1}{#2}{#3}{useriii}%  
}
```

\GLSaccessuseriii Display the user3 value (no link and no check for existence). converted to upper case.

```
\newcommand*\GLSaccessuseriii[1]{%  
  \protect\glsuppercase{\glsentryuseriii{#1}}}
```

\GLSaccessfmtuseriii

```
\GLSaccessfmtuseriii{\insert}{\cs}{\label}
```

```
\newcommand*\GLSaccessfmtuseriii[3]{%  
  \GLSfmtfield{#1}{#2}{#3}{useriii}%  
}
```

USER4

\glsaccessuseriv Display the user4 value (no link and no check for existence).

```
\newcommand*\glsaccessuseriv[1]{\glsentryuseriv{#1}}
```

\glsaccessfmtuseriv

```
\glsaccessfmtuseriv{\insert}{\cs}{\label}
```

```
\newcommand*\glsaccessfmtuseriv[3]{%  
  \glsfmtfield{#1}{#2}{#3}{useriv}%  
}
```

\GLSaccessuseriv Display the user4 value (no link and no check for existence) with the first letter converted to upper case.

```
\newcommand*\GLSaccessuseriv[1]{\GLSentryuseriv{#1}}
```

\Glsaccessfmtuseriv

```
\Glsaccessfmtuseriv{\insert}{\cs}{\label}
```

```
\newcommand*\Glsaccessfmtuseriv[3]{%  
  \Glsfmtfield{#1}{#2}{#3}{useriv}%  
}
```


`\GLSaccessuseriv` Display the `user4` value (no link and no check for existence). converted to upper case.

```
\newcommand*{\GLSaccessuseriv}[1]{%
\protect\glsuppercase{\glsentryuseriv{#1}}}
```

`\GLSaccessfmtuseriv` `{\insert}{\langle cs \rangle}{\langle label \rangle}`

`\GLSaccessfmtuseriv`

```
\newcommand*{\GLSaccessfmtuseriv}[3]{%
\GLSfmtfield{#1}{#2}{#3}{useriv}%
}
```

USER5

`\glsaccessuserv` Display the `user5` value (no link and no check for existence).

```
\newcommand*{\glsaccessuserv}[1]{\glsentryuserv{#1}}
```

`\glsaccessfmtuserv` `{\insert}{\langle cs \rangle}{\langle label \rangle}`

`\glsaccessfmtuserv`

```
\newcommand*{\glsaccessfmtuserv}[3]{%
\glsfmtfield{#1}{#2}{#3}{userv}%
}
```

`\Glsaccessuserv` Display the `user5` value (no link and no check for existence) with the first letter converted to upper case.

```
\newcommand*{\Glsaccessuserv}[1]{\Glsentryuserv{#1}}
```

`\Glsaccessfmtuserv` `{\insert}{\langle cs \rangle}{\langle label \rangle}`

`\Glsaccessfmtuserv`

```
\newcommand*{\Glsaccessfmtuserv}[3]{%
\Glsfmtfield{#1}{#2}{#3}{userv}%
}
```

`\GLSaccessuserv` Display the `user5` value (no link and no check for existence). converted to upper case.

```
\newcommand*{\GLSaccessuserv}[1]{%
\protect\glsuppercase{\glsentryuserv{#1}}}
```

`\GLSaccessfmtuserv` `{\insert}{\langle cs \rangle}{\langle label \rangle}`

`\GLSaccessfmtuserv`

```
\newcommand*{\GLSaccessfmtuservi}[3]{%
  \GLSfmtfield{#1}{#2}{#3}{uservi}%
}
```

USER6

\glsaccessuservi Display the user6 value (no link and no check for existence).

```
\newcommand*{\glsaccessuservi}[1]{\glsentryuservi{#1}}
```

```
\glsaccessfmtuservi{\insert}{\cs}{\label}
```

\glsaccessfmtuservi

```
\newcommand*{\glsaccessfmtuservi}[3]{%
  \glsfmtfield{#1}{#2}{#3}{uservi}%
}
```

\Glsaccessuservi Display the user6 value (no link and no check for existence) with the first letter converted to upper case.

```
\newcommand*{\Glsaccessuservi}[1]{\Glsentryuservi{#1}}
```

```
\Glsaccessfmtuservi{\insert}{\cs}{\label}
```

\Glsaccessfmtuservi

```
\newcommand*{\Glsaccessfmtuservi}[3]{%
  \Glsfmtfield{#1}{#2}{#3}{uservi}%
}
```

\GLSaccessuservi Display the user6 value (no link and no check for existence). converted to upper case.

```
\newcommand*{\GLSaccessuservi}[1]{%
  \protect\glsuppercase{\glsentryuservi{#1}}}
```

```
\GLSaccessfmtuservi{\insert}{\cs}{\label}
```

\GLSaccessfmtuservi

```
\newcommand*{\GLSaccessfmtuservi}[3]{%
  \GLSfmtfield{#1}{#2}{#3}{uservi}%
}
```

\@gls@initaccesskeys This does nothing if there's no accessibility support.

```
\newcommand*{\@gls@initaccesskeys}{}
```

```

\@gls@setup@default@access This does nothing if there's no accessibility support.
    \newcommand{\@gls@setup@default@access}{}

\extrAccSuppAbbrSetNoLongAttrs This does nothing if there's no accessibility support.
    \newcommand*{\glstrAccSuppAbbrSetNoLongAttrs}[1]{}

\extrAccSuppAbbrSetFirstLongAttrs This does nothing if there's no accessibility support.
    \newcommand*{\glstrAccSuppAbbrSetFirstLongAttrs}[1]{}

\extrAccSuppAbbrSetTextShortAttrs This does nothing if there's no accessibility support.
    \newcommand*{\glstrAccSuppAbbrSetTextShortAttrs}[1]{}

\extrAccSuppAbbrSetNameShortAttrs This does nothing if there's no accessibility support.
    \newcommand*{\glstrAccSuppAbbrSetNameShortAttrs}[1]{}

\extrAccSuppAbbrSetNameLongAttrs This does nothing if there's no accessibility support.
    \newcommand*{\glstrAccSuppAbbrSetNameLongAttrs}[1]{}

End of else part
}

```

Identify sentence-case mappings:

```

\glsmfuaddmap{\glsaccessname}{\Glsaccessname}
\glsmfuaddmap{\glsaccessfmtname}{\Glsaccessfmtname}
\glsmfublocker{\GLSaccessname}
\glsmfublocker{\GLSaccessfmtname}
\glsmfuaddmap{\glsaccesstext}{\Glsaccesstext}
\glsmfuaddmap{\glsaccessfmttext}{\Glsaccessfmttext}
\glsmfublocker{\GLSaccesstext}
\glsmfublocker{\GLSaccessfmttext}
\glsmfuaddmap{\glsaccessplural}{\Glsaccessplural}
\glsmfuaddmap{\glsaccessfmtplural}{\Glsaccessfmtplural}
\glsmfublocker{\GLSaccessplural}
\glsmfublocker{\GLSaccessfmtplural}
\glsmfuaddmap{\glsaccessfirst}{\Glsaccessfirst}
\glsmfuaddmap{\glsaccessfmtfirst}{\Glsaccessfmtfirst}
\glsmfublocker{\GLSaccessfirst}
\glsmfublocker{\GLSaccessfmtfirst}
\glsmfuaddmap{\glsaccessfirstplural}{\Glsaccessfirstplural}
\glsmfuaddmap{\glsaccessfmtfirstplural}{\Glsaccessfmtfirstplural}
\glsmfublocker{\GLSaccessfirstplural}
\glsmfublocker{\GLSaccessfmtfirstplural}
\glsmfuaddmap{\glsaccesssymbol}{\Glsaccesssymbol}
\glsmfuaddmap{\glsaccessfmtsymbol}{\Glsaccessfmtsymbol}
\glsmfublocker{\GLSaccesssymbol}
\glsmfublocker{\GLSaccessfmtsymbol}
\glsmfuaddmap{\glsaccesssymbolplural}{\Glsaccesssymbolplural}
\glsmfuaddmap{\glsaccessfmtsymbolplural}{\Glsaccessfmtsymbolplural}
\glsmfublocker{\GLSaccesssymbolplural}

```

```

\glsmfublocker{\GLSaccessfmtsymbollplural}
\glsmfuaddmap{\glaccessdesc}{\Glsaccessdesc}
\glsmfuaddmap{\glaccessfmdesc}{\Glsaccessfmdesc}
\glsmfublocker{\GLSaccessdesc}
\glsmfublocker{\GLSaccessfmdesc}
\glsmfuaddmap{\glaccessdescplural}{\Glsaccessdescplural}
\glsmfuaddmap{\glaccessfmdescplural}{\Glsaccessfmdescplural}
\glsmfublocker{\GLSaccessdescplural}
\glsmfublocker{\GLSaccessfmdescplural}
\glsmfuaddmap{\glaccessshort}{\Glsaccessshort}
\glsmfuaddmap{\glaccessfmdshort}{\Glsaccessfmdshort}
\glsmfublocker{\GLSaccessshort}
\glsmfublocker{\GLSaccessfmdshort}
\glsmfuaddmap{\glaccessshortpl}{\Glsaccessshortpl}
\glsmfuaddmap{\glaccessfmdshortpl}{\Glsaccessfmdshortpl}
\glsmfublocker{\GLSaccessshortpl}
\glsmfublocker{\GLSaccessfmdshortpl}
\glsmfuaddmap{\glaccesslong}{\Glsaccesslong}
\glsmfuaddmap{\glaccessfmdlong}{\Glsaccessfmdlong}
\glsmfublocker{\GLSaccesslong}
\glsmfublocker{\GLSaccessfmdlong}
\glsmfuaddmap{\glaccesslongpl}{\Glsaccesslongpl}
\glsmfuaddmap{\glaccessfmdlongpl}{\Glsaccessfmdlongpl}
\glsmfublocker{\GLSaccesslongpl}
\glsmfublocker{\GLSaccessfmdlongpl}
\glsmfuaddmap{\glaccessuseri}{\Glsaccessuseri}
\glsmfuaddmap{\glaccessfmduseri}{\Glsaccessfmduseri}
\glsmfublocker{\GLSaccessuseri}
\glsmfublocker{\GLSaccessfmduseri}
\glsmfuaddmap{\glaccessuserii}{\Glsaccessuserii}
\glsmfuaddmap{\glaccessfmduserii}{\Glsaccessfmduserii}
\glsmfublocker{\GLSaccessuserii}
\glsmfublocker{\GLSaccessfmduserii}
\glsmfuaddmap{\glaccessuseriii}{\Glsaccessuseriii}
\glsmfuaddmap{\glaccessfmduseriii}{\Glsaccessfmduseriii}
\glsmfublocker{\GLSaccessuseriii}
\glsmfublocker{\GLSaccessfmduseriii}
\glsmfuaddmap{\glaccessuseriv}{\Glsaccessuseriv}
\glsmfuaddmap{\glaccessfmduseriv}{\Glsaccessfmduseriv}
\glsmfublocker{\GLSaccessuseriv}
\glsmfublocker{\GLSaccessfmduseriv}
\glsmfuaddmap{\glaccessuserv}{\Glsaccessuserv}
\glsmfuaddmap{\glaccessfmduserv}{\Glsaccessfmduserv}
\glsmfublocker{\GLSaccessuserv}
\glsmfublocker{\GLSaccessfmduserv}
\glsmfuaddmap{\glaccessuservi}{\Glsaccessuservi}
\glsmfuaddmap{\glaccessfmduservi}{\Glsaccessfmduservi}
\glsmfublocker{\GLSaccessuservi}
\glsmfublocker{\GLSaccessfmduservi}

```

1.6 Categories

`\glscategory` Add a new storage key that can be used to indicate a category. The default category is `general`.

```
\glsaddstoragekey{category}{general}{\glscategory}
```

`\glsifcategory` Convenient shortcut to determine if an entry has the given category.

```
\newcommand{\glsifcategory}[4]{%
  \ifglsfieldeq{#1}{category}{#2}{#3}{#4}%
}
```

Categories can have attributes.

```
\glssetcategoryattribute{<category>}{<attribute-label>}
{<value>}
```

`\glssetcategoryattribute`

Set (or override if already set) an attribute for the given category.

```
\newcommand*{\glssetcategoryattribute}[3]{%
  \csdef{@glsxtr@categoryattr@@#1@#2}{#3}%
}
```

```
\glssetcategoriesattribute{<category list>}
{<attribute-label>}{<value>}
```

`\glssetcategoriesattribute`

Similar to above, but globally apply to each category in the list.

```
\newcommand*{\glssetcategoriesattribute}[3]{%
  \@for\@gls@thiscatlabel:=#1\do{%
    \csgdef{@glsxtr@categoryattr@@\@gls@thiscatlabel @#2}{#3}%
  }%
}
```

```
\glssetcategoriesattributes{<category list>}
{<attribute-label list>}{<value>}
```

`\glssetcategoriesattributes`

Similar to above, but apply to each category and attribute in the list.

```
\newcommand*{\glssetcategoriesattributes}[3]{%
```

Group to avoid problems with nested `\@for`.

```
{%
  \@for\@gls@thisattrlabel:=#2\do{%
    \glssetcategoriesattribute{#1}{\@gls@thisattrlabel}{#3}%
  }%
}%
}
```

`\glsetcategoryattributes`

`\glsetcategoryattributes{<category>}{<attribute list>}{<value>}`

Similar to above, but globally apply to each attribute in the list to the given category.

```
\newcommand*{\glsetcategoryattributes}[3]{%
  \@for\@gls@thisattrlabel:=#2\do{%
    \csgdef{\glstr@categoryattr@#1\@gls@thisattrlabel}{#3}%
  }%
}
```

`\glgetcategoryattribute`

`\glgetcategoryattribute{<category>}{<attribute-label>}`

Get the value of the given attribute for the given category. Does nothing if the attribute isn't defined.

```
\newcommand*{\glgetcategoryattribute}[2]{%
  \csuse{\glstr@categoryattr@#1@#2}%
}
```

`\glunsetcategoryattribute`

`\glunsetcategoryattribute{<category>}{<attribute-label>}`

Unsets the given attribute for the given category.

```
\newcommand*{\glunsetcategoryattribute}[2]{%
  \csundef{\glstr@categoryattr@#1@#2}%
}
```

`\glshascategoryattribute`

`\glshascategoryattribute{<category>}{<attribute-label>}{<true>}{<false>}`

Tests if the category has the given attribute set.

```
\newcommand*{\glshascategoryattribute}[4]{%
  \ifcsvoid{\glstr@categoryattr@#1@#2}{#4}{#3}%
}
```

`\glsetattribute`

`\glsetattribute{<entry label>}{<attribute-label>}{<value>}`

Short cut where the category label is obtained from the entry information.

```
\newcommand*{\glsetattribute}[3]{%
  \glsetcategoryattribute{\glscategory{#1}}{#2}{#3}%
}
```

`\glsggetattribute`

```
\glsggetattribute{<entry label>}{<attribute-label>}
```

Short cut where the category label is obtained from the entry information.

```
\newcommand*{\glsggetattribute}[2]{%
  \glsggetcategoryattribute{\glscategory{#1}}{#2}%
}
```

`\glshasattribute`

```
\glshasattribute{<entry
label>}{<attribute-label>}{<true>}{<false>}
```

Short cut to test if the given attribute has been set where the category label is obtained from the entry information.

```
\newcommand*{\glshasattribute}[4]{%
  \ifglentryexists{#1}%
  {\glshascategoryattribute{\glscategory{#1}}{#2}{#3}{#4}}%
  {#4}%
}
```

`\glusifcategoryattribute`

```
\glusifcategoryattribute{<category>}{<attribute-label>}{<value>}{<true
part>}{<false part>}
```

True if category has the attribute with the given value.

```
\newcommand{\glusifcategoryattribute}[5]{%
  \ifcsundef{@glsxtr@categoryattr@#1@#2}%
  {#5}%
  {\ifcsstring{@glsxtr@categoryattr@#1@#2}{#3}{#4}{#5}}%
}
```

`\glusifattribute`

```
\glusifattribute{<entry label>}{<attribute-label>}{<value>}{<true
part>}{<false part>}
```

Short cut to determine if the given entry has a category with the given attribute set.

```
\newcommand{\glusifattribute}[5]{%
  \ifglentryexists{#1}%
  {\glusifcategoryattribute{\glscategory{#1}}{#2}{#3}{#4}{#5}}%
  {#5}%
}
```

Provide expandable test to determine if attribute is set to true.

`\@glxtr@truevalue`

```
\newcommand*{\@glxtr@truevalue}{true}
```

```
\glsifcategoryattributetrue{<category-label>}{<attribute>}
{<true>}{<false>}
```

`\glsifcategoryattributetrue`

Does *<false>* if the entry hasn't been defined.

```
\newcommand*{\glsifcategoryattributetrue}[4]{%
\ifcsequal{\@glxtr@categoryattr@#1@#2}%
{\@glxtr@truevalue}%
{#3}{#4}%
}
```

```
\glsifattributetrue{<label>}{<attribute>}{<true>}{<false>}
```

`\glsifattributetrue`

Does *<false>* if the entry hasn't been defined.

```
\newcommand*{\glsifattributetrue}[4]{%
\ifcsundef{glo@glsetoklabel{#1}@category}%
{#4}
{\ifcsequal
{\@glxtr@categoryattr@%csname glo@glsetoklabel{#1}@category\endcsname @#2}%
{\@glxtr@truevalue}%
{#3}{#4}%
}%
}
```

```
\glsifcategoryattributehasitem{<category>}
{<attribute-label>}{<item>}{<true
part>}{<false part>}
```

`\glsifcategoryattributehasitem`

True if category has the attribute (whose value is a comma-separated list) contains the given item. The *<item>* is expanded.

```
\newrobustcmd{\glsifcategoryattributehasitem}[5]{%
\ifcsundef{\@glxtr@categoryattr@#1@#2}%
{#5}%
{%
\protected@edef\gls@tmp{%
\noexpand\DTLifinlist{#3}{\csuse{\@glxtr@categoryattr@#1@#2}}}%
\gls@tmp{#4}{#5}%
}%
}
```

Set attributes for the default general category:

```
\glssetcategoryattribute{general}{regular}{true}
```


Acronyms are regular by default, since they're typically just treated like normal words.

```
\glsssetcategoryattribute{acronym}{regular}{true}
```

`\glsssetregularcategory` Convenient shortcut to add the regular attribute.

```
\newcommand*{\glsssetregularcategory}[1]{%
  \glsssetcategoryattribute{#1}{regular}{true}%
}
```

`\glsifregularcategory`

```
\glsifregularcategory{<category>}{<true part>}{<false part>}
```

Short cut to determine if a category has the regular attribute explicitly set to true.

```
\newcommand{\glsifregularcategory}[3]{%
  \glsifcategoryattribute{#1}{regular}{true}{#2}{#3}%
}
```

```
\glsifnotregularcategory{<category>}{<true part>}{<false part>}
```

`\glsifnotregularcategory`

Short cut to determine if a category has the regular attribute explicitly set to false.

```
\newcommand{\glsifnotregularcategory}[3]{%
  \glsifcategoryattribute{#1}{regular}{false}{#2}{#3}%
}
```

```
\glsifregular{<entry label>}{<true part>}{<false part>}
```

`\glsifregular`

Short cut to determine if an entry has a regular attribute set to true.

```
\newcommand{\glsifregular}[3]{%
  \glsifregularcategory{\glscategory{#1}}{#2}{#3}%
}
```

```
\glsifnotregular{<entry label>}{<true part>}{<false part>}
```

`\glsifnotregular`

Short cut to determine if an entry has a regular attribute set to false.

```
\newcommand{\glsifnotregular}[3]{%
  \glsifnotregularcategory{\glscategory{#1}}{#2}{#3}%
}
```

```
\glsforeachcategory[<glossary
labels>]{<category-label>}{<glossary-cs>}{<label-cs>}
{<body>}
```

`\glsforeachcategory`

Iterates through all entries in all the glossaries (or just those listed in *<glossary labels>*) and does *<body>* if the category matches *<category-label>*. The control sequences *<glossary-cs>* and *<label-cs>* may be used in *<body>* to access the glossary label and entry label for the current iteration.

```
\newcommand{\glsforeachcategory}[5][\@glo@types]{%
\forallglossaries[#1]{#3}%
{%
\glstrifemptyglossary{#3}{}%
{%
\forallsentries[#3]{#4}%
{%
\glsifcategory{#4}{#2}{#5}{}%
}%
}%
}%
}
```

```
\glsforeachwithattribute[<glossary
labels>]{<attribute-label>}{<attribute-value>}
{<glossary-cs>}{<label-cs>}{<body>}
```

`\glsforeachwithattribute`

Iterates through all entries in all the glossaries (or just those listed in *<glossary labels>*) and does *<body>* if the category attribute *<attribute-label>* matches *<attribute-value>*. The control sequences *<glossary-cs>* and *<label-cs>* may be used in *<body>* to access the glossary label and entry label for the current iteration.

```
\newcommand{\glsforeachwithattribute}[6][\@glo@types]{%
\forallglossaries[#1]{#4}%
{%
\forallsentries[#4]{#5}%
{%
\glsifattribute{#5}{#2}{#3}{#6}{}%
}%
}%
}
```

If `\newterm` has been defined, redefine it so that it automatically sets the category label to index and add `\glstrpostdescription`.

```
\ifdef\newterm
{%
```

`\newterm`

```
\renewcommand*{\newterm}[2] [] {%
  \newglossaryentry{#2}%
    {type=index,category=index,name={#2},%
      description={\glstrpostdescription\nopostdesc},#1}%
}
```

Indexed terms are regular by default.

```
\glsssetcategoryattribute{index}{regular}{true}
```

`\glstrpostdescindex`

```
\newcommand*{\glstrpostdescindex}{}

}
{}
```

If the `symbols` package option was used, define a similar command for symbols, but set the default sort to the label rather than the name as the symbols will typically contain commands that will confuse `makeindex` and `xindy`.

```
\ifdef\printsymbols
{%
```

`\glstrnewsymbol` Unlike `\newterm`, this has a separate argument for the label (since the symbol will likely contain commands).

```
\newcommand*{\glstrnewsymbol}[3] [] {%
  \newglossaryentry{#2}{name={#3},sort={#2},type=symbols,category=symbol,#1}%
}
```

Symbols are regular by default.

```
\glsssetcategoryattribute{symbol}{regular}{true}
```

`\glstrpostdescsymbol`

```
\newcommand*{\glstrpostdescsymbol}{}

}
{}
```

Similar for the `numbers` option.

```
\ifdef\printnumbers
{%
```

`\glstrnewnumber`

```
\ifdef\printnumbers
  \newcommand*{\glstrnewnumber}[3] [] {%
    \newglossaryentry{#2}{name={#3},sort={#2},type=numbers,category=number,#1}%
  }
}
```

Numbers are regular by default.

```
\glsssetcategoryattribute{number}{regular}{true}
```

`\glsxtrpostdescnumber`

```
\newcommand*{\glsxtrpostdescnumber}{}

}

{}
```

`\glsxtrsetcategory` Set the category for all listed labels. The first argument is the list of entry labels and the second argument is the category label.

```
\newcommand*{\glsxtrsetcategory}[2]{%
  \@for\@glsxtr@label:=#1\do
  {%
    \glsfieldxdef{\@glsxtr@label}{category}{#2}%
  }%
}
```

`\glsxtrsetcategoryforall` Set the category for all entries in the listed glossaries. The first argument is the list of glossary labels and the second argument is the category label.

```
\newcommand*{\glsxtrsetcategoryforall}[2]{%
  \forallglossaries[#1]{\@glsxtr@type}{%
    \forglsentries[\@glsxtr@type]{\@glsxtr@label}%
    {%
      \glsfieldxdef{\@glsxtr@label}{category}{#2}%
    }%
  }%
}
```

`\glsxtrfieldtitlecase{<label>}{<field>}`

`\glsxtrfieldtitlecase`

Apply title casing to the contents of the given field.

```
\newcommand*{\glsxtrfieldtitlecase}[2]{%
  \expandafter\glsxtrfieldtitlecasecs\expandafter
  {\csname glo@\glsdetoklabel{#1}@\#2\endcsname}%
}
```

`\glsxtrfieldtitlecasecs` The command used by `\glsxtrfieldtitlecase`. May be redefined to use a different command, for example, `\xcapitalisefmtwords`. Check for `\glscapitalisewords`, which was added to glossaries v4.48.

```
\ifdef\glscapitalisewords
{
  \newcommand*{\glsxtrfieldtitlecasecs}[1]{%
    \expandafter\glscapitalisewords\expandafter{#1}}
}
{
  \newcommand*{\glsxtrfieldtitlecasecs}[1]{\xcapitalisewords{#1}}
}
```

Provide a convenient way to modify glossary styles without having to define a new style just to convert the first letter of fields to upper case.

`\glossentrydesc` If the `glossdesc` attribute is “firstuc” convert first letter to upper case. If the attribute is “title” use title case.

```
\@ifpackageloaded{glossaries-accsupp}
{
  \renewcommand*{\glossentrydesc}[1]{%
    \glsdoifexistsorwarn{#1}%
    {%
      \glssetabbrvfmt{\glscategory{#1}}%
```

As from version 1.04, allow the `glossdescfont` attribute to determine the font applied.

```
\glsasattribute{#1}{glossdescfont}%
{%
  \protected@edef\@glsxtr@attrval{\glsgetattribute{#1}{glossdescfont}}%
  \ifcsdef{\@glsxtr@attrval}%
  {%
    \letcs{\@glsxtr@glossdescfont}{\@glsxtr@attrval}%
  }%
  {%
    \GlossariesExtraWarning{Unknown control sequence name
      ‘\@glsxtr@attrval’ supplied in glossdescfont attribute
      for entry ‘#1’. Ignoring}%
    \let\@glsxtr@glossdescfont\@firstofone
  }%
}%
{\let\@glsxtr@glossdescfont\@firstofone}%
\glsifattribute{#1}{glossdesc}{firstuc}%
{%
  \@glsxtr@glossdescfont{\Glsaccessdesc{#1}}%
}%
{%
  \glsifattribute{#1}{glossdesc}{title}%
  {%
    \@glsxtr@do@titlecaps@warn
    \glsdescriptionaccessdisplay
  }%
  \@glsxtr@glossdescfont{\glsxtrfieldtitlecase{#1}{desc}}%
}%
{#1}%
}%
{%
  \@glsxtr@glossdescfont{\Glsaccessdesc{#1}}%
}%
}%
}%
}
}
{
  \renewcommand*{\glossentrydesc}[1]{%
    \glsdoifexistsorwarn{#1}%
```

```

{%
\glsetabbrvfmt{\glscategory{#1}}%
\glshasattribute{#1}{glossdescfont}%
{%
\protected@edef\@glxtr@attrval{\glsetattribute{#1}{glossdescfont}}%
\ifcsdef{\@glxtr@attrval}%
{%
\letcs{\@glxtr@glossdescfont}{\@glxtr@attrval}%
}%
{%
\GlossariesExtraWarning{Unknown control sequence name
'\@glxtr@attrval' supplied in glossdescfont attribute
for entry '#1'. Ignoring}%
\let\@glxtr@glossdescfont\@firstofone
}%
}%
{\let\@glxtr@glossdescfont\@firstofone}%
\gl@ifattribute{#1}{glossdesc}{firstuc}%
{%
\@glxtr@glossdescfont{\Glsentrydesc{#1}}%
}%
{%
\gl@ifattribute{#1}{glossdesc}{title}%
{%
\@glxtr@do@titlecaps@warn
\@glxtr@glossdescfont{\glxtr@field@titlecase{#1}{desc}}%
}%
{%
\@glxtr@glossdescfont{\Glsentrydesc{#1}}%
}%
}%
}%
}
}

```

`\glossentryname` If the `glossname` attribute is “firstuc” convert first letter to upper case. If the attribute is “title” use title case.

```

\@ifpackageloaded{glossaries-accsupp}
{
\renewcommand*{\glossentryname}[1]{%
\@glsoifexistsorwarn{#1}%
{%
\glsetabbrvfmt{\glscategory{#1}}%

```

As from v1.54, do pre-name hook:

```
\glxtr@prenamehook{#1}%
```

As from version 1.04, allow the `glossnamefont` attribute to determine the font applied.

```
\glshasattribute{#1}{glossnamefont}%
```

```

{%
\protected@edef\@glstr@attrval{\glsetattribute{#1}{glossnamefont}}%
\ifcsdef{\@glstr@attrval}%
{%
\letcs{\@glstr@glossnamefont}{\@glstr@attrval}%
}%
{%
\GlossariesExtraWarning{Unknown control sequence name
'\@glstr@attrval' supplied in glossnamefont attribute
for entry '#1'. Reverting to default \string\glsnamefont}%
\let\@glstr@glossnamefont\glsnamefont
}%
}%
{\let\@glstr@glossnamefont\glsnamefont}%
\glsifattribute{#1}{glossname}{firstuc}%
{%
\glsnameaccessdisplay
{%
\@glstr@glossnamefont{\Glsentryname{#1}}%
}%
{#1}%
}%
{%
\glsifattribute{#1}{glossname}{title}%
{%
\@glstr@do@titlecaps@warn
\glsnameaccessdisplay
{%
\@glstr@glossnamefont{\glstrfieldtitlecase{#1}{name}}%
}%
{#1}%
}%
{%
\glsifattribute{#1}{glossname}{uc}%
{%
\glsnameaccessdisplay
{%

```

Hide the label from the upper-casing command.

```

\letcs{\glo@name}{glo@\glsdetoklabel{#1}@name}%
\@glstr@glossnamefont{\glssupercase{\glo@name}}%
}%
{#1}%
}%
{%
\letcs{\glo@name}{glo@\glsdetoklabel{#1}@name}%
\glsnameaccessdisplay
{%
\expandafter\@glstr@glossnamefont\expandafter{\glo@name}%
}%

```

```

        {#1}%
      }%
    }%
  }%

```

Do post-name hook:

```

    \glxstrpostnamehook{#1}%
  }%
}
{
  \renewcommand*{\glossentryname}[1]{%
    \@glsdoifexistsorwarn{#1}%
    {%
      \glsssetabbrvfmt{\glscategory{#1}}%

```

As from v1.54, do pre-name hook:

```

    \glxstrprernamehook{#1}%
    \glshasattribute{#1}{glossnamefont}%
    {%
      \protected@edef\@glxstr@attrval{\glsetattribute{#1}{glossnamefont}}%
      \ifcsdef{\@glxstr@attrval}%
      {%
        \letcs{\@glxstr@glossnamefont}{\@glxstr@attrval}%
      }%
      {%
        \GlossariesExtraWarning{Unknown control sequence name
          '\@glxstr@attrval' supplied in glossnamefont attribute
          for entry '#1'. Reverting to default \string\glsnamefont}%
        \let\@glxstr@glossnamefont\glsnamefont
      }%
    }%
    {\let\@glxstr@glossnamefont\glsnamefont}%
    \glsifattribute{#1}{glossname}{firstuc}%
    {%
      \@glxstr@glossnamefont{\Glsentryname{#1}}%
    }%
    {%
      \glsifattribute{#1}{glossname}{title}%
      {%
        \@glxstr@do@titlecaps@warn
        \@glxstr@glossnamefont{\glxstrfieldtitlecase{#1}{name}}%
      }%
      {%
        \glsifattribute{#1}{glossname}{uc}%
        {%

```

Hide the label from the upper-casing command.

```

    \letcs{\glo@name}{glo@\glsetoklabel{#1}@name}%
    \@glxstr@glossnamefont{\glssupercase{\glo@name}}%

```



```
}%
{%
```

This little trick is used by glossaries to allow the user to redefine `\glsnamefont` to use `\makefirstuc`. Support it even though they can now use the `firstuc` attribute.

```
\letcs{\glo@name}{glo@\glsdetoklabel{#1}@name}%
\expandafter\@glxtr@glossnamefont\expandafter{\glo@name}%
}%
}%
}%
```

Do post-name hook.

```
\glxtrpostnamehook{#1}%
}%
}
}
```

`\Glossentryname` Redefine to set the abbreviation format and accessibility support.

```
\@ifpackageloaded{glossaries-accsupp}
{
  \renewcommand*{\Glossentryname}[1]{%
    \@glsdoifexistsorwarn{#1}%
    {%
      \glsssetabbrvfmt{\glscategory{#1}}%
```

As from v1.54, do pre-name hook:

```
\glxtrprenamehook{#1}%
```

As from version 1.04, allow the `glossnamefont` attribute to determine the font applied.

```
\glshasattribute{#1}{glossnamefont}%
{%
  \protected@edef\@glxtr@attrval{\glsetattribute{#1}{glossnamefont}}%
  \ifcsdef{\@glxtr@attrval}%
  {%
    \letcs{\@glxtr@glossnamefont}{\@glxtr@attrval}%
  }%
  {%
    \GlossariesExtraWarning{Unknown control sequence name
      '\@glxtr@attrval' supplied in glossnamefont attribute
      for entry '#1'. Reverting to default \string\glsnamefont}%
    \let\@glxtr@glossnamefont\glsnamefont
  }%
}%
{\let\@glxtr@glossnamefont\glsnamefont}%
\glsnameaccessdisplay
{%
  \@glxtr@glossnamefont{\Glsentryname{#1}}%
}%
{#1}%
```

Do post-name hook:

```

\glstrpostnamehook{#1}%
}%
}
}
{
\renewcommand*{\Glossentryname}[1]{%
\@glsdoifexistsorwarn{#1}%
{%
\glsetabbrvfmt{\glscategory{#1}}%

```

As from v1.54, do pre-name hook:

```

\glstrprernamehook{#1}%
\glshasattribute{#1}{glossnamefont}%
{%

\protected@edef\@glstr@attrval{\glsetattribute{#1}{glossnamefont}}%
\ifcsdef{\@glstr@attrval}%
{%
\letcs{\@glstr@glossnamefont}{\@glstr@attrval}%
}%
{%
\GlossariesExtraWarning{Unknown control sequence name
'\@glstr@attrval' supplied in glossnamefont attribute
for entry '#1'. Reverting to default \string\glstr@glossnamefont}%
\let\@glstr@glossnamefont\glstr@glossnamefont
}%
}%
{\let\@glstr@glossnamefont\glstr@glossnamefont}%
\@glstr@glossnamefont{\Glsentryname{#1}}%

```

Do post-name hook:

```

\glstrpostnamehook{#1}%
}%
}
}

```

`\GlossEntryName` This command was only added to glossaries v4.59 so provide a definition in case an older version is installed.

```

\providecommand*{\GlossEntryName}[1]{%
\glstr@glossnamefont{\glstr@glossnamefont}{\Glsentrytitlecase{#1}{name}}%
}

```

Redefine to set the abbreviation format and accessibility support.

```

\@ifpackageloaded{glossaries-accsupp}
{
\renewcommand*{\GlossEntryName}[1]{%
\@glsdoifexistsorwarn{#1}%
{%
\glsetabbrvfmt{\glscategory{#1}}%

```

Do pre-name hook:

```
\glxtrprnamehook{#1}%
```

Allow the glossnamefont attribute to determine the font applied.

```
\glshasattribute{#1}{glossnamefont}%
{%
  \protected@edef\@glxtr@attrval{\glsetattribute{#1}{glossnamefont}}%
  \ifcsdef{\@glxtr@attrval}%
  {%
    \letcs{\@glxtr@glossnamefont}{\@glxtr@attrval}%
  }%
  {%
    \GlossariesExtraWarning{Unknown control sequence name
      '\@glxtr@attrval' supplied in glossnamefont attribute
      for entry '#1'. Reverting to default \string\glsnamefont}%
    \let\@glxtr@glossnamefont\glsnamefont
  }%
}%
{\let\@glxtr@glossnamefont\glsnamefont}%
\glsnameaccessdisplay
{%
  \@glxtr@glossnamefont{\glsetentrytitlecase{#1}{name}}%
}%
{#1}%
```

Do post-name hook:

```
\glxtrpostnamehook{#1}%
}%
}
{
  \renewcommand*{\GlossEntryName}[1]{%
    \@glsdoidexistsorwarn{#1}%
  {%
    \glsetabbrvfmt{\glscategory{#1}}%
  }
}
```

Do pre-name hook:

```
\glxtrprnamehook{#1}%
\glshasattribute{#1}{glossnamefont}%
{%
  \protected@edef\@glxtr@attrval{\glsetattribute{#1}{glossnamefont}}%
  \ifcsdef{\@glxtr@attrval}%
  {%
    \letcs{\@glxtr@glossnamefont}{\@glxtr@attrval}%
  }%
  {%
    \GlossariesExtraWarning{Unknown control sequence name
      '\@glxtr@attrval' supplied in glossnamefont attribute
      for entry '#1'. Reverting to default \string\glsnamefont}%
    \let\@glxtr@glossnamefont\glsnamefont
  }%
}
```

```
}%
{\let\@glsxtr@glossnamefont\glsnamefont}%
\@glsxtr@glossnamefont{\glsentrytitlecase{#1}{name}}}%
```

Do post-name hook:

```
\glsxtrpostnamehook{#1}%
}%
}
}
```

`\glsxtrprenamehook`

```
\newcommand*{\glsxtrprenamehook}[1]{}
```

Provide a convenient way to also index the entries using the standard `\index` mechanism. This may use different actual, encap and escape characters to those used for the glossaries.

`\glsxtrpostnamehook` Hook to append stuff after the name is displayed in the glossary. The argument is the entry's label.

```
\newcommand*{\glsxtrpostnamehook}[1]{%
\let\@glsnumberformat\@glsxtr@defaultnumberformat
\glsxtrdoautoindexname{#1}{indexname}}%
```

Allow additional code regardless of category:

```
\glsextrapostnamehook{#1}%
```

Allow categories to hook in here.

```
\csuse{glsxtrpostname\glscategory{#1}}%
}
```

`\glsextrapostnamehook`

```
\newcommand*{\glsextrapostnamehook}[1]{}%
```

`\glsdefpostname` Provide a convenient command for defining the post-name hook for the given category.

```
\newcommand*{\glsdefpostname}[2]{%
\csdef{glsxtrpostname#1}{#2}%
}
```

`\glsxtr@setaccessdisplay`

```
\@ifpackageloaded{glossaries-accsupp}
{
\newcommand*{\glsxtr@setaccessdisplay}[1]{%
\ifcsdef{gls#1accessdisplay}%
{\letcs\@glsxtr@accessdisplay{gls#1accessdisplay}}%
}%
```

This is essentially the reverse of `\@gls@fetchfield`, since the field supplied to `\glossentryname` has to be the internal label, but the `\gls $\langle field \rangle$ accessdisplay` commands use the key name.

```

\protected@edef\@gls@thisval{#1}%
\@for\@gls@map:=\@gls@keymap\do{%
\protected@edef\@this@key{\expandafter\@secondoftwo\@gls@map}%
\ifdefequal{\@this@key}{\@gls@thisval}%
{%
\protected@edef\@gls@thisval{\expandafter\@firstoftwo\@gls@map}%
\@endfortrue
}%
}%
}%
\ifcsdef{gls\@gls@thisval accessdisplay}%
{\letcs\@glsxtr@accessdisplay{gls\@gls@thisval accessdisplay}}%
{\let\@glsxtr@accessdisplay\@firstoftwo}%
}%
}
}
{%
\newcommand*\@glsxtr@setaccessdisplay}[1]{%
\let\@glsxtr@accessdisplay\@firstoftwo
}

```

`\glossentrynameother` Provide a command that works like `\glossentryname` but accesses a different field (which must be supplied using its internal field label).

```

\newrobustcmd*\@glossentrynameother}[2]{%
\@glsdoifexistsorwarn{#1}%
{%

```

Accessibility support:

```
\glsxtr@setaccessdisplay{#2}%
```

Set the abbreviation format:

```
\glssetabbrvfmt{\glscategory{#1}}%
```

As from v1.54, do pre-name hook:

```

\glsxtrpreramehook{#1}%
\glshasattribute{#1}{glossnamefont}%
{%
\protected@edef\@glsxtr@attrval{\glsgetattribute{#1}{glossnamefont}}%
\ifcsdef{\@glsxtr@attrval}%
{%
\letcs{\@glsxtr@glossnamefont}{\@glsxtr@attrval}%
}%
{%
\GlossariesExtraWarning{Unknown control sequence name
'\@glsxtr@attrval' supplied in glossnamefont attribute
for entry '#1'. Reverting to default \string\glsnamefont}%
\let\@glsxtr@glossnamefont\glsnamefont
}%
}%
{\let\@glsxtr@glossnamefont\glsnamefont}%
\glsifattribute{#1}{glossname}{firstuc}%

```

```

{%
  \@glsxtr@accessdisplay
  {\@glsxtr@glossnamefont{\@Gls@entry@field{#1}{#2}}}%
  {#1}%
}%
{%
  \glsifattribute{#1}{glossname}{title}%
  {%
    \@glsxtr@do@titlecaps@warn
    \@glsxtr@accessdisplay
    {\@glsxtr@glossnamefont{\glsxtrfieldtitlecase{#1}{#2}}}%
    {#1}%
  }%
  {%
    \glsifattribute{#1}{glossname}{uc}%
    {%
      \letcs{\glo@name}{glo@\glsdetoklabel{#1}@#2}%
      \@glsxtr@accessdisplay
      {\@glsxtr@glossnamefont{\glsupercase{\glo@name}}}%
      {#1}%
    }%
    {%
      \letcs{\glo@name}{glo@\glsdetoklabel{#1}@#2}%
      \@glsxtr@accessdisplay
      {\expandafter\@glsxtr@glossnamefont\expandafter{\glo@name}}%
      {#1}%
    }%
  }%
}%
Do post-name hook.
\glsxtrpostnamehook{#1}%
}%
}

```

`\Glossentrynameother` Provide a command that works like `\Glossentryname` but accesses a different field (which must be supplied using its internal field label).

```

\newrobustcmd*{\Glossentrynameother}[2]{%
  \@glsdoifexistsorwarn{#1}%
  {%

```

Accessibility support:

```
\glsxtr@setaccessdisplay{#2}%
```

Set the abbreviation format:

```
\glssetabbrvfmt{\glscategory{#1}}%
```

Do pre-name hook:

```

\glsxtrprenamehook{#1}%
\glsattribute{#1}{glossnamefont}%
{%

```

```

\protected@edef\@glxtr@attrval{\glsetattribute{#1}{glossnamefont}}%
\ifcsdef{\@glxtr@attrval}%
{%
  \letcs{\@glxtr@glossnamefont}{\@glxtr@attrval}%
}%
{%
  \GlossariesExtraWarning{Unknown control sequence name
    '\@glxtr@attrval' supplied in glossnamefont attribute
    for entry '#1'. Reverting to default \string\glsnamefont}%
  \let\@glxtr@glossnamefont\glsnamefont
}%
}%
{\let\@glxtr@glossnamefont\glsnamefont}%
\@glxtr@accessdisplay
{\@glxtr@glossnamefont{\@Gls@entry@field{#1}{#2}}}%
{#1}%

```

Do post-name hook.

```

\glxtrpostnamehook{#1}%
}%
}

```

`\GLOSSentrynameother` Provide a command that works like `\GLOSSentryname` but accesses a different field (which must be supplied using its internal field label).

```

\newrobustcmd*{\GLOSSentrynameother}[2]{%
  \glsdoifexistsorwarn{#1}%
}%

```

Accessibility support:

```

\glxtr@setaccessdisplay{#2}%

```

Set the abbreviation format:

```

\glssetabbrvfmt{\glscategory{#1}}%

```

Do pre-name hook:

```

\glxtrprernamehook{#1}%
\glshasattribute{#1}{glossnamefont}%
{%
  \protected@edef\@glxtr@attrval{\glsetattribute{#1}{glossnamefont}}%
  \ifcsdef{\@glxtr@attrval}%
  {%
    \letcs{\@glxtr@glossnamefont}{\@glxtr@attrval}%
  }%
  {%
    \GlossariesExtraWarning{Unknown control sequence name
      '\@glxtr@attrval' supplied in glossnamefont attribute
      for entry '#1'. Reverting to default \string\glsnamefont}%
    \let\@glxtr@glossnamefont\glsnamefont
  }%
}%
{\let\@glxtr@glossnamefont\glsnamefont}%

```

```

\@glxtr@accessdisplay
{\@glxtr@glossnamefont{\glssupercase{\@glxtr@entry@field{#1}{#2}}}}%
{#1}%

```

Do post-name hook.

```

\glxtrpostnamehook{#1}%
}%
}

```

`\GlossEntryNameOther` Provide a command that works like `\GlossEntryName` but accesses a different field (which must be supplied using its internal field label).

```

\newrobustcmd*{\GlossEntryNameOther}[2]{%
\@glxdoifexistsorwarn{#1}%
{%

```

Accessibility support:

```

\glxtr@setaccessdisplay{#2}%

```

Set the abbreviation format:

```

\glxsetabbrvfmt{\glscategory{#1}}%

```

Do pre-name hook:

```

\glxtrprernamehook{#1}%
\glshasattribute{#1}{glossnamefont}%
{%
\protected@edef\@glxtr@attrval{\glxgetattribute{#1}{glossnamefont}}%
\ifcsdef{\@glxtr@attrval}%
{%
\letcs{\@glxtr@glossnamefont}{\@glxtr@attrval}%
}%
{%
\GlossariesExtraWarning{Unknown control sequence name
'\@glxtr@attrval' supplied in glossnamefont attribute
for entry '#1'. Reverting to default \string\glxnamefont}%
\let\@glxtr@glossnamefont\glxnamefont
}%
}%
{\let\@glxtr@glossnamefont\glxnamefont}%
\@glxtr@accessdisplay
{\@glxtr@glossnamefont{\glxentrytitlecase{#1}{#2}}}%
{#1}%

```

Do post-name hook.

```

\glxtrpostnamehook{#1}%
}%
}

```

`\if@glxtr@format@override` Determines if the format key should override the indexing attribute value.

```

\newif\if@glxtr@format@override
\@glxtr@format@overridefalse

```


If overriding is enabled, the `\glshypernumber` command will have to be redefined in the index to use `\hyperpage` instead.

`\trEnableIndexFormatOverride`

```
\@ifpackageloaded{hyperref}
{
```

If `hyperref`'s `hyperindex` option is on, then `hyperref` will automatically add `\hyperpage`, so don't add it.

```
\ifHy@hyperindex
\newcommand*{\GlsXtrEnableIndexFormatOverride}{%
\@glsxtr@format@overridetrue
\appto\theindex{\let\glshypernumber\@firstofone}%
}
\else
\newcommand*{\GlsXtrEnableIndexFormatOverride}{%
\@glsxtr@format@overridetrue
\appto\theindex{\let\glshypernumber\hyperpage}%
}
\fi
}
{
\newcommand*{\GlsXtrEnableIndexFormatOverride}{%
\@glsxtr@format@overridetrue
}
}
\@onlypreamble\GlsXtrEnableIndexFormatOverride
```

`\glsxtrdoautoindexname`

```
\newcommand*{\glsxtrdoautoindexname}[2]{%
\glshasattribute{#1}{#2}%
{%
```

Escape any `makeindex`/`xindy` characters in the value of the `name` field. Take care with `babel` as this won't work if the category code has changed for those characters.

```
\@glsxtr@autoindex@setname{#1}%
```

If the attribute value is simply “true” don't add an `encap`, otherwise use the value as the `encap`.

```
\protected@edef\@glsxtr@attrval{\glsggetattribute{#1}{#2}}%
\if@glsxtr@format@override

\ifx\@glsnnumberformat\@glsxtr@defaultnumberformat
\else
\let\@glsxtr@attrval\@glsnnumberformat
\fi
\fi

\ifdefstring{\@glsxtr@attrval}{true}%
{}%
```

```

        {\protected@eappto\@glo@name{\@glsxtr@autoindex@encap\@glsxtr@attrval}}}%
        \expandafter\glsxtrautoindex\expandafter{\@glo@name}%
    }%
    {}%
}

\glsxtrautoindex
\newcommand*{\glsxtrautoindex}{\index}

\glsxtrautoindexesc
\newcommand{\glsxtrautoindexesc}{%
    \@gls@checkmkidxchars\@glo@sort
    \@glsxtr@autoindex@doextra@esc\@glo@sort
}

\@glsxtr@autoindex@setname Assign \@glo@name for use with indexname attribute.
\newcommand*{\@glsxtr@autoindex@setname}[1]{%
    \protected@edef\@glo@name{\glsxtrautoindexentry{#1}}%
    \glsxtrautoindexassignsort{\@glo@sort}{#1}%
    \glsxtrautoindexesc
    \epreto\@glo@name{\@glo@sort\@glsxtr@autoindex@at}%
}

\glsxtrautoindexentry Command used for the actual part when auto-indexing.
\newcommand*{\glsxtrautoindexentry}[1]{\string\glsentryname{#1}}

\glsxtrautoindexassignsort Used to assign the sort value when auto-indexing.
\newcommand*{\glsxtrautoindexassignsort}[2]{%
    \glsletentryfield{#1}{#2}{sort}%
}

\glsxtr@autoindex@doextra@esc
\newcommand*{\@glsxtr@autoindex@doextra@esc}[1]{%
    Escape the escape character unless it has already been escaped.
    \ifx\@glsxtr@autoindex@esc\@gls@quotechar
    \else
        \def\@gls@checkedmkidx{}%
        \edef\@glsxtr@checkspch{%
            \noexpand\@glsxtr@autoindex@escquote\expandonce{#1}%
            \noexpand\@empty\@glsxtr@autoindex@esc\noexpand\@nnil
            \@glsxtr@autoindex@esc\noexpand\@empty\noexpand\@glsxtr@endescspch}%
        \@glsxtr@checkspch
        \let#1\@gls@checkedmkidx\relax
    \fi
    Escape actual character unless it has already been escaped.
    \ifx\@glsxtr@autoindex@at\@gls@actualchar
    \else
        \def\@gls@checkedmkidx{}%

```

```

\edef\@glstr@checkspch{%
  \noexpand\@glstr@autoindex@escat\expandonce{#1}%
  \noexpand\@empty\@glstr@autoindex@at\noexpand\@nnil
  \@glstr@autoindex@at\noexpand\@empty\noexpand\@glstr@endescspch}%
\@glstr@checkspch
\let#1\@glstr@checkedmkidx\relax
\fi

```

Escape level character unless it has already been escaped.

```

\ifx\@glstr@autoindex@level\@glstr@levelchar
\else
  \def\@glstr@checkedmkidx{%
    \edef\@glstr@checkspch{%
      \noexpand\@glstr@autoindex@esclevel\expandonce{#1}%
      \noexpand\@empty\@glstr@autoindex@level\noexpand\@nnil
      \@glstr@autoindex@level\noexpand\@empty\noexpand\@glstr@endescspch}%
    \@glstr@checkspch
    \let#1\@glstr@checkedmkidx\relax
  }
\fi

```

Escape encap character unless it has already been escaped.

```

\ifx\@glstr@autoindex@encap\@glstr@encapchar
\else
  \def\@glstr@checkedmkidx{%
    \edef\@glstr@checkspch{%
      \noexpand\@glstr@autoindex@escencap\expandonce{#1}%
      \noexpand\@empty\@glstr@autoindex@encap\noexpand\@nnil
      \@glstr@autoindex@encap\noexpand\@empty\noexpand\@glstr@endescspch}%
    \@glstr@checkspch
    \let#1\@glstr@checkedmkidx\relax
  }
\fi
}

```

The user commands here have a preamble-only restriction to ensure they are set before required and also to reduce the chances of complications caused by babel's shorthands.

`\@glstr@autoindex@at` Actual character for use with `\index`.

```
\newcommand*{\@glstr@autoindex@at}{}
```

`\GlsXtrSetActualChar` Set the actual character.

```

\newcommand*{\GlsXtrSetActualChar}[1]{%
  \gdef\@glstr@autoindex@at{#1}%
  \def\@glstr@autoindex@escat##1##2##3\@glstr@endescspch{%
    \@glstr@autoindex@escspch{#1}{\@glstr@autoindex@escat}{##1}{##2}{##3}%
  }%
}
\@onlypreamble\GlsXtrSetActualChar
\makeatother
\GlsXtrSetActualChar{@}
\makeatletter

```

`\@glxtr@autoindex@encap` Encap character for use with `\index`.

```
\newcommand*{\@glxtr@autoindex@encap}{}%
```

`\GlsXtrSetEncapChar` Set the encap character.

```
\newcommand*{\GlsXtrSetEncapChar}[1]{%
\gdef\@glxtr@autoindex@encap{#1}%
\def\@glxtr@autoindex@escencap##1#1##2#1##3\@glxtr@endescspch{%
\@glxtr@autoindex@escspch{#1}{\@glxtr@autoindex@escencap}{##1}{##2}{##3}%
}%
}
\GlsXtrSetEncapChar{!}
\@onlypreamble\GlsXtrSetEncapChar
```

`\@glxtr@autoindex@level` Level character for use with `\index`.

```
\newcommand*{\@glxtr@autoindex@level}{}%
```

`\GlsXtrSetLevelChar` Set the encap character.

```
\newcommand*{\GlsXtrSetLevelChar}[1]{%
\gdef\@glxtr@autoindex@level{#1}%
\def\@glxtr@autoindex@esclevel##1#1##2#1##3\@glxtr@endescspch{%
\@glxtr@autoindex@escspch{#1}{\@glxtr@autoindex@esclevel}{##1}{##2}{##3}%
}%
}
\GlsXtrSetLevelChar{!}
\@onlypreamble\GlsXtrSetLevelChar
```

`\@glxtr@autoindex@esc` Escape character for use with `\index`.

```
\newcommand*{\@glxtr@autoindex@esc}{"}%
```

`\GlsXtrSetEscChar` Set the escape character.

```
\newcommand*{\GlsXtrSetEscChar}[1]{%
\gdef\@glxtr@autoindex@esc{#1}%
\def\@glxtr@autoindex@escquote##1#1##2#1##3\@glxtr@endescspch{%
\@glxtr@autoindex@escspch{#1}{\@glxtr@autoindex@escquote}{##1}{##2}{##3}%
}%
}
\GlsXtrSetEscChar{"}
\@onlypreamble\GlsXtrSetEscChar
```

Set if defined. (For example, if doc package has been loaded.) Actual character `\actualchar`:

```
\ifdef\actualchar
{\expandafter\GlsXtrSetActualChar\expandafter{\actualchar}}
{}%
```

Quote character `\quotechar`:

```
\ifdef\quotechar
{\expandafter\GlsXtrSetEscChar\expandafter{\quotechar}}
{}%
```

Level character \levelchar:

```
\ifdef\levelchar
{\expandafter\GlsXtrSetLevelChar\expandafter{\levelchar}}
{}
```

Encap character \encapchar:

```
\ifdef\encapchar
{\expandafter\GlsXtrSetEncapChar\expandafter{\encapchar}}
{}
```

\@glstr@gobbleto@endescspch

```
\def\@glstr@gobbleto@endescspch#1\@glstr@endescspch{}
```

```
\@@glstr@autoindex@escspch{<char>}{<cs>}{<pre>}{<mid>}
{<post>}
```

\@@glstr@autoindex@esc@spch

```
\newcommand*{\@glstr@autoindex@escspch}[5]{%
\@glstr@tmpb=\expandafter{\@glstr@checkedmkidx}%
\toks@={#3}%
\ifx\@nnil#3\relax
\def\@glstr@checkspch{\@glstr@gobbleto@endescspch#5\@glstr@endescspch}%
\else
\ifx\@nnil#4\relax
\edef\@glstr@checkedmkidx{\the\@glstr@tmpb\the\toks@}%
\def\@glstr@checkspch{\@glstr@gobbleto@endescspch
#4#5\@glstr@endescspch}%
\else
\edef\@glstr@checkedmkidx{\the\@glstr@tmpb\the\toks@
\@glstr@autoindex@esc#1}%
\def\@glstr@checkspch{#2#5#1\@nnil#1\@glstr@endescspch}%
\fi
\fi
\@glstr@checkspch
}
```

\Glossentrydesc Redefine to set the abbreviation format and accessibility support.

```
\renewcommand*{\Glossentrydesc}[1]{%
\glstoifexistsorwarn{#1}%
{%
\glsssetabbrvfmt{\glscategory{#1}}%
\Glsaccessdesc{#1}%
}%
}
```

\glossentrysymbol Redefine to set the format and accessibility support. Allow for the possibility of being used in a section heading for standalone entry definitions.

```
\renewcommand*{\glossentrysymbol}[1]{%
\glstexorpdfstring{\@glossentrysymbol{#1}}{\glstentrypdfsymbol{#1}}%
}
```

`\glsentrypdfsymbol` May be redefined to a field that expands to a value that's more suitable for PDF bookmarks.

```
\newcommand{\glsentrypdfsymbol}[1]{\glsentrysymbol{#1}}
```

`\@glossentrysymbol` There are no case-changing attributes as it's less usual for symbols.

```
\newrobustcmd*{\@glossentrysymbol}[1]{%
  \glsdoifexistsorwarn{#1}%
  {%
    \begingroup
      \glssetabbrvfmt{\glscategory{#1}}%
      \glshasattribute{#1}{glosssymbolfont}%
      {%
        \protected@edef\glsxtr@attrval{\glsgetattribute{#1}{glosssymbolfont}}%
        \ifcsdef{\glsxtr@attrval}%
        {%
          \letcs{\glsxtr@glosssymbolfont}{\@glsxtr@attrval}%
        }%
        {%
          \GlossariesExtraWarning{Unknown control sequence name
            '\@glsxtr@attrval' supplied in glosssymbolfont attribute
            for entry '#1'. Ignoring}%
          \let\@glsxtr@glosssymbolfont\@firstofone
        }%
      }%
      {\let\@glsxtr@glosssymbolfont\@firstofone}%
      \@glsxtr@glosssymbolfont{\glsaccesssymbol{#1}}%
    \endgroup
  }%
}
```

`\Glossentrysymbol` Redefine to set the abbreviation format and accessibility support.

```
\renewcommand*{\Glossentrysymbol}[1]{%
  \glsdoifexistsorwarn{#1}%
  {%
    \glssetabbrvfmt{\glscategory{#1}}%
    \Glsaccesssymbol{#1}%
  }%
}
```

Allow initials to be marked but only use the formatting for the tag in the glossary.

`\GlsXtrEnableInitialTagging` Allow initial tagging. The first argument is a list of categories to apply this to. The second argument is the name of the command to use to tag the initials. This can't already be defined for safety unless the starred version is used.

```
\newcommand*{\GlsXtrEnableInitialTagging}{%
  \@ifstar\s@glsxtr@enabletagging\@glsxtr@enabletagging
}
\@onlypreamble\GlsXtrEnableInitialTagging
```

`\@glsxtr@enabletagging` Starred version undefines command.

```
\newcommand*{\s@glsxtr@enabletagging}[2]{%
  \undef#2%
  \@glsxtr@enabletagging{#1}{#2}%
}
```

`\@glsxtr@enabletagging` Internal command.

```
\newcommand*{\@glsxtr@enabletagging}[2]{%
  Set attributes for categories given in the first argument.
  \@for\@glsxtr@cat:=#1\do
  {%
    \ifdefempty\@glsxtr@cat
    {}%
    {\glsssetcategoryattribute{\@glsxtr@cat}{tagging}{true}}%
  }%
  \newrobustcmd*#2[1]{##1}%
  \def\@glsxtr@taggingcs{#2}%
  \renewcommand*\@glsxtr@activate@initialtagging{%
    \let#2\@glsxtr@tag
  }%
  \ifundef\@gls@preglossaryhook
  {\GlossariesExtraWarning{Initial tagging requires at least
    glossaries.sty v4.19 to work correctly}}%
  {}%
}
```

Are we using an old version of `mfirstuc` that has a bug in `\capitalisewords`?
If so, patch it so we don't have a problem with a combination of tagging and title case.

`\mfu@checkword@do` If this command hasn't been defined, then we have pre v2.02 of `mfirstuc`

```
\ifundef\mfu@checkword@do
{
  \newcommand*{\mfu@checkword@do}[1]{%
    \ifdefstring{\mfu@checkword@arg}{#1}%
    {%
      \let\@mfu@domakefirstuc\@firstofone
      \listbreak
    }%
    {}%
  }
}
```

`\mfu@checkword` `\capitalisewords` was introduced in `mfirstuc` v1.06. If `\mfu@checkword` hasn't been defined `mfirstuc` is too old to support the title case attribute.

```
\ifundef\mfu@checkword
{
  \newcommand{\@glsxtr@do@titlecaps@warn}{%
    \GlossariesExtraWarning{mfirstuc.sty too old. Title Caps
      support not available}%
  }
}
```

One warning should suffice.

```

\let\@glxtr@do@titlecaps@warn\relax
}
}
{
\renewcommand*{\mfu@checkword}[1]{%
\def\mfu@checkword@arg{#1}%
\let\@mfu@domakefirstuc\makefirstuc
\forlistloop\mfu@checkword@do\@mfu@nocaplist
}
}
}
{}% no patch required

```

\@glxtr@do@titlecaps@warn Do warning if title case not supported.

```
\newcommand*{\@glxtr@do@titlecaps@warn}{}
```

glxtr@activate@initialtagging Used in \printglossary but at least v4.19 of glossaries required.

```
\newcommand*{\@glxtr@activate@initialtagging{}}
```

\@glxtr@tag Definition of tagging command when used in glossary.

```

\newrobustcmd*{\@glxtr@tag}[1]{%
\glsifattribute{\glscurrententrylabel}{tagging}{true}%
{\glxtrtagfont{#1}}{#1}%
}

```

\glxtrtagfont Used in the glossary.

```
\newcommand*{\glxtrtagfont}[1]{\underline{#1}}
```

\@gls@preglossaryhook This macro was introduced in glossaries version 4.19, so it may not be defined. If it hasn't been defined this feature is unavailable. A check is added for the entry's existence to prevent errors from occurring if the user removes an entry or changes the label, which can interrupt the build process.

```

\ifdef\@gls@preglossaryhook
{
\renewcommand*{\@gls@preglossaryhook}{%
\@glxtr@activate@initialtagging

```

Since the glossaries are automatically scoped, \@glxtr@org@postdescription shouldn't already be defined, but check anyway just as a precautionary measure.

```

\ifundef\@glxtr@org@postdescription
{%
\let\@glxtr@org@postdescription\glspostdescription
\renewcommand*{\glspostdescription}{%
\ifglentryexists{\glscurrententrylabel}%
{%
\glxtrpostdescription
\@glxtr@org@postdescription
}%
}

```



```

        {}%
    }%
}%
{}%

Enable the options used by \@@glxtrp:
    \glossxtrsetpopts
}%
}
{}

\glxtrpostdescription This command will only be used if \@gls@preglossaryhook is available and the
glossary style uses \glspostdescription without modifying it. (\nopostdesc
will suppress this.) The glossaries-extra-stylemods package will add the post
description hook to all the predefined styles that don't include it.
    \newcommand*{\glxtrpostdescription}{%
        \csuse{glxtrpostdesc\glscategory{\glscurrententrylabel}}}%
    }

\glxtrpostdescgeneral
    \newcommand*{\glxtrpostdescgeneral}{}

\glxtrpostdescterm This is redundant as it doesn't match any common categories. \newterm sets
the category to index.
    \newcommand*{\glxtrpostdescterm}{}

\glxtrpostdescacronym
    \newcommand*{\glxtrpostdescacronym}{}

\glxtrpostdescabbreviation
    \newcommand*{\glxtrpostdescabbreviation}{}

\glsdefpostdesc Provide a convenient command for defining the post-description hook for the
given category.
    \newcommand*{\glsdefpostdesc}[2]{%
        \csdef{glxtrpostdesc#1}{#2}%
    }

\glspostlinkhook Redefine the post link hook used by commands like \gls to make it easier for
categories or attributes to modify this action. Since this hook occurs outside
the existence check of commands like \gls, this needs to be checked again here.
Do nothing if the entry hasn't been defined.
    \renewcommand*{\glspostlinkhook}{%
        \ifglsentryexists{\glslabel}{\glxtrpostlinkhook}}}%
    }

```

`\glstrpostlinkhook` The entry label should already be stored in `\glslabel` by `\@gls@link`.

```

\newcommand*{\glstrpostlinkhook}{%
  \glstrdiscardperiod{\glslabel}%
  {\glstrpostlinkendsentence}%
  {\glstrtrifcustomdiscardperiod
    {\glstrtrifperiod{\glstrpostlinkendsentence}{\glstrpostlink}}%
    {\glstrpostlink}}%
  }%
}

```

`\glstrtrifcustomdiscardperiod` Allow user to provide a custom check. Should expand to #2 if no check is required otherwise expand to #1.

```

\newcommand*{\glstrtrifcustomdiscardperiod}[2]{#2}

```

`\glstrpostlink`

```

\newcommand*{\glstrpostlink}{%
  \csuse{glstrpostlink\glscategory{\glslabel}}%
}

```

`\glsdefpostlink` Provide a convenient command for defining the post-link hook for the given category. Doesn't allow an empty argument (which) would overwrite `\glstrpostlink`.

```

\newcommand*{\glsdefpostlink}[2]{%
  \ifthenelse{\equal{#1}{}}{%
    {\PackageError{glossaries-extra}
      {Invalid empty category label in \string\glsdefpostlink}{}}%
    {\csdef{glstrpostlink#1}{#2}}%
  }
}

```

`\glspretopostlink` Similar to the above but prepend.

```

\newcommand*{\glspretopostlink}[2]{%
  \ifthenelse{\equal{#1}{}}{%
    {\PackageError{glossaries-extra}
      {Invalid empty category label in \string\glspretopostlink}{}}%
    {%
      \ifcsundef{glstrpostlink#1}
        {\csdef{glstrpostlink#1}{#2}}%
        {\cspretopostlink{glstrpostlink#1}{#2}}%
      }%
    }
}

```

`\glsapptopostlink` Similar to the above but append.

```

\newcommand*{\glsapptopostlink}[2]{%

```

`\ifthenelse` is used to ensure that the expanded value is tested. (The category label must be fully expandable.)

```
\ifthenelse{\equal{#1}{}}{%
  {\PackageError{glossaries-extra}
    {Invalid empty category label in \string\glspretopostlink}{}}%
  {%
    \ifcsundef{glsxtrpostlink#1}
      {\csdef{glsxtrpostlink#1}{#2}}%
      {\csappto{glsxtrpostlink#1}{#2}}%
    }%
  }
```

`\glsxtrpostlinkendsentence` Done by `\glsxtrpostlinkhook` if a full stop is discarded.

```
\newcommand*{\glsxtrpostlinkendsentence}{%
  \ifcsdef{glsxtrpostlink\glscategory{\glslabel}}
  {%
    \csuse{glsxtrpostlink\glscategory{\glslabel}}%
  }
```

Put the full stop back.

```
.\spacefactor\sffcode{.} \relax
}%
{%
```

Assume the full stop was discarded because the entry ends with a period, so adjust the spacefactor.

```
\spacefactor\sffcode{.} \relax
}%
}
```

`\glsxtrpostlinkAddDescOnFirstUse` Provide a command for appending the description in parentheses on first use, for the convenience of users wanting to add this to the post link hook.

```
\newcommand*{\glsxtrpostlinkAddDescOnFirstUse}{%
  \glsxtrifwasfirstuse{\glsxtrgenentrytextfmt{ }%
    \glsxtrparen{\glsaccessfmtdesc}{\glsxtrgenentrytextfmt}{\glslabel}}}%
}
```

`\glsxtrpostlinkAddSymbolOnFirstUse` Provide a command for appending the symbol (if defined) in parentheses on first use, for the convenience of users wanting to add this to the post link hook.

```
\newcommand*{\glsxtrpostlinkAddSymbolOnFirstUse}{%
  \glsxtrifwasfirstuse
  {%
    \ifglshassymbol{\glslabel}%
    {\glsxtrgenentrytextfmt{ }%
      \glsxtrparen{\glsaccessfmtsymbol}{\glsxtrgenentrytextfmt}{\glslabel}}}%
    {}%
  }%
  {}%
}
```

`\linkAddSymbolDescOnFirstUse` Provide a command for appending the symbol (if defined) and description in parentheses on first use, for the convenience of users wanting to add this to the post link hook.

```
\newcommand*{\glxtrpostlinkAddSymbolDescOnFirstUse}{%
  \glxtrifwasfirstuse
  {%
    \glxtrgenentrytextfmt{ }\glxtrparen
    {%
      \ifglshassymbol{\glslabel}%
      {\glaccessfmtsymboll{\glxtrgenentrytextfmt}{\glslabel}%
      \expandafter\glxtrgenentrytextfmt\expandafter{\glxtrpostlinkSymbolDescSep}}%
      {}%
      \glaccessfmdesc{}{\glxtrgenentrytextfmt}{\glslabel}%
    }%
  }%
  {}%
}
```

`\glxtrpostlinkSymbolDescSep` Separator used in the above

```
\newcommand*{\glxtrpostlinkSymbolDescSep}{, }
```

`\discardperiodretainfirstuse`

```
\newcommand*{\glxtrdiscardperiodretainfirstuse}[3]{%
  \glxtrifwassubsequentorshort{\glxtrifperiod{#2}{#3}}{#3}%
}
```

`\glxtrdiscardperiod` Discard following period (if present) if the `discardperiod` attribute is true. If a period is discarded, do the second argument otherwise do the third argument. The entry label is in the first argument. Since this is designed for abbreviations that end with a period, check if the plural form was used (which typically won't end with a period).

```
\newcommand*{\glxtrdiscardperiod}[3]{%
  \glusifattribute{#1}{retainfirstuseperiod}{true}%
  {\glxtrdiscardperiodretainfirstuse{#1}{#2}{#3}}%
  {%
    \glusifattribute{#1}{discardperiod}{true}%
    {%
      \glusifplural
      {%
        \glusifattribute{#1}{pluraldiscardperiod}{true}%
        {\glxtrifperiod{#2}{#3}}%
        {#3}%
      }%
    }%
    \glxtrifperiod{#2}{#3}%
  }%
  {#3}%
}%
```

}

`\glxtrifperiod` Make a convenient user command to check if the next character is a full stop (period). Works like `\@ifstar` but uses `\new@ifnextchar` rather than `\ifnextchar`

```
\newcommand*\glxtrifperiod}[1]{\new@ifnextchar.\{\@firstoftwo{#1}}}
```

Sometimes it's useful to test if there's a punctuation character following the glossary entry.

`\glxtr@punclist` List of characters identified as punctuation marks. (Be careful of `babel` short-hands!) This doesn't allow for punctuation marks made up from multiple characters (such as `'`).

```
\newcommand*\glxtr@punclist{\.,;?!}
```

`\glxtraddpunctuationmark` Add character to punctuation list.

```
\newcommand*\glxtraddpunctuationmark}[1]{\appto\glxtr@punclist{#1}}
```

`\glxtrsetpunctuationmarks` Reset the punctuation list.

```
\newcommand*\glxtrsetpunctuationmarks[1]{\def\glxtr@punclist{#1}}
```

```
\glxtrifnextpunc{<true part>}{<false part>}
```

`\glxtrifnextpunc`

Test if this is followed by a punctuation mark. (Adapted from `\new@ifnextchar`.)

```
\newcommand*\glxtrifnextpunc}[2]{%
\def\reserved@a{#1}%
\def\reserved@b{#2}%
\futurelet\@glspunc@token\glxtr@ifnextpunc
}
```

`\glxtr@ifnextpunc`

```
\newcommand*\glxtr@ifnextpunc{%
\glxtr@ifpunctoken{\@glspunc@token}{\let\reserved@b\reserved@a}{}%
\reserved@b
}
```

`\glxtr@ifpunctoken` Test if the token given in the first argument is in the punctuation list.

```
\newcommand*\glxtr@ifpunctoken}[1]{%
\expandafter\@glxtr@ifpunctoken\expandafter#1\glxtr@punclist\@nnil
}
```

`\@glxtr@ifpunctoken`

```
\def\@glxtr@ifpunctoken#1#2{%
\let\reserved@d=#2%
\ifx\reserved@d\@nnil
\let\glxtr@next\@glxtr@notfoundinlist
\else
```

```

\ifx#1\reserved@d
\let\glstr@next\glstr@foundinlist
\else
\let\glstr@next\glstr@ifpunctoken
\fi
\fi
\glstr@next#1%
}

```

```
\glstr@foundinlist
```

```
\def\glstr@foundinlist#1\@nnil{\@firstoftwo}
```

```
\glstr@notfoundinlist
```

```
\def\glstr@notfoundinlist#1{\@secondoftwo}
```

```
\glstrdopostpunc
```

```
\glstrdopostpunc{<code>}
```

If this is followed by a punctuation character, do *<code>* after the character otherwise do *<code>* before whatever comes next.

```

\newrobustcmd{\glstrdopostpunc}[1]{%
\glstr@ifnextpunc{\glstr@swaptwo{#1}}{#1}%
}

```

```
\glstr@swaptwo
```

```
\newcommand{\glstr@swaptwo}[2]{#2#1}
```

1.7 Abbreviations

The “acronym” code from `glossaries` is misnamed as it’s more often used for other forms of abbreviations. This code corrects this inconsistency, but rather than just having synonyms, provide commands for abbreviations that have a similar, but not identical, underlying mechanism to acronyms.

If there’s a style for the given category, it needs to be applied by `\newabbreviation`.

```

\define@key{glstrabbrv}{category}{%
\protected@edef\glscategorylabel{#1}%
}

```

The `shortplural` and `longplural` are parsed separately, so are now in another key family. Save the short plural form. This may be needed before the entry is defined.

```

\define@key{glstrabbrvpl}{shortplural}{%
\def\@glstr@shortpl{#1}%
}

```

Similarly for the long plural form.

```
\define@key{glstrabbrvpl}{longplural}{%
  \def\@gls@longpl{#1}%
}
```

Token registers for the short plural and long plural, provided for use in the abbreviation style definitions.

```
\glsshortpltok
\newtoks\glsshortpltok
```

```
\glslongpltok
\newtoks\glslongpltok
```

`\@glstr@insertdots` Provided in case user wants to automatically insert dots between each letter of the abbreviation. This should be applied before defining the abbreviation to optimise the document build. (Otherwise, it would have to be done each time the short form is required, which is an unnecessary waste of time.) For this to work the short form must be expanded when passed to `\newabbreviation`. Note that explicitly using the `short` or `shortplural` keys will override this.

```
\newcommand*{\@glstr@insertdots}[2]{%
  \def#1{}%
  \@glstr@insert@dots#1#2\@nnil
}
```

```
\@glstr@insert@dots
\newcommand*{\@glstr@insert@dots}[2]{%
  \ifx\@nnil#2\relax
    \let\@glstr@insert@dots@next\@gobble
  \else
    \ifx\relax#2\relax
      \else
        \appto#1{#2.}%
      \fi
    \let\@glstr@insert@dots@next\@glstr@insert@dots
  \fi
  \@glstr@insert@dots@next#1%
}
```

Similarly provide a way of replacing spaces with `\glstrwordsep`, which first needs to be defined:

```
\glstrwordsep
\newcommand*{\glstrwordsep}{\glstrgenentrytextfmt{ }}
```

```
\glstrwordsephyphen
\newcommand*{\glstrwordsephyphen}{\glstrgenentrytextfmt{-}}
```

Each word is marked with

`\glxtrword`

```
\newcommand*{\glxtrword}[1]{\glxtrgenentrytextfmt{#1}}
```

`\@glxtr@markwordseps`

```
\newcommand*{\@glxtr@markwordseps}[2]{%
  \def#1{%
    \@glxtr@mark@wordseps#1#2 \@nnil
  }
}
```

`\@glxtr@mark@wordseps`

```
\def\@glxtr@mark@wordseps#1#2 #3{%
  \ifdefempty{#1}%
  {\def#1{\protect\glxtrword{#2}}}%
  {\appto#1{\protect\glxtrwordsep\protect\glxtrword{#2}}}%
  \ifx\@nnil#3\relax
    \let\@glxtr@mark@wordseps@next\relax
  \else
    \def\@glxtr@mark@wordseps@next{%
      \@glxtr@mark@wordseps#1#3}%
    \fi
  \@glxtr@mark@wordseps@next
}
```

`\newabbreviation` Define a new generic abbreviation.

```
\newcommand*{\newabbreviation}[4][[]]{%
  \glxtr@newabbreviation{#1}{#2}{#3}{#4}%
}
```

`\glxtr@newabbreviation` Internal macro. (bib2gls has an option that needs to temporarily redefine `\newabbreviation`. This is just makes it easier to save and restore the original definition.)

```
\newcommand*{\glxtr@newabbreviation}[4]{%
  \glskeylisttok{#1}%
  \glslabeltok{#2}%
  \glsshorttok{#3}%
  \glslongtok{#4}%
}
```

Save the original short and long values (before attribute settings modify them).

```
\def\glxtrorgshort{#3}%
\def\glxtrorglong{#4}%

\def\glxtrorgkeylist{#1}%

```

Provide extra settings for hooks. Make sure to append a comma if this hook is changed.

```
\def\ExtraCustomAbbreviationFields{}
```

Initialise accessibility settings if required.

```
\@gls@initaccesskeys
```


Get the category.

```
\def\glscategorylabel{abbreviation}%
```

Ignore the shortplural and longplural keys.

```
\setkeys*{glstrabbrv}{#1}%
```

Save remaining keys, just in case any hook also uses \setkeys

```
\let\@glstrabbrv@rmkeys\XKV@rm
```

Set the abbreviation style.

```
\ifcsdef{@glstrabbrv@current@\glscategorylabel}%  
{%
```

Warning should already have been issued.

```
\let\@glstr@orgwarndep\GlsXtrWarnDeprecatedAbbrStyle  
\let\GlsXtrWarnDeprecatedAbbrStyle\@gobbletwo  
\glstr@applyabbrvstyle{\csname @glstrabbrv@current@\glscategorylabel\endcsname}%  
\let\GlsXtrWarnDeprecatedAbbrStyle\@glstr@orgwarndep  
}%  
{%
```

If no style has been associated with this category, fallback on the style for the abbreviation category.

```
\glstr@applyabbrvstyle{\@glstrabbrv@current@abbreviation}%  
}%
```

Set the default long plural

```
\def\@gls@longpl{#4\glspluralsuffix}%
```

Has the markwords attribute been set?

```
\glsifcategoryattribute{\glscategorylabel}{markwords}{true}%  
{%  
  \@glstr@markwordseps\@gls@long{#4}%
```

Update \glslongtok.

```
\expandafter\glslongtok\expandafter{\@gls@long}%
```

Mark this entry as having a description with formatting.

```
\glsexclapplyinnerfmtfield{\the\glslabeltok}{desc}%  
}%  
{}%
```

Has the markshortwords attribute been set? (Not compatible with insertdots.)

```
\let\@glstr@if@markshortwords\@secondoftwo  
\glsifcategoryattribute{\glscategorylabel}{markshortwords}{true}%  
{%
```

Don't mark words until the default plural has been obtained.

```
\let\@glstr@if@markshortwords\@firstoftwo  
\def\@gls@short{#3}%  
}%  
{%
```

Has the insertdots attribute been set?

```
\glsifcategoryattribute{\glscategorylabel}{insertdots}{true}%
{%
  \glsxtr@insertdots\gls@short{#3}%

  \appto\gls@short{\@}%
}%
{\def\gls@short{#3}}%
}%
```

Has the aposplural attribute been set? (Not compatible with noshortplural.)

```
\glsifcategoryattribute{\glscategorylabel}{aposplural}{true}%
{%
  \expandafter\def\expandafter\gls@shortpl\expandafter{\gls@short
    '\abrvpluralsuffix}%
}%
{%
```

Has the noshortplural attribute been set?

```
\glsifcategoryattribute{\glscategorylabel}{noshortplural}{true}%
{%
  \let\gls@shortpl\gls@short
}%
{%
  \expandafter\def\expandafter\gls@shortpl\expandafter{\gls@short
    \abrvpluralsuffix}%
}%
}%
\@glsxtr@if@markshortwords
{%
  \expandafter\glsxtr@markwordseps\expandafter\gls@short
  \expandafter{\gls@short}%
}%
{}
```

Update \glsshorttok:

```
\expandafter\glsshorttok\expandafter{\gls@short}%
```

Hook for further customisation if required:

```
\glsxtrnewabrevpresetkeyhook{#1}{#2}{#3}%
```

Get the short and long plurals provided by user in optional argument to override defaults, if necessary. Save the default short plural.

```
\let\gls@default@shortpl\gls@shortpl
\let\XKV@rm\glsxtrabrv@rmkeys
\setrmkeys*\glsxtrabrvpl}%
```

Update \glskeylisttok so that it only has the remaining keys.

```
\expandafter\glskeylisttok\expandafter{\XKV@rm}%
```

Save in case required.

```
\let\gls@org@longpl\gls@longpl
\let\gls@org@shortpl\gls@shortpl
```

Has the markwords attribute been set?

```
\glsifcategoryattribute{\glscategorylabel}{markwords}{true}%
{%
  \expandafter\@glstr@markwordseps\expandafter\@gls@longpl\expandafter
  {\@gls@longpl}%
}%
{%}
```

Has the markshortwords attribute been set?

```
\@glstr@if@markshortwords
{%
  \expandafter\@glstr@markwordseps\expandafter\@gls@shortpl
  \expandafter{\@gls@shortpl}%
}%
{%}
```

Has the insertdots attribute been set?

```
\ifx\@gls@default@shortpl\@gls@shortpl
\else
  \glsifcategoryattribute{\glscategorylabel}{insertdots}{true}%
  {%
    \expandafter\@glstr@insertdots\expandafter\@gls@shortpl
    \expandafter{\@gls@shortpl}%
    \appto\@gls@shortpl{\@}%
  }%
  {%}
\fi
}%
```

Set the plural token registers so the values can be accessed by the abbreviation styles.

```
\expandafter\glsshortpltok\expandafter{\@gls@shortpl}%
\expandafter\glslongpltok\expandafter{\@gls@longpl}%
```

Hook for accessibility support (does nothing if glossaries-accsupp hasn't been loaded).

```
\@gls@setup@default@access
```

Do any extra setup provided by hook:

```
\newabbreviationhook
```

Define this entry:

```
\protected@edef\@do@newglossaryentry{%
  \noexpand\newglossaryentry{\the\glslabeltok}%
  {%
    type={\glstrabbrvtype},%
    category={\glscategorylabel},%
    short={\the\glsshorttok},%
    shortplural={\the\glsshortpltok},%
    long={\the\glslongtok},%
    longplural={\the\glslongpltok},%
    name={\the\glsshorttok},%
```

`\CustomAbbreviationFields,%`

Hook may override abbreviation style default settings.

`\ExtraCustomAbbreviationFields`

Any explicit fields set in the optional argument override all other settings, except for the ones that have already been processed.

`\the\glskeylisttok`

`}%`

`}%`

`\@do@newglossaryentry`

Obtain the type and add it to the list of abbreviations.

`\@glsxtr@addabbreviationlist{\glsentrytype{\the\glslabeltok}}%`

Exclude name, first, firstpl, text and plural fields from inner fmt as they include formatting commands. The description may also need adding, depending on the style.

`\glsexclapplyinnerfmtfield{\the\glslabeltok}{first}%`

`\glsexclapplyinnerfmtfield{\the\glslabeltok}{firstpl}%`

`\glsexclapplyinnerfmtfield{\the\glslabeltok}{text}%`

`\glsexclapplyinnerfmtfield{\the\glslabeltok}{plural}%`

`\glsexclapplyinnerfmtfield{\the\glslabeltok}{name}%`

`\GlsXtrPostNewAbbreviation`

`}`

`\glsxtrnewabbrevpresetkeyhook` Hook for extra stuff in `\newabbreviation`

`\newcommand*{\glsxtrnewabbrevpresetkeyhook}[3]{}`

`\GlsXtrPostNewAbbreviation` Hook used by abbreviation styles.

`\newcommand*{\GlsXtrPostNewAbbreviation}{}%`

`\newabbreviationhook` Hook for use with `\newabbreviation`.

`\newcommand*{\newabbreviationhook}{}%`

`\CustomAbbreviationFields`

`\newcommand*{\CustomAbbreviationFields}{}%`

`\glsxtrparen` For the parenthetical styles.

`\newcommand*{\glsxtrparen}[1]{%`

`\glsxtrgenentrytextfmt{(#1\glsxtrgenentrytextfmt{)}}%`

`\glsxtrfullformat` Full format without case change.

`\newcommand*{\glsxtrfullformat}[2]{%`

`\ifglsxtrininsertinside`

`\glsfirstlongfont{\glsaccessfmtlong{#2}{\glsxtrgenentrytextfmt}{#1}}%`

`\else`

`\glsfirstlongfont{\glsaccessfmtlong{}}{\glsxtrgenentrytextfmt}{#1}}%`

`\glsxtrgenentrytextfmt{#2}}%`

`\fi`

```

\glxstrfullsep{#1}%
\glxstrparen{\protect\glsfirstabbrvfont
  {\glsaccessfmtshort{}\glxstrgenentrytextfmt}{#1}}}%
}

```

`\Glsxtrfullformat` Full format with case change.

```

\newcommand*\Glsxtrfullformat}[2]{%
  \ifglxstrinsertinside
    \glsfirstlongfont{\Glsaccessfmtlong{#2}{\glxstrgenentrytextfmt}{#1}}%
  \else
    \glsfirstlongfont{\Glsaccessfmtlong{}\glxstrgenentrytextfmt}{#1}}%
    \glxstrgenentrytextfmt{#2}%
  \fi
  \glxstrfullsep{#1}%
  \glxstrparen{\protect\glsfirstabbrvfont
    {\glsaccessfmtshort{}\glxstrgenentrytextfmt}{#1}}}%
}
\glsmfuaddmap\glxstrfullformat\Glsxtrfullformat

```

`\GLSxtrfullformat` Full format with all caps.

```

\newcommand*\GLSxtrfullformat}[2]{%
  \ifglxstrinsertinside
    \glsfirstlongfont{\GLSaccessfmtlong{#2}{\glxstrgenentrytextfmt}{#1}}%
  \else
    \glsfirstlongfont{\GLSaccessfmtlong{}\glxstrgenentrytextfmt}{#1}}%
    \glsupercase{\glxstrgenentrytextfmt{#2}}%
  \fi
  \glxstrfullsep{#1}%
  \glxstrparen{\protect\glsfirstabbrvfont
    {\GLSaccessfmtshort{}\glxstrgenentrytextfmt}{#1}}}%
}
\glsmfublocker\GLSxtrfullformat

```

`\glxstrfullplformat` Plural full format without case change.

```

\newcommand*\glxstrfullplformat}[2]{%
  \ifglxstrinsertinside
    \glsfirstlongfont{\glsaccessfmtlongpl{#2}{\glxstrgenentrytextfmt}{#1}}%
  \else
    \glsfirstlongfont{\glsaccessfmtlongpl{}\glxstrgenentrytextfmt}{#1}}%
    \glxstrgenentrytextfmt{#2}%
  \fi
  \glxstrfullsep{#1}%
  \glxstrparen{\protect\glsfirstabbrvfont
    {\glsaccessfmtshortpl{}\glxstrgenentrytextfmt}{#1}}}%
}

```

`\Glsxtrfullplformat` Plural full format with case change.

```

\newcommand*\Glsxtrfullplformat}[2]{%
  \ifglxstrinsertinside

```

```

\glsfirstlongfont{\Glsaccessfmtlongpl{#2}{\glsxtrgenentrytextfmt}{#1}}%
\else
\glsfirstlongfont{\Glsaccessfmtlongpl{}{\glsxtrgenentrytextfmt}{#1}}%
\glsxtrgenentrytextfmt{#2}%
\fi
\glsxtrfullsep{#1}%
\glsxtrparen{\protect\glsfirstabbrvfont
  {\glsaccessfmtshortpl{}{\glsxtrgenentrytextfmt}{#1}}}%
}
\glsmfuaddmap{\glsxtrfullplformat}{\Glsxtrfullplformat}

\GLSxtrfullplformat Full format with all caps.
\newcommand*{\GLSxtrfullplformat}[2]{%
  \ifglsxtrininsertinside
  \glsfirstlongfont{\GLSaccessfmtlongpl{#2}{\glsxtrgenentrytextfmt}{#1}}%
  \else
  \glsfirstlongfont{\GLSaccessfmtlongpl{}{\glsxtrgenentrytextfmt}{#1}}%
  \glsuppercase{\glsxtrgenentrytextfmt{#2}}%
  \fi
  \glsxtrfullsep{#1}%
  \glsxtrparen{\protect\glsfirstabbrvfont
    {\GLSaccessfmtshortpl{}{\glsxtrgenentrytextfmt}{#1}}}%
  }
\glsmfublocker{\GLSxtrfullplformat}

\GLSxtr@fullformat@fallback Fallback for custom styles that don't implement all caps version.
\newcommand*{\GLSxtr@fullformat@fallback}[2]{%
  \glsuppercase{\glsxtrfullformat{##1}{##2}}%
}%

\GLSxtr@fullplformat@fallback Fallback for custom styles that don't implement all caps version.
\newcommand*{\GLSxtr@fullplformat@fallback}[2]{%
  \glsuppercase{\glsxtrfullplformat{##1}{##2}}%
}%

\glsxtrfullsep Separator used by full format is a space by default. The argument is the entry's
label.
\newcommand*{\glsxtrfullsep}[1]{\glsxtrgenentrytextfmt{ }}

In-line formats in case first use isn't compatible with \glsentryfull (for
example, first use suppresses the long form or uses a footnote).

\glsxtrinlinefullformat Full format without case change.
\newcommand*{\glsxtrinlinefullformat}{\glsxtrfullformat}

\Glsxtrinlinefullformat Full format with case change.
\newcommand*{\Glsxtrinlinefullformat}{\Glsxtrfullformat}

\GLSxtrinlinefullformat Full format with all caps.
\newcommand*{\GLSxtrinlinefullformat}{\GLSxtrfullformat}

```

`\glstrfullplformat` Plural full format without case change.

```
\newcommand*{\glstrinlinefullplformat}{\glstrfullplformat}
```

`\Glsxtrinlinefullplformat` Plural full format with case change.

```
\newcommand*{\Glsxtrinlinefullplformat}{\Glsxtrfullplformat}
```

`\GLSxtrinlinefullplformat` Full format with all caps.

```
\newcommand*{\GLSxtrinlinefullplformat}{\GLSxtrfullplformat}
```

Redefine `\glentryfull` etc to use the inline format. Since these commands are supposed to be expandable, they can only use the currently applied style. If there are mixed styles, you'll need to use the `\glstrfull` set of commands instead. If expandable sentence case is required, use `\MFUsentencecase` on the non-case-change version.

`\glentryfull`

```
\renewcommand*{\glentryfull}[1]{\glxtrinlinefullformat{#1}{}}
```

`\Glsentryfull`

```
\renewcommand*{\Glsentryfull}[1]{\Glsxtrinlinefullformat{#1}{}}
\glsmfuaddmap{\glentryfull}{\Glsentryfull}
```

`\glentryfullpl`

```
\renewcommand*{\glentryfullpl}[1]{\glxtrinlinefullplformat{#1}{}}
```

`\Glsentryfullpl`

```
\renewcommand*{\Glsentryfullpl}[1]{\Glsxtrinlinefullplformat{#1}{}}
\glsmfuaddmap{\glentryfullpl}{\Glsentryfullpl}
```

`\glsfirstabbrvfont` Font changing command used for the abbreviation on first use or in the full format.

```
\newcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvdefaultfont{#1}}
```

`\glsfirstinnerfmtabbrvfont` Include inner formatting command.

```
\newrobustcmd*{\glsfirstinnerfmtabbrvfont}[1]{%
\glsfirstabbrvfont{\glstrgenentrytextfmt{#1}}%
}
```

`\glsfirstxpabbrvfont` Expand to appropriate formatting command.

```
\newcommand*{\glsfirstxpabbrvfont}[2]{%
\glsifcategoryattributetrue{#2}{markshortwords}%
{\protect\glsfirstabbrvfont{#1}}%
{\glsfirstinnerfmtabbrvfont{#1}}%
}
```

`\glsfirstabbrvdefaultfont` Font changing command used for the abbreviation on first use or in the full format.

```
\newcommand*{\glsfirstabbrvdefaultfont}[1]{\glsabbrvdefaultfont{#1}}
```

`\glsabbrvfont` Font changing command used for the abbreviation on subsequent use. This is redefined by the abbreviation styles, as appropriate.

```
\newcommand*{\glsabbrvfont}[1]{\glsabbrvdefaultfont{#1}}
```

`\glsinnerfmtabbrvfont` Include inner formatting command.

```
\newrobustcmd*{\glsinnerfmtabbrvfont}[1]{%
  \glsabbrvfont{\glsxtrgenentrytextfmt{#1}}%
}
```

`\glxpabbrvfont` Expand to appropriate formatting command.

```
\newcommand*{\glxpabbrvfont}[2]{%
  \glsifcategoryattributetrue{#2}{markshortwords}%
  {\protect\glsabbrvfont{#1}}%
  {\glsinnerfmtabbrvfont{#1}}%
}
```

`\glsabbrvdefaultfont`

```
\newcommand*{\glsabbrvdefaultfont}[1]{#1}
```

`\glslongfont` Font changing command used for the long form in commands like `\glsxtrlong`.

```
\newcommand*{\glslongfont}[1]{\glslongdefaultfont{#1}}
```

`\glsinnerfmtlongfont` Include inner formatting command.

```
\newrobustcmd*{\glsinnerfmtlongfont}[1]{%
  \glslongfont{\glsxtrgenentrytextfmt{#1}}%
}
```

`\glxplongfont` Expand to appropriate formatting command.

```
\newcommand*{\glxplongfont}[2]{%
  \glsifcategoryattributetrue{#2}{markwords}%
  {\protect\glslongfont{#1}}%
  {\glsinnerfmtlongfont{#1}}%
}
```

`\glslongdefaultfont` Default font changing command used for the long form in commands like `\glsxtrlong`.

```
\newcommand*{\glslongdefaultfont}[1]{#1}
```

`\glsfirstlongfont` Font changing command used for the long form on first use or in the full format.

```
\newcommand*{\glsfirstlongfont}[1]{\glslongfont{#1}}
```

`\glsfirstinnerfmtlongfont` Include inner formatting command.

```
\newrobustcmd*{\glsfirstinnerfmtlongfont}[1]{%
  \glsfirstlongfont{\glsxtrgenentrytextfmt{#1}}%
}
```


`\glsfirstxplongfont` Expand to appropriate formatting command.

```
\newcommand*{\glsfirstxplongfont}[2]{%
  \glsifcategoryattributetrue{#2}{markwords}%
  {\protect\glsfirstlongfont{#1}}%
  {\glsfirstinnerfmtlongfont{#1}}%
}
```

`\glsfirstlongdefaultfont`

```
\newcommand*{\glsfirstlongdefaultfont}[1]{\glslongdefaultfont{#1}}
```

`\glsxtrabbrvpluralsuffix` Default plural suffix. Allow an alternative default suffix for abbreviations.

```
\newcommand*{\glsxtrabbrvpluralsuffix}{\glsacrpluralsuffix}
```

`\abbrvpluralsuffix` Default plural suffix.

```
\newcommand*{\abbrvpluralsuffix}{\glsxtrabbrvpluralsuffix}
```

`\glsxtrrevert` Provide a way to counteract the abbreviation font.

```
\newcommand*{\glsxtrrevert}[1]{\glsxtrdefaultrevert{#1}}%
```

`\glsxtrdefaultrevert` The default simply does its argument.

```
\newcommand*{\glsxtrdefaultrevert}[1]{#1}%
```

`\glsxtrfull` Full form (no case-change).

```
\newrobustcmd*{\glsxtrfull}{\@gls@hyp@opt\@ns@glsxtrfull}
\newcommand*{\ns@glsxtrfull}[2][]{%
  \new@ifnextchar[{\@glsxtr@full{#1}{#2}}%
  {\@glsxtr@full{#1}{#2}[]}%
}
```

`\@glsxtr@full` Low-level macro:

```
\def\@glsxtr@full#1#2[#3]{%
  \def\glsxtrcurrentfield{#3}%

```

If the `record` option has been used, the information needs to be written to the aux file regardless of whether the entry exists (unless indexing has been switched off).

```
\@glsxtr@record{#1}{#2}{\glslink}%
\glsdoifexists{#2}%
{%
  \glssetabbrvfmt{\glscategory{#2}}%
  \let\do@gls@link@checkfirsthyper\@gls@link@nocheckfirsthyper
  \let\glsxtrifwasglslike\@secondoftwo
  \let\glsifplural\@secondoftwo
  \let\glsapscase\@firstofthree
  \glsxtrfullsaveinsert{#2}{#3}%
}
```

The `innertextformat` support should be provided within the inline command.

```
\def\glscustomtext{\glsxtrinlinefullformat{#2}{#3}}%
```

What should `\glxtrifwasfirstuse` be set to here? Where the inline and display full forms are the same, this is essentially emulating first use, to it make sense for the postlink hook to pretend it was a first use instance. It makes less sense if the inline and display forms are different. Provide a hook to make it easier to reconfigure.

```

\glxtrsetupfulldefs
\@gls@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
}%
\glspostlinkhook
}

```

`\glxtrsetupfulldefs`

```

\newcommand*{\glxtrsetupfulldefs}{%
\let\glxtrifwasfirstuse\@firstoftwo
}

```

`\Glsxtrfull` Full form (first letter uppercase).

```

\newrobustcmd*{\Glsxtrfull}{\@gls@hyp@opt\@ns@Glsxtrfull}
\newcommand*\@ns@Glsxtrfull[2][]{%
\new@ifnextchar[{\@Glsxtr@full{#1}{#2}}{%
{\@Glsxtr@full{#1}{#2}[]}%
}
\glsmfuaddmap{\glxtrfull}{\Glsxtrfull}

```

`\@Glsxtr@full` Low-level macro:

```

\def\@Glsxtr@full#1#2[#3]{%
\def\glxtrcurrentfield{%
\glsdoifexists{#2}%
{%
\glsssetabbrvfmt{\glscategory{#2}}%
\let\do@gls@link@checkfirsthyper\@gls@link@nocheckfirsthyper
\let\glxtrifwasglslike\@secondoftwo
\let\glsifplural\@secondoftwo
\let\glscapscase\@secondofthree
\glxtrfullsaveinsert{#2}{#3}%

```

The `innertextformat` support should be provided within the inline command.

```

\def\glscustomtext{\Glsxtrinlinefullformat{#2}{#3}}%
\glxtrsetupfulldefs
\@gls@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
}%
\glspostlinkhook
}

```

`\GLSxtrfull` Full form (all uppercase).

```

\newrobustcmd*{\GLSxtrfull}{\@gls@hyp@opt\@ns@GLSxtrfull}
\newcommand*\@ns@GLSxtrfull[2][]{%
\new@ifnextchar[{\@GLSxtr@full{#1}{#2}}{%
{\@GLSxtr@full{#1}{#2}[]}%
}

```

`\@GLSxtr@full` Low-level macro:

```
\def\@GLSxtr@full#1#2[#3]{%
  \def\glstrcurrentfield{%
    \glsoifexists{#2}%
    {%
      \glsetabbrvfmt{\glscategory{#2}}%
      \let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
      \let\glstrifwasglslike\@secondoftwo
      \let\gl@ifplural\@secondoftwo
      \let\glscapscase\@thirdofthree
      \glstrfullsaveinsert{#2}{#3}%
    }
  }
```

The `innertextformat` support should be provided within the inline command.

```
\def\glscustomtext{\GLSxtrinlinefullformat{#2}{#3}}%
\glstrsetupfulldefs
\@gl@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
}%
\glspostlinkhook
}
\glsmfublocker{\GLSxtrfull}
```

`\glstrfullpl` Plural full form (no case-change).

```
\newrobustcmd*{\glstrfullpl}{\@gl@hyp@opt\ns@glstrfullpl}
\newcommand*{\ns@glstrfullpl[2] []}{%
  \new@ifnextchar[{\@glstr@fullpl{#1}{#2}}%
    {\@glstr@fullpl{#1}{#2} []}%
}
```

`\@glstr@fullpl` Low-level macro:

```
\def\@glstr@fullpl#1#2[#3]{%
  \def\glstrcurrentfield{%
```

If the `record` option has been used, the information needs to be written to the aux file regardless of whether the entry exists (unless indexing has been switched off).

```
\@glstr@record{#1}{#2}{\gl@link}%
\glsoifexists{#2}%
{%
  \glsetabbrvfmt{\glscategory{#2}}%
  \let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
  \let\glstrifwasglslike\@secondoftwo
  \let\gl@ifplural\@firstoftwo
  \let\glscapscase\@firstofthree
  \glstrfullsaveinsert{#2}{#3}%
}
```

The `innertextformat` support should be provided within the inline command.

```
\def\glscustomtext{\glxtrinlinefullplformat{#2}{#3}}%
\glstrsetupfulldefs
\@gl@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
}%
```

```

\glspostlinkhook
}

```

`\Glsxtrfullpl` Plural full form (first letter uppercase).

```

\newrobustcmd*{\Glsxtrfullpl}{\@gls@hyp@opt\ns@Glsxtrfullpl}
\newcommand*\ns@Glsxtrfullpl[2][\%
  \new@ifnextchar[\@Glsxtr@fullpl{#1}{#2}]{\%
    {\@Glsxtr@fullpl{#1}{#2}}{}}{\%
}
\glsmfuaddmap{\glxtrfullpl}{\Glsxtrfullpl}

```

`\@Glsxtr@fullpl` Low-level macro:

```

\def\@Glsxtr@fullpl#1#2[#3]{\%
  \def\glxtrcurrentfield{\%

```

If the `record` option has been used, the information needs to be written to the aux file regardless of whether the entry exists (unless indexing has been switched off).

```

\@glxtr@record{#1}{#2}{\glslink}{\%
\glsdofexists{#2}{\%
{\%
  \glsssetabbrvfmt{\glscategory{#2}}{\%
  \let\do@glslink@checkfirsthyper\@glslink@nocheckfirsthyper
  \let\glxtrifwasglslike\@secondoftwo
  \let\glslifplural\@firstoftwo
  \let\glscapscase\@secondofthree
  \glxtrfullsaveinsert{#2}{#3}{\%

```

The `innertextformat` support should be provided within the inline command.

```

\def\glscustomtext{\Glsxtrinlinefullplformat{#2}{#3}}{\%
\glxtrsetupfulldefs
\@glslink[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}{\%
}%
\glspostlinkhook
}

```

`\GLSxtrfullpl` Plural full form (all upper case).

```

\newrobustcmd*{\GLSxtrfullpl}{\@gls@hyp@opt\ns@GLSxtrfullpl}
\newcommand*\ns@GLSxtrfullpl[2][\%
  \new@ifnextchar[\@GLSxtr@fullpl{#1}{#2}]{\%
    {\@GLSxtr@fullpl{#1}{#2}}{}}{\%
}
\glsmfublocker{\GLSxtrfullpl}

```

`\@GLSxtr@fullpl` Low-level macro:

```

\def\@GLSxtr@fullpl#1#2[#3]{\%
  \def\glxtrcurrentfield{\%

```

If the `record` option has been used, the information needs to be written to the aux file regardless of whether the entry exists (unless indexing has been switched off).

```

\@glxtr@record{#1}{#2}{glslink}%
\glsdoifexists{#2}%
{%
  \let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
  \let\glxtrifwasglslike\@secondoftwo
  \let\glsifplural\@firstoftwo
  \let\glscapscase\@thirdofthree
  \glxtrfullsaveinsert{#2}{#3}%

```

The innertextformat support should be provided within the inline command.

```

\def\glscustomtext{%
  \GLSxtrinlinefullplformat{#2}{#3}}%
\glxtrsetupfulldefs
\@gl@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
}%
\glspostlinkhook
}

```

The short and long forms work in a similar way to acronyms.

`\glxtrshort`

```

\newrobustcmd*{\glxtrshort}{\@gl@hyp@opt\@ns@glxtrshort}

```

Define the un-starred form. Need to determine if there is a final optional argument

```

\newcommand*{\ns@glxtrshort}[2][{}]{%
  \new@ifnextchar[{\@glxtrshort{#1}{#2}}{\@glxtrshort{#1}{#2}[{}]}%
}

```

Read in the final optional argument:

```

\def\@glxtrshort#1#2[#3]{%
  \def\glxtrcurrentfield{short}%

```

If the record option has been used, the information needs to be written to the aux file regardless of whether the entry exists (unless indexing has been switched off).

```

\@glxtr@record{#1}{#2}{glslink}%
\glsdoifexists{#2}%
{%

```

Need to make sure `\glsabbrvfont` is set correctly.

```

\glsssetabbrvfmt{\glscategory{#2}}%
\let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
\let\glxtrifwasglslike\@secondoftwo
\let\glxtrifwasfirsttuse\@secondoftwo
\let\glsifplural\@secondoftwo
\let\glscapscase\@firstofthree
\glxtrsaveinsert{#2}{#3}%
\def\glscustomtext{%
  \glxtrshortformat{#2}{#3}{\glsabbrvfont}%
}%
\@gl@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%

```

```

    }%
    \glspostlinkhook
}

\Glsxtrshort
  \newrobustcmd*{\Glsxtrshort}{\@gls@hyp@opt\ns@Glsxtrshort}
  \glsmfuaddmap{\glxtrshort}{\Glsxtrshort}
Define the un-starred form. Need to determine if there is a final optional argu-
ment
  \newcommand*{\ns@Glsxtrshort}[2][{}]{%
    \new@ifnextchar[{\@Glsxtrshort{#1}{#2}}{\@Glsxtrshort{#1}{#2}[]}%
  }
Read in the final optional argument:
  \def\@Glsxtrshort#1#2[#3]{%
    \def\glxtrcurrentfield{short}%
If the record option has been used, the information needs to be written to the
aux file regardless of whether the entry exists (unless indexing has been switched
off).
    \@glxtr@record{#1}{#2}{\glslink}%
    \glsoifexists{#2}%
    {%
      \glsssetabbrvfmt{\glscategory{#2}}%
      \let\do@gls@link@checkfirsthyper\@gls@link@nocheckfirsthyper
      \let\glxtrifwasglslike\@secondoftwo
      \let\glxtrifwasfirstuse\@secondoftwo
      \let\glsifplural\@secondoftwo
      \let\glscapscase\@secondofthree
      \glxtrsaveinsert{#2}{#3}%
      \def\glscustomtext{%
        \Glsxtrshortformat{#2}{#3}{\glsabbrvfont}%
      }%
      \@gls@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
    }%
    \glspostlinkhook
  }

\GLSxtrshort
  \newrobustcmd*{\GLSxtrshort}{\@gls@hyp@opt\ns@GLSxtrshort}
  \glsmfublocker{\GLSxtrshort}
Define the un-starred form. Need to determine if there is a final optional argu-
ment
  \newcommand*{\ns@GLSxtrshort}[2][{}]{%
    \new@ifnextchar[{\@GLSxtrshort{#1}{#2}}{\@GLSxtrshort{#1}{#2}[]}%
  }
Read in the final optional argument:
  \def\@GLSxtrshort#1#2[#3]{%
    \def\glxtrcurrentfield{short}%

```

If the record option has been used, the information needs to be written to the aux file regardless of whether the entry exists (unless indexing has been switched off).

```
\@glxtr@record{#1}{#2}{glslink}%
\glsdoifexists{#2}%
{%
  \glsssetabbrvfmt{\glscategory{#2}}%
  \let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
  \let\glxtrifwasglslike\@secondoftwo
  \let\glxtrifwasfirstuse\@secondoftwo
  \let\glsifplural\@secondoftwo
  \let\glscapscase\@thirdofthree
  \glxtrsaveinsert{#2}{#3}%
  \def\glscustomtext{\GLSxtrshortformat{#2}{#3}{\glsabbrvfont}}%
  \@gl@link{#1}{#2}{\csname gls@\glstype @entryfmt\endcsname}%
}%
\glspostlinkhook
}
```

`\glxtrsetlongfirstuse` Assigns `\glxtrifwasfirstuse` for the long commands. The argument is the entry label. This now makes commands such as `\glxtrlong` simulate first use.

```
\newcommand{\glxtrsetlongfirstuse}[1]{%
  \let\glxtrifwasfirstuse\@firstoftwo
}
```

`\glxtrlong`

```
\newrobustcmd*{\glxtrlong}{\@gl@hyp@opt\@ns@glxtrlong}
```

Define the un-starred form. Need to determine if there is a final optional argument

```
\newcommand*{\ns@glxtrlong}[2][]{%
  \new@ifnextchar[{\@glxtrlong{#1}{#2}}{\@glxtrlong{#1}{#2} []}%
}
```

Read in the final optional argument:

```
\def\@glxtrlong#1#2[#3]{%
  \def\glxtrcurrentfield{long}%
}
```

If the record option has been used, the information needs to be written to the aux file regardless of whether the entry exists (unless indexing has been switched off).

```
\@glxtr@record{#1}{#2}{glslink}%
\glsdoifexists{#2}%
{%
  \let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
  \let\glxtrifwasglslike\@secondoftwo
  \let\glsifplural\@secondoftwo
  \let\glscapscase\@firstofthree
  \glxtrsetlongfirstuse{#2}%
}
```

```

\glxtrsaveinsert{#2}{#3}%
\def\glscustomtext{%
  \glxtrlongformat{#2}{#3}{\glslongfont}%
}%
\@gls@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
}%
\glspostlinkhook
}

```

\Glsxtrlong

```

\newrobustcmd*{\Glsxtrlong}{\@gls@hyp@opt\ns@Glsxtrlong}
\glsmfuaddmap{\glxtrlong}{\Glsxtrlong}

```

Define the un-starred form. Need to determine if there is a final optional argument

```

\newcommand*{\ns@Glsxtrlong}[2] [] {%
  \new@ifnextchar[{\@Glsxtrlong{#1}{#2}}{\@Glsxtrlong{#1}{#2} []}%
}

```

Read in the final optional argument:

```

\def\@Glsxtrlong#1#2[#3] {%
  \def\glxtrcurrentfield{long}%

```

If the record option has been used, the information needs to be written to the aux file regardless of whether the entry exists (unless indexing has been switched off).

```

\@glxtr@record{#1}{#2}{\glslink}%
\glsoifexists{#2}%
{%
  \let\do@gls@link@checkfirsthyper\@gls@link@nocheckfirsthyper
  \let\glxtrifwasglslike\@secondoftwo
  \let\glsifplural\@secondoftwo
  \let\glscapscase\@secondofthree
  \glxtrsetlongfirstuse{#2}%
  \glxtrsaveinsert{#2}{#3}%
  \def\glscustomtext{%
    \Glsxtrlongformat{#2}{#3}{\glslongfont}%
  }%
  \@gls@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
}%
\glspostlinkhook
}

```

\GLSxtrlong

```

\newrobustcmd*{\GLSxtrlong}{\@gls@hyp@opt\ns@GLSxtrlong}
\glsmfublocker{\GLSxtrlong}

```

Define the un-starred form. Need to determine if there is a final optional argument

```

\newcommand*{\ns@GLSxtrlong}[2] [] {%
  \new@ifnextchar[{\@GLSxtrlong{#1}{#2}}{\@GLSxtrlong{#1}{#2} []}%
}

```


}

Read in the final optional argument:

```
\def\@GLSxtrlong#1#2[#3]{%
  \def\glxtrcurrentfield{long}%
```

If the `record` option has been used, the information needs to be written to the aux file regardless of whether the entry exists (unless indexing has been switched off).

```
\@glxtr@record{#1}{#2}{glslink}%
\glsoifexists{#2}%
{%
  \let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
  \let\glxtrifwasglslake\@secondoftwo
  \let\gl@ifplural\@secondoftwo
  \let\glscapscase\@thirdofthree
  \glxtrsetlongfirstuse{#2}%
  \glxtrsinsert{#2}{#3}%
  \def\glscustomtext{%
    \GLSxtrlongformat{#2}{#3}{\glslongfont}%
  }%
  \@gl@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
}%
\glspostlinkhook
}
```

Plural short forms:

`\glxtrshortpl`

```
\newrobustcmd*{\glxtrshortpl}{\@gl@hyp@opt\@ns@glxtrshortpl}
```

Define the un-starred form. Need to determine if there is a final optional argument

```
\newcommand*{\@ns@glxtrshortpl}[2][ ]{%
  \new@ifnextchar[{\@glxtrshortpl{#1}{#2}}{\@glxtrshortpl{#1}{#2}[ ]}%
}
```

Read in the final optional argument:

```
\def\@glxtrshortpl#1#2[#3]{%
  \def\glxtrcurrentfield{short}%
```

If the `record` option has been used, the information needs to be written to the aux file regardless of whether the entry exists (unless indexing has been switched off).

```
\@glxtr@record{#1}{#2}{glslink}%
\glsoifexists{#2}%
{%
  \glsetabbrvfmt{\glscategory{#2}}%
  \let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
  \let\glxtrifwasglslake\@secondoftwo
  \let\glxtrifwasfirstuse\@secondoftwo
```

```

\let\glsifplural\@firstoftwo
\let\glscapscase\@firstofthree
\glxtrsaveinsert{#2}{#3}%
\def\glscustomtext{%
  \glxtrshortplformat{#2}{#3}{\glsabbrvfont}%
}%
\@gls@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
}%
\glspostlinkhook
}

```

\Glsxtrshortpl

```

\newrobustcmd*{\Glsxtrshortpl}{\@gls@hyp@opt\@ns@Glsxtrshortpl}
\glsmfuaddmap{\glxtrshortpl}{\Glsxtrshortpl}

```

Define the un-starred form. Need to determine if there is a final optional argument

```

\newcommand*{\ns@Glsxtrshortpl}[2][{}]{%
  \new@ifnextchar[{\@Glsxtrshortpl{#1}{#2}}{\@Glsxtrshortpl{#1}{#2}[]}%
}

```

Read in the final optional argument:

```

\def\@Glsxtrshortpl#1#2[#3]{%
  \def\glxtrcurrentfield{short}%

```

If the record option has been used, the information needs to be written to the aux file regardless of whether the entry exists (unless indexing has been switched off).

```

\@glxtr@record{#1}{#2}{\glslink}%
\glsdoifexists{#2}%
{%
  \glssetabbrvfmt{\glscategory{#2}}%
  \let\do@gls@link@checkfirsthyper\@gls@link@nocheckfirsthyper
  \let\glxtrifwasglslike\@secondoftwo
  \let\glxtrifwasfirsttuse\@secondoftwo
  \let\glsifplural\@firstoftwo
  \let\glscapscase\@secondofthree
  \glxtrsaveinsert{#2}{#3}%
  \def\glscustomtext{%
    \Glsxtrshortplformat{#2}{#3}{\glsabbrvfont}%
  }%
  \@gls@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
}%
\glspostlinkhook
}

```

\GLSxtrshortpl

```

\newrobustcmd*{\GLSxtrshortpl}{\@gls@hyp@opt\@ns@GLSxtrshortpl}
\glsmfublocker{\GLSxtrshortpl}

```

Define the un-starred form. Need to determine if there is a final optional argument

```
\newcommand*{\ns@GLSxtrshortpl}[2][{}]{%
  \new@ifnextchar[{\@GLSxtrshortpl{#1}{#2}}{\@GLSxtrshortpl{#1}{#2}[{}]}%
}
```

Read in the final optional argument:

```
\def\@GLSxtrshortpl#1#2[#3]{%
  \def\glxstrcurrentfield{short}%
```

If the `record` option has been used, the information needs to be written to the aux file regardless of whether the entry exists (unless indexing has been switched off).

```
\@glxstr@record{#1}{#2}{glslink}%
\glstoifexists{#2}%
{%
  \glsssetabbrvfmt{\glscategory{#2}}%
  \let\do@glsl@link@checkfirsthyper\@glsl@link@nocheckfirsthyper
  \let\glxstrifwasglsl\@secondoftwo
  \let\glxstrifwasfirstuse\@secondoftwo
  \let\glslifplural\@firstoftwo
  \let\glscaps\@thirdoftwo
  \glxstrsaveinsert{#2}{#3}%
  \def\glscustomtext{%
    \GLSxtrshortplformat{#2}{#3}{\glssabbrvfont}%
  }%
  \@glsl@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
}%
\glspostlinkhook
}
```

Plural long forms:

`\glsxtrlongpl`

```
\newrobustcmd*{\glsxtrlongpl}{\@glsl@hyp@opt\ns@glsxtrlongpl}
```

Define the un-starred form. Need to determine if there is a final optional argument

```
\newcommand*{\ns@glsxtrlongpl}[2][{}]{%
  \new@ifnextchar[{\@glsxtrlongpl{#1}{#2}}{\@glsxtrlongpl{#1}{#2}[{}]}%
}
```

Read in the final optional argument:

```
\def\@glsxtrlongpl#1#2[#3]{%
  \def\glxstrcurrentfield{long}%
```

If the `record` option has been used, the information needs to be written to the aux file regardless of whether the entry exists (unless indexing has been switched off).

```
\@glxstr@record{#1}{#2}{glslink}%
\glstoifexists{#2}%
```

```

    {%
      \let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
      \let\glxtrifwasglslike\@secondoftwo
      \let\glsifplural\@firstoftwo
      \let\glscapscase\@firstofthree
      \glxtrsetlongfirstuse{#2}%
      \glxtrsaveinsert{#2}{#3}%
      \def\glscustomtext{%
        \glxtrlongplformat{#2}{#3}{\glslongfont}%
      }%
      \@gl@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
    }%
    \glspostlinkhook
  }

\Glsxtrlongpl

\newrobustcmd*{\Glsxtrlongpl}{\@gl@hyp@opt\@ns@Glsxtrlongpl}
\glsmfuaddmap{\Glsxtrlongpl}{\Glsxtrlongpl}

Define the un-starred form. Need to determine if there is a final optional argument
\newcommand*{\ns@Glsxtrlongpl}[2][{}]{%
  \new@ifnextchar[{\@Glsxtrlongpl{#1}{#2}}{\@Glsxtrlongpl{#1}{#2}[]}%
}

Read in the final optional argument:
\def\@Glsxtrlongpl#1#2[#3]{%
  \def\glxtrcurrentfield{long}%

If the record option has been used, the information needs to be written to the
aux file regardless of whether the entry exists (unless indexing has been switched
off).
  \@glxtr@record{#1}{#2}{\glslink}%
  \glsoifexists{#2}%
  {%
    \let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
    \let\glxtrifwasglslike\@secondoftwo
    \let\glsifplural\@firstoftwo
    \let\glscapscase\@secondofthree
    \glxtrsetlongfirstuse{#2}%
    \glxtrsaveinsert{#2}{#3}%
    \def\glscustomtext{%
      \Glsxtrlongplformat{#2}{#3}{\glslongfont}%
    }%
    \@gl@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
  }%
  \glspostlinkhook
}

\GLSxtrlongpl

```

```
\newrobustcmd*{\GLSxtrlongpl}{\@gls@hyp@opt\@ns@GLSxtrlongpl}
\glsmfublocker{\GLSxtrlongpl}
```

Define the un-starred form. Need to determine if there is a final optional argument

```
\newcommand*{\ns@GLSxtrlongpl}[2][\%]
  \new@ifnextchar[{\@GLSxtrlongpl{#1}{#2}}{\@GLSxtrlongpl{#1}{#2}[]}%
}
```

Read in the final optional argument:

```
\def\@GLSxtrlongpl#1#2[#3]{%
  \def\glstrcurrentfield{long}%
```

If the `record` option has been used, the information needs to be written to the aux file regardless of whether the entry exists (unless indexing has been switched off).

```
\@glstr@record{#1}{#2}{\glslink}%
\glsoifexists{#2}%
{%
  \let\do@gls@link@checkfirsthyper\@gls@link@nocheckfirsthyper
  \let\glstrifwasglslike\@secondoftwo
  \let\glisifplural\@firstoftwo
  \let\glscapscase\@thirdofthree
  \glstrsetlongfirstuse{#2}%
  \glstrsaveinsert{#2}{#3}%
  \def\glscustomtext{%
    \GLSxtrlongplformat{#2}{#3}{\glslongfont}%
  }%
  \@gls@link{#1}{#2}{\csname gls@\glstype @entryfmt\endcsname}%
}%
\glspostlinkhook
}
```

`\glsetabbrvfmt` Set the current format for the given category (or the abbreviation category if unset).

```
\newcommand*{\glsetabbrvfmt}[1]{%
  \ifcsdef{@glsabbrv@current@#1}%
  {\glstr@applyabbrvfmt{\csname @glsabbrv@current@#1\endcsname}}%
  {\glstr@applyabbrvfmt{\@glsabbrv@current@abbreviation}}%
}
```

`\gluseabbrvfont` Provide a way to use the abbreviation font for a given category for arbitrary text.

```
\newrobustcmd*{\gluseabbrvfont}[2][{\glsetabbrvfmt{#2}\glabbrvfont{#1}}]
```

`\gluselongfont` Provide a way to use the long font for a given category for arbitrary text.

```
\newrobustcmd*{\gluselongfont}[2][{\glsetabbrvfmt{#2}\glslongfont{#1}}]
```

`\glstrgenabbrvfmt` Similar to `\glsgenacfmt`, but for abbreviations. The expansion is to ensure that `\glsinsert` is expanded before being passed to `\glsfmtfield` etc in the event that an inner command is being used (which typically signifies a complex formatting command such as those provided by `soul`).

```
\newcommand*{\glstrgenabbrvfmt}{%
  \ifdefempty\glscustomtext
  {%
    \ifglssused\glslabel
    {%
```

Subsequent use:

```
\glssifplural
{%
```

Subsequent plural form:

```
\glscapscase
{%
```

Subsequent plural form, don't adjust case:

```
\expandafter\glstrsubsequentplfmt\expandafter\glslabel
\expandafter{\glsinsert}%
}%
{%
```

Subsequent plural form, make first letter upper case:

```
\expandafter\Glsxtrsubsequentplfmt\expandafter\glslabel
\expandafter{\glsinsert}%
}%
{%
```

Subsequent plural form, all caps:

```
\expandafter\GLSxtrsubsequentplfmt\expandafter\glslabel
\expandafter{\glsinsert}%
}%
}%
{%
```

Subsequent singular form

```
\glscapscase
{%
```

Subsequent singular form, don't adjust case:

```
\expandafter\glstrsubsequentfmt\expandafter\glslabel
\expandafter{\glsinsert}%
}%
{%
```

Subsequent singular form, make first letter upper case:

```
\expandafter\Glsxtrsubsequentfmt\expandafter
\glslabel\expandafter{\glsinsert}%
}%
{%
```

Subsequent singular form, all caps:

```

\expandafter\GLSxtrsubsequentfmt\expandafter
\glslabel\expandafter{\glsinsert}%
}%
}%
}%
{%

```

First use:

```

\glsifplural
{%

```

First use plural form:

```

\glscapscase
{%

```

First use plural form, don't adjust case:

```

\expandafter\glxtrfullplformat\expandafter\glslabel
\expandafter{\glsinsert}%
}%
{%

```

First use plural form, make first letter upper case:

```

\expandafter\Glsxtrfullplformat\expandafter\glslabel
\expandafter{\glsinsert}%
}%
{%

```

First use plural form, all caps:

```

\expandafter\GLSxtrfullplformat\expandafter\glslabel
\expandafter{\glsinsert}%
}%
}%
{%

```

First use singular form

```

\glscapscase
{%

```

First use singular form, don't adjust case:

```

\expandafter\glxtrfullformat\expandafter\glslabel
\expandafter{\glsinsert}%
}%
{%

```

First use singular form, make first letter upper case:

```

\expandafter\Glsxtrfullformat\expandafter\glslabel
\expandafter{\glsinsert}%
}%
{%

```

First use singular form, all caps:

```

\expandafter\GLSxtrfullformat\expandafter\glslabel

```

```

        \expandafter{\glsinsert}%
      }%
    }%
  }%
}%
{%

```

Custom text provided in `\glsdisp`. (The insert is most likely to be empty at this point.) Any inner formatting can be supplied with the custom text.

```

    \glscustomtext
  }%
}

```

`\glsxtrsubsequentfmt` Subsequent use format (singular no case change).

```

\newcommand*{\glsxtrsubsequentfmt}[2]{%
  \glsifattribute{#1}{markshortwords}{true}%
  {%
    \ifglsxtrininsertinside
      \glsabbrvfont{\glsaccessshort{#1}\glsxtrgenentrytextfmt{#2}}%
    \else
      \glsabbrvfont{\glsaccessshort{#1}}\glsxtrgenentrytextfmt{#2}%
    \fi
  }%
  {%
    \ifglsxtrininsertinside
      \glsabbrvfont{\glsaccessfmtshort{#2}\glsxtrgenentrytextfmt{#1}}%
    \else
      \glsabbrvfont{\glsaccessfmtshort{}}\glsxtrgenentrytextfmt{#1}}%
      \glsxtrgenentrytextfmt{#2}%
    \fi
  }%
}
\let\glsxtrdefaultsubsequentfmt\glsxtrsubsequentfmt

```

`\glsxtrsubsequentplfmt` Subsequent use format (plural no case change).

```

\newcommand*{\glsxtrsubsequentplfmt}[2]{%
  \glsifattribute{#1}{markshortwords}{true}%
  {%
    \ifglsxtrininsertinside
      \glsabbrvfont{\glsaccessshortpl{#1}\glsxtrgenentrytextfmt{#2}}%
    \else
      \glsabbrvfont{\glsaccessshortpl{#1}}\glsxtrgenentrytextfmt{#2}%
    \fi
  }%
  {%
    \ifglsxtrininsertinside
      \glsabbrvfont{\glsaccessfmtshortpl{#2}\glsxtrgenentrytextfmt{#1}}%
    \else
      \glsabbrvfont{\glsaccessfmtshortpl{}}\glsxtrgenentrytextfmt{#1}}%
      \glsxtrgenentrytextfmt{#2}%
    \fi
  }%
}

```



```

        \fi
      }%
    }
    \let\glxtrdefaultsubsequentplfmt\glxtrsubsequentplfmt

\Glsxtrsubsequentfmt Subsequent use format (singular, first letter uppercase).
\newcommand*{\Glsxtrsubsequentfmt}[2]{%
  \glsifattribute{#1}{markshortwords}{true}%
  {%
    \ifglxtrininsertinside
      \glsabbrvfont{\Glsaccessshort{#1}}\glxtrgenentrytextfmt{#2}}%
    \else
      \glsabbrvfont{\Glsaccessshort{#1}}\glxtrgenentrytextfmt{#2}%
    \fi
  }%
  {%
    \ifglxtrininsertinside
      \glsabbrvfont{\Glsaccessfmtshort{#2}}{\glxtrgenentrytextfmt{#1}}%
    \else
      \glsabbrvfont{\Glsaccessfmtshort{}}{\glxtrgenentrytextfmt{#1}}%
      \glxtrgenentrytextfmt{#2}%
    \fi
  }%
}
\let\Glsxtrdefaultsubsequentfmt\Glsxtrsubsequentfmt
\glsmfuaddmap{\glxtrsubsequentfmt}{\Glsxtrsubsequentfmt}

\Glsxtrsubsequentplfmt Subsequent use format (plural, first letter uppercase).
\newcommand*{\Glsxtrsubsequentplfmt}[2]{%
  \glsifattribute{#1}{markshortwords}{true}%
  {%
    \ifglxtrininsertinside
      \glsabbrvfont{\Glsaccessshortpl{#1}}\glxtrgenentrytextfmt{#2}}%
    \else
      \glsabbrvfont{\Glsaccessshortpl{#1}}\glxtrgenentrytextfmt{#2}%
    \fi
  }%
  {%
    \ifglxtrininsertinside
      \glsabbrvfont{\Glsaccessfmtshortpl{#2}}{\glxtrgenentrytextfmt{#1}}%
    \else
      \glsabbrvfont{\Glsaccessfmtshortpl{}}{\glxtrgenentrytextfmt{#1}}%
      \glxtrgenentrytextfmt{#2}%
    \fi
  }%
}
\let\Glsxtrdefaultsubsequentplfmt\Glsxtrsubsequentplfmt
\glsmfuaddmap{\glxtrsubsequentplfmt}{\Glsxtrsubsequentplfmt}

\GLSxtrsubsequentfmt Subsequent use format (singular, all caps).

```

```

\newcommand*{\GLSxtrsubsequentfmt}[2]{%
  \glsifattribute{#1}{markshortwords}{true}%
  {%
    \ifglstrinsertinside
      \glsabbrvfont{\GLSaccessshort{#1}}%
      \glsuppercase{\glstrgenentrytextfmt{#2}}}%
    \else
      \glsabbrvfont{\GLSaccessshort{#1}}%
      \glsuppercase{\glstrgenentrytextfmt{#2}}}%
    \fi
  }%
  {%
    \ifglstrinsertinside
      \glsabbrvfont{\GLSaccessfmtshort{#2}}{\glstrgenentrytextfmt}{#1}}%
    \else
      \glsabbrvfont{\GLSaccessfmtshort{}}{\glstrgenentrytextfmt}{#1}}%
      \glsuppercase{\glstrgenentrytextfmt{#2}}}%
    \fi
  }%
}
\glsmfublocker{\GLSxtrsubsequentfmt}
\let\GLSxtrdefaultsubsequentfmt\GLSxtrsubsequentfmt

```

`\GLSxtrsubsequentplfmt` Subsequent use format (plural, all caps).

```

\newcommand*{\GLSxtrsubsequentplfmt}[2]{%
  \glsifattribute{#1}{markshortwords}{true}%
  {%
    \ifglstrinsertinside
      \glsabbrvfont{\GLSaccessshortpl{#1}}%
      \glsuppercase{\glstrgenentrytextfmt{#2}}}%
    \else
      \glsabbrvfont{\GLSaccessshortpl{#1}}%
      \glsuppercase{\glstrgenentrytextfmt{#2}}}%
    \fi
  }%
  {%
    \ifglstrinsertinside
      \glsabbrvfont{\GLSaccessfmtshortpl{#2}}{\glstrgenentrytextfmt}{#1}}%
    \else
      \glsabbrvfont{\GLSaccessfmtshortpl{}}{\glstrgenentrytextfmt}{#1}}%
      \glsuppercase{\glstrgenentrytextfmt{#2}}}%
    \fi
  }%
}
\glsmfublocker{\GLSxtrsubsequentplfmt}
\let\GLSxtrdefaultsubsequentplfmt\GLSxtrsubsequentplfmt

```

1.7.1 Abbreviation Styles Setup

`\setabbreviationstyle`

```
\newcommand*{\setabbreviationstyle}[2][abbreviation]{%
  \ifcsundef{@glsabbrv@dispstyle@setup@#2}%
  {%
    \PackageError{glossaries-extra}{Undefined abbreviation style ‘#2’}{}%
  }%
  {%
```

Have abbreviations already been defined for this category?

```
\ifcsstring{@glsabbrv@current@#1}{#2}%
{%
```

Style already set.

```
}%
{%
  \def\@glsxtr@dostylewarn{%
    \glsforeachincategory{#1}{\@gls@type}{\@gls@label}%
    {%
      \def\@glsxtr@dostylewarn{\GlossariesWarning{Abbreviation
        style has been switched \MessageBreak
        for category ‘#1’, \MessageBreak
        but there have already been entries \MessageBreak
        defined for this category. Unwanted \MessageBreak
        side-effects may result}}%
      \@endfortrue
    }%
    \@glsxtr@dostylewarn
```

Set up the style for the given category.

```
\csdef{@glsabbrv@current@#1}{#2}%
\protected@edef\glscategorylabel{#1}%
\glsxtr@applyabbrvstyle{#2}%
}%
}%
}
```

`\glsxtr@applyabbrvstyle` Apply the abbreviation style without existence check.

```
\newcommand*{\glsxtr@applyabbrvstyle}[1]{%
  \csuse{@glsabbrv@dispstyle@setup@#1}%
  \csuse{@glsabbrv@dispstyle@fmts@#1}%
}
```

`\glsxtr@applyabbrvfmt` Only apply the style formats.

```
\newcommand*{\glsxtr@applyabbrvfmt}[1]{%
  \csuse{@glsabbrv@dispstyle@fmts@#1}%
}
```

`\glsxtrsetcomplexstyle` Identify an entry as having a complex abbreviation style that doesn’t work with `\GLSfirst` etc. The argument is the entry label. The second argument should

be numeric: 1 (all caps doesn't work), 2 (all caps and insert don't work), 3 (insert doesn't work).

```
\newcommand*{\glxtrsetcomplexstyle}[2]{%
  \csdef{@glxtr@has@complexstyle@#1}{#2}%
}
```

`\glxtr@do@ifcomplexstyle@allcaps` Do second argument if entry identified by first argument has a problem with all caps. Does nothing otherwise.

```
\newcommand*{\glxtr@do@ifcomplexstyle@allcaps}[2]{%
  \ifcsdef{@glxtr@has@complexstyle@#1}%
  {%
    \ifnum\csuse{@glxtr@has@complexstyle@#1}<1
    \else
    \ifnum\csuse{@glxtr@has@complexstyle@#1}<3
      #2%
    \fi
  \fi
}%
}%
}
```

`\glxtr@do@ifcomplexstyle@insert` Do second argument if entry identified by first argument has a problem with the insert argument. Does nothing otherwise.

```
\newcommand*{\glxtr@do@ifcomplexstyle@insert}[2]{%
  \ifcsdef{@glxtr@has@complexstyle@#1}%
  {%
    \ifnum\csuse{@glxtr@has@complexstyle@#1}<2
    \else
      #2%
    \fi
 }%
}%
}
```

`\GlossariesAbbrStyleTooComplexWarning`

```
\newcommand*{\GlossariesAbbrStyleTooComplexWarning}[2]{%
  \GlossariesExtraWarning{Abbreviation style used by ‘#1’ too complex #2}%
}
```

`\glxtr@check@complexstyle` The first argument is the label the second is the insert.

```
\newcommand*{\glxtr@check@complexstyle}[2]{%
  \ifx\glscapscase\@thirdofthree
  \glxtr@do@ifcomplexstyle@allcaps{#1}%
  {%
    \glxtrifwasfirstuse
  {%
    \glxifplural
  {%
    \GlossariesAbbrStyleTooComplexWarning{#1}{for \string\GLSfirstplural.
  }
  }
  }
}
```

```

        Use \string\GLSpl{#1} or \string\GLSxtrfullpl{#1} instead.
        Switching off all-caps%
    }%
}%
{%
    \GlossariesAbbrStyleTooComplexWarning{#1}{for \string\GLSfirst.
        Use \string\GLS{#1} or \string\GLSxtrfull{#1} instead.
        Switching off all-caps%
    }%
}%
}%
{%
    \glsifplural
    {%
        \GlossariesAbbrStyleTooComplexWarning{#1}{for \string\GLSplural.
            Use \string\GLSpl{#1} or \string\GLSxtrshortpl{#1} instead.
            Switching off all-caps%
        }%
    }%
    {%
        \GlossariesAbbrStyleTooComplexWarning{#1}{for \string\GLSxtrshort.
            Use \string\GLS{#1} or \string\GLSxtrshort{#1} instead.
            Switching off all-caps%
        }%
    }%
}%
\let\glscapscase\@firstofthree
}%
\fi
\ifstrempy{#2}{}%
{%
    \glsxtr@do@ifcomplexstyle@insert{#1}%
    {%
        \GlossariesAbbrStyleTooComplexWarning{#1}%
        {to support insert argument with commands like \string\glsfirst\space or
        \string\glstext. Unexpected results may occur. Use commands
        like \string\gls\space or \string\glsxtrshort\space instead}%
    }%
}%
}

```

`\newabbreviationstyle` This is different from `\newacronymstyle`. The first argument is the label, the second argument sets the information required when defining the new abbreviation and the third argument sets the commands used to display the full format.

```

\newcommand*{\newabbreviationstyle}[3]{%
    \ifcsdef{@glsabbrv@dispstyle@setup@#1}%
    {%
        \PackageError{glossaries-extra}{Abbreviation style ‘#1’ already
        defined}{}%
    }%
}

```

```
}%
{%
\csdef{@glsabbrv@dispstyle@setup@#1}{%
```

Initialise hook to do nothing. The style may change this.

```
\renewcommand*{\GlsXtrPostNewAbbreviation}{}%
#2}%
\csdef{@glsabbrv@dispstyle@fmts@#1}{%
```

Assume in-line form is the same as first use. The style may change this.

```
\renewcommand*{\glxtrinlinefullformat}{\glxtrfullformat}%
\renewcommand*{\Glsxtrinlinefullformat}{\Glsxtrfullformat}%
\renewcommand*{\GLSxtrinlinefullformat}{\GLSxtrfullformat}%
\renewcommand*{\glxtrinlinefullplformat}{\glxtrfullplformat}%
\renewcommand*{\Glsxtrinlinefullplformat}{\Glsxtrfullplformat}%
\renewcommand*{\GLSxtrinlinefullplformat}{\GLSxtrfullplformat}%
```

In the event that some custom styles predate the introduction of the all caps versions, provide default definitions:

```
\renewcommand*{\GLSxtrfullformat}{\GLSxtr@fullformat@fallback}%
\renewcommand*{\GLSxtrfullplformat}{\GLSxtr@fullplformat@fallback}%
```

Reset `\glxtrs subsequentfmt` etc in case a style changes this.

```
\let\glxtrs subsequentfmt\glxtrdefault subsequentfmt
\let\glxtrs subsequentplfmt\glxtrdefault subsequentplfmt
\let\Glsxtrs subsequentfmt\Glsxtrdefault subsequentfmt
\let\Glsxtrs subsequentplfmt\Glsxtrdefault subsequentplfmt
\let\GLSxtrs subsequentfmt\GLSxtrdefault subsequentfmt
\let\GLSxtrs subsequentplfmt\GLSxtrdefault subsequentplfmt
#3}%
```

```
}%
}
```

`\renewabbreviationstyle`

```
\newcommand*{\renewabbreviationstyle}[3]{%
\ifcsundef{@glsabbrv@dispstyle@setup@#1}
{%
\PackageError{glossaries-extra}{Abbreviation style ‘#1’ not defined}{}%
}%
{%
\csdef{@glsabbrv@dispstyle@setup@#1}{%
```

Initialise hook to do nothing. The style may change this.

```
\renewcommand*{\GlsXtrPostNewAbbreviation}{}%
#2}%
\csdef{@glsabbrv@dispstyle@fmts@#1}{%
```

Assume in-line form is the same as first use. The style may change this.

```
\renewcommand*{\glxtrinlinefullformat}{\glxtrfullformat}%
\renewcommand*{\Glsxtrinlinefullformat}{\Glsxtrfullformat}%
\renewcommand*{\GLSxtrinlinefullformat}{\GLSxtrfullformat}%
\renewcommand*{\glxtrinlinefullplformat}{\glxtrfullplformat}%
```

```
\renewcommand*{\Glsxtrinlinefullplformat}{\Glsxtrfullplformat}%
\renewcommand*{\GLSxtrinlinefullplformat}{\GLSxtrfullplformat}%
```

In the event that some custom styles predate the introduction of the all caps versions, provide default definitions:

```
\renewcommand*{\GLSxtrfullformat}{\GLSxtr@fullformat@fallback}%
\renewcommand*{\GLSxtrfullplformat}{\GLSxtr@fullplformat@fallback}%
```

Reset `\glsxtrsubsequentfmt` etc in case a style changes this.

```
\let\glsxtrsubsequentfmt\glsxtrdefaultsubsequentfmt
\let\glsxtrsubsequentplfmt\glsxtrdefaultsubsequentplfmt
\let\Glsxtrsubsequentfmt\Glsxtrdefaultsubsequentfmt
\let\Glsxtrsubsequentplfmt\Glsxtrdefaultsubsequentplfmt
\let\GLSxtrsubsequentfmt\GLSxtrdefaultsubsequentfmt
\let\GLSxtrsubsequentplfmt\GLSxtrdefaultsubsequentplfmt
#3}%
```

```
}%
}
```

`\letabbreviationstyle` Define a synonym for an abbreviation style. The first argument is the new name. The second argument is the original style's name.

```
\newcommand*{\letabbreviationstyle}[2]{%
  \csletcs{@glsabbrv@dispstyle@setup@#1}{@glsabbrv@dispstyle@setup@#2}%
  \csletcs{@glsabbrv@dispstyle@fmts@#1}{@glsabbrv@dispstyle@fmts@#2}%
}
```

```
\@glsxtr@deprecated@abbrstyle{<old-name>}{<new-name>}
```

`\glsxtr@deprecated@abbrstyle`

Define a synonym for a deprecated abbreviation style.

```
\newcommand*{\@glsxtr@deprecated@abbrstyle}[2]{%
  \csdef{@glsabbrv@dispstyle@setup@#1}{%
    \GlsXtrWarnDeprecatedAbbrStyle{#1}{#2}%
    \csuse{@glsabbrv@dispstyle@setup@#2}%
  }%
  \csletcs{@glsabbrv@dispstyle@fmts@#1}{@glsabbrv@dispstyle@fmts@#2}%
}
```

`\GlsXtrWarnDeprecatedAbbrStyle` Generate warning for deprecated style use.

```
\newcommand*{\GlsXtrWarnDeprecatedAbbrStyle}[2]{%
  \GlossariesExtraWarning{Deprecated abbreviation style name ‘#1’,
    use ‘#2’ instead}%
}
```

`\GlsXtrUseAbbrStyleSetup`

```
\newcommand*{\GlsXtrUseAbbrStyleSetup}[1]{%
  \ifcsundef{@glsabbrv@dispstyle@setup@#1}%
  {%
    \PackageError{glossaries-extra}%
```

```

        {Unknown abbreviation style definitions ‘#1’}{}%
    }%
    {%
        \csname @glsabbrv@dispstyle@setup@#1\endcsname
    }%
}

\GlsXtrUseAbbrStyleFmts

\newcommand*{\GlsXtrUseAbbrStyleFmts}[1]{%
    \ifcsundef{@glsabbrv@dispstyle@fmts@#1}%
    {%
        \PackageError{glossaries-extra}%
        {Unknown abbreviation style formats ‘#1’}{}%
    }%
    {%
        \csname @glsabbrv@dispstyle@fmts@#1\endcsname
    }%
}

```

1.7.2 Predefined Styles

Define some common styles. These will set the `first`, `firstplural`, `text` and `plural` keys, even if the `regular` attribute isn’t set to “true”. If this attribute is set, commands like `\gls` will use them as per a regular entry, otherwise those keys will be ignored unless explicitly invoked by the user with commands like `\glsfirst`. In order for the sentence case versions to work correctly, `\glstrfullformat` needs to be expanded when those keys are set. The final optional argument of `\glsfirst` will behave differently to the final optional argument of `\gls` with some styles.

v1.49 has introduced `innertextformat` for formatting commands that need access to the actual text (which is normally too deeply embedded). The styles have been modified to allow for this. The all caps versions also now need to be implemented within the styles as again the text is now too deeply embedded for the case change to otherwise work.

`\ifglstrinsertinside` Switch to determine if the insert text should be inside or outside the font changing command. The default is outside.

```

\newif\ifglstrinsertinside
\glstrinsertinsidefalse

```

The abbreviation styles are now defined in the file `glossaries-extra-abbrstyles.def`, which needs to be input here:

```

\input{glossaries-extra-abbrstyles.def}

```

1.8 Using Entries in Headings

There are four main problems with using entries in sectioning commands: they can mess with the first use flag if they end up in the table of contents,

they can add unwanted numbers to the entry's location list, the label is corrupted if used inside `\MakeUppercase` (which is used by the default headings style) and they need to be expandable for PDF bookmarks. The `glossaries` package therefore recommends the use of the expandable commands, such as `\glstryshort`, instead but this doesn't reflect the formatting since it doesn't include `\glsabbrvfont`. The commands below are an attempt to get around these problems.

The PDF bookmark issue can easily be fixed with `hyperref`'s `\texorpdfstring` which can simply use the expandable command in the PDF string case. The `TEX` string case can now use `\glstrshort` with the `noindex` key set, which prevents the unwanted additions to the location list, and the `hyper` key set to false, which prevents the problem of nested links. This just leaves one thing left that needs to be dealt with, and that's what to do if the heading style uses `\MakeUppercase`.

Note that `glossaries` automatically loads `textcase` unless `mfirstuc 2.08+` is detected, so the label can be protected from case change with `textcase`'s `\NoCaseChange`. This means that we don't have a problem provided the page style uses `\MakeTextUppercase`, but the default heading page style uses `\MakeUppercase`. (With newer versions of `mfirstuc`, exclusions are used to protect labels).

To get around this, save the original definition of `\markboth` and `\markright` and adjust it so that `\MakeUppercase` is temporarily redefined to `\MakeTextUppercase`. Some packages or classes redefine these commands, so we can't just assume they still have the original kernel definition. This only needs to be done with old versions of `mfirstuc`.

`\markright` Save original definition:

```
\let\@glstr@org@markright\markright
```

Redefine (grouping not added in case it interferes with the original code):

```
\renewcommand*{\markright}[1]{%
\glstrmarkhook
\@glstr@org@markright{\@glstrinmark#1\@glstrnotinmark}%
\glstrrestoremarkhook
}
```

`\markboth` Save original definition:

```
\let\@glstr@org@markboth\markboth
```

Redefine (grouping not added in case it interferes with the original code):

```
\renewcommand*{\markboth}[2]{%
\glstrmarkhook
\@glstr@org@markboth
{\@glstrinmark#1\@glstrnotinmark}%
{\@glstrinmark#2\@glstrnotinmark}%
\glstrrestoremarkhook
}
```

Also do this for `\starttoc`

`\starttoc` Save original definition:

```
\let\@glxtr@org@@starttoc\starttoc
```

Redefine:

```
\renewcommand*{\starttoc}[1]{%
\let\glxtrifintoc\@firstoftwo
\glxtrmarkhook
\@glxtrinmark
\@glxtr@org@@starttoc{#1}%
\glxtrrestoremarkhook
\let\glxtrifintoc\@secondoftwo
}
```

If this causes a problem provide a simple way of switching back to the original definitions:

`\glxtrRevertMarks`

```
\newcommand*{\glxtrRevertMarks}{%
\let\markright\@glxtr@org@markright
\let\markboth\@glxtr@org@markboth
\let\starttoc\@glxtr@org@@starttoc
}
```

`\glxtrRevertTocMarks` Just restores `\starttoc`.

```
\newcommand*{\glxtrRevertTocMarks}{%
\let\starttoc\@glxtr@org@@starttoc
}
```

`\glxtrifinmark`

```
\newcommand*{\glxtrifinmark}[2]{#2}
```

`\@glxtrinmark`

```
\newrobustcmd*{\@glxtrinmark}{%
\let\glxtrifinmark\@firstoftwo
}
```

`\@glxtrnotinmark`

```
\newrobustcmd*{\@glxtrnotinmark}{%
\let\glxtrifinmark\@secondoftwo
}
```

`\glxtrtitleorpdforheading`

```
\newcommand*{\glxtrtitleorpdforheading}[3]{%
\glxtrifinmark{#3}{\glstexorpdfstring{#1}{#2}}}
```

This will require `\GetTitleStringSetup{expand}` to work.

```
\ifdef\GetTitleStringDisableCommands
{\GetTitleStringDisableCommands{\let\glxtrtitleorpdforheading\@thirdofthree
\let\glxtrifinmark\@firstoftwo}}
{}}
```

`\glxtrmarkhook` Hook used in new definition of `\markboth` and `\markright` to make some changes to apply to the marks:

```
\newcommand*{\glxtrmarkhook}{%
```

Save current definitions:

```
\@glxtr@saveMakeUppercase
\let\@glxtr@org@glxtrtitleorpdforheading\glxtrtitleorpdforheading
\let\@glxtr@org@glxtrtitleshort\glxtrtitleshort
\let\@glxtr@org@glxtrtitleshortpl\glxtrtitleshortpl
\let\@glxtr@org@GLsxtrtitleshort\GLsxtrtitleshort
\let\@glxtr@org@GLsxtrtitleshortpl\GLsxtrtitleshortpl
\let\@glxtr@org@GLSxtrtitleshort\GLSxtrtitleshort
\let\@glxtr@org@GLSxtrtitleshortpl\GLSxtrtitleshortpl
\let\@glxtr@org@glxtrtitlename\glxtrtitlename
\let\@glxtr@org@GLsxtrtitlename\GLsxtrtitlename

\let\@glxtr@org@GLSxtrtitlename\GLSxtrtitlename
\let\@glxtr@org@glxtrtitletext\glxtrtitletext
\let\@glxtr@org@GLsxtrtitletext\GLsxtrtitletext
\let\@glxtr@org@GLSxtrtitletext\GLSxtrtitletext
\let\@glxtr@org@glxtrtitleplural\glxtrtitleplural
\let\@glxtr@org@GLsxtrtitleplural\GLsxtrtitleplural
\let\@glxtr@org@GLSxtrtitleplural\GLSxtrtitleplural
\let\@glxtr@org@glxtrtitlefirst\glxtrtitlefirst
\let\@glxtr@org@GLsxtrtitlefirst\GLsxtrtitlefirst

\let\@glxtr@org@GLSxtrtitlefirst\GLSxtrtitlefirst
\let\@glxtr@org@glxtrtitlefirstplural\glxtrtitlefirstplural
\let\@glxtr@org@GLsxtrtitlefirstplural\GLsxtrtitlefirstplural
\let\@glxtr@org@GLSxtrtitlefirstplural\GLSxtrtitlefirstplural
\let\@glxtr@org@glxtrtitlelong\glxtrtitlelong
\let\@glxtr@org@glxtrtitlelongpl\glxtrtitlelongpl
\let\@glxtr@org@GLsxtrtitlelong\GLsxtrtitlelong
\let\@glxtr@org@GLsxtrtitlelongpl\GLsxtrtitlelongpl
\let\@glxtr@org@glxtrtitlefull\glxtrtitlefull
\let\@glxtr@org@glxtrtitlefullpl\glxtrtitlefullpl
\let\@glxtr@org@GLsxtrtitlefull\GLsxtrtitlefull
\let\@glxtr@org@GLsxtrtitlefullpl\GLsxtrtitlefullpl
\let\@glxtr@org@GLSxtrtitlefull\GLSxtrtitlefull
\let\@glxtr@org@GLSxtrtitlefullpl\GLSxtrtitlefullpl
```

New definitions

```
\let\glxtrifinmark\@firstoftwo
\@glxtr@assignMakeUppercase
\let\glxtrtitleorpdforheading\@thirdofthree
\let\glxtrtitleshort\glxtrheadshort
\let\glxtrtitleshortpl\glxtrheadshortpl
\let\GLsxtrtitleshort\GLsxtrheadshort
\let\GLsxtrtitleshortpl\GLsxtrheadshortpl
\let\GLSxtrtitleshort\GLSxtrheadshort
\let\GLSxtrtitleshortpl\GLSxtrheadshortpl
```

```

\let\glxstrtitlename\glxstrheadname
\let\Glsxstrtitlename\Glsxstrheadname
\let\GLSxstrtitlename\GLSxstrheadname
\let\glxstrtitletext\glxstrheadtext
\let\Glsxstrtitletext\Glsxstrheadtext
\let\GLSxstrtitletext\GLSxstrheadtext
\let\glxstrtitleplural\glxstrheadplural
\let\Glsxstrtitleplural\Glsxstrheadplural
\let\GLSxstrtitleplural\GLSxstrheadplural
\let\glxstrtitlefirst\glxstrheadfirst
\let\Glsxstrtitlefirst\Glsxstrheadfirst
\let\GLSxstrtitlefirst\GLSxstrheadfirst
\let\glxstrtitlefirstplural\glxstrheadfirstplural
\let\Glsxstrtitlefirstplural\Glsxstrheadfirstplural
\let\GLSxstrtitlefirstplural\GLSxstrheadfirstplural
\let\glxstrtitlelong\glxstrheadlong
\let\glxstrtitlelongpl\glxstrheadlongpl
\let\Glsxstrtitlelong\Glsxstrheadlong
\let\Glsxstrtitlelongpl\Glsxstrheadlongpl
\let\glxstrtitlefull\glxstrheadfull
\let\glxstrtitlefullpl\glxstrheadfullpl
\let\Glsxstrtitlefull\Glsxstrheadfull
\let\Glsxstrtitlefullpl\Glsxstrheadfullpl
\let\GLSxstrtitlefull\GLSxstrheadfull
\let\GLSxstrtitlefullpl\GLSxstrheadfullpl
}

```

`\glxstrrestoremarkhook` Hook used in new definition of `\markboth` and `\markright` to restore the modified definitions. (This is in case the original `\markboth` and `\markright` shouldn't be grouped for some reason. There already is some grouping within those original definitions, but some of the code lies outside that grouping, and possibly there's a reason for it.)

```

\newcommand*{\glxstrrestoremarkhook}{%
  \let\glxstrifinmark\@secondoftwo
  \@glxstr@restoreMakeUppercase
  \let\glxstrtitleorpdforheading\@glxstr@org@glxstrtitleorpdforheading
  \let\glxstrtitleshort\@glxstr@org@glxstrtitleshort
  \let\glxstrtitleshortpl\@glxstr@org@glxstrtitleshortpl
  \let\GLSxstrtitleshort\@glxstr@org@GLSxstrtitleshort
  \let\GLSxstrtitleshortpl\@glxstr@org@GLSxstrtitleshortpl
  \let\GLSxstrtitleshort\@glxstr@org@GLSxstrtitleshort
  \let\GLSxstrtitleshortpl\@glxstr@org@GLSxstrtitleshortpl
  \let\glxstrtitlename\@glxstr@org@glxstrtitlename
  \let\Glsxstrtitlename\@glxstr@org@Glsxstrtitlename
  \let\GLSxstrtitlename\@glxstr@org@GLSxstrtitlename
  \let\glxstrtitletext\@glxstr@org@glxstrtitletext
  \let\Glsxstrtitletext\@glxstr@org@Glsxstrtitletext
  \let\GLSxstrtitletext\@glxstr@org@GLSxstrtitletext
  \let\glxstrtitleplural\@glxstr@org@glxstrtitleplural
}

```

```

\let\Glsxtrtitleplural\@glxtr@org@Glsxtrtitleplural
\let\GLSxtrtitleplural\@glxtr@org@GLSxtrtitleplural
\let\glxtrtitlefirst\@glxtr@org@glxtrtitlefirst
\let\Glsxtrtitlefirst\@glxtr@org@Glsxtrtitlefirst
\let\GLSxtrtitlefirst\@glxtr@org@GLSxtrtitlefirst
\let\glxtrtitlefirstplural\@glxtr@org@glxtrtitlefirstplural
\let\Glsxtrtitlefirstplural\@glxtr@org@Glsxtrtitlefirstplural
\let\GLSxtrtitlefirstplural\@glxtr@org@GLSxtrtitlefirstplural
\let\glxtrtitlelong\@glxtr@org@glxtrtitlelong
\let\glxtrtitlelongpl\@glxtr@org@glxtrtitlelongpl
\let\Glsxtrtitlelong\@glxtr@org@Glsxtrtitlelong
\let\Glsxtrtitlelongpl\@glxtr@org@Glsxtrtitlelongpl
\let\glxtrtitlefull\@glxtr@org@glxtrtitlefull
\let\glxtrtitlefullpl\@glxtr@org@glxtrtitlefullpl
\let\Glsxtrtitlefull\@glxtr@org@Glsxtrtitlefull
\let\Glsxtrtitlefullpl\@glxtr@org@Glsxtrtitlefullpl
\let\GLSxtrtitlefull\@glxtr@org@GLSxtrtitlefull
\let\GLSxtrtitlefullpl\@glxtr@org@GLSxtrtitlefullpl
}

```

Instead of using one document-wide conditional, use `headuc` attribute to determine whether or not to use the all upper case form.

`\glxtrtitleopts` Make it possible to change the default options within the title (but not the page header or table of contents).

```
\newcommand*{\glxtrtitleopts}{noindex,hyper=false}
```

```
\glxtr@title@field{<cs>}{<label>}
```

`\glxtr@title@field`

Used by all the `\glxtrtitle<field>` commands for consistency.

```

\newcommand*{\glxtr@title@field}[2]{%
  \expandafter#1\expandafter[\glxtrtitleopts]{#2}[]%
}

```

`\glxtrheadshort` Command used to display short form in the page header.

```

\newcommand*{\glxtrheadshort}[1]{%
  \protect\NoCaseChange
  {%
    \glxtrifheaduc{#1}%
    {%
      \GLSxtrshort[noindex,hyper=false]{#1}[]%
    }%
    {%
      \glxtrshort[noindex,hyper=false]{#1}[]%
    }%
  }%
}

```

`\glxstrtitleshort` Command to display short form of abbreviation in section title.

```
\newrobustcmd*{\glxstrtitleshort}[1]{%
  \glxstr@title@field\glxstrshort{#1}%
}
```

`\glxstrheadshortpl` Command used to display plural short form in the page header. If you want the text converted to upper case, this needs to be redefined to use `\GLSxtrshortpl` instead. If you are using a smallcaps style, the default fonts don't provide italic smallcaps.

```
\newcommand*{\glxstrheadshortpl}[1]{%
  \protect\NoCaseChange
  {%
    \glxstrifheaduc{#1}%
    {%
      \GLSxtrshortpl[noindex,hyper=false]{#1}[]%
    }%
    {%
      \glxstrshortpl[noindex,hyper=false]{#1}[]%
    }%
  }%
}
```

`\glxstrtitleshortpl` Command to display plural short form of abbreviation in section title.

```
\newrobustcmd*{\glxstrtitleshortpl}[1]{%
  \glxstr@title@field\glxstrshortpl{#1}%
}
```

`\Glsxtrheadshort` Command used to display short form in the page header with the first letter converted to upper case.

```
\newcommand*{\Glsxtrheadshort}[1]{%
  \protect\NoCaseChange
  {%
    \glxstrifheaduc{#1}%
    {%
      \GLSxtrshort[noindex,hyper=false]{#1}[]%
    }%
    {%
      \Glsxtrshort[noindex,hyper=false]{#1}[]%
    }%
  }%
}
```

`\Glsxtrtitleshort` Command to display short form of abbreviation in section title with the first letter converted to upper case.

```
\newrobustcmd*{\Glsxtrtitleshort}[1]{%
  \glxstr@title@field\Glsxtrshort{#1}%
}
```

`\GLSxtrheadshort` There's no need to check for the headuc attribute.

```

\newcommand*{\GLSxtrheadshort}[1]{%
\protect\NoCaseChange
{%
\GLSxtrshort[noindex,hyper=false]{#1}[]%
}%
}

```

`\GLSxtrtitleshort` Command to display short form of abbreviation in section title in all upper case.

```

\newrobustcmd*{\GLSxtrtitleshort}[1]{%
\glxtr@title@field\GLSxtrshort{#1}%
}

```

`\GLSxtrheadshortpl` There's no need to check for the headuc attribute.

```

\newcommand*{\GLSxtrheadshortpl}[1]{%
\protect\NoCaseChange
{%
\GLSxtrshortpl[noindex,hyper=false]{#1}[]%
}%
}

```

`\Glsxtrheadshortpl` Command used to display plural short form in the page header with the first letter converted to upper case.

```

\newcommand*{\Glsxtrheadshortpl}[1]{%
\protect\NoCaseChange
{%
\glxtrifheaduc{#1}%
{%
\GLSxtrshortpl[noindex,hyper=false]{#1}[]%
}%
{%
\Glsxtrshortpl[noindex,hyper=false]{#1}[]%
}%
}%
}

```

`\Glsxtrtitleshortpl` Command to display plural short form of abbreviation in section title with the first letter converted to upper case.

```

\newrobustcmd*{\Glsxtrtitleshortpl}[1]{%
\glxtr@title@field\Glsxtrshortpl{#1}%
}

```

`\GLSxtrtitleshortpl` Command to display plural short form of abbreviation in section title in all upper case.

```

\newrobustcmd*{\GLSxtrtitleshortpl}[1]{%
\glxtr@title@field\GLSxtrshortpl{#1}%
}

```

`\glxtrheadname` As above but for the name value.

```

\newcommand*{\glxtrheadname}[1]{%
\protect\NoCaseChange
{%
\glxtrifheaduc{#1}%
{%
\GLSname[noindex,hyper=false]{#1}[]%
}%
}%
\glSname[noindex,hyper=false]{#1}[]%
}%
}

```

`\glxtrtrtitlename` Command to display name value in section title.

```

\newrobustcmd*{\glxtrtrtitlename}[1]{%
\glxtr@title@field\glSname{#1}%
}

```

`\Glsxtrheadname` First letter converted to upper case

```

\newcommand*{\Glsxtrheadname}[1]{%
\protect\NoCaseChange
{%
\glxtrifheaduc{#1}%
{%
\GLSname[noindex,hyper=false]{#1}[]%
}%
}%
\GLSname[noindex,hyper=false]{#1}[]%
}%
}

```

`\Glsxtrtrtitlename` Command to display name value in section title with the first letter changed to upper case.

```

\newrobustcmd*{\Glsxtrtrtitlename}[1]{%
\glxtr@title@field\GLSname{#1}%
}

```

`\GLSxtrheadname` There's no need to check for the headuc attribute.

```

\newcommand*{\GLSxtrheadname}[1]{%
\protect\NoCaseChange
{%
\GLSname[noindex,hyper=false]{#1}[]%
}%
}

```

`\GLSxtrtrtitlename` Command to display name value in section title in all upper case.

```

\newrobustcmd*{\GLSxtrtrtitlename}[1]{%

```



```

        \glsxtr@title@field\GLSname{#1}%
    }

\glsxtrheadtext As above but for the text value.
    \newcommand*{\glsxtrheadtext}[1]{%
        \protect\NoCaseChange
        {%
            \glsxtrifheaduc{#1}%
            {%
                \GLStext[noindex,hyper=false]{#1}[]%
            }%
            {%
                \glstext[noindex,hyper=false]{#1}[]%
            }%
        }%
    }

\glsxtrtitletext Command to display text value in section title.
    \newrobustcmd*{\glsxtrtitletext}[1]{%
        \glsxtr@title@field\glstext{#1}%
    }

\Glsxtrheadtext First letter converted to upper case
    \newcommand*{\Glsxtrheadtext}[1]{%
        \protect\NoCaseChange
        {%
            \glsxtrifheaduc{#1}%
            {%
                \GLStext[noindex,hyper=false]{#1}[]%
            }%
            {%
                \Glstext[noindex,hyper=false]{#1}[]%
            }%
        }%
    }

\Glsxtrtitletext Command to display text value in section title with the first letter changed to
upper case.
    \newrobustcmd*{\Glsxtrtitletext}[1]{%
        \glsxtr@title@field\Glstext{#1}%
    }

\GLSxtrheadtext There's no need to check for the headuc attribute.
    \newcommand*{\GLSxtrheadtext}[1]{%
        \protect\NoCaseChange
        {%
            \GLStext[noindex,hyper=false]{#1}[]%
        }%
    }

```

```

\GLSxtrtitletext Command to display text value in section title in all upper case.
\newrobustcmd*{\GLSxtrtitletext}[1]{%
  \glxtr@title@field\GLStext{#1}%
}

\glxtrheadplural As above but for the plural value.
\newcommand*{\glxtrheadplural}[1]{%
  \protect\NoCaseChange
  {%
    \glxtrifheaduc{#1}%
    {%
      \GLSplural[noindex,hyper=false]{#1}[]%
    }%
    {%
      \glsplural[noindex,hyper=false]{#1}[]%
    }%
  }%
}

\glxtrtitleplural Command to display plural value in section title.
\newrobustcmd*{\glxtrtitleplural}[1]{%
  \glxtr@title@field\glsplural{#1}%
}

\Glsxtrheadplural Convert first letter to upper case.
\newcommand*{\Glsxtrheadplural}[1]{%
  \protect\NoCaseChange
  {%
    \glxtrifheaduc{#1}%
    {%
      \GLSplural[noindex,hyper=false]{#1}[]%
    }%
    {%
      \Glsplural[noindex,hyper=false]{#1}[]%
    }%
  }%
}

\Glsxtrtitleplural Command to display plural value in section title with the first letter changed to
upper case.
\newrobustcmd*{\Glsxtrtitleplural}[1]{%
  \glxtr@title@field\Glsplural{#1}%
}

\GLSxtrheadplural There's no need to check for the headuc attribute.
\newcommand*{\GLSxtrheadplural}[1]{%
  \protect\NoCaseChange
  {%
    \GLSplural[noindex,hyper=false]{#1}[]%
  }%
}

```

```

    }%
  }

\GLSxtrtitleplural Command to display plural value in section title in all upper case.
    \newrobustcmd*{\GLSxtrtitleplural}[1]{%
      \glstr@title@field\GLSplural{#1}%
    }

\glstrheadfirst As above but for the first value.
    \newcommand*{\glstrheadfirst}[1]{%
      \protect\NoCaseChange
      {%
        \glstrifheaduc{#1}%
        {%
          \GLSfirst[noindex,hyper=false]{#1}[]%
        }%
        {%
          \glstrfirst[noindex,hyper=false]{#1}[]%
        }%
      }%
    }

\glstrtitlefirst Command to display first value in section title.
    \newrobustcmd*{\glstrtitlefirst}[1]{%
      \glstr@title@field\glstrfirst{#1}%
    }

\Glsxtrheadfirst First letter converted to upper case
    \newcommand*{\Glsxtrheadfirst}[1]{%
      \protect\NoCaseChange
      {%
        \glstrifheaduc{#1}%
        {%
          \GLSfirst[noindex,hyper=false]{#1}[]%
        }%
        {%
          \Glsfirst[noindex,hyper=false]{#1}[]%
        }%
      }%
    }

\Glsxtrtitlefirst Command to display first value in section title with the first letter changed to
upper case.
    \newrobustcmd*{\Glsxtrtitlefirst}[1]{%
      \glstr@title@field\Glsfirst{#1}%
    }

\GLSxtrheadfirst There's no need to check for the headuc attribute.
    \newcommand*{\GLSxtrheadfirst}[1]{%

```

```

\protect\NoCaseChange
{%
  \GLSfirst[noindex,hyper=false]{#1}[]%
}%
}

```

`\GLSxtrtitlefirst` Command to display first value in section title in all upper case.

```

\newrobustcmd*{\GLSxtrtitlefirst}[1]{%
  \glxtr@title@field\GLSfirst{#1}%
}

```

`\glxtrheadfirstplural` As above but for the firstplural value.

```

\newcommand*{\glxtrheadfirstplural}[1]{%
  \protect\NoCaseChange
  {%
    \glxtrifheaduc{#1}%
    {%
      \GLSfirstplural[noindex,hyper=false]{#1}[]%
    }%
    {%
      \glSfirstplural[noindex,hyper=false]{#1}[]%
    }%
  }%
}

```

`\glxtrtitlefirstplural` Command to display firstplural value in section title.

```

\newrobustcmd*{\glxtrtitlefirstplural}[1]{%
  \glxtr@title@field\glSfirstplural{#1}%
}

```

`\Glsxtrheadfirstplural` First letter converted to upper case

```

\newcommand*{\Glsxtrheadfirstplural}[1]{%
  \protect\NoCaseChange
  {%
    \glxtrifheaduc{#1}%
    {%
      \GLSfirstplural[noindex,hyper=false]{#1}[]%
    }%
    {%
      \Glsfirstplural[noindex,hyper=false]{#1}[]%
    }%
  }%
}

```

`\Glsxtrtitlefirstplural` Command to display first value in section title with the first letter changed to upper case.

```

\newrobustcmd*{\Glsxtrtitlefirstplural}[1]{%
  \glxtr@title@field\Glsfirstplural{#1}%
}

```

`\GLSxtrheadfirstplural` There's no need to check for the headuc attribute.

```
\newcommand*{\GLSxtrheadfirstplural}[1]{%
\protect\NoCaseChange
{%
\GLSfirstplural[noindex,hyper=false]{#1}[]%
}%
}
```

`\GLSxtrtitlefirstplural` Command to display first value in section title in all upper case.

```
\newrobustcmd*{\GLSxtrtitlefirstplural}[1]{%
\glxtr@title@field\GLSfirstplural{#1}%
}
```

`\glxtrheadlong` Command used to display long form in the page header.

```
\newcommand*{\glxtrheadlong}[1]{%
\protect\NoCaseChange
{%
\glxtrifheaduc{#1}%
{%
\GLSxtrlong[noindex,hyper=false]{#1}[]%
}%
{%
\glxtrlong[noindex,hyper=false]{#1}[]%
}%
}%
}
```

`\glxtrtitlelong` Command to display long form of abbreviation in section title.

```
\newrobustcmd*{\glxtrtitlelong}[1]{%
\glxtr@title@field\glxtrlong{#1}%
}
```

`\glxtrheadlongpl` Command used to display plural long form in the page header. If you want the text converted to upper case, this needs to be redefined to use `\GLSxtrlongpl` instead. If you are using a smallcaps style, the default fonts don't provide italic smallcaps.

```
\newcommand*{\glxtrheadlongpl}[1]{%
\protect\NoCaseChange
{%
\glxtrifheaduc{#1}%
{%
\GLSxtrlongpl[noindex,hyper=false]{#1}[]%
}%
{%
\glxtrlongpl[noindex,hyper=false]{#1}[]%
}%
}%
}
```

`\glxstrtitlelongpl` Command to display plural long form of abbreviation in section title.

```

\newrobustcmd*{\glxstrtitlelongpl}[1]{%
  \glxstr@title@field\glxstrlongpl{#1}%
}

```

`\GLxtrheadlong` Command used to display long form in the page header with the first letter converted to upper case.

```

\newcommand*{\GLxtrheadlong}[1]{%
  \protect\NoCaseChange
  {%
    \glxstrifheaduc{#1}%
    {%
      \GLSxtrlong[noindex,hyper=false]{#1}[]%
    }%
    {%
      \GLSxtrlong[noindex,hyper=false]{#1}[]%
    }%
  }%
}

```

`\Glsxtrtitlelong` Command to display long form of abbreviation in section title with the first letter converted to upper case.

```

\newrobustcmd*{\Glsxtrtitlelong}[1]{%
  \glxstr@title@field\GLSxtrlong{#1}%
}

```

`\GLSxtrtitlelong` Command to display long form of abbreviation in section title in all upper case.

```

\newrobustcmd*{\GLSxtrtitlelong}[1]{%
  \glxstr@title@field\GLSxtrlong{#1}%
}

```

`\GLSxtrheadlong` There's no need to check for the headuc attribute.

```

\newcommand*{\GLSxtrheadlong}[1]{%
  \protect\NoCaseChange
  {%
    \GLSxtrlong[noindex,hyper=false]{#1}[]%
  }%
}

```

`\Glsxtrheadlongpl` Command used to display plural long form in the page header with the first letter converted to upper case.

```

\newcommand*{\Glsxtrheadlongpl}[1]{%
  \protect\NoCaseChange
  {%
    \glxstrifheaduc{#1}%
    {%
      \GLSxtrlongpl[noindex,hyper=false]{#1}[]%
    }%
  }%
}

```

```

    {%
      \Glsxtrlongpl[noindex,hyper=false]{#1}[]%
    }%
  }%
}

```

`\Glsxtrtitlelongpl` Command to display plural long form of abbreviation in section title with the first letter converted to upper case.

```

\newrobustcmd*{\Glsxtrtitlelongpl}[1]{%
  \glxtr@title@field\Glsxtrlongpl{#1}%
}

```

`\GLSxtrtitlelongpl` Command to display plural long form of abbreviation in section title in all upper case.

```

\newrobustcmd*{\GLSxtrtitlelongpl}[1]{%
  \glxtr@title@field\GLSxtrlongpl{#1}%
}

```

`\GLSxtrheadlongpl` There's no need to check for the headuc attribute.

```

\newcommand*{\GLSxtrheadlongpl}[1]{%
  \protect\NoCaseChange
  {%
    \Glsxtrlongpl[noindex,hyper=false]{#1}[]%
  }%
}

```

`\glxtrheadfull` Command used to display full form in the page header.

```

\newcommand*{\glxtrheadfull}[1]{%
  \protect\NoCaseChange
  {%
    \glxtrifheaduc{#1}%
  }%
  \GLSxtrfull[noindex,hyper=false]{#1}[]%
  {%
    \glxtrfull[noindex,hyper=false]{#1}[]%
  }%
}

```

`\glxtrtitlefull` Command to display full form of abbreviation in section title.

```

\newrobustcmd*{\glxtrtitlefull}[1]{%
  \glxtr@title@field\glxtrfull{#1}%
}

```

`\glxtrheadfullpl` Command used to display plural full form in the page header. If you want the text converted to upper case, this needs to be redefined to use `\GLSxtrfullpl` instead. If you are using a smallcaps style, the default fonts don't provide italic smallcaps.

```

\newcommand*{\glxtrheadfullpl}[1]{%
\protect\NoCaseChange
{%
\glxtrifheaduc{#1}%
{%
\GLSxtrfullpl[noindex,hyper=false]{#1}[]%
}%
}%
\glxtrfullpl[noindex,hyper=false]{#1}[]%
}%
}

```

`\glxtrtitlefullpl` Command to display plural full form of abbreviation in section title.

```

\newrobustcmd*{\glxtrtitlefullpl}[1]{%
\glxtr@title@field\glxtrfullpl{#1}%
}

```

`\GLSxtrheadfull` Command used to display full form in the page header with the first letter converted to upper case.

```

\newcommand*{\GLSxtrheadfull}[1]{%
\protect\NoCaseChange
{%
\glxtrifheaduc{#1}%
{%
\GLSxtrfull[noindex,hyper=false]{#1}[]%
}%
}%
\GLSxtrfull[noindex,hyper=false]{#1}[]%
}%
}

```

`\GLSxtrtitlefull` Command to display full form of abbreviation in section title with the first letter converted to upper case.

```

\newrobustcmd*{\GLSxtrtitlefull}[1]{%
\glxtr@title@field\GLSxtrfull{#1}%
}

```

`\GLSxtrheadfull` There's no need to check for the headuc attribute.

```

\newcommand*{\GLSxtrheadfull}[1]{%
\protect\NoCaseChange
{%
\GLSxtrfull[noindex,hyper=false]{#1}[]%
}%
}

```

`\GLSxtrtitlefull` Command to display full form of abbreviation in section title in all upper case.


```

\newrobustcmd*{\GLSxtrtitlefull}[1]{%
  \glxtr@title@field\GLSxtrfull{#1}%
}

```

`\Glsxtrheadfullpl` Command used to display plural full form in the page header with the first letter converted to upper case.

```

\newcommand*{\Glsxtrheadfullpl}[1]{%
  \protect\NoCaseChange
  {%
    \glxtrifheaduc{#1}%
    {%
      \GLSxtrfullpl[noindex,hyper=false]{#1}[]%
    }%
    {%
      \Glsxtrfullpl[noindex,hyper=false]{#1}[]%
    }%
  }%
}

```

`\Glsxtrtitlefullpl` Command to display plural full form of abbreviation in section title with the first letter converted to upper case.

```

\newrobustcmd*{\Glsxtrtitlefullpl}[1]{%
  \glxtr@title@field\Glsxtrfullpl{#1}%
}

```

`\GLSxtrheadfullpl` There's no need to check for the headuc attribute.

```

\newcommand*{\GLSxtrheadfullpl}[1]{%
  \protect\NoCaseChange
  {%
    \GLSxtrfullpl[noindex,hyper=false]{#1}[]%
  }%
}

```

`\GLSxtrtitlefullpl` Command to display plural full form of abbreviation in section title in all upper case.

```

\newrobustcmd*{\GLSxtrtitlefullpl}[1]{%
  \glxtr@title@field\GLSxtrfullpl{#1}%
}

```

`\glsfmtshort` Provide a way of using the formatted short form in section headings. If `hyperref` has been loaded, use `\texorpdfstring` for convenience in PDF bookmarks.

```

\newcommand*{\glsfmtshort}[1]{%
  \glstexorpdfstring
  {%
    \glsxtrtitleshort{#1}}%
  {%
    \glsentryshort{#1}}%
}

```

Similarly for the plural version.

`\glsfmtshortpl`

```
\newcommand*{\glsfmtshortpl}[1]{%
  \glstexorpdfstring
    {\glsxtrtitleshortpl{#1}}%
    {\glsentryshortpl{#1}}%
}
```

Use the expandable `\MFUsentencecase` in the PDF bookmark.

`\Glsfmtshort` Singular form (first letter uppercase).

```
\newcommand*{\Glsfmtshort}[1]{%
  \glstexorpdfstring
    {\Glsxtrtitleshort{#1}}%
    {\MFUsentencecase{\glsentryshort{#1}}}%
}
\glsmfuaddmap{\glsfmtshort}{\Glsfmtshort}
```

`\Glsfmtshortpl` Plural form (first letter uppercase).

```
\newcommand*{\Glsfmtshortpl}[1]{%
  \glstexorpdfstring
    {\Glsxtrtitleshortpl{#1}}%
    {\MFUsentencecase{\glsentryshortpl{#1}}}%
}
\glsmfuaddmap{\glsfmtshortpl}{\Glsfmtshortpl}
```

Similarly for all-caps.

`\GLSfmtshort`

```
\newcommand*{\GLSfmtshort}[1]{%
  \glstexorpdfstring
    {\GLSxtrtitleshort{#1}}%
    {\GLSxtrusefield{#1}{short}}%
}
\glsmfublocker{\GLSfmtshort}
```

`\GLSfmtshortpl`

```
\newcommand*{\GLSfmtshortpl}[1]{%
  \glstexorpdfstring
    {\GLSxtrtitleshortpl{#1}}%
    {\GLSxtrusefield{#1}{shortpl}}%
}
\glsmfublocker{\GLSfmtshortpl}
```

`\glsfmtname` As above but for the name value.

```
\newcommand*{\glsfmtname}[1]{%
  \glstexorpdfstring
    {\glsxtrtitlename{#1}}%
    {\glsentryname{#1}}%
}
```

```

\Glsfmtname First letter converted to upper case.
\newcommand*{\Glsfmtname}[1]{%
  \glstexorpdfstring
  {\Glsxtrtitlename{#1}}%
  {\MFUsentencecase{\glsentryname{#1}}}%
}
\glsmfuaddmap{\Glsfmtname}{\Glsfmtname}

\GLSfmtname All upper case.
\newcommand*{\GLSfmtname}[1]{%
  \glstexorpdfstring
  {\GLSxtrtitlename{#1}}%
  {\GLSxtrusefield{#1}{name}}%
}
\glsmfublocker{\GLSfmtname}

\glsfmttext As above but for the text value.
\newcommand*{\glsfmttext}[1]{%
  \glstexorpdfstring
  {\glsxtrtitletext{#1}}%
  {\glsentrytext{#1}}%
}

\Glsfmttext First letter converted to upper case.
\newcommand*{\Glsfmttext}[1]{%
  \glstexorpdfstring
  {\Glsxtrtitletext{#1}}%
  {\MFUsentencecase{\glsentrytext{#1}}}%
}
\glsmfuaddmap{\Glsfmttext}{\Glsfmttext}

\GLSfmttext All upper case.
\newcommand*{\GLSfmttext}[1]{%
  \glstexorpdfstring
  {\GLSxtrtitletext{#1}}%
  {\GLSxtrusefield{#1}{text}}%
}
\glsmfublocker{\GLSfmttext}

\glsfmtplural As above but for the plural value.
\newcommand*{\glsfmtplural}[1]{%
  \glstexorpdfstring
  {\glsxtrtitleplural{#1}}%
  {\glsentryplural{#1}}%
}

\Glsfmtplural First letter converted to upper case.
\newcommand*{\Glsfmtplural}[1]{%
  \glstexorpdfstring

```

```

        {\Glsxtrtitleplural{#1}}%
        {\MFUsentencecase{\glstryplural{#1}}}%
    }
    \glsmfuaddmap{\glsfmtplural}{\Glsfmtplural}

\GLSfmtplural All upper case.
    \newcommand*{\GLSfmtplural}[1]{%
        \glstexorpdfstring
        {\Glsxtrtitleplural{#1}}%
        {\Glsxtrusefield{#1}{plural}}}%
    }
    \glsmfublocker{\GLSfmtplural}

\glsfmtfirst As above but for the first value.
    \newcommand*{\glsfmtfirst}[1]{%
        \glstexorpdfstring
        {\glxtrtitlefirst{#1}}%
        {\glstryfirst{#1}}}%
    }

\Glsfmtfirst First letter converted to upper case.
    \newcommand*{\Glsfmtfirst}[1]{%
        \glstexorpdfstring
        {\Glsxtrtitlefirst{#1}}%
        {\MFUsentencecase{\glstryfirst{#1}}}%
    }
    \glsmfuaddmap{\glsfmtfirst}{\Glsfmtfirst}

\GLSfmtfirst All upper case.
    \newcommand*{\GLSfmtfirst}[1]{%
        \glstexorpdfstring
        {\Glsxtrtitlefirst{#1}}%
        {\Glsxtrusefield{#1}{first}}}%
    }
    \glsmfublocker{\GLSfmtfirst}

\glsfmtfirstpl As above but for the firstplural value.
    \newcommand*{\glsfmtfirstpl}[1]{%
        \glstexorpdfstring
        {\glxtrtitlefirstplural{#1}}%
        {\glsxtrusefield{#1}{firstpl}}}%
    }

\Glsfmtfirstpl First letter converted to upper case.
    \newcommand*{\Glsfmtfirstpl}[1]{%
        \glstexorpdfstring
        {\Glsxtrtitlefirstplural{#1}}%
        {\MFUsentencecase{\glstryfirstplural{#1}}}%
    }

```

```

\GLSfmtfirstpl All upper case.
\newcommand*{\GLSfmtfirstpl}[1]{%
  \glstexorpdfstring
  {\GLSxtrtitlefirstplural{#1}}%
  {\GLSxtrusefield{#1}{firstpl}}%
}
\glsmfublocker{\GLSfmtfirstpl}

\glsfmtlong As above but for the long value.
\newcommand*{\glsfmtlong}[1]{%
  \glstexorpdfstring
  {\glsxtrtitlelong{#1}}%
  {\glsentrylong{#1}}%
}

\Glsfmtlong First letter converted to upper case.
\newcommand*{\Glsfmtlong}[1]{%
  \glstexorpdfstring
  {\Glsxtrtitlelong{#1}}%
  {\glspdfsentencecase{\glsentrylong{#1}}}%
}
\glsmfuaddmap{\glsfmtlong}{\Glsfmtlong}

\GLSfmtlong All upper case.
\newcommand*{\GLSfmtlong}[1]{%
  \glstexorpdfstring
  {\GLSxtrtitlelong{#1}}%
  {\GLSxtrusefield{#1}{long}}%
}
\glsmfublocker{\GLSfmtlong}

\glsfmtlongpl As above but for the longplural value.
\newcommand*{\glsfmtlongpl}[1]{%
  \glstexorpdfstring
  {\glsxtrtitlelongpl{#1}}%
  {\glsentrylongpl{#1}}%
}

\Glsfmtlongpl First letter converted to upper case.
\newcommand*{\Glsfmtlongpl}[1]{%
  \glstexorpdfstring
  {\Glsxtrtitlelongpl{#1}}%
  {\glspdfsentencecase{\glsentrylongpl{#1}}}%
}
\glsmfuaddmap{\glsfmtlongpl}{\Glsfmtlongpl}

\GLSfmtlongpl All upper case.
\newcommand*{\GLSfmtlongpl}[1]{%
  \glstexorpdfstring

```

```

        {\GLSxtrtitlelongpl{#1}}%
        {\GLSxtrusefield{#1}{longpl}}%
    }
    \glsmfublocker{\GLSfmtlongpl}

\glspdffmtfull Can't use \glxtrinlinefullformat in PDF bookmarks as it's not fully ex-
pandable. This command is for the PDF part of \texorpdfstring for the full
form.
    \newcommand*{\glspdffmtfull}[1]{\glentrylong{#1} (\glentryshort{#1})}%

\glspdffmtfullpl Likewise for plural.
    \newcommand*{\glspdffmtfullpl}[1]{\glentrylongpl{#1} (\glentryshortpl{#1})}%

\glsfmtfull In-line full format.
    \newcommand*{\glsfmtfull}[1]{%
        \glstexorpdfstring
        {\GLSxtrtitlefull{#1}}%
        {\glspdffmtfull{#1}}%
    }

\Glsfmtfull First letter converted to upper case.
    \newcommand*{\Glsfmtfull}[1]{%
        \glstexorpdfstring
        {\GLSxtrtitlefull{#1}}%
        {\glspdfsentencecase{\glspdfmtfull{#1}}}%
    }
    \glsmfuaddmap{\glsfmtfull}{\Glsfmtfull}

\GLSfmtfull All upper case. This explicitly uses \text_uppercase:n in case an old version
of glossaries or mfirstuc is present.
    \ExplSyntaxOn
    \newcommand*{\GLSfmtfull}[1]{%
        \glstexorpdfstring
        {\GLSxtrtitlefull{#1}}%
        {\text_uppercase:n{\glspdfmtfull{#1}}}%
    }
    \ExplSyntaxOff
    \glsmfublocker{\GLSfmtfull}

\glsfmtfullpl In-line full plural format.
    \newcommand*{\glsfmtfullpl}[1]{%
        \glstexorpdfstring
        {\GLSxtrtitlefullpl{#1}}%
        {\glspdfmtfullpl{#1}}%
    }

\Glsfmtfullpl First letter converted to upper case.
    \newcommand*{\Glsfmtfullpl}[1]{%

```

```

\glstexorpdfstring
{\Glsxtrtitlefullpl{#1}}%
{\glspdfsentencecase{\glspdfmtfullpl{#1}{}}}%
}
\glsmfuaddmap{\glsfmtfullpl}{\Glsfmtfullpl}

```

`\Glsfmtfullpl` All upper case. This explicitly uses `\text_uppercase:n` in case an old version of glossaries or mfirstuc is present.

```

\ExplSyntaxOn
\newcommand*{\Glsfmtfullpl}[1]{%
\glstexorpdfstring
{\Glsxtrtitlefullpl{#1}}%
{\text_uppercase:n{\glspdfmtfullpl{#1}{}}}%
}
\ExplSyntaxOff
\glsmfublocker{\Glsfmtfullpl}

```

1.9 Prefixes

Provide support for glossaries-prefix.

`\pglsprefix`

```
\pglsprefix{<entry-label>}{<prefix-field>}
```

A shortcut way of inserting the prefix and separator if they are required. If this needs to be redefined, use `\ifglsfldvoid` for an expandable test.

```

\newcommand{\pglsprefix}[2]{%
\ifcempty{glo@\glstetoklabel{#1}@#2}{}%
{\csuse{glo@\glstetoklabel{#1}@#2}\glsprefixsep}%
}

```

`\Pglsprefix`

```
\Pglsprefix{<entry-label>}{<prefix-field>}
```

Similar to `\pglsprefix` but sentence case. The conditional is omitted as it will have to already be checked.

```

\newcommand{\Pglsprefix}[2]{%
\Glsxtrusefield{#1}{#2}\glsprefixsep
}

```

`\PGLSprefix`

```
\PGLSprefix{<entry-label>}{<prefix-field>}
```

As `\pglsprefix` but all caps.

```

\newcommand{\PGLSprefix}[2]{%
\ifcempty{glo@\glstetoklabel{#1}@#2}{}%
{\glsuppercase{\csuse{glo@\glstetoklabel{#1}@#2}\glsprefixsep}}%
}

```

Abbreviations. Short form uses prefix and prefixplural fields.

`\pglsxtrshort` No case-change.

```
\newrobustcmd*{\pglsxtrshort}{\@gls@hyp@opt\ns@pglsxtrshort}
\newcommand*{\ns@pglsxtrshort}[2] [] {%
  \new@ifnextchar[{\@pglsxtrshort{#1}{#2}}{\@pglsxtrshort{#1}{#2} []}%
}
\def\@pglsxtrshort#1#2[#3]{%
  \pglsprefix{#2}{prefix}%
  \@glsxtrshort{#1}{#2}[#3]%
}
```

`\Pglxtrshort` Sentence case.

```
\newrobustcmd*{\Pglxtrshort}{\@gls@hyp@opt\ns@Pglxtrshort}
\newcommand*{\ns@Pglxtrshort}[2] [] {%
  \new@ifnextchar[{\@Pglxtrshort{#1}{#2}}{\@Pglxtrshort{#1}{#2} []}%
}
\def\@Pglxtrshort#1#2[#3]{%
  \ifglshasprefix{#2}%
  {%
    \Pglsprefix{#2}{prefix}%
    \@glsxtrshort{#1}{#2}[#3]%
  }%
  {\@Glsxtrshort{#1}{#2}[#3]}%
}
\glsmfuaddmap{\pglsxtrshort}{\Pglxtrshort}
```

`\PGLSxtrshort` All-caps is also fairly simple.

```
\newrobustcmd*{\PGLSxtrshort}{\@gls@hyp@opt\ns@PGLSxtrshort}
\newcommand*{\ns@PGLSxtrshort}[2] [] {%
  \new@ifnextchar[{\@PGLSxtrshort{#1}{#2}}{\@PGLSxtrshort{#1}{#2} []}%
}
\def\@PGLSxtrshort#1#2[#3]{%
  \PGLSprefix{#2}{prefix}%
  \@GLSxtrshort{#1}{#2}[#3]%
}
\glsmfublocker{\PGLSxtrshort}
```

Short plural.

`\pglsxtrshortpl`

```
\newrobustcmd*{\pglsxtrshortpl}{\@gls@hyp@opt\ns@pglsxtrshortpl}
\newcommand*{\ns@pglsxtrshortpl}[2] [] {%
  \new@ifnextchar[{\@pglsxtrshortpl{#1}{#2}}{\@pglsxtrshortpl{#1}{#2} []}%
}
\def\@pglsxtrshortpl#1#2[#3]{%
  \pglsprefix{#2}{prefixplural}%
  \@glsxtrshortpl{#1}{#2}[#3]%
}
```


\Pglstrshortpl

```
\newrobustcmd*{\Pglstrshortpl}{\@gls@hyp@opt\@ns@Pglstrshortpl}
\newcommand*{\ns@Pglstrshortpl}[2] [] {%
  \new@ifnextchar[{\@Pglstrshortpl{#1}{#2}}{\@Pglstrshortpl{#1}{#2} []}%
}
\def\@Pglstrshortpl#1#2[#3]{%
  \ifglshasprefixplural{#2}%
  {%
    \Pglsprefix{#2}{prefixplural}%
    \@glstrshortpl{#1}{#2}[#3]%
  }%
  {\@Glsstrshortpl{#1}{#2}[#3]}%
}
\glsmfuaddmap{\pglstrshortpl}{\Pglstrshortpl}
```

\PGLSxtrshortpl All-caps is also fairly simple.

```
\newrobustcmd*{\PGLSxtrshortpl}{\@gls@hyp@opt\@ns@PGLSxtrshortpl}
\newcommand*{\ns@PGLSxtrshortpl}[2] [] {%
  \new@ifnextchar[{\@PGLSxtrshortpl{#1}{#2}}{\@PGLSxtrshortpl{#1}{#2} []}%
}
\def\@PGLSxtrshortpl#1#2[#3]{%
  \PGLSprefix{#2}{prefixplural}%
  \@GLSxtrshortpl{#1}{#2}[#3]%
}
\glsmfublocker{\PGLSxtrshortpl}
```

Long form uses prefixfirst and prefixfirstplural fields.

\pglsxtrlong No case-change.

```
\newrobustcmd*{\pglsxtrlong}{\@gls@hyp@opt\@ns@pglsxtrlong}
\newcommand*{\ns@pglsxtrlong}[2] [] {%
  \new@ifnextchar[{\@pglsxtrlong{#1}{#2}}{\@pglsxtrlong{#1}{#2} []}%
}
\def\@pglsxtrlong#1#2[#3]{%
  \pglsprefix{#2}{prefixfirst}%
  \@glsxtrlong{#1}{#2}[#3]%
}
```

\Pglxtrlong Sentence case.

```
\newrobustcmd*{\Pglxtrlong}{\@gls@hyp@opt\@ns@Pglxtrlong}
\newcommand*{\ns@Pglxtrlong}[2] [] {%
  \new@ifnextchar[{\@Pglxtrlong{#1}{#2}}{\@Pglxtrlong{#1}{#2} []}%
}
\def\@Pglxtrlong#1#2[#3]{%
  \ifglshasprefixfirst{#2}%
  {%
    \Pglsprefix{#2}{prefixfirst}%
    \@glxtrlong{#1}{#2}[#3]%
  }%
}
```

```

    {\@Glsxtrlong{#1}{#2}[#3]}%
}
\glsmfuaddmap{\pglsxtrlong}{\Pglxtrlong}

```

\PGLSxtrlong All-caps is also fairly simple.

```

\newrobustcmd*{\PGLSxtrlong}{\@gls@hyp@opt\ns@PGLSxtrlong}
\newcommand*{\ns@PGLSxtrlong}[2] [] {%
  \new@ifnextchar[{\@PGLSxtrlong{#1}{#2}}{\@PGLSxtrlong{#1}{#2} []}%
}
\def\@PGLSxtrlong#1#2[#3]{%
  \PGLSprefix{#2}{prefixfirst}%
  \@GLSxtrlong{#1}{#2}[#3]%
}
\glsmfublocker{\PGLSxtrlong}

```

Long plural.

\pglsxtrlongpl

```

\newrobustcmd*{\pglsxtrlongpl}{\@gls@hyp@opt\ns@pglsxtrlongpl}
\newcommand*{\ns@pglsxtrlongpl}[2] [] {%
  \new@ifnextchar[{\@pglsxtrlongpl{#1}{#2}}{\@pglsxtrlongpl{#1}{#2} []}%
}
\def\@pglsxtrlongpl#1#2[#3]{%
  \pglsprefix{#2}{prefixfirstplural}%
  \@glxtrlongpl{#1}{#2}[#3]%
}

```

\Pglxtrlongpl

```

\newrobustcmd*{\Pglxtrlongpl}{\@gls@hyp@opt\ns@Pglxtrlongpl}
\newcommand*{\ns@Pglxtrlongpl}[2] [] {%
  \new@ifnextchar[{\@Pglxtrlongpl{#1}{#2}}{\@Pglxtrlongpl{#1}{#2} []}%
}
\def\@Pglxtrlongpl#1#2[#3]{%
  \ifglshasprefixfirstplural{#2}%
  {%
    \Pglsprefix{#2}{prefixfirstplural}%
    \@glxtrlongpl{#1}{#2}[#3]%
  }%
  {\@Glsxtrlongpl{#1}{#2}[#3]}%
}
\glsmfuaddmap{\pglsxtrlongpl}{\Pglxtrlongpl}

```

\PGLSxtrlongpl All-caps is also fairly simple.

```

\newrobustcmd*{\PGLSxtrlongpl}{\@gls@hyp@opt\ns@PGLSxtrlongpl}
\newcommand*{\ns@PGLSxtrlongpl}[2] [] {%
  \new@ifnextchar[{\@PGLSxtrlongpl{#1}{#2}}{\@PGLSxtrlongpl{#1}{#2} []}%
}
\def\@PGLSxtrlongpl#1#2[#3]{%
  \PGLSprefix{#2}{prefixfirstplural}%
  \@GLSxtrlongpl{#1}{#2}[#3]%
}

```

```

    }
    \glsmfublocker{\PGLSxtrlongpl}

    Title commands (analogous to \glsfmtshort etc).

\pglsfmtshort
\newcommand*{\pglsfmtshort}[1]{%
  \pglsprefix{#1}{prefix}%
  \glsfmtshort{#1}%
}

\Pglsfmtshort
\newcommand*{\Pglsfmtshort}[1]{%
  \glstexorpdfstring
  {\Pglsxtrtitleshort{#1}}%
  {\glspdfsentencecase{
    \pglsprefix{#1}{prefix}%
    \glentryshort{#1}}%
  }%
}
\glsmfuaddmap{\pglsfmtshort}{\Pglsfmtshort}

\Pglsxtrtitleshort
\newrobustcmd*{\Pglsxtrtitleshort}[1]{%
  \glsxtr@title@field\Pglsxtrshort{#1}%
}

\PGLSfmtshort
\newcommand*{\PGLSfmtshort}[1]{%
  \PGLSprefix{#1}{prefix}%
  \GLSfmtshort{#1}%
}
\glsmfublocker{\PGLSfmtshort}

\pglsfmtshortpl
\newcommand*{\pglsfmtshortpl}[1]{%
  \pglsprefix{#1}{prefixplural}%
  \glsfmtshortpl{#1}%
}

\Pglsfmtshortpl
\newcommand*{\Pglsfmtshortpl}[1]{%
  \glstexorpdfstring
  {\Pglsxtrtitleshortpl{#1}}%
  {\glspdfsentencecase
  {
    \pglsprefix{#1}{prefixplural}%
    \glentryshortpl{#1}%
  }%
}

```

```

    }%
  }
  \glsmfuaddmap{\pglsfmtshortpl}{\Pglfmtshortpl}

\Pglstrtitleshortpl
  \newrobustcmd*{\Pglstrtitleshortpl}[1]{%
    \glstr@title@field\Pglstrshortpl{#1}%
  }

\PGLSfmtshortpl
  \newcommand*{\PGLSfmtshortpl}[1]{%
    \PGLSprefix{#1}{prefixplural}%
    \GLSfmtshortpl{#1}%
  }
  \glsmfublocker{\PGLSfmtshortpl}

\pglsfmtlong
  \newcommand*{\pglsfmtlong}[1]{%
    \pglsprefix{#1}{prefixfirst}%
    \glfmtlong{#1}%
  }

\Pglfmtlong
  \newcommand*{\Pglfmtlong}[1]{%
    \glstexorpdfstring
    {\Pglstrtitlelong{#1}}%
    {\glspdfsentencecase{%
      \pglsprefix{#1}{prefixfirst}%
      \glentrylong{#1}}%
    }%
  }
  \glsmfuaddmap{\pglsfmtlong}{\Pglfmtlong}

\Pglstrtitlelong
  \newrobustcmd*{\Pglstrtitlelong}[1]{%
    \glstr@title@field\Pglstrlong{#1}%
  }

\PGLSfmtlong
  \newcommand*{\PGLSfmtlong}[1]{%
    \PGLSprefix{#1}{prefixfirst}%
    \GLSfmtlong{#1}%
  }
  \glsmfublocker{\PGLSfmtlong}

\pglsfmtlongpl
  \newcommand*{\pglsfmtlongpl}[1]{%
    \pglsprefix{#1}{prefixfirstplural}%
    \glfmtlongpl{#1}%
  }

```

```

\Glsfmtlongpl
\newcommand*\Glsfmtlongpl[1]{%
  \glstexorpdfstring
  {\Pglstrtitlelongpl{#1}}%
  {\glspdfsentencecase
   {%
    \pglsprefix{#1}{prefixfirstplural}%
    \glstentrylongpl{#1}%
   }%
  }%
}
\glsmfuaddmap{\pglsfmtlongpl}{\Glsfmtlongpl}

\Pglstrtitlelongpl
\newrobustcmd*\Pglstrtitlelongpl[1]{%
  \glstr@title@field\Pglstrlongpl{#1}%
}

\PGLSfmtlongpl
\newcommand*\PGLSfmtlongpl[1]{%
  \PGLSprefix{#1}{prefixfirstplural}%
  \GLSfmtlongpl{#1}%
}
\glsmfublocker{\PGLSfmtlongpl}

```

1.10 Multi (Combined/Compound) Entries

(I'd rather call these combined or compound entries but `\cgl` is already taken.)

New to version 1.48, the commands here provide a way of referencing multiple entries as a single unit. For example, biological organisms are often referred to by their genus and species, such as *Clostridium botulinum* and *Clostridium perfringens* (where the genus is *Clostridium*). The genus is often abbreviated after first use, regardless of which species in the genus is being referenced. For example, “*Clostridium botulinum* and *C. perfringens*”. This can't be supported by any abbreviation styles unless the genus and species names are defined separately. For example:

```

%\setabbreviationstyle{long-only-short-only}
%\newabbreviation{clostridium}{C.}{Clostridium}
%\newglossaryentry{botulinum}{name={botulinum},description={}}
%\newglossaryentry{perfringens}{name={perfringens},description={}}
%

```

This means that the entries then need to be referenced using a rather cumbersome method:

```

%\gls{clostridium} \gls{botulinum} and \gls{clostridium}
%\gls{perfringens}
%

```

This section provides a command that will provide a way of defining a label that represents a combination of entries (which must all be first defined). For example:

```
%\multiglossaryentry{cbot}{clostridium,botulinum}
%
```

This label can then be referenced using `\mgls`, which internally uses `\gls` for each component. The last component in the list is considered the “main” component (not to be confused with the main glossary). If this isn’t the case, the label of the main component should be added in the optional argument before the label list. Note that the multi-label (`cbot` in this case) can’t be referenced using commands like `\gls`.

First define the general set of options that should be applied to all multi-entries. These can be set with:

```
\multiglossaryentrysetup
    \newcommand*{\multiglossaryentrysetup}[1]{\setkeys{glsxtrcombined}{#1}}

\@gls@combined@indexmain Numeric value: 0=false (don't index main component), 1=true (always index
main component), 2=first (only index main component on first use). Default:
1 (true);
    \newcommand*{\@gls@combined@indexmain}{1}
    \define@choicekey{glsxtrcombined}{indexmain}%
        [\@gls@combined@indexmain@val\@gls@combined@indexmain]
        {false,true,first}[true]{}

\@gls@combined@indexothers Numeric value: 0=false (don't index other components), 1=true (always index
other components), 2=first (only index other components on first use). Default:
2 (first);
    \newcommand*{\@gls@combined@indexothers}{2}
    \define@choicekey{glsxtrcombined}{indexothers}%
        [\@gls@combined@indexothers@val\@gls@combined@indexothers]
        {false,true,first}[true]{}

\@gls@combined@hyper Numeric value: 0=none (\mgls doesn't create a hyperlink), 1=allmain (all con-
tent hyperlinks to the main component), 2=mainonly (only the main component
has a hyperlink), 3=individual (each component has a hyperlink to their own
target). Default: 3.
    \newcommand*{\@gls@combined@hyper}{3}
    \define@choicekey{glsxtrcombined}{hyper}%
        [\@gls@combined@hyper@val\@gls@combined@hyper]
        {none,allmain,mainonly,individual,otheronly,notmainfirst,nototherfirst,notfirst}{}

\@gls@combined@encapmain Location encap value for main component (corresponding to format key in
\gls).
    \newcommand*{\@gls@combined@encapmain}{glsnumberformat}
    \define@key{glsxtrcombined}{encapmain}{%
    \renewcommand*{\@gls@combined@encapmain}{#1}%
    }
}
```

`\@gls@combined@encapothers` Location encap value for other components (corresponding to format key in `\gls`).

```

\newcommand*{\@gls@combined@encapothers}{glsnumberformat}
\define@key{glsxtrcombined}{encapothers}{%
\renewcommand*{\@gls@combined@encapothers}{#1}%
}

```

`\@gls@combined@textformat` Encapsulate entire content with the command identified by the given control sequence name.

```

\newcommand*{\@gls@combined@textformat}{@firstofone}
\define@key{glsxtrcombined}{textformat}{%
\renewcommand*{\@gls@combined@textformat}{#1}%
}

```

`\@gls@combined@category` Assign a category to the combined set.

```

\newcommand*{\@gls@combined@category}{}
\define@key{glsxtrcombined}{category}{%
\renewcommand*{\@gls@combined@category}{#1}%
}

```

Pre-options family:

```

\define@key{glsxtrcombinedpreopts}{category}{%
\renewcommand*{\@gls@combined@category}{#1}%
}

```

`\@gls@combined@mglsopts` Default options to pass to `\mgl`.

```

\newcommand*{\@gls@combined@mglsopts}{}
\define@key{glsxtrcombined}{mglsopts}{%
\renewcommand*{\@gls@combined@mglsopts}{#1}%
}
\define@key{glsxtrcombinedpreopts}{mglsopts}{%
\@gls@combined@mglsopts@do
{%
\renewcommand*{\@gls@combined@mglsopts}{#1}%
}%
}

```

`\@gls@combined@mglsopts@do`

```

\newcommand*{\@gls@combined@mglsopts@do}[1]{#1}

```

`\mgl@disable@mglsopts`

```

\newcommand*{\mgl@disable@mglsopts}{%
\let\@gls@combined@mglsopts@do\@gls@combined@mglsopts@do@not
}

```

`\mgl@enable@mglsopts`

```

\newcommand*{\mgl@enable@mglsopts}{%
\let\@gls@combined@mglsopts@do\@firstofone
}

```

```

\@gls@combined@mglsopts@do
    \newcommand*{\@gls@combined@mglsopts@do@not}[1]{%
        \PackageError{glossaries-extra}{‘mglsopts’ key not permitted inside
            ‘setup’ value}{}%
    }

\@gls@combined@firstprefix Prefix for multi-entry first use.
    \newcommand*{\@gls@combined@firstprefix}{}
    \define@key{glsxtrcombined}{firstprefix}{%
        \renewcommand*{\@gls@combined@firstprefix}{#1}%
    }

\@gls@combined@usedprefix Prefix for multi-entry subsequent first use.
    \newcommand*{\@gls@combined@usedprefix}{}
    \define@key{glsxtrcombined}{usedprefix}{%
        \renewcommand*{\@gls@combined@usedprefix}{#1}%
    }

\@gls@combined@firstsuffix Suffix for multi-entry first use.
    \newcommand*{\@gls@combined@firstsuffix}{}
    \define@key{glsxtrcombined}{firstsuffix}{%
        \renewcommand*{\@gls@combined@firstsuffix}{#1}%
    }

\@gls@combined@usedsuffix Suffix for multi-entry subsequent first use.
    \newcommand*{\@gls@combined@usedsuffix}{}
    \define@key{glsxtrcombined}{usedsuffix}{%
        \renewcommand*{\@gls@combined@usedsuffix}{#1}%
    }

\@gls@combined@firstskipmain Skip the main element on first use (multi-entry first use not element first use).
    \define@boolkey{glsxtrcombined}{firstskipmain}[true]{}
    \KV@glxtrcombined@firstskipmainfalse

\@gls@combined@firstskipothers Skip the other elements on first use (multi-entry first use not element first use).
    \define@boolkey{glsxtrcombined}{firstskipothers}[true]{}
    \KV@glxtrcombined@firstskipothersfalse

\@gls@combined@usedskipmain Skip the main element on subsequent use (multi-entry subsequent use not element subsequent use).
    \define@boolkey{glsxtrcombined}{usedskipmain}[true]{}
    \KV@glxtrcombined@usedskipmainfalse

\@gls@combined@usedskipothers Skip the other elements on subsequent use (multi-entry subsequent use not element subsequent use).
    \define@boolkey{glsxtrcombined}{usedskipothers}[true]{}
    \KV@glxtrcombined@usedskipothersfalse

```


`\@gls@combined@postlinks` Determine whether or not to use the individual element post-link hooks.

```

\newcommand*{\@gls@combined@postlinks@nr}{0}
\define@choicekey{glsxtrcombined}{postlinks}%
[\@gls@combined@postlinks@val\@gls@combined@postlinks@nr]
{none,all,notlast,mainnotlast,mainonly,othernotlast,otheronly}{}

```

`\@gls@combined@mpostlink` Determine whether or not to use the multi-entry post-link hook.

```

\newcommand*{\@gls@combined@mpostlink@nr}{1}
\define@choicekey{glsxtrcombined}{mpostlink}%
[\@gls@combined@mpostlink@val\@gls@combined@mpostlink@nr]
{false,true,firstonly,usedonly}[true]{}

```

`\@gls@combined@mpostlinkelement` Determine which element to use for the post-link hook.

```

\newcommand*{\@gls@combined@mpostlinkelement@nr}{0}
\define@choicekey{glsxtrcombined}{mpostlinkelement}%
[\@gls@combined@mpostlinkelement@val\@gls@combined@mpostlinkelement@nr]
{last,main,custom}{}

```

`\glsxtrifmulti`

```

\newcommand*{\glsxtrifmulti}[3]{\ifcsdef{@gls@combined@#1@main}{#2}{#3}}

```

`\glsxtrmultimain`

```

\newcommand*{\glsxtrmultimain}[1]{\csuse{@gls@combined@#1@main}}

```

`\glsxtrmultilist`

```

\newcommand*{\glsxtrmultilist}[1]{\csuse{@gls@combined@#1@list}}

```

`\glsxtrmultitotalelements` Total number of elements.

```

\newcommand*{\glsxtrmultitotalelements}[1]{\csuse{@gls@combined@#1@total}}

```

`\glsxtrmultimainindex` Index of main element (starting from 1). If the main element is the last element in the list then this should equal the total number of elements.

```

\newcommand*{\glsxtrmultimainindex}[1]{\csuse{@gls@combined@#1@mainindex}}

```

`\glsxtrmultilastotherindex` Index of the last non-main element.

```

\newcommand*{\glsxtrmultilastotherindex}[1]{\csuse{@gls@combined@#1@lastotherindex}}

```

`\ifmultiglossaryentryglobal` Make definitions global.

```

\newif\ifmultiglossaryentryglobal
\multiglossaryentryglobalfalse

```

`\mglselementindex` Count register to keep track of the current element index.

```

\newcount\mglselementindex

```

```

\multiglossaryentry[\langle options \rangle]{\langle multi-label \rangle}[\langle main label \rangle]
{\langle label
list \rangle}

```

`\multiglossaryentry`

Defines the label $\langle multi-label \rangle$ that can be used in `\mgl`s.

```
\newrobustcmd{\multiglossaryentry}[1][]{%
\def\@gls@combined@current@opts{#1}%
\ifnum\@glsxtr@docdefval=1\relax
\let\@multi@glossentry@donext\@defmultiglossaryentry
\else
\let\@multi@glossentry@donext\@multiglossaryentry
\fi
\@multi@glossentry@donext
}
```

`\@multiglossaryentry`

```
\newcommand*{\@multiglossaryentry}[1]{%
\def\@gls@combined@current@label{#1}%
\@multi@glossaryentry
}
```

`\@multi@glossaryentry` Check for existence.

```
\newcommand*{\@multi@glossaryentry}[2][]{%
\ifcsdef{\@gls@combined@\@gls@combined@current@label @main}%
{\PackageError{glossaries-extra}%
{Multi-entry label ‘\@gls@combined@current@label’ already defined}%
{}}%
}%
{%
\@multi@glossary@entry{#1}{#2}%
}%
}
```

`\@defmultiglossaryentry` Used if document definitions are on.

```
\newcommand*{\@defmultiglossaryentry}[1]{%
\def\@gls@combined@current@label{#1}%
\@def@multi@glossaryentry
}
```

`\@def@multi@glossaryentry` Used if document definitions are on.

```
\newcommand*{\@def@multi@glossaryentry}[2][]{%
\let\@def@multi@glossaryentry@do\@multi@glossary@entry
\ifundef\@glsxtr@docdefs@multilist
{%
\gdef\@glsxtr@docdefs@multilist{%
\listxadd
{\@glsxtr@docdefs@multilist}{\expandonce\@gls@combined@current@label}%
}%
{%
\xifinlist{\@gls@combined@current@label}{\@glsxtr@docdefs@multilist}%
{%
\PackageError{glossaries-extra}%
{Multi-entry label ‘\@gls@combined@current@label’ already defined}%
}
```

```

    {}%
    \let\@def@multi@glossaryentry@do\@gobbletwo
  }%
  {%
    \listxadd
    {\@glstr@docdefs@multilist}{\expandonce\@gls@combined@current@label}%
  }%
}%
\@def@multi@glossaryentry@do{#1}{#2}%
}

```

`\@multi@glossary@doifexists`

```
\newcommand*{\@multi@glossary@doifexists}{\glsdoifexists}
```

```

\providemultiglossaryentry[\langle options \rangle]{\langle multi-label \rangle}[\langle main
label \rangle]{\langle label
list \rangle}

```

`\providemultiglossaryentry`

Defines a multi-entry unless it has already been defined.

```

\newrobustcmd{\providemultiglossaryentry}[2] [] {%
  \def\@gls@combined@current@opts{#1}%
  \def\@gls@combined@current@label{#2}%
  \ifcsdef{\@gls@combined@\@gls@combined@current@label @main}%
  {\def\@multi@glossentry@donext{\@provide@multi@glossaryentry@noop}}%
  {%
    \ifnum\@glstr@docdefval=1\relax
    \def\@multi@glossentry@donext{\@def@multi@glossaryentry}%
    \else
    \def\@multi@glossentry@donext{\@multi@glossaryentry}%
    \fi
  }%
  \@multi@glossentry@donext
}

```

`\@multi@glossaryentry@noop` Do nothing.

```
\newcommand*{\@provide@multi@glossaryentry@noop}[2] [] {}
```

`\@multi@glossaryentry@list` List of all defined multi-entry sets.

```
\newcommand*{\@multi@glossaryentry@list}{}%
```

`\@multi@glossary@entry`

```

\newcommand*{\@multi@glossary@entry}[2] {%
  \protected@edef\@gls@combined@current@main{#1}%

```

Fully expand list.

```
\protected@edef\@gls@combined@currentlist{#2}%
```

Count items in list, check they are all defined, and find last item at the same time.

```

\mglselementindex=0\relax
\@for\@gls@tmp:=\@gls@combined@currentlist\do{%
  \advance\mglselementindex by 1\relax
  \@multi@glossary@doifexists{\@gls@tmp}{}%
  \let\@gls@combined@finalitem\@gls@tmp
  \ifdefvoid\@gls@combined@current@main
  {%
  {%
    \ifx\@gls@combined@current@main\@gls@tmp
    \ifmultiglossaryentryglobal
      \global\cslet{\@gls@combined@\@gls@combined@current@label @main}%
        \@gls@combined@current@main
      \csxdef{\@gls@combined@\@gls@combined@current@label @mainindex}%
        {\the\mglselementindex}%
    \else
      \cslet{\@gls@combined@\@gls@combined@current@label @main}%
        \@gls@combined@current@main
      \csedef{\@gls@combined@\@gls@combined@current@label @mainindex}%
        {\the\mglselementindex}%
    \fi
  \else
    \ifmultiglossaryentryglobal
      \csxdef{\@gls@combined@\@gls@combined@current@label @lastotherindex}%
        {\the\mglselementindex}%
    \else
      \csedef{\@gls@combined@\@gls@combined@current@label @lastotherindex}%
        {\the\mglselementindex}%
    \fi
  \fi
}%
}%
\ifmultiglossaryentryglobal
  \csxdef{\@gls@combined@\@gls@combined@current@label @total}%
    {\the\mglselementindex}%
\else
  \csedef{\@gls@combined@\@gls@combined@current@label @total}%
    {\the\mglselementindex}%
\fi
\ifnum\mglselementindex<2\relax
  \PackageError{glossaries-extra}{At least 2 labels required in
    multi-entry element list (\number\mglselementindex\space found)}{}%
\else
  \ifdefvoid\@gls@combined@current@main
  {%
  {%

```

If `\@gls@combined@<label>@main` hasn't been set then it wasn't included in the list.

```

\ifcsundef{@gls@combined@\@gls@combined@current@label @main}%
{\PackageError{glossaries-extra}%
{Main element '@gls@combined@current@main' not found in list}%
{The final element '@gls@combined@finalitem' will be used instead}

```

Set to empty so that the default (final element) is used instead.

```

\let@gls@combined@current@main\@empty
}%
{}%
}%
\ifdefvoid@gls@combined@current@main
{%

```

Set main to final element.

```

\ifmultiglossaryentryglobal
\global\cslet{@gls@combined@\@gls@combined@current@label @main}%
\@gls@combined@finalitem
\global\csletcs{@gls@combined@\@gls@combined@current@label @mainindex}%
{@gls@combined@\@gls@combined@current@label @total}%
\csxdef{@gls@combined@\@gls@combined@current@label @lastotherindex}%
{\the\numexpr\mglselementindex-1 }%
\else
\cslet{@gls@combined@\@gls@combined@current@label @main}%
\@gls@combined@finalitem
\csletcs{@gls@combined@\@gls@combined@current@label @mainindex}%
{@gls@combined@\@gls@combined@current@label @total}%
\csedef{@gls@combined@\@gls@combined@current@label @lastotherindex}%
{\the\numexpr\mglselementindex-1 }%
\fi
}%
{}%
\ifmultiglossaryentryglobal

```

Globally define element list.

```

\global\cslet{@gls@combined@\@gls@combined@current@label @list}%
\@gls@combined@currentlist

```

Globally define options.

```

\protected\csxdef{@gls@combined@\@gls@combined@current@label @options}%
{\@gls@combined@current@opts}%

```

Global conditional definition.

```

\expandafter\@ifdefinable
\csname if@gls@combined@\@gls@combined@current@label @flag\endcsname
{\expandafter\global\expandafter
\newif\csname if@gls@combined@\@gls@combined@current@label @flag\endcsname}%
\expandafter\global
\csname @gls@combined@\@gls@combined@current@label @flagfalse\endcsname
\else

```

Locally define element list.

```

\cslet{@gls@combined@\@gls@combined@current@label @list}%
\@gls@combined@currentlist

```

Locally define options.

```
\protected\csedef{@gls@combined@\@gls@combined@current@label @options}%
{\@gls@combined@current@opts}%
```

Local conditional definition.

```
\newboolean{@gls@combined@\@gls@combined@current@label @flag}%
\csname @gls@combined@\@gls@combined@current@label @flagfalse\endcsname
\fi
\fi
\writemultiglossentry
{\@gls@combined@current@opts}{\@gls@combined@current@label}%
{\csuse{@gls@combined@\@gls@combined@current@label @main}}{#2}%
```

Append label to list.

```
\ifmultiglossaryentryglobal
\ifdefempty\@multi@glossaryentry@list
{\let\@multi@glossaryentry@list\@gls@combined@current@label}%
{%
\ea\pto\@multi@glossaryentry@list{,\@expandonce\@gls@combined@current@label}%
}%
\else
\ifdefempty\@multi@glossaryentry@list
{\global\let\@multi@glossaryentry@list\@gls@combined@current@label}%
{%
\xappto\@multi@glossaryentry@list{,\@expandonce\@gls@combined@current@label}%
}%
\fi
}
```

```
\@glsxtr@multientry{<options>}{<multilabel>}{<main>}{<list>}
```

\@glsxtr@multientry

Information for aux file. Useful for bib2gls and also for docdef.

```
\newcommand*{@glsxtr@multientry}[4]{%
\ifnum\@glsxtr@docdefval=1\relax
\bgroup
\def\@gls@combined@current@opts{#1}%
\def\@gls@combined@current@label{#2}%
\let\@multi@glossary@doifexists\@secondoftwo
\let\writemultiglossentry\@gobblefour
\multiglossaryentryglobaltrue
\@multi@glossary@entry{#3}{#4}%
\egroup
\fi
}
```

\writemultiglossentry This can be redefined to do nothing if the information isn't required.

```
\newcommand*{\writemultiglossentry}[4]{%
\protected@write\@auxout{}{\string\@glsxtr@multientry{#1}{#2}{#3}{#4}}%
}
```

`\ifmglsused` Determines whether or not the multi-entry set has been referenced by commands like `\mgls` or `\mglsname`.

```
\newcommand*{\ifmglsused}[3]{%
  \ifbool{@gls@combined@#1@flag}{#2}{#3}%
}
```

`\mglsunset` Unset the flag.

```
\newcommand*{\mglsunset}[1]{%
  \gls@ifnotmeasuring
  {%
    \glstrifmulti{#1}{\@mglsunset{#1}}%
    {%
      \glstrundefaction{Multi entry ‘#1’ hasn’t been defined}%
      {You need to define ‘#1’ with \string\multiglossaryentry}%
    }%
  }%
}
```

`\@mglsunset`

```
\newcommand*{\@mglsunset}[1]{%
  \expandafter\global\csname @gls@combined@#1@flagtrue\endcsname
}
```

`\mglsreset` Unset the flag.

```
\newcommand*{\mglsreset}[1]{%
  \gls@ifnotmeasuring
  {%
    \glstrifmulti{#1}{\@mglsreset{#1}}%
    {%
      \glstrundefaction{Multi entry ‘#1’ hasn’t been defined}%
      {You need to define ‘#1’ with \string\multiglossaryentry}%
    }%
  }%
}
```

`\@mglsreset`

```
\newcommand*{\@mglsreset}[1]{%
  \expandafter\global\csname @gls@combined@#1@flagfalse\endcsname
}
```

`\mglslocalunset` Unset the flag.

```
\newcommand*{\mglslocalunset}[1]{%
  \gls@ifnotmeasuring
  {%
    \glstrifmulti{#1}{\@mglslocalunset{#1}}%
    {%
      \glstrundefaction{Multi entry ‘#1’ hasn’t been defined}%
      {You need to define ‘#1’ with \string\multiglossaryentry}%
    }%
  }%
```

```

    }%
  }

\@mglslocalunset
  \newcommand*{\@mglslocalunset}[1]{%
    \csname @gls@combined@#1@flagtrue\endcsname
  }

\mglslocalreset Unset the flag.
  \newcommand*{\mglslocalreset}[1]{%
    \gls@ifnotmeasuring
    {%
      \glsxtrifmulti{#1}{\@mglslocalreset{#1}}%
      {%
        \glsxtrundefaction{Multi entry ‘#1’ hasn’t been defined}%
        {You need to define ‘#1’ with \string\multiglossaryentry}%
      }%
    }%
  }

\@mglslocalreset
  \newcommand*{\@mglslocalreset}[1]{%
    \csname @gls@combined@#1@flagfalse\endcsname
  }

\mglsunsetall Unset all.
  \newcommand*{\mglsunsetall}{%
    \@for\@mgls@thislabel:=\@multi@glossaryentry@list\do{\mglsunset\@mgls@thislabel}%
  }%

\mglsresetall Reset all.
  \newcommand*{\mglsresetall}{%
    \@for\@mgls@thislabel:=\@multi@glossaryentry@list\do{\mglsreset\@mgls@thislabel}%
  }%

\mglsSetName{<multi-label>}{<new main>}

\mglsSetMain
  Allow the main label to be changed (local).
  \newrobustcmd{\mglsSetMain}[2]{%
    \ifcsundef{@gls@combined@#1@main}%
    {\PackageError{glossaries-extra}{Multi-entry label ‘#1’ not defined}{}%
    {%
      \protected@edef\@gls@combined@current@main{#2}%
      \letcs\@gls@combined@currentlist{\@gls@combined@#1@list}%
    }}
    Check that the given label is in the list of elements and update main and last
    other element index.
    \mglselementindex=0\relax

```



```

\count@=0\relax
\@for\@gls@tmp:=\@gls@combined@currentlist\do{%
  \advance\mglselementindex by 1\relax
  \ifx\@gls@combined@current@main\@gls@tmp
    \count@=\mglselementindex\relax
    \let\@gls@combined@finalitem\@gls@tmp
    \ifmultiglossaryentryglobal
      \global\cslet{\@gls@combined@#1@main}\@gls@combined@current@main
      \csxdef{\@gls@combined@#1@mainindex}{\the\mglselementindex}%
    \else
      \cslet{\@gls@combined@#1@main}\@gls@combined@current@main
      \csedef{\@gls@combined@#1@mainindex}{\the\mglselementindex}%
    \fi
  \else
    \ifmultiglossaryentryglobal
      \csxdef{\@gls@combined@#1@lastotherindex}{\the\mglselementindex}%
    \else
      \csedef{\@gls@combined@#1@lastotherindex}{\the\mglselementindex}%
    \fi
  \fi
}%
\ifnum\count@=0\relax
  \PackageError{glossaries-extra}{Label ‘#2’ is not in ‘#1’ set
    (\@gls@combined@currentlist)}{ }%

```

Default to final item.

```

\ifmultiglossaryentryglobal
  \global\cslet{\@gls@combined@#1@main}\@gls@combined@finalitem
  \csxdef{\@gls@combined@#1@mainindex}{\the\mglselementindex}%
  \csxdef{\@gls@combined@#1@lastotherindex}{%
    \number\numexpr\mglselementindex-1 }%
  \else
    \cslet{\@gls@combined@#1@main}\@gls@combined@finalitem
    \csedef{\@gls@combined@#1@mainindex}{\the\mglselementindex}%
    \csedef{\@gls@combined@#1@lastotherindex}{%
      \number\numexpr\mglselementindex-1 }%
    \fi
  \fi
}%
}

```

```
\mglSetOptions{<multi-label>}{<new options>}
```

\mglSetOptions

Allow the options to be changed (local). No expansion is applied.

```

\newrobustcmd{\mglSetOptions}[2]{%
  \ifcsundef{\@gls@combined@#1@main}%
  {\PackageError{glossaries-extra}{Multi-entry label ‘#1’ not defined}{}}%
  {\csdef{\@gls@combined@#1@options}{#2}%

```

```
}%
}
```

```
\mglAddOptions{<multi-label>}{<extra options>}
```

`\mglAddOptions`

Allow the options to be changed (local). No expansion is applied.

```
\newrobustcmd{\mglAddOptions}[2]{%
  \ifcsundef{@gls@combined@#1@main}%
  {\PackageError{glossaries-extra}{Multi-entry label ‘#1’ not defined}{}}%
  {%
    \ifcempty{@gls@combined@#1@options}%
    {\csdef{@gls@combined@#1@options}{#2}}%
    {\csappto{@gls@combined@#1@options}{, #2}}%
  }%
}
```

Options for `\mgl`:

`\@mgl@all` Options to apply to all elements.

```
\newcommand*{\@mgl@all}{}
\define@key{mgl}{all}{\renewcommand*{\@mgl@all}{#1}}
```

`\@mgl@main` Options to apply to the main element only.

```
\newcommand*{\@mgl@main}{}
\define@key{mgl}{main}{\renewcommand*{\@mgl@main}{#1}}
```

`\@mgl@others` Options to apply to the other (no main) elements.

```
\newcommand*{\@mgl@others}{}
\define@key{mgl}{others}{\renewcommand*{\@mgl@others}{#1}}
```

`\@mgl@setup` Options to apply to `\multiglossaryentrysetup`.

```
\newcommand*{\@mgl@setup}{}
\define@key{mgl}{setup}{%
  \@mgl@setup@do{\renewcommand*{\@mgl@setup}{#1}}%
}
```

`\@mgl@setup@do`

```
\newcommand*{\@mgl@setup@do}[1]{#1}
```

`\@mgl@setup@do@not`

```
\newcommand*{\@mgl@setup@do@not}[1]{%
  \PackageError{glossaries-extra}{‘setup’ key not permitted inside
  ‘mglsopts’ value}{}}%
}
```

`\mgl@disable@setup`

```
\newcommand*{\mgl@disable@setup}{%
  \let\@mgl@setup@do\@mgl@setup@do@not
}
```

```

\mgls@enable@setup
    \newcommand*{\mgls@enable@setup}{%
        \let\@mgls@setup@do\@firstofone
    }

\@mgls@unsetaction
    \newcommand\@mgls@unsetaction{0}
    \define@choicekey{mgls}{multiunset}[\@mgls@unsetaction@val\@mgls@unsetaction]%
        {global,local,none}{}

\ifKV@mgls@presetlocal
    \define@boolkey{mgls}{presetlocal}[true]{}
    \KV@mgls@presetlocalfalse

\@mgls@hyper
    \newcommand*{\@mgls@hyper}{}
    \define@choicekey{mgls}{hyper}[\@mgls@hyper@val\@mgls@hyper@nr]{true,false}[true]%
    {%
        \renewcommand*{\@mgls@hyper}{hyper=#1}%
        \ifnum\@mgls@hyper@nr=1\relax
            \let\@mgls@hyperlink\@secondoftwo
        \else
            \let\@mgls@hyperlink\@@mgls@hyperlink
        \fi
    }

\@@mgls@hyperlink
    \newcommand*{\@@mgls@hyperlink}[2]{%
        \ifx\@glslink\glsdonohyperlink
            #2%
        \else
            \glsxtr@org@dohyperlink{\glslinkprefix#1}{#2}%
        \fi
    }

\@mgls@hyperlink
    \let\@mgls@hyperlink\@@mgls@hyperlink

\mglsforelements
    \mglsforelements{\langle multi-label \rangle}{\langle cs \rangle}{\langle body \rangle}

    \newcommand*{\mglsforelements}[3]{%
        \expandafter\@for\expandafter#2\expandafter:\expandafter
            =csname @gls@combined@#1@list@endcsname\do{#3}%
    }

\mglsforotherelements
    \mglsforotherelements{\langle multi-label \rangle}{\langle cs \rangle}{\langle body \rangle}

```

```

\newcommand*{\mglsotherelements}[3]{%
  \expandafter\@for\expandafter#2\expandafter:\expandafter
    =\csname @gls@combined@#1@list\endcsname\do
    {\expandafter\ifdefequal\csname @gls@combined@#1@main\endcsname{#2}-{#3}}%
}

\mglsetothers
\newcommand*{\mglsetothers}[1]{%
  \mglsotherelements{#1}{\@gls@tmp}{\glsset{\@gls@tmp}}%
}

\mglsetlocalothers
\newcommand*{\mglsetlocalothers}[1]{%
  \mglsotherelements{#1}{\@gls@tmp}{\glslocalset{\@gls@tmp}}%
}

\mglsetreset
\newcommand*{\mglsetreset}[1]{%
  \ifKV@mgl@presetlocal
    \glslocalreset{#1}%
  \else
    \glsreset{#1}%
  \fi
}

\mglsetunset
\newcommand*{\mglsetunset}[1]{%
  \ifKV@mgl@presetlocal
    \glslocalunset{#1}%
  \else
    \glsunset{#1}%
  \fi
}

\@mgl@resetall
\newcommand*{\@mgl@resetall}{}
\define@choicekey{mgl}{resetall}%
[\@mgl@resetall@val\@mgl@resetall@nr]{false,true}[true]%
{%
  \ifcase\@mgl@resetall@nr\relax
    \renewcommand*{\@mgl@resetall}{}%
  \or
    \renewcommand*{\@mgl@resetall}{%
      \@for\@gls@resetlabel:=\mglcurrentlist\do{\mglsetreset\@gls@resetlabel}}%
    \renewcommand*{\@mgl@unsetall}{}%
  \fi
}

```

```

\@mgls@resetmain

\newcommand*{\@mgls@resetmain}{}
\define@choicekey{mgls}{resetmain}
[\@mgls@resetmain@val\@mgls@resetmain@nr]{false,true}[true]%
{%
\ifcase\@mgls@resetmain@nr\relax
\renewcommand*{\@mgls@resetmain}{}%
\or
\renewcommand*{\@mgls@resetmain}{\mglselementreset\mglscurrentmainlabel}%
\renewcommand*{\@mgls@unsetmain}{}%
\fi
}

```

```

\@mgls@resetothers

\newcommand*{\@mgls@resetothers}{}
\define@choicekey{mgls}{resetothers}
[\@mgls@resetothers@val\@mgls@resetothers@nr]{false,true}[true]%
{%
\ifcase\@mgls@resetothers@nr\relax
\renewcommand*{\@mgls@resetothers}{}%
\or
\renewcommand*{\@mgls@resetothers}{%
\@for\@gls@resetlabel:=\mglscurrentlist\do{%
\ifx\@gls@resetlabel\mglscurrentmainlabel
\else
\mglselementreset\@gls@resetlabel
\fi
}%
}%
\renewcommand*{\@mgls@unsetothers}{}%
\fi
}

```

```

\@mgls@unsetall

\newcommand*{\@mgls@unsetall}{}
\define@choicekey{mgls}{unsetall}%
[\@mgls@unsetall@val\@mgls@unsetall@nr]{false,true}[true]%
{%
\ifcase\@mgls@unsetall@nr\relax
\renewcommand*{\@mgls@unsetall}{}%
\or
\renewcommand*{\@mgls@unsetall}{%
\@for\@gls@unsetlabel:=\mglscurrentlist\do{\mglselementunset\@gls@unsetlabel}}%
\renewcommand*{\@mgls@resetall}{}%
\fi
}

```

```

\@mgls@unsetmain

\newcommand*{\@mgls@unsetmain}{}

```

```

\define@choicekey{mgl}{unsetmain}
[ \@mgl@unsetmain@val \@mgl@unsetmain@nr ] {false,true} [true] %
{ %
  \ifcase \@mgl@unsetmain@nr \relax
    \renewcommand*{ \@mgl@unsetmain } { } %
  \or
    \renewcommand*{ \@mgl@unsetmain } { \mglselementunset \mglcurrentmainlabel } %
    \renewcommand*{ \@mgl@resetmain } { } %
  \fi
}

```

`\@mgl@unsetothers`

```

\newcommand*{ \@mgl@unsetothers } { }
\define@choicekey{mgl}{unsetothers}
[ \@mgl@unsetothers@val \@mgl@unsetothers@nr ] {false,true} [true] %
{ %
  \ifcase \@mgl@unsetothers@nr \relax
    \renewcommand*{ \@mgl@unsetothers } { } %
  \or
    \renewcommand*{ \@mgl@unsetothers } { %
      \@for \@gls@unsetlabel := \mglcurrentlist \do { %
        \ifx \@gls@unsetlabel \mglcurrentmainlabel
          \else
            \mglselementunset \@gls@unsetlabel
          \fi
        } %
      } %
    \renewcommand*{ \@mgl@resetothers } { } %
  \fi
}

```

`\glxtr@setup@docurrent` Set up the commands to determine whether or not to do the current element.

```

\newcommand{ \glxtr@setup@docurrent } { %

```

`\mglcurrentlabel` expands to the label of the current element. Should this element be skipped?

```

\ifx \mglcurrentlabel \mglcurrentmainlabel

```

Main element. Should it be skipped?

```

\mglisfirstuse
{ %
  \ifKV@glxtrcombined@firstskipmain
    \let \@mgl@do@current@element \gobble
  \else
    \let \@mgl@do@current@element \@firstofone
  \fi
} %
{ %
  \ifKV@glxtrcombined@usedskipmain
    \let \@mgl@do@current@element \gobble

```

```

        \else
        \let\@mgls@do@current@element\@firstofone
        \fi
    }%
\else
Other element. Should it be skipped?
\mglsisfirstuse
{%
    \ifKV@glstrcombined@firstskipothers
    \let\@mgls@do@current@element\@gobble
    \else
    \let\@mgls@do@current@element\@firstofone
    \fi
}%
{%
    \ifKV@glstrcombined@usedskipothers
    \let\@mgls@do@current@element\@gobble
    \else
    \let\@mgls@do@current@element\@firstofone
    \fi
}%
\fi
}

```

`\glstr@mgls@checklastelement` If the last element is skipped, `\mglsiflast` needs adjusting. The first argument should be either "first" or "used". The second argument is the multi-element label.

```

\newcommand*{\glstr@mgls@checklastelement}[2]{%
    \ifbool{KV@glstrcombined@#1skipmain}%
    {%
        \ifbool{KV@glstrcombined@#1skipothers}%
        {%

```

This condition has already been checked for.

```

    }%
    {%

```

Main skipped. The last item will be the last other element.

```

        \ifnum\mglsindex=\glstrmultilastotherindex{#2}\relax
        \let\mglsiflast\@firstoftwo
        \else
        \let\mglsiflast\@secondoftwo
        \fi
    }%
}%
{%

```

Main not skipped.

```

    \ifbool{KV@glstrcombined@#1skipothers}%
    {%

```

Others skipped. The main element is the only item.

```
\ifnum\mglsselementindex=\glxstrmultimainindex{#2}\relax
\let\mglsiflast\@firstoftwo
\else
\let\mglsiflast\@secondoftwo
\fi
}%
{%
```

None skipped. This isn't the last element.

```
\let\mglsiflast\@secondoftwo
}%
}%
}
```

`\glxstrmglsWarnAllSkipped` Warning if all elements are skipped. The first argument is the warning message, the second argument is the inserted content (final optional argument), the third command is the encapsulation command (which may be a hyperlink).

```
\newcommand{\glxstrmglsWarnAllSkipped}[3]{%
\GlossariesExtraWarning{#1}%
#3{#2}%
}
```

`\glxstr@mgl@applyopts`

```
\newcommand*{\glxstr@mgl@applyopts}[1]{%
\edef\@mgl@doptions{\noexpand\setkeys*{mgl}{\expandonce#1}}%
\@mgl@doptions}
```

Append any unknown options to all.

```
\ifdefvoid\XKV@rm{}\eappto\@mgl@all{\expandonce\XKV@rm}}%
```

If setup key has been used, check for pre-option keys:

```
\ifdefvoid\@mgl@setup
{}%
{%
\edef\@mgl@doptions{%
\noexpand\setkeys*{glxstrcombinedpreopts}{\expandonce\@mgl@setup}}%
\mgl@disable@mglsopts
\@mgl@doptions
\mgl@enable@mglsopts}
```

Save remaining setup options.

```
\ifx\@mgl@setuptoptions\empty
\let\@mgl@setuptoptions\XKV@rm
\else
\eappto\@mgl@setuptoptions{\expandonce\XKV@rm}%
\fi
}%
```

Apply gls unset/reset options.

```
\@mgl@resetall
```



```

\@mgl@unsetall
\@mgl@resetmain
\@mgl@unsetmain
\@mgl@resetothers
\@mgl@unsetothers

```

Disable.

```

\let\@mgl@resetall\@empty
\let\@mgl@resetmain\@empty
\let\@mgl@resetothers\@empty
\let\@mgl@unsetall\@empty
\let\@mgl@unsetmain\@empty
\let\@mgl@unsetothers\@empty

```

First use flags.

```

\ifmgl@used\mgl@currentmultilabel
{\let\mgl@sisfirstuse\@secondoftwo}%
{\let\mgl@sisfirstuse\@firstoftwo}%
}

```

\@firstofthree

```

\providecommand{\@firstofthree}[3]{#1}

```

\@secondofthree

```

\providecommand{\@secondofthree}[3]{#2}

```

\@thirdofthree

```

\providecommand{\@thirdofthree}[3]{#3}

```

The main internal command for referencing multi-entries:

```

\glxtr@mgl@inner{<options>}{<label>}{<insert>}{<first
cs>}{<not first cs>}{<main first cs>}{<main other cs>}

```

\glxtr@mgl@inner

```

\newcommand*\glxtr@mgl@inner[7]{%
\let\mgl@lastmainlabel\@empty
\let\mgl@siflastmainwasfirstuse\@firstoftwo
\let\mgl@siflastmainwasplural\@secondoftwo
\let\mgl@siflastmaincapscase\@firstofthree
\let\mgl@siflastmainskipped\@firstoftwo
\bgroup
\ifcsundef{@gls@combined@#2@main}%
{%
\glxtrundefaction{Multi entry ‘#2’ hasn’t been defined}%
{You need to define ‘#2’ with \string\multiglossaryentry}%
\gdef\@mgl@post@hookdefs{%
\protected@edef\mgl@lastmultilabel{#2}%
\let\mgl@swasfirstuse\@firstoftwo
\let\mgl@lastcategory\@empty

```

```

\let\mglsiflastelementskipped\@firstoftwo
\let\mglsiflastelementwasfirstuse\@firstoftwo
\let\mglsiflastelementwasplural\@secondoftwo
\let\mglsiflastelementcapscase\@firstofthree
\let\mglslastelementlabel\@empty
\let\mgls@do@postlinkhook\relax
}%
}%
{%

```

Initialise hooks in case component entries haven't been defined (which may happen with bib2gls).

```

\let\glstrifwasfirstuse\@firstoftwo
\let\glsifplural\@secondoftwo
\let\glscapscase\@firstofthree

```

Save information for hooks.

```

\protected@edef\mglscurrentmultilabel{#2}%
\letcs\mglscurrentmainlabel{@gls@combined@#2@main}%
\letcs\mglscurrentlist{@gls@combined@#2@list}%
\letcs\mglscurrentoptions{@gls@combined@#2@options}%

```

Initialise (may be changed if multiunset is present):

```

\ifmglsused\mglscurrentmultilabel
{\let\mglsisfirstuse\@secondoftwo}%
{\let\mglsisfirstuse\@firstoftwo}%

```

Only obtain pre-option keys:

```

\edef\@mgls@doptions{%
  \noexpand\setkeys*{glstrcombinedpreopts}{\expandonce\mglscurrentoptions}}%
\@mgls@doptions

```

Save remaining setup options.

```

\let\@mgls@setuptoptions\XKV@rm

```

Apply \mgls options.

```

\mgls@disable@setup
\ifdefvoid{@gls@combined@mglsopts}
{}%
{\glstr@mgls@applyopts{@gls@combined@mglsopts}%
\mgls@enable@setup

```

Apply options provided in #1.

```

\ifstrempy{#1}{-}{\def\@mgls@options{#1}\glstr@mgls@applyopts\@mgls@options}%

```

Check for attribute settings.

```

\ifx{@gls@combined@category}\empty

```

No category

```

\else

```

Attribute options:

```

\glshascategoryattribute{\@gls@combined@category}{multioptions}%

```

```
{%
\letcs\@mgl@attroptions{\glxtr@categoryattr@@\@gl@combined@category
@multioptions}%
```

Only obtain pre-option keys:

```
\let\@gl@combined@mglsopts\@empty
\edef\@mgl@doptions{%
\noexpand\setkeys*{\glxtrcombinedpreopts}{\expandonce\@mgl@attroptions}}%
\@mgl@doptions
```

Append remaining options:

```
\eappto\@mgl@setoptions{,\expandonce\XKV@rm}%
\ifx\@gl@combined@mglsopts\@empty
\else
```

mgl options found:

```
\let\@mgl@setup\@empty
\mgl@disable@setup
\glxtr@mgl@applyopts\@gl@combined@mglsopts
\mgl@enable@setup
\fi
}%
{}%
\fi
```

Apply setup options.

```
\edef\@mgl@doptions{%
\noexpand\setkeys{\glxtrcombined}{\expandonce\@mgl@setoptions}}%
\@mgl@doptions
```

Provide local user-level access to category:

```
\let\mglcurrentcategory\@gl@combined@category
```

Should the entire content be a hyperlink?

```
\ifnum\@gl@combined@hyper=1\relax
\def\@mgl@combinedlink{\@mgl@hyperlink{\mglcurrentmainlabel}}%
\else
\def\@mgl@combinedlink{\@firstofone}%
\fi
```

Entire content encapsulator.

```
\def\@gl@combined@encapsulator##1{%
\@mgl@combinedlink{\csuse{\@gl@combined@textformat}{##1}}}%
```

Initialise.

```
\let\@mgl@do@current@element\@firstofone
```

Check if all elements are being skipped.

```
\mglsisfirstuse
{%
\ifKV@glxtrcombined@firstskipmain
\ifKV@glxtrcombined@firstskipothers
```

Just do the warning and insert. This will ignore the loop.

```

\let\@gls@org@combined@encapsulator\@gls@combined@encapsulator
\def\@gls@combined@encapsulator##1{%
  \glstrmglWarnAllSkipped{All elements skipped for
    first use of multi-entry '#2'#{#3}%
    {\@gls@org@combined@encapsulator}%
  }%
  \let\@mgl@do@current@element\@gobble
\fi
\fi
}%
{%
  \ifKV@glstrcombined@usedskipmain
    \ifKV@glstrcombined@usedskipothers

```

Just do the warning and insert. This will ignore the loop.

```

\let\@gls@org@combined@encapsulator\@gls@combined@encapsulator
\def\@gls@combined@encapsulator##1{%
  \glstrmglWarnAllSkipped{All elements skipped for
    subsequent use of multi-entry '#2'#{#3}%
    {\@gls@org@combined@encapsulator}%
  }%
  \let\@mgl@do@current@element\@gobble
\fi
\fi
}%

```

Determine prefix and suffix.

```

\mglsisfirstuse
{%
  \let\mglscurrentprefix\@gls@combined@firstprefix
  \let\mglscurrentsuffix\@gls@combined@firstsuffix
}%
{%
  \let\mglscurrentprefix\@gls@combined@usedprefix
  \let\mglscurrentsuffix\@gls@combined@usedsuffix
}%

```

Set up post-link hook used after current scope.

```

\xdef\@mgl@post@hookdefs{%
  \noexpand\def\noexpand\mglslastmultilabel{\expandonce\mglscurrentmultilabel}%
  \noexpand\def\noexpand\mglslastcategory{\mglscurrentcategory}%
}%
\ifx\@mgl@do@current@element\@gobble
  \gappto\@mgl@post@hookdefs{%
    \let\mglslastelementskipped\@firstoftwo
    \let\mglslastelementlabel\@empty
    \let\mglslastelementwasfirstuse\@firstoftwo
    \let\mglslastelementwasplural\@secondoftwo
    \let\mglslastelementcapscase\@firstofthree
  }%

```

```

\fi
\mglsisfirstuse
{%
  \gappto\@mglspost@hookdefs{\let\mglswasfirstuse\@firstoftwo}%
Determine if the multi-entry post-link hook should be applied.
  \ifcase\@gls@combined@mpostlink@nr\relax
mpostlink=false.
    \gappto\@mglspost@hookdefs{\let\mgl@do@postlinkhook\relax}%
  \or
mpostlink=true.
    \ifcase\@gls@combined@mpostlinkelement@nr\relax
      \gappto\@mglspost@hookdefs{\let\mgl@do@postlinkhook\mglslastelementpostlinkhook}%
    \or
      \gappto\@mglspost@hookdefs{\let\mgl@do@postlinkhook\mglslastmainpostlinkhook}%
    \or
      \gappto\@mglspost@hookdefs{\let\mgl@do@postlinkhook\mglscustompostlinkhook}%
    \fi
  \or
mpostlink=firstonly.
    \ifcase\@gls@combined@mpostlinkelement@nr\relax
      \gappto\@mglspost@hookdefs{\let\mgl@do@postlinkhook\mglslastelementpostlinkhook}%
    \or
      \gappto\@mglspost@hookdefs{\let\mgl@do@postlinkhook\mglslastmainpostlinkhook}%
    \or
      \gappto\@mglspost@hookdefs{\let\mgl@do@postlinkhook\mglscustompostlinkhook}%
    \fi
  \or
mpostlink=usedonly.
    \gappto\@mglspost@hookdefs{\let\mgl@do@postlinkhook\relax}%
  \fi
}%
{%
  \gappto\@mglspost@hookdefs{\let\mglswasfirstuse\@secondoftwo}%
Determine if the multi-entry post-link hook should be applied.
  \ifcase\@gls@combined@mpostlink@nr\relax
mpostlink=false.
    \gappto\@mglspost@hookdefs{\let\mgl@do@postlinkhook\relax}%
  \or
mpostlink=true.
    \ifcase\@gls@combined@mpostlinkelement@nr\relax
      \gappto\@mglspost@hookdefs{\let\mgl@do@postlinkhook\mglslastelementpostlinkhook}%
    \or
      \gappto\@mglspost@hookdefs{\let\mgl@do@postlinkhook\mglslastmainpostlinkhook}%
    \or
      \gappto\@mglspost@hookdefs{\let\mgl@do@postlinkhook\mglscustompostlinkhook}%

```

```

        \fi
    \or
mpostlink=firstonly.
        \gappto\@mgls@post@hookdefs{\let\mgls@do@postlinkhook\relax}%
    \or
mpostlink=usedonly.
        \ifcase\@gls@combined@mpostlinkelement@nr\relax
        \gappto\@mgls@post@hookdefs{\let\mgls@do@postlinkhook\mglslastelementpostlinkhook}%
        \or
        \gappto\@mgls@post@hookdefs{\let\mgls@do@postlinkhook\mglslastmainpostlinkhook}%
        \or
        \gappto\@mgls@post@hookdefs{\let\mgls@do@postlinkhook\mglscustompostlinkhook}%
        \fi
    \fi
}%

Save current post-link hook.
\let\mgls@org@postlinkhook\glspostlinkhook

Prefix.
\mglsprefix

Initialise last element label (for \mglsuffix).
\let\mglslastelementlabel\@empty
\@gls@combined@encapsulator
{%

Save previous label.
\def\@mgls@previouslabel{}%
\mglselementindex=0\relax
\@for\mglscurrentlabel:=\mglscurrentlist\do{%
\advance\mglselementindex by 1\relax
\glxtr@setup@docurrent

Is this the last element?
\ifx\@xfor@nextelement\@nnil
\let\mglsiflast\@firstoftwo
\else
\let\mglsiflast\@secondoftwo

Are any elements being skipped?
\mglsisfirstuse
{%
\glxtr@mgls@checklastelement{first}{#2}%
}%
{%
\glxtr@mgls@checklastelement{used}{#2}%
}%
\fi

Should the element post-link hook be used?
\ifcase\@gls@combined@postlinks@nr\relax

```

```

postlinks=none
    \let\glspostlinkhook\relax
\or
postlinks=all
    \let\glspostlinkhook\mglorg@postlinkhook
\or
postlinks=notlast
    \mgliflast
    {%
        \let\glspostlinkhook\relax
    }%
    {%
        \let\glspostlinkhook\mglorg@postlinkhook
    }%
\or
postlinks=mainnotlast
    \ifx\mglcurrentlabel\mglcurrentmainlabel
        \mgliflast
        {%
            \let\glspostlinkhook\relax
        }%
        {%
            \let\glspostlinkhook\mglorg@postlinkhook
        }%
    \else
        \let\glspostlinkhook\relax
    \fi
\or
postlinks=mainonly
    \ifx\mglcurrentlabel\mglcurrentmainlabel
        \let\glspostlinkhook\mglorg@postlinkhook
    \else
        \let\glspostlinkhook\relax
    \fi
\or
postlinks=othernotlast
    \ifx\mglcurrentlabel\mglcurrentmainlabel
        \let\glspostlinkhook\relax
    \else
        \mgliflast
        {%
            \let\glspostlinkhook\relax
        }%
        {%
            \let\glspostlinkhook\mglorg@postlinkhook
        }%
    \fi
\or

```

```

\fi
\or
postlinks=otheronly
\ifx\mglscurrentlabel\mglscurrentmainlabel
\let\glspostlinkhook\relax
\else
\let\glspostlinkhook\mgls@org@postlinkhook
\fi
\fi

```

Save the last element for the multi-entry post-link hook.

```

\mglsiflast
{%
\xappto\@mgls@post@hookdefs{%
\noexpand\def\noexpand\mglslastelementlabel
{\expandonce\mglscurrentlabel}}%
}%
{}%

```

Do current element:

```

\@mgls@do@current@element
{%

```

Pre element hook.

```

\mglselementprehook

```

Is this the first use of the current element?

```

\GlsXtrIfUnusedOrUndefined{\mglscurrentlabel}%
{\let\@mgls@current@iffirstuse\@firstoftwo}%
{\let\@mgls@current@iffirstuse\@secondoftwo}%
\ifx\mglscurrentlabel\mglscurrentmainlabel

```

Main element. Location encap option:

```

\edef\@mgls@current@options{format=\@gls@combined@encapmain}%

```

Indexing option:

```

\ifcase\@gls@combined@indexmain
\appto\@mgls@current@options{,noindex}%
\or
\appto\@mgls@current@options{,noindex=false}%
\or
\@mgls@current@iffirstuse
{\appto\@mgls@current@options{,noindex=false}}%
{\appto\@mgls@current@options{,noindex}}%
\fi

```

Hyperlink option:

```

\ifcase\@gls@combined@hyper\relax
\appto\@mgls@current@options{,hyper=false}% none
\or
\appto\@mgls@current@options{,hyper=false}% allmain
\or

```



```

\appto\@mgl@current@options{,\@mgl@hyper}% mainly
\or
\appto\@mgl@current@options{,\@mgl@hyper}% individual
\or
\appto\@mgl@current@options{,hyper=false}% otheronly
\or
\mgl@isfirstuse
{%
\appto\@mgl@current@options{,hyper=false}% notmainfirst
}%
{%
\appto\@mgl@current@options{,\@mgl@hyper}% notmainfirst
}%
\or
\appto\@mgl@current@options{,\@mgl@hyper}% nototherfirst
\or
\mgl@isfirstuse
{%
\appto\@mgl@current@options{,hyper=false}% notfirst
}%
{%
\appto\@mgl@current@options{,\@mgl@hyper}% notfirst
}%
\fi

```

Append all and then main:

```

\appto\@mgl@current@options{,\@mgl@all,\@mgl@main}%
\else

```

Other element. Location encaps option:

```

\edef\@mgl@current@options{format=\@gls@combined@encapothers}%

```

Indexing option:

```

\ifcase\@gls@combined@indexothers\relax
\appto\@mgl@current@options{,noindex}%
\or
\appto\@mgl@current@options{,noindex=false}%
\or
\@mgl@current@iffirstuse
{\appto\@mgl@current@options{,noindex=false}}%
{\appto\@mgl@current@options{,noindex}}%
\fi

```

Hyperlink option:

```

\ifcase\@gls@combined@hyper\relax
\appto\@mgl@current@options{,hyper=false}% none
\or
\appto\@mgl@current@options{,hyper=false}% allmain
\or
\appto\@mgl@current@options{,hyper=false}% mainly
\or

```

```

\eaopto\@mgl@current@options{,\@mgl@hyper}% individual
\or
\eaopto\@mgl@current@options{,\@mgl@hyper}% otheronly
\or
\eaopto\@mgl@current@options{,\@mgl@hyper}% notmainfirst
\or
\mgl@isfirstuse
{%
\eaopto\@mgl@current@options{,hyper=false}% nototherfirst
}%
{%
\eaopto\@mgl@current@options{,\@mgl@hyper}% nototherfirst
}%
\or
\mgl@isfirstuse
{%
\eaopto\@mgl@current@options{,hyper=false}% notfirst
}%
{%
\eaopto\@mgl@current@options{,\@mgl@hyper}% notfirst
}%
\fi

```

Append all and then others:

```

\eaopto\@mgl@current@options{,\@mgl@all,\@mgl@others}%
\fi

```

Is this the first element?

```

\ifx\@mgl@previouslabel\empty
\ifx\mgl@currentlabel\mgl@currentmainlabel
\let\@mgl@cs#6\relax
\else
\let\@mgl@cs#4\relax
\fi
\else

```

Not the first element so add separator.

```

\@mgl@previous@iffirstuse
{%
\@mgl@current@iffirstuse
{\glscombinedfirstsepfirst{\@mgl@previouslabel}{\mgl@currentlabel}}%
{\glscombinedfirstsep{\@mgl@previouslabel}{\mgl@currentlabel}}%
}%
{%
\@mgl@current@iffirstuse
{\glscombinedsepfirst{\@mgl@previouslabel}{\mgl@currentlabel}}%
{\glscombinedsep{\@mgl@previouslabel}{\mgl@currentlabel}}%
}%
\ifx\mgl@currentlabel\mgl@currentmainlabel
\let\@mgl@cs#7\relax
\else

```

```

\let\@mgls@cs#5\relax
\fi
\fi

```

Is this the last element?

```

\mglsiflast
{\expandafter\@mgls@cs\expandafter{\@mgls@current@options}{\mglscurrentlabel}[\#3]}%
{\expandafter\@mgls@cs\expandafter{\@mgls@current@options}{\mglscurrentlabel}[]}%

```

Is this the main element? If so, save information for post-link hook.

```

\ifx\mglscurrentlabel\mglscurrentmainlabel
\gappto\@mgls@post@hookdefs{%
\noexpand\def\noexpand\mglslastmainlabel
{\expandonce\mglscurrentmainlabel}%
}%
\glstrifwasfirstuse
{%
\gappto\@mgls@post@hookdefs{\let\mglsiflastmainwasfirstuse\@firstoftwo}%
}%
{%
\gappto\@mgls@post@hookdefs{\let\mglsiflastmainwasfirstuse\@secondoftwo}%
}%
\glsifplural
{%
\gappto\@mgls@post@hookdefs{\let\mglsiflastmainwasplural\@firstoftwo}%
}%
{%
\gappto\@mgls@post@hookdefs{\let\mglsiflastmainwasplural\@secondoftwo}%
}%
\glscapscase
{%
\gappto\@mgls@post@hookdefs{%
\let\mglsiflastmaincapscase\@firstofthree
}%
}%
{%
\gappto\@mgls@post@hookdefs{%
\let\mglsiflastmaincapscase\@secondofthree
}%
}%
{%
\gappto\@mgls@post@hookdefs{%
\let\mglsiflastmaincapscase\@thirdofthree
}%
}%
\fi
\let\@mgls@previouslabel\mglscurrentlabel
\let\@mgls@previous@iffirstuse\@mgls@current@iffirstuse
}%

```

Post element hook.

```

\mglselementposthook
}%
\ifx\mglslastmainlabel\@empty
\gappto\@mgls@post@hookdefs{\let\mglsiflastmainskipped\@firstoftwo}%
\else
\gappto\@mgls@post@hookdefs{\let\mglsiflastmainskipped\@secondoftwo}%
\fi

```

Encapsulator may introduce grouping so check here.

```

\ifx\@mgls@do@current@element\@gobble
\gappto\@mgls@post@hookdefs{\let\mglsiflastelementskipped\@firstoftwo}%
\else
\gappto\@mgls@post@hookdefs{\let\mglsiflastelementskipped\@secondoftwo}%
\fi
\glstrifwasfirstuse
{%
\gappto\@mgls@post@hookdefs{\let\mglsiflastelementwasfirstuse\@firstoftwo}%
}%
{%
\gappto\@mgls@post@hookdefs{\let\mglsiflastelementwasfirstuse\@secondoftwo}%
}%
\glsifplural
{%
\gappto\@mgls@post@hookdefs{\let\mglsiflastelementwasplural\@firstoftwo}%
}%
{%
\gappto\@mgls@post@hookdefs{\let\mglsiflastelementwasplural\@secondoftwo}%
}%
\glscapscase
{%
\gappto\@mgls@post@hookdefs{%
\let\mglsiflastelementcapscase\@firstofthree
}%
}%
{%
\gappto\@mgls@post@hookdefs{%
\let\mglsiflastelementcapscase\@secondofthree
}%
}%
{%
\gappto\@mgls@post@hookdefs{%
\let\mglsiflastelementcapscase\@thirdofthree
}%
}%
}%

```

Suffix needs post-link hook commands.

```

\@mgls@post@hookdefs
\mglssuffix

```

Unset multi-entry first use flag after current scope.

```

\ifcase\@mgls@unsetaction\relax
\zappto\@mgls@post@hookdefs{%
\noexpand\mglsunset{\expandonce\mglscurrentmultilabel}}%
\or
\zappto\@mgls@post@hookdefs{%
\noexpand\mglslocalunset{\expandonce\mglscurrentmultilabel}}%
\fi
}%
\glstrmglswrite{#2}%
\egroup
\@mgls@post@hookdefs
\mgls@do@postlinkhook
}

\mglscustompostlinkhook

\newcommand*{\mglscustompostlinkhook}{}

\mglslastelementpostlinkhook

\newcommand*{\mglslastelementpostlinkhook}{%
\let\glstrifwasfirstuse\mglsiflastelementwasfirstuse
\let\glstifplural\mglsiflastelementwasplural
\let\glscapscase\mglsiflastelementcapscase
\let\glslabel\mglslastelementlabel
\glspostlinkhook
}

\mglslastmainpostlinkhook

\newcommand*{\mglslastmainpostlinkhook}{%
\let\glstrifwasfirstuse\mglsiflastmainwasfirstuse
\let\glstifplural\mglsiflastmainwasplural
\let\glscapscase\mglsiflastmaincapscase
\let\glslabel\mglslastmainlabel
\glspostlinkhook
}

\mglsdefcategoryprefix

\newcommand*{\mglsdefcategoryprefix}[2]{%
\csdef{mglsprefix@#1}{#2}%
}

\mglsdescategoryprefix

\newcommand*{\mglsdescategoryprefix}[3]{%
\ifcsdef{mglsprefix@#1}{#2}{#3}%
}

\mglsusecategoryprefix

\newcommand*{\mglsusecategoryprefix}[1]{%
\csuse{mglsprefix@#1}%
}

```

`\mglsprefix`

```
\newcommand*{\mglsprefix}{%
\ifdefempty\mglscurrentcategory
{\mglscurrentprefix}%
{%
\mglshascategoryprefix{\mglscurrentcategory}%
{\mglsecategoryprefix{\mglscurrentcategory}}%
{\mglscurrentprefix}%
}%
}
```

`\mgldefcategorysuffix`

```
\newcommand*{\mgldefcategorysuffix}[2]{%
\csdef{mglssuffix@#1}{#2}%
}
```

`\mglshascategorysuffix`

```
\newcommand*{\mglshascategorysuffix}[3]{%
\ifcsdef{mglssuffix@#1}{#2}{#3}%
}
```

`\mglsecategorysuffix`

```
\newcommand*{\mglsecategorysuffix}[1]{%
\csuse{mglssuffix@#1}%
}
```

`\mglssuffix`

```
\newcommand*{\mglssuffix}{%
\ifdefempty\mglscurrentcategory
{\ifdefempty{\mglscurrentsuffix}{\space(\mglscurrentsuffix)}}%
{%
\mglshascategorysuffix{\mglscurrentcategory}%
{\mglsecategorysuffix{\mglscurrentcategory}}%
{\ifdefempty{\mglscurrentsuffix}{\space(\mglscurrentsuffix)}}%
}%
}
```

`\mglselementprehook`

```
\newcommand*{\mglselementprehook}{}
```

`\mglselementposthook`

```
\newcommand*{\mglselementposthook}{}
```

Separators.

`\glscombinedsep` Separator between two elements that have been marked as used. This takes the two element labels as arguments.

```
\newcommand*{\glscombinedsep}[2]{%
\glsattribute{#1}{combinedsep}%
}
```

```

    {\glsgetattribute{#1}{combinedsep}}%
    { }%
}

```

`\glscombinedfirstsepfirst` Separator following and preceding a first use.

```

\newcommand*{\glscombinedfirstsepfirst}[2]{%
  \glshasattribute{#1}{combinedfirstsepfirst}%
  {\glsgetattribute{#1}{combinedfirstsepfirst}}%
  {\glscombinedsep{#1}{#2}}%
}

```

`\glscombinedfirstsep` Separator following a first use.

```

\newcommand*{\glscombinedfirstsep}[2]{%
  \glshasattribute{#1}{combinedfirstsep}%
  {\glsgetattribute{#1}{combinedfirstsep}}%
  {\glscombinedsep{#1}{#2}}%
}

```

`\glscombinedsepfirst` Separator preceding a first use.

```

\newcommand*{\glscombinedsepfirst}[2]{%
  \glshasattribute{#1}{combinedsepfirst}%
  {\glsgetattribute{#1}{combinedsepfirst}}%
  {\glscombinedsep{#1}{#2}}%
}

```

`\glssetcombinedsepabbrvnbs` Provide shortcut for using non-breakable space following an abbreviation that has already been used.

```

\newcommand*{\glssetcombinedsepabbrvnbs}{%
  \renewcommand*{\glscombinedsep}[2]{%
    \glshasattribute{##1}{combinedsep}%
    {\glsgetattribute{##1}{combinedsep}}%
    {\ifglshasshort{##1}{~}{ }}%
  }%
  \renewcommand*{\glscombinedsepfirst}[2]{%
    \glshasattribute{##1}{combinedsepfirst}%
    {\glsgetattribute{##1}{combinedsepfirst}}%
    {\ifglshasshort{##1}{~}{ }}%
  }%
  \renewcommand*{\glscombinedfirstsep}[2]{%
    \glshasattribute{##1}{combinedfirstsep}%
    {\glsgetattribute{##1}{combinedfirstsep}}%
    { }%
  }%
  \renewcommand*{\glscombinedfirstsepfirst}[2]{%
    \glshasattribute{##1}{combinedfirstsepfirst}%
    {\glsgetattribute{##1}{combinedfirstsepfirst}}%
    { }%
  }%
}

```

`\glssetcombinedsepabbrvnone` Provide shortcut for using nothing if either on next use are abbreviations (otherwise use space).

```
\newcommand*\glssetcombinedsepabbrvnone{%
\renewcommand*\glscombinedsep}[2]{%
\glsattribute{##1}{combinedsep}%
{\glsgetattribute{##1}{combinedsep}}%
{\ifglshasshort{##1}{ }\ifglshasshort{##2}{ }{ } }%
}%
\renewcommand*\glscombinedsepfirst}[2]{%
\glsattribute{##1}{combinedsepfirst}%
{\glsgetattribute{##1}{combinedsepfirst}}%
{\ifglshasshort{##1}{ }\ifglshasshort{##2}{ }{ } }%
}%
\renewcommand*\glscombinedfirstsep}[2]{%
\glsattribute{##1}{combinedfirstsep}%
{\glsgetattribute{##1}{combinedfirstsep}}%
{\ifglshasshort{##2}{ }\ifglshasshort{##3}{ }{ } }%
}%
\renewcommand*\glscombinedfirstsepfirst}[2]{%
\glsattribute{##1}{combinedfirstsepfirst}%
{\glsgetattribute{##1}{combinedfirstsepfirst}}%
{ }%
}%
}
```

`\glssetcombinedsepnarrow` Measures both.

```
\newcommand*\glssetcombinedsepnarrow}[2]{%
\renewcommand*\glscombinedsep}[2]{%
\glsattribute{##1}{combinedsep}%
{\glsgetattribute{##1}{combinedsep}}%
{%
\ifglshasshort{##1}%
{\glsmeasurewidth{\dimen@}{\glsentryshort{##1}}}%
{\glsmeasurewidth{\dimen@}{\glsentrytext{##1}}}%
\ifdim\dimen@<#1\relax
#2%
\else
\ifglshasshort{##2}%
{\glsmeasurewidth{\dimen@}{\glsentryshort{##2}}}%
{\glsmeasurewidth{\dimen@}{\glsentrytext{##2}}}%
\ifdim\dimen@<#1\relax
#2%
\else
\space
\fi
\fi
}%
}%
\renewcommand*\glscombinedsepfirst}[2]{%
```



```

\glshasattribute{##1}{combinedsepfirst}%
{\glsggetattribute{##1}{combinedsepfirst}}%
{%
  \ifglshasshort{##1}%
  {\glsmmeasurewidth{\dimen@}{\glsentryshort{##1}}}%
  {\glsmmeasurewidth{\dimen@}{\glsentrytext{##1}}}%
  \ifdim\dimen@<#1\relax
  #2%
  \else
  \ifhaslong{##2}%
  {\glsmmeasurewidth{\dimen@}{\glsentrylong{##2}}}%
  {\glsmmeasurewidth{\dimen@}{\glsentryfirst{##2}}}%
  \ifdim\dimen@<#1\relax
  #2%
  \else
  \space
  \fi
  \fi
}%
}%
\renewcommand*{\glsccombinedfirstsep}[2]{%
\glshasattribute{##1}{combinedfirstsep}%
{\glsggetattribute{##1}{combinedfirstsep}}%
{%
  \ifhaslong{##1}%
  {\glsmmeasurewidth{\dimen@}{\glsentrylong{##1}}}%
  {\glsmmeasurewidth{\dimen@}{\glsentryfirst{##1}}}%
  \ifdim\dimen@<#1\relax
  #2%
  \else
  \ifglshasshort{##2}%
  {\glsmmeasurewidth{\dimen@}{\glsentryshort{##2}}}%
  {\glsmmeasurewidth{\dimen@}{\glsentrytext{##2}}}%
  \ifdim\dimen@<#1\relax
  #2%
  \else
  \space
  \fi
  \fi
}%
}%
\renewcommand*{\glsccombinedfirstsepfirst}[2]{%
\glshasattribute{##1}{combinedfirstsepfirst}%
{\glsggetattribute{##1}{combinedfirstsepfirst}}%
{%
  \ifhaslong{##1}%
  {\glsmmeasurewidth{\dimen@}{\glsentrylong{##1}}}%
  {\glsmmeasurewidth{\dimen@}{\glsentryfirst{##1}}}%
  \ifdim\dimen@<#1\relax
  #2%

```

```

\else
  \ifhaslong{##2}%
    {\glsmeasurewidth{\dimen@}{\glsentrylong{##2}}}%
    {\glsmeasurewidth{\dimen@}{\glsentryfirst{##2}}}%
    \ifdim\dimen@<#1\relax
      #2%
    \else
      \space
    \fi
  \fi
}%
}%
}

```

`\@glsxtr@mglswrite` Write information to the aux file for bib2gls to pick up, but only need to do it once per label since it only indicates which multi-entry has been referenced without any additional information.

```

\newcommand{\glsxtr@mglswrite}[1]{%
  \ifx\@glsxtr@record@setting\@glsxtr@record@setting@off
  \else
    \protected@edef\@glsxtr@mglslabel{#1}%
    \ifdef\@glsxtr@mglssreflist
      {%
        \expandafter\DTLifinlist\expandafter{\@glsxtr@mglslabel}%
        {\@glsxtr@mglssreflist}{}%
        {%
          \xappto\@glsxtr@mglssreflist{,\expandonce\@glsxtr@mglslabel}%
          \if@mglswriteseparaterefs
            \protected@write\@auxout{}{\string\@glsxtr@mglssrefs{#1}}%
          \fi
        }%
      }%
    {%
      \global\let\@glsxtr@mglssreflist\@glsxtr@mglslabel
      \if@mglswriteseparaterefs
        \protected@write\@auxout{}{\string\@glsxtr@mglssrefs{#1}}%
      \else

```

Bug fix #262: `\immediate\protected@write` doesn't work in end document hook when tikz loaded. No real need for `\protected@write` as `\@glsxtr@mglssreflist` is just a comma-separated list of labels, but use `\expandonce` in case labels contain UTF-8 characters.

```

      \AtEndDocument{\immediate\write\@auxout
        {\string\@glsxtr@mglssrefs{\expandonce{\@glsxtr@mglssreflist}}}}%
      \fi
      \@mglswriteseparateref@cond
    }%
  \fi
}

```

```

\@glxtr@mglrefs
    \newcommand{\@glxtr@mglrefs}[1]{}

\if@mgl@writesepraterefs If this conditional is changed, it must be done before the first instance of any
\mgl-like command.
    \newif\if@mgl@writesepraterefs \@mgl@writesepraterefsfalse

\mglWriteSeparateRefsTrue
    \newcommand{\mglWriteSeparateRefsTrue}{\global\@mgl@writesepraterefstrue}

\mglWriteSeparateRefsFalse
    \newcommand{\mglWriteSeparateRefsFalse}{\global\@mgl@writesepraterefsfalse}

\sable@writeseprateref@cond
    \newcommand*{\@mgl@disable@writeseprateref@cond}{%
        \gdef\mglWriteSeparateRefsTrue{\PackageError{glossaries-extra}%
            {Too late to use \string\mglWriteSeparateRefsTrue}%
            {\string\mglWriteSeparateRefsTrue\space can only be used before
            the first instance of any \string\mgl-like command}}%
        \gdef\mglWriteSeparateRefsFalse{\PackageError{glossaries-extra}%
            {Too late to use \string\mglWriteSeparateRefsFalse}%
            {\string\mglWriteSeparateRefsFalse\space can only be used before
            the first instance of any \string\mgl-like command}}%
    }

\glxtr@newmgl
    \newcommand{\glxtr@newmgl}[6][]{%
        \edef\@glxtr@newmgl@do{%
            \noexpand\newrobustcmd*{\expandonce{\csname #2\endcsname}}%
            {\noexpand\@gl@hyp@opt\expandonce{\csname ns@glxtr@#2\endcsname}}%
            \noexpand\newcommand*{\expandonce{\csname ns@glxtr@#2\endcsname}}[2][]{%
                \noexpand\new@ifnextchar[%
                    {\expandonce{\csname glxtr@#2\endcsname}{####1}{####2}}%
                    {\expandonce{\csname glxtr@#2\endcsname}{####1}{####2}[]}%
                }%
            \noexpand\def\expandonce{\csname glxtr@#2\endcsname}####1####2[####3]{%
                \noexpand\@glxtr@mgl@linkdefs{\unexpanded{#1}}%
                \noexpand\def\noexpand\glxtrcurrentmglscsname{#2}%
                \noexpand\glxtr@mgl@inner{####1}{####2}{####3}%
                {\noexpand#3}{\noexpand#4}{\noexpand#5}{\noexpand#6}%
            }%
        }%
        \@glxtr@newmgl@do
        \ifx\@glxtr@record@setting\@glxtr@record@setting@off
        \else

```

Provide a way for bib2gls to recognise the command (this will make it easier to add extra commands without having to modify bib2gls).

```

        \ifdef\@glxtr@mglslitelist

```

```

        {\xappto\@glsxtr@mglslikelist{,#2}}%
        {%
            \gdef\@glsxtr@mglslikelist{#2}%
            \AtEndDocument{\immediate\protected@write\@auxout{}%
                {\string\@glsxtr@mglslslike{\@glsxtr@mglslikelist}}}%
        }%
    \fi
}

\@glsxtr@mglsl@linkdefs

\newcommand{\@glsxtr@mglsl@linkdefs}[1]{%
    \ifstrempy{#1}%
    {%
        \let\glsxtrifwasglslike\@firstoftwo
        \def\glsxtrcurrentfield{}%
    }%
    {%
        \let\glsxtrifwasglslike\@secondoftwo
        \def\glsxtrcurrentfield{#1}%
    }%
}

\@glsxtr@mglslslike

\newcommand*{\@glsxtr@mglslslike}[1]{%

    \GlsXtrMglsOrGls{\langle mgl s cs \rangle}{\langle gl s cs \rangle}{\langle modifier \rangle}[\langle options \rangle]
    {\langle label \rangle}[\langle insert \rangle]

\GlsXtrMglsOrGls

\newcommand*{\GlsXtrMglsOrGls}[2]{%
    \def\@glsxtr@mglsl@or@glsl@mcs{#1}%
    \def\@glsxtr@mglsl@or@glsl@gcs{#2}%
    \@ifstar{\s@GlsXtrMglsOrGls}%
    {%
        \@ifnextchar+{\@firstoftwo{\p@GlsXtrMglsOrGls}}%
        {%
            \ifdefempty\@glsl@alt@hyp@opt@char\@GlsXtrMglsOrGls\alt@GlsXtrMglsOrGls
        }%
    }%
}

\alt@GlsXtrMglsOrGls

\newcommand*{\alt@GlsXtrMglsOrGls}{%
    \expandafter\@ifnextchar\@glsl@alt@hyp@opt@char
    {\@firstoftwo{\@alt@GlsXtrMglsOrGls}}{\@GlsXtrMglsOrGls}%
}

```

`\@GlsXtrMglsOrGls`

```
\newcommand*{\@GlsXtrMglsOrGls}[2][{}]{%
  \glstrifmulti{#2}%
  {\@glstr@mglso@r@glsmcs[#1]{#2}}%
  {\@glstr@mglso@r@glsgcs[#1]{#2}}%
}
```

`\s@GlsXtrMglsOrGls`

```
\newcommand*{\s@GlsXtrMglsOrGls}[2][{}]{%
  \glstrifmulti{#2}%
  {\@glstr@mglso@r@glsmcs*[#1]{#2}}%
  {\@glstr@mglso@r@glsgcs*[#1]{#2}}%
}
```

`\p@GlsXtrMglsOrGls`

```
\newcommand*{\p@GlsXtrMglsOrGls}[2][{}]{%
  \glstrifmulti{#2}%
  {\@glstr@mglso@r@glsmcs+[#1]{#2}}%
  {\@glstr@mglso@r@glsgcs+[#1]{#2}}%
}
```

`\@alt@GlsXtrMglsOrGls`

```
\newcommand*{\@alt@GlsXtrMglsOrGls}[2][{}]{%
  \glstrifmulti{#2}%
  {\expandafter\@glstr@mglso@r@glsmcs\@glso@alt@hyp@opt@char[#1]{#2}}%
  {\expandafter\@glstr@mglso@r@glsgcs\@glso@alt@hyp@opt@char[#1]{#2}}%
}
```

`\mgls`

`\mgls[<options>]{<label>}[<insert>]`

Use `\gls` for all elements.

```
\glstr@newmgls{mgls}{\@gls@}{\@gls@}{\@gls@}{\@gls@}%
```

`\mglspl`

`\mglspl[<options>]{<label>}[<insert>]`

Use `\glspl` for all elements.

```
\glstr@newmgls{mglspl}{\@glspl@}{\@glspl@}{\@glspl@}{\@glspl@}%
```

`\mglsmainpl`

`\mglsmainpl[<options>]{<label>}[<insert>]`

Only use `\glspl` for the main element, otherwise use `\gls`.

```
\glstr@newmgls{mglsmainpl}{\@gls@}{\@gls@}{\@glspl@}{\@glspl@}%
```

\Mgls

`\Mgls[<options>]{<label>}[<insert>]`

Use \Gls for first element and \gls for others.

```
\glstr@newmgls{Mgls}{\@Gls@}{\@gls@}{\@Gls@}{\@gls@}%  
\glsmfuaddmap{\mgls}{\Mgls}
```

\Mglspl

`\Mglspl[<options>]{<label>}[<insert>]`

Use \Glspl for first element and \glspl for others.

```
\glstr@newmgls{Mglspl}{\@Glspl@}{\@glspl@}{\@Glspl@}{\@glspl@}%  
\glsmfuaddmap{\mglspl}{\Mglspl}
```

\Mglsmainpl

`\Mglsmainpl[<options>]{<label>}[<insert>]`

Upper case the first element, no case change for others. Use plural for the main element only.

```
\glstr@newmgls{Mglsmainpl}{\@Gls@}{\@gls@}{\@Glspl@}{\@glspl@}%  
\glsmfuaddmap{\mglsmainpl}{\Mglsmainpl}
```

\MGls

`\MGls[<options>]{<label>}[<insert>]`

Use \Gls for all elements.

```
\glstr@newmgls{MGls}{\@Gls@}{\@Gls@}{\@Gls@}{\@Gls@}%  
\glsmfublocker{\MGls}
```

\MGlspl

`\MGlspl[<options>]{<label>}[<insert>]`

Use \Glspl for all elements.

```
\glstr@newmgls{MGlspl}{\@Glspl@}{\@Glspl@}{\@Glspl@}{\@Glspl@}%  
\glsmfublocker{\MGlspl}
```

\MGlsmainpl

`\MGlsmainpl[<options>]{<label>}[<insert>]`

Start all elements with upper case. Only use plural for main element.

```
\glstr@newmgls{MGlsmainpl}{\@Gls@}{\@Gls@}{\@Glspl@}{\@Glspl@}%  
\glsmfublocker{\MGlsmainpl}
```

\MGLS

`\MGLS[<options>]{<label>}[<insert>]`

Use \GLS for all elements.

```
\glxtr@newmgl{s}{MGLS}{\@GLS@}{\@GLS@}{\@GLS@}{\@GLS@}%
\glsmfublocker{\MGLS}
```

`\MGLSp1[⟨options⟩]{⟨label⟩}[⟨insert⟩]`

`\MGLSp1`

Use \GLSp1 for all elements.

```
\glxtr@newmgl{s}{MGLSp1}{\@GLSp1@}{\@GLSp1@}{\@GLSp1@}{\@GLSp1@}%
\glsmfublocker{\MGLSp1}
```

`\MGLSmainp1[⟨options⟩]{⟨label⟩}[⟨insert⟩]`

`\MGLSmainp1`

Upper case all elements. Only use plural for main element.

```
\glxtr@newmgl{s}{MGLSmainp1}{\@GLS@}{\@GLS@}{\@GLSp1@}{\@GLSp1@}%
\glsmfublocker{\MGLSmainp1}
```

`\@glslongortext@`

```
\def\@glslongortext#1#2[#3]{%
  \ifglshaslong{#2}{\@glxtrlong{#1}{#2}[#3]}{\@glstext@{#1}{#2}[#3]}%
}
```

`\@glsshortortext@`

```
\def\@glsshortortext#1#2[#3]{%
  \ifglshasshort{#2}{\@glxtrshort{#1}{#2}[#3]}{\@glstext@{#1}{#2}[#3]}%
}
```

`\@glsfullorfirst@`

```
\def\@glsfullorfirst#1#2[#3]{%
  \ifglshasshort{#2}{\@glxtr@full{#1}{#2}[#3]}{\@glsfirst@{#1}{#2}[#3]}%
}
```

`\@Glslongortext@`

```
\def\@Glslongortext#1#2[#3]{%
  \ifglshaslong{#2}{\@Glsxtrlong{#1}{#2}[#3]}{\@Glstext@{#1}{#2}[#3]}%
}
```

`\@Glsshortortext@`

```
\def\@Glsshortortext#1#2[#3]{%
  \ifglshasshort{#2}{\@Glsxtrshort{#1}{#2}[#3]}{\@Glstext@{#1}{#2}[#3]}%
}
```

`\@Glsfullorfirst@`

```
\def\@Glsfullorfirst#1#2[#3]{%
  \ifglshasshort{#2}{\@Glsxtr@full{#1}{#2}[#3]}{\@Glsfirst@{#1}{#2}[#3]}%
}
```

<code>\mglsshort</code>	<div><code>\mglsshort[<i>\langle options \rangle</i>]{<i>\langle label \rangle</i>}[<i>\langle insert \rangle</i>]</code></div> <p>Use short or text for all elements.</p> <pre>\glxtr@newmglshort{mglsshort}% {\@glsshortortext}{\@glsshortortext}{\@glsshortortext}{\@glsshortortext}%</pre>
<code>\mglslong</code>	<div><code>\mglslong[<i>\langle options \rangle</i>]{<i>\langle label \rangle</i>}[<i>\langle insert \rangle</i>]</code></div> <p>Use long or text for all elements.</p> <pre>\glxtr@newmgls[long]{mglslong}% {\@glslongortext}{\@glslongortext}{\@glslongortext}{\@glslongortext}%</pre>
<code>\mglsfull</code>	<div><code>\mglsfull[<i>\langle options \rangle</i>]{<i>\langle label \rangle</i>}[<i>\langle insert \rangle</i>]</code></div> <p>Use full or first for all elements.</p> <pre>\glxtr@newmgls[first]{mglsfull}% {\@glsfuallorfirst}{\@glsfuallorfirst}{\@glsfuallorfirst}{\@glsfuallorfirst}%</pre>
<code>\Mglsshort</code>	<div><code>\Mglsshort[<i>\langle options \rangle</i>]{<i>\langle label \rangle</i>}[<i>\langle insert \rangle</i>]</code></div> <p>Use short or text for all elements with initial cap on first element.</p> <pre>\glxtr@newmglshort{Mglsshort}% {\@Glsshortortext}{\@Glsshortortext}{\@Glsshortortext}{\@Glsshortortext}% \glsmfuaddmap{\mglsshort}{\Mglsshort}</pre>
<code>\Mglslong</code>	<div><code>\Mglslong[<i>\langle options \rangle</i>]{<i>\langle label \rangle</i>}[<i>\langle insert \rangle</i>]</code></div> <p>Use long or text for all elements with initial cap on first element.</p> <pre>\glxtr@newmgls[long]{Mglslong}% {\@Glslongortext}{\@Glslongortext}{\@Glslongortext}{\@Glslongortext}% \glsmfuaddmap{\mglslong}{\Mglslong}</pre>
<code>\Mglsfull</code>	<div><code>\Mglsfull[<i>\langle options \rangle</i>]{<i>\langle label \rangle</i>}[<i>\langle insert \rangle</i>]</code></div> <p>Use full or first for all elements with initial cap on first element.</p> <pre>\glxtr@newmgls[first]{Mglsfull}% {\@Glsfuallorfirst}{\@Glsfuallorfirst}{\@Glsfuallorfirst}{\@Glsfuallorfirst}% \glsmfuaddmap{\mglsfull}{\Mglsfull}</pre>

`\mglsname` `\mglsname[<options>]{<label>}[<insert>]`

Use name for all elements.

```
\glstr@newmgls[name]{mglsname}%
{\@glsname@}{\@glsname@}{\@glsname@}{\@glsname@}%
```

`\Mglsname` `\Mglsname[<options>]{<label>}[<insert>]`

Use name for all elements with initial cap on first element.

```
\glstr@newmgls[name]{Mglsname}%
{\@Glsname@}{\@glsname@}{\@Glsname@}{\@glsname@}%
\glsmfuaddmap{\mglsname}{\Mglsname}
```

`\MGlsname` `\MGlsname[<options>]{<label>}[<insert>]`

Use name for all elements with initial cap on all elements.

```
\glstr@newmgls[name]{MGlsname}%
{\@Glsname@}{\@Glsname@}{\@Glsname@}{\@Glsname@}%
\glsmfublocker{\MGlsname}
```

`\@glssymbolorgls`

```
\def\@glssymbolorgls#1#2[#3]{%
\ifglshassymbol{#2}{\@glssymbol@{#1}{#2}[#3]}{\@gls@{#1}{#2}[#3]}%
}
```

`\@glssymbolorGls`

```
\def\@glssymbolorGls#1#2[#3]{%
\ifglshassymbol{#2}{\@glssymbol@{#1}{#2}[#3]}{\@Gls@{#1}{#2}[#3]}%
}
```

`\mglssymbol` `\mglssymbol[<options>]{<label>}[<insert>]`

Use `\glssymbol` if the symbol key is set otherwise use `\gls`.

```
\glstr@newmgls[symbol]{mglssymbol}%
{\@glssymbolorgls}{\@glssymbolorgls}{\@glssymbolorgls}{\@glssymbolorgls}%
```

`\Mglssymbol` `\Mglssymbol[<options>]{<label>}[<insert>]`

As above but initial the first element if it's not a symbol.

```
\glstr@newmgls[symbol]{Mglssymbol}%
{\@glssymbolorGls}{\@glssymbolorgls}{\@glssymbolorGls}{\@glssymbolorgls}%
\glsmfuaddmap{\mglssymbol}{\Mglssymbol}
```

`\MGlssymbol[$\langle options \rangle$]{ $\langle label \rangle$ }[$\langle insert \rangle$]`

As above but initial each element if it's not a symbol.

```
\glxtr@newmgl[symbol]{MGlssymbol}%
{\@glssymbolorGls}{\@glssymbolorGls}{\@glssymbolorGls}{\@glssymbolorGls}%
\glsmfublocker{\MGlssymbol}
```

`\mglsfield`

```
\newcommand{\mglsfield}{useri}
```

`\@glsfildorgls`

```
\def\@glsfildorgls#1#2[#3]{%
\glxtrifhasfield{\mglsfield}{#2}%
{\@glsdisp[#1]{#2}{\glscurrentfieldvalue#3}}%
{\@glso{#1}{#2}[#3]}%
}
```

`\@Glsfildorgls`

```
\def\@Glsfildorgls#1#2[#3]{%
\glxtrifhasfield{\mglsfield}{#2}%
{\@glsdisp[#1]{#2}{%
\expandafter\glssentencecase\expandafter{\glscurrentfieldvalue#3}}}%
{\@GlsO{#1}{#2}[#3]}%
}
```

`\mglsusefield[$\langle options \rangle$]{ $\langle label \rangle$ }[$\langle insert \rangle$]`

Use the field given by `\mglsfield`.

```
\glxtr@newmgl[\mglsfield]{mglsusefield}%
{\@glsfildorgls}{\@glsfildorgls}{\@glsfildorgls}{\@glsfildorgls}%
\glsmfuaddmap{\mglsusefield}{\Mglsusefield}
```

`\Mglsusefield[$\langle options \rangle$]{ $\langle label \rangle$ }[$\langle insert \rangle$]`

As above but use initial cap for first element only.

```
\glxtr@newmgl[\mglsfield]{Mglsusefield}%
{\@Glsfildorgls}{\@Glsfildorgls}{\@Glsfildorgls}{\@Glsfildorgls}%
\glsmfuaddmap{\mglsusefield}{\Mglsusefield}
```

`\MGlusefield[$\langle options \rangle$]{ $\langle label \rangle$ }[$\langle insert \rangle$]`

As above but use initial cap for all elements.

```
\glxtr@newmgl[\mglsfield]{MGlusefield}%
{\@Glsfildorgls}{\@Glsfildorgls}{\@Glsfildorgls}{\@Glsfildorgls}%
\glsmfublocker{\MGlusefield}
```

Use commands provided by `glossaries-prefix` if it has been loaded.

```
\mpglsWarning
\newcommand*{\mpglsWarning}{%
  \GlossariesExtraWarning{glossaries-prefix.sty is required for
    \string\mpgls\space family of commands}%
}

\@pglsorgls
\def\@pglsorgls#1#2[#3]{%
  \ifdef\@pgls@{\@pgls@{#1}{#2}[#3]}\mpglsWarning\@gls@{#1}{#2}[#3]}%
}

\@pglsorglspl
\def\@pglsorglspl#1#2[#3]{%
  \ifdef\@pglspl@{\@pglspl@{#1}{#2}[#3]}\mpglsWarning\@glspl@{#1}{#2}[#3]}%
}

\@Pglorgls
\def\@Pglorgls#1#2[#3]{%
  \ifdef\@Pgl@{\@Pgl@{#1}{#2}[#3]}\mpglsWarning\@Gls@{#1}{#2}[#3]}%
}

\@pglsorglspl
\def\@pglsorglspl#1#2[#3]{%
  \ifdef\@pglspl@{\@pglspl@{#1}{#2}[#3]}\mpglsWarning\@glspl@{#1}{#2}[#3]}%
}

\@Pglorglspl
\def\@Pglorglspl#1#2[#3]{%
  \ifdef\@Pglspl@{\@Pglspl@{#1}{#2}[#3]}\mpglsWarning\@Glspl@{#1}{#2}[#3]}%
}

\@PGLSorgls
\def\@PGLSorgls#1#2[#3]{%
  \ifdef\@PGLS@{\@PGLS@{#1}{#2}[#3]}\mpglsWarning\@GLS@{#1}{#2}[#3]}%
}

\@PGLSorglspl
\def\@PGLSorglspl#1#2[#3]{%
  \ifdef\@PGLSpl@{\@PGLSpl@{#1}{#2}[#3]}\mpglsWarning\@GLSpl@{#1}{#2}[#3]}%
}
```

`\mpgls[<options>]{<label>}[<insert>]`

`\mpgls`

Use `\pgls` for the first element and `\gls` for the remainder.

```
\glsxtr@newmgls{mpgls}{\@pglsorgls@}{\@gls@}{\@pglsorgls@}{\@gls@}%
```

`\mpglspl`

`\mpglspl[<options>]{<label>}[<insert>]`

Use `\pglspl` for the first element and `\glspl` for the remainder.

`\glsxtr@newmgls{mpglspl}{\@pglsorglspl@}{\@glspl@}{\@pglsorglspl@}{\@glspl@}%`

`\mpglsmainpl`

`\mpglsmainpl[<options>]{<label>}[<insert>]`

Only use plural for main element and only use prefixing command for first element.

`\glsxtr@newmgls{mpglsmainpl}{\@pglsorgls@}{\@gls@}{\@pglsorglspl@}{\@glspl@}%`

`\Mpgls`

`\Mpgls[<options>]{<label>}[<insert>]`

Use `\Pgls` for the first element and `\gls` for the remainder.

`\glsxtr@newmgls{Mpgls}{\@Pglsorgls@}{\@gls@}{\@Pglsorgls@}{\@gls@}%`

`\glsmfuaddmap{mpgls}{Mpgls}`

`\Mpglspl`

`\Mpglspl[<options>]{<label>}[<insert>]`

Use `\Pglspl` for the first element and `\glspl` for the remainder.

`\glsxtr@newmgls{Mpglspl}{\@Pglsorglspl@}{\@glspl@}{\@Pglsorglspl@}{\@glspl@}%`

`\glsmfuaddmap{mpglspl}{Mpglspl}`

`\Mpglsmainpl`

`\Mpglsmainpl[<options>]{<label>}[<insert>]`

Only use plural for main element and only use first letter uppercase prefixing command for first element.

`\glsxtr@newmgls{Mpglsmainpl}{\@Pglsorgls@}{\@gls@}{\@Pglsorglspl@}{\@glspl@}%`

`\glsmfuaddmap{mpglsmainpl}{Mpglsmainpl}`

`\MPGls`

`\MPGls[<options>]{<label>}[<insert>]`

Use `\Pgls` for the first element and `\Gls` for the remainder.

`\glsxtr@newmgls{MPGls}{\@Pglsorgls@}{\@Gls@}{\@Pglsorgls@}{\@Gls@}%`

`\glsmfublocker{MPGls}`

`\MPGlspl`

`\MPGlspl[<options>]{<label>}[<insert>]`

Use `\Pglspl` for the first element and `\Glspl` for the remainder.

```
\glstr@newmgl{s{MPGlspl}{\@Pglsglsp1@}{\@Glspl@}{\@Pglsglsp1@}{\@Glspl@}%
\glsmfublocker{\MPGlspl}}
```

`\MPGlsmainpl`

```
\MPGlsmainpl[<options>]{<label>}[<insert>]
```

Only use plural for main element and first letter uppercase all elements.

```
\glstr@newmgl{s{MPGlsmainpl}{\@Pglsglsp1@}{\@Gls@}{\@Pglsglsp1@}{\@Glspl@}%
\glsmfublocker{\MPGlsmainpl}}
```

`\MPGLS`

```
\MPGLS[<options>]{<label>}[<insert>]
```

Use `\PGLS` for the first element and `\GLS` for the remainder.

```
\glstr@newmgl{s{MPGLS}{\@PGLSorgls@}{\@GLS@}{\@PGLSorgls@}{\@GLS@}%
\glsmfublocker{\MPGLS}}
```

`\MPGLSpl`

```
\MPGLSpl[<options>]{<label>}[<insert>]
```

Use `\PGLSpl` for the first element and `\GLSpl` for the remainder.

```
\glstr@newmgl{s{MPGLSpl}{\@PGLSorglsp1@}{\@GLSpl@}{\@PGLSorglsp1@}{\@GLSpl@}%
\glsmfublocker{\MPGLSpl}}
```

`\MPGLSmainpl`

```
\MPGLSmainpl[<options>]{<label>}[<insert>]
```

Only use plural for main element and uppercase all elements.

```
\glstr@newmgl{s{MPGLSmainpl}{\@PGLSorgls@}{\@GLS@}{\@PGLSorglsp1@}{\@GLSpl@}%
\glsmfublocker{\MPGLSmainpl}}
```

Not currently implementing any other variations.

1.11 Multi-Lingual Support

Add the facility to load language modules, if they are installed, but none are provided with this package.

`\glstrcontinuedname` Provide for use in `\printunsrtable`.

```
\providecommand{\glstrcontinuedname}{continued}
```

`\RequireGlossariesExtraLang`

```
\newcommand*{\RequireGlossariesExtraLang}[1]{%
  \ifundefined{ver@glossariesxtr-#1.ldf}{\input{glossariesxtr-#1.ldf}}{}}%
```

`\ProvidesGlossariesExtraLang`

```
\newcommand*{\ProvidesGlossariesExtraLang}[1]{%
  \ProvidesFile{glossariesxtr-#1.ldf}%
}
```

Load any required language modules that are available. This doesn't generate any warning if none are found, since they're not essential. (The only command that really needs defining for the document is `\abbreviationsname`, which can simply be redefined. However, with `bib2gls` it might be useful to provide custom rules for a particular locale.)

`\glxtr@loaddialect` The dialect label should be stored in `\this@dialect` before using this command.

```
\newcommand{\glxtr@loaddialect}{%
  \IfTrackedLanguageFileExists{\this@dialect}%
  {glossariesxtr-}% prefix
  {.ldf}%
  {%
    \RequireGlossariesExtraLang{\CurrentTrackedTag}%
  }%
  {}% not found
}
```

If `glossaries-extra-bib2gls` has been loaded, `\@glxtrdialecthook` will check for the associated script, otherwise it will do nothing.

```
\@glxtrdialecthook
}

\@ifpackageloaded{tracklang} {%
  \AnyTrackedLanguages
  {%
    \ForEachTrackedDialect{\this@dialect}{\glxtr@loaddialect}%
  }%
  {}%
} {}
```

The style needs to be set at the end to ensure that `\setglossarystyle` has been redefined and extra style commands have been defined. Load `glossaries-extra-stylemods` if required.

```
\@glxtr@redefstyles
```

and set the style:

```
\@glxtr@do@style
```

2 Predefined Abbreviation Styles (`glossaries-extra-abbrstyles.def`)

```
\ProvidesFile{glossaries-extra-abbrstyles.def}[2026/03/06 v2.0 (NLCT)]
```

This file contains the predefined abbreviation styles. Some helper commands first.

`\glxstrlongshortname`

```
\newcommand*{\glxstrlongshortname}{%
  \glxspabbrvfont{\the\glsshorttok}{\glscategorylabel}%
}
```

Provide convenient wrappers for common formats.

`\glxstrlongformat`

```
\glxstrlongformat{<label>}{<insert>}{<longfmtcs>}
```

```
\newcommand*{\glxstrlongformat}[3]{%
```

Don't add inner formatting if markwords attribute set as the inner formatting is implemented within `\glxstrword` and `\glxstrwordsep`.

```
\glxifattribute{#1}{markwords}{true}%
{%
  \ifglxstrinsertinside
    #3{\glxsaccesslong{#1}\glxstrgenentrytextfmt{#2}}%
  \else
    #3{\glxsaccesslong{#1}}\glxstrgenentrytextfmt{#2}%
  \fi
}%
{%
  \ifglxstrinsertinside
    #3{\glxsaccessfmlong{#2}{\glxstrgenentrytextfmt{#1}}}%
  \else
    #3{\glxsaccessfmlong{}{\glxstrgenentrytextfmt{#1}}}%
    \glxstrgenentrytextfmt{#2}%
  \fi
}%
}%
```

`\glxstrlongplformat`

```
\glxstrlongplformat{<label>}{<insert>}{<longfmtcs>}
```

```
\newcommand*{\glxstrlongplformat}[3]{%
  \glxifattribute{#1}{markwords}{true}%
  {%
    \ifglxstrinsertinside
      #3{\glxsaccesslongpl{#1}\glxstrgenentrytextfmt{#2}}%
    \else
      #3{\glxsaccesslongpl{#1}}\glxstrgenentrytextfmt{#2}%
    \fi
  }%
}
```

```

{%
  \ifglstrinsertinside
    #3{\glsaccessfmtlongpl{#2}{\glstrgenentrytextfmt}{#1}}}%
  \else
    #3{\glsaccessfmtlongpl{}{\glstrgenentrytextfmt}{#1}}}%
    \glstrgenentrytextfmt{#2}%
  \fi
}%
}%

```

`\Glsxtrlongformat{<label>}{<insert>}{<longfmtcs>}`

`\Glsxtrlongformat`

```

\newcommand*{\Glsxtrlongformat}[3]{%
  \glsifattribute{#1}{keywords}{true}%
  {%
    \ifglstrinsertinside
      #3{\Glsaccesslong{#1}\glstrgenentrytextfmt{#2}}}%
    \else
      #3{\Glsaccesslong{#1}\glstrgenentrytextfmt{#2}}}%
    \fi
  }%
  {%
    \ifglstrinsertinside
      #3{\Glsaccessfmtlong{#2}{\glstrgenentrytextfmt}{#1}}}%
    \else
      #3{\Glsaccessfmtlong{}{\glstrgenentrytextfmt}{#1}}}%
      \glstrgenentrytextfmt{#2}%
    \fi
  }%
}%

```

`\Glsxtrlongplformat{<label>}{<insert>}{<longfmtcs>}`

`\Glsxtrlongplformat`

```

\newcommand*{\Glsxtrlongplformat}[3]{%
  \glsifattribute{#1}{keywords}{true}%
  {%
    \ifglstrinsertinside
      #3{\Glsaccesslongpl{#1}\glstrgenentrytextfmt{#2}}}%
    \else
      #3{\Glsaccesslongpl{#1}\glstrgenentrytextfmt{#2}}}%
    \fi
  }%
  {%
    \ifglstrinsertinside

```



```

#3{\Glsaccessfmtlongpl{#2}{\glstrgenentrytextfmt}{#1}}%
\else
#3{\Glsaccessfmtlongpl{}{\glstrgenentrytextfmt}{#1}}%
\glstrgenentrytextfmt{#2}%
\fi
}%
}%

```

\GLSxtrlongformat

\GLSxtrlongformat{<label>}{<insert>}{<longfmtcs>}

```

\newcommand*{\GLSxtrlongformat}[3]{%
\glsifattribute{#1}{keywords}{true}%
{%
\ifglstrinsertinside
#3{\Glsaccesslong{#1}\mfirstucMakeUppercase{\glstrgenentrytextfmt{#2}}}%
\else
#3{\Glsaccesslong{#1}}\mfirstucMakeUppercase{\glstrgenentrytextfmt{#2}}%
\fi
}%
{%
\ifglstrinsertinside
#3{\Glsaccessfmtlong{#2}{\glstrgenentrytextfmt}{#1}}%
\else
#3{\Glsaccessfmtlong{}{\glstrgenentrytextfmt}{#1}}%
\mfirstucMakeUppercase{\glstrgenentrytextfmt{#2}}%
\fi
}%
}%

```

\GLSxtrlongplformat

\GLSxtrlongplformat{<label>}{<insert>}{<longfmtcs>}

```

\newcommand*{\GLSxtrlongplformat}[3]{%
\glsifattribute{#1}{keywords}{true}%
{%
\ifglstrinsertinside
#3{\Glsaccesslongpl{#1}\mfirstucMakeUppercase{\glstrgenentrytextfmt{#2}}}%
\else
#3{\Glsaccesslongpl{#1}}\mfirstucMakeUppercase{\glstrgenentrytextfmt{#2}}%
\fi
}%
{%
\ifglstrinsertinside
#3{\Glsaccessfmtlongpl{#2}{\glstrgenentrytextfmt}{#1}}%
\else

```

```

        #3{\GLSaccessfmtlongpl{}\glstrgenentrytextfmt{#1}}%
        \mfirstucMakeUppercase{\glstrgenentrytextfmt{#2}}%
    \fi
}%
}%

```

`\glstrlongformatgrp`

`\glstrlongformatgrp{<label>}{<insert>}{<longfmtcs>}`

Add grouping around insert.

```

\newcommand*{\glstrlongformatgrp}[3]{%
  \glrifattribute{#1}{keywords}{true}%
  {%
    \ifglstrinsertinside
      #3{\glaccesslong{#1}{\glstrgenentrytextfmt{#2}}}%
    \else
      #3{\glaccesslong{#1}{\glstrgenentrytextfmt{#2}}}%
    \fi
  }%
  {%
    #3{\glaccessfmtlong{}\glstrgenentrytextfmt{#1}}%
    \ifglstrinsertinside
      {#3{\glstrgenentrytextfmt{#2}}}%
    \else
      {\glstrgenentrytextfmt{#2}}%
    \fi
  }%
}%

```

`\glstrlongplformatgrp`

`\glstrlongformatplgrp{<label>}{<insert>}{<longfmtcs>}`

Add grouping around insert.

```

\newcommand*{\glstrlongplformatgrp}[3]{%
  \glrifattribute{#1}{keywords}{true}%
  {%
    \ifglstrinsertinside
      #3{\glaccesslongpl{#1}{\glstrgenentrytextfmt{#2}}}%
    \else
      #3{\glaccesslongpl{#1}{\glstrgenentrytextfmt{#2}}}%
    \fi
  }%
  {%
    #3{\glaccessfmtlongpl{}\glstrgenentrytextfmt{#1}}%
    \ifglstrinsertinside
      {#3{\glstrgenentrytextfmt{#2}}}%
    \else
      {\glstrgenentrytextfmt{#2}}%
    \fi
  }%
}%

```

```

\fi
}%
}%

```

```
\Glsxtrlongformatgrp{\label}{\insert}{\longfmtcs}
```

\Glsxtrlongformatgrp

Add grouping around insert.

```

\newcommand*\Glsxtrlongformatgrp[3]{%
  \glsifattribute{#1}{markwords}{true}%
  {%
    \ifglstrinsertinside
      #3{\Glsaccesslong{#1}{\glstrgenentrytextfmt{#2}}}%
    \else
      #3{\Glsaccesslong{#1}{\glstrgenentrytextfmt{#2}}}%
    \fi
  }%
  {%
    #3{\Glsaccessfmtlong}{\glstrgenentrytextfmt{#1}}%
    \ifglstrinsertinside
      {#3{\glstrgenentrytextfmt{#2}}}%
    \else
      {\glstrgenentrytextfmt{#2}}%
    \fi
  }%
}%

```

```
\Glsxtrlongformatplgrp{\label}{\insert}{\longfmtcs}
```

\Glsxtrlongplformatgrp

Add grouping around insert.

```

\newcommand*\Glsxtrlongplformatgrp[3]{%
  \glsifattribute{#1}{markwords}{true}%
  {%
    \ifglstrinsertinside
      #3{\Glsaccesslongpl{#1}{\glstrgenentrytextfmt{#2}}}%
    \else
      #3{\Glsaccesslongpl{#1}{\glstrgenentrytextfmt{#2}}}%
    \fi
  }%
  {%
    #3{\Glsaccessfmtlongpl}{\glstrgenentrytextfmt{#1}}%
    \ifglstrinsertinside
      {#3{\glstrgenentrytextfmt{#2}}}%
    \else
      {\glstrgenentrytextfmt{#2}}%
    \fi
  }%
}%

```

\GLSxtrlongformatgrp

\GLSxtrlongformatgrp{<label>}{<insert>}{<longfmtcs>}

Add grouping around insert.

```
\newcommand*{\GLSxtrlongformatgrp}[3]{%
  \glsifattribute{#1}{markwords}{true}%
  {%
    \ifglstrinsertinside
      #3{\GLSaccesslong{#1}{\mfirstucMakeUppercase{\glstrgenentrytextfmt{#2}}}}%
    \else
      #3{\GLSaccesslong{#1}{\mfirstucMakeUppercase{\glstrgenentrytextfmt{#2}}}}%
    \fi
  }%
  {%
    #3{\GLSaccessfmtlong{}{\glstrgenentrytextfmt}{#1}}%
    \ifglstrinsertinside
      {\mfirstucMakeUppercase{#3{\glstrgenentrytextfmt{#2}}}}%
    \else
      {\mfirstucMakeUppercase{\glstrgenentrytextfmt{#2}}}%
    \fi
  }%
}%
```

\GLSxtrlongplformatgrp

\GLSxtrlongformatplgrp{<label>}{<insert>}{<longfmtcs>}

Add grouping around insert.

```
\newcommand*{\GLSxtrlongplformatgrp}[3]{%
  \glsifattribute{#1}{markwords}{true}%
  {%
    \ifglstrinsertinside
      #3{\GLSaccesslongpl{#1}{\mfirstucMakeUppercase{\glstrgenentrytextfmt{#2}}}}%
    \else
      #3{\GLSaccesslongpl{#1}{\mfirstucMakeUppercase{\glstrgenentrytextfmt{#2}}}}%
    \fi
  }%
  {%
    #3{\GLSaccessfmtlongpl{}{\glstrgenentrytextfmt}{#1}}%
    \ifglstrinsertinside
      {\mfirstucMakeUppercase{#3{\glstrgenentrytextfmt{#2}}}}%
    \else
      {\mfirstucMakeUppercase{\glstrgenentrytextfmt{#2}}}%
    \fi
  }%
}%
```

\glstrshortformat

\glstrshortformat{<label>}{<insert>}{<shortfmtcs>}

```

\newcommand*{\glxtrshortformat}[3]{%
  \glsifattribute{#1}{markshortwords}{true}%
  {%
    \ifglxtrinsertinside
      #3{\glsaccesssshort{#1}\glxtrgenentrytextfmt{#2}}%
    \else
      #3{\glsaccesssshort{#1}}\glxtrgenentrytextfmt{#2}%
    \fi
  }%
  {%
    \ifglxtrinsertinside
      #3{\glsaccessfmtshort{#2}{\glxtrgenentrytextfmt}{#1}}%
    \else
      #3{\glsaccessfmtshort{}{\glxtrgenentrytextfmt}{#1}}%
      \glxtrgenentrytextfmt{#2}%
    \fi
  }%
}%

```

\glxtrshortplformat

```
\glxtrshortplformat{<label>}{<insert>}{<shortfmtcs>}
```

```

\newcommand*{\glxtrshortplformat}[3]{%
  \glsifattribute{#1}{markshortwords}{true}%
  {%
    \ifglxtrinsertinside
      #3{\glsaccesssshortpl{#1}\glxtrgenentrytextfmt{#2}}%
    \else
      #3{\glsaccesssshortpl{#1}}\glxtrgenentrytextfmt{#2}%
    \fi
  }%
  {%
    \ifglxtrinsertinside
      #3{\glsaccessfmtshortpl{#2}{\glxtrgenentrytextfmt}{#1}}%
    \else
      #3{\glsaccessfmtshortpl{}{\glxtrgenentrytextfmt}{#1}}%
      \glxtrgenentrytextfmt{#2}%
    \fi
  }%
}%

```

\Glsxtrshortformat

```
\Glsxtrshortformat{<label>}{<insert>}{<shortfmtcs>}
```

```
\newcommand*{\Glsxtrshortformat}[3]{%
```

```

\glsifattribute{#1}{markshortwords}{true}%
{%
  \ifglstrinsertinside
    #3{\Glsaccesssshort{#1}\glstrgenentrytextfmt{#2}}%
  \else
    #3{\Glsaccesssshort{#1}}\glstrgenentrytextfmt{#2}%
  \fi
}%
{%
  \ifglstrinsertinside
    #3{\Glsaccessfmtshort{#2}{\glstrgenentrytextfmt}{#1}}%
  \else
    #3{\Glsaccessfmtshort{}{\glstrgenentrytextfmt}{#1}}%
    \glstrgenentrytextfmt{#2}%
  \fi
}%
}%

```

`\Glsxtrshortplformat{<label>}{<insert>}{<shortfmtcs>}`

`\Glsxtrshortplformat`

```

\newcommand*{\Glsxtrshortplformat}[3]{%
  \glsifattribute{#1}{markshortwords}{true}%
  {%
    \ifglstrinsertinside
      #3{\Glsaccesssshortpl{#1}\glstrgenentrytextfmt{#2}}%
    \else
      #3{\Glsaccesssshortpl{#1}}\glstrgenentrytextfmt{#2}%
    \fi
  }%
  {%
    \ifglstrinsertinside
      #3{\Glsaccessfmtshortpl{#2}{\glstrgenentrytextfmt}{#1}}%
    \else
      #3{\Glsaccessfmtshortpl{}{\glstrgenentrytextfmt}{#1}}%
      \glstrgenentrytextfmt{#2}%
    \fi
  }%
}%

```

`\GLSxtrshortformat{<label>}{<insert>}{<shortfmtcs>}`

`\GLSxtrshortformat`

```

\newcommand*{\GLSxtrshortformat}[3]{%
  \glsifattribute{#1}{markshortwords}{true}%
  {%

```

```

\ifglstrinsertinside
  #3{\GLSaccessshort{#1}\mfirstucMakeUppercase{\glstrgenentrytextfmt{#2}}}%
\else
  #3{\GLSaccessshort{#1}}\mfirstucMakeUppercase{\glstrgenentrytextfmt{#2}}%
\fi
}%
{%
\ifglstrinsertinside
  #3{\GLSaccessfmtshort{#2}{\glstrgenentrytextfmt}{#1}}%
\else
  #3{\GLSaccessfmtshort{}{\glstrgenentrytextfmt}{#1}}%
  \mfirstucMakeUppercase{\glstrgenentrytextfmt{#2}}%
\fi
}%
}%

```

`\GLSxtrshortplformat{<label>}{<insert>}{<shortfmtcs>}`

`\GLSxtrshortplformat`

```

\newcommand*{\GLSxtrshortplformat}[3]{%
  \gl@ifattribute{#1}{markshortwords}{true}%
  {%
    \ifglstrinsertinside
      #3{\GLSaccessshortpl{#1}\mfirstucMakeUppercase{\glstrgenentrytextfmt{#2}}}%
    \else
      #3{\GLSaccessshortpl{#1}}\mfirstucMakeUppercase{\glstrgenentrytextfmt{#2}}%
    \fi
  }%
  {%
    \ifglstrinsertinside
      #3{\GLSaccessfmtshortpl{#2}{\glstrgenentrytextfmt}{#1}}%
    \else
      #3{\GLSaccessfmtshortpl{}{\glstrgenentrytextfmt}{#1}}%
      \mfirstucMakeUppercase{\glstrgenentrytextfmt{#2}}%
    \fi
  }%
}%

```

`\glstrshortformatgrp{<label>}{<insert>}{<shortfmtcs>}`

`\glstrshortformatgrp`

Add grouping around insert.

```

\newcommand*{\glstrshortformatgrp}[3]{%
  \gl@ifattribute{#1}{markshortwords}{true}%
  {%
    \ifglstrinsertinside
      #3{\glaccessshort{#1}{\glstrgenentrytextfmt{#2}}}%
    \fi
  }%
}

```

```

\else
  #3{\glsaccesssshort{#1}}{\glsxtrgenentrytextfmt{#2}}%
\fi
}%
{%
  #3{\glsaccessfmtshort{}}{\glsxtrgenentrytextfmt{#1}}%
  \ifglsxtrinsertinside
    {#3{\glsxtrgenentrytextfmt{#2}}}%
  \else
    {\glsxtrgenentrytextfmt{#2}}%
  \fi
}%
}%

```

`\glsxtrshortplformatgrp{<label>}{<insert>}{<shortfmtcs>}`

`\glsxtrshortplformatgrp`

Add grouping around insert.

```

\newcommand*{\glsxtrshortplformatgrp}[3]{%
  \glsifattribute{#1}{markshortwords}{true}%
  {%
    \ifglsxtrinsertinside
      #3{\glsaccesssshortpl{#1}}{\glsxtrgenentrytextfmt{#2}}}%
    \else
      #3{\glsaccesssshortpl{#1}}{\glsxtrgenentrytextfmt{#2}}%
    \fi
  }%
  {%
    #3{\glsaccessfmtshortpl{}}{\glsxtrgenentrytextfmt{#1}}%
    \ifglsxtrinsertinside
      {#3{\glsxtrgenentrytextfmt{#2}}}%
    \else
      {\glsxtrgenentrytextfmt{#2}}%
    \fi
  }%
}%

```

`\Glsxtrshortformatgrp{<label>}{<insert>}{<shortfmtcs>}`

`\Glsxtrshortformatgrp`

Add grouping around insert.

```

\newcommand*{\Glsxtrshortformatgrp}[3]{%
  \glsifattribute{#1}{markshortwords}{true}%
  {%
    \ifglsxtrinsertinside
      #3{\Glsaccesssshort{#1}}{\glsxtrgenentrytextfmt{#2}}}%
    \else
      #3{\Glsaccesssshort{#1}}{\glsxtrgenentrytextfmt{#2}}%
    \fi
  }%
}%

```



```

\fi
}%
{%
#3{\Glsaccessfmtshort{ }\glstrgenentrytextfmt{#1}}%
\ifglstrinsertinside
{#3{\glstrgenentrytextfmt{#2}}}%
\else
{\glstrgenentrytextfmt{#2}}%
\fi
}%
}%

```

`\Glsxtrshortplformatgrp{<label>}{<insert>}{<shortfmtcs>}`

`\Glsxtrshortplformatgrp`

Add grouping around insert.

```

\newcommand*{\Glsxtrshortplformatgrp}[3]{%
\glsifattribute{#1}{markshortwords}{true}%
{%
\ifglstrinsertinside
#3{\Glsaccesssshortpl{#1}{\glstrgenentrytextfmt{#2}}}%
\else
#3{\Glsaccesssshortpl{#1}{\glstrgenentrytextfmt{#2}}}%
\fi
}%
}%
#3{\Glsaccessfmtshortpl{ }\glstrgenentrytextfmt{#1}}%
\ifglstrinsertinside
{#3{\glstrgenentrytextfmt{#2}}}%
\else
{\glstrgenentrytextfmt{#2}}%
\fi
}%
}%

```

`\GLSxtrshortformatgrp{<label>}{<insert>}{<shortfmtcs>}`

`\GLSxtrshortformatgrp`

Add grouping around insert.

```

\newcommand*{\GLSxtrshortformatgrp}[3]{%
\glsifattribute{#1}{markshortwords}{true}%
{%
\ifglstrinsertinside
#3{\GLSaccesssshort{#1}{\mfirstucMakeUppercase{\glstrgenentrytextfmt{#2}}}}%
\else
#3{\GLSaccesssshort{#1}{\mfirstucMakeUppercase{\glstrgenentrytextfmt{#2}}}}%
\fi
}%
}%

```

```
{%
#3{\GLSaccessfmtshort}{\glstrgenentrytextfmt}{#1}}%
\ifglstrinsertinside
{\mfirstucMakeUppercase{#3{\glstrgenentrytextfmt}{#2}}}%
\else
{\mfirstucMakeUppercase{\glstrgenentrytextfmt}{#2}}%
\fi
}%
}%
```

```
\GLSxtrshortplformatgrp{\label}{\insert}{\shortfmtcs}
```

\GLSxtrshortplformatgrp

Add grouping around insert.

```
\newcommand*{\GLSxtrshortplformatgrp}[3]{%
\glswifattribute{#1}{markshortwords}{true}%
{%
\ifglstrinsertinside
#3{\GLSaccessshortpl{#1}{\mfirstucMakeUppercase{\glstrgenentrytextfmt}{#2}}}%
\else
#3{\GLSaccessshortpl{#1}{\mfirstucMakeUppercase{\glstrgenentrytextfmt}{#2}}}%
\fi
}%
}%
#3{\GLSaccessfmtshortpl}{\glstrgenentrytextfmt}{#1}}%
\ifglstrinsertinside
{\mfirstucMakeUppercase{#3{\glstrgenentrytextfmt}{#2}}}%
\else
{\mfirstucMakeUppercase{\glstrgenentrytextfmt}{#2}}%
\fi
}%
}%
```

```
\glsxtrlongshortformat{\label}{\insert}{\longfmtcs}
{\shortfmtcs}
```

\glsxtrlongshortformat

```
\newcommand*{\glsxtrlongshortformat}[4]{%
\glsxtrlongformat{#1}{#2}{#3}%
\glsxtrfullsep{#1}%
\glsxtrparen{\glsxtrshortformat{#1}{#4}}%
}%
```

```
\glsxtrlongshortplformat{\label}{\insert}{\longfmtcs}
{\shortfmtcs}
```

\glsxtrlongshortplformat

```
\newcommand*\glstrlongshortplformat[4]{%
  \glstrlongplformat{#1}{#2}{#3}%
  \glstrfullsep{#1}%
  \glstrparen{\glstrshortplformat{#1}{#4}}%
}%
```

\Glsxtrlongshortformat

```
\Glsxtrlongshortformat{<label>}{<insert>}{<longfmtcs>}
{<shortfmtcs>}
```

```
\newcommand*\Glsxtrlongshortformat[4]{%
  \Glsxtrlongformat{#1}{#2}{#3}%
  \glstrfullsep{#1}%
  \glstrparen{\glstrshortformat{#1}{#4}}%
}%
```

\Glsxtrlongshortplformat

```
\Glsxtrlongshortplformat{<label>}{<insert>}{<longfmtcs>}
{<shortfmtcs>}
```

```
\newcommand*\Glsxtrlongshortplformat[4]{%
  \Glsxtrlongplformat{#1}{#2}{#3}%
  \glstrfullsep{#1}%
  \glstrparen{\glstrshortplformat{#1}{#4}}%
}%
```

\GLSxtrlongshortformat

```
\GLSxtrlongshortformat{<label>}{<insert>}{<longfmtcs>}
{<shortfmtcs>}
```

```
\newcommand*\GLSxtrlongshortformat[4]{%
  \GLSxtrlongformat{#1}{#2}{#3}%
  \glstrfullsep{#1}%
  \glstrparen{\GLSxtrshortformat{#1}{#4}}%
}%
```

\GLSxtrlongshortplformat

```
\GLSxtrlongshortplformat{<label>}{<insert>}{<longfmtcs>}
{<shortfmtcs>}
```

```
\newcommand*\GLSxtrlongshortplformat[4]{%
```

```

\GLSxtrlongplformat{#1}{#2}{#3}%
\glsxtrfullsep{#1}%
\glsxtrparen{\GLSxtrshortplformat{#1}{#4}}%
}%

```

\glsxtrshortlongformat

```

\glsxtrshortlongformat{<label>}{<insert>}{<longfmtcs>}
{<shortfmtcs>}

```

```

\newcommand*{\glsxtrshortlongformat}[4]{%
\glsxtrshortformat{#1}{#2}{#4}%
\glsxtrfullsep{#1}%
\glsxtrparen{\glsxtrlongformat{#1}{#3}}%
}%

```

\glsxtrshortlongplformat

```

\glsxtrshortlongplformat{<label>}{<insert>}{<longfmtcs>}
{<shortfmtcs>}

```

```

\newcommand*{\glsxtrshortlongplformat}[4]{%
\glsxtrshortplformat{#1}{#2}{#4}%
\glsxtrfullsep{#1}%
\glsxtrparen{\glsxtrlongplformat{#1}{#3}}%
}%

```

\Glsxtrshortlongformat

```

\Glsxtrshortlongformat{<label>}{<insert>}{<longfmtcs>}
{<shortfmtcs>}

```

```

\newcommand*{\Glsxtrshortlongformat}[4]{%
\Glsxtrshortformat{#1}{#2}{#4}%
\glsxtrfullsep{#1}%
\glsxtrparen{\glsxtrlongformat{#1}{#3}}%
}%

```

\Glsxtrshortlongplformat

```

\Glsxtrshortlongplformat{<label>}{<insert>}{<longfmtcs>}
{<shortfmtcs>}

```

```

\newcommand*{\Glsxtrshortlongplformat}[4]{%
\Glsxtrshortplformat{#1}{#2}{#4}%
\glsxtrfullsep{#1}%

```

```
\glsxtrparen{\glsxtrlongplformat{#1}{#3}}%
}%
```

\GlsXtrshortlongformat

```
\GlsXtrshortlongformat{<label>}{<insert>}{<longfmtcs>}
{<shortfmtcs>}
```

```
\newcommand*\GlsXtrshortlongformat[4]{%
\GlsXtrshortformat{#1}{#2}{#4}%
\glsxtrfullsep{#1}%
\glsxtrparen{\GlsXtrlongformat{#1}{#3}}%
}%
```

\GlsXtrshortlongplformat

```
\GlsXtrshortlongplformat{<label>}{<insert>}{<longfmtcs>}
{<shortfmtcs>}
```

```
\newcommand*\GlsXtrshortlongplformat[4]{%
\GlsXtrshorttplformat{#1}{#2}{#4}%
\glsxtrfullsep{#1}%
\glsxtrparen{\GlsXtrlongplformat{#1}{#3}}%
}%
```

\glsxtrfootnotelongformat

```
\glsxtrfootnotelongformat{<label>}{<longfmtcs>}
```

```
\newcommand*\glsxtrfootnotelongformat[2]{%
\glsxtrlongformat{#1}{#2}%
}%
```

\glsxtrfootnotelongplformat

```
\glsxtrfootnotelongplformat{<label>}{<longfmtcs>}
```

```
\newcommand*\glsxtrfootnotelongplformat[2]{%
\glsxtrlongplformat{#1}{#2}%
}%
```

\glsxtrpostfootnotelongformat

```
\glsxtrpostfootnotelongformat{<label>}{<longfmtcs>}
```

```
\newcommand*\glsxtrpostfootnotelongformat{%
```

```
\glxtrfootnotelongformat
}%
```

```
\glxtruserpostshortformat{<label>}{<shortfmtcs>}
```

\glxtrpostusersshortformat

```
\newcommand*{\glxtrpostusersshortformat}[2]{%
\glxtrifallcaps
{\GLSxtrusersshortformat{#1}{#2}}%
{\glxtrusersshortformat{#1}{#2}}%
}%
```

```
\glxtrusersshortformat{<label>}{<shortfmtcs>}
```

\glxtrusersshortformat

```
\newcommand*{\glxtrusersshortformat}[2]{%
\glxtruserparen{\glxtrshortformat{#1}{#2}}{#1}%
}%
```

```
\glxtrusersshorttplformat{<label>}{<shortfmtcs>}
```

\glxtrusersshorttplformat

```
\newcommand*{\glxtrusersshorttplformat}[2]{%
\glxtruserparen{\glxtrshorttplformat{#1}{#2}}{#1}%
}%
```

```
\GLSxtrusersshortformat{<label>}{<shortfmtcs>}
```

\GLSxtrusersshortformat

```
\newcommand*{\GLSxtrusersshortformat}[2]{%
\GLSxtruserparen{\GLSxtrshortformat{#1}{#2}}{#1}%
}%
```

```
\GLSxtrusersshorttplformat{<label>}{<shortfmtcs>}
```

\GLSxtrusersshorttplformat

```
\newcommand*{\GLSxtrusersshorttplformat}[2]{%
\GLSxtruserparen{\GLSxtrshorttplformat{#1}{#2}}{#1}%
}%
```

\glxtrpostuserlongformat

\glxtruserpostlongformat{<label>}{<longfmtcs>}

```
\newcommand*{\glxtrpostuserlongformat}[2]{%
  \glxtrifallcaps
  {\GLSxtruserlongformat{#1}{#2}}%
  {\glxtruserlongformat{#1}{#2}}%
}%
```

\glxtruserlongformat

\glxtruserlongformat{<label>}{<longfmtcs>}

```
\newcommand*{\glxtruserlongformat}[2]{%
  \glxtruserparen{\glxtrlongformat{#1}{#2}}{#1}%
}%
```

\GLSxtruserlongformat

\GLSxtruserlongformat{<label>}{<longfmtcs>}

```
\newcommand*{\GLSxtruserlongformat}[2]{%
  \GLSxtruserparen{\GLSxtrlongformat{#1}{#2}}{#1}%
}%
```

\glxtruserlongplformat

\glxtruserlongplformat{<label>}{<longfmtcs>}

```
\newcommand*{\glxtruserlongplformat}[2]{%
  \glxtruserparen{\glxtrlongplformat{#1}{#2}}{#1}%
}%
```

\GLSxtruserlongplformat

\GLSxtruserlongplformat{<label>}{<longfmtcs>}

```
\newcommand*{\GLSxtruserlongplformat}[2]{%
  \GLSxtruserparen{\GLSxtrlongplformat{#1}{#2}}{#1}%
}%
```

\glxtruserlongshortformat

\glxtruserlongshortformat{<label>}{<insert>}{<longfmtcs>}{<shortfmtcs>}

```
\newcommand*\glxtruserlongshortformat}[4]{%
  \glxtrlongformat{#1}{#2}{#3}%
  \glxtrusershortformat{#1}{#4}%
}%
```

```
\glxtruserlongshortplformat{<label>}{<insert>}{<longfmtcs>}
{<shortfmtcs>}
```

\glxtruserlongshortplformat

```
\newcommand*\glxtruserlongshortplformat}[4]{%
  \glxtrlongplformat{#1}{#2}{#3}%
  \glxtrusershortplformat{#1}{#4}%
}%
```

```
\Glsxtruserlongshortformat{<label>}{<insert>}{<longfmtcs>}
{<shortfmtcs>}
```

\Glsxtruserlongshortformat

```
\newcommand*\Glsxtruserlongshortformat}[4]{%
  \Glsxtrlongformat{#1}{#2}{#3}%
  \glxtrusershortformat{#1}{#4}%
}%
```

```
\Glsxtruserlongshortplformat{<label>}{<insert>}{<longfmtcs>}
{<shortfmtcs>}
```

\Glsxtruserlongshortplformat

```
\newcommand*\Glsxtruserlongshortplformat}[4]{%
  \Glsxtrlongplformat{#1}{#2}{#3}%
  \glxtrusershortplformat{#1}{#4}%
}%
```

```
\GLSxtruserlongshortformat{<label>}{<insert>}{<longfmtcs>}
{<shortfmtcs>}
```

\GLSxtruserlongshortformat

```
\newcommand*\GLSxtruserlongshortformat}[4]{%
  \GLSxtrlongformat{#1}{#2}{#3}%
  \GLSxtrusershortformat{#1}{#4}%
}%
```


\GLSxtruserlongshortplformat

```
\GLSxtruserlongshortplformat{<label>}{<insert>}{<longfmtcs>}
{<shortfmtcs>}
```

```
\newcommand*{\GLSxtruserlongshortplformat}[4]{%
  \GLSxtrlongplformat{#1}{#2}{#3}%
  \GLSxtrusershortplformat{#1}{#4}%
}%
```

\glxtrusershortlongformat

```
\glxtrusershortlongformat{<label>}{<insert>}{<longfmtcs>}
{<shortfmtcs>}
```

```
\newcommand*{\glxtrusershortlongformat}[4]{%
  \glxtrshortformat{#1}{#2}{#3}%
  \glxtruserlongformat{#1}{#4}%
}%
```

\glxtrusershortlongplformat

```
\glxtrusershortlongplformat{<label>}{<insert>}{<longfmtcs>}
{<shortfmtcs>}
```

```
\newcommand*{\glxtrusershortlongplformat}[4]{%
  \glxtrshortplformat{#1}{#2}{#3}%
  \glxtruserlongplformat{#1}{#4}%
}%
```

\Glsxtrusershortlongformat

```
\Glsxtrusershortlongformat{<label>}{<insert>}{<longfmtcs>}
{<shortfmtcs>}
```

```
\newcommand*{\Glsxtrusershortlongformat}[4]{%
  \Glsxtrshortformat{#1}{#2}{#3}%
  \glxtruserlongformat{#1}{#4}%
}%
```

\Glsxtrusershortlongplformat

```
\Glsxtrusershortlongplformat{<label>}{<insert>}{<longfmtcs>}
{<shortfmtcs>}
```

```
\newcommand*{\Glsxtrusershortlongplformat}[4]{%
```

```

\GLSxtrshortplformat{#1}{#2}{#3}%
\GLSxtruserlongplformat{#1}{#4}%
}%

```

```

\GLSxtrusershortlongformat{<label>}{<insert>}{<longfmtcs>}
{<shortfmtcs>}

```

\GLSxtrusershortlongformat

```

\newcommand*{\GLSxtrusershortlongformat}[4]{%
\GLSxtrshortformat{#1}{#2}{#3}%
\GLSxtruserlongformat{#1}{#4}%
}%

```

```

\GLSxtrusershortlongplformat{<label>}{<insert>}{<longfmtcs>}
{<shortfmtcs>}

```

\GLSxtrusershortlongplformat

```

\newcommand*{\GLSxtrusershortlongplformat}[4]{%
\GLSxtrshortplformat{#1}{#2}{#3}%
\GLSxtruserlongplformat{#1}{#4}%
}%

```

2.1 Predefined Styles (Default Font)

long-short

```

\newabbreviationstyle{long-short}%
{%

```

Set accessibility attributes if enabled.

```

\GLSxtrAccSuppAbbrSetFirstLongAttrs\glscategorylabel

```

Setup the default fields.

```

\renewcommand*{\CustomAbbreviationFields}{%
name={\GLSxtrlongshortname},
sort={\the\GLSshorttok},
first={\GLSfirstxplongfont{\the\GLSlongtok}{\glscategorylabel}%
\protect\GLSxtrfullsep{\the\GLSlabeltok}%
\protect\GLSxtrparen{\GLSfirstxpabrvfont{\the\GLSshorttok}{\glscategorylabel}}},%
firstplural={\GLSfirstxplongfont{\the\GLSlongpltok}{\glscategorylabel}%
\protect\GLSxtrfullsep{\the\GLSlabeltok}%
\protect\GLSxtrparen{\GLSfirstxpabrvfont{\the\GLSshortpltok}{\glscategorylabel}}},%
plural={\GLSxpabrvfont{\the\GLSshortpltok}{\glscategorylabel}}},%
text={\GLSxpabrvfont{\the\GLSshorttok}{\glscategorylabel}}},%
description={\the\GLSlongtok}}}%

```

Unset the `regular` attribute if it has been set.

```
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glstrsetcomplexstyle{\the\glslabeltok}{3}%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glsssetattribute{\the\glslabeltok}{regular}{false}%
  }%
}%
{%
}
```

In case the user wants to mix and match font styles, these are redefined here.

```
\renewcommand*{\abbrvpluralsuffix}{\glstrabbrvpluralsuffix}%
\renewcommand*{\glstrabbrvfont}[1]{\glstrabbrvdefaultfont{##1}}%
\renewcommand*{\glstrfirstabbrvfont}[1]{\glstrfirstabbrvdefaultfont{##1}}%
\renewcommand*{\glstrfirstlongfont}[1]{\glstrfirstlongdefaultfont{##1}}%
\renewcommand*{\glstrlongfont}[1]{\glstrlongdefaultfont{##1}}%
\renewcommand*{\glstrrevert}[1]{\glstrdefaultrevert{##1}}%
```

The first use full form and the inline full form are the same for this style.

```
\renewcommand*{\glstrfullformat}[2]{%
  \glstrlongshortformat{##1}{##2}%
  {\glstrfirstlongfont}{\glstrfirstabbrvfont}%
}%
\renewcommand*{\glstrfullplformat}[2]{%
  \glstrlongshortplformat{##1}{##2}%
  {\glstrfirstlongfont}{\glstrfirstabbrvfont}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \Glsxtrlongshortformat{##1}{##2}%
  {\glstrfirstlongfont}{\glstrfirstabbrvfont}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \Glsxtrlongshortplformat{##1}{##2}%
  {\glstrfirstlongfont}{\glstrfirstabbrvfont}%
}%
\renewcommand*{\GLSxtrfullformat}[2]{%
  \GLSxtrlongshortformat{##1}{##2}%
  {\glstrfirstlongfont}{\glstrfirstabbrvfont}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
  \GLSxtrlongshortplformat{##1}{##2}%
  {\glstrfirstlongfont}{\glstrfirstabbrvfont}%
}%
}
```

Set this as the default style for general abbreviations:

```
\setabbreviationstyle{long-short}
```

`\glxtrlongshortdescsort`

```
\newcommand*{\glxtrlongshortdescsort}{%
\expandonce\glxtrorglong\space (\expandonce\glxtrorgshort)%
}
```

`\glxtrlongshortdescname`

```
\newcommand*{\glxtrlongshortdescname}{%
\glxplongfont{\the\glslongtok}{\glscategorylabel}%
\protect\glxtrfullsep{\the\glslabeltok}%
\protect\glxtrparen{\glxpabbrvfont{\the\glsshorttok}{\glscategorylabel}}%
}
```

`long-short-desc` User supplies description. The long form is included in the name.

```
\newabbreviationstyle{long-short-desc}%
{%
```

Set accessibility attributes if enabled.

```
\glxtrAccSuppAbbrSetTextShortAttrs\glscategorylabel
```

Setup the default fields.

```
\renewcommand*{\CustomAbbreviationFields}{%
name={\glxtrlongshortdescname},
sort={\glxtrlongshortdescsort},%
first={\glsfirstxplongfont{\the\glslongtok}{\glscategorylabel}%
\protect\glxtrfullsep{\the\glslabeltok}%
\protect\glxtrparen{\glsfirstxpabbrvfont{\the\glsshorttok}{\glscategorylabel}}},%
firstplural={\glsfirstxplongfont{\the\glslongpltok}{\glscategorylabel}%
\protect\glxtrfullsep{\the\glslabeltok}%
\protect\glxtrparen{\glsfirstxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}}},%
```

The text key should only have the short form.

```
text={\glxpabbrvfont{\the\glsshorttok}{\glscategorylabel}},%
plural={\glxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}}%
}%
```

Unset the regular attribute if it has been set.

```
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glxtrsetcomplexstyle{\the\glslabeltok}{3}%
\glshasattribute{\the\glslabeltok}{regular}%
{%
\glissetattribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%
\GlsXtrUseAbbrStyleFmts{long-short}%
}
```

`\glxtrshortlongname`

```
\newcommand*{\glxtrshortlongname}{%
  \glxpabbrvfont{\the\glsshorttok}{\glscategorylabel}%
}
```

`short-long` Short form followed by long form in parenthesis on first use.

```
\newabbreviationstyle{short-long}%
{%
```

Set accessibility attributes if enabled.

```
\glxtrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
```

Setup the default fields.

```
\renewcommand*{\CustomAbbreviationFields}{%
  name={\glxtrshortlongname},
  sort={\the\glsshorttok},
  description={\the\glslongtok},%
  first={\glsfirstxpabbrvfont{\the\glsshorttok}{\glscategorylabel}%
    \protect\glxtrfullsep{\the\glslabeltok}%
    \protect\glxtrparen{\glsfirstxplongfont{\the\glslongtok}{\glscategorylabel}}},%
  firstplural={\glsfirstxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}%
    \protect\glxtrfullsep{\the\glslabeltok}%
    \protect\glxtrparen{\glsfirstxplongfont{\the\glslongpltok}{\glscategorylabel}}},%

  text={\glxpabbrvfont{\the\glsshorttok}{\glscategorylabel}},%
  plural={\glxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}}}%
```

Unset the regular attribute if it has been set.

```
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glissetattribute{\the\glslabeltok}{regular}{false}%
  }%
  {}%
}%
}%
{%
```

In case the user wants to mix and match font styles, these are redefined here.

```
\renewcommand*{\abbrvpluralsuffix}{\glxtrabbrvpluralsuffix}%
\renewcommand*{\glsabrvfont}[1]{\glsabrvdefaultfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvdefaultfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%
```

The first use full form and the inline full form are the same for this style.

```
\renewcommand*{\glxtrfullformat}[2]{%
  \glxtrshortlongformat{##1}{##2}%
  {\glsfirstlongfont}{\glsfirstabbrvfont}%
}%
\renewcommand*{\glxtrfullplformat}[2]{%
```

```

\glstrshortlongplformat{##1}{##2}%
{\glstrfirstlongfont}{\glstrfirstabbrvfont}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
\Glsxtrshortlongformat{##1}{##2}%
{\glstrfirstlongfont}{\glstrfirstabbrvfont}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
\Glsxtrshortlongplformat{##1}{##2}%
{\glstrfirstlongfont}{\glstrfirstabbrvfont}%
}%
\renewcommand*{\GLSxtrfullformat}[2]{%
\GLSxtrshortlongformat{##1}{##2}%
{\glstrfirstlongfont}{\glstrfirstabbrvfont}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
\GLSxtrshortlongplformat{##1}{##2}%
{\glstrfirstlongfont}{\glstrfirstabbrvfont}%
}%
}

```

`\glstrshortlongdescsort`

```
\newcommand*{\glstrshortlongdescsort}{\expandonce\glstrorgshort}
```

`\glstrshortlongdescname`

```

\newcommand*{\glstrshortlongdescname}{%
\glxpabbrvfont{\the\glsshorttok}{\glscategorylabel}%
\protect\glxtrfullsep{\the\glslabeltok}%
\protect\glxtrparen{\glxplongfont{\the\glslongtok}{\glscategorylabel}}%
}

```

`short-long-desc` User supplies description. The long form is included in the name.

```

\newabbreviationstyle{short-long-desc}%
{%

```

Set accessibility attributes if enabled.

```
\glstrAccSuppAbbrSetTextShortAttrs\glscategorylabel
```

Setup the default fields.

```

\renewcommand*{\CustomAbbreviationFields}{%
name={\glstrshortlongdescname},
sort={\glstrshortlongdescsort},
first={\glstrfirstxpabbrvfont{\the\glsshorttok}{\glscategorylabel}%
\protect\glxtrfullsep{\the\glslabeltok}%
\protect\glxtrparen{\glstrfirstxplongfont{\the\glslongtok}{\glscategorylabel}}},%
firstplural={\glstrfirstxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}%
\protect\glxtrfullsep{\the\glslabeltok}%
\protect\glxtrparen{\glstrfirstxplongfont{\the\glslongpltok}{\glscategorylabel}}},%
text={\glxpabbrvfont{\the\glsshorttok}{\glscategorylabel}},%

```

```
plural={\glxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}}%
}%
```

Unset the regular attribute if it has been set.

```
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glstrsetcomplexstyle{\the\glslabeltok}{3}%
\glshasattribute{\the\glslabeltok}{regular}%
{%
\glissetattribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%
\GlsXtrUseAbbrStyleFmts{short-long}%
}
```

`\glsfirstlongfootnotefont` Only used by the “footnote” styles.

```
\newcommand*{\glsfirstlongfootnotefont}[1]{\glslongfootnotefont{#1}}%
```

`\glslongfootnotefont` Only used by the “footnote” styles.

```
\newcommand*{\glslongfootnotefont}[1]{\glslongdefaultfont{#1}}%
```

`\glstrabbrvfootnote`

```
\glstrabbrvfootnote{<label>}{<long>}
```

Command used by footnote abbreviation styles. The default definition ignores the first argument. The second argument *<long>* includes the font changing command and may be the singular or plural form, depending on the command that was used (for example, `\gls` or `\glsp1`).

```
\newcommand*{\glstrabbrvfootnote}[2]{\footnote{#2}}
```

`\glstrpostabbrvfootnote` Used by post-footnote style to include formatting.

```
\newrobustcmd*{\glstrpostabbrvfootnote}[2]{%
\glstrabbrvfootnote{#1}%
{#2\glstrpostfootnotelongformat{#1}{\glsfirstlongfootnotefont}}%
}
```

`\xpglstrpostabbrvfootnote` Perform all the appropriate expansions to ensure `\glslabel` and `\glstrassignlinktextfmt` are expanded as they may be lost by the time the footnote occurs.

```
\newcommand*{\xpglstrpostabbrvfootnote}{%
\expandafter\expandafter\expandafter
\glstrpostabbrvfootnote
\expandafter\expandafter\expandafter
{\expandafter\glslabel\expandafter}\expandafter
{\glstrassignlinktextfmt}%
}
```

`\glstrfootnotename`

```
\newcommand*{\glstrfootnotename}{%  
  \glxpabbrvfont{\the\glsshorttok}{\glscategorylabel}%  
}
```

footnote Short form followed by long form in footnote on first use.

```
\newabbreviationstyle{footnote}{%  
  {%
```

Set accessibility attributes if enabled. (Add `firstshortaccess` since long form is hidden in a footnote on first use.) The inner formatting isn't be applied to the footnote text because the `innertextformat` key value may have gone out of scope by that the time the footnote text is processed. (Neither is the outer formatting applied.)

```
\glstrAccSuppAbbrSetNoLongAttrs\glscategorylabel
```

Setup the default fields.

```
\renewcommand*{\CustomAbbreviationFields}{%  
  name={\glstrfootnotename},  
  sort={\the\glsshorttok},  
  description={\the\glslongtok},%  
  
  first={\glsfirstxpabbrvfont{\the\glsshorttok}{\glscategorylabel}%  
    \protect\glstrabbrvfootnote{\the\glslabeltok}%  
    {\protect\glsfirstlongfootnotefont{\the\glslongtok}}},%  
  firstplural={\glsfirstxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}%  
    \protect\glstrabbrvfootnote{\the\glslabeltok}%  
    {\protect\glsfirstlongfootnotefont{\the\glslongpltok}}},%  
  
  text={\glxpabbrvfont{\the\glsshorttok}{\glscategorylabel}},%  
  plural={\glxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}}}%
```

Switch off hyperlinks on first use to prevent nested hyperlinks, and unset the regular attribute if it has been set.

```
\renewcommand*{\GlsXtrPostNewAbbreviation}{%  
  \glissetattribute{\the\glslabeltok}{nohyperfirst}{true}%  
  \glshasattribute{\the\glslabeltok}{regular}%  
  {%  
    \glissetattribute{\the\glslabeltok}{regular}{false}%  
  }%  
}%  
{%
```

In case the user wants to mix and match font styles, these are redefined here.

```
\renewcommand*{\abbrvpluralsuffix}{\glstrabbrvpluralsuffix}%  
\renewcommand*{\glabbrvfont}[1]{\glabbrvdefaultfont{##1}}%  
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvdefaultfont{##1}}%  
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongfootnotefont{##1}}%  
\renewcommand*{\glslongfont}[1]{\glslongfootnotefont{##1}}%
```


The full format displays the short form followed by the long form as a footnote.

```

\renewcommand*{\glxstrfullformat}[2]{%
  \glxstrshortformat{##1}{##2}{\glsfirstabbrvfont}%
  \protect\glxstrabbrvfootnote{##1}%
  {\glxstrfootnotelongformat{##1}{\glsfirstlongfootnotefont}}%
}%
\renewcommand*{\glxstrfullplformat}[2]{%
  \glxstrshortplformat{##1}{##2}{\glsfirstabbrvfont}%
  \protect\glxstrabbrvfootnote{##1}%
  {\glxstrfootnotelongplformat{##1}{\glsfirstlongfootnotefont}}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \Glsxtrshortformat{##1}{##2}{\glsfirstabbrvfont}%
  \protect\glxstrabbrvfootnote{##1}%
  {\glxstrfootnotelongformat{##1}{\glsfirstlongfootnotefont}}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \Glsxtrshortplformat{##1}{##2}{\glsfirstabbrvfont}%
  \protect\glxstrabbrvfootnote{##1}%
  {\glxstrfootnotelongplformat{##1}{\glsfirstlongfootnotefont}}%
}%
\renewcommand*{\GLSxtrfullformat}[2]{%
  \GLSxtrshortformat{##1}{##2}{\glsfirstabbrvfont}%
  \protect\glxstrabbrvfootnote{##1}%
  {\glxstrfootnotelongformat{##1}{\glsfirstlongfootnotefont}}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
  \GLSxtrshortplformat{##1}{##2}{\glsfirstabbrvfont}%
  \protect\glxstrabbrvfootnote{##1}%
  {\glxstrfootnotelongplformat{##1}{\glsfirstlongfootnotefont}}%
}%

```

The first use full form and the inline full form use the short (long) style.

```

\renewcommand*{\glxstrinlinefullformat}[2]{%
  \glxstrshortlongformat{##1}{##2}%
  {\glsfirstlongfootnotefont}{\glsfirstabbrvfont}%
}%
\renewcommand*{\glxstrinlinefullplformat}[2]{%
  \glxstrshortlongplformat{##1}{##2}%
  {\glsfirstlongfootnotefont}{\glsfirstabbrvfont}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \Glsxtrshortlongformat{##1}{##2}%
  {\glsfirstlongfootnotefont}{\glsfirstabbrvfont}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \Glsxtrshortlongplformat{##1}{##2}%
  {\glsfirstlongfootnotefont}{\glsfirstabbrvfont}%
}%
\renewcommand*{\GLSxtrinlinefullformat}[2]{%

```

```

\GLSxtrshortlongformat{##1}{##2}%
{\glsfirstlongfootnotefont}{\glsfirstabbrvfont}%
}%
\renewcommand*{\GLSxtrinlinefullplformat}[2]{%
\GLSxtrshortlongplformat{##1}{##2}%
{\glsfirstlongfootnotefont}{\glsfirstabbrvfont}%
}%
}

```

short-footnote

```
\letabbreviationstyle{short-footnote}{footnote}
```

\glsxtrfootnotedesname

```

\newcommand*{\glsxtrfootnotedesname}{%
\glsxpabbrvfont{\the\glsshorttok}{\glscategorylabel}%
\protect\glsxtrfullsep{\the\glslabeltok}%
\protect\glsxtrparen{\glsxplongfont{\the\glslongtok}{\glscategorylabel}}%
}

```

\glsxtrfootnotedesort

```
\newcommand*{\glsxtrfootnotedesort}{\the\glsshorttok}
```

short-footnote-desc Like short-footnote but with user supplied description.

```

\newabbreviationstyle{short-footnote-desc}{%
{%

```

Set accessibility attributes if enabled

```
\glsxtrAccSuppAbbrSetNameLongAttrs\glscategorylabel
```

Setup the default fields.

```

\renewcommand*{\CustomAbbreviationFields}{%
name={\glsxtrfootnotedesname},
sort={\glsxtrfootnotedesort},
first={\glsfirstxpabbrvfont{\the\glsshorttok}{\glscategorylabel}%
\protect\glsxtrabbrvfootnote{\the\glslabeltok}%
{\protect\glsfirstlongfootnotefont{\the\glslongtok}}},%
firstplural={\glsfirstxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}%
\protect\glsxtrabbrvfootnote{\the\glslabeltok}%
{\protect\glsfirstlongfootnotefont{\the\glslongpltok}}},%
text={\glsxpabbrvfont{\the\glsshorttok}{\glscategorylabel}}},%
plural={\glsxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}}}%

```

Switch off hyperlinks on first use to prevent nested hyperlinks, and unset the regular attribute if it has been set.

```

\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glsssetattribute{\the\glslabeltok}{nohyperfirst}{true}%
\glshasattribute{\the\glslabeltok}{regular}%
{%
\glsssetattribute{\the\glslabeltok}{regular}{false}%
}%

```

```

    {}%
  }%
}%
{%
  \GlsXtrUseAbbrStyleFmts{footnote}%
}

```

footnote-desc Synonym.

```
\letabbreviationstyle{footnote-desc}{short-footnote-desc}
```

postfootnote Similar to **footnote** but the footnote is placed afterwards, outside the link. This avoids nested links and can also move the footnote marker after any following punctuation mark. Pre v1.07 included `\footnote` in the first keys, which was incorrect as it caused duplicate footnotes.

```

\newabbreviationstyle{postfootnote}%
{%

```

Set accessibility attributes if enabled. (Add `firstshortaccess` since long form is hidden in a footnote on first use.)

```
\glstrAccSuppAbbrSetNoLongAttrs\glscategorylabel
```

Setup the default fields.

```

\renewcommand*{\CustomAbbreviationFields}{%
  name={\glstrfootnotename},
  sort={\the\glsshorttok},
  description={\the\glslongtok},%
  first={\glstrfirstpabrvfont{\the\glsshorttok}{\glscategorylabel}},%
  firstplural={\glstrfirstpabrvfont{\the\glsshortpltok}{\glscategorylabel}},%

  text={\glstrpabrvfont{\the\glsshorttok}{\glscategorylabel}},%
  plural={\glstrpabrvfont{\the\glsshortpltok}{\glscategorylabel}}}%

```

Make this category insert a footnote after the link if this was the first use, and unset the `regular` attribute if it has been set.

```

\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \csdef{glstrpostlink\glscategorylabel}{%

```

The footnote needs to be suppressed in the inline form. Previously this was done by redefining `glstrsetupfulldefs` but that interferes with other styles. Instead, this now uses `\glstrifwasglslike`

```

\glstrifwasglslikeandfirstuse
{%

```

Ensure `\glslabel` and `\glstrassignlinktextfmt` are expanded as they may be lost by the time the footnote occurs.

```

\glstrdopostpunc{\expandafter\expandafter\expandafter
\glstrpostabrvfootnote
\expandafter\expandafter\expandafter
{\expandafter\glslabel\expandafter}\expandafter
{\glstrassignlinktextfmt}}}%
}{}%

```

```

}%
\glshasattribute{\the\glslabeltok}{regular}%
{%
  \glissetattribute{\the\glslabeltok}{regular}{false}%
}%
}%
{}%
}%
{}%

```

In case the user wants to mix and match font styles, these are redefined here.

```

\renewcommand*\abbrvpluralsuffix{\glxtrabbrvpluralsuffix}%
\renewcommand*\glsabrvfont[1]{\glsabrvdefaultfont{##1}}%
\renewcommand*\glsfirstabbrvfont[1]{\glsfirstabbrvdefaultfont{##1}}%
\renewcommand*\glsfirstlongfont[1]{\glsfirstlongfootnotefont{##1}}%
\renewcommand*\glslongfont[1]{\glslongfootnotefont{##1}}%

```

The full format displays the short form. The long form is deferred.

```

\renewcommand*\glxtrfullformat[2]{%
  \glxtrshortformat{##1}{##2}{\glsfirstabbrvfont}%
}%
\renewcommand*\glxtrfullplformat[2]{%
  \glxtrshortplformat{##1}{##2}{\glsfirstabbrvfont}%
}%
\renewcommand*\Glsxtrfullformat[2]{%
  \Glsxtrshortformat{##1}{##2}{\glsfirstabbrvfont}%
}%
\renewcommand*\Glsxtrfullplformat[2]{%
  \Glsxtrshortplformat{##1}{##2}{\glsfirstabbrvfont}%
}%
\renewcommand*\GLSxtrfullformat[2]{%
  \GLSxtrshortformat{##1}{##2}{\glsfirstabbrvfont}%
}%
\renewcommand*\GLSxtrfullplformat[2]{%
  \GLSxtrshortplformat{##1}{##2}{\glsfirstabbrvfont}%
}%

```

The first use full form and the inline full form use the short (long) style.

```

\renewcommand*\glxtrininlinefullformat[2]{%
  \glxtrshortlongformat{##1}{##2}%
  {\glsfirstlongfootnotefont}{\glsfirstabbrvfont}%
}%
\renewcommand*\glxtrininlinefullplformat[2]{%
  \glxtrshortlongplformat{##1}{##2}%
  {\glsfirstlongfootnotefont}{\glsfirstabbrvfont}%
}%
\renewcommand*\Glsxtrininlinefullformat[2]{%
  \Glsxtrshortlongformat{##1}{##2}%
  {\glsfirstlongfootnotefont}{\glsfirstabbrvfont}%
}%
\renewcommand*\Glsxtrininlinefullplformat[2]{%

```

```

\Glsxtrshortlongplformat{##1}{##2}%
{\glsfirstlongfootnotefont}{\glsfirstabbrvfont}%
}%
\renewcommand*{\GlsXtrinlinefullformat}[2]{%
\Glsxtrshortlongformat{##1}{##2}%
{\glsfirstlongfootnotefont}{\glsfirstabbrvfont}%
}%
\renewcommand*{\GlsXtrinlinefullplformat}[2]{%
\Glsxtrshortlongplformat{##1}{##2}%
{\glsfirstlongfootnotefont}{\glsfirstabbrvfont}%
}%
}

```

short-postfootnote

```
\letabbreviationstyle{short-postfootnote}{postfootnote}
```

short-postfootnote-desc Like short-postfootnote but with user supplied description.

```

\newabbreviationstyle{short-postfootnote-desc}%
{%

```

Set accessibility attributes if enabled.

```
\glxtrAccSuppAbbrSetNameLongAttrs\glscategorylabel
```

Setup the default fields.

```

\renewcommand*{\CustomAbbreviationFields}{%
name={\glxtrfootnotedesname},
sort={\glxtrfootnotedesort},
first={\glsfirstxpabbrvfont{\the\glsshorttok}{\glscategorylabel}},%
firstplural={\glsfirstxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}},%

text={\glxspabbrvfont{\the\glsshorttok}{\glscategorylabel}},%
plural={\glxspabbrvfont{\the\glsshortpltok}{\glscategorylabel}}}%

```

Make this category insert a footnote after the link if this was the first use, and unset the `regular` attribute if it has been set. Previously this was done by redefining `glxtrsetupfuldefs` but that interferes with other styles. Instead, this now uses `\glxtrifwasglslike`

```

\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\csdef{glxtrpostlink\glscategorylabel}{%
\glxtrifwasglslikeandfirstuse
}%

```

Ensure `\glslabel` and `\glxtrassignlinktextfmt` are expanded as they may be lost by the time the footnote occurs.

```

\glxtrdopostpunc{\expandafter\expandafter\expandafter
\glxtrpostabbrvfootnote
\expandafter\expandafter\expandafter
{\expandafter\glslabel\expandafter}\expandafter
{\glxtrassignlinktextfmt}}}%
}%
{}%

```

```

}%
\glshasattribute{\the\glslabeltok}{regular}%
{%
  \glissetattribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%
\GlsXtrUseAbbrStyleFmts{postfootnote}%
}

```

postfootnote-desc

```
\letabbreviationstyle{postfootnote-desc}{short-postfootnote-desc}
```

\glxtrshortnolongname

```

\newcommand*{\glxtrshortnolongname}{%
  \glxppabrvfont{\the\glsshorttok}{\glscategorylabel}%
}

```

short Provide a style that only displays the short form on first use, but the short and long form can be displayed with the “full” commands that use the inline format. If the user supplies a description, the long form won’t be displayed in the predefined glossary styles, but the post description hook can be employed to automatically insert it.

```

\newabbreviationstyle{short}%
{%

```

Set accessibility attributes if enabled.

```
\glxtrAccSuppAbbrSetNoLongAttrs\glscategorylabel
```

Setup the default fields.

```

\renewcommand*{\CustomAbbreviationFields}{%
  name={\glxtrshortnolongname},
  sort={\the\glsshorttok},
  first={\glsfirstrpabrvfont{\the\glsshorttok}{\glscategorylabel}},
  firstplural={\glsfirstrpabrvfont{\the\glsshortpltok}{\glscategorylabel}},
  text={\glxppabrvfont{\the\glsshorttok}{\glscategorylabel}},
  plural={\glxppabrvfont{\the\glsshortpltok}{\glscategorylabel}},
  description={\the\glslongtok}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glissetattribute{\the\glslabeltok}{regular}{true}}%
}%
{%

```

In case the user wants to mix and match font styles, these are redefined here.

```

\renewcommand*{\abbrvpluralsuffix}{\glxtrabbrvpluralsuffix}%
\renewcommand*{\glabbrvfont}[1]{\glabbrvdefaultfont{##1}}%
\renewcommand*{\glsfirabbrvfont}[1]{\glsfirabbrvdefaultfont{##1}}%
\renewcommand*{\glsfirlongfont}[1]{\glsfirlongdefaultfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%

```

The inline full form displays the short form followed by the long form in parentheses.

```
\renewcommand*{\glxstrinlinefullformat}[2]{%
  \glxstrshortlongformat{##1}{##2}%
  {\glsfirstlongfont}{\glsfirstabbrvfont}%
}%
\renewcommand*{\glxstrinlinefullplformat}[2]{%
  \glxstrshortlongplformat{##1}{##2}%
  {\glsfirstlongfont}{\glsfirstabbrvfont}%
}%
\renewcommand*{\Glsxstrinlinefullformat}[2]{%
  \Glsxstrshortlongformat{##1}{##2}%
  {\glsfirstlongfont}{\glsfirstabbrvfont}%
}%
\renewcommand*{\Glsxstrinlinefullplformat}[2]{%
  \Glsxstrshortlongplformat{##1}{##2}%
  {\glsfirstlongfont}{\glsfirstabbrvfont}%
}%
\renewcommand*{\GLSxstrinlinefullformat}[2]{%
  \GLSxstrshortlongformat{##1}{##2}%
  {\glsfirstlongfont}{\glsfirstabbrvfont}%
}%
\renewcommand*{\GLSxstrinlinefullplformat}[2]{%
  \GLSxstrshortlongplformat{##1}{##2}%
  {\glsfirstlongfont}{\glsfirstabbrvfont}%
}%
}
```

The first use full form only displays the short form, but it typically won't be used as the `regular` attribute is set by this style.

```
\renewcommand*{\glxstrfullformat}[2]{%
  \glxstrshortformat{##1}{##2}{\glsfirstabbrvfont}%
}%
\renewcommand*{\glxstrfullplformat}[2]{%
  \glxstrshortplformat{##1}{##2}{\glsfirstabbrvfont}%
}%
\renewcommand*{\Glsxstrfullformat}[2]{%
  \Glsxstrshortformat{##1}{##2}{\glsfirstabbrvfont}%
}%
\renewcommand*{\Glsxstrfullplformat}[2]{%
  \Glsxstrshortplformat{##1}{##2}{\glsfirstabbrvfont}%
}%
\renewcommand*{\GLSxstrfullformat}[2]{%
  \GLSxstrshortformat{##1}{##2}{\glsfirstabbrvfont}%
}%
\renewcommand*{\GLSxstrfullplformat}[2]{%
  \GLSxstrshortplformat{##1}{##2}{\glsfirstabbrvfont}%
}%
}
```

Set this as the default style for acronyms:

```

\setabbreviationstyle[acronym]{short}

short-nolong
\letabbreviationstyle{short-nolong}{short}

short-nolong-noreg Like short-nolong but doesn't set the regular attribute.
\newabbreviationstyle{short-nolong-noreg}%
{%
  \GlsXtrUseAbbrStyleSetup{short-nolong}%
  Unset the regular attribute if it has been set.
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \glshasattribute{\the\glslabeltok}{regular}%
    {%
      \glissetattribute{\the\glslabeltok}{regular}{false}%
    }%
  }%
}%
{%
  \GlsXtrUseAbbrStyleFmts{short-nolong}%
}%

\glxtrshortdescname
\newcommand*{\glxtrshortdescname}{%
  \glxtpabrvfont{\the\glsshorttok}{\glscategorylabel}%
  \protect\glxtrfullsep{\the\glslabeltok}%
  \protect\glxtrparen{\glxplongfont{\the\glslongtok}{\glscategorylabel}}%
}%

short-desc The user must supply the description in this style. The long form is added to
the name. The short style (possibly with the post-description hooks set) might
be a better option.
\newabbreviationstyle{short-desc}%
{%
  Set accessibility attributes if enabled.
  \glxtrAccSuppAbbrSetNoLongAttrs\glscategorylabel
  Setup the default fields.
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glxtrshortdescname},
    sort={\the\glsshorttok},
    first={\glxfirstxpabrvfont{\the\glsshorttok}{\glscategorylabel}},
    firstplural={\glxfirstxpabrvfont{\the\glsshortpltok}{\glscategorylabel}},
    text={\glxtpabrvfont{\the\glsshorttok}{\glscategorylabel}},
    plural={\glxtpabrvfont{\the\glsshortpltok}{\glscategorylabel}}}%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \glissetattribute{\the\glslabeltok}{regular}{true}}%
}%
{%

```


In case the user wants to mix and match font styles, these are redefined here.

```
\renewcommand*\abbrvpluralsuffix{\glxtrabbrvpluralsuffix}%
\renewcommand*\glsabbrvfont[1]{\glsabbrvdefaultfont{##1}}%
\renewcommand*\glsfirstabbrvfont[1]{\glsfirstabbrvdefaultfont{##1}}%
\renewcommand*\glsfirstlongfont[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*\glslongfont[1]{\glslongdefaultfont{##1}}%
```

The inline full form displays the short format followed by the long form in parentheses.

```
\renewcommand*\glxtrinlinefullformat[2]{%
  \glxtrshortlongformat{##1}{##2}%
  {\glsfirstlongfont}{\glsfirstabbrvfont}}%
}%
\renewcommand*\glxtrinlinefullplformat[2]{%
  \glxtrshortlongplformat{##1}{##2}%
  {\glsfirstlongfont}{\glsfirstabbrvfont}}%
}%
\renewcommand*\Glsxtrinlinefullformat[2]{%
  \Glsxtrshortlongformat{##1}{##2}%
  {\glsfirstlongfont}{\glsfirstabbrvfont}}%
}%
\renewcommand*\Glsxtrinlinefullplformat[2]{%
  \Glsxtrshortlongplformat{##1}{##2}%
  {\glsfirstlongfont}{\glsfirstabbrvfont}}%
}%
\renewcommand*\GLSxtrinlinefullformat[2]{%
  \GLSxtrshortlongformat{##1}{##2}%
  {\glsfirstlongfont}{\glsfirstabbrvfont}}%
}%
\renewcommand*\GLSxtrinlinefullplformat[2]{%
  \GLSxtrshortlongplformat{##1}{##2}%
  {\glsfirstlongfont}{\glsfirstabbrvfont}}%
}%
```

The first use full form only displays the short form, but it typically won't be used as the `regular` attribute is set by this style.

```
\renewcommand*\glxtrfullformat[2]{%
  \glxtrshortformat{##1}{##2}{\glsfirstabbrvfont}}%
}%
\renewcommand*\glxtrfullplformat[2]{%
  \glxtrshortplformat{##1}{##2}{\glsfirstabbrvfont}}%
}%
\renewcommand*\Glsxtrfullformat[2]{%
  \Glsxtrshortformat{##1}{##2}{\glsfirstabbrvfont}}%
}%
\renewcommand*\Glsxtrfullplformat[2]{%
  \Glsxtrshortplformat{##1}{##2}{\glsfirstabbrvfont}}%
}%
\renewcommand*\GLSxtrfullformat[2]{%
  \GLSxtrshortformat{##1}{##2}{\glsfirstabbrvfont}}%
}%
```

```

}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
  \GLSxtrshortplformat{##1}{##2}{\glsfirstabbrvfont}%
}%
}

```

short-nolong-desc

```
\letabbreviationstyle{short-nolong-desc}{short-desc}
```

short-nolong-desc-noreg Like short-nolong-desc but doesn't set the regular attribute.

```

\newabbreviationstyle{short-nolong-desc-noreg}%
{%
  \GLSxtrUseAbbrStyleSetup{short-nolong-desc}%
  Unset the regular attribute if it has been set.
  \renewcommand*{\GLSxtrPostNewAbbreviation}{%
    \glshasattribute{\the\glslabeltok}{regular}%
    {%
      \glissetattribute{\the\glslabeltok}{regular}{false}%
    }%
  }%
}%
{%
  \GLSxtrUseAbbrStyleFmts{short-nolong-desc}%
}

```

nolong-short Similar to short-nolong but the full form shows the long form followed by the short form in parentheses.

```

\newabbreviationstyle{nolong-short}%
{%
  \GLSxtrUseAbbrStyleSetup{short-nolong}%
}%
{%
  \GLSxtrUseAbbrStyleFmts{short-nolong}%
}

```

The inline full form displays the long form followed by the short form in parentheses.

```

\renewcommand*{\glxtrinlinefullformat}[2]{%
  \glxtrlongshortformat{##1}{##2}%
  {\glsfirstlongfont}{\glsfirstabbrvfont}%
}%
\renewcommand*{\glxtrinlinefullplformat}[2]{%
  \glxtrlongshortplformat{##1}{##2}%
  {\glsfirstlongfont}{\glsfirstabbrvfont}%
}%
\renewcommand*{\GLSxtrinlinefullformat}[2]{%
  \GLSxtrlongshortformat{##1}{##2}%
  {\glsfirstlongfont}{\glsfirstabbrvfont}%
}%

```

```

\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \Glsxtrlongshortplformat{##1}{##2}%
  {\glsfirstlongfont}{\glsfirstabbrvfont}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \Glsxtrlongshortformat{##1}{##2}%
  {\glsfirstlongfont}{\glsfirstabbrvfont}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \Glsxtrlongshortplformat{##1}{##2}%
  {\glsfirstlongfont}{\glsfirstabbrvfont}%
}%
}

```

nolong-short-noreg Like nolong-short but doesn't set the regular attribute.

```

\newabbreviationstyle{nolong-short-noreg}%
{%
  \GlsXtrUseAbbrStyleSetup{nolong-short}%
}
Unset the regular attribute if it has been set.
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glssetattribute{\the\glslabeltok}{regular}{false}%
  }%
  {}%
}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glssetattribute{\the\glslabeltok}{regular}{false}%
  }%
  {}%
}%
\GlsXtrUseAbbrStyleFmts{nolong-short}%
}

```

\glsxtrlongnoshortdescname

```

\newcommand*{\glsxtrlongnoshortdescname}{%
  \glsxplongfont{\the\glslongtok}{\glscategorylabel}%
}

```

long-desc Provide a style that only displays the long form, but the long and short form can be displayed with the “full” commands that use the inline format. The predefined glossary styles won't show the short form. The user must supply a description for this style. The accessibility attributes don't need setting here.

```

\newabbreviationstyle{long-desc}%
{%
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glsxtrlongnoshortdescname},
    sort={\the\glslongtok},
    first={\glsfirstxplongfont{\the\glslongtok}{\glscategorylabel}},
    firstplural={\glsfirstxplongfont{\the\glslongpltok}{\glscategorylabel}},
    text={\glsxplongfont{\the\glslongtok}{\glscategorylabel}},
    plural={\glsxplongfont{\the\glslongpltok}{\glscategorylabel}}%
  }
}

```

```
}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glssetattribute{\the\glslabeltok}{regular}{true}}%
}%
{%
```

In case the user wants to mix and match font styles, these are redefined here.

```
\renewcommand*{\abbrvpluralsuffix}{\glxtrabbrvpluralsuffix}%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvdefaultfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvdefaultfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%
```

The format for subsequent use (not used when the regular attribute is set).

```
\renewcommand*{\glxtrs subsequentfmt}[2]{%
  \glxtrlongformat{##1}{##2}{\glslongfont}}%
}%
\renewcommand*{\glxtrs subsequentplfmt}[2]{%
  \glxtrlongplformat{##1}{##2}{\glslongfont}}%
}%
\renewcommand*{\Glsxtrs subsequentfmt}[2]{%
  \Glsxtrlongformat{##1}{##2}{\glslongfont}}%
}%
\renewcommand*{\Glsxtrs subsequentplfmt}[2]{%
  \Glsxtrlongplformat{##1}{##2}{\glslongfont}}%
}%
\renewcommand*{\GLSxtrs subsequentfmt}[2]{%
  \GLSxtrlongformat{##1}{##2}{\glslongfont}}%
}%
\renewcommand*{\GLSxtrs subsequentplfmt}[2]{%
  \GLSxtrlongplformat{##1}{##2}{\glslongfont}}%
}%
```

The inline full form displays the long format followed by the short form in parentheses.

```
\renewcommand*{\glxtrinlinefullformat}[2]{%
  \glxtrlongshortformat{##1}{##2}%
  {\glsfirstlongfont}{\glsfirstabbrvfont}}%
}%
\renewcommand*{\glxtrinlinefullplformat}[2]{%
  \glxtrlongshortplformat{##1}{##2}%
  {\glsfirstlongfont}{\glsfirstabbrvfont}}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \Glsxtrlongshortformat{##1}{##2}%
  {\glsfirstlongfont}{\glsfirstabbrvfont}}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \Glsxtrlongshortplformat{##1}{##2}%
  {\glsfirstlongfont}{\glsfirstabbrvfont}}%
}%
```

```

\renewcommand*{\GLSxtrinlinefullformat}[2]{%
  \GLSxtrlongshortformat{##1}{##2}%
  {\glsfirstlongfont}{\glsfirstabbrvfont}%
}%
\renewcommand*{\GLSxtrinlinefullplformat}[2]{%
  \GLSxtrlongshortplformat{##1}{##2}%
  {\glsfirstlongfont}{\glsfirstabbrvfont}%
}%

```

The first use full form only displays the long form, but it typically won't be used as the `regular` attribute is set by this style.

```

\renewcommand*{\glsxtrfullformat}[2]{%
  \glsxtrlongformat{##1}{##2}{\glsfirstlongfont}%
}%
\renewcommand*{\glsxtrfullplformat}[2]{%
  \glsxtrlongplformat{##1}{##2}{\glsfirstlongfont}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \Glsxtrlongformat{##1}{##2}{\glsfirstlongfont}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \Glsxtrlongplformat{##1}{##2}{\glsfirstlongfont}%
}%
\renewcommand*{\GLSxtrfullformat}[2]{%
  \GLSxtrlongformat{##1}{##2}{\glsfirstlongfont}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
  \GLSxtrlongplformat{##1}{##2}{\glsfirstlongfont}%
}%
}

```

`long-noshort-desc` Provide a synonym that matches similar styles.

```
\letabbreviationstyle{long-noshort-desc}{long-desc}
```

`long-noshort-desc-noreg` Like `long-noshort-desc` but doesn't set the `regular` attribute.

```

\newabbreviationstyle{long-noshort-desc-noreg}%
{%
  \GlsXtrUseAbbrStyleSetup{long-noshort-desc}%
}

```

Unset the `regular` attribute if it has been set.

```

\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glissetattribute{\the\glslabeltok}{regular}{false}%
  }%
}%
{%
  \GlsXtrUseAbbrStyleFmts{long-noshort-desc}%
}

```

`\glxstrlongnoshortname`

```
\newcommand*{\glxstrlongnoshortname}{%  
  \glxppabrvfont{\the\glsshorttok}{\glscategorylabel}%  
}
```

`long` It doesn't really make a great deal of sense to have a long-only style that doesn't have a description (unless no glossary is required), but the best course of action here is to use the short form as the name and the long form as the description.

```
\newabbreviationstyle{long}%  
{%
```

Set accessibility attributes if enabled.

```
\glxstrAccSuppAbbrSetNameShortAttrs\glscategorylabel
```

Setup the default fields.

```
\renewcommand*{\CustomAbbreviationFields}{%  
  name={\glxstrlongnoshortname},  
  sort={\the\glsshorttok},  
  first={\glxfirstxplongfont{\the\glslongtok}{\glscategorylabel}},  
  firstplural={\glxfirstxplongfont{\the\glslongpltok}{\glscategorylabel}},  
  text={\glxplongfont{\the\glslongtok}{\glscategorylabel}},  
  plural={\glxplongfont{\the\glslongpltok}{\glscategorylabel}},%  
  description={\the\glslongtok}%  
}%  
\renewcommand*{\GlsXtrPostNewAbbreviation}{%  
  \glsssetattribute{\the\glslabeltok}{regular}{true}}%  
}%  
{%  
  \GlsXtrUseAbbrStyleFmts{long-desc}%  
}
```

`long-noshort` Provide a synonym that matches similar styles.

```
\letabbreviationstyle{long-noshort}{long}
```

`long-noshort-noreg` Like `long-noshort` but doesn't set the regular attribute.

```
\newabbreviationstyle{long-noshort-noreg}%  
{%  
  \GlsXtrUseAbbrStyleSetup{long-noshort}%
```

Unset the regular attribute if it has been set.

```
\renewcommand*{\GlsXtrPostNewAbbreviation}{%  
  \glshasattribute{\the\glslabeltok}{regular}%  
  {%  
    \glsssetattribute{\the\glslabeltok}{regular}{false}%  
  }%  
  {}%  
}%  
}%  
{%  
  \GlsXtrUseAbbrStyleFmts{long-noshort}%  
}
```

2.2 Predefined Styles (Small Capitals)

These styles use `\textsc` for the short form.

`\glxtrscfont` Maintained for backward-compatibility.
`\newcommand*{\glxtrscfont}[1]{\textsc{#1}}`

`\glsabbrvscfont` Added for consistent naming.
`\newcommand*{\glsabbrvscfont}{\glxtrscfont}`

`\glxtrfirstscfont` Maintained for backward-compatibility.
`\newcommand*{\glxtrfirstscfont}[1]{\glsabbrvscfont{#1}}`

`\glsfirstabbrvscfont` Added for consistent naming.
`\newcommand*{\glsfirstabbrvscfont}{\glxtrfirstscfont}`

and for the default short form suffix:

`\glxtrscsuffix` `\protect` needs to come inside `\glxtrscsuffix` to avoid interfering with all caps.
`\newcommand*{\glxtrscsuffix}{\protect\glstextup{\glxtrabbrvpluralsuffix}}`

`\glxtrscinvert` Cancel smallcaps.
`\newcommand*{\glxtrscinvert}[1]{\glstextup{#1}}%`

v1.49: the following now use commands like `\glsfirstinnerfmtabbrvfont` instead of `\glsfirstabbrvscfont` etc. This makes it easier to apply the inner formatting. The scoping added in v1.48 with `\glslinkwrcontent` should prevent formatting leakage in the event of nested commands. The only problem will be if commands like `\glstryfirst` are used, but those aren't designed for consistent formatting. It will also make it easier to locally redefine `\glsfirstinnerfmtabbrvfont` to strip the formatting if those commands are used (rather than having to define all the possible abbreviation style formatting commands). Since these new commands are robust they don't need protecting.

`long-short-sc`

`\newabbreviationstyle{long-short-sc}%`
`{%`

Set accessibility attributes if enabled.

`\glxtrAccSuppAbbrSetFirstLongAttrs\glscategorylabel`

Setup the default fields.

`\renewcommand*{\CustomAbbreviationFields}{%`
`name={\glxtrlongshortname},`
`sort={\the\glsshorttok},`
`first={\glsfirstxplongfont{\the\glslongtok}{\glscategorylabel}%`
`\protect\glxtrfullsep{\the\glslabeltok}%`
`\protect\glxtrparen{\glsfirstxpabbrvfont{\the\glsshorttok}{\glscategorylabel}}},%`
`firstplural={\glsfirstxplongfont{\the\glslongpltok}{\glscategorylabel}%`

```

\protect\glxtrfullsep{\the\glslabeltok}%
\protect\glxtrparen{\glxfirstxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}}},%
text={\glxpabbrvfont{\the\glsshorttok}{\glscategorylabel}},%
plural={\glxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}},%
description={\the\glslongtok}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glxtrsetcomplexstyle{\the\glslabeltok}{3}%
\glshasattribute{\the\glslabeltok}{regular}%
{%
\glssetattribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%
{%

```

Use smallcaps and adjust the plural suffix to revert to upright.

```

\renewcommand*{\abbrvpluralsuffix}{\glxtrscsuffix}%
\renewcommand*{\glxabbrvfont}[1]{\glxabbrvscfont{##1}}%
\renewcommand*{\glxfirstabbrvfont}[1]{\glxfirstabbrvscfont{##1}}%
\renewcommand*{\glxtrrevert}[1]{\glxtrscinvert{##1}}%

```

Use the default long fonts.

```

\renewcommand*{\glxfirstlongfont}[1]{\glxfirstlongdefaultfont{##1}}%
\renewcommand*{\glxlongfont}[1]{\glxlongdefaultfont{##1}}%

```

The first use full form and the inline full form are the same for this style.

```

\renewcommand*{\glxtrfullformat}[2]{%
\glxtrlongshortformat{##1}{##2}%
{\glxfirstlongdefaultfont}{\glxfirstabbrvscfont}%
}%
\renewcommand*{\glxtrfullplformat}[2]{%
\glxtrlongshortplformat{##1}{##2}%
{\glxfirstlongdefaultfont}{\glxfirstabbrvscfont}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
\Glsxtrlongshortformat{##1}{##2}%
{\glxfirstlongdefaultfont}{\glxfirstabbrvscfont}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
\Glsxtrlongshortplformat{##1}{##2}%
{\glxfirstlongdefaultfont}{\glxfirstabbrvscfont}%
}%
\renewcommand*{\GLSxtrfullformat}[2]{%
\GLSxtrlongshortformat{##1}{##2}%
{\glxfirstlongdefaultfont}{\glxfirstabbrvscfont}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
\GLSxtrlongshortplformat{##1}{##2}%
{\glxfirstlongdefaultfont}{\glxfirstabbrvscfont}%
}%

```


}

long-short-sc-desc

```
\newabbreviationstyle{long-short-sc-desc}%
{%
```

Set accessibility attributes if enabled.

```
\glxstrAccSuppAbbrSetTextShortAttrs\glscategorylabel
```

Setup the default fields.

```
\renewcommand*{\CustomAbbreviationFields}{%
  name={\glxstrlongshortdescname},
  sort={\glxstrlongshortdescsort},%
  first={\glsfirstxplongfont{\the\glslongtok}{\glscategorylabel}%
    \protect\glxstrfullsep{\the\glslabeltok}%
    \protect\glxstrparen{\glsfirstxpabrvfont{\the\glsshorttok}{\glscategorylabel}}},%
  firstplural={\glsfirstxplongfont{\the\glslongpltok}{\glscategorylabel}%
    \protect\glxstrfullsep{\the\glslabeltok}%
    \protect\glxstrparen{\glsfirstxpabrvfont{\the\glsshortpltok}{\glscategorylabel}}},%
  text={\glxspabrvfont{\the\glsshorttok}{\glscategorylabel}},%
  plural={\glxspabrvfont{\the\glsshortpltok}{\glscategorylabel}}%
}%
```

Unset the regular attribute if it has been set.

```
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glxstrsetcomplexstyle{\the\glslabeltok}{3}%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glissetattribute{\the\glslabeltok}{regular}{false}%
  }%
  {}%
}%
```

As long-short-sc style:

```
\GlsXtrUseAbbrStyleFmts{long-short-sc}%
}
```

short-sc-long Now the short (long) version

```
\newabbreviationstyle{short-sc-long}%
{%
```

Set accessibility attributes if enabled.

```
\glxstrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
```

Setup the default fields.

```
\renewcommand*{\CustomAbbreviationFields}{%
  name={\glxstrshortlongname},
  sort={\the\glsshorttok},
  description={\the\glslongtok},%
  first={\glsfirstxpabrvfont{\the\glsshorttok}{\glscategorylabel}}%
```

```

\protect\glxtrfullsep{\the\glslabeltok}%
\protect\glxtrparen{\glstxtrplongfont{\the\glslongtok}{\glscategorylabel}}},%
firstplural={\glstxtrpabrvfont{\the\glsshortpltok}{\glscategorylabel}%
\protect\glxtrfullsep{\the\glslabeltok}%
\protect\glxtrparen{\glstxtrplongfont{\the\glslongpltok}{\glscategorylabel}}},%
text={\glstxtrpabrvfont{\the\glsshorttok}{\glscategorylabel}}},%
plural={\glstxtrpabrvfont{\the\glsshortpltok}{\glscategorylabel}}}%

```

Unset the regular attribute if it has been set.

```

\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glxtrsetcomplexstyle{\the\glslabeltok}{3}%
\glshasattribute{\the\glslabeltok}{regular}%
{%
\glissetattribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%

```

Use smallcaps and adjust the plural suffix to revert to upright.

```

\renewcommand*{\abbrvpluralsuffix}{\glstxrscsuffix}%
\renewcommand*{\glstxtrpabrvfont}[1]{\glstxtrpabrvfont{##1}}%
\renewcommand*{\glstxtrfirstabbrvfont}[1]{\glstxtrfirstabbrvfont{##1}}%
\renewcommand*{\glstxtrfirstlongfont}[1]{\glstxtrfirstlongdefaultfont{##1}}%
\renewcommand*{\glstxtrlongfont}[1]{\glstxtrlongdefaultfont{##1}}%
\renewcommand*{\glstxtrrevert}[1]{\glstxtrrevert{##1}}%

```

The first use full form and the inline full form are the same for this style.

```

\renewcommand*{\glstxtrfullformat}[2]{%
\glstxtrshortlongformat{##1}{##2}%
{\glstxtrfirstlongdefaultfont}{\glstxtrfirstabbrvfont}%
}%
\renewcommand*{\glstxtrfullplformat}[2]{%
\glstxtrshortlongplformat{##1}{##2}%
{\glstxtrfirstlongdefaultfont}{\glstxtrfirstabbrvfont}%
}%
\renewcommand*{\GlsXtrfullformat}[2]{%
\GlsXtrshortlongformat{##1}{##2}%
{\glstxtrfirstlongdefaultfont}{\glstxtrfirstabbrvfont}%
}%
\renewcommand*{\GlsXtrfullplformat}[2]{%
\GlsXtrshortlongplformat{##1}{##2}%
{\glstxtrfirstlongdefaultfont}{\glstxtrfirstabbrvfont}%
}%
\renewcommand*{\GLSxtrfullformat}[2]{%
\GLSxtrshortlongformat{##1}{##2}%
{\glstxtrfirstlongdefaultfont}{\glstxtrfirstabbrvfont}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
\GLSxtrshortlongplformat{##1}{##2}%

```

```

        {\glsfirstlongdefaultfont}{\glsfirstabbrvscfont}%
    }%
}

```

short-sc-long-desc As before but user provides description

```

\newabbreviationstyle{short-sc-long-desc}%
{%

```

Set accessibility attributes if enabled.

```

\glsxtrAccSuppAbbrSetTextShortAttrs\glscategorylabel

```

Setup the default fields.

```

\renewcommand*{\CustomAbbreviationFields}{%
    name={\glsxtrshortlongdescname},
    sort={\glsxtrshortlongdescsort},
    first={\glsfirstxpabbrvfont{\the\glsshorttok}{\glscategorylabel}%
        \protect\glsxtrfullsep{\the\glslabeltok}%
        \protect\glsxtrparen{\glsfirstxplongfont{\the\glslongtok}{\glscategorylabel}}},%
    firstplural={\glsfirstxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}%
        \protect\glsxtrfullsep{\the\glslabeltok}%
        \protect\glsxtrparen{\glsfirstxplongfont{\the\glslongpltok}{\glscategorylabel}}},%
    text={\glsxpabbrvfont{\the\glsshorttok}{\glscategorylabel}}},%
    plural={\glsxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}}%
}%

```

Unset the regular attribute if it has been set.

```

\renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \glsxtrsetcomplexstyle{\the\glslabeltok}{3}%
    \glshasattribute{\the\glslabeltok}{regular}%
    {%
        \glissetattribute{\the\glslabeltok}{regular}{false}%
    }%
    {}%
}%

```

As short-sc-long style:

```

\GlsXtrUseAbbrStyleFmts{short-sc-long}%
}

```

short-sc

```

\newabbreviationstyle{short-sc}%
{%

```

Set accessibility attributes if enabled.

```

\glsxtrAccSuppAbbrSetNoLongAttrs\glscategorylabel

```

Setup the default fields.

```

\renewcommand*{\CustomAbbreviationFields}{%
    name={\glsxtrshortnolongname},
    sort={\the\glsshorttok},

```

```

first={\glsfirstxpabbrvfont{\the\glsshorttok}{\glscategorylabel}},
firstplural={\glsfirstxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}},
text={\glspabbrvfont{\the\glsshorttok}{\glscategorylabel}},
plural={\glspabbrvfont{\the\glsshortpltok}{\glscategorylabel}},
description={\the\glslongtok}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glssetattribute{\the\glslabeltok}{regular}{true}}%
}%
{%

```

Use smallcaps and adjust the plural suffix to revert to upright.

```

\renewcommand*{\abrvpluralsuffix}{\glstrscsuffix}%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvscfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvscfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%
\renewcommand*{\glsxtrrevert}[1]{\glsxtrsc revert{##1}}%

```

The inline full form displays the short form followed by the long form in parentheses.

```

\renewcommand*{\glsxtrinlinefullformat}[2]{%
  \glsxtrshortlongformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvscfont}}%
}%
\renewcommand*{\glsxtrinlinefullplformat}[2]{%
  \glsxtrshortlongplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvscfont}}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \Glsxtrshortlongformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvscfont}}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \Glsxtrshortlongplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvscfont}}%
}%
\renewcommand*{\GLSxtrinlinefullformat}[2]{%
  \GLSxtrshortlongformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvscfont}}%
}%
\renewcommand*{\GLSxtrinlinefullplformat}[2]{%
  \GLSxtrshortlongplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvscfont}}%
}%

```

The first use full form only displays the short form, but it typically won't be used as the **regular** attribute is set by this style.

```

\renewcommand*{\glsxtrfullformat}[2]{%
  \glsxtrshortformat{##1}{##2}{\glsfirstabbrvscfont}}%
}%

```

```

\renewcommand*{\glxtrfullplformat}[2]{%
  \glxtrshortplformat{##1}{##2}{\glsfirstabbrvscfont}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \Glsxtrshortformat{##1}{##2}{\glsfirstabbrvscfont}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \Glsxtrshortplformat{##1}{##2}{\glsfirstabbrvscfont}%
}%
\renewcommand*{\GLSxtrfullformat}[2]{%
  \GLSxtrshortformat{##1}{##2}{\glsfirstabbrvscfont}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
  \GLSxtrshortplformat{##1}{##2}{\glsfirstabbrvscfont}%
}%
}

```

short-sc-nolong

```
\letabbreviationstyle{short-sc-nolong}{short-sc}
```

short-sc-desc

```

\newabbreviationstyle{short-sc-desc}%
{%

```

Set accessibility attributes if enabled.

```
\glxtrAccSuppAbbrSetNameLongAttrs\glscategorylabel
```

Setup the default fields.

```

\renewcommand*{\CustomAbbreviationFields}{%
  name={\glxtrshortdescname},
  sort={\the\glsshorttok},
  first={\glsfirstxpabbrvfont{\the\glsshorttok}{\glscategorylabel}},
  firstplural={\glsfirstxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}},
  text={\glxpabbrvfont{\the\glsshorttok}{\glscategorylabel}},
  plural={\glxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glsetattribute{\the\glslabeltok}{regular}{true}}%
}%
{%

```

Use smallcaps and adjust the plural suffix to revert to upright.

```

\renewcommand*{\abbrvpluralsuffix}{\glxtrscsuffix}%
\renewcommand*{\glabbrvfont}[1]{\glabbrvscfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvscfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%
\renewcommand*{\glxtrrevert}[1]{\glxtrscinvert{##1}}%

```

The inline full form displays the short format followed by the long form in parentheses.

```
\renewcommand*{\glxtrinlinefullformat}[2]{%
```

```

\glstrshortlongformat{##1}{##2}%
{\glsfirstlongdefaultfont}{\glsfirstabbrvscfont}%
}%
\renewcommand*{\glstrinlinefullplformat}[2]{%
\glstrshortlongplformat{##1}{##2}%
{\glsfirstlongdefaultfont}{\glsfirstabbrvscfont}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
\Glsxtrshortlongformat{##1}{##2}%
{\glsfirstlongdefaultfont}{\glsfirstabbrvscfont}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
\Glsxtrshortlongplformat{##1}{##2}%
{\glsfirstlongdefaultfont}{\glsfirstabbrvscfont}%
}%
\renewcommand*{\GLSxtrinlinefullformat}[2]{%
\GLSxtrshortlongformat{##1}{##2}%
{\glsfirstlongdefaultfont}{\glsfirstabbrvscfont}%
}%
\renewcommand*{\GLSxtrinlinefullplformat}[2]{%
\GLSxtrshortlongplformat{##1}{##2}%
{\glsfirstlongdefaultfont}{\glsfirstabbrvscfont}%
}%
}

```

The first use full form only displays the short form, but it typically won't be used as the `regular` attribute is set by this style.

```

\renewcommand*{\glstrfullformat}[2]{%
\glstrshortformat{##1}{##2}{\glsfirstabbrvscfont}%
}%
\renewcommand*{\glstrfullplformat}[2]{%
\glstrshortplformat{##1}{##2}{\glsfirstabbrvscfont}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
\Glsxtrshortformat{##1}{##2}{\glsfirstabbrvscfont}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
\Glsxtrshortplformat{##1}{##2}{\glsfirstabbrvscfont}%
}%
\renewcommand*{\GLSxtrfullformat}[2]{%
\GLSxtrshortformat{##1}{##2}{\glsfirstabbrvscfont}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
\GLSxtrshortplformat{##1}{##2}{\glsfirstabbrvscfont}%
}%
}

```

`short-sc-nolong-desc`

```
\letabbreviationstyle{short-sc-nolong-desc}{short-sc-desc}
```

`nolong-short-sc`

```

\newabbreviationstyle{nolong-short-sc}%
{%
  \GlsXtrUseAbbrStyleSetup{short-sc-nolong}%
}%
{%
  \GlsXtrUseAbbrStyleFmts{short-sc-nolong}%

```

The inline full form displays the long form followed by the short form in parentheses.

```

\renewcommand*{\glxtrinlinefullformat}[2]{%
  \glxtrlongshortformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvscfont}%
}%
\renewcommand*{\glxtrinlinefullplformat}[2]{%
  \glxtrlongshortplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvscfont}%
}%
\renewcommand*{\GLsxtrinlinefullformat}[2]{%
  \GLsxtrlongshortformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvscfont}%
}%
\renewcommand*{\GLsxtrinlinefullplformat}[2]{%
  \GLsxtrlongshortplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvscfont}%
}%
\renewcommand*{\GLSxtrinlinefullformat}[2]{%
  \GLSxtrlongshortformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvscfont}%
}%
\renewcommand*{\GLSxtrinlinefullplformat}[2]{%
  \GLSxtrlongshortplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvscfont}%
}%
}

```

long-noshort-sc The smallcaps font will only be used if the short form is explicitly invoked through commands like `\glxtrshort`. No accessibility attributes needed here.

```

\newabbreviationstyle{long-noshort-sc}%
{%
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glxtrlongnoshortname},
    sort={\the\glsshorttok},
    first={\glsfirstxplongfont{\the\glslongtok}{\glscategorylabel}},
    firstplural={\glsfirstxplongfont{\the\glslongpltok}{\glscategorylabel}},
    text={\glsxplongfont{\the\glslongtok}{\glscategorylabel}},
    plural={\glsxplongfont{\the\glslongpltok}{\glscategorylabel}},%
    description={\the\glslongtok}%
  }%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \glsssetattribute{\the\glslabeltok}{regular}{true}}%

```

```
}%
{%
```

Use smallcaps and adjust the plural suffix to revert to upright.

```
\renewcommand*\abbrvpluralsuffix{\glxtrscsuffix}%
\renewcommand*\glsabbrvfont[1]{\glsabbrvscfont{##1}}%
\renewcommand*\glsfirstabbrvfont[1]{\glsfirstabbrvscfont{##1}}%
\renewcommand*\glsfirstlongfont[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*\glslongfont[1]{\glslongdefaultfont{##1}}%
\renewcommand*\glxtrrevert[1]{\glxtrscinvert{##1}}%
```

The format for subsequent use (not used when the regular attribute is set).

```
\renewcommand*\glxtrsubsequentfmt[2]{%
\glxtrlongformat{##1}{##2}{\glslongdefaultfont}%
}%
\renewcommand*\glxtrsubsequentplfmt[2]{%
\glxtrlongplformat{##1}{##2}{\glslongdefaultfont}%
}%
\renewcommand*\Glsxtrsubsequentfmt[2]{%
\Glsxtrlongformat{##1}{##2}{\glslongdefaultfont}%
}%
\renewcommand*\Glsxtrsubsequentplfmt[2]{%
\Glsxtrlongplformat{##1}{##2}{\glslongdefaultfont}%
}%
\renewcommand*\GLSxtrsubsequentfmt[2]{%
\GLSxtrlongformat{##1}{##2}{\glslongdefaultfont}%
}%
\renewcommand*\Glsxtrsubsequentplfmt[2]{%
\GLSxtrlongplformat{##1}{##2}{\glslongdefaultfont}%
}%
```

The inline full form displays the long format followed by the short form in parentheses.

```
\renewcommand*\glxtrinlinefullformat[2]{%
\glxtrlongshortformat{##1}{##2}%
{\glsfirstlongdefaultfont}{\glsfirstabbrvscfont}%
}%
\renewcommand*\glxtrinlinefullplformat[2]{%
\glxtrlongshortplformat{##1}{##2}%
{\glsfirstlongdefaultfont}{\glsfirstabbrvscfont}%
}%
\renewcommand*\Glsxtrinlinefullformat[2]{%
\Glsxtrlongshortformat{##1}{##2}%
{\glsfirstlongdefaultfont}{\glsfirstabbrvscfont}%
}%
\renewcommand*\Glsxtrinlinefullplformat[2]{%
\Glsxtrlongshortplformat{##1}{##2}%
{\glsfirstlongdefaultfont}{\glsfirstabbrvscfont}%
}%
\renewcommand*\GLSxtrinlinefullformat[2]{%
\GLSxtrlongshortformat{##1}{##2}%
}
```



```

        {\glsfirstlongdefaultfont}{\glsfirstabbrvscfont}%
    }%
    \renewcommand*{\GLSxtrinlinefullplformat}[2]{%
        \GLSxtrlongshortplformat{##1}{##2}%
        {\glsfirstlongdefaultfont}{\glsfirstabbrvscfont}%
    }%

```

The first use full form only displays the long form, but it typically won't be used as the `regular` attribute is set by this style.

```

    \renewcommand*{\glsxtrfullformat}[2]{%
        \glsxtrlongformat{##1}{##2}{\glsfirstlongdefaultfont}%
    }%
    \renewcommand*{\glsxtrfullplformat}[2]{%
        \glsxtrlongplformat{##1}{##2}{\glsfirstlongdefaultfont}%
    }%
    \renewcommand*{\Glsxtrfullformat}[2]{%
        \Glsxtrlongformat{##1}{##2}{\glsfirstlongdefaultfont}%
    }%
    \renewcommand*{\Glsxtrfullplformat}[2]{%
        \Glsxtrlongplformat{##1}{##2}{\glsfirstlongdefaultfont}%
    }%
    \renewcommand*{\GLSxtrfullformat}[2]{%
        \GLSxtrlongformat{##1}{##2}{\glsfirstlongdefaultfont}%
    }%
    \renewcommand*{\GLSxtrfullplformat}[2]{%
        \GLSxtrlongplformat{##1}{##2}{\glsfirstlongdefaultfont}%
    }%
}

```

`long-sc` Backward compatibility:

```

\@glsxtr@deprecated@abbrstyle{long-sc}{long-noshort-sc}

```

`long-noshort-sc-desc` The smallcaps font will only be used if the short form is explicitly invoked through commands like `\glsxtrshort`.

```

\newabbreviationstyle{long-noshort-sc-desc}%
{%
    \GlsXtrUseAbbrStyleSetup{long-noshort-desc}%
}%
{%

```

Use smallcaps and adjust the plural suffix to revert to upright.

```

\renewcommand*{\abbrvpluralsuffix}{\glsxtrscsuffix}%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvscfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvscfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%
\renewcommand*{\glsxtrrevert}[1]{\glsxtrsc revert{##1}}%

```

The format for subsequent use (not used when the `regular` attribute is set).

```

\renewcommand*{\glsxtrsubsequentfmt}[2]{%
    \glsxtrlongformat{##1}{##2}{\glslongdefaultfont}%
}

```

```

}%
\renewcommand*{\glxtrsubsequentplfmt}[2]{%
  \glxtrlongplformat{##1}{##2}{\glslongdefaultfont}%
}%
\renewcommand*{\Glsxtrsubsequentfmt}[2]{%
  \Glsxtrlongformat{##1}{##2}{\glslongdefaultfont}%
}%
\renewcommand*{\Glsxtrsubsequentplfmt}[2]{%
  \Glsxtrlongplformat{##1}{##2}{\glslongdefaultfont}%
}%
\renewcommand*{\GLSxtrsubsequentfmt}[2]{%
  \GLSxtrlongformat{##1}{##2}{\glslongdefaultfont}%
}%
\renewcommand*{\GLSxtrsubsequentplfmt}[2]{%
  \GLSxtrlongplformat{##1}{##2}{\glslongdefaultfont}%
}%

```

The inline full form displays the long format followed by the short form in parentheses.

```

\renewcommand*{\glxtrininlinefullformat}[2]{%
  \glxtrlongshortformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvscfont}%
}%
\renewcommand*{\glxtrininlinefullplformat}[2]{%
  \glxtrlongshortplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvscfont}%
}%
\renewcommand*{\Glsxtrininlinefullformat}[2]{%
  \Glsxtrlongshortformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvscfont}%
}%
\renewcommand*{\Glsxtrininlinefullplformat}[2]{%
  \Glsxtrlongshortplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvscfont}%
}%
\renewcommand*{\GLSxtrininlinefullformat}[2]{%
  \GLSxtrlongshortformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvscfont}%
}%
\renewcommand*{\GLSxtrininlinefullplformat}[2]{%
  \GLSxtrlongshortplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvscfont}%
}%

```

The first use full form only displays the long form, but it typically won't be used as the `regular` attribute is set by this style.

```

\renewcommand*{\glxtrfullformat}[2]{%
  \glxtrlongformat{##1}{##2}{\glsfirstlongdefaultfont}%
}%
\renewcommand*{\glxtrfullplformat}[2]{%

```

```

\glstrlongplformat{##1}{##2}{\glfirstlongdefaultfont}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
\Glsxtrlongformat{##1}{##2}{\glfirstlongdefaultfont}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
\Glsxtrlongplformat{##1}{##2}{\glfirstlongdefaultfont}%
}%
\renewcommand*{\GLSxtrfullformat}[2]{%
\GLSxtrlongformat{##1}{##2}{\glfirstlongdefaultfont}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
\GLSxtrlongplformat{##1}{##2}{\glfirstlongdefaultfont}%
}%
}

```

long-desc-sc Backward compatibility:

```
\@glxtr@deprecated@abbrstyle{long-desc-sc}{long-noshort-sc-desc}
```

short-sc-footnote

```

\newabbreviationstyle{short-sc-footnote}%
{%

```

Set accessibility attributes if enabled.

```
\glxtrAccSuppAbbrSetNoLongAttrs\glscategorylabel
```

Setup the default fields.

```

\renewcommand*{\CustomAbbreviationFields}{%
name={\glxtrfootnotename},
sort={\the\glsshorttok},
description={\the\glslongtok},%
first={\glsfirstxpabbrvfont{\the\glsshorttok}{\glscategorylabel}%
\protect\glxtrabbrvfootnote{\the\glslabeltok}%
{\protect\glsfirstlongfootnotefont{\the\glslongtok}}},%
firstplural={\glsfirstxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}%
\protect\glxtrabbrvfootnote{\the\glslabeltok}%
{\protect\glsfirstlongfootnotefont{\the\glslongpltok}}},%
text={\glsexpabbrvfont{\the\glsshorttok}{\glscategorylabel}},%
plural={\glsexpabbrvfont{\the\glsshortpltok}{\glscategorylabel}}}%

```

Switch off hyperlinks on first use to prevent nested hyperlinks, and unset the regular attribute if it has been set.

```

\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glsssetAttribute{\the\glslabeltok}{nohyperfirst}{true}%
\glshasattribute{\the\glslabeltok}{regular}%
{%
\glsssetAttribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%
}%

```

{%

Use smallcaps and adjust the plural suffix to revert to upright.

```
\renewcommand*\abbrevpluralsuffix{\glxtrscsuffix}%
\renewcommand*\glsabbrvfont[1]{\glsabbrvscfont{##1}}%
\renewcommand*\glsfirstabbrvfont[1]{\glsfirstabbrvscfont{##1}}%
\renewcommand*\glsfirstlongfont[1]{\glsfirstlongfootnotefont{##1}}%
\renewcommand*\glslongfont[1]{\glslongfootnotefont{##1}}%
\renewcommand*\glxtrrevert[1]{\glxtrscreevert{##1}}%
```

The full format displays the short form followed by the long form as a footnote.

```
\renewcommand*\glxtrfullformat[2]{%
\glxtrshortformat{##1}{##2}{\glsfirstabbrvscfont}%
\protect\glxtrabbrvfootnote{##1}%
{\glxtrfootnotelongformat{##1}{\glsfirstlongfootnotefont}}%
}%
\renewcommand*\glxtrfullplformat[2]{%
\glxtrshortplformat{##1}{##2}{\glsfirstabbrvscfont}%
\protect\glxtrabbrvfootnote{##1}%
{\glxtrfootnotelongplformat{##1}{\glsfirstlongfootnotefont}}%
}%
\renewcommand*\Glsxtrfullformat[2]{%
\Glsxtrshortformat{##1}{##2}{\glsfirstabbrvscfont}%
\protect\glxtrabbrvfootnote{##1}%
{\glxtrfootnotelongformat{##1}{\glsfirstlongfootnotefont}}%
}%
\renewcommand*\Glsxtrfullplformat[2]{%
\Glsxtrshortplformat{##1}{##2}{\glsfirstabbrvscfont}%
\protect\glxtrabbrvfootnote{##1}%
{\glxtrfootnotelongplformat{##1}{\glsfirstlongfootnotefont}}%
}%
\renewcommand*\GLSxtrfullformat[2]{%
\GLSxtrshortformat{##1}{##2}{\glsfirstabbrvscfont}%
\protect\glxtrabbrvfootnote{##1}%
{\glxtrfootnotelongformat{##1}{\glsfirstlongfootnotefont}}%
}%
\renewcommand*\GLSxtrfullplformat[2]{%
\GLSxtrshortplformat{##1}{##2}{\glsfirstabbrvscfont}%
\protect\glxtrabbrvfootnote{##1}%
{\glxtrfootnotelongplformat{##1}{\glsfirstlongfootnotefont}}%
}%
\renewcommand*\GLSxtrinlinefullformat[2]{%
\glxtrshortlongformat{##1}{##2}%
{\glsfirstlongfootnotefont}{\glsfirstabbrvscfont}%
}%
\renewcommand*\glxtrinlinefullplformat[2]{%
\glxtrshortlongplformat{##1}{##2}%
{\glsfirstlongfootnotefont}{\glsfirstabbrvscfont}%
}%
\renewcommand*\GLSxtrinlinefullplformat[2]{%
\GLSxtrshortlongplformat{##1}{##2}%
{\glsfirstlongfootnotefont}{\glsfirstabbrvscfont}%
}%
\renewcommand*\GLSxtrinlinefullformat[2]{%
\GLSxtrshortlongformat{##1}{##2}%
{\glsfirstlongfootnotefont}{\glsfirstabbrvscfont}%
}%
```

The first use full form and the inline full form use the short (long) style.

```
\renewcommand*\glxtrinlinefullformat[2]{%
\glxtrshortlongformat{##1}{##2}%
{\glsfirstlongfootnotefont}{\glsfirstabbrvscfont}%
}%
\renewcommand*\glxtrinlinefullplformat[2]{%
\glxtrshortlongplformat{##1}{##2}%
{\glsfirstlongfootnotefont}{\glsfirstabbrvscfont}%
}%
\renewcommand*\GLSxtrinlinefullformat[2]{%
\GLSxtrshortlongformat{##1}{##2}%
{\glsfirstlongfootnotefont}{\glsfirstabbrvscfont}%
}%
\renewcommand*\GLSxtrinlinefullplformat[2]{%
\GLSxtrshortlongplformat{##1}{##2}%
{\glsfirstlongfootnotefont}{\glsfirstabbrvscfont}%
}%
```

```

\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \Glsxtrshortlongformat{##1}{##2}%
  {\glsfirstlongfootnotefont}{\glsfirstabbrvscfont}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \Glsxtrshortlongplformat{##1}{##2}%
  {\glsfirstlongfootnotefont}{\glsfirstabbrvscfont}%
}%
\renewcommand*{\GLSxtrinlinefullformat}[2]{%
  \GLSxtrshortlongformat{##1}{##2}%
  {\glsfirstlongfootnotefont}{\glsfirstabbrvscfont}%
}%
\renewcommand*{\GLSxtrinlinefullplformat}[2]{%
  \GLSxtrshortlongplformat{##1}{##2}%
  {\glsfirstlongfootnotefont}{\glsfirstabbrvscfont}%
}%
}

```

footnote-sc Backward compatibility:

```
\@glxtr@deprecated@abbrstyle{footnote-sc}{short-sc-footnote}
```

short-sc-footnote-desc Like short-sc-footnote but with user supplied description.

```

\newabbreviationstyle{short-sc-footnote-desc}%
{%

```

Set accessibility attributes if enabled.

```
\glxtrAccSuppAbbrSetNameLongAttrs\glscategorylabel
```

Setup the default fields.

```

\renewcommand*{\CustomAbbreviationFields}{%
  name={\glxtrfootnotedesname},
  sort={\glxtrfootnotedesort},
  first={\glsfirstxpabbrvfont{\the\glsshorttok}{\glscategorylabel}%
    \protect\glxtrabbrvfootnote{\the\glslabeltok}%
    {\protect\glsfirstlongfootnotefont{\the\glslongtok}}},%
  firstplural={\glsfirstxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}%
    \protect\glxtrabbrvfootnote{\the\glslabeltok}%
    {\protect\glsfirstlongfootnotefont{\the\glslongpltok}}},%
  text={\glxppabbrvfont{\the\glsshorttok}{\glscategorylabel}},%
  plural={\glxppabbrvfont{\the\glsshortpltok}{\glscategorylabel}}}

```

Switch off hyperlinks on first use to prevent nested hyperlinks, and unset the regular attribute if it has been set.

```

\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glssetattribute{\the\glslabeltok}{nohyperfirst}{true}%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glssetattribute{\the\glslabeltok}{regular}{false}%
  }%
  {}%
}%

```

```
}%
{%
  \GlsXtrUseAbbrStyleFmts{short-sc-footnote}%
}
```

short-sc-postfootnote

```
\newabbreviationstyle{short-sc-postfootnote}%
{%
```

Set accessibility attributes if enabled.

```
\glstrAccSuppAbbrSetNoLongAttrs\glscategorylabel
```

Setup the default fields.

```
\renewcommand*{\CustomAbbreviationFields}{%
  name={\glstrfootnotename},
  sort={\the\glsshorttok},
  description={\the\glslongtok},%
  first={\glsfirstxpabbrfont{\the\glsshorttok}{\glscategorylabel}},%
  firstplural={\glsfirstxpabbrfont{\the\glsshortpltok}{\glscategorylabel}},%
  text={\glspabbrfont{\the\glsshorttok}{\glscategorylabel}},%
  plural={\glspabbrfont{\the\glsshortpltok}{\glscategorylabel}}}%
```

Make this category insert a footnote after the link if this was the first use, and unset the `regular` attribute if it has been set. The footnote needs to be suppressed in the inline form. Previously this was done by redefining `glstrsetupfulldefs` but that interferes with other styles. Instead, this now uses `\glstrifwasglslike`

```
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \csdef{glstrpostlink\glscategorylabel}{%
    \glstrifwasglslikeandfirstuse
    {%
      \glstrdopostpunc{\xpglstrpostabbrvfootnote}%
    }%
  }%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glsssetattribute{\the\glslabeltok}{regular}{false}%
  }%
  {}%
}%
}%
{%
```

Use smallcaps and adjust the plural suffix to revert to upright.

```
\renewcommand*{\abbrvpluralsuffix}{\glstrscsuffix}%
\renewcommand*{\glsabbrfont}[1]{\glsabbrvscfont{##1}}%
\renewcommand*{\glsfirstabbrfont}[1]{\glsfirstabbrvscfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongfootnotefont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongfootnotefont{##1}}%
\renewcommand*{\glstrrevert}[1]{\glstrscrevert{##1}}%
```

The full format displays the short form. The long form is deferred.

```
\renewcommand*\glsxtrfullformat}[2]{%
  \glsxtrshortformat{##1}{##2}{\glsfirstabbrvscfont}%
}%
\renewcommand*\glsxtrfullplformat}[2]{%
  \glsxtrshorttplformat{##1}{##2}{\glsfirstabbrvscfont}%
}%
\renewcommand*\Glsxtrfullformat}[2]{%
  \Glsxtrshortformat{##1}{##2}{\glsfirstabbrvscfont}%
}%
\renewcommand*\Glsxtrfullplformat}[2]{%
  \Glsxtrshorttplformat{##1}{##2}{\glsfirstabbrvscfont}%
}%
\renewcommand*\GLSxtrfullformat}[2]{%
  \GLSxtrshortformat{##1}{##2}{\glsfirstabbrvscfont}%
}%
\renewcommand*\GLSxtrfullplformat}[2]{%
  \GLSxtrshorttplformat{##1}{##2}{\glsfirstabbrvscfont}%
}%
```

The first use full form and the inline full form use the short (long) style.

```
\renewcommand*\glsxtrinlinefullformat}[2]{%
  \glsxtrshortlongformat{##1}{##2}%
  {\glsfirstlongfootnotefont}{\glsfirstabbrvscfont}%
}%
\renewcommand*\glsxtrinlinefullplformat}[2]{%
  \glsxtrshortlongplformat{##1}{##2}%
  {\glsfirstlongfootnotefont}{\glsfirstabbrvscfont}%
}%
\renewcommand*\Glsxtrinlinefullformat}[2]{%
  \Glsxtrshortlongformat{##1}{##2}%
  {\glsfirstlongfootnotefont}{\glsfirstabbrvscfont}%
}%
\renewcommand*\Glsxtrinlinefullplformat}[2]{%
  \Glsxtrshortlongplformat{##1}{##2}%
  {\glsfirstlongfootnotefont}{\glsfirstabbrvscfont}%
}%
\renewcommand*\GLSxtrinlinefullformat}[2]{%
  \GLSxtrshortlongformat{##1}{##2}%
  {\glsfirstlongfootnotefont}{\glsfirstabbrvscfont}%
}%
\renewcommand*\GLSxtrinlinefullplformat}[2]{%
  \GLSxtrshortlongplformat{##1}{##2}%
  {\glsfirstlongfootnotefont}{\glsfirstabbrvscfont}%
}%
}%
```

postfootnote-sc Backward compatibility:

```
\@glsxtr@deprecated@abbrstyle{postfootnote-sc}{short-sc-postfootnote}
```

`short-sc-postfootnote-desc` Like `short-sc-footnote` but with user supplied description.

```
\newabbreviationstyle{short-sc-postfootnote-desc}{%
{%
```

Set accessibility attributes if enabled.

```
\glxtrAccSuppAbbrSetNameLongAttrs\glscategorylabel
```

Setup the default fields.

```
\renewcommand*{\CustomAbbreviationFields}{%
name={\glxtrfootnotedesname},
sort={\glxtrfootnotedesort},
first={\glsfirstxpabrvfont{\the\glsshorttok}{\glscategorylabel}},%
firstplural={\glsfirstxpabrvfont{\the\glsshortpltok}{\glscategorylabel}},%
text={\glxpabrvfont{\the\glsshorttok}{\glscategorylabel}},%
plural={\glxpabrvfont{\the\glsshortpltok}{\glscategorylabel}}}%
```

Make this category insert a footnote after the link if this was the first use, and unset the `regular` attribute if it has been set. The footnote needs to be suppressed in the inline form. Previously this was done by redefining `glxtrsetupfuldefs` but that interferes with other styles. Instead, this now uses `\glxtrifwasglsl`

```
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\csdef{glxtrpostlink\glscategorylabel}{%
\glxtrifwasglslandfirstuse
{%
\glxtrdopostpunc{\xpglxtrpostabrvfootnote}%
}%
}%
\glshasattribute{\the\glslabeltok}{regular}%
{%
\glissetattribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%
}%
\GlsXtrUseAbbrStyleFmts{short-sc-postfootnote}%
}
```

2.3 Predefined Styles (Fake Small Capitals)

These styles require the `relsize` package, which must be loaded by the user. These styles all use:

```
\glxtrsmfont Maintained for backward compatibility.
\newcommand*{\glxtrsmfont}[1]{\textsmaller{#1}}
```

```
\glsabrvsmfont Added for consistent naming.
\newcommand*{\glsabrvsmfont}{\glxtrsmfont}
```


`\glxtrfirstsmfont` Maintained for backward compatibility.

```
\newcommand*\glxtrfirstsmfont[1]{\glsabbrvsmfont{#1}}
```

`\glsfirstabbrvsmfont` Added for consistent naming.

```
\newcommand*\glsfirstabbrvsmfont{\glxtrfirstsmfont}
```

and for the default short form suffix:

```
\glxtrsmsuffix
\newcommand*\glxtrsmsuffix{\glxtrabbrvpluralsuffix}
```

`\glxtrsmrevert`

```
\newcommand*\glxtrsmrevert[1]{\textlarger{#1}}
```

`long-short-sm`

```
\newabbreviationstyle{long-short-sm}%
{%
```

Set accessibility attributes if enabled.

```
\glxtrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
```

Setup the default fields.

```
\renewcommand*\CustomAbbreviationFields{%
  name={\glxtrlongshortname},
  sort={\the\glsshorttok},
  first={\glsfirstxplongfont{\the\glslongtok}{\glscategorylabel}%
    \protect\glxtrfullsep{\the\glslabeltok}%
    \protect\glxtrparen{\glsfirstxpabbrvfont{\the\glsshorttok}{\glscategorylabel}}},%
  firstplural={\glsfirstxplongfont{\the\glslongpltok}{\glscategorylabel}%
    \protect\glxtrfullsep{\the\glslabeltok}%
    \protect\glxtrparen{\glsfirstxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}}},%
  text={\glxpabbrvfont{\the\glsshorttok}{\glscategorylabel}},%
  plural={\glxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}},%
  description={\the\glslongtok}}%
\renewcommand*\GlsXtrPostNewAbbreviation{%
  \glxtrsetcomplexstyle{\the\glslabeltok}{3}%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glissetattribute{\the\glslabeltok}{regular}{false}%
  }%
  {}%
}%
}%
{%
```

```
\renewcommand*\glsabbrvfont[1]{\glsabbrvsmfont{##1}}%
\renewcommand*\glsfirstabbrvfont[1]{\glsfirstabbrvsmfont{##1}}%
\renewcommand*\abbrvpluralsuffix{\glxtrsmsuffix}%
\renewcommand*\glxtrrevert[1]{\glxtrsmrevert{##1}}%
```

Use the default long fonts.

```
\renewcommand*\glsfirstlongfont}[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*\glslongfont}[1]{\glslongdefaultfont{##1}}%
```

The first use full form and the inline full form are the same for this style.

```
\renewcommand*\glsxtrfullformat}[2]{%
  \glsxtrlongshortformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}}%
}%
\renewcommand*\glsxtrfullplformat}[2]{%
  \glsxtrlongshortplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}}%
}%
\renewcommand*\Glsxtrfullformat}[2]{%
  \Glsxtrlongshortformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}}%
}%
\renewcommand*\Glsxtrfullplformat}[2]{%
  \Glsxtrlongshortplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}}%
}%
\renewcommand*\GLSxtrfullformat}[2]{%
  \GLSxtrlongshortformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}}%
}%
\renewcommand*\GLSxtrfullplformat}[2]{%
  \GLSxtrlongshortplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}}%
}%
}
```

long-short-sm-desc

```
\newabbreviationstyle{long-short-sm-desc}%
{%
```

Set accessibility attributes if enabled.

```
\glsxtrAccSuppAbbrSetTextShortAttrs\glscategorylabel
```

Setup the default fields.

```
\renewcommand*\CustomAbbreviationFields{%
  name={\glsxtrlongshortdescname},
  sort={\glsxtrlongshortdescsort},%
  first={\glsfirstxplongfont{\the\glslongtok}{\glscategorylabel}%
    \protect\glsxtrfullsep{\the\glslabeltok}%
    \protect\glsxtrparen{\glsfirstxppabrvfont{\the\glsshorttok}{\glscategorylabel}}},%
  firstplural={\glsfirstxplongfont{\the\glslongpltok}{\glscategorylabel}%
    \protect\glsxtrfullsep{\the\glslabeltok}%
    \protect\glsxtrparen{\glsfirstxppabrvfont{\the\glsshortpltok}{\glscategorylabel}}},%
  text={\glsxpabrvfont{\the\glsshorttok}{\glscategorylabel}},%
  plural={\glsxpabrvfont{\the\glsshortpltok}{\glscategorylabel}}%
}%
```

Unset the `regular` attribute if it has been set.

```
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glxtrsetcomplexstyle{\the\glslabeltok}{3}%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glsssetattribute{\the\glslabeltok}{regular}{false}%
  }%
}%
{%
```

As long-short-sm style:

```
\GlsXtrUseAbbrStyleFmts{long-short-sm}%
}
```

`short-sm-long` Now the short (long) version

```
\newabbreviationstyle{short-sm-long}%
{%
```

Set accessibility attributes if enabled.

```
\glxtrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
```

Setup the default fields.

```
\renewcommand*{\CustomAbbreviationFields}{%
  name={\glxtrshortlongname},
  sort={\the\glssshorttok},
  description={\the\glslongtok},%
  first={\glsfirstxpabrvfont{\the\glssshorttok}{\glscategorylabel}%
    \protect\glxtrfullsep{\the\glslabeltok}%
    \protect\glxtrparen{\glsfirstxplongfont{\the\glslongtok}{\glscategorylabel}}},%
  firstplural={\glsfirstxpabrvfont{\the\glssshortpltok}{\glscategorylabel}%
    \protect\glxtrfullsep{\the\glslabeltok}%
    \protect\glxtrparen{\glsfirstxplongfont{\the\glslongpltok}{\glscategorylabel}}},%
  text={\glxpabrvfont{\the\glssshorttok}{\glscategorylabel}},%
  plural={\glxpabrvfont{\the\glssshortpltok}{\glscategorylabel}}}%
}
```

Unset the `regular` attribute if it has been set.

```
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glxtrsetcomplexstyle{\the\glslabeltok}{3}%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glsssetattribute{\the\glslabeltok}{regular}{false}%
  }%
}%
{%

\renewcommand*\glsabrvfont[1]{\glsabrvsmfont{##1}}%
\renewcommand*\glsfirstabrvfont[1]{\glsfirstabrvsmfont{##1}}%
```

```

\renewcommand*{\abbrvpluralsuffix}{\glxtrsmsuffix}%
\renewcommand*{\glxtrrevert}[1]{\glxtrsmrevert{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%

```

The first use full form and the inline full form are the same for this style.

```

\renewcommand*{\glxtrfullformat}[2]{%
  \glxtrshortlongformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\glxtrfullplformat}[2]{%
  \glxtrshortlongplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \Glsxtrshortlongformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \Glsxtrshortlongplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\GLSxtrfullformat}[2]{%
  \GLSxtrshortlongformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
  \GLSxtrshortlongplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%
}

```

short-sm-long-desc As before but user provides description

```

\newabbreviationstyle{short-sm-long-desc}%
{%

```

Set accessibility attributes if enabled.

```

\glxtrAccSuppAbbrSetTextShortAttrs\glscategorylabel

```

Setup the default fields.

```

\renewcommand*{\CustomAbbreviationFields}{%
  name={\glxtrshortlongdescname},
  sort={\glxtrshortlongdescsort},
  first={\glsfirstxpabbrvfont{\the\glsshorttok}{\glscategorylabel}}%
  \protect\glxtrfullsep{\the\glslabeltok}%
  \protect\glxtrparen{\glsfirstxplongfont{\the\glslongtok}{\glscategorylabel}}},%
  firstplural={\glsfirstxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}}%
  \protect\glxtrfullsep{\the\glslabeltok}%
  \protect\glxtrparen{\glsfirstxplongfont{\the\glslongpltok}{\glscategorylabel}}},%
  text={\glxppabbrvfont{\the\glsshorttok}{\glscategorylabel}}%,
  plural={\glxppabbrvfont{\the\glsshortpltok}{\glscategorylabel}}%
}

```

}%

Unset the regular attribute if it has been set.

```
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glstrsetcomplexstyle{\the\glslabeltok}{3}%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glissetattribute{\the\glslabeltok}{regular}{false}%
  }%
  {%
  }%
}
```

As short-sm-long style:

```
\GlsXtrUseAbbrStyleFmts{short-sm-long}%
}
```

short-sm

```
\newabbreviationstyle{short-sm}%
{%
```

Set accessibility attributes if enabled.

```
\glstrAccSuppAbbrSetNameLongAttrs\glscategorylabel
```

Setup the default fields.

```
\renewcommand*{\CustomAbbreviationFields}{%
  name={\glstrshortnolongname},
  sort={\the\glsshorttok},
  first={\glsfirstxpabrvfont{\the\glsshorttok}{\glscategorylabel}},
  firstplural={\glsfirstxpabrvfont{\the\glsshortpltok}{\glscategorylabel}},
  text={\glsexpabrvfont{\the\glsshorttok}{\glscategorylabel}},
  plural={\glsexpabrvfont{\the\glsshortpltok}{\glscategorylabel}},
  description={\the\glslongtok}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glissetattribute{\the\glslabeltok}{regular}{true}}%
}%
{%
```

```
\renewcommand*\glsabrvfont[1]{\glsabrvsmfont{##1}}%
\renewcommand*\glsfirstabrvfont[1]{\glsfirstabrvsmfont{##1}}%
\renewcommand*\abrvpluralsuffix{\glstrsmsuffix}%
\renewcommand*\glstrrevert[1]{\glstrsmrevert{##1}}%
\renewcommand*\glsfirstlongfont[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*\glslongfont[1]{\glslongdefaultfont{##1}}%
```

The inline full form displays the short form followed by the long form in parentheses.

```
\renewcommand*\glstrinlinefullformat[2]{%
  \glstrshortlongformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabrvsmfont}%
}%
```

```

\renewcommand*{\glxstrinlinefullplformat}[2]{%
  \glxstrshortlongplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%

\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \Glsxtrshortlongformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%

\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \Glsxtrshortlongplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%

\renewcommand*{\GLSxtrinlinefullformat}[2]{%
  \GLSxtrshortlongformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%

\renewcommand*{\GLSxtrinlinefullplformat}[2]{%
  \GLSxtrshortlongplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%

```

The first use full form only displays the short form, but it typically won't be used as the `regular` attribute is set by this style.

```

\renewcommand*{\glxstrfullformat}[2]{%
  \glxstrshortformat{##1}{##2}{\glsfirstabbrvsmfont}%
}%

\renewcommand*{\glxstrfullplformat}[2]{%
  \glxstrshortplformat{##1}{##2}{\glsfirstabbrvsmfont}%
}%

\renewcommand*{\Glsxtrfullformat}[2]{%
  \Glsxtrshortformat{##1}{##2}{\glsfirstabbrvsmfont}%
}%

\renewcommand*{\Glsxtrfullplformat}[2]{%
  \Glsxtrshortplformat{##1}{##2}{\glsfirstabbrvsmfont}%
}%

\renewcommand*{\GLSxtrfullformat}[2]{%
  \GLSxtrshortformat{##1}{##2}{\glsfirstabbrvsmfont}%
}%

\renewcommand*{\GLSxtrfullplformat}[2]{%
  \GLSxtrshortplformat{##1}{##2}{\glsfirstabbrvsmfont}%
}%
}

```

`short-sm-nolong`

```
\letabbreviationstyle{short-sm-nolong}{short-sm}
```

`short-sm-desc`

```

\newabbreviationstyle{short-sm-desc}%
{%

```

Set accessibility attributes if enabled.

```
\glstrAccSuppAbbrSetNoLongAttrs\glscategorylabel
```

Setup the default fields.

```
\renewcommand*{\CustomAbbreviationFields}{%
  name={\glstrshortdescname},
  sort={\the\glsshorttok},
  first={\glsfirstxpabbrvfont{\the\glsshorttok}{\glscategorylabel}},
  firstplural={\glsfirstxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}},
  text={\glsexpabbrvfont{\the\glsshorttok}{\glscategorylabel}},
  plural={\glsexpabbrvfont{\the\glsshortpltok}{\glscategorylabel}}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glsssetAttribute{\the\glslabeltok}{regular}{true}}%
}%
{%

\renewcommand*\glsabbrvfont[1]{\glsabbrvsmfont{##1}}%
\renewcommand*\glsfirstabbrvfont[1]{\glsfirstabbrvsmfont{##1}}%
\renewcommand*\{abbrvpluralsuffix}{\glstrsmsuffix}%
\renewcommand*\glstrrevert[1]{\glstrsmrevert{##1}}%
\renewcommand*\glsfirstlongfont[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*\glslongfont[1]{\glslongdefaultfont{##1}}%
```

The inline full form displays the short format followed by the long form in parentheses.

```
\renewcommand*{\glstrinlinefullformat}[2]{%
  \glstrshortlongformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\glstrinlinefullplformat}[2]{%
  \glstrshortlongplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \Glsxtrshortlongformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \Glsxtrshortlongplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\GLSxtrinlinefullformat}[2]{%
  \GLSxtrshortlongformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\GLSxtrinlinefullplformat}[2]{%
  \GLSxtrshortlongplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%
```

The first use full form only displays the short form, but it typically won't be used as the `regular` attribute is set by this style.

```
\renewcommand*{\glxstrfullformat}[2]{%
  \glxstrshortformat{##1}{##2}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\glxstrfullplformat}[2]{%
  \glxstrshortplformat{##1}{##2}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \Glsxtrshortformat{##1}{##2}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \Glsxtrshortplformat{##1}{##2}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\GLSxtrfullformat}[2]{%
  \GLSxtrshortformat{##1}{##2}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
  \GLSxtrshortplformat{##1}{##2}{\glsfirstabbrvsmfont}%
}%
}
```

`short-sm-nolong-desc`

```
\letabbreviationstyle{short-sm-nolong-desc}{short-sm-desc}
```

`nolong-short-sm`

```
\newabbreviationstyle{nolong-short-sm}%
{%
  \GlsXtrUseAbbrStyleSetup{short-sm-nolong}%
}%
{%
  \GlsXtrUseAbbrStyleFmts{short-sm-nolong}%
}
```

The inline full form displays the long form followed by the short form in parentheses.

```
\renewcommand*{\glxstrinlinefullformat}[2]{%
  \glxstrlongshortformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\glxstrinlinefullplformat}[2]{%
  \glxstrlongshortplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \Glsxtrlongshortformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \Glsxtrlongshortplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}
```



```

}%
\renewcommand*{\GLSxtrinlinefullformat}[2]{%
  \GLSxtrlongshortformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\GLSxtrinlinefullplformat}[2]{%
  \GLSxtrlongshortplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%
}

```

`long-noshort-sm` The smallcaps font will only be used if the short form is explicitly invoked through commands like `\glsxtrshort`.

```

\newabbreviationstyle{long-noshort-sm}%
{%

```

Set accessibility attributes if enabled.

```

\glsxtrAccSuppAbbrSetNameShortAttrs\glscategorylabel

```

Setup the default fields.

```

\renewcommand*{\CustomAbbreviationFields}{%
  name={\glsxtrlongnoshortname},
  sort={\the\glsshorttok},
  first={\glsfirstxplongfont{\the\glslongtok}{\glscategorylabel}},
  firstplural={\glsfirstxplongfont{\the\glslongpltok}{\glscategorylabel}},
  text={\glsxplongfont{\the\glslongtok}{\glscategorylabel}},
  plural={\glsxplongfont{\the\glslongpltok}{\glscategorylabel}},%
  description={\the\glslongtok}%
}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glssetattribute{\the\glslabeltok}{regular}{true}}%
}%
{%

```

```

\renewcommand*\glsabbrvfont[1]{\glsabbrvsmfont{##1}}%
\renewcommand*\glsfirstabbrvfont[1]{\glsfirstabbrvsmfont{##1}}%
\renewcommand*\abbrvpluralsuffix{\glsxtrsmsuffix}%
\renewcommand*\glsxtrrevert[1]{\glsxtrsmrevert{##1}}%
\renewcommand*\glsfirstlongfont[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*\glslongfont[1]{\glslongdefaultfont{##1}}%

```

The format for subsequent use (not used when the regular attribute is set).

```

\renewcommand*{\glsxtrsubsequentfmt}[2]{%
  \glsxtrlongformat{##1}{##2}{\glslongdefaultfont}%
}%
\renewcommand*{\glsxtrsubsequentplfmt}[2]{%
  \glsxtrlongplformat{##1}{##2}{\glslongdefaultfont}%
}%
\renewcommand*{\Glsxtrsubsequentfmt}[2]{%
  \Glsxtrlongformat{##1}{##2}{\glslongdefaultfont}%
}%

```

```

\renewcommand*{\Glsxtrsubsequentplfmt}[2]{%
  \Glsxtrlongplformat{##1}{##2}{\glslongdefaultfont}%
}%
\renewcommand*{\Glsxtrsubsequentfmt}[2]{%
  \Glsxtrlongformat{##1}{##2}{\glslongdefaultfont}%
}%
\renewcommand*{\Glsxtrsubsequentplfmt}[2]{%
  \Glsxtrlongplformat{##1}{##2}{\glslongdefaultfont}%
}%

```

The inline full form displays the long format followed by the short form in parentheses.

```

\renewcommand*{\glsxtrinlinefullformat}[2]{%
  \glsxtrlongshortformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\glsxtrinlinefullplformat}[2]{%
  \glsxtrlongshortplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \Glsxtrlongshortformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \Glsxtrlongshortplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \Glsxtrlongshortformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \Glsxtrlongshortplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%

```

The first use full form only displays the long form, but it typically won't be used as the `regular` attribute is set by this style.

```

\renewcommand*{\glsxtrfullformat}[2]{%
  \glsxtrlongformat{##1}{##2}{\glsfirstlongdefaultfont}%
}%
\renewcommand*{\glsxtrfullplformat}[2]{%
  \glsxtrlongplformat{##1}{##2}{\glsfirstlongdefaultfont}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \Glsxtrlongformat{##1}{##2}{\glsfirstlongdefaultfont}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \Glsxtrlongplformat{##1}{##2}{\glsfirstlongdefaultfont}%
}%

```

```

}%
\renewcommand*\GLSxtrfullformat}[2]{%
  \GLSxtrlongformat{##1}{##2}{\glsfirstlongdefaultfont}%
}%
\renewcommand*\GLSxtrfullplformat}[2]{%
  \GLSxtrlongplformat{##1}{##2}{\glsfirstlongdefaultfont}%
}%
}

```

`long-sm` Backward compatibility:

```
\@glxtr@deprecated@abbrstyle{long-sm}{long-noshort-sm}
```

`long-noshort-sm-desc` The smaller font will only be used if the short form is explicitly invoked through commands like `\glsxtrshort`.

```

\newabbreviationstyle{long-noshort-sm-desc}%
{%
  \GlsXtrUseAbbrStyleSetup{long-noshort-desc}%
}%
{%

\renewcommand*\glsabbrvfont[1]{\glsabbrvsmfont{##1}}%
\renewcommand*\glsfirstabbrvfont[1]{\glsfirstabbrvsmfont{##1}}%
\renewcommand*\abbrvpluralsuffix{\glsxtrsmsuffix}%
\renewcommand*\glsxtrrevert[1]{\glsxtrsmrevert{##1}}%
\renewcommand*\glsfirstlongfont[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*\glslongfont[1]{\glslongdefaultfont{##1}}%

```

The format for subsequent use (not used when the regular attribute is set).

```

\renewcommand*\glsxtrsubsequentfmt}[2]{%
  \glsxtrlongformat{##1}{##2}{\glslongdefaultfont}%
}%
\renewcommand*\glsxtrsubsequentplfmt}[2]{%
  \glsxtrlongplformat{##1}{##2}{\glslongdefaultfont}%
}%
\renewcommand*\Glsxtrsubsequentfmt}[2]{%
  \Glsxtrlongformat{##1}{##2}{\glslongdefaultfont}%
}%
\renewcommand*\Glsxtrsubsequentplfmt}[2]{%
  \Glsxtrlongplformat{##1}{##2}{\glslongdefaultfont}%
}%
\renewcommand*\GLSxtrsubsequentfmt}[2]{%
  \GLSxtrlongformat{##1}{##2}{\glslongdefaultfont}%
}%
\renewcommand*\GLSxtrsubsequentplfmt}[2]{%
  \GLSxtrlongplformat{##1}{##2}{\glslongdefaultfont}%
}%

```

The inline full form displays the long format followed by the short form in parentheses.

```
\renewcommand*\glsxtrinlinefullformat}[2]{%
```

```

\glstrlongshortformat{##1}{##2}%
{\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\glstrinlinefullplformat}[2]{%
\glstrlongshortplformat{##1}{##2}%
{\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
\Glsxtrlongshortformat{##1}{##2}%
{\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
\Glsxtrlongshortplformat{##1}{##2}%
{\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\GLSxtrinlinefullformat}[2]{%
\GLSxtrlongshortformat{##1}{##2}%
{\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\GLSxtrinlinefullplformat}[2]{%
\GLSxtrlongshortplformat{##1}{##2}%
{\glsfirstlongdefaultfont}{\glsfirstabbrvsmfont}%
}%
}

```

The first use full form only displays the long form, but it typically won't be used as the `regular` attribute is set by this style.

```

\renewcommand*{\glstrfullformat}[2]{%
\glstrlongformat{##1}{##2}{\glsfirstlongdefaultfont}%
}%
\renewcommand*{\glstrfullplformat}[2]{%
\glstrlongplformat{##1}{##2}{\glsfirstlongdefaultfont}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
\Glsxtrlongformat{##1}{##2}{\glsfirstlongdefaultfont}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
\Glsxtrlongplformat{##1}{##2}{\glsfirstlongdefaultfont}%
}%
\renewcommand*{\GLSxtrfullformat}[2]{%
\GLSxtrlongformat{##1}{##2}{\glsfirstlongdefaultfont}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
\GLSxtrlongplformat{##1}{##2}{\glsfirstlongdefaultfont}%
}%
}

```

`long-desc-sm` Backward compatibility:

```
\@glstr@deprecated@abbrstyle{long-desc-sm}{long-noshort-sm-desc}
```

`short-sm-footnote`

```
\newabbreviationstyle{short-sm-footnote}%
{%
```

Set accessibility attributes if enabled.

```
\glstrAccSuppAbbrSetNoLongAttrs\glscategorylabel
```

Setup the default fields.

```
\renewcommand*{\CustomAbbreviationFields}{%
  name={\glstrfootnotename},
  sort={\the\glsshorttok},
  description={\the\glslongtok},%
  first={\glstrfirstxabbrvfont{\the\glsshorttok}{\glscategorylabel}%
    \protect\glstrabbrvfootnote{\the\glslabeltok}%
    {\protect\glstrfirstlongfootnotefont{\the\glslongtok}}},%
  firstplural={\glstrfirstxabbrvfont{\the\glsshortpltok}{\glscategorylabel}%
    \protect\glstrabbrvfootnote{\the\glslabeltok}%
    {\protect\glstrfirstlongfootnotefont{\the\glslongpltok}}},%
  text={\glstrxabbrvfont{\the\glsshorttok}{\glscategorylabel}},%
  plural={\glstrxabbrvfont{\the\glsshortpltok}{\glscategorylabel}}}%
```

Switch off hyperlinks on first use to prevent nested hyperlinks, and unset the regular attribute if it has been set.

```
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glsssetAttribute{\the\glslabeltok}{nohyperfirst}{true}%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glsssetAttribute{\the\glslabeltok}{regular}{false}%
  }%
  {}%
}%
}%
{%
```

```
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvsmfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvsmfont{##1}}%
\renewcommand*{\abbrvpluralsuffix}{\glstrsmsuffix}%
\renewcommand*{\glstrrevert}[1]{\glstrsmrevert{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongfootnotefont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongfootnotefont{##1}}%
```

The full format displays the short form followed by the long form as a footnote.

```
\renewcommand*{\glstrfullformat}[2]{%
  \glstrshortformat{##1}{##2}{\glsfirstabbrvsmfont}%
  \protect\glstrabbrvfootnote{##1}%
  {\glstrfootnotelongformat{##1}{\glsfirstlongfootnotefont}}%
}%
\renewcommand*{\glstrfullplformat}[2]{%
  \glstrshortplformat{##1}{##2}{\glsfirstabbrvsmfont}%
  \protect\glstrabbrvfootnote{##1}%
  {\glstrfootnotelongplformat{##1}{\glsfirstlongfootnotefont}}%
}%
```

```

\renewcommand*{\Glsxtrfullformat}[2]{%
  \Glsxtrshortformat{##1}{##2}{\glsfirstabbrvsmfont}%
  \protect\glsxtrabbrvfootnote{##1}%
  {\glsxtrfootnotelongformat{##1}{\glsfirstlongfootnotefont}}}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \Glsxtrshortplformat{##1}{##2}{\glsfirstabbrvsmfont}%
  \protect\glsxtrabbrvfootnote{##1}%
  {\glsxtrfootnotelongplformat{##1}{\glsfirstlongfootnotefont}}}%
}%
\renewcommand*{\GLSxtrfullformat}[2]{%
  \GLSxtrshortformat{##1}{##2}{\glsfirstabbrvsmfont}%
  \protect\glsxtrabbrvfootnote{##1}%
  {\glsxtrfootnotelongformat{##1}{\glsfirstlongfootnotefont}}}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
  \GLSxtrshortplformat{##1}{##2}{\glsfirstabbrvsmfont}%
  \protect\glsxtrabbrvfootnote{##1}%
  {\glsxtrfootnotelongplformat{##1}{\glsfirstlongfootnotefont}}}%
}%

```

The first use full form and the inline full form use the short (long) style.

```

\renewcommand*{\glsxtrinlinefullformat}[2]{%
  \glsxtrshortlongformat{##1}{##2}%
  {\glsfirstlongfootnotefont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\glsxtrinlinefullplformat}[2]{%
  \glsxtrshortlongplformat{##1}{##2}%
  {\glsfirstlongfootnotefont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \Glsxtrshortlongformat{##1}{##2}%
  {\glsfirstlongfootnotefont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \Glsxtrshortlongplformat{##1}{##2}%
  {\glsfirstlongfootnotefont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\GLSxtrinlinefullformat}[2]{%
  \GLSxtrshortlongformat{##1}{##2}%
  {\glsfirstlongfootnotefont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\GLSxtrinlinefullplformat}[2]{%
  \GLSxtrshortlongplformat{##1}{##2}%
  {\glsfirstlongfootnotefont}{\glsfirstabbrvsmfont}%
}%
}

```

footnote-sm Backward compatibility:

```

\@glsxtr@deprecated@abbrstyle{footnote-sm}{short-sm-footnote}

```

short-sm-footnote-desc Like short-footnote but with user supplied description.

```
\newabbreviationstyle{short-sm-footnote-desc}{%  
{%
```

Set accessibility attributes if enabled.

```
\glstrAccSuppAbbrSetNameLongAttrs\glscategorylabel
```

Setup the default fields.

```
\renewcommand*{\CustomAbbreviationFields}{%  
  name={\glstrfootnotedesname},  
  sort={\glstrfootnotedesort},  
  first={\glstrfirstpabrvfont{\the\glsshorttok}{\glscategorylabel}}%  
  \protect\glstrabrvfootnote{\the\glslabeltok}%  
    {\protect\glstrfirstlongfootnote{\the\glslongtok}}},%  
  firstplural={\glstrfirstpabrvfont{\the\glsshortpltok}{\glscategorylabel}}%  
  \protect\glstrabrvfootnote{\the\glslabeltok}%  
    {\protect\glstrfirstlongfootnote{\the\glslongpltok}}},%  
  text={\glstrpabrvfont{\the\glsshorttok}{\glscategorylabel}}},%  
  plural={\glstrpabrvfont{\the\glsshortpltok}{\glscategorylabel}}}%
```

Switch off hyperlinks on first use to prevent nested hyperlinks, and unset the regular attribute if it has been set.

```
\renewcommand*{\GlsXtrPostNewAbbreviation}{%  
  \glsssetAttribute{\the\glslabeltok}{nohyperfirst}{true}%  
  \glshasattribute{\the\glslabeltok}{regular}%  
  {%  
    \glsssetAttribute{\the\glslabeltok}{regular}{false}%  
  }%  
  {%  
  }%  
  {%  
    \GlsXtrUseAbbrStyleFmts{short-sm-footnote}%  
  }
```

short-sm-postfootnote

```
\newabbreviationstyle{short-sm-postfootnote}{%  
{%
```

Set accessibility attributes if enabled.

```
\glstrAccSuppAbbrSetNoLongAttrs\glscategorylabel
```

Setup the default fields.

```
\renewcommand*{\CustomAbbreviationFields}{%  
  name={\glstrfootnotename},  
  sort={\the\glsshorttok},  
  description={\the\glslongtok},%  
  first={\glstrfirstpabrvfont{\the\glsshorttok}{\glscategorylabel}}},%  
  firstplural={\glstrfirstpabrvfont{\the\glsshortpltok}{\glscategorylabel}}},%  
  text={\glstrpabrvfont{\the\glsshorttok}{\glscategorylabel}}},%  
  plural={\glstrpabrvfont{\the\glsshortpltok}{\glscategorylabel}}}%
```

Make this category insert a footnote after the link if this was the first use, and unset the `regular` attribute if it has been set. The footnote needs to be suppressed in the inline form. Previously this was done by redefining `glxtrsetupfulldefs` but that interferes with other styles. Instead, this now uses `\glxtrifwasglslike`

```
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\csdef{glxtrpostlink\glscategorylabel}{%
\glxtrifwasglslikeandfirstuse
{%
\glxtrdopostpunc{\xpglxtrpostabbrvfootnote}%
}%
}%
\glshasattribute{\the\glslabelltok}{regular}%
{%
\glissetattribute{\the\glslabelltok}{regular}{false}%
}%
}%
}%
{%

\renewcommand*{\glxtrshortformat}[1]{\glxtrshortformat{##1}}%
\renewcommand*{\glxtrfullformat}[1]{\glxtrfullformat{##1}}%
\renewcommand*{\glxtrshortformat}[1]{\glxtrshortformat{##1}}%
\renewcommand*{\glxtrfullformat}[1]{\glxtrfullformat{##1}}%
\renewcommand*{\glxtrshortformat}[1]{\glxtrshortformat{##1}}%
\renewcommand*{\glxtrfullformat}[1]{\glxtrfullformat{##1}}%
\renewcommand*{\glxtrshortformat}[1]{\glxtrshortformat{##1}}%
\renewcommand*{\glxtrfullformat}[1]{\glxtrfullformat{##1}}%
```

The full format displays the short form. The long form is deferred.

```
\renewcommand*{\glxtrshortformat}[1]{\glxtrshortformat{##1}}%
\renewcommand*{\glxtrfullformat}[1]{\glxtrfullformat{##1}}%
\renewcommand*{\glxtrshortformat}[1]{\glxtrshortformat{##1}}%
\renewcommand*{\glxtrfullformat}[1]{\glxtrfullformat{##1}}%
\renewcommand*{\glxtrshortformat}[1]{\glxtrshortformat{##1}}%
\renewcommand*{\glxtrfullformat}[1]{\glxtrfullformat{##1}}%
\renewcommand*{\glxtrshortformat}[1]{\glxtrshortformat{##1}}%
\renewcommand*{\glxtrfullformat}[1]{\glxtrfullformat{##1}}%
\renewcommand*{\glxtrshortformat}[1]{\glxtrshortformat{##1}}%
\renewcommand*{\glxtrfullformat}[1]{\glxtrfullformat{##1}}%
\renewcommand*{\glxtrshortformat}[1]{\glxtrshortformat{##1}}%
\renewcommand*{\glxtrfullformat}[1]{\glxtrfullformat{##1}}%
```

The first use full form and the inline full form use the short (long) style.

```
\renewcommand*{\glxtrshortformat}[1]{\glxtrshortformat{##1}}%
```



```

\glstrshortlongformat{##1}{##2}%
{\glsfirstlongfootnotefont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\glstrinlinefullplformat}[2]{%
\glstrshortlongplformat{##1}{##2}%
{\glsfirstlongfootnotefont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
\Glsxtrshortlongformat{##1}{##2}%
{\glsfirstlongfootnotefont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
\Glsxtrshortlongplformat{##1}{##2}%
{\glsfirstlongfootnotefont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\GLSxtrinlinefullformat}[2]{%
\GLSxtrshortlongformat{##1}{##2}%
{\glsfirstlongfootnotefont}{\glsfirstabbrvsmfont}%
}%
\renewcommand*{\GLSxtrinlinefullplformat}[2]{%
\GLSxtrshortlongplformat{##1}{##2}%
{\glsfirstlongfootnotefont}{\glsfirstabbrvsmfont}%
}%
}

```

postfootnote-sm Backward compatibility:

```
\@glstr@deprecated@abbrstyle{postfootnote-sm}{short-sm-postfootnote}
```

short-sm-postfootnote-desc Like short-sm-postfootnote but with user supplied description.

```
\newabbreviationstyle{short-sm-postfootnote-desc}%
%
```

Set accessibility attributes if enabled.

```
\glstrAccSuppAbbrSetNameLongAttrs\glscategorylabel
```

Setup the default fields.

```

\renewcommand*{\CustomAbbreviationFields}{%
name={\glstrfootnotedesname},
sort={\glstrfootnotedesort},
first={\glsfirstxpabbrvfont{\the\glsshorttok}{\glscategorylabel}},%
firstplural={\glsfirstxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}},%
text={\glsexpabbrvfont{\the\glsshorttok}{\glscategorylabel}},%
plural={\glsexpabbrvfont{\the\glsshortpltok}{\glscategorylabel}}}%

```

Make this category insert a footnote after the link if this was the first use, and unset the `regular` attribute if it has been set. The footnote needs to be suppressed in the inline form. Previously this was done by redefining `glstrsetupfulldefs` but that interferes with other styles. Instead, this now uses `\glstrifwasglslike`

```

\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\csdef{glstrpostlink\glscategorylabel}{%

```

```

\glstrifwasglslikeandfirstuse
{%
Ensure \glslabel is expanded as it may be lost by the time the footnote occurs.
\glstrdopostpunc{\xpglsxrpostabbrvfootnote}%
}%
{}%
}%
\glshasattribute{\the\glslabeltok}{regular}%
{%
\glissetattribute{\the\glslabeltok}{regular}{false}%
}%
{}%
}%
}%
{%
\GlsXtrUseAbbrStyleFmts{short-sm-postfootnote}%
}

```

2.4 Predefined Styles (Emphasized)

These styles use `\emph` for the short form.

```

\glsabbrvemfont
\newcommand*{\glsabbrvemfont}[1]{\emph{#1}}%

\glsfirstabbrvemfont
\newcommand*{\glsfirstabbrvemfont}[1]{\glsabbrvemfont{#1}}%

```

The default short form suffix:

```

\glxtremsuffix
\newcommand*{\glxtremsuffix}{\glstrabbrvpluralsuffix}

\glsfirstlongemfont Only used by the “long-em” styles.
\newcommand*{\glsfirstlongemfont}[1]{\glslongemfont{#1}}%

```

```

\glslongemfont Only used by the “long-em” styles.
\newcommand*{\glslongemfont}[1]{\emph{#1}}%

```

```

\glxtremrevert
\newcommand*{\glxtremrevert}[1]{\textup{#1}}%

```

`long-short-em` The long form is just set in the default long font.

```

\newabbreviationstyle{long-short-em}%
{%

```

Set accessibility attributes if enabled.

```

\glstrAccSuppAbbrSetFirstLongAttrs\glscategorylabel

```

Setup the default fields.

```
\renewcommand*{\CustomAbbreviationFields}{%
  name={\glxtrlongshortname},
  sort={\the\glsshorttok},
  first={\glsfirstrlongfont{\the\glslongtok}{\glscategorylabel}%
    \protect\glxtrfullsep{\the\glslabeltok}%
    \protect\glxtrparen{\glsfirstrpabrvfont{\the\glsshorttok}{\glscategorylabel}}},%
  firstplural={\glsfirstrlongfont{\the\glslongpltok}{\glscategorylabel}%
    \protect\glxtrfullsep{\the\glslabeltok}%
    \protect\glxtrparen{\glsfirstrpabrvfont{\the\glsshortpltok}{\glscategorylabel}}},%
  text={\glxrpabrvfont{\the\glsshorttok}{\glscategorylabel}},%
  plural={\glxrpabrvfont{\the\glsshortpltok}{\glscategorylabel}},%
  description={\the\glslongtok}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glxtrsetcomplexstyle{\the\glslabeltok}{3}%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glsssetattribute{\the\glslabeltok}{regular}{false}%
  }%
  {%
  }%
}%
}%
{%
  \renewcommand*\glsabrvfont[1]{\glsabrvfont{##1}}%
  \renewcommand*\glsfirstrabrvfont[1]{\glsfirstrabrvfont{##1}}%
  \renewcommand*\abbrvpluralsuffix{\glxtremsuffix}%
  \renewcommand*\glxtrrevert[1]{\glxtremrevert{##1}}%
```

Use the default long fonts.

```
\renewcommand*{\glsfirstrlongfont}[1]{\glsfirstrlongdefaultfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%
```

The first use full form and the inline full form are the same for this style.

```
\renewcommand*{\glxtrfullformat}[2]{%
  \glxtrlongshortformat{##1}{##2}%
  {\glsfirstrlongdefaultfont}{\glsfirstrabrvfont}%
}%
\renewcommand*{\glxtrfullplformat}[2]{%
  \glxtrlongshortplformat{##1}{##2}%
  {\glsfirstrlongdefaultfont}{\glsfirstrabrvfont}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \Glsxtrlongshortformat{##1}{##2}%
  {\glsfirstrlongdefaultfont}{\glsfirstrabrvfont}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \Glsxtrlongshortplformat{##1}{##2}%
  {\glsfirstrlongdefaultfont}{\glsfirstrabrvfont}%
}%
```

```

\renewcommand*{\GLSxtrfullformat}[2]{%
  \GLSxtrlongshortformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
  \GLSxtrlongshortplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}%
}%
}

```

long-short-em-desc

```

\newabbreviationstyle{long-short-em-desc}%
{%

```

Set accessibility attributes if enabled.

```

\glsxtrAccSuppAbbrSetTextShortAttrs\glscategorylabel

```

Setup the default fields.

```

\renewcommand*{\CustomAbbreviationFields}{%
  name={\glsxtrlongshortdescname},
  sort={\glsxtrlongshortdescsort},%
  first={\glsfirstxplongfont{\the\glslongtok}{\glscategorylabel}%
    \protect\glsxtrfullsep{\the\glslabeltok}%
    \protect\glsxtrparen{\glsfirstxpabbrvfont{\the\glsshorttok}{\glscategorylabel}}},%
  firstplural={\glsfirstxplongfont{\the\glslongpltok}{\glscategorylabel}%
    \protect\glsxtrfullsep{\the\glslabeltok}%
    \protect\glsxtrparen{\glsfirstxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}}},%
  text={\glsxpabbrvfont{\the\glsshorttok}{\glscategorylabel}},%
  plural={\glsxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}}%
}%

```

Unset the regular attribute if it has been set.

```

\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glsxtrsetcomplexstyle{\the\glslabeltok}{3}%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glssetattribute{\the\glslabeltok}{regular}{false}%
  }%
  {}%
}%
{%

```

As long-short-em style:

```

\GlsXtrUseAbbrStyleFmts{long-short-em}%
}

```

long-em-short-em

```

\newabbreviationstyle{long-em-short-em}%
{%

```

Set accessibility attributes if enabled.

```
\glstrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
```

Setup the default fields. `\glslongemfont` is used in the description since `\glsdesc` doesn't set the style.

```
\renewcommand*{\CustomAbbreviationFields}{%
  name={\glstrlongshortname},
  sort={\the\glsshorttok},
  first={\glstrfirstxplongfont{\the\glslongtok}{\glscategorylabel}%
    \protect\glstrfullsep{\the\glslabeltok}%
    \protect\glstrparen{\glstrfirstxpabrvfont{\the\glsshorttok}{\glscategorylabel}}},%
  firstplural={\glstrfirstxplongfont{\the\glslongpltok}{\glscategorylabel}%
    \protect\glstrfullsep{\the\glslabeltok}%
    \protect\glstrparen{\glstrfirstxpabrvfont{\the\glsshortpltok}{\glscategorylabel}}},%

  text={\glxpabrvfont{\the\glsshorttok}{\glscategorylabel}},%
  plural={\glxpabrvfont{\the\glsshortpltok}{\glscategorylabel}},%
  description={\protect\glslongemfont{\the\glslongtok}}}%
```

Unset the regular attribute if it has been set.

```
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glsexclapplyinnerfmtfield{\the\glslabeltok}{desc}%
  \glstrsetcomplexstyle{\the\glslabeltok}{3}%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glsetattribute{\the\glslabeltok}{regular}{false}%
  }%
  {}%
}%
{}%
{}%

\renewcommand*{\abrvpluralsuffix}{\glxtremsuffix}%
\renewcommand*{\glstrrevert}[1]{\glxtremrevert{##1}}%
\renewcommand*{\glsabrvfont}[1]{\glsabrvemfont{##1}}%
\renewcommand*{\glstrfirstabrvfont}[1]{\glstrfirstabrvemfont{##1}}%
\renewcommand*{\glstrfirstlongfont}[1]{\glstrfirstlongemfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongemfont{##1}}%
```

The first use full form and the inline full form are the same for this style.

```
\renewcommand*{\glstrfullformat}[2]{%
  \glstrlongshortformat{##1}{##2}%
  {\glstrfirstlongemfont}{\glstrfirstabrvemfont}%
}%
\renewcommand*{\glstrfullplformat}[2]{%
  \glstrlongshortplformat{##1}{##2}%
  {\glstrfirstlongemfont}{\glstrfirstabrvemfont}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \Glsxtrlongshortformat{##1}{##2}%
  {\glstrfirstlongemfont}{\glstrfirstabrvemfont}%
}%
```

```

}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \Glsxtrlongshortplformat{##1}{##2}%
  {\glsfirstlongemfont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \Glsxtrlongshortformat{##1}{##2}%
  {\glsfirstlongemfont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \Glsxtrlongshortplformat{##1}{##2}%
  {\glsfirstlongemfont}{\glsfirstabbrvemfont}%
}%
}

```

long-em-short-em-desc

```

\newabbreviationstyle{long-em-short-em-desc}%
{%

```

Set accessibility attributes if enabled.

```
\glsxtrAccSuppAbbrSetTextShortAttrs\glscategorylabel
```

Setup the default fields.

```

\renewcommand*{\CustomAbbreviationFields}{%
  name={\glsxtrlongshortdescname},
  sort={\glsxtrlongshortdescsort},%
  first={\glsfirstxplongfont{\the\glslongtok}{\glscategorylabel}%
    \protect\glsxtrfullsep{\the\glslabeltok}%
    \protect\glsxtrparen{\glsfirstxpabrvfont{\the\glsshorttok}{\glscategorylabel}}},%
  firstplural={\glsfirstxplongfont{\the\glslongpltok}{\glscategorylabel}%
    \protect\glsxtrfullsep{\the\glslabeltok}%
    \protect\glsxtrparen{\glsfirstxpabrvfont{\the\glsshortpltok}{\glscategorylabel}}},%
  text={\glsxpabrvfont{\the\glsshorttok}{\glscategorylabel}},%
  plural={\glsxpabrvfont{\the\glsshortpltok}{\glscategorylabel}}%
}%

```

Unset the regular attribute if it has been set.

```

\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glsxtrsetcomplexstyle{\the\glslabeltok}{3}%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glssetattribute{\the\glslabeltok}{regular}{false}%
  }%
  {%
  }%
}%
\GlsXtrUseAbbrStyleFmts{long-em-short-em}%
}

```

short-em-long Now the short (long) version

```
\newabbreviationstyle{short-em-long}%
{%
```

Set accessibility attributes if enabled.

```
\glstrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
```

Setup the default fields.

```
\renewcommand*{\CustomAbbreviationFields}{%
  name={\glstrshortlongname},
  sort={\the\glsshorttok},
  description={\the\glslongtok},%
  first={\glsfirstxppabrvfont{\the\glsshorttok}{\glscategorylabel}}%
  \protect\glstrfullsep{\the\glslabeltok}%
  \protect\glstrparen{\glsfirstxplongfont{\the\glslongtok}{\glscategorylabel}}},%
  firstplural={\glsfirstxppabrvfont{\the\glsshortpltok}{\glscategorylabel}}%
  \protect\glstrfullsep{\the\glslabeltok}%
  \protect\glstrparen{\glsfirstxplongfont{\the\glslongpltok}{\glscategorylabel}}},%
  text={\glspabrvfont{\the\glsshorttok}{\glscategorylabel}}},%
  plural={\glspabrvfont{\the\glsshortpltok}{\glscategorylabel}}}%
```

Unset the regular attribute if it has been set.

```
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glstrsetcomplexstyle{\the\glslabeltok}{3}%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glissetattribute{\the\glslabeltok}{regular}{false}%
  }%
  {}%
}%
}%
{%
```

Mostly as short-long style:

```
\renewcommand*{\abbrvpluralsuffix}{\glxtremsuffix}%
\renewcommand*{\glstrrevert}[1]{\glxtremrevert{##1}}%
\renewcommand*{\glsabrvfont}[1]{\glsabrvemfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvemfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%
```

The first use full form and the inline full form are the same for this style.

```
\renewcommand*{\glstrfullformat}[2]{%
  \glstrshortlongformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}}%
}%
\renewcommand*{\glstrfullplformat}[2]{%
  \glstrshortlongplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \Glsxtrshortlongformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}}%
```

```

}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \Glsxtrshortlongplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\GLSxtrfullformat}[2]{%
  \GLSxtrshortlongformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
  \GLSxtrshortlongplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}%
}%
}

```

`short-em-long-desc` As before but user provides description

```

\newabbreviationstyle{short-em-long-desc}%
{%

```

Set accessibility attributes if enabled.

```

\glsxtrAccSuppAbbrSetTextShortAttrs\glscategorylabel

```

Setup the default fields.

```

\renewcommand*{\CustomAbbreviationFields}{%
  name={\glsxtrshortlongdescname},
  sort={\glsxtrshortlongdescsort},
  first={\glsfirstxpabrvfont{\the\glsshorttok}{\glscategorylabel}%
    \protect\glsxtrfullsep{\the\glslabeltok}%
    \protect\glsxtrparen{\glsfirstxplongfont{\the\glslongtok}{\glscategorylabel}}},%
  firstplural={\glsfirstxpabrvfont{\the\glsshortpltok}{\glscategorylabel}%
    \protect\glsxtrfullsep{\the\glslabeltok}%
    \protect\glsxtrparen{\glsfirstxplongfont{\the\glslongpltok}{\glscategorylabel}}},%
  text={\glsxpabrvfont{\the\glsshorttok}{\glscategorylabel}},%
  plural={\glsxpabrvfont{\the\glsshortpltok}{\glscategorylabel}}%
}%

```

Unset the regular attribute if it has been set.

```

\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glsxtrsetcomplexstyle{\the\glslabeltok}{3}%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glssetattribute{\the\glslabeltok}{regular}{false}%
  }%
  {}%
}%
{%
  \GlsXtrUseAbbrStyleFmts{short-em-long}%
}

```

`short-em-long-em`


```
\newabbreviationstyle{short-em-long-em}%
{%
```

Set accessibility attributes if enabled.

```
\glstrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
```

Setup the default fields. `\glslongemfont` is used in the description since `\glstdesc` doesn't set the style.

```
\renewcommand*{\CustomAbbreviationFields}{%
  name={\glstrshortlongname},
  sort={\the\glsshorttok},
  description={\protect\glslongemfont{\the\glslongtok}},%
  first={\glsfirstxpabrvfont{\the\glsshorttok}{\glscategorylabel}%
    \protect\glstrfullsep{\the\glslabeltok}%
    \protect\glstrparen{\glsfirstxplongfont{\the\glslongtok}{\glscategorylabel}}},%
  firstplural={\glsfirstxpabrvfont{\the\glsshortpltok}{\glscategorylabel}%
    \protect\glstrfullsep{\the\glslabeltok}%
    \protect\glstrparen{\glsfirstxplongfont{\the\glslongpltok}{\glscategorylabel}}},%

  text={\glsexpabrvfont{\the\glsshorttok}{\glscategorylabel}},%
  plural={\glsexpabrvfont{\the\glsshortpltok}{\glscategorylabel}}}%
```

Unset the regular attribute if it has been set.

```
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glsexclapplyinnerfmtfield{\the\glslabeltok}{desc}%
  \glstrsetcomplexstyle{\the\glslabeltok}{3}%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glissetattribute{\the\glslabeltok}{regular}{false}%
  }%
  {}%
}%
{%
```

```
\renewcommand*{\abbrvpluralsuffix}{\glxtremsuffix}%
\renewcommand*{\glstrrevert}[1]{\glxtremrevert{##1}}%
\renewcommand*{\glsabrvfont}[1]{\glsabrvemfont{##1}}%
\renewcommand*{\glsfirstabrvfont}[1]{\glsfirstabrvemfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongemfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongemfont{##1}}%
```

The first use full form and the inline full form are the same for this style.

```
\renewcommand*{\glstrfullformat}[2]{%
  \glstrshortlongformat{##1}{##2}%
  {\glsfirstlongemfont}{\glsfirstabrvemfont}%
}%
\renewcommand*{\glstrfullplformat}[2]{%
  \glstrshortlongplformat{##1}{##2}%
  {\glsfirstlongemfont}{\glsfirstabrvemfont}%
}%
```

```

\renewcommand*{\Glsxtrfullformat}[2]{%
  \Glsxtrshortlongformat{##1}{##2}%
  {\glsfirstlongemfont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \Glsxtrshortlongplformat{##1}{##2}%
  {\glsfirstlongemfont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\GLSxtrfullformat}[2]{%
  \GLSxtrshortlongformat{##1}{##2}%
  {\glsfirstlongemfont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
  \GLSxtrshortlongplformat{##1}{##2}%
  {\glsfirstlongemfont}{\glsfirstabbrvemfont}%
}%
}

```

short-em-long-em-desc

```

\newabbreviationstyle{short-em-long-em-desc}%
{%

```

Set accessibility attributes if enabled.

```
\glsxtrAccSuppAbbrSetTextShortAttrs\glscategorylabel
```

Setup the default fields.

```

\renewcommand*{\CustomAbbreviationFields}{%
  name={\glsxtrshortlongdescname},%
  sort={\glsxtrshortlongdescsort},%
  first={\glsfirstxpabrvfont{\the\glsshorttok}{\glscategorylabel}%
    \protect\glsxtrfullsep{\the\glslabeltok}%
    \protect\glsxtrparen{\glsfirstxplongfont{\the\glslongtok}{\glscategorylabel}}},%
  firstplural={\glsfirstxpabrvfont{\the\glsshortpltok}{\glscategorylabel}%
    \protect\glsxtrfullsep{\the\glslabeltok}%
    \protect\glsxtrparen{\glsfirstxplongfont{\the\glslongpltok}{\glscategorylabel}}},%
  text={\glsxpabrvfont{\the\glsshorttok}{\glscategorylabel}},%
  plural={\glsxpabrvfont{\the\glsshortpltok}{\glscategorylabel}}%
}%

```

Unset the regular attribute if it has been set.

```

\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glsxtrsetcomplexstyle{\the\glslabeltok}{3}%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glssetattribute{\the\glslabeltok}{regular}{false}%
  }%
  {}%
}%
\GlsXtrUseAbbrStyleFmts{short-em-long-em}%

```

}

short-em

\newabbreviationstyle{short-em}%

{%

Set accessibility attributes if enabled.

\glstrAccSuppAbbrSetNoLongAttrs\glscategorylabel

Setup the default fields.

\renewcommand*{\CustomAbbreviationFields}{%

name={\glstrshortnolongname},

sort={\the\glsshorttok},

first={\glstxfirstpabrvfont{\the\glsshorttok}{\glscategorylabel}},

firstplural={\glstxfirstpabrvfont{\the\glsshortpltok}{\glscategorylabel}},

text={\glstxpabrvfont{\the\glsshorttok}{\glscategorylabel}},

plural={\glstxpabrvfont{\the\glsshortpltok}{\glscategorylabel}},

description={\the\glslongtok}}%

\renewcommand*{\GlsXtrPostNewAbbreviation}{%

\glsssetAttribute{\the\glslabeltok}{regular}{true}}%

%

{%

\renewcommand*{\abbrvpluralsuffix}{\glstxremsuffix}%

\renewcommand*{\glstxrrevert}[1]{\glstxrevert{##1}}%

\renewcommand*{\glsabrvfont}[1]{\glsabrvfont{##1}}%

\renewcommand*{\glstxfirstabrvfont}[1]{\glstxfirstabrvfont{##1}}%

\renewcommand*{\glstxfirstlongfont}[1]{\glstxfirstlongdefaultfont{##1}}%

\renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%

The inline full form displays the short form followed by the long form in parentheses.

\renewcommand*{\glstxtrinlinefullformat}[2]{%

\glstxrshortlongformat{##1}{##2}%

{\glstxfirstlongdefaultfont}{\glstxfirstabrvfont}}%

%

\renewcommand*{\glstxtrinlinefullplformat}[2]{%

\glstxrshortlongplformat{##1}{##2}%

{\glstxfirstlongdefaultfont}{\glstxfirstabrvfont}}%

%

\renewcommand*{\Glsxtrinlinefullformat}[2]{%

\Glsxtrshortlongformat{##1}{##2}%

{\glstxfirstlongdefaultfont}{\glstxfirstabrvfont}}%

%

\renewcommand*{\Glsxtrinlinefullplformat}[2]{%

\Glsxtrshortlongplformat{##1}{##2}%

{\glstxfirstlongdefaultfont}{\glstxfirstabrvfont}}%

%

\renewcommand*{\GLSxtrinlinefullformat}[2]{%

\GLSxtrshortlongformat{##1}{##2}%

{\glstxfirstlongdefaultfont}{\glstxfirstabrvfont}}%

```
}%
\renewcommand*{\GLSxtrinlinefullplformat}[2]{%
  \GLSxtrshortlongplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}%
}%
```

The first use full form only displays the short form, but it typically won't be used as the regular attribute is set by this style.

```
\renewcommand*{\glsxtrfullformat}[2]{%
  \glsxtrshortformat{##1}{##2}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\glsxtrfullplformat}[2]{%
  \glsxtrshorttplformat{##1}{##2}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \Glsxtrshortformat{##1}{##2}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \Glsxtrshorttplformat{##1}{##2}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\GLSxtrfullformat}[2]{%
  \GLSxtrshortformat{##1}{##2}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
  \GLSxtrshorttplformat{##1}{##2}{\glsfirstabbrvemfont}%
}%
}
```

short-em-nolong

```
\letabbreviationstyle{short-em-nolong}{short-em}
```

short-em-desc

```
\newabbreviationstyle{short-em-desc}%
{%
```

Set accessibility attributes if enabled. The default name includes the long form but `\glsxtrshortdescname` could be modified to omit the long form, so include the `nameshortaccess` attribute.

```
\glsxtrAccSuppAbbrSetNoLongAttrs\glscategorylabel
```

Setup the default fields.

```
\renewcommand*{\CustomAbbreviationFields}{%
  name={\glsxtrshortdescname},
  sort={\the\glsshorttok},
  first={\glsfirstxpabbrvfont{\the\glsshorttok}{\glscategorylabel}},
  firstplural={\glsfirstxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}},
  text={\glsxpabbrvfont{\the\glsshorttok}{\glscategorylabel}},
  plural={\glsxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glssetattribute{\the\glslabeltok}{regular}{true}}%
```

```

}%
{%

\renewcommand*{\abbrevpluralsuffix}{\glxtremsuffix}%
\renewcommand*{\glxtrrevert}[1]{\glxtremrevert{##1}}%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvemfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvemfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%

```

The inline full form displays the short format followed by the long form in parentheses.

```

\renewcommand*{\glxtrinlinefullformat}[2]{%
  \glxtrshortlongformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}}%
}%
\renewcommand*{\glxtrinlinefullplformat}[2]{%
  \glxtrshortlongplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \Glsxtrshortlongformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \Glsxtrshortlongplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}}%
}%
\renewcommand*{\GLSxtrinlinefullformat}[2]{%
  \GLSxtrshortlongformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}}%
}%
\renewcommand*{\GLSxtrinlinefullplformat}[2]{%
  \GLSxtrshortlongplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}}%
}%

```

The first use full form only displays the short form, but it typically won't be used as the regular attribute is set by this style.

```

\renewcommand*{\glxtrfullformat}[2]{%
  \glxtrshortformat{##1}{##2}{\glsfirstabbrvemfont}}%
}%
\renewcommand*{\glxtrfullplformat}[2]{%
  \glxtrshortplformat{##1}{##2}{\glsfirstabbrvemfont}}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \Glsxtrshortformat{##1}{##2}{\glsfirstabbrvemfont}}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \Glsxtrshortplformat{##1}{##2}{\glsfirstabbrvemfont}}%
}%

```

```

\renewcommand*{\GLSxtrfullformat}[2]{%
  \GLSxtrshortformat{##1}{##2}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
  \GLSxtrshorttplformat{##1}{##2}{\glsfirstabbrvemfont}%
}%
}

```

short-em-nolong-desc

```
\letabbreviationstyle{short-em-nolong-desc}{short-em-desc}
```

nolong-short-em

```

\newabbreviationstyle{nolong-short-em}%
{%
  \GlsXtrUseAbbrStyleSetup{short-em-nolong}%
}%
{%
  \GlsXtrUseAbbrStyleFmts{short-em-nolong}%
}

```

The inline full form displays the long form followed by the short form in parentheses.

```

\renewcommand*{\glsxtrinlinefullformat}[2]{%
  \glsxtrlongshortformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\glsxtrinlinefullplformat}[2]{%
  \glsxtrlongshorttplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \Glsxtrlongshortformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \Glsxtrlongshorttplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\GLSxtrinlinefullformat}[2]{%
  \GLSxtrlongshortformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\GLSxtrinlinefullplformat}[2]{%
  \GLSxtrlongshorttplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}%
}%
}

```

long-noshort-em The short form is explicitly invoked through commands like `\glsxtrshort`.

```

\newabbreviationstyle{long-noshort-em}%
{%

```

Set accessibility attributes if enabled.

```
\glxstrAccSuppAbbrSetNameShortAttrs\glscategorylabel
```

Setup the default fields.

```
\renewcommand*{\CustomAbbreviationFields}{%
  name={\glxstrlongnoshortname},
  sort={\the\glsshorttok},
  first={\glsfirstxplongfont{\the\glslongtok}{\glscategorylabel}},
  firstplural={\glsfirstxplongfont{\the\glslongpltok}{\glscategorylabel}},
  text={\glsxplongfont{\the\glslongtok}{\glscategorylabel}},
  plural={\glsxplongfont{\the\glslongpltok}{\glscategorylabel}},%
  description={\the\glslongtok}%
}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glissetattribute{\the\glslabeltok}{regular}{true}}%
}%
{%

\renewcommand*{\abbrvpluralsuffix}{\glxtremsuffix}%
\renewcommand*{\glxtrrevert}[1]{\glxtremrevert{##1}}%
\renewcommand*{\glsabrvfont}[1]{\glsabrvfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvemfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%
```

The format for subsequent use (not used when the regular attribute is set).

```
\renewcommand*{\glxtrs subsequentfmt}[2]{%
  \glxtrlongformat{##1}{##2}{\glslongdefaultfont}%
}%
\renewcommand*{\glxtrs subsequentplfmt}[2]{%
  \glxtrlongplformat{##1}{##2}{\glslongdefaultfont}%
}%
\renewcommand*{\GLxtrs subsequentfmt}[2]{%
  \GLxtrlongformat{##1}{##2}{\glslongdefaultfont}%
}%
\renewcommand*{\GLxtrs subsequentplfmt}[2]{%
  \GLxtrlongplformat{##1}{##2}{\glslongdefaultfont}%
}%
\renewcommand*{\GLSxtrs subsequentfmt}[2]{%
  \GLSxtrlongformat{##1}{##2}{\glslongdefaultfont}%
}%
\renewcommand*{\GLSxtrs subsequentplfmt}[2]{%
  \GLSxtrlongplformat{##1}{##2}{\glslongdefaultfont}%
}%
```

The inline full form displays the long format followed by the short form in parentheses.

```
\renewcommand*{\glxtrinlinefullformat}[2]{%
  \glxtrlongshortformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}%
}%
```

```

\renewcommand*{\glxstrinlinefullplformat}[2]{%
  \glxstrlongshortplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \Glsxtrlongshortformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \Glsxtrlongshortplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\GLSxtrinlinefullformat}[2]{%
  \GLSxtrlongshortformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\GLSxtrinlinefullplformat}[2]{%
  \GLSxtrlongshortplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}%
}%

```

The first use full form only displays the long form, but it typically won't be used as the `regular` attribute is set by this style.

```

\renewcommand*{\glxstrfullformat}[2]{%
  \glxstrlongformat{##1}{##2}{\glsfirstlongdefaultfont}%
}%
\renewcommand*{\glxstrfullplformat}[2]{%
  \glxstrlongplformat{##1}{##2}{\glsfirstlongdefaultfont}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \Glsxtrlongformat{##1}{##2}{\glsfirstlongdefaultfont}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \Glsxtrlongplformat{##1}{##2}{\glsfirstlongdefaultfont}%
}%
\renewcommand*{\GLSxtrfullformat}[2]{%
  \GLSxtrlongformat{##1}{##2}{\glsfirstlongdefaultfont}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
  \GLSxtrlongplformat{##1}{##2}{\glsfirstlongdefaultfont}%
}%
}

```

`long-em` Backward compatibility:

```
\@glxstr@deprecated@abbrstyle{long-em}{long-noshort-em}
```

`long-em-noshort-em` The short form is explicitly invoked through commands like `\glxstrshort`.

```

\newabbreviationstyle{long-em-noshort-em}%
{%

```


Set accessibility attributes if enabled.

```
\glstrAccSuppAbbrSetNameShortAttrs\glscategorylabel
```

Setup the default fields.

```
\renewcommand*{\CustomAbbreviationFields}{%
  name={\glstrlongnoshortname},
  sort={\the\glsshorttok},
  first={\glsfirstxplongfont{\the\glslongtok}{\glscategorylabel}},
  firstplural={\glsfirstxplongfont{\the\glslongpltok}{\glscategorylabel}},
  text={\glsxplongfont{\the\glslongtok}{\glscategorylabel}},
  plural={\glsxplongfont{\the\glslongpltok}{\glscategorylabel}},%
  description={\protect\glslongemfont{\the\glslongtok}}%
}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glsexclapplyinnerfmtfield{\the\glslabeltok}{desc}%
  \glsssetAttribute{\the\glslabeltok}{regular}{true}}%
}%
{%
```

```
\renewcommand*{\abbrvpluralsuffix}{\glxtremsuffix}%
\renewcommand*{\glstrrevert}[1]{\glxtremrevert{##1}}%
\renewcommand*{\glsabrvfont}[1]{\glsabrvemfont{##1}}%
\renewcommand*{\glsfirstabrvfont}[1]{\glsfirstabrvemfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongemfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongemfont{##1}}%
```

The format for subsequent use (not used when the regular attribute is set).

```
\renewcommand*{\glstrsubsequentfmt}[2]{%
  \glstrlongformat{##1}{##2}{\glslongemfont}%
}%
\renewcommand*{\glstrsubsequentplfmt}[2]{%
  \glstrlongplformat{##1}{##2}{\glslongemfont}%
}%
\renewcommand*{\Glsxtrsubsequentfmt}[2]{%
  \Glsxtrlongformat{##1}{##2}{\glslongemfont}%
}%
\renewcommand*{\Glsxtrsubsequentplfmt}[2]{%
  \Glsxtrlongplformat{##1}{##2}{\glslongemfont}%
}%
\renewcommand*{\GLSxtrsubsequentfmt}[2]{%
  \GLSxtrlongformat{##1}{##2}{\glslongemfont}%
}%
\renewcommand*{\GLSxtrsubsequentplfmt}[2]{%
  \GLSxtrlongplformat{##1}{##2}{\glslongemfont}%
}%
```

The inline full form displays the long format followed by the short form in parentheses.

```
\renewcommand*{\glstrinlinefullformat}[2]{%
  \glstrlongshortformat{##1}{##2}%
  {\glsfirstlongemfont}{\glsfirstabrvemfont}%
}
```

```

}%
\renewcommand*{\glxstrinlinefullplformat}[2]{%
  \glxstrlongshortplformat{##1}{##2}%
  {\glsfirstlongemfont}{\glsfirstabbrvemfont}}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \Glsxtrlongshortformat{##1}{##2}%
  {\glsfirstlongemfont}{\glsfirstabbrvemfont}}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \Glsxtrlongshortplformat{##1}{##2}%
  {\glsfirstlongemfont}{\glsfirstabbrvemfont}}%
}%
\renewcommand*{\GLSxtrinlinefullformat}[2]{%
  \GLSxtrlongshortformat{##1}{##2}%
  {\glsfirstlongemfont}{\glsfirstabbrvemfont}}%
}%
\renewcommand*{\GLSxtrinlinefullplformat}[2]{%
  \GLSxtrlongshortplformat{##1}{##2}%
  {\glsfirstlongemfont}{\glsfirstabbrvemfont}}%
}%

```

The first use full form only displays the long form, but it typically won't be used as the `regular` attribute is set by this style.

```

\renewcommand*{\glxstrfullformat}[2]{%
  \glxstrlongformat{##1}{##2}{\glsfirstlongemfont}}%
}%
\renewcommand*{\glxstrfullplformat}[2]{%
  \glxstrlongplformat{##1}{##2}{\glsfirstlongemfont}}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \Glsxtrlongformat{##1}{##2}{\glsfirstlongemfont}}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \Glsxtrlongplformat{##1}{##2}{\glsfirstlongemfont}}%
}%
\renewcommand*{\GLSxtrfullformat}[2]{%
  \GLSxtrlongformat{##1}{##2}{\glsfirstlongemfont}}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
  \GLSxtrlongplformat{##1}{##2}{\glsfirstlongemfont}}%
}%
}

```

`long-em-noshort-em-noreg` Like `long-em-noshort-em` but doesn't set the `regular` attribute.

```

\newabbreviationstyle{long-em-noshort-em-noreg}%
{%

```

Set accessibility attributes if enabled.

```

\glxstrAccSuppAbbrSetNameShortAttrs\glscategorylabel

```

Setup the default fields.

```
\GlsXtrUseAbbrStyleSetup{long-em-noshort-em}%
```

Unset the regular attribute if it has been set.

```
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glissetattribute{\the\glslabeltok}{regular}{false}%
  }%
}%
{%
  \GlsXtrUseAbbrStyleFmts{long-em-noshort-em}%
}
```

long-noshort-em-desc The emphasized font will only be used if the short form is explicitly invoked through commands like `\glsxtrshort`.

```
\newabbreviationstyle{long-noshort-em-desc}%
{%
  \GlsXtrUseAbbrStyleSetup{long-noshort-desc}%
}%
{%

  \renewcommand*{\abbrvpluralsuffix}{\glxtremsuffix}%
  \renewcommand*{\glxtrrevert}[1]{\glxtremrevert{##1}}%
  \renewcommand*{\glsabrvfont}[1]{\glsabrvemfont{##1}}%
  \renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvemfont{##1}}%
  \renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongdefaultfont{##1}}%
  \renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%
```

The format for subsequent use (not used when the regular attribute is set).

```
\renewcommand*{\glxtrsubsequentfmt}[2]{%
  \glsxtrlongformat{##1}{##2}{\glslongdefaultfont}%
}%
\renewcommand*{\glxtrsubsequentplfmt}[2]{%
  \glsxtrlongplformat{##1}{##2}{\glslongdefaultfont}%
}%
\renewcommand*{\Glsxtrsubsequentfmt}[2]{%
  \Glsxtrlongformat{##1}{##2}{\glslongdefaultfont}%
}%
\renewcommand*{\Glsxtrsubsequentplfmt}[2]{%
  \Glsxtrlongplformat{##1}{##2}{\glslongdefaultfont}%
}%
\renewcommand*{\GLSxtrsubsequentfmt}[2]{%
  \GLSxtrlongformat{##1}{##2}{\glslongdefaultfont}%
}%
\renewcommand*{\GLSxtrsubsequentplfmt}[2]{%
  \GLSxtrlongplformat{##1}{##2}{\glslongdefaultfont}%
}%
```

The inline full form displays the long format followed by the short form in parentheses.

```
\renewcommand*{\glxstrinlinefullformat}[2]{%
  \glxstrlongshortformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\glxstrinlinefullplformat}[2]{%
  \glxstrlongshorttplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \Glsxtrlongshortformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \Glsxtrlongshorttplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\GLSxtrinlinefullformat}[2]{%
  \GLSxtrlongshortformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\GLSxtrinlinefullplformat}[2]{%
  \GLSxtrlongshorttplformat{##1}{##2}%
  {\glsfirstlongdefaultfont}{\glsfirstabbrvemfont}%
}%
```

The first use full form only displays the long form, but it typically won't be used as the `regular` attribute is set by this style.

```
\renewcommand*{\glxstrfullformat}[2]{%
  \glxstrlongformat{##1}{##2}{\glsfirstlongdefaultfont}%
}%
\renewcommand*{\glxstrfullplformat}[2]{%
  \glxstrlongplformat{##1}{##2}{\glsfirstlongdefaultfont}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \Glsxtrlongformat{##1}{##2}{\glsfirstlongdefaultfont}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \Glsxtrlongplformat{##1}{##2}{\glsfirstlongdefaultfont}%
}%
\renewcommand*{\GLSxtrfullformat}[2]{%
  \GLSxtrlongformat{##1}{##2}{\glsfirstlongdefaultfont}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
  \GLSxtrlongplformat{##1}{##2}{\glsfirstlongdefaultfont}%
}%
}
```

long-desc-em Backward compatibility:

`\@glxtr@deprecated@abbrstyle{long-desc-em}{long-noshort-em-desc}`

`long-em-noshort-em-desc` The short form is explicitly invoked through commands like `\glxtrshort`. The long form is emphasized. No accessibility attributes need to be set.

```
\newabbreviationstyle{long-em-noshort-em-desc}%
{%
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glxtrlongnoshortdescname},
    sort={\the\glslongtok},
    first={\glsfirstxplongfont{\the\glslongtok}{\glscategorylabel}},
    firstplural={\glsfirstxplongfont{\the\glslongpltok}{\glscategorylabel}},
    text={\glsxplongfont{\the\glslongtok}{\glscategorylabel}},
    plural={\glsxplongfont{\the\glslongpltok}{\glscategorylabel}}}%
  }%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \glsssetAttribute{\the\glslabeltok}{regular}{true}}%
  }%
  {%

    \renewcommand*{\abbrvpluralsuffix}{\glxtremsuffix}%
    \renewcommand*{\glxtrrevert}[1]{\glxtremrevert{##1}}%
    \renewcommand*{\glsabrvfont}[1]{\glsabrvfont{##1}}%
    \renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvfont{##1}}%
    \renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongfont{##1}}%
    \renewcommand*{\glslongfont}[1]{\glslongfont{##1}}%
```

The format for subsequent use (not used when the regular attribute is set).

```
\renewcommand*{\glxtrsubsequentfmt}[2]{%
  \glxtrlongformat{##1}{##2}{\glslongemfont}%
}%
\renewcommand*{\glxtrsubsequentplfmt}[2]{%
  \glxtrlongplformat{##1}{##2}{\glslongemfont}%
}%
\renewcommand*{\Glsxtrsubsequentfmt}[2]{%
  \Glsxtrlongformat{##1}{##2}{\glslongemfont}%
}%
\renewcommand*{\Glsxtrsubsequentplfmt}[2]{%
  \Glsxtrlongplformat{##1}{##2}{\glslongemfont}%
}%
\renewcommand*{\GLSxtrsubsequentfmt}[2]{%
  \GLSxtrlongformat{##1}{##2}{\glslongemfont}%
}%
\renewcommand*{\GLSxtrsubsequentplfmt}[2]{%
  \GLSxtrlongplformat{##1}{##2}{\glslongemfont}%
}%
```

The inline full form displays the long format followed by the short form in parentheses.

```
\renewcommand*{\glxtrinlinefullformat}[2]{%
  \glxtrlongshortformat{##1}{##2}%
```

```

        {\glsfirstlongemfont}{\glsfirstabbrvemfont}%
    }%
\renewcommand*{\glsxtrinlinefullplformat}[2]{%
    \glsxtrlongshortplformat{##1}{##2}%
    {\glsfirstlongemfont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
    \Glsxtrlongshortformat{##1}{##2}%
    {\glsfirstlongemfont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
    \Glsxtrlongshortplformat{##1}{##2}%
    {\glsfirstlongemfont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\GLSxtrinlinefullformat}[2]{%
    \GLSxtrlongshortformat{##1}{##2}%
    {\glsfirstlongemfont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\GLSxtrinlinefullplformat}[2]{%
    \GLSxtrlongshortplformat{##1}{##2}%
    {\glsfirstlongemfont}{\glsfirstabbrvemfont}%
}%

```

The first use full form only displays the long form, but it typically won't be used as the `regular` attribute is set by this style.

```

\renewcommand*{\glsxtrfullformat}[2]{%
    \glsxtrlongformat{##1}{##2}{\glsfirstlongemfont}%
}%
\renewcommand*{\glsxtrfullplformat}[2]{%
    \glsxtrlongplformat{##1}{##2}{\glsfirstlongemfont}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
    \Glsxtrlongformat{##1}{##2}{\glsfirstlongemfont}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
    \Glsxtrlongplformat{##1}{##2}{\glsfirstlongemfont}%
}%
\renewcommand*{\GLSxtrfullformat}[2]{%
    \GLSxtrlongformat{##1}{##2}{\glsfirstlongemfont}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
    \GLSxtrlongplformat{##1}{##2}{\glsfirstlongemfont}%
}%
}

```

`long-em-noshort-em-desc-noreg` Like `long-em-noshort-em-desc` but doesn't set the `regular` attribute.

```

\newabbreviationstyle{long-em-noshort-em-desc-noreg}%
{%
    \GlsXtrUseAbbrStyleSetup{long-em-noshort-em-desc}%
}

```

Unset the `regular` attribute if it has been set.

```

\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glsssetAttribute{\the\glslabeltok}{regular}{false}%
  }%
  {}%
}%
}%
{%
  \GlsXtrUseAbbrStyleFmts{long-em-noshort-em-desc}%
}

```

short-em-footnote

```

\newabbreviationstyle{short-em-footnote}%
{%

```

Set accessibility attributes if enabled.

```

\glstrAccSuppAbbrSetNoLongAttrs\glscategorylabel

```

Setup the default fields.

```

\renewcommand*{\CustomAbbreviationFields}{%
  name={\glstrfootnotename},
  sort={\the\glsshorttok},
  description={\the\glslongtok},%
  first={\glstxfirstpabrvfont{\the\glsshorttok}{\glscategorylabel}%
    \protect\glstrabbrvfootnote{\the\glslabeltok}%
    {\protect\glstfirstlongfootnote{\the\glslongtok}}},%
  firstplural={\glstxfirstpabrvfont{\the\glsshortpltok}{\glscategorylabel}%
    \protect\glstrabbrvfootnote{\the\glslabeltok}%
    {\protect\glstfirstlongfootnote{\the\glslongpltok}}},%
  text={\glstxpabrvfont{\the\glsshorttok}{\glscategorylabel}},%
  plural={\glstxpabrvfont{\the\glsshortpltok}{\glscategorylabel}}}

```

Switch off hyperlinks on first use to prevent nested hyperlinks, and unset the regular attribute if it has been set.

```

\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glsssetAttribute{\the\glslabeltok}{nohyperfirst}{true}%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glsssetAttribute{\the\glslabeltok}{regular}{false}%
  }%
  {}%
}%
}%
{%

```

```

\renewcommand*{\abbrvpluralsuffix}{\glstxtremsuffix}%
\renewcommand*{\glstxrrevert}[1]{\glstxtremrevert{##1}}%
\renewcommand*{\glstxabbrvfont}[1]{\glstxabbrvemfont{##1}}%
\renewcommand*{\glstfirstabbrvfont}[1]{\glstfirstabbrvemfont{##1}}%
\renewcommand*{\glstfirstlongfont}[1]{\glstfirstlongfootnotefont{##1}}%
\renewcommand*{\glstlongfont}[1]{\glstlongfootnotefont{##1}}%

```

The full format displays the short form followed by the long form as a footnote.

```
\renewcommand*{\glstrfullformat}[2]{%
  \glstrshortformat{##1}{##2}{\glsfirstabbrvemfont}%
  \protect\glstrabbrvfootnote{##1}%
  {\glstrfootnotelongformat{##1}{\glsfirstlongfootnotefont}}%
}%
\renewcommand*{\glstrfullplformat}[2]{%
  \glstrshortplformat{##1}{##2}{\glsfirstabbrvemfont}%
  \protect\glstrabbrvfootnote{##1}%
  {\glstrfootnotelongplformat{##1}{\glsfirstlongfootnotefont}}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \Glsxtrshortformat{##1}{##2}{\glsfirstabbrvemfont}%
  \protect\glstrabbrvfootnote{##1}%
  {\glstrfootnotelongformat{##1}{\glsfirstlongfootnotefont}}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \Glsxtrshortplformat{##1}{##2}{\glsfirstabbrvemfont}%
  \protect\glstrabbrvfootnote{##1}%
  {\glstrfootnotelongplformat{##1}{\glsfirstlongfootnotefont}}%
}%
\renewcommand*{\GLSxtrfullformat}[2]{%
  \GLSxtrshortformat{##1}{##2}{\glsfirstabbrvemfont}%
  \protect\glstrabbrvfootnote{##1}%
  {\glstrfootnotelongformat{##1}{\glsfirstlongfootnotefont}}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
  \GLSxtrshortplformat{##1}{##2}{\glsfirstabbrvemfont}%
  \protect\glstrabbrvfootnote{##1}%
  {\glstrfootnotelongplformat{##1}{\glsfirstlongfootnotefont}}%
}%
```

The first use inline full form uses the short (long) style.

```
\renewcommand*{\glstrinlinefullformat}[2]{%
  \glstrshortlongformat{##1}{##2}%
  {\glsfirstlongfootnotefont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\glstrinlinefullplformat}[2]{%
  \glstrshortlongplformat{##1}{##2}%
  {\glsfirstlongfootnotefont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \Glsxtrshortlongformat{##1}{##2}%
  {\glsfirstlongfootnotefont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \Glsxtrshortlongplformat{##1}{##2}%
  {\glsfirstlongfootnotefont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\GLSxtrinlinefullformat}[2]{%
  \GLSxtrshortlongformat{##1}{##2}%
  {\glsfirstlongfootnotefont}{\glsfirstabbrvemfont}%
}%
```



```

\GLSxtrshortlongformat{##1}{##2}%
{\glsfirstlongfootnotefont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\GLSxtrinlinefullplformat}[2]{%
\GLSxtrshortlongplformat{##1}{##2}%
{\glsfirstlongfootnotefont}{\glsfirstabbrvemfont}%
}%
}

```

footnote-em Backward compatibility:

```
\@glxtr@deprecated@abbrstyle{footnote-em}{short-em-footnote}
```

short-em-footnote-desc Like short-em-footnote but with user supplied description.

```

\newabbreviationstyle{short-em-footnote-desc}{%
{%

```

Set accessibility attributes if enabled.

```
\glxtrAccSuppAbbrSetNameLongAttrs\glscategorylabel
```

Setup the default fields.

```

\renewcommand*{\CustomAbbreviationFields}{%
name={\glxtrfootnotedesname},
sort={\glxtrfootnotedesort},
first={\glsfirstxpabbrvfont{\the\glsshorttok}{\glscategorylabel}%
\protect\glxtrabbrvfootnote{\the\glslabeltok}%
{\protect\glsfirstlongfootnotefont{\the\glslongtok}}},%
firstplural={\glsfirstxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}%
\protect\glxtrabbrvfootnote{\the\glslabeltok}%
{\protect\glsfirstlongfootnotefont{\the\glslongpltok}}},%
text={\glsexpabbrvfont{\the\glsshorttok}{\glscategorylabel}}},%
plural={\glsexpabbrvfont{\the\glsshortpltok}{\glscategorylabel}}}%

```

Switch off hyperlinks on first use to prevent nested hyperlinks, and unset the regular attribute if it has been set.

```

\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glssetattribute{\the\glslabeltok}{nohyperfirst}{true}%
\glshasattribute{\the\glslabeltok}{regular}%
{%
\glssetattribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%
{\%
\GlsXtrUseAbbrStyleFmts{short-em-footnote}%
}

```

short-em-postfootnote

```

\newabbreviationstyle{short-em-postfootnote}{%
{%

```

Set accessibility attributes if enabled.

```
\glxstrAccSuppAbbrSetNoLongAttrs\glscategorylabel
```

Setup the default fields.

```
\renewcommand*{\CustomAbbreviationFields}{%
  name={\glxstrfootnotename},
  sort={\the\glsshorttok},
  description={\the\glslongtok},%
  first={\glsfirstxpabrvfont{\the\glsshorttok}{\glscategorylabel}},%
  firstplural={\glsfirstxpabrvfont{\the\glsshortpltok}{\glscategorylabel}},%
  text={\glxspabrvfont{\the\glsshorttok}{\glscategorylabel}},%
  plural={\glxspabrvfont{\the\glsshortpltok}{\glscategorylabel}}}%
```

Make this category insert a footnote after the link if this was the first use, and unset the `regular` attribute if it has been set. Previously this was done by redefining `glxstrsetupfuldefs` but that interferes with other styles. Instead, this now uses `\glxstrifwasglsl`

```
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \csdef{glxstrpostlink\glscategorylabel}{%
    \glxstrifwasglslfirstuse
  }%
```

Ensure `\glslabel` is expanded as it may be lost by the time the footnote occurs.

```
    \glxstrdopostpunc{\xpglxstrpostabrvfootnote}%
  }%
  {}%
}%
\glshasattribute{\the\glslabeltok}{regular}%
{%
  \glissetattribute{\the\glslabeltok}{regular}{false}%
}%
{}%
}%
}%
{%
```

```
\renewcommand*{\abrvpluralsuffix}{\glxtremsuffix}%
\renewcommand*{\glxtrrevert}[1]{\glxtremrevert{##1}}%
\renewcommand*{\glsabrvfont}[1]{\glsabrvfont{##1}}%
\renewcommand*{\glsfirstabrvfont}[1]{\glsfirstabrvfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongfont{##1}}%
```

The full format displays the short form. The long form is deferred.

```
\renewcommand*{\glxtrfullformat}[2]{%
  \glxtrshortformat{##1}{##2}{\glsfirstabrvfont}%
}%
\renewcommand*{\glxtrfullplformat}[2]{%
  \glxtrshortplformat{##1}{##2}{\glsfirstabrvfont}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
```

```

\Glsxtrshortformat{##1}{##2}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
\Glsxtrshortplformat{##1}{##2}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
\Glsxtrshortformat{##1}{##2}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
\Glsxtrshortplformat{##1}{##2}{\glsfirstabbrvemfont}%
}%

```

The inline full form uses the short (long) style.

```

\renewcommand*{\glsxtrinlinefullformat}[2]{%
\glsxtrshortlongformat{##1}{##2}%
{\glsfirstlongfootnotefont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\glsxtrinlinefullplformat}[2]{%
\glsxtrshortlongplformat{##1}{##2}%
{\glsfirstlongfootnotefont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
\Glsxtrshortlongformat{##1}{##2}%
{\glsfirstlongfootnotefont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
\Glsxtrshortlongplformat{##1}{##2}%
{\glsfirstlongfootnotefont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\GLSxtrinlinefullformat}[2]{%
\GLSxtrshortlongformat{##1}{##2}%
{\glsfirstlongfootnotefont}{\glsfirstabbrvemfont}%
}%
\renewcommand*{\GLSxtrinlinefullplformat}[2]{%
\GLSxtrshortlongplformat{##1}{##2}%
{\glsfirstlongfootnotefont}{\glsfirstabbrvemfont}%
}%
}

```

postfootnote-em Backward compatibility:

```
\@glsxtr@deprecated@abbrstyle{postfootnote-em}{short-em-postfootnote}
```

short-em-postfootnote-desc Like short-em-postfootnote but with user supplied description.

```
\newabbreviationstyle{short-em-postfootnote-desc}%
%
```

Set accessibility attributes if enabled.

```
\glsxtrAccSuppAbbrSetNameLongAttrs\glscategorylabel
```

Setup the default fields.

```
\renewcommand*{\CustomAbbreviationFields}{%
```

```

name={\glxtrfootnotedesname},
sort={\glxtrfootnotedesort},
first={\glsfirstxpabbrvfont{\the\glsshorttok}{\glscategorylabel}},%
firstplural={\glsfirstxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}},%
text={\glxppabbrvfont{\the\glsshorttok}{\glscategorylabel}},%
plural={\glxppabbrvfont{\the\glsshortpltok}{\glscategorylabel}}}%

```

Make this category insert a footnote after the link if this was the first use, and unset the `regular` attribute if it has been set. Previously this was done by redefining `glxtrsetupfulldefs` but that interferes with other styles. Instead, this now uses `\glxtrifwasglslke`

```

\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\csdef{glxtrpostlink\glscategorylabel}{%
\glxtrifwasglslkeandfirstuse
{%
\glxtrdopostpunc{\xpglxtrpostabbrvfootnote}%
}%
}%
\glshasattribute{\the\glslabeltok}{regular}%
{%
\glsselattribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%
\GlsXtrUseAbbrStyleFmts{short-em-postfootnote}%
}

```

2.5 Predefined Styles (User Parentheses Hook)

These styles allow the user to adjust the parenthetical forms. These styles all test for the existence of the field given by:

`\glxtruserfield` Default is the `useri` field.

```
\newcommand*{\glxtruserfield}{useri}
```

`\glxtruserparenssep` Separator used inside parenthetical content.

```
\newcommand*{\glxtruserparenssep}{, }
```

`\glxtruserfieldfmt` Used to format the value of the field given by `\glxtruserfield`.

```
\newcommand*{\glxtruserfieldfmt}[1]{#1}
```

`\glxtruserparen` The format of the parenthetical information. The first argument is the long/short form. The second argument is the entry's label. If `\glscurrentfieldvalue` has been defined, then we have at least `glossaries v4.23`, which makes it easier for the user to adjust this.

```
\ifdef\glscurrentfieldvalue
```

```

{
  \newcommand*{\glxtruserparen}[2]{%
    \glxtrfullsep{#2}%
    \glxtrparen
    {#1\ifglshasfield{\glxtruserfield}{#2}%
      {\expandafter\glxtrgenentrytextfmt\expandafter{\glxtruserparensep}%
        \glxtruserfieldfmt{\expandafter\glxtrgenentrytextfmt\expandafter{\glscurrentfieldvalue}}}%
      }{}%
    }%
  }
}
{
  \newcommand*{\glxtruserparen}[2]{%
    \glxtrfullsep{#2}%
    \glxtrparen
    {#1\ifglshasfield{\glxtruserfield}{#2}%
      {\expandafter\glxtrgenentrytextfmt\expandafter{\glxtruserparensep}%
        \glxtruserfieldfmt{\expandafter\glxtrgenentrytextfmt\expandafter{\@glo@thisvalue}}}%
      }{}%
    }%
  }
}

```

`\GLSxtruserparen` As above but converts the user supplied information to all-caps. The first argument should be provided in all-caps if required.

```

\ifdef\glscurrentfieldvalue
{
  \newcommand*{\GLSxtruserparen}[2]{%
    \glxtrfullsep{#2}%
    \glxtrparen
    {#1\ifglshasfield{\glxtruserfield}{#2}%
      {\expandafter\glxtrgenentrytextfmt\expandafter{\glxtruserparensep}%
        \glxtruserfieldfmt{\expandafter\mfirstucMakeUppercase\expandafter{\expandafter
          \glxtrgenentrytextfmt\expandafter{\glscurrentfieldvalue}}}%
        }{}%
      }%
    }
  }
}
{
  \newcommand*{\GLSxtruserparen}[2]{%
    \glxtrfullsep{#2}%
    \glxtrparen
    {#1\ifglshasfield{\glxtruserfield}{#2}%
      {\expandafter\glxtrgenentrytextfmt\expandafter{\glxtruserparensep}%
        \glxtruserfieldfmt{\expandafter\mfirstucMakeUppercase\expandafter{\expandafter
          \glxtrgenentrytextfmt\expandafter{\@glo@thisvalue}}}%
        }{}%
      }%
    }
  }
}

```

Font used for short form:

```
\glsabbrvuserfont
\newcommand*{\glsabbrvuserfont}[1]{\glsabbrvdefaultfont{#1}}
```

Font used for short form on first use:

```
\glsfirstabbrvuserfont
\newcommand*{\glsfirstabbrvuserfont}[1]{\glsabbrvuserfont{#1}}
```

Font used for long form:

```
\glslonguserfont
\newcommand*{\glslonguserfont}[1]{\glslongdefaultfont{#1}}
```

Font used for long form on first use:

```
\glsfirstlonguserfont
\newcommand*{\glsfirstlonguserfont}[1]{\glslonguserfont{#1}}
```

The default short form suffix:

```
\glxtrusersuffix
\newcommand*{\glxtrusersuffix}{\glxtrabbrvpluralsuffix}
```

Description encapsulator.

`\glsuserdescription` The first argument is the description. The second argument is the label.

```
\newcommand*{\glsuserdescription}[2]{\glslonguserfont{#1}}
```

`long-short-user`

```
\newabbreviationstyle{long-short-user}%
{%
```

Set accessibility attributes if enabled.

```
\glxtrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
```

Setup the default fields.

```
\renewcommand*{\CustomAbbreviationFields}{%
  name={\glxtrlongshortname},
  sort={\the\glsshorttok},
  first={\protect\glsfirstlonguserfont{\the\glslongtok}%
    \protect\glxtruserparen{\protect\glsfirstabbrvuserfont{\the\glsshorttok}}%
    {\the\glslabeltok}},%
  firstplural={\protect\glsfirstlonguserfont{\the\glslongpltok}%
    \protect\glxtruserparen
    {\protect\glsfirstabbrvuserfont{\the\glsshortpltok}}{\the\glslabeltok}},%
  text={\protect\glsabbrvuserfont{\the\glsshorttok}},%
  plural={\protect\glsabbrvuserfont{\the\glsshortpltok}},%
  description={\protect\glsuserdescription{\the\glslongtok}%
    {\the\glslabeltok}}}%
```

Unset the `regular` attribute if it has been set.

```
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glsexclapplyinnerfmtfield{\the\glslabeltok}{desc}%
  \glsxtrsetcomplexstyle{\the\glslabeltok}{2}%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glissetattribute{\the\glslabeltok}{regular}{false}%
  }%
  {}%
}%
%
```

In case the user wants to mix and match font styles, these are redefined here.

```
\renewcommand*{\abbrvpluralsuffix}{\glsxtrusersuffix}%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvuserfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvuserfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlonguserfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslonguserfont{##1}}%
```

The first use full form and the inline full form are the same for this style.

```
\renewcommand*{\glsxtrfullformat}[2]{%
  \glsxtruserlongshortformat{##1}{##2}%
  {\glsfirstlonguserfont}{\glsfirstabbrvuserfont}%
}%
\renewcommand*{\glsxtrfullplformat}[2]{%
  \glsxtruserlongshortplformat{##1}{##2}%
  {\glsfirstlonguserfont}{\glsfirstabbrvuserfont}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \Glsxtruserlongshortformat{##1}{##2}%
  {\glsfirstlonguserfont}{\glsfirstabbrvuserfont}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \Glsxtruserlongshortplformat{##1}{##2}%
  {\glsfirstlonguserfont}{\glsfirstabbrvuserfont}%
}%
\renewcommand*{\GLSxtrfullformat}[2]{%
  \GLSxtruserlongshortformat{##1}{##2}%
  {\glsfirstlonguserfont}{\glsfirstabbrvuserfont}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
  \GLSxtruserlongshortplformat{##1}{##2}%
  {\glsfirstlonguserfont}{\glsfirstabbrvuserfont}%
}%
}
```

`long-postshort-user` Like `long-short-user` but defers the parenthetical matter to after the link.

```
\newabbreviationstyle{long-postshort-user}%
%
```

\glsxtrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
Setup the default fields.

In case the user wants to mix and match font styles, these are redefined here.

First use full form:

544


```

}%
\renewcommand*{\GLSxtrfullformat}[2]{%
  \GLSxtrlongformat{##1}{##2}{\glsfirstlonguserfont}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
  \GLSxtrlongplformat{##1}{##2}{\glsfirstlonguserfont}%
}%
}

```

Small-caps is awkward, so support for that is added.

```

\glsabbrvscuserfont
\newcommand*{\glsabbrvscuserfont}{\glsabbrvscfont}%

\glsfirstabbrvscuserfont
\newcommand*{\glsfirstabbrvscuserfont}{\glsabbrvscuserfont}%

```

The default short form suffix:

```

\glsxtrscusersuffix
\newcommand*{\glsxtrscusersuffix}{\glsxtrscsuffix}

\glsxtrscuserrevert
\newcommand*{\glsxtrscuserrevert}{\glsxtrscerevert}

```

```

\glsxtrlongshortscusername The default name format for this style.
\newcommand*{\glsxtrlongshortscusername}{%
  \protect\glsabbrvscuserfont{\the\glsshorttok}%
}

```

long-postshort-sc-user Like long-postshort-sc-user but uses smallcaps.

```

\newabbreviationstyle{long-postshort-sc-user}%
{%

```

Set accessibility attributes if enabled.

```

\glsxtrAccSuppAbbrSetFirstLongAttrs\glscategorylabel

```

Setup the default fields.

```

\renewcommand*{\CustomAbbreviationFields}{%
  name={\glsxtrlongshortscusername},
  sort={\the\glsshorttok},
  first={\protect\glsfirstlonguserfont{\the\glslongtok}},%
  firstplural={\protect\glsfirstlonguserfont{\the\glslongpltok}},%
  text={\protect\glsabbrvscuserfont{\the\glsshorttok}},%
  plural={\protect\glsabbrvscuserfont{\the\glsshortpltok}},%
  description={\protect\glsuserdescription{\the\glslongtok}%
    {\the\glslabeltok}}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glsexclapplyinnerfmtfield{\the\glslabeltok}{desc}%
  \csdef{glsxtrpostlink\glscategorylabel}{%

```

```

\glxstrifwasfirstuse
{%
  \glxstrpostusershortformat{\glslabel}{\glsfirstabbrvcuserfont}%
}%
{}%
}%
\glshasattribute{\the\glslabeltok}{regular}%
{%
  \glissetattribute{\the\glslabeltok}{regular}{false}%
}%
{}%
}%
}%
{%

```

In case the user wants to mix and match font styles, these are redefined here.

```

\renewcommand*{\abbrvpluralsuffix}{\glxtrscusersuffix}%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvcuserfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvcuserfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlonguserfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslonguserfont{##1}}%
\renewcommand*{\glxtrrevert}[1]{\glxtrscuserrevert{##1}}%

```

First use full form:

```

\renewcommand*{\glxtrfullformat}[2]{%
  \glxtrlongformat{##1}{##2}{\glsfirstlonguserfont}%
}%
\renewcommand*{\glxtrfullplformat}[2]{%
  \glxtrlongplformat{##1}{##2}{\glsfirstlonguserfont}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \Glsxtrlongformat{##1}{##2}{\glsfirstlonguserfont}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \Glsxtrlongplformat{##1}{##2}{\glsfirstlonguserfont}%
}%
\renewcommand*{\GLSxtrfullformat}[2]{%
  \GLSxtrlongformat{##1}{##2}{\glsfirstlonguserfont}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
  \GLSxtrlongplformat{##1}{##2}{\glsfirstlonguserfont}%
}%

```

In-line format is the same as the first use format.

```

}

```

`\glxtrlongshortuserdesname`

```

\newcommand*{\glxtrlongshortuserdesname}{%
  \protect\glslonguserfont{\the\glslongtok}%
  \protect\glxtruserparen
  {\protect\glsabbrvuserfont{\the\glsshorttok}}{\the\glslabeltok}%
}

```

}

long-postshort-user-desc Like long-postshort-user but the user supplies the description.

```
\newabbreviationstyle{long-postshort-user-desc}%  
{%
```

Set accessibility attributes if enabled.

```
\glstrAccSuppAbbrSetTextShortAttrs\glscategorylabel
```

Setup the default fields.

```
\renewcommand*{\CustomAbbreviationFields}{%  
  name={\glstrlongshortuserdescname},  
  sort={\the\glslongtok},  
  first={\protect\glstrfirstlonguserfont{\the\glslongtok}},%  
  firstplural={\protect\glstrfirstlonguserfont{\the\glslongpltok}},%  
  
  text={\protect\glstrabbrvuserfont{\the\glsshorttok}},%  
  plural={\protect\glstrabbrvuserfont{\the\glsshortpltok}}}%  
}%  
\renewcommand*{\GlsXtrPostNewAbbreviation}{%  
  \csdef{glstrpostlink\glscategorylabel}{%  
    \glstrifwasfirstuse  
    {%  
      \glstrpostusershortformat{\glslabel}{\glstrfirstabbrvuserfont}%  
    }%  
    {}%  
  }%  
  \glshasattribute{\the\glslabeltok}{regular}%  
  {%  
    \glsssetattribute{\the\glslabeltok}{regular}{false}%  
  }%  
  {}%  
}%  
}%  
{%  
  \GlsXtrUseAbbrStyleFmts{long-postshort-user}%  
}
```

glstrlongshortscuserdescname

```
\newcommand*{\glstrlongshortscuserdescname}{%  
  \protect\glslonguserfont{\the\glslongtok}%  
  \protect\glstruserparen  
  {\protect\glstrabbrvscuserfont{\the\glsshorttok}}{\the\glslabeltok}%  
}
```

long-postshort-sc-user-desc Like long-postshort-sc-user but the user supplies the description.

```
\newabbreviationstyle{long-postshort-sc-user-desc}%  
{%
```

Set accessibility attributes if enabled.

```
\glstrAccSuppAbbrSetTextShortAttrs\glscategorylabel
```

Setup the default fields.

```
\renewcommand*{\CustomAbbreviationFields}{%
  name={\glxstrlongshortscuserdescname},
  sort={\the\glslongtok},
  first={\protect\glsfirstlonguserfont{\the\glslongtok}},%
  firstplural={\protect\glsfirstlonguserfont{\the\glslongpltok}},%
  text={\protect\glsabbrvscuserfont{\the\glsshorttok}},%
  plural={\protect\glsabbrvscuserfont{\the\glsshortpltok}}}%
}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \csdef{glxstrpostlink\glscategorylabel}{%
    \glxstrifwasfirstuse
    {%
      \glxstrpostusershortformat{\glslabel}{\glsfirstabbrvscuserfont}%
    }%
  }%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glissetattribute{\the\glslabeltok}{regular}{false}%
  }%
  {%
  }%
}%
{\%
  \GlsXtrUseAbbrStyleFmts{long-postshort-sc-user}%
}
```

short-postlong-user Like short-long-user but defers the parenthetical matter to after the link.

```
\newabbreviationstyle{short-postlong-user}%
{%
```

Set accessibility attributes if enabled.

```
\glxstrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
```

Setup the default fields.

```
\renewcommand*{\CustomAbbreviationFields}{%
  name={\glxstrshortlongname},
  sort={\the\glsshorttok},
  first={\protect\glsfirstlonguserfont{\the\glslongtok}},%
  firstplural={\protect\glsfirstlonguserfont{\the\glslongpltok}},%

  text={\protect\glsabbrvuserfont{\the\glsshorttok}},%
  plural={\protect\glsabbrvuserfont{\the\glsshortpltok}},%
  description={\protect\glsuserdescription{\the\glslongtok}%
    {\the\glslabeltok}}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glsexclapplyinnerfmtfield{\the\glslabeltok}{desc}%
  \csdef{glxstrpostlink\glscategorylabel}{%
    \glxstrifwasfirstuse
```

```

    {%
      \glxstrpostuserlongformat{\glslabel}{\glsfirstlonguserfont}%
    }%
  {}%
}%
\glshasattribute{\the\glslabeltok}{regular}%
{%
  \glissetattribute{\the\glslabeltok}{regular}{false}%
}%
{}%
}%
}%
{%

```

In case the user wants to mix and match font styles, these are redefined here.

```

\renewcommand*{\abbrvpluralsuffix}{\glxstrusersuffix}%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvuserfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvuserfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlonguserfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslonguserfont{##1}}%

```

First use full form:

```

\renewcommand*{\glxstrfullformat}[2]{%
  \glxstrshortformat{##1}{##2}{\glsfirstabbrvuserfont}%
}%
\renewcommand*{\glxstrfullplformat}[2]{%
  \glxstrshortplformat{##1}{##2}{\glsfirstabbrvuserfont}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \Glsxtrshortformat{##1}{##2}{\glsfirstabbrvuserfont}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \Glsxtrshortplformat{##1}{##2}{\glsfirstabbrvuserfont}%
}%
\renewcommand*{\GLSxtrfullformat}[2]{%
  \GLSxtrshortformat{##1}{##2}{\glsfirstabbrvuserfont}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
  \GLSxtrshortplformat{##1}{##2}{\glsfirstabbrvuserfont}%
}%

```

In-line format should be the same.

```

}

```

glxstrshortlonguserdescname

```

\newcommand*{\glxstrshortlonguserdescname}{%
  \protect\glsabbrvuserfont{\the\glsshorttok}%
  \protect\glxstruserparen
  {\protect\glslonguserfont{\the\glslongtok}}%
  {\the\glslabeltok}%
}

```

short-postlong-user-desc Like short-postlong-user but leaves the user to specify the description.

```
\newabbreviationstyle{short-postlong-user-desc}%  
{%
```

Set accessibility attributes if enabled.

```
\glstrAccSuppAbbrSetTextShortAttrs\glscategorylabel
```

Setup the default fields.

```
\renewcommand*{\CustomAbbreviationFields}{%  
  name={\glstrshortlonguserdescname},  
  sort={\the\glsshorttok},  
  first={\protect\glfirstlonguserfont{\the\glslongtok}},%  
  firstplural={\protect\glfirstlonguserfont{\the\glslongpltok}},%  
  
  text={\protect\glsabbrvuserfont{\the\glsshorttok}},%  
  plural={\protect\glsabbrvuserfont{\the\glsshortpltok}}%  
}%  
\renewcommand*{\GlsXtrPostNewAbbreviation}{%  
  \csdef{glstrpostlink\glscategorylabel}{%  
    \glstrifwasfirstuse  
    {%  
      \glstrpostuserlongformat{\glslabel}{\glfirstlonguserfont}%  
    }%  
    {}%  
  }%  
  \glshasattribute{\the\glslabeltok}{regular}%  
  {%  
    \glissetattribute{\the\glslabeltok}{regular}{false}%  
  }%  
  {}%  
}%  
}%  
{%  
  \GlsXtrUseAbbrStyleFmts{short-postlong-user}%  
}
```

long-short-user-desc

```
\newabbreviationstyle{long-short-user-desc}%  
{%
```

Set accessibility attributes if enabled.

```
\glstrAccSuppAbbrSetTextShortAttrs\glscategorylabel
```

Setup the default fields.

```
\renewcommand*{\CustomAbbreviationFields}{%  
  name={\glstrlongshortuserdescname},  
  sort={\glstrlongshortdescsort},%  
  
  first={\protect\glfirstlonguserfont{\the\glslongtok}}%  
  \protect\glstruserparen{\protect\glfirstabbrvuserfont{\the\glsshorttok}}%  
  {\the\glslabeltok}},%  
  firstplural={\protect\glfirstlonguserfont{\the\glslongpltok}}%
```

```

\protect\glxtruserparen
{\protect\glsfirstabbrvuserfont{\the\glsshortpltok}}{\the\glslabeltok}},%
text={\protect\glsabbrvfont{\the\glsshorttok}},%
plural={\protect\glsabbrvfont{\the\glsshortpltok}}}%
}%

```

Unset the regular attribute if it has been set.

```

\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glxtrsetcomplexstyle{\the\glslabeltok}{2}%
\glshasattribute{\the\glslabeltok}{regular}%
{%
\glissetattribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%
{\%
\GlsXtrUseAbbrStyleFmts{long-short-user}%
}

```

short-long-user

```

\newabbreviationstyle{short-long-user}%
{%

```

Set accessibility attributes if enabled.

```
\glxtrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
```

Setup the default fields.

\glslonguserfont is used in the description since \glsdesc doesn't set the style. (Now in \glsuserdescription.)

```

\renewcommand*{\CustomAbbreviationFields}{%
name={\glxtrshortlongname},
sort={\the\glsshorttok},
description={\protect\glsuserdescription{\the\glslongtok}%
{\the\glslabeltok}},%
first={\protect\glsfirstabbrvuserfont{\the\glsshorttok}%
\protect\glxtruserparen{\protect\glsfirstlonguserfont{\the\glslongtok}}%
{\the\glslabeltok}},%
firstplural={\protect\glsfirstabbrvuserfont{\the\glsshortpltok}%
\protect\glxtruserparen{\protect\glsfirstlonguserfont{\the\glslongpltok}}%
{\the\glslabeltok}},%

text={\protect\glsabbrvuserfont{\the\glsshorttok}},%
plural={\protect\glsabbrvuserfont{\the\glsshortpltok}}}%

```

Unset the regular attribute if it has been set.

```

\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glsexclapplyinnerfmtfield{\the\glslabeltok}{desc}%
\glxtrsetcomplexstyle{\the\glslabeltok}{2}%
\glshasattribute{\the\glslabeltok}{regular}%

```

```

    {%
      \glsetattribute{\the\glslabeltok}{regular}{false}%
    }%
    {}%
  }%
}%
{%

```

In case the user wants to mix and match font styles, these are redefined here.

```

\renewcommand*{\abbrvpluralsuffix}{\glxtrusersuffix}%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvuserfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvuserfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlonguserfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslonguserfont{##1}}%

```

The first use full form and the inline full form are the same for this style.

```

\renewcommand*{\glxtrfullformat}[2]{%
  \glxtrusershortlongformat{##1}{##2}%
  {\glsfirstlonguserfont}{\glsfirstabbrvuserfont}%
}%
\renewcommand*{\glxtrfullplformat}[2]{%
  \glxtrusershortlongplformat{##1}{##2}%
  {\glsfirstlonguserfont}{\glsfirstabbrvuserfont}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \Glsxtrusershortlongformat{##1}{##2}%
  {\glsfirstlonguserfont}{\glsfirstabbrvuserfont}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \Glsxtrusershortlongplformat{##1}{##2}%
  {\glsfirstlonguserfont}{\glsfirstabbrvuserfont}%
}%
\renewcommand*{\GLSxtrfullformat}[2]{%
  \GLSxtrusershortlongformat{##1}{##2}%
  {\glsfirstlonguserfont}{\glsfirstabbrvuserfont}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
  \GLSxtrusershortlongplformat{##1}{##2}%
  {\glsfirstlonguserfont}{\glsfirstabbrvuserfont}%
}%
}

```

short-long-user-desc

```

\newabbreviationstyle{short-long-user-desc}%
{%

```

Set accessibility attributes if enabled.

```

\glxtrAccSuppAbbrSetTextShortAttrs\glscategorylabel

```

Setup the default fields.

```

\renewcommand*{\CustomAbbreviationFields}{%

```



```

name={\glxtrshortlonguserdescname},
sort={\glxtrshortlongdescsort},%

first={\protect\glxtrshortlonguserfont{\the\glsshorttok}%
\protect\glxtruserparen{\protect\glxtrshortlonguserfont{\the\glslongtok}}}%
{\the\glslabeltok}},%
firstplural={\protect\glxtrshortlonguserfont{\the\glsshortpltok}%
\protect\glxtruserparen{\protect\glxtrshortlonguserfont{\the\glslongpltok}}}%
{\the\glslabeltok}},%
text={\protect\glxtrshortlonguserfont{\the\glsshorttok}},%
plural={\protect\glxtrshortlonguserfont{\the\glsshortpltok}}}%
}%

Unset the regular attribute if it has been set.
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glxtrsetcomplexstyle{\the\glslabeltok}{2}%
\glxtrhasattribute{\the\glslabeltok}{regular}%
{%
\glxtrsetattribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%
{%
\GlsXtrUseAbbrStyleFmts{short-long-user}%
}

```

2.6 Predefined Styles (Hyphen)

These styles are designed to work with the `markwords` attribute. They check if the inserted material (provided by the final optional argument of commands like `\gls`) starts with a hyphen. If it does, the insert is added to the parenthetical material. Note that commands like `\glxtrlong` set `\glsinsert` to empty with the entire link-text stored in `\glscustomtext`.

```

\glxtrifhyphenstart Checks if the argument starts with a hyphen. The argument may be \glsinsert
so check for that and expand.
\newrobustcmd*{\glxtrifhyphenstart}[3]{%
\ifx\glsinsert#1\relax
\expandafter\@glxtrifhyphenstart#1\relax\relax
\@end@glxtrifhyphenstart{#2}{#3}%
\else
\@glxtrifhyphenstart#1\relax\relax\@end@glxtrifhyphenstart{#2}{#3}%
\fi
}

\@glxtrifhyphenstart
\def\@glxtrifhyphenstart#1#2\@end@glxtrifhyphenstart#3#4{%
\ifx-#1\relax#3\else #4\fi
}

```

`\glxstrlonghyphenshort`

```
\glxstrlonghyphenshort{<label>}{<long>}{<short>}{<insert>}
```

The `<long>` and `<short>` arguments may be the plural form. The `<long>` argument may also be the first letter uppercase form. This unfortunately doesn't fit in with the new `\glxstrshortformat` etc commands, but is retained for backward-compatibility. This means that the inserted part has to have a separate encapsulation for the inner format. The `<long>` and `<short>` arguments will need to include the inner format.

```
\newcommand*{\glxstrlonghyphenshort}[4]{%
```

Grouping is needed to localise the redefinitions.

```
{%
```

If `<insert>` starts with a hyphen, redefine `\glxstrwordsep` to a hyphen. The inserted material is also inserted into the parenthetical part. (The inserted material is grouped as a precautionary measure.) No change is made to `\glxstrwordsep` if `<insert>` doesn't start with a hyphen.

```
\glxstrifhyphenstart{#4}{\let\glxstrwordsep\glxstrwordsephyphen}{}%
\glsfirstlonghyphenfont{#2\ifglxstrinsertinside
  {\glxstrgenentrytextfmt{#4}}\fi}%
\ifglxstrinsertinside\else{\glxstrgenentrytextfmt{#4}}\fi
\glxstrfullsep{#1}%
\glxstrparen{\glsfirstabbrvhyphenfont{#3\ifglxstrinsertinside
  {\glxstrgenentrytextfmt{#4}}\fi}%
\ifglxstrinsertinside\else{\glxstrgenentrytextfmt{#4}}\fi}%
}%
}
```

`\GLSxtrlonghyphenshort` As above but convert the insert to uppercase. The long and short should already have the case-change applied.

```
\newcommand*{\GLSxtrlonghyphenshort}[4]{%
  {%
    \glxstrifhyphenstart{#4}{\let\glxstrwordsep\glxstrwordsephyphen}{}%
    \glsfirstlonghyphenfont{#2\ifglxstrinsertinside
      {\mfirstucMakeUppercase{\glxstrgenentrytextfmt{#4}}}\fi}%
    \ifglxstrinsertinside\else
      {\mfirstucMakeUppercase{\glxstrgenentrytextfmt{#4}}}%
    \fi
    \glxstrfullsep{#1}%
    \glxstrparen{\glsfirstabbrvhyphenfont{#3\ifglxstrinsertinside
      {\mfirstucMakeUppercase{\glxstrgenentrytextfmt{#4}}}\fi}%
    \ifglxstrinsertinside\else
      {\mfirstucMakeUppercase{\glxstrgenentrytextfmt{#4}}}%
    \fi}%
  }%
}
```

```
\glsxtrshorthyphennolong{<label>}{<short>}{<insert>}
```

`\glsxtrshorthyphennolong`

The `<short>` argument may be the plural form and may also be the first letter uppercase form.

As `\glsxtrlonghyphenshort` but where only the short form should be shown.

```
\newcommand*{\glsxtrshorthyphennolong}[3]{%
```

Grouping is needed to localise the redefinitions.

```
{%
```

If `<insert>` starts with a hyphen, redefine `\glsxtrwordsep` to a hyphen.

```
\glsxtrifhyphenstart{#3}{\let\glsxtrwordsep\glsxtrwordsephyphen}{}%
```

```
\glsfirstabbrvhyphenfont{#2\ifglsxtrininsertinside
```

```
{\glsxtrgenentrytextfmt{#3}}\fi}%
```

```
\ifglsxtrininsertinside\else{\glsxtrgenentrytextfmt{#3}}\fi
```

```
}%
```

```
}
```

`\GLSxtrshorthyphennolong` As above but all-caps.

```
\newcommand*{\GLSxtrshorthyphennolong}[3]{%
```

```
{%
```

```
\glsxtrifhyphenstart{#3}{\let\glsxtrwordsep\glsxtrwordsephyphen}{}%
```

```
\glsfirstabbrvhyphenfont{#2\ifglsxtrininsertinside
```

```
{\mfirstucMakeUppercase{\glsxtrgenentrytextfmt{#3}}}\fi}%
```

```
\ifglsxtrininsertinside\else
```

```
{\mfirstucMakeUppercase{\glsxtrgenentrytextfmt{#3}}}%
```

```
\fi
```

```
}%
```

```
}
```

`\glsabbrvhyphenfont`

```
\newcommand*{\glsabbrvhyphenfont}{\glsabbrvdefaultfont}%
```

`\glsfirstabbrvhyphenfont`

```
\newcommand*{\glsfirstabbrvhyphenfont}{\glsabbrvhyphenfont}%
```

`\glslonghyphenfont`

```
\newcommand*{\glslonghyphenfont}{\glslongdefaultfont}%
```

`\glsfirstlonghyphenfont`

```
\newcommand*{\glsfirstlonghyphenfont}{\glslonghyphenfont}%
```

The default short form suffix:

`\glsxtrhyphensuffix`

```
\newcommand*{\glsxtrhyphensuffix}{\glsxtrabbrvpluralsuffix}
```

`\glxtrlonghyphensort`

```
\newcommand*{\glxtrlonghyphensort}{\expandonce\glxtrorgshort}
```

`long-hyphen-short-hyphen` Designed for use with the `markwords` attribute.

```
\newabbreviationstyle{long-hyphen-short-hyphen}%
{%
```

Set accessibility attributes if enabled.

```
\glxtrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
```

Setup the default fields.

```
\renewcommand*{\CustomAbbreviationFields}{%
  name={\glxtrlongshortname},
  sort={\glxtrlonghyphensort},
  first={\protect\glsfirstlonghyphenfont{\the\glslongtok}%
    \protect\glxtrfullsep{\the\glslabeltok}%
    \protect\glxtrparen{\protect\glsfirstabbrvhyphenfont{\the\glsshorttok}}},%
  firstplural={\protect\glsfirstlonghyphenfont{\the\glslongpltok}%
    \protect\glxtrfullsep{\the\glslabeltok}%
    \protect\glxtrparen{\protect\glsfirstabbrvhyphenfont{\the\glsshortpltok}}},%
  text={\protect\glsabbrvhyphenfont{\the\glsshorttok}},%
  plural={\protect\glsabbrvhyphenfont{\the\glsshortpltok}},%
  description={\protect\glslonghyphenfont{\the\glslongtok}}}%
```

Unset the regular attribute if it has been set.

```
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glsexclapplyinnerfmtfield{\the\glslabeltok}{desc}%
  \glxtrsetcomplexstyle{\the\glslabeltok}{3}%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glissetattribute{\the\glslabeltok}{regular}{false}%
  }%
  {}%
}%
}%
{%
  \renewcommand*{\abbrvpluralsuffix}{\glxtrhyphensuffix}%
  \renewcommand*{\glsabbrvfont}[1]{\glsabbrvhyphenfont{##1}}%
  \renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvhyphenfont{##1}}%
  \renewcommand*{\glsfirstlongfont}[1]{\glsfirstlonghyphenfont{##1}}%
  \renewcommand*{\glslongfont}[1]{\glslonghyphenfont{##1}}%
```

The first use full form and the inline full form are the same for this style.

```
\renewcommand*{\glxtrfullformat}[2]{%
  \glxtrlonghyphensort{##1}%
  {%
    \glusifattribute{##1}{markwords}{true}%
  }%
  \glsaccesslong{##1}%
}%
{%
```

```

        \glsaccessfmtlong{}\glsxtrgenentrytextfmt}{##1}%
    }%
}%
{%
    \glsifattribute{##1}{markshortwords}{true}%
    {%
        \glsaccessshort{##1}%
    }%
    {%
        \glsaccessfmtshort{}\glsxtrgenentrytextfmt}{##1}%
    }%
}%
{##2}%
}%
\renewcommand*\glsxtrfullplformat}[2]{%
    \glsxtrlonghyphenshort{##1}%
    {%
        \glsifattribute{##1}{markwords}{true}%
        {%
            \glsaccesslongpl{##1}%
        }%
        {%
            \glsaccessfmtlongpl{}\glsxtrgenentrytextfmt}{##1}%
        }%
    }%
    {%
        \glsifattribute{##1}{markshortwords}{true}%
        {%
            \glsaccessshortpl{##1}%
        }%
        {%
            \glsaccessfmtshortpl{}\glsxtrgenentrytextfmt}{##1}%
        }%
    }%
    {##2}%
}%
\renewcommand*\Glsxtrfullformat}[2]{%
    \glsxtrlonghyphenshort{##1}%
    {%
        \glsifattribute{##1}{markwords}{true}%
        {%
            \Glsaccesslong{##1}%
        }%
        {%
            \Glsaccessfmtlong{}\glsxtrgenentrytextfmt}{##1}%
        }%
    }%
    {%
        \glsifattribute{##1}{markshortwords}{true}%
        {%

```

```

        \glsaccesssshort{##1}%
    }%
    {%
        \glsaccessfmtshort{}{\glsxtrgenentrytextfmt}{##1}%
    }%
}%
{##2}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
    \glsxtrlonghyphenshort{##1}%
    {%
        \glsifattribute{##1}{markwords}{true}%
        {%
            \Glsaccesslongpl{##1}%
        }%
        {%
            \Glsaccessfmtlongpl{}{\glsxtrgenentrytextfmt}{##1}%
        }%
    }%
    {%
        \glsifattribute{##1}{markshortwords}{true}%
        {%
            \glsaccesssshortpl{##1}%
        }%
        {%
            \glsaccessfmtshortpl{}{\glsxtrgenentrytextfmt}{##1}%
        }%
    }%
    {##2}%
}%
\renewcommand*{\GLSxtrfullformat}[2]{%
    \GLSxtrlonghyphenshort{##1}%
    {%
        \glsifattribute{##1}{markwords}{true}%
        {%
            \GLSaccesslong{##1}%
        }%
        {%
            \GLSaccessfmtlong{}{\glsxtrgenentrytextfmt}{##1}%
        }%
    }%
    {%
        \glsifattribute{##1}{markshortwords}{true}%
        {%
            \GLSaccesssshort{##1}%
        }%
        {%
            \GLSaccessfmtshort{}{\glsxtrgenentrytextfmt}{##1}%
        }%
    }%
}%

```

```

    {##2}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
  \GLSxtrlonghyphenshort{##1}%
  {%
    \glsifattribute{##1}{markwords}{true}%
    {%
      \GLSaccesslongpl{##1}%
    }%
    {%
      \GLSaccessfmtlongpl{}{\glsxtrgenentrytextfmt}{##1}%
    }%
  }%
  {%
    \glsifattribute{##1}{markshortwords}{true}%
    {%
      \GLSaccessshortpl{##1}%
    }%
    {%
      \GLSaccessfmtshortpl{}{\glsxtrgenentrytextfmt}{##1}%
    }%
  }%
  {##2}%
}%

```

Subsequent form also needs checking for a hyphen in case the short form has spaces.

```

\renewcommand*{\glsxtrsubsequentfmt}[2]{%
  \glsxtrshorthyphennolong{##1}%
  {%
    \glsifattribute{##1}{markshortwords}{true}%
    {%
      \glsaccessshort{##1}%
    }%
    {%
      \glsaccessfmtshort{}{\glsxtrgenentrytextfmt}{##1}%
    }%
  }%
  {##2}%
}%
\renewcommand*{\glsxtrsubsequentplfmt}[2]{%
  \glsxtrshorthyphennolong{##1}%
  {%
    \glsifattribute{##1}{markshortwords}{true}%
    {%
      \glsaccessshortpl{##1}%
    }%
    {%
      \glsaccessfmtshortpl{}{\glsxtrgenentrytextfmt}{##1}%
    }%
  }%

```

```

}%
{##2}%
}%
\renewcommand*{\Glsxtrsubsequentfmt}[2]{%
\glsxtrshorthyphennolong{##1}%
{%
\glsifattribute{##1}{markshortwords}{true}%
{%
\Glsaccessshort{##1}%
}%
}%
\Glsaccessfmtshort{}{\glsxtrgenentrytextfmt}{##1}%
}%
}%
{##2}%
}%
\renewcommand*{\Glsxtrsubsequentplfmt}[2]{%
\glsxtrshorthyphennolong{##1}%
{%
\glsifattribute{##1}{markshortwords}{true}%
{%
\Glsaccessshortpl{##1}%
}%
}%
\Glsaccessfmtshortpl{}{\glsxtrgenentrytextfmt}{##1}%
}%
}%
{##2}%
}%
\renewcommand*{\GLSxtrsubsequentfmt}[2]{%
\GLSxtrshorthyphennolong{##1}%
{%
\glsifattribute{##1}{markshortwords}{true}%
{%
\GLSaccessshort{##1}%
}%
}%
\GLSaccessfmtshort{}{\glsxtrgenentrytextfmt}{##1}%
}%
}%
{##2}%
}%
\renewcommand*{\GLSxtrsubsequentplfmt}[2]{%
\GLSxtrshorthyphennolong{##1}%
{%
\glsifattribute{##1}{markshortwords}{true}%
{%
\GLSaccessshortpl{##1}%
}%
}%
}%

```



```

        \GLSaccessfmtshortpl{\glxtrgenentrytextfmt}{##1}%
      }%
    }%
    {##2}%
  }%
}

```

long-hyphen-short-hyphen-desc Like long-hyphen-short-hyphen but the description must be supplied by the user.

```

\newabbreviationstyle{long-hyphen-short-hyphen-desc}%
{%

```

Set accessibility attributes if enabled.

```

\glxtrAccSuppAbbrSetTextShortAttrs\glscategorylabel

```

Setup the default fields.

```

\renewcommand*{\CustomAbbreviationFields}{%
  name={\glxtrlongshortdescname},
  sort={\glxtrlongshortdescsort},
  first={\protect\glsfirstlonghyphenfont{\the\glslongtok}%
    \protect\glxtrfullsep{\the\glslabeltok}%
    \protect\glxtrparen{\protect\glsfirstabbrvhyphenfont{\the\glsshorttok}}},%
  firstplural={\protect\glsfirstlonghyphenfont{\the\glslongpltok}%
    \protect\glxtrfullsep{\the\glslabeltok}%
    \protect\glxtrparen{\protect\glsfirstabbrvhyphenfont{\the\glsshortpltok}}},%
  text={\protect\glsabbrvhyphenfont{\the\glsshorttok}},%
  plural={\protect\glsabbrvhyphenfont{\the\glsshortpltok}}%
}%

```

Unset the regular attribute if it has been set.

```

\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glxtrsetcomplexstyle{\the\glslabeltok}{3}%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glissetattribute{\the\glslabeltok}{regular}{false}%
  }%
  {}%
}%
{%
  \GlsXtrUseAbbrStyleFmts{long-hyphen-short-hyphen}%
}

```

```

\glxtrlonghyphennoshort{\langle label \rangle}{\langle long \rangle}{\langle insert \rangle}

```

\glxtrlonghyphennoshort

As with \glxtrlonghyphenshort this doesn't fit in with the new \glxtrshortformat so the inserted part has to have a separate encapsulation for the inner format. The *\langle long \rangle* argument will need to include the inner format.

```

\newcommand*{\glxtrlonghyphennoshort}[3]{%

```

Grouping is needed to localise the redefinitions.

```
{%
```

If *<insert>* starts with a hyphen, redefine `\glxtrwordsep` to a hyphen. The inserted material is also inserted into the parenthetical part. (The inserted material is grouped as a precautionary measure.) No change is made to `\glxtrwordsep` if *<insert>* doesn't start with a hyphen.

```
\glxtrifhyphenstart{#3}{\let\glxtrwordsep\glxtrwordsephyphen}{}%
\glsfirstlonghyphenfont{#2\ifglxtrininsertinside
  {\glxtrgenentrytextfmt{#3}}\fi}%
\ifglxtrininsertinside\else{\glxtrgenentrytextfmt{#3}}\fi
}%
}
```

`\GLSxtrlonghyphennoshort` As above but convert insert to all-caps.

```
\newcommand*{\GLSxtrlonghyphennoshort}[3]{%
{%
\glxtrifhyphenstart{#3}{\let\glxtrwordsep\glxtrwordsephyphen}{}%
\glsfirstlonghyphenfont{#2\ifglxtrininsertinside
  {\mfirstucMakeUppercase{\glxtrgenentrytextfmt{#3}}}\fi}%
\ifglxtrininsertinside\else
  {\mfirstucMakeUppercase{\glxtrgenentrytextfmt{#3}}}%
\fi
}%
}
```

`\xtrlonghyphennoshortdescsort`

```
\newcommand*{\glxtrlonghyphennoshortdescsort}{\expandonce\glxtrorglong}
```

`long-hyphen-noshort-desc-noreg`

This version doesn't show the short form (except explicitly with `\glxtrshort`). Since `\glxtrshort` doesn't support the hyphen switch, the short form just uses the default short-form font command. This style won't work with the regular as the regular form isn't flexible enough. No accessibility attributes need to be set.

```
\newabbreviationstyle{long-hyphen-noshort-desc-noreg}%
{%
\renewcommand*{\CustomAbbreviationFields}{%
  name={\glxtrlongnoshortdescname},
  sort={\glxtrlonghyphennoshortdescsort},
  first={\protect\glsfirstlonghyphenfont{\the\glslongtok}},%
  firstplural={\protect\glsfirstlonghyphenfont{\the\glslongpltok}},%
  text={\protect\glslonghyphenfont{\the\glslongtok}},%
  plural={\protect\glslonghyphenfont{\the\glslongpltok}}}%
}%
}
```

Unset the regular attribute if it has been set.

```
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glshasattribute{\the\glslabeltok}{regular}%
}%
}
```

```

\glsssetAttribute{\the\glslabeltok}{regular}{false}%
}%
{}%
}%
}%
{%

```

In case the user wants to mix and match font styles, these are redefined here.

```

\renewcommand*\abbrvpluralsuffix{\glstrabbrvpluralsuffix}%
\renewcommand*\glsabbrvfont[1]{\glsabbrvdefaultfont{##1}}%
\renewcommand*\glsfirstabbrvfont[1]{\glsfirstabbrvdefaultfont{##1}}%
\renewcommand*\glsfirstlongfont[1]{\glsfirstlonghyphenfont{##1}}%
\renewcommand*\glslongfont[1]{\glslonghyphenfont{##1}}%

```

The inline full form displays the long format followed by the short form in parentheses (as long-hyphen-short-hyphen).

```

\renewcommand*\glstrinlinefullformat[2]{%
\glstrlonghyphenshort{##1}%
{%
\glsifattribute{##1}{markwords}{true}%
{%
\glsaccesslong{##1}%
}%
}%
\glsaccessfmtlong{\glstrgenentrytextfmt}{##1}%
}%
}%
{%
\glsifattribute{##1}{markshortwords}{true}%
{%
\glsaccessshort{##1}%
}%
}%
\glsaccessfmtshort{\glstrgenentrytextfmt}{##1}%
}%
}%
{##2}%
}%
\renewcommand*\glstrinlinefullplformat[2]{%
\glstrlonghyphenshort{##1}%
{%
\glsifattribute{##1}{markwords}{true}%
{%
\glsaccesslongpl{##1}%
}%
}%
\glsaccessfmtlongpl{\glstrgenentrytextfmt}{##1}%
}%
}%
{%
\glsifattribute{##1}{markshortwords}{true}%

```

```

    {%
      \glsaccessshortpl{##1}%
    }%
    {%
      \glsaccessfmtshortpl{}{\glsxtrgenentrytextfmt}{##1}%
    }%
  }%
  {##2}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \glsxtrlonghyphenshort{##1}%
  {%
    \glsifattribute{##1}{markwords}{true}%
    {%
      \Glsaccesslong{##1}%
    }%
    {%
      \Glsaccessfmtlong{}{\glsxtrgenentrytextfmt}{##1}%
    }%
  }%
  {%
    \glsifattribute{##1}{markshortwords}{true}%
    {%
      \glsaccessshort{##1}%
    }%
    {%
      \glsaccessfmtshort{}{\glsxtrgenentrytextfmt}{##1}%
    }%
  }%
  {##2}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \glsxtrlonghyphenshort{##1}%
  {%
    \glsifattribute{##1}{markwords}{true}%
    {%
      \Glsaccesslongpl{##1}%
    }%
    {%
      \Glsaccessfmtlongpl{}{\glsxtrgenentrytextfmt}{##1}%
    }%
  }%
  {%
    \glsifattribute{##1}{markshortwords}{true}%
    {%
      \glsaccessshortpl{##1}%
    }%
    {%
      \glsaccessfmtshortpl{}{\glsxtrgenentrytextfmt}{##1}%
    }%
  }%

```

```

    }%
    {##2}%
}%
\renewcommand*{\GLSxtrinlinefullformat}[2]{%
\GLSxtrlonghyphenshort{##1}%
{%
\glsifattribute{##1}{markwords}{true}%
{%
\GLSaccesslong{##1}%
}%
{%
\GLSaccessfmtlong{}{\glsxtrgenentrytextfmt}{##1}%
}%
}%
{%
\glsifattribute{##1}{markshortwords}{true}%
{%
\GLSaccessshort{##1}%
}%
{%
\GLSaccessfmtshort{}{\glsxtrgenentrytextfmt}{##1}%
}%
}%
{##2}%
}%
\renewcommand*{\GLSxtrinlinefullplformat}[2]{%
\GLSxtrlonghyphenshort{##1}%
{%
\glsifattribute{##1}{markwords}{true}%
{%
\GLSaccesslongpl{##1}%
}%
{%
\GLSaccessfmtlongpl{}{\glsxtrgenentrytextfmt}{##1}%
}%
}%
{%
\glsifattribute{##1}{markshortwords}{true}%
{%
\GLSaccessshortpl{##1}%
}%
{%
\GLSaccessfmtshortpl{}{\glsxtrgenentrytextfmt}{##1}%
}%
}%
{##2}%
}%

```

The first use full form only displays the long form.

```
\renewcommand*{\glsxtrfullformat}[2]{%
```

```

\glxtrlonghyphennoshort{##1}%
{%
  \glusifattribute{##1}{keywords}{true}%
  {%
    \glaccesslong{##1}%
  }%
  {%
    \glaccessfmtlong{}{\glxtrgenentrytextfmt}{##1}%
  }%
}%
{##2}%
}%
\renewcommand*{\glxtrfullplformat}[2]{%
  \glxtrlonghyphennoshort{##1}%
  {%
    \glusifattribute{##1}{keywords}{true}%
    {%
      \glaccesslongpl{##1}%
    }%
    {%
      \glaccessfmtlongpl{}{\glxtrgenentrytextfmt}{##1}%
    }%
  }%
  {##2}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \glxtrlonghyphennoshort{##1}%
  {%
    \glusifattribute{##1}{keywords}{true}%
    {%
      \Glsaccesslong{##1}%
    }%
    {%
      \Glsaccessfmtlong{}{\glxtrgenentrytextfmt}{##1}%
    }%
  }%
  {##2}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \glxtrlonghyphennoshort{##1}%
  {%
    \glusifattribute{##1}{keywords}{true}%
    {%
      \Glsaccesslongpl{##1}%
    }%
    {%
      \Glsaccessfmtlongpl{}{\glxtrgenentrytextfmt}{##1}%
    }%
  }%
  {##2}%
}%

```

```

}%
\renewcommand*{\GLSxtrfullformat}[2]{%
  \GLSxtrlonghyphennoshort{##1}%
  {%
    \glsifattribute{##1}{markwords}{true}%
    {%
      \GLSaccesslong{##1}%
    }%
    {%
      \GLSaccessfmtlong{}{\glsxtrgenentrytextfmt}{##1}%
    }%
  }%
  {##2}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
  \GLSxtrlonghyphennoshort{##1}%
  {%
    \glsifattribute{##1}{markwords}{true}%
    {%
      \GLSaccesslongpl{##1}%
    }%
    {%
      \GLSaccessfmtlongpl{}{\glsxtrgenentrytextfmt}{##1}%
    }%
  }%
  {##2}%
}%

```

The format for subsequent use (not used when the regular attribute is set).

```

\renewcommand*{\glsxtrs subsequentfmt}[2]{%
  \glsxtrlonghyphennoshort{##1}%
  {%
    \glsifattribute{##1}{markwords}{true}%
    {%
      \glsaccesslong{##1}%
    }%
    {%
      \glsaccessfmtlong{}{\glsxtrgenentrytextfmt}{##1}%
    }%
  }%
  {##2}%
}%
\renewcommand*{\glsxtrs subsequentplfmt}[2]{%
  \glsxtrlonghyphennoshort{##1}%
  {%
    \glsifattribute{##1}{markwords}{true}%
    {%
      \glsaccesslongpl{##1}%
    }%
    {%
      \glsaccessfmtlongpl{}{\glsxtrgenentrytextfmt}{##1}%
    }%
  }%
  {##2}%
}%

```

```

        \glsaccessfmtlongpl{}\glsxtrgenentrytextfmt}{##1}%
    }%
}%
{##2}%
}%
\renewcommand*\Glsxtrsubsequentfmt}[2]{%
    \glsxtrlonghyphennoshort{##1}%
    {%
        \glsifattribute{##1}{markwords}{true}%
        {%
            \Glsaccesslong{##1}%
        }%
        {%
            \Glsaccessfmtlong{}\glsxtrgenentrytextfmt}{##1}%
        }%
    }%
}%
{##2}%
}%
\renewcommand*\Glsxtrsubsequentplfmt}[2]{%
    \glsxtrlonghyphennoshort{##1}%
    {%
        \glsifattribute{##1}{markwords}{true}%
        {%
            \Glsaccesslongpl{##1}%
        }%
        {%
            \Glsaccessfmtlongpl{}\glsxtrgenentrytextfmt}{##1}%
        }%
    }%
}%
{##2}%
}%
\renewcommand*\GLSxtrsubsequentfmt}[2]{%
    \GLSxtrlonghyphennoshort{##1}%
    {%
        \glsifattribute{##1}{markwords}{true}%
        {%
            \GLSaccesslong{##1}%
        }%
        {%
            \GLSaccessfmtlong{}\glsxtrgenentrytextfmt}{##1}%
        }%
    }%
}%
{##2}%
}%
\renewcommand*\GLSxtrsubsequentplfmt}[2]{%
    \GLSxtrlonghyphennoshort{##1}%
    {%
        \glsifattribute{##1}{markwords}{true}%
        {%
            \GLSaccesslongpl{##1}%
        }%
    }%
}%

```



```

    }%
    {%
      \GLSaccessfmtlongpl{}\glstrgenentrytextfmt}{##1}%
    }%
  }%
  {##2}%
}%
}

```

`\glstrlonghyphennoshortsort`

```
\newcommand*\glstrlonghyphennoshortsort{\expandonce\glstrorgshort}
```

`long-hyphen-noshort-noreg`

It doesn't really make a great deal of sense to have a long-only style that doesn't have a description (unless no glossary is required), but the best course of action here is to use the short form as the name and the long form as the description.

```

\newabbreviationstyle{long-hyphen-noshort-noreg}%
{%

```

Set accessibility attributes if enabled.

```
\glstrAccSuppAbbrSetNameShortAttrs\glscategorylabel
```

Setup the default fields.

```

\renewcommand*\CustomAbbreviationFields{%
  name={\glstrlongnoshortname},
  sort={\glstrlonghyphennoshortsort},
  first={\protect\glstrfirstlonghyphenfont{\the\glstrlongtok}},%
  firstplural={\protect\glstrfirstlonghyphenfont{\the\glstrlongpltok}},%
  text={\protect\glstrlonghyphenfont{\the\glstrlongtok}},%
  plural={\protect\glstrlonghyphenfont{\the\glstrlongpltok}},%
  description={\the\glstrlongtok}%
}%

```

Unset the regular attribute if it has been set.

```

\renewcommand*\GlsXtrPostNewAbbreviation{%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glissetattribute{\the\glslabeltok}{regular}{false}%
  }%
  {}%
}%
{%

```

```

\GlsXtrUseAbbrStyleFmts{long-hyphen-noshort-desc-noreg}%
}

```

```
\glstrlonghyphen{\langle long \rangle}{\langle label \rangle}{\langle insert \rangle}
```

`\glstrlonghyphen`

Used by `long-hyphen-postshort-hyphen`. The `\langle insert \rangle` is check to determine if it starts with a hyphen but isn't used here as it's moved to the post-link hook.

The `<long>` argument will need to include the inner format.

```
\newcommand*{\glxtrlonghyphen}[3]{%
```

Grouping is needed to localise the redefinitions.

```
{%
  \glxtrifhyphenstart{#3}{\let\glxtrwordsep\glxtrwordsephyphen}{}%
  \glsfirslonghyphenfont{#1}%
}%
}
```

```
\glxtrposthyphenshort{<label>}{<insert>}
```

`\glxtrposthyphenshort`

Used in the post-link hook for the long-hyphen-postshort-hyphen style. Much like `\glxtrlonghyphenshort` but omits the `<long>` part. This always uses the singular short form.

```
\newcommand*{\glxtrposthyphenshort}[2]{%
{%
  \glxtrifhyphenstart{#2}{\let\glxtrwordsep\glxtrwordsephyphen}{}%
  \ifglxtrininsertinside
    {\glsfirslonghyphenfont{\glxtrgenentrytextfmt{#2}}}%
  \else
    {\glxtrgenentrytextfmt{#2}}%
  \fi
  \glxtrfullsep{#1}%
  \glxtrparen
  {%
    \glxtrshortformat{#1}{#2}{\glsfirstabbrvhyphenfont}%
  }%
}%
}
```

`\GLSxtrposthyphenshort` As above but all caps.

```
\newcommand*{\GLSxtrposthyphenshort}[2]{%
{%
  \glxtrifhyphenstart{#2}{\let\glxtrwordsep\glxtrwordsephyphen}{}%
  \ifglxtrininsertinside
    {\glsfirslonghyphenfont{\mfirstucMakeUppercase{\glxtrgenentrytextfmt{#2}}}}%
  \else
    {\mfirstucMakeUppercase{\glxtrgenentrytextfmt{#2}}}%
  \fi
  \glxtrfullsep{#1}%
  \glxtrparen
  {%
    \GLSxtrshortformat{#1}{#2}{\glsfirstabbrvhyphenfont}%
  }%
}%
}
```

`\glsxtrposthyphenshortpl` As above but plural.

```
\newcommand*{\glsxtrposthyphenshortpl}[2]{%
  {%
    \glsxtrifhyphenstart{#2}{\let\glsxtrwordsep\glsxtrwordsephyphen}{}%
    \ifglsxtrininsertinside
      {\glsfirstlonghyphenfont{\glsxtrgenentrytextfmt{#2}}}%
    \else
      {\glsxtrgenentrytextfmt{#2}}%
    \fi
    \glsxtrfullsep{#1}%
    \glsxtrparen
    {%
      \glsxtrshortplformat{#1}{#2}{\glsfirstabbrvhyphenfont}%
    }%
  }%
}
```

`\GLSxtrposthyphenshortpl` As above but all caps.

```
\newcommand*{\GLSxtrposthyphenshortpl}[2]{%
  {%
    \glsxtrifhyphenstart{#2}{\let\glsxtrwordsep\glsxtrwordsephyphen}{}%
    \ifglsxtrininsertinside
      {\glsfirstlonghyphenfont{\mfirstucMakeUppercase{\glsxtrgenentrytextfmt{#2}}}}%
    \else
      {\mfirstucMakeUppercase{\glsxtrgenentrytextfmt{#2}}}%
    \fi
    \glsxtrfullsep{#1}%
    \glsxtrparen
    {%
      \GLSxtrshortplformat{#1}{#2}{\glsfirstabbrvhyphenfont}%
    }%
  }%
}
```

`\xpglsxtrposthyphenshort` Expand placeholders and check for all caps.

```
\newcommand*{\xpglsxtrposthyphenshort}{%
  \glsxtrifallcaps
  {%
    \expandafter\GLSxtrposthyphenshort\expandafter\glslabel
    \expandafter{\glsinsert}%
  }%
  {%
    \expandafter\glsxtrposthyphenshort\expandafter\glslabel
    \expandafter{\glsinsert}%
  }%
}
```

`\glsxtrposthyphensubsequent{<label>}{<insert>}`

`\glsxtrposthyphensubsequent`

Format in the post-link hook for subsequent use. The label is ignored by default. This just does the insert part with appropriate formatting.

```
\newcommand*{\glxtrposthyphensubsequent}[2]{%
  \ifglxtrininsertinside
    \glsabbrvfont{\glxtrgenentrytextfmt{#2}}}%
  \else
    {\glxtrgenentrytextfmt{#2}}%
  \fi
}
```

`\GLSxtrposthyphensubsequent` As above but all caps.

```
\newcommand*{\GLSxtrposthyphensubsequent}[2]{%
  \ifglxtrininsertinside
    \glsabbrvfont{\mfirstucMakeUppercase{\glxtrgenentrytextfmt{#2}}}%
  \else
    {\mfirstucMakeUppercase{\glxtrgenentrytextfmt{#2}}}%
  \fi
}
```

`\pglsxtrposthyphensubsequent` Expand placeholders and check for all caps.

```
\newcommand*{\xpglsxtrposthyphensubsequent}{%
  \glxtrifallcaps
  {%
    \expandafter\GLSxtrposthyphensubsequent\expandafter\glslabel
    \expandafter{\glsinsert}%
  }%
  {%
    \expandafter\glxtrposthyphensubsequent\expandafter\glslabel
    \expandafter{\glsinsert}%
  }%
}
```

```
\glxtrshorthyphennoinsert{<label>}{<short>}{<insert>}
```

`\glxtrshorthyphennoinsert`

As with `\glxtrshorthyphennoinsert` but doesn't actually show the insert.

```
\newcommand*{\glxtrshorthyphennoinsert}[3]{%
```

Grouping is needed to localise the redefinitions.

```
{%
```

If `<insert>` starts with a hyphen, redefine `\glxtrwordsep` to a hyphen.

```
\glxtrifhyphenstart{#3}{\let\glxtrwordsep\glxtrwordsephyphen}{}%
\glsfirstabbrvhyphenfont{#2}%
}%
}
```

`\long-hyphen-postshort-hyphen` Like `long-hyphen-short-hyphen` but shifts the insert and parenthetical material to the post-link hook.

```
\newabbreviationstyle{long-hyphen-postshort-hyphen}%
{%
```

Set accessibility attributes if enabled.

```
\glstrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
```

Setup the default fields.

```
\renewcommand*{\CustomAbbreviationFields}{%
  name={\glstrlongshortname},
  sort={\glstrlonghyphensort},
  first={\protect\glstrfirstlonghyphenfont{\the\glstrlongtok}},%
  firstplural={\protect\glstrfirstlonghyphenfont{\the\glstrlongpltok}},%
  text={\protect\glstrabbrvhyphenfont{\the\glstrshorttok}},%
  plural={\protect\glstrabbrvhyphenfont{\the\glstrshortpltok}},%
  description={\protect\glstrlonghyphenfont{\the\glstrlongtok}}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glsexclapplyinnerfmtfield{\the\glstrlabeltok}{desc}%
  \csdef{glstrpostlink\glscategorylabel}{%
    \glstrifwasfirstuse
    {%
      \xpglstrposthyphenshort
    }%
  }%
```

Put the insertion into the post-link:

```
\xpglstrposthyphensubsequent
}%
}%
\glshasattribute{\the\glstrlabeltok}{regular}%
{%
  \glissetattribute{\the\glstrlabeltok}{regular}{false}%
}%
}%
}%
{%
```

In case the user wants to mix and match font styles, these are redefined here.

```
\renewcommand*{\abbrvpluralsuffix}{\glstrabbrvpluralsuffix}%
\renewcommand*{\glstrabbrvfont}[1]{\glstrabbrvhyphenfont{##1}}%
\renewcommand*{\glstrfirstabbrvfont}[1]{\glstrfirstabbrvhyphenfont{##1}}%
\renewcommand*{\glstrfirstlongfont}[1]{\glstrfirstlonghyphenfont{##1}}%
\renewcommand*{\glstrlongfont}[1]{\glstrlonghyphenfont{##1}}%
```

Subsequent use needs to omit the insertion but it needs to perform the space-hyphen substitution:

```
\renewcommand*{\glstrsubsequentfmt}[2]{%
  \glstrshorthyphennoinsert{##1}%
  {%
    \glstrifattribute{##1}{markshortwords}{true}%
    {%
      \glstraccessshort{##1}%
    }%
  }%
```

```

    }%
    {%
        \glsaccessfmtshort{}\{\glsxtrgenentrytextfmt\}{##1}%
    }%
}%
{##2}%
}%
\renewcommand*\{\glsxtrsubsequentplfmt}[2]{%
    \glsxtrshorthyphennoinsert{##1}%
    {%
        \glsifattribute{##1}{markshortwords}{true}%
        {%
            \glsaccessshortpl{##1}%
        }%
        {%
            \glsaccessfmtshortpl{}\{\glsxtrgenentrytextfmt\}{##1}%
        }%
    }%
    {##2}%
}%
\renewcommand*\{\Glsxtrsubsequentfmt}[2]{%
    \glsxtrshorthyphennoinsert{##1}%
    {%
        \glsifattribute{##1}{markshortwords}{true}%
        {%
            \Glsaccessshort{##1}%
        }%
        {%
            \Glsaccessfmtshort{}\{\glsxtrgenentrytextfmt\}{##1}%
        }%
    }%
    {##2}%
}%
\renewcommand*\{\Glsxtrsubsequentplfmt}[2]{%
    \glsxtrshorthyphennoinsert{##1}%
    {%
        \glsifattribute{##1}{markshortwords}{true}%
        {%
            \Glsaccessshortpl{##1}%
        }%
        {%
            \Glsaccessfmtshortpl{}\{\glsxtrgenentrytextfmt\}{##1}%
        }%
    }%
    {##2}%
}%
\renewcommand*\{\GLSxtrsubsequentfmt}[2]{%
    \glsxtrshorthyphennoinsert{##1}%
    {%
        \glsifattribute{##1}{markshortwords}{true}%

```

```

    {%
      \GLSaccessshort{##1}%
    }%
    {%
      \GLSaccessfmtshort{}{\glstrgenentrytextfmt}{##1}%
    }%
  }%
  {##2}%
}%
\renewcommand*{\GLSxtrsubsequentplfmt}[2]{%
  \glstrshortthyphennoinsert{##1}%
  {%
    \glrifattribute{##1}{markshortwords}{true}%
    {%
      \GLSaccessshortpl{##1}%
    }%
    {%
      \GLSaccessfmtshortpl{}{\glstrgenentrytextfmt}{##1}%
    }%
  }%
  {##2}%
}%

```

First use full form:

```

\renewcommand*{\glstrfullformat}[2]{%
  \glstrlonghyphen
  {%
    \glrifattribute{##1}{markwords}{true}%
    {%
      \glaccesslong{##1}%
    }%
    {%
      \glaccessfmtlong{}{\glstrgenentrytextfmt}{##1}%
    }%
  }%
  {##1}{##2}%
}%
\renewcommand*{\glstrfullplformat}[2]{%
  \glstrlonghyphen
  {%
    \glrifattribute{##1}{markwords}{true}%
    {%
      \glaccesslongpl{##1}%
    }%
    {%
      \glaccessfmtlongpl{}{\glstrgenentrytextfmt}{##1}%
    }%
  }%
  {##1}{##2}%
}%

```

```

\renewcommand*{\Glsxtrfullformat}[2]{%
  \glsxtrlonghyphen
  {%
    \glsifattribute{##1}{keywords}{true}%
    {%
      \Glsaccesslong{##1}%
    }%
    {%
      \Glsaccessfmtlong{}{\glsxtrgenentrytextfmt}{##1}%
    }%
  }%
  {##1}{##2}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \glsxtrlonghyphen
  {%
    \glsifattribute{##1}{keywords}{true}%
    {%
      \Glsaccesslongpl{##1}%
    }%
    {%
      \Glsaccessfmtlongpl{}{\glsxtrgenentrytextfmt}{##1}%
    }%
  }%
  {##1}{##2}%
}%
\renewcommand*{\GLSxtrfullformat}[2]{%
  \glsxtrlonghyphen
  {%
    \glsifattribute{##1}{keywords}{true}%
    {%
      \GLSaccesslong{##1}%
    }%
    {%
      \GLSaccessfmtlong{}{\glsxtrgenentrytextfmt}{##1}%
    }%
  }%
  {##1}{##2}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
  \glsxtrlonghyphen
  {%
    \glsifattribute{##1}{keywords}{true}%
    {%
      \GLSaccesslongpl{##1}%
    }%
    {%
      \GLSaccessfmtlongpl{}{\glsxtrgenentrytextfmt}{##1}%
    }%
  }%
  {##1}{##2}%
}%

```



```

    {##1}{##2}%
}%

```

In-line format.

```

\renewcommand*{\glxstrinlinefullformat}[2]{%
  \glxstrlongformatgrp{##1}{##2}{\glsfirstlonghyphenfont}%
}%
\renewcommand*{\glxstrinlinefullplformat}[2]{%
  \glxstrlongplformatgrp{##1}{##2}{\glsfirstlonghyphenfont}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \Glsxtrlongformatgrp{##1}{##2}{\glsfirstlonghyphenfont}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \Glsxtrlongplformatgrp{##1}{##2}{\glsfirstlonghyphenfont}%
}%
\renewcommand*{\GLSxtrinlinefullformat}[2]{%
  \GLSxtrlongformatgrp{##1}{##2}{\glsfirstlonghyphenfont}%
}%
\renewcommand*{\GLSxtrinlinefullplformat}[2]{%
  \GLSxtrlongplformatgrp{##1}{##2}{\glsfirstlonghyphenfont}%
}%
}

```

`hyphen-postshort-hyphen-desc` Like long-hyphen-postshort-hyphen but the description must be supplied by the user.

```

\newabbreviationstyle{long-hyphen-postshort-hyphen-desc}%
{%

```

Set accessibility attributes if enabled.

```

\glxstrAccSuppAbbrSetTextShortAttrs\glscategorylabel

```

Setup the default fields.

```

\renewcommand*{\CustomAbbreviationFields}{%
  name={\glxstrlongshortdescname},
  sort={\glxstrlongshortdescsort},%
  first={\protect\glsfirstlonghyphenfont{\the\glslongtok}},%
  firstplural={\protect\glsfirstlonghyphenfont{\the\glslongpltok}},%
  text={\protect\glsabbrvhyphenfont{\the\glsshorttok}},%
  plural={\protect\glsabbrvhyphenfont{\the\glsshortpltok}}%
}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \csdef{glxstrpostlink\glscategorylabel}{%
    \glxstrifwasfirstuse
    {%
      \xpglsxtrposthyphenshort
    }%
    {%

```

Put the insertion into the post-link:

```

    \xpglsxtrposthyphensubsequent

```

```

    }%
  }%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glssetattribute{\the\glslabeltok}{regular}{false}%
  }%
  {}%
}%
}%
{%
  \GlsXtrUseAbbrStyleFmts{long-hyphen-postshort-hyphen}%
}

```

```
\glsxtrshorthyphenlong{<label>}{<short>}{<long>}{<insert>}
```

\glsxtrshorthyphenlong

The *<long>* and *<short>* arguments may be the plural form. The *<long>* argument may also be the first letter uppercase form.

As with `\glsxtrlonghyphenshort` this doesn't fit in with the new `\glsxtrshortformat` so the inserted part has to have a separate encapsulation for the inner format. The *<long>* argument will need to include the inner format.

```
\newcommand*{\glsxtrshorthyphenlong}[4]{%
```

Grouping is needed to localise the redefinitions.

```
{%
```

If *<insert>* starts with a hyphen, redefine `\glsxtrwordsep` to a hyphen. The inserted material is also inserted into the parenthetical part. (The inserted material is grouped as a precautionary measure.)

```

  \glsxtrifhyphenstart{#4}{\let\glsxtrwordsep\glsxtrwordsephyphen}{}%
  \glsfirstabbrvhyphenfont{#2\ifglsxtrininsertinside
    {\glsxtrgenentrytextfmt{#4}}\fi}%
  \ifglsxtrininsertinside\else\glsxtrgenentrytextfmt{#4}}\fi
  \glsxtrfullsep{#1}%
  \glsxtrparen{\glsfirstlonghyphenfont{#3%
    \ifglsxtrininsertinside{\glsxtrgenentrytextfmt{#4}}\fi}%
    \ifglsxtrininsertinside\else{\glsxtrgenentrytextfmt{#4}}\fi}%
  }%
}

```

\GLSxtrshorthyphenlong As above but convert insert to all-caps. The long and short form arguments should be provided as all-caps.

```

\newcommand*{\GLSxtrshorthyphenlong}[4]{%
  {%
    \glsxtrifhyphenstart{#4}{\let\glsxtrwordsep\glsxtrwordsephyphen}{}%
    \glsfirstabbrvhyphenfont{#2\ifglsxtrininsertinside
      {\mfirstucMakeUppercase{\glsxtrgenentrytextfmt{#4}}}\fi}%
    \ifglsxtrininsertinside\else
      {\mfirstucMakeUppercase{\glsxtrgenentrytextfmt{#4}}}%

```

```

\fi
\glxtrfullsep{#1}%
\glxtrparen{\glsfirstlonghyphenfont{#3%
  \ifglxtrinsertinside{\mfirstucMakeUppercase{\glxtrgenentrytextfmt{#4}}}\fi}%
  \ifglxtrinsertinside\else
    {\mfirstucMakeUppercase{\glxtrgenentrytextfmt{#4}}}%
  \fi}%
}%
}

```

`\glxtrshorthyphenlongsort`

```
\newcommand*{\glxtrshorthyphenlongsort}{\expandonce\glxtrorgshort}
```

`short-hyphen-long-hyphen` Designed for use with the `markwords` attribute.

```

\newabbreviationstyle{short-hyphen-long-hyphen}%
{%

```

Set accessibility attributes if enabled.

```
\glxtrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
```

Setup the default fields.

```

\renewcommand*{\CustomAbbreviationFields}{%
  name={\glxtrshortlongname},
  sort={\glxtrshorthyphenlongsort},
  first={\protect\glsfirstabbrvhyphenfont{\the\glsshorttok}%
    \protect\glxtrfullsep{\the\glslabeltok}%
    \protect\glxtrparen{\protect\glsfirstlonghyphenfont{\the\glslongtok}}},%
  firstplural={\protect\glsfirstabbrvhyphenfont{\the\glsshortpltok}%
    \protect\glxtrfullsep{\the\glslabeltok}%
    \protect\glxtrparen{\protect\glsfirstlonghyphenfont{\the\glslongpltok}}},%
  text={\protect\glsabbrvhyphenfont{\the\glsshorttok}},%
  plural={\protect\glsabbrvhyphenfont{\the\glsshortpltok}},%
  description={\protect\glslonghyphenfont{\the\glslongtok}}}

```

Unset the regular attribute if it has been set.

```

\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glsexclapplyinnerfmtfield{\the\glslabeltok}{desc}%
  \glxtrsetcomplexstyle{\the\glslabeltok}{3}%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glissetattribute{\the\glslabeltok}{regular}{false}%
  }%
  {}%
}%

```

```

}%
{%
\renewcommand*{\abbrvpluralsuffix}{\glxtrhyphensuffix}%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvhyphenfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvhyphenfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlonghyphenfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslonghyphenfont{##1}}%

```

The first use full form and the inline full form are the same for this style.

```

\renewcommand*{\glstrfullformat}[2]{%
  \glstrshorthyphenlong{##1}%
  {%
    \glrifattribute{##1}{markshortwords}{true}%
    {%
      \glaccessshort{##1}%
    }%
    {%
      \glaccessfmtshort{}{\glstrgenentrytextfmt}{##1}%
    }%
  }%
  {%
    \glrifattribute{##1}{markwords}{true}%
    {%
      \glaccesslong{##1}%
    }%
    {%
      \glaccessfmtlong{}{\glstrgenentrytextfmt}{##1}%
    }%
  }%
  {##2}%
}%
\renewcommand*{\glstrfullplformat}[2]{%
  \glstrshorthyphenlong{##1}%
  {%
    \glrifattribute{##1}{markshortwords}{true}%
    {%
      \glaccessshortpl{##1}%
    }%
    {%
      \glaccessfmtshortpl{}{\glstrgenentrytextfmt}{##1}%
    }%
  }%
  {%
    \glrifattribute{##1}{marklongwords}{true}%
    {%
      \glaccesslongpl{##1}%
    }%
    {%
      \glaccessfmtlongpl{}{\glstrgenentrytextfmt}{##1}%
    }%
  }%
  {##2}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \glstrshorthyphenlong{##1}%
  {%
    \glrifattribute{##1}{markshortwords}{true}%

```

```

    {%
      \Glsaccessshort{##1}%
    }%
    {%
      \Glsaccessfmtshort{}\{\glstrgenentrytextfmt\}{##1}%
    }%
  }%
  {%
    \glrifattribute{##1}{markwords}{true}%
    {%
      \Glsaccesslong{##1}%
    }%
    {%
      \Glsaccessfmtlong{}\{\glstrgenentrytextfmt\}{##1}%
    }%
  }%
  {##2}%
}%
\renewcommand*\{\Glsxtrfullplformat}[2]{%
  \glstrshorthyphenlong{##1}%
  {%
    \glrifattribute{##1}{markshortwords}{true}%
    {%
      \Glsaccessshortpl{##1}%
    }%
    {%
      \Glsaccessfmtshortpl{}\{\glstrgenentrytextfmt\}{##1}%
    }%
  }%
  {%
    \glrifattribute{##1}{markwords}{true}%
    {%
      \Glsaccesslongpl{##1}%
    }%
    {%
      \Glsaccessfmtlongpl{}\{\glstrgenentrytextfmt\}{##1}%
    }%
  }%
  {##2}%
}%
\renewcommand*\{\GLSxtrfullformat}[2]{%
  \GLSxtrshorthyphenlong{##1}%
  {%
    \glrifattribute{##1}{markshortwords}{true}%
    {%
      \GLSaccessshort{##1}%
    }%
    {%
      \GLSaccessfmtshort{}\{\glstrgenentrytextfmt\}{##1}%
    }%
  }%

```

```

}%
{%
  \glsifattribute{##1}{markwords}{true}%
  {%
    \GLSaccesslong{##1}%
  }%
  {%
    \GLSaccessfmtlong{}{\glsxtrgenentrytextfmt}{##1}%
  }%
}%
{##2}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
  \GLSxtrshorthyphenlong{##1}%
  {%
    \glsifattribute{##1}{markshortwords}{true}%
    {%
      \GLSaccessshortpl{##1}%
    }%
    {%
      \GLSaccessfmtshortpl{}{\glsxtrgenentrytextfmt}{##1}%
    }%
  }%
  {%
    \glsifattribute{##1}{markwords}{true}%
    {%
      \GLSaccesslongpl{##1}%
    }%
    {%
      \GLSaccessfmtlongpl{}{\glsxtrgenentrytextfmt}{##1}%
    }%
  }%
  {##2}%
}%

```

Subsequent form also needs checking for a hyphen in case the short form has spaces.

```

\renewcommand*{\glsxtrsubsequentfmt}[2]{%
  \glsxtrshorthyphennolong{##1}%
  {%
    \glsifattribute{##1}{markshortwords}{true}%
    {%
      \glsaccessshort{##1}%
    }%
    {%
      \glsaccessfmtshort{}{\glsxtrgenentrytextfmt}{##1}%
    }%
  }%
  {##2}%
}%

```

```

\renewcommand*{\glxtrsubsequentplfmt}[2]{%
  \glxtrshorthyphennolong{##1}%
  {%
    \glusifattribute{##1}{markshortwords}{true}%
    {%
      \glsaccessshortpl{##1}%
    }%
    {%
      \glsaccessfmtshortpl{}{\glxtrgenentrytextfmt}{##1}%
    }%
  }%
  {##2}%
}%
\renewcommand*{\Glsxtrsubsequentfmt}[2]{%
  \glxtrshorthyphennolong{##1}%
  {%
    \glusifattribute{##1}{markshortwords}{true}%
    {%
      \Glsaccessshort{##1}%
    }%
    {%
      \Glsaccessfmtshort{}{\glxtrgenentrytextfmt}{##1}%
    }%
  }%
  {##2}%
}%
\renewcommand*{\Glsxtrsubsequentplfmt}[2]{%
  \glxtrshorthyphennolong{##1}%
  {%
    \glusifattribute{##1}{markshortwords}{true}%
    {%
      \Glsaccessshortpl{##1}%
    }%
    {%
      \Glsaccessfmtshortpl{}{\glxtrgenentrytextfmt}{##1}%
    }%
  }%
  {##2}%
}%
\renewcommand*{\GLSxtrsubsequentfmt}[2]{%
  \GLSxtrshorthyphennolong{##1}%
  {%
    \glusifattribute{##1}{markshortwords}{true}%
    {%
      \GLSaccessshort{##1}%
    }%
    {%
      \GLSaccessfmtshort{}{\glxtrgenentrytextfmt}{##1}%
    }%
  }%
  {##2}%
}%

```

```

    {##2}%
  }%
\renewcommand*{\GLSxtrsubsequentplfmt}[2]{%
  \GLSxtrshorthyphennolong{##1}%
  {%
    \gl@ifattribute{##1}{markshortwords}{true}%
    {%
      \GLSaccessshortpl{##1}%
    }%
    {%
      \GLSaccessfmtshortpl{}{\glxtrgenentrytextfmt}{##1}%
    }%
  }%
  {##2}%
}%
}

```

short-hyphen-long-hyphen-desc Like short-hyphen-long-hyphen but the description must be supplied by the user.

```

\newabbreviationstyle{short-hyphen-long-hyphen-desc}%
{%

```

Set accessibility attributes if enabled.

```

\glxtrAccSuppAbbrSetTextShortAttrs\glscategorylabel

```

Setup the default fields.

```

\renewcommand*{\CustomAbbreviationFields}{%
  name={\glxtrshortlongdescname},
  sort={\glxtrshortlongdescsort},
  first={\protect\glsfirstabbrvhyphenfont{\the\glsshorttok}%
    \protect\glxtrfullsep{\the\glslabeltok}%
    \protect\glxtrparen{\protect\glsfirstlonghyphenfont{\the\glslongtok}}},%
  firstplural={\protect\glsfirstabbrvhyphenfont{\the\glsshortpltok}%
    \protect\glxtrfullsep{\the\glslabeltok}%
    \protect\glxtrparen{\protect\glsfirstlonghyphenfont{\the\glslongpltok}}},%
  text={\protect\glsabbrvhyphenfont{\the\glsshorttok}},%
  plural={\protect\glsabbrvhyphenfont{\the\glsshortpltok}}%
}%

```

Unset the regular attribute if it has been set.

```

\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glxtrsetcomplexstyle{\the\glslabeltok}{3}%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glissetattribute{\the\glslabeltok}{regular}{false}%
  }%
  {}%
}%
}%
\GlsXtrUseAbbrStyleFmts{short-hyphen-long-hyphen}%
}

```


`\glxtrshorthyphen`

```
\glxtrshorthyphen{<short>}{<label>}{<insert>}
```

Used by short-hyphen-postlong-hyphen. The *<insert>* is checked to determine if it starts with a hyphen but isn't used here as it's moved to the post-link hook.

```
\newcommand*{\glxtrshorthyphen}[3]{%
```

Grouping is needed to localise the redefinitions.

```
{%
  \glxtrifhyphenstart{#3}{\let\glxtrwordsep\glxtrwordsephyphen}{}%
  \glsfirstabbrvhyphenfont{#1}%
}%
}
```

`\glxtrposthyphenlong`

```
\glxtrposthyphenlong{<label>}{<insert>}
```

Used in the post-link hook for the short-hyphen-postlong-hyphen style. Much like `\glxtrshorthyphenlong` but omits the *<short>* part. This always uses the singular long form.

```
\newcommand*{\glxtrposthyphenlong}[2]{%
{%
  \glxtrifhyphenstart{#2}{\let\glxtrwordsep\glxtrwordsephyphen}{}%
  \ifglxtrininsertinside
    {\glsfirstabbrvhyphenfont{\glxtrgenentrytextfmt{#2}}}%
  \else
    {\glxtrgenentrytextfmt{#2}}%
  \fi
  \glxtrfullsep{#1}%
  \glxtrparen
    {\glxtrlongformatgrp{#1}{#2}{\glsfirstlonghyphenfont}}%
}%
}
```

`\GLSxtrposthyphenlong` As above but all-caps.

```
\newcommand*{\GLSxtrposthyphenlong}[2]{%
{%
  \glxtrifhyphenstart{#2}{\let\glxtrwordsep\glxtrwordsephyphen}{}%
  \ifglxtrininsertinside
    {\glsfirstabbrvhyphenfont{\mfirstucMakeUppercase{\glxtrgenentrytextfmt{#2}}}}%
  \else
    {\mfirstucMakeUppercase{\glxtrgenentrytextfmt{#2}}}%
  \fi
  \glxtrfullsep{#1}%
  \GLSxtrparen
    {\GLSxtrlongformatgrp{#1}{#2}{\glsfirstlonghyphenfont}}%
}%
}
```

Plural versions in case they are required.

`\glxstrposthyphenlongpl`

```
\newcommand*{\glxstrposthyphenlongpl}[2]{%
  {%
    \glxstrifhyphenstart{#2}{\let\glxstrwordsep\glxstrwordsephyphen}{}%
    \ifglxstrinsertinside
      {\glsfirstabbrvhyphenfont{\glxstrgenentrytextfmt{#2}}}%
    \else
      {\glxstrgenentrytextfmt{#2}}%
    \fi
    \glxstrfullsep{#1}%
    \glxstrparen
      {\glxstrlongplformatgrp{#1}{#2}{\glsfirstlonghyphenfont}}%
  }%
}
```

`\GLSxtrposthyphenlongpl` As above but all-caps.

```
\newcommand*{\GLSxtrposthyphenlongpl}[2]{%
  {%
    \glxstrifhyphenstart{#2}{\let\glxstrwordsep\glxstrwordsephyphen}{}%
    \ifglxstrinsertinside
      {\glsfirstabbrvhyphenfont{\mfirstucMakeUppercase{\glxstrgenentrytextfmt{#2}}}}%
    \else
      {\mfirstucMakeUppercase{\glxstrgenentrytextfmt{#2}}}%
    \fi
    \glxstrfullsep{#1}%
    \glxstrparen
      {\GLSxtrlongplformatgrp{#1}{#2}{\glsfirstlonghyphenfont}}%
  }%
}
```

`\xpglxstrposthyphenlong` Expand placeholders and check for all caps.

```
\newcommand*{\xpglxstrposthyphenlong}{%
  \glxstrifallcaps
  {%
    \expandafter\GLSxtrposthyphenlong\expandafter\glslabel
      \expandafter{\glsininsert}%
  }%
  {%
    \expandafter\glxstrposthyphenlong\expandafter\glslabel
      \expandafter{\glsininsert}%
  }%
}
```

`short-hyphen-postlong-hyphen` Like short-hyphen-long-hyphen but shifts the insert and parenthetical material to the post-link hook.

```
\newabbreviationstyle{short-hyphen-postlong-hyphen}%
{%
```

Set accessibility attributes if enabled.

```
\glstrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
```

Setup the default fields.

```
\renewcommand*{\CustomAbbreviationFields}{%
  name={\glstrshortlongname},
  sort={\glstrshorthyphenlongsort},
  first={\protect\glfirstabbrvhyphenfont{\the\glsshorttok}},%
  firstplural={\protect\glfirstabbrvhyphenfont{\the\glsshortpltok}},%
  text={\protect\glabbrvhyphenfont{\the\glsshorttok}},%
  plural={\protect\glabbrvhyphenfont{\the\glsshortpltok}},%
  description={\protect\glslonghyphenfont{\the\glslongtok}}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glsexclapplyinnerfmtfield{\the\glslabeltok}{desc}%
  \csdef{glstrpostlink\glscategorylabel}{%
    \glstrifwasfirstuse
    {%
      \xpglstrposthyphenlong
    }%
  }%
```

Put the insertion into the post-link:

```
    \xpglstrposthyphensubsequent
  }%
}%
\glshasattribute{\the\glslabeltok}{regular}%
{%
  \glissetattribute{\the\glslabeltok}{regular}{false}%
}%
{}%
}%
}%
{%
```

In case the user wants to mix and match font styles, these are redefined here.

```
\renewcommand*{\abbrvpluralsuffix}{\glstrabbrvpluralsuffix}%
\renewcommand*{\glabbrvfont}[1]{\glabbrvhyphenfont{##1}}%
\renewcommand*{\glfirstabbrvfont}[1]{\glfirstabbrvhyphenfont{##1}}%
\renewcommand*{\glfirstlongfont}[1]{\glfirstlonghyphenfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslonghyphenfont{##1}}%
```

Subsequent use needs to omit the insertion but it needs to perform the space-hyphen substitution:

```
\renewcommand*{\glstrsubsequentfmt}[2]{%
  \glstrshorthyphennoinsert{##1}%
  {%
    \glusifattribute{##1}{markshortwords}{true}%
    {%
      \glaccessshort{##1}%
    }%
  }%
```

```

        \glsaccessfmtshort{}\glsxtrgenentrytextfmt}{##1}%
    }%
}%
{##2}%
}%
\renewcommand*\glsxtrsubsequentplfmt}[2]{%
    \glsxtrshorthyphennoinsert{##1}%
    {%
        \glsifattribute{##1}{markshortwords}{true}%
        {%
            \glsaccessshortpl{##1}%
        }%
        {%
            \glsaccessfmtshortpl{}\glsxtrgenentrytextfmt}{##1}%
        }%
    }%
}%
{##2}%
}%
\renewcommand*\Glsxtrsubsequentfmt}[2]{%
    \glsxtrshorthyphennoinsert{##1}%
    {%
        \glsifattribute{##1}{markshortwords}{true}%
        {%
            \Glsaccessshort{##1}%
        }%
        {%
            \Glsaccessfmtshort{}\glsxtrgenentrytextfmt}{##1}%
        }%
    }%
}%
{##2}%
}%
\renewcommand*\Glsxtrsubsequentplfmt}[2]{%
    \glsxtrshorthyphennoinsert{##1}%
    {%
        \glsifattribute{##1}{markshortwords}{true}%
        {%
            \Glsaccessshortpl{##1}%
        }%
        {%
            \Glsaccessfmtshortpl{}\glsxtrgenentrytextfmt}{##1}%
        }%
    }%
}%
{##2}%
}%
\renewcommand*\GLSxtrsubsequentfmt}[2]{%
    \glsxtrshorthyphennoinsert{##1}%
    {%
        \glsifattribute{##1}{markshortwords}{true}%
        {%
            \GLSaccessshort{##1}%
        }%
    }%
}%

```

```

    }%
    {%
        \GLSaccessfmtshort{}\glstrgenentrytextfmt}{##1}%
    }%
}%
{##2}%
}%
\renewcommand*\GLSxtrsubsequentplfmt}[2]{%
    \glstrshorthyphennoinsert{##1}%
    {%
        \glrifattribute{##1}{markshortwords}{true}%
        {%
            \GLSaccessshortpl{##1}%
        }%
        {%
            \GLSaccessfmtshortpl{}\glstrgenentrytextfmt}{##1}%
        }%
    }%
    {##2}%
}%

```

First use full form:

```

\renewcommand*\glstrfullformat}[2]{%
    \glstrshorthyphen
    {%
        \glrifattribute{##1}{markshortwords}{true}%
        {%
            \glaccessshort{##1}%
        }%
        {%
            \glaccessfmtshort{}\glstrgenentrytextfmt}{##1}%
        }%
    }%
    {##1}{##2}%
}%
\renewcommand*\glstrfullplformat}[2]{%
    \glstrshorthyphen
    {%
        \glrifattribute{##1}{markshortwords}{true}%
        {%
            \glaccessshortpl{##1}%
        }%
        {%
            \glaccessfmtshortpl{}\glstrgenentrytextfmt}{##1}%
        }%
    }%
    {##1}{##2}%
}%
\renewcommand*\Glsxtrfullformat}[2]{%
    \glstrshorthyphen

```

```

{%
  \glsifattribute{##1}{markshortwords}{true}%
  {%
    \Glsaccessshort{##1}%
  }%
  {%
    \Glsaccessfmtshort{}{\glsxtrgenentrytextfmt}{##1}%
  }%
}%
{##1}{##2}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \glsxtrshorthyphen
  {%
    \glsifattribute{##1}{markshortwords}{true}%
    {%
      \Glsaccessshortpl{##1}%
    }%
    {%
      \Glsaccessfmtshortpl{}{\glsxtrgenentrytextfmt}{##1}%
    }%
  }{##1}{##2}%
}%
\renewcommand*{\GLSxtrfullformat}[2]{%
  \glsxtrshorthyphen
  {%
    \glsifattribute{##1}{markshortwords}{true}%
    {%
      \GLSaccessshort{##1}%
    }%
    {%
      \GLSaccessfmtshort{}{\glsxtrgenentrytextfmt}{##1}%
    }%
  }{##1}{##2}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
  \glsxtrshorthyphen
  {%
    \glsifattribute{##1}{markshortwords}{true}%
    {%
      \GLSaccessshortpl{##1}%
    }%
    {%
      \GLSaccessfmtshortpl{}{\glsxtrgenentrytextfmt}{##1}%
    }%
  }{##1}{##2}%
}%

```

In-line format. Commands like `\glsxtrfull` set `\glsinsert` to empty.

The entire link-text (provided by the following commands) is stored in `\glscustomtext`. Note that unless the insert is saved, it won't appear in the post-link hook.

```
\renewcommand*\glsxtrinlinefullformat}[2]{%
  \glsxtrshortformatgrp{##1}{##2}{\glsfirstabbrvhyphenfont}%
}%
\renewcommand*\glsxtrinlinefullplformat}[2]{%
  \glsxtrshorttplformatgrp{##1}{##2}{\glsfirstabbrvhyphenfont}%
}%
\renewcommand*\Glsxtrinlinefullformat}[2]{%
  \Glsxtrshortformatgrp{##1}{##2}{\glsfirstabbrvhyphenfont}%
}%
\renewcommand*\Glsxtrinlinefullplformat}[2]{%
  \Glsxtrshorttplformatgrp{##1}{##2}{\glsfirstabbrvhyphenfont}%
}%
\renewcommand*\GLSxtrinlinefullformat}[2]{%
  \GLSxtrshortformatgrp{##1}{##2}{\glsfirstabbrvhyphenfont}%
}%
\renewcommand*\GLSxtrinlinefullplformat}[2]{%
  \GLSxtrshorttplformatgrp{##1}{##2}{\glsfirstabbrvhyphenfont}%
}%
}
```

`hyphen-postlong-hyphen-desc` Like `short-hyphen-postlong-hyphen` but the description must be supplied by the user.

```
\newabbreviationstyle{short-hyphen-postlong-hyphen-desc}%
{%
```

Set accessibility attributes if enabled.

```
\glsxtrAccSuppAbbrSetTextShortAttrs\glscategorylabel
```

Setup the default fields.

```
\renewcommand*\CustomAbbreviationFields{%
  name={\glsxtrshortlongdescname},
  sort={\glsxtrshortlongdescsort},%
  first={\protect\glsfirstabbrvhyphenfont{\the\glsshorttok}},%
  firstplural={\protect\glsfirstabbrvhyphenfont{\the\glsshortpltok}},%
  text={\protect\glsabbrvhyphenfont{\the\glsshorttok}},%
  plural={\protect\glsabbrvhyphenfont{\the\glsshortpltok}}}%
\renewcommand*\GlsXtrPostNewAbbreviation{%
  \csdef{glsxtrpostlink\glscategorylabel}{%
    \glsxtrifwasfirstuse
    {%
      \xpglsxtrposthyphenlong
    }%
  }%
```

Put the insertion into the post-link:

```
\xpglsxtrposthyphensubsequent
```

```

    }%
  }%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glissetattribute{\the\glslabeltok}{regular}{false}%
  }%
  {}%
}%
}%
{%
  \GlsXtrUseAbbrStyleFmts{short-hyphen-postlong-hyphen}%
}

```

2.7 Predefined Styles (No Short on First Use)

These styles show only the long form on first use and only the short form on subsequent use.

```

\glsabbrvonlyfont
    \newcommand*{\glsabbrvonlyfont}{\glsabbrvdefaultfont}%

\glsfirstabbrvonlyfont
    \newcommand*{\glsfirstabbrvonlyfont}{\glsabbrvonlyfont}%

\glslongonlyfont
    \newcommand*{\glslongonlyfont}{\glslongdefaultfont}%

\glsfirstlongonlyfont
    \newcommand*{\glsfirstlongonlyfont}{\glslongonlyfont}%

```

The default short form suffix:

```

\glxtronlysuffix
    \newcommand*{\glxtronlysuffix}{\glxtrabbrvppluralsuffix}

\glxtronlyname The default name format for this style.
    \newcommand*{\glxtronlyname}{%
      \protect\glsabbrvonlyfont{\the\glsshorttok}%
    }

```

```

long-only-short-only
    \newabbreviationstyle{long-only-short-only}%
    {%
      Set accessibility attributes if enabled.
      \glxtrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
    }

```


Setup the default fields.

```
\renewcommand*{\CustomAbbreviationFields}{%
  name={\glstronlyname},
  sort={\the\glsshorttok},
  first={\glstxplongfont{\the\glslongtok}{\glscategorylabel}},%
  firstplural={\glstxplongfont{\the\glslongpltok}{\glscategorylabel}},%
  text={\glxpabbrvfont{\the\glsshorttok}{\glscategorylabel}},%
  plural={\glxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}},%
  description={\protect\glslongonlyfont{\the\glslongtok}}}%
```

Unset the regular attribute if it has been set.

```
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glsexclapplyinnerfmtfield{\the\glslabeltok}{desc}%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glissetattribute{\the\glslabeltok}{regular}{false}%
  }%
  {}%
}%
}%
{%

\renewcommand*{\abrvpluralsuffix}{\glstronlysuffix}%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvonlyfont{##1}}%
\renewcommand*{\glstxplongfont}[1]{\glstxplongonlyfont{##1}}%
\renewcommand*{\glstxlongfont}[1]{\glstxlongonlyfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongonlyfont{##1}}%
```

The first use full form doesn't show the short form.

```
\renewcommand*{\glstrfullformat}[2]{%
  \glstrlongformat{##1}{##2}{\glstxlongonlyfont}%
}%
\renewcommand*{\glstrfullplformat}[2]{%
  \glstrlongplformat{##1}{##2}{\glstxlongonlyfont}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \Glsxtrlongformat{##1}{##2}{\glstxlongonlyfont}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \Glsxtrlongplformat{##1}{##2}{\glstxlongonlyfont}%
}%
\renewcommand*{\GLSxtrfullformat}[2]{%
  \GLSxtrlongformat{##1}{##2}{\glstxlongonlyfont}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
  \GLSxtrlongplformat{##1}{##2}{\glstxlongonlyfont}%
}%
```

The inline full form does show the short form.

```
\renewcommand*{\glstrinlinefullformat}[2]{%
  \glstrlongshortformat{##1}{##2}%
```

```

        {\glsfirstlongonlyfont}{\glsfirstabbrvonlyfont}%
    }%
    \renewcommand*{\glxstrinlinefullplformat}[2]{%
        \glxstrlongshortplformat{##1}{##2}%
        {\glsfirstlongonlyfont}{\glsfirstabbrvonlyfont}%
    }%
    \renewcommand*{\Glsxtrinlinefullformat}[2]{%
        \Glsxtrlongshortformat{##1}{##2}%
        {\glsfirstlongonlyfont}{\glsfirstabbrvonlyfont}%
    }%
    \renewcommand*{\Glsxtrinlinefullplformat}[2]{%
        \Glsxtrlongshortplformat{##1}{##2}%
        {\glsfirstlongonlyfont}{\glsfirstabbrvonlyfont}%
    }%
    \renewcommand*{\GLSxtrinlinefullformat}[2]{%
        \GLSxtrlongshortformat{##1}{##2}%
        {\glsfirstlongonlyfont}{\glsfirstabbrvonlyfont}%
    }%
    \renewcommand*{\GLSxtrinlinefullplformat}[2]{%
        \GLSxtrlongshortplformat{##1}{##2}%
        {\glsfirstlongonlyfont}{\glsfirstabbrvonlyfont}%
    }%
}

```

`\glxstronlydescsort`

```
\newcommand*{\glxstronlydescsort}{\the\glslongtok}
```

`\glxstronlydescname`

```

\newcommand*{\glxstronlydescname}{%
    \protect\glslongfont{\the\glslongtok}%
}

```

`long-only-short-only-desc`

```

\newabbreviationstyle{long-only-short-only-desc}%
{%

```

Set accessibility attributes if enabled.

```
\glxstrAccSuppAbbrSetTextShortAttrs\glscategorylabel
```

Setup the default fields.

```

\renewcommand*{\CustomAbbreviationFields}{%
    name={\glxstronlydescname},
    sort={\glxstronlydescsort},%
    first={\glsfirstxplongfont{\the\glslongtok}{\glscategorylabel}},%
    firstplural={\glsfirstxplongfont{\the\glslongpltok}{\glscategorylabel}},%
    text={\glxspabbrvfont{\the\glsshorttok}{\glscategorylabel}},%
    plural={\glxspabbrvfont{\the\glsshortpltok}{\glscategorylabel}}%
}%

```

Unset the regular attribute if it has been set.

```

\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glissetattribute{\the\glslabeltok}{regular}{false}%
  }%
  {}%
}%
\newcommand*{\GlsXtrUseAbbrStyleFmts{long-only-short-only}%
}

```

Small-caps is awkward, so support for that is added.

```

\glsabbrvsconlyfont
\newcommand*{\glsabbrvsconlyfont}{\glsabbrvscfont}%

\glsfirstabbrvsconlyfont
\newcommand*{\glsfirstabbrvsconlyfont}{\glsabbrvsconlyfont}%

```

The default short form suffix:

```

\glsxtrscnlysuffix
\newcommand*{\glsxtrscnlysuffix}{\glsxtrscsuffix}

\glsxtrscnlyrevert
\newcommand*{\glsxtrscnlyrevert}{\glsxtrsc revert}

\glsxtrscnlyname The default name format for this style.
\newcommand*{\glsxtrscnlyname}{%
  \protect\glsabbrvsconlyfont{\the\glsshorttok}%
}

```

```

long-only-short-sc-only
\newabbreviationstyle{long-only-short-sc-only}%
{%

```

Set accessibility attributes if enabled.

```
\glsxtrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
```

Setup the default fields.

```

\renewcommand*{\CustomAbbreviationFields}{%
  name={\glsxtrscnlyname},
  sort={\the\glsshorttok},
  first={\glsfirstxplongfont{\the\glslongtok}{\glscategorylabel}},%
  firstplural={\glsfirstxplongfont{\the\glslongpltok}{\glscategorylabel}},%
  text={\protect\glsabbrvsconlyfont{\the\glsshorttok}},%
  plural={\protect\glsabbrvsconlyfont{\the\glsshortpltok}},%
  description={\protect\glslongonlyfont{\the\glslongtok}}}

```

Unset the `regular` attribute if it has been set.

```
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glsexclapplyinnerfmtfield{\the\glslabeltok}{desc}%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glsssetAttribute{\the\glslabeltok}{regular}{false}%
  }%
}%
}%
{%
  \renewcommand*{\abbrvpluralsuffix}{\glsxtrsconlysuffix}%
  \renewcommand*{\glssabbrvfont}[1]{\glssabbrvsconlyfont{##1}}%
  \renewcommand*{\glssfirstabbrvfont}[1]{\glssfirstabbrvsconlyfont{##1}}%
  \renewcommand*{\glssfirstlongfont}[1]{\glssfirstlongonlyfont{##1}}%
  \renewcommand*{\glsslongfont}[1]{\glsslongonlyfont{##1}}%
  \renewcommand*{\glsxtrrevert}[1]{\glsxtrsconlyrevert{##1}}%
```

The first use full form doesn't show the short form.

```
\renewcommand*{\glsxtrfullformat}[2]{%
  \glsxtrlongformat{##1}{##2}{\glssfirstlongonlyfont}%
}%
\renewcommand*{\glsxtrfullplformat}[2]{%
  \glsxtrlongplformat{##1}{##2}{\glssfirstlongonlyfont}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \Glsxtrlongformat{##1}{##2}{\glssfirstlongonlyfont}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \Glsxtrlongplformat{##1}{##2}{\glssfirstlongonlyfont}%
}%
\renewcommand*{\GLSxtrfullformat}[2]{%
  \GLSxtrlongformat{##1}{##2}{\glssfirstlongonlyfont}%
}%
\renewcommand*{\GLSxtrfullplformat}[2]{%
  \GLSxtrlongplformat{##1}{##2}{\glssfirstlongonlyfont}%
}%
```

The inline full form does show the short form.

```
\renewcommand*{\glsxtrinlinefullformat}[2]{%
  \glsxtrlongshortformat{##1}{##2}%
  {\glssfirstlongonlyfont}{\glssfirstabbrvsconlyfont}%
}%
\renewcommand*{\glsxtrinlinefullplformat}[2]{%
  \glsxtrlongshortplformat{##1}{##2}%
  {\glssfirstlongonlyfont}{\glssfirstabbrvsconlyfont}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \Glsxtrlongshortformat{##1}{##2}%
  {\glssfirstlongonlyfont}{\glssfirstabbrvsconlyfont}%
}%
```

```

}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \Glsxtrlongshortplformat{##1}{##2}%
  {\glsfirstlongonlyfont}{\glsfirstabbrvsonlyfont}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \Glsxtrlongshortformat{##1}{##2}%
  {\glsfirstlongonlyfont}{\glsfirstabbrvsonlyfont}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \Glsxtrlongshortplformat{##1}{##2}%
  {\glsfirstlongonlyfont}{\glsfirstabbrvsonlyfont}%
}%
}

\glsxtrsconlydescsort
\newcommand*{\glsxtrsconlydescsort}{\glsxtronlydescsort}

\glsxtrsconlydescname
\newcommand*{\glsxtrsconlydescname}{\glsxtronlydescname}

long-only-short-sc-only-desc
\newabbreviationstyle{long-only-short-sc-only-desc}%
{%
Set accessibility attributes if enabled.
\glsxtrAccSuppAbbrSetTextShortAttrs\glscategorylabel
Setup the default fields.
\renewcommand*{\CustomAbbreviationFields}{%
  name={\glsxtrsconlydescname},
  sort={\glsxtrsconlydescsort},%
  first={\glsfirstxplongfont{\the\glslongtok}{\glscategorylabel}},%
  firstplural={\glsfirstxplongfont{\the\glslongpltok}{\glscategorylabel}},%
  text={\glsxpabbrvfont{\the\glsshorttok}{\glscategorylabel}},%
  plural={\glsxpabbrvfont{\the\glsshortpltok}{\glscategorylabel}}%
}%
Unset the regular attribute if it has been set.
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glsasattribute{\the\glslabeltok}{regular}%
  {%
    \glssetattribute{\the\glslabeltok}{regular}{false}%
  }%
  {%
  }%
}%
\GlsXtrUseAbbrStyleFmts{long-only-short-sc-only}%
}

```

3 Commands Specific to bib2gls (glossaries-extra-bib2gls.sty)

This package provides additional support for bib2gls and is automatically loaded by the record option.

```
\NeedsTeXFormat{LaTeX2e}
```

Rollback releases:

```
\DeclareRelease{v1.48}{2021-11-22}{glossaries-extra-bib2gls-2021-11-22.sty}
\DeclareCurrentRelease{1.9}{2025-11-03}
```

Declare package:

```
\ProvidesPackage{glossaries-extra-bib2gls}[2026/03/06 v2.0 (NLCT)]
```

Provide convenient shortcut commands for predefined glossary types.

```
\printunsrtacronyms
```

```
\ifglsacronym
  \providecommand*\printunsrtacronyms[1] [] {%
    \printunsrtglossary[type=\acronymtype,#1]}%
\fi
```

```
\printunsrtindex
```

```
\ifglossaryexists{index}
{
  \providecommand*\printunsrtindex[1] [] {%
    \printunsrtglossary[type=index,#1]}%
  {}
}
```

```
\printunsrtsymbols
```

```
\ifglossaryexists{symbols}
{
  \providecommand*\printunsrtsymbols[1] [] {%
    \printunsrtglossary[type=symbols,#1]}%
  {}
}
```

```
\printunsrtnumbers
```

```
\ifglossaryexists{numbers}
{
  \providecommand*\printunsrtnumbers[1] [] {%
    \printunsrtglossary[type=numbers,#1]}%
  {}
}
```

```
\printunsrtabbreviations
```

```
\ifglossaryexists{abbreviations}
{
  \providecommand*\printunsrtabbreviations[1] [] {%
    \printunsrtglossary[type=abbreviations,#1]}%
  {}
}
```

`\glsdisplaynumberlist` Allow `\glsdisplaynumberlist` and make it robust.

```
\renewcommand*{\glsdisplaynumberlist}[1]{%
  \glsdoifexists{#1}%
  {%
    {\let\bibglsgldelimN\glsnumlistsep
     \let\bibglsgldelimN\glsnumlistlastsep
     \glsxtrusefield{#1}{location}}%
  }%
}%
}
```

```
\robustify\glsdisplaynumberlist
```

`\glsentrynumberlist`

```
\renewcommand*{\glsentrynumberlist}[1]{\glsxtrusefield{#1}{location}}
```

`\IfTeXParserLib` This is defined by the `TEX` parser library to behave like `\@firstoftwo`. May be used to provide different code in fields that may be interpreted.

```
\providecommand{\IfTeXParserLib}[2]{#2}
```

The next command is similar but is specifically for `bib2gls` and won't in general be recognised by the `TEX` parser library if used by other applications (such as the converter tools provided with `bib2gls`).

`\IfNotBibGls` This is defined by the `bib2gls` interpreter to behave like `\@secondoftwo`.

```
\providecommand{\IfNotBibGls}[2]{#1}
```

These are some convenient macros for use with custom rules.

`\glshex`

```
\newcommand*{\glshex}{\string\u}
```

`\glscapturedgroup`

```
\newcommand*{\glscapturedgroup}{\string\$}
```

`\glshashchar` Expands to a literal hash character (similar to `\glsbackslash`)

```
\ifdef\glshashchar
{}
{\edef\glshashchar{\expandafter\@gobble\string\#}}
```

`\GlsXtrResourceInitEscSequences` Protect commands that shouldn't expand in resource options as they have a special meaning in the context of those options. This command may be added to the definition of `\glsxtrresourceinit`.

```
\newcommand*{\GlsXtrResourceInitEscSequences}{%
  \def\u{\string\u}%
  \def\.{\string\.%}
  \def\{\{\string\}%
  \def\/{\string\/}%
  \def\|{\string\|}%
  \def\&{\string\&}%
}
```

```

\def\+{\string\+}%
\def\<{\string\<}%
\def\>{\string\>}%
\def\*{\string\*}%
\def\${\string\$}%
\def\~{\string\~}%
\def\~{\string\~}%
\def\({\string\({}%
\def\){\string\)}}%
\def\[{\string\[}%
\def\]{\string\]}%
\def\"{\string\"}%
\def\-{\string\-%
\def\?{\string\?}%
\def\#{\string\#}%
\def\: {\string\:}%
\def\cs##1{\glsbackslash##1}%
\def\CS{\string\CS}%
\def\NULL{\string\NULL\space}%
\def\IN{\string\IN\space}%
\def\NIN{\string\NIN\space}%
\def\PREFIXOF{\string\PREFIXOF\space}%
\def\NOTPREFIXOF{\string\NOTPREFIXOF\space}%
\def\SUFFIXOF{\string\SUFFIXOF\space}%
\def\NOTSUFFIXOF{\string\NOTSUFFIXOF\space}%
\def\LC{\string\LC}%
\def\UC{\string\UC}%
\def\FIRSTLC{\string\FIRSTLC}%
\def\FIRSTUC{\string\FIRSTUC}%
\def\TITLE{\string\TITLE}%
\def\MGP{\string\MGP}%
\def\LEN{\string\LEN}%
\def\TRIM{\string\TRIM}%
\def\INTERPRET{\string\INTERPRET}%
\def\LABELIFY{\string\LABELIFY}%
\def\LABELIFYLIST{\string\LABELIFYLIST}%
\def\CAT{\string\CAT}%
}

```

`\GlsXtrIfHasNonZeroChildCount` For use with bib2gls's save-child-count resource option.

```

\newcommand*{\GlsXtrIfHasNonZeroChildCount}{%
  \ifstar\s@GlsXtrIfHasNonZeroChildCount\@GlsXtrIfHasNonZeroChildCount
}

```

`\GlsXtrIfHasNonZeroChildCount`

```

\newcommand*{\@GlsXtrIfHasNonZeroChildCount}[3]{%
  \@GlsXtrIfFieldNonZero{childcount}{#1}{#2}{#3}%
}

```


`\GlsXtrIfHasNonZeroChildCount`

```
\newcommand*{\s@GlsXtrIfHasNonZeroChildCount}[3]{%
\s@GlsXtrIfFieldNonZero{childcount}{#1}{#2}{#3}%
}
```

`\glstrprovidecommand` For use in @preamble, this behaves like `\providecommand` in the document but like `\renewcommand` in bib2gls.

```
\newcommand*{\glstrprovidecommand}{\providecommand}
```

`\glstrenewcommand` Like `\renewcommand` but only generates a warning rather than an error if the command isn't defined.

```
\newcommand*{\glstrenewcommand}{\@star@or@long\glstr@renewcommand}
```

`\glstr@renewcommand`

```
\newcommand*{\glstr@renewcommand}[1]{%
\begingroup \escapechar\m@ne\xdef\@gtempa{\string#1}\endgroup
\expandafter\@ifundefined\@gtempa
{%
\GlossariesExtraWarning{can't redefine \noexpand#1(not already defined)}%
}%
\relax
\relax
\let\@ifdefinable\@rc@ifdefinable
\new@command#1%
}
```

```
\glstr@wrglossarylocation{<wr-loc>}{<page>}
```

`\glstr@wrglossarylocation`

For use with indexcounter and bib2gls. This just expands to `<wr-loc>` to allow `\glsnoidxdisplayloc` to obtain the hyperlink target. The page number obtained when bib2gls parses the aux file.

```
\newcommand*{\glstr@wrglossarylocation}[2]{#1}
```

```
\GlsXtrIndexCounterLink{<text>}{<label>}
```

`\GlsXtrIndexCounterLink`

For use with indexcounter and bib2gls.

```
\ifdef\hyperref
{%
\newcommand*{\GlsXtrIndexCounterLink}[2]{%
\glstrifhasfield{indexcounter}{#2}%
{\hyperref[wrglossary.\glscurrentfieldvalue]{#1}}%
{#1}%
}
}
{
```

```
\newcommand*{\GlsXtrIndexCounterLink}[2]{#1}
}
```

\GlsXtrDualField

\GlsXtrDualField

The internal field used to store the dual label. The `dual`-field defaults to `dual` if no value is supplied so that's used as the default.

```
\newcommand*{\GlsXtrDualField}{dual}
```

\GlsXtrDualBackLink{<text>}{<label>}

\GlsXtrDualBackLink

Adds a hyperlink to the dual entry.

```
\newcommand*{\GlsXtrDualBackLink}[2]{%
  \glstrifhasfield{\GlsXtrDualField}{#2}%
  {\glshyperlink[#1]{\glscurrentfieldvalue}}%
  {#1}%
}
```

\GlsXtrBibTeXEntryAliases Convenient shortcut for use with `entry-type-aliases` to alias standard \LaTeX entry types to `@bibtexentry`.

```
\newcommand*{\GlsXtrBibTeXEntryAliases}{%
  article=bibtexentry,
  book=bibtexentry,
  booklet=bibtexentry,
  conference=bibtexentry,
  inbook=bibtexentry,
  incollection=bibtexentry,
  inproceedings=bibtexentry,
  manual=bibtexentry,
  mastersthesis=bibtexentry,
  misc=bibtexentry,
  phdthesis=bibtexentry,
  proceedings=bibtexentry,
  techreport=bibtexentry,
  unpublished=bibtexentry
}
```

\GlsXtrProvideBibTeXFields Convenient shortcut to define the standard \LaTeX fields.

```
\newcommand*{\GlsXtrProvideBibTeXFields}{%
  \glsaddstoragekey{address}{}{\glstrbibaddress}%
  \glsaddstoragekey{author}{}{\glstrbibauthor}%
  \glsaddstoragekey{booktitle}{}{\glstrbibbooktitle}%
  \glsaddstoragekey{chapter}{}{\glstrbibchapter}%
  \glsaddstoragekey{edition}{}{\glstrbibedition}%
  \glsaddstoragekey{howpublished}{}{\glstrbibhowpublished}%
  \glsaddstoragekey{institution}{}{\glstrbibinstitution}%
}
```

```

\glsaddstoragekey{journal}{\glsxtrbibjournal}%
\glsaddstoragekey{month}{\glsxtrbibmonth}%
\glsaddstoragekey{note}{\glsxtrbibnote}%
\glsaddstoragekey{number}{\glsxtrbibnumber}%
\glsaddstoragekey{organization}{\glsxtrbiborganization}%
\glsaddstoragekey{pages}{\glsxtrbibpages}%
\glsaddstoragekey{publisher}{\glsxtrbibpublisher}%
\glsaddstoragekey{school}{\glsxtrbibschooll}%
\glsaddstoragekey{series}{\glsxtrbibseries}%
\glsaddstoragekey{title}{\glsxtrbibtitle}%
\glsaddstoragekey{bibtextype}{\glsxtrbibtype}%
\glsaddstoragekey{volume}{\glsxtrbibvolume}%
}

```

Multiple supplementary references are only supported with `bib2gls`.

`\glsxtrmultisuppllocation` This is like `\glsxtrsupphypernumber` but the second argument is the external file name (which isn't obtained from the `externallocation` attribute). The third argument is the formatting (encap) control sequence *name*. This is ignored by default, but is set by `bib2gls` to the original encap in case it's required.

```

\newcommand*\glsxtrmultisuppllocation[3]{%
  {%
    \def\glsxtrsuppllocationurl{#2}%
    \glshypernumber{#1}%
  }%
}

```

```

\glsxtrdisplaysupplloc{<prefix>}{<counter>}{<format>}{<src>}{<location>}

```

`\glsxtrdisplaysupplloc`

This is like `\glsnoidxdisplayloc` but is used for supplementary locations and so requires an extra argument.

```

\newcommand*\glsxtrdisplaysupplloc[5]{%
  \setentrycounter[#1]{#2}%
  \glsxtrmultisuppllocation{#5}{#4}{#3}%
}

```

`\glsxtr@setlocationanchor`

```

\ExplSyntaxOn
\cs_new:Npn \glsxtr@setlocationanchor #1 #2
{
  \group_begin:
  \glswrglossdisableanchorcmds
  \exp_args:NNNe
  \group_end:
  \tl_set:Nn #1 { \text_purify:n { #2 } }
}
\ExplSyntaxOff

```

`\glxtrdisplaylocnameref` `\glxtrdisplaylocnameref{<prefix>}{<counter>}{<format>}{<location>}{<name>}{<href>}{<hcounter>}{<external file>}` Used with the `[nameref]` record package option. The `<href>` argument was obtained from `\@currentHref` and the `<hcounter>` argument was obtained from `\theHentrycounter`, which is more reliable. If `hyperref` hasn't been loaded, this just behaves like `\glsnoidxdisplayloc`.

```
\ifundef\hyperlink
{
  \newcommand*\glxtrdisplaylocnameref}[8]{%
    \glsnoidxdisplayloc{#1}{#2}{#3}{#4}%
  }
}
{
```

Default action uses `<hcounter>`. Equations and pages typically don't have a title, so check the counter name (otherwise the title may be the section or chapter title, which can be confusing). As from v1.42, this now checks if the control sequence `\glxtr<counter>locfmt` is defined. The prefix argument is redundant.

```
\newcommand*\glxtrdisplaylocnameref}[8]{%
  \def\glxtrrecentanchor{#6}%
  \glxtr@setlocationanchor\glxtrlocationanchor{#2.#7}%
```

Initialise `\glxtractualanchor`:

```
\let\glxtractualanchor\glxtrlocationanchor
\glxtrsetactualanchor{#2}%
\ifcsdef\glxtr#2locfmt{%
  {\glxtrnameref link{#3}{\csuse\glxtr#2locfmt}{#4}{#5}}{\glxtractualanchor}{#8}}%
  {%
    \ifstrempy{#5}%
    {%
```

No title, so just use the location as the link text.

```
\glxtrnameref link{#3}{#4}{\glxtractualanchor}{#8}%
}%
{%
  \ifstrequal{#2}{page}%
  {\glxtrnameref link{#3}{#4}{\glxtractualanchor}{#8}}%
  {\glxtrtitlednameref link{#3}{#4}{#5}{#8}}%
}%
}%
}
```

`\glxtractualanchor` Does nothing by default. May be redefined to override the default.

```
\newcommand{\glxtrsetactualanchor}[1]{}
```

```
\glxtrtitlednameref link{<format>}{<location>}{<title>}{<file>}
```

`\glxtrtitlednameref link`

```
\newcommand{\glxstrtitlednamerefink}[4]{%
  \glxstrnamerefink{#1}{#2}{\glxstrrecentanchor}{#4}%
}
```

`\glxstrequationlocfmt`

```
\glxstrequationlocfmt{<location>}{<title>}
```

```
\newcommand*{\glxstrequationlocfmt}[2]{( #1 )}
```

`\glxstrwrglossarylocfmt`

```
\glxstrwrglossarylocfmt{<location>}{<title>}
```

```
\newcommand*{\glxstrwrglossarylocfmt}[2]{%
  {\@@glxstrwrglosscountermark{#1}%
  \let\glxstr@wrglossarylocation\@secondoftwo
  #1}%
}
```

`\glxstrnamerefink`

```
\glxstrnamerefink{<format>}{<title>}{<href>}{<external
file>}
```

```
\newcommand*{\glxstrnamerefink}[4]{%
```

Locally change `\glshypernumber` to `\@firstofone` to remove the normal location hyperlink.

```
\begingroup
\let\glshypernumber\@firstofone
```

If the `<external file>` argument is empty, an internal link is used, otherwise an external one is needed.

```
\ifstrempy{#4}%
{\glxstrfmtinternalnameref{#3}{#1}{#2}}%
{\glxstrfmtexternalnameref{#3}{#1}{#2}{#4}}%
\endgroup
}
```

`\glxstrnameloclink`

```
\glxstrnameloclink{<prefix>}{<counter>}{<format>}{<location>}{<text>}{<external
file>}
```

Like `\@gls@numberlink`, this creates a hyperlink to the target obtained from the prefix, counter and location but uses `<text>` as the hyperlink text. As with regular indexing, this will fail if the target name can't be formed by prefixing the location value.

```

\newcommand{\glxtrnameloclink}[6]{%
\begin{group}
\setentrycounter[#1]{#2}%
\def\glxtr@locationhypertext{#5}%
\let\glshypernumber\@firstofone
\def\@glsnnumberformat{#3}%
\def\glxtrsupplocationurl{#6}%
\toks@={}%
\@glxtr@bibgls@removespaces#4 \@nil
\end{group}
}

```

\@glxtr@bibgls@removespaces

```

\def\@glxtr@bibgls@removespaces#1 #2\@nil{%
\toks@=\expandafter{\the\toks@#1}%
\ifx\@#2\%

\edef\@glo@tmp{\the\toks@}%
\ifx\@glo@tmp\empty
\else
\protected@edef\@glo@tmp{\glentrycounter\@glo@counterprefix\the\toks@}%
\ifdefined\glxtrsupplocationurl
{%
\expandafter\glxtrfmtinternalnameref\expandafter{\@glo@tmp}%
{\@glsnnumberformat}\glxtr@locationhypertext}%
}%
{%
\expandafter\glxtrfmtexternalnameref\expandafter{\@glo@tmp}%
{\@glsnnumberformat}\glxtr@locationhypertext}\glxtrsupplocationurl}%
}%
\fi
\else
\@gls@ReturnAfterFi{%
\@glxtr@bibgls@removespaces#2\@nil
}%
\fi
}

```

\glxtrfmtinternalnameref

`\glxtrfmtinternalnameloc{<target>}{<format>}{<title>}`

```

\newcommand*{\glxtrfmtinternalnameref}[3]{%
\csuse{#2}{\glsdohyperlink{#1}{#3}}%
}

```

\glxtrfmtexternalnameref

`\glxtrfmtexternalnameloc{<target>}{<format>}{<title>}`
`{<file>}`

```

\newcommand*{\glstrfmtexternalnameref}[4]{%
  \csuse{#2}{\hyperref{#4}{#1}{#3}}%
}

```

```

\glstrSetWidest{<type>}{<level>}{<text>}

```

\glstrSetWidest

As from bib2gls v1.8, this is used by the `set-widest` resource option for the `alttree` and the styles provided by the `glossary-longextra` package.

```

\newcommand*{\glstrSetWidest}[3]{%

```

Check which style options have been provided. (The style packages may not have been loaded.)

```

  \ifdef\glupdatewidest
  {%
    \ifdef\glslongextraUpdateWidest
    {%

```

Relevant style packages all loaded. If the `<type>` has been given, append to glossary preamble.

```

      \ifstrempy{#1}
      {%
        \glupdatewidest[#2]{#3}%
        \ifnum#2=0\relax
          \glslongextraUpdateWidest{#3}%
        \else
          \glslongextraUpdateWidestChild{#2}{#3}%
        \fi
      }%
    {%
      \apptoglossarypreamble[#1]{\glupdatewidest[#2]{#3}}%
      \ifnum#2=0\relax
        \apptoglossarypreamble[#1]{\glslongextraUpdateWidest{#3}}%
      \else
        \apptoglossarypreamble[#1]{\glslongextraUpdateWidestChild{#2}{#3}}%
      \fi
    }%
  }%
  {%

```

Only `alttree`.

```

      \ifstrempy{#1}
      {%
        \glupdatewidest[#2]{#3}%
      }%
    {%
      \apptoglossarypreamble[#1]{\glupdatewidest[#2]{#3}}%
    }%
  }%
}%

```

```

{%
\glsupdatewidest hasn't been defined. This could just mean that the
glossaries-extra-stylemods package hasn't been loaded.
\ifdef\glssetwidest
{%
\ifdef\glslongextraUpdateWidest
{%

```

Relevant glossary-tree and glossary-longextra have been loaded. If the $\langle type \rangle$ has been given, append to glossary preamble.

```

\ifstrempy{#1}
{%
\glssetwidest[#2]{#3}%
\ifnum#2=0\relax
\glslongextraUpdateWidest{#3}%
\else
\glslongextraUpdateWidestChild{#2}{#3}%
\fi
}%
{%
\apptoglossarypreamble[#1]{\glssetwidest[#2]{#3}}%
\ifnum#2=0\relax
\apptoglossarypreamble[#1]{\glslongextraUpdateWidest{#3}}%
\else
\apptoglossarypreamble[#1]{\glslongextraUpdateWidestChild{#2}{#3}}%
\fi
}%
}%
{%

```

Only alttree.

```

\ifstrempy{#1}
{%
\glssetwidest[#2]{#3}%
}%
{%
\apptoglossarypreamble[#1]{\glssetwidest[#2]{#3}}%
}%
}%
}%
{%
\ifdef\glslongextraUpdateWidest
{%

```

glossary-longextra has been loaded.

```

\ifstrempy{#1}
{%
\ifnum#2=0\relax
\glslongextraUpdateWidest{#3}%
\else

```



```

        \glslongextraUpdateWidestChild{#2}{#3}%
      \fi
    }%
  {%
    \ifnum#2=0\relax
      \apptoglossarypreamble[#1]{\glslongextraUpdateWidest{#3}}%
    \else
      \apptoglossarypreamble[#1]{\glslongextraUpdateWidestChild{#2}{#3}}%
    \fi
  }%
}%
}

```

Neither glossary-tree nor glossary-longextra have been loaded. Do nothing.

```

    {}%
  }%
}%
}

```

```
\glsxtrSetWidestFallback{<max depth>}{<list>}
```

\glsxtrSetWidestFallback

Used when bib2gls can't determine the widest name. The *<list>* argument is a comma-separated list of glossary labels. The *<max depth>* refers to the maximum hierarchical depth. This will either be 0 (only top-level entries) or 2 (up to two child-levels).

```

\newcommand*{\glsxtrSetWidestFallback}[2]{%
  \ifnum#1=0\relax
    \ifdef\glsFindWidestTopLevelName
      {%
        \glsFindWidestTopLevelName[#2]%
      }%
    {%
      \GlossariesExtraWarning{You need stylemods={tree} to
        provide a fallback for set-widest}%
    }%
  \else
    \ifdef\glsFindWidestLevelTwo
      {%
        \glsFindWidestLevelTwo[#2]%
        \ifdef\glslongextraUpdateWidestChild
          {%
            \glslongextraUpdateWidestChild{#1}{\csuse{@glswidestnamei}}%
            \glslongextraUpdateWidestChild{#1}{\csuse{@glswidestnameii}}%
          }%
        {}%
      }%
    {%
      \GlossariesExtraWarning{You need stylemods={tree} to
        provide a fallback for set-widest}%
    }%
  }

```

```

    }%
  \fi
}

```

`\@glxstr@labelprefixes` List of label prefixes.

```
\newcommand*{\@glxstr@labelprefixes}{}
```

`\glxstrclearlabelprefixes` List of label prefixes.

```

\newcommand*{\glxstrclearlabelprefixes}{%
  \renewcommand*{\@glxstr@labelprefixes}{}%
}

```

`\glxstraddlabelprefix` Add prefix to the list. These should be added in the order of precedence with the last one as a fallback. This doesn't check against duplicates as it may be useful to replicate a prefix at the end as the fallback.

```

\newcommand*{\glxstraddlabelprefix}[1]{%
  \ifstrempy{#1}%
  {\glxstraddlabelprefix{\empty}}%
  {%
    \ifdefempty\@glxstr@labelprefixes
    {\def\@glxstr@labelprefixes{#1}}%
    {\appto\@glxstr@labelprefixes{,#1}}%
  }%
}

```

`\glxstrprependlabelprefix` Inserts at the start of the list.

```

\newcommand*{\glxstrprependlabelprefix}[1]{%
  \ifstrempy{#1}%
  {\glxstrprependlabelprefix{\empty}}%
  {%
    \ifdefempty\@glxstr@labelprefixes
    {\def\@glxstr@labelprefixes{#1}}%
    {\preto\@glxstr@labelprefixes{#1,}}%
  }%
}

```

```
\glxstrifinlabelprefixlist{<prefix>}{<true>}{<false>}
```

`\glxstrifinlabelprefixlist`

Test if the given prefix is in the list.

```

\newcommand*{\glxstrifinlabelprefixlist}[3]{%
  \ifstrempy{#1}%
  {\glxstrifinlabelprefixlist{\empty}{#2}{#3}}%
  {%
    \DTLifinlist{#1}{\@glxstr@labelprefixes}{#2}{#3}%
  }%
}

```

`\@glxtr@prefixlabellist` This is provided for the benefit of `bib2gls`. It's possible that the user may add more prefixes after the start of the document, but that can lead to inconsistencies. The final element of the list (the fallback) is the only prefix of interest for `bib2gls`.

```
\AtBeginDocument{%
  \protected@write\@auxout{}\string\providecommand{\string\@glxtr@prefixlabellist}[1]{}%
  \protected@write\@auxout{}\string\@glxtr@prefixlabellist{\@glxtr@labelprefixes}%
}
```

Before v1.49, the last label was used as a fallback, but this doesn't make sense when the first matching label is used when entries are defined. The selection should be deferred to `bib2gls`, which means passing the list of label choices to `bib2gls`.

`\@glxtr@dglsnomatch` No match found so record all possibilities. Requires `bib2gls v3.0+`. This will add the final insert argument but won't be able to apply any case-changing etc.

```
\def\@glxtr@dglsnomatch#1#2[#3]{%
  \begingroup
```

This is a cut-down version of `\@glxtr@record`. Use the fallback label in the event any hooks have to reference `\glslabel`. This is mainly to prevent an undefined control sequence error. It can't be relied on as the actual label.

```
\let\glslabel\@glsl@thislabel
\let\@glslnumberformat\@glxtr@defaultnumberformat
\def\@glxtr@thevalue{%
\def\@glxtr@theHvalue{\@glxtr@thevalue}%
\let\@glxtr@org@theHvalue\@glxtr@theHvalue
\let\@glsl@counter\glscounter
\if@glxtr@equations
  \@glxtr@use@equation@counter
\fi
\@glsl@setdefault@glslink@opts
\@glxtr@glslink@prekeys
\setkeys{glslink}{#1}%
\glxtr@do@autoadd{glslink}%
```

Can't increment associated counter.

```
\ifKV@glslink@noindex
  \GlossariesExtraWarning{Can't obtain a match for prefix
    candidates: \@glxtr@prefixedlist. Check the label spelling or rerun}%
\else
  \ifdefempty{\@glxtr@thevalue}%
  {%
    \ifx\@glxtr@org@theHvalue\@glxtr@theHvalue
    \else
      \let\theHglstrycounter\@glxtr@theHvalue
    \fi
  }%
  {%
```

```

\let\theglsentrycounter\@glxtr@thevalue
\let\theHglentrycounter\@glxtr@theHvalue
}%
\glxtr@saveentrycounter
\@glxtr@dorecord\@glxtr@prefixedlist
\glxtr@select@entry\glxtr@do@select@nameref@record

```

Issue warning.

```

\GlossariesExtraWarning{Can't obtain a match for prefix
candidates: \@glxtr@prefixedlist. Check the label spelling, use bib2gls v3.0+ to
select entry and rerun LaTeX}%
\fi
\@glxtrundeftag#3%
\endgroup
}

```

`\glxtr@select@entry` Instruction to bib2gls to select the first found label in the list.

```
\newcommand*{\glxtr@select@entry}[5]{}
```

`\glxtr@select@entry@nameref` Instruction to bib2gls to select the first found label in the list as though it has a record.

```
\newcommand*{\glxtr@select@entry@nameref}[8]{}
```

`\glxtr@do@select@nameref@record` Instruction to bib2gls to select the first found label in the list as though it has a record.

```

\newcommand*{\glxtr@do@select@nameref@record}[5]{%
\gls@ifnotmeasuring
{%
\protected@write\@auxout{}\string\glxtr@select@entry@nameref
{#1}{#2}{#3}{#4}{#5}%
{\csuse{@currentlabelname}}{\csuse{@currentHref}}%
{\theHglentrycounter}}%
}%
}

```

`\GlsXtrPrefixLabelFallbackLast` Determine whether the first or last label should be used as the fallback in the event that there's no match on any prefixes.

```

\newif\ifGlsXtrPrefixLabelFallbackLast
\GlsXtrPrefixLabelFallbackLasttrue

```

`\@glxtr@get@prefixedlabel` Iterate through all the prefixes and find the first prefix and label combination that exists. If none found, this could mean that it's the first L^AT_EX run.

```
\newcommand*{\@glxtr@get@prefixedlabel}[1]{%
```

Grouping is used in case of a nested for loop.

```
\begingroup
```

Initialise to the unprefix label in the event that the list is empty.

```
\protected@edef\@gls@thislabel{#1}%
```

Save the first label.

```
\let\@glsxtr@prefixedfirstlabel\@gls@thislabel
\def\@glsxtr@set@prefixedfirstlabel{%
  \let\@glsxtr@prefixedfirstlabel\@gls@thislabel
  \let\@glsxtr@set@prefixedfirstlabel\relax
}%
```

List of labels in the event that no combination is found.

```
\let\@glsxtr@prefixedlist\@empty
```

Iterate over all labels.

```
\count@=0\relax
\@for\@glsxtr@prefix:=\@glsxtr@labelprefixes\do
{%
  \advance\count@ by 1\relax
  \protected@edef\@gls@thislabel{\@glsxtr@prefix#1}%
  \@glsxtr@set@prefixedfirstlabel
```

Check if this label exists.

```
\ifglentryexists{\@gls@thislabel}%
{%
  \@endfortrue
```

Found a label that exists. Clear the list.

```
\let\@glsxtr@prefixedlist\@empty
}%
{%
```

Append or prepend to list.

```
\ifdefempty\@glsxtr@prefixedlist
{\let\@glsxtr@prefixedlist\@gls@thislabel}%
{%
  \ifGlsXtrPrefixLabelFallbackLast
    \epreto\@glsxtr@prefixedlist{\expandonce\@gls@thislabel,}%
  \else
    \eappto\@glsxtr@prefixedlist{\, \expandonce\@gls@thislabel}%
  \fi
}%
}%
\if@endfor
```

Loop ended prematurely, which means label was found.

```
\else
\ifnum\count@>1\relax
\ifGlsXtrPrefixLabelFallbackLast
\else
```

Fallback on first label.

```
\let\@gls@thislabel\@glsxtr@prefixedfirstlabel
\fi
\else
```

Only one prefix so assume that one.

```

\let\@glxtr@prefixedlist\@empty
\fi
\fi

\edef\@glo@tmp{\endgroup
\noexpand\def\noexpand\@glxtr@prefixedlist{\expandonce\@glxtr@prefixedlist}%
\noexpand\def\noexpand\@gls@thislabel{\expandonce\@gls@thislabel}}\@glo@tmp
}

```

`\predglshook` Hook for use at the start of the `\dgl`s-like commands. The argument is the found prefixed label. Not used if no match found.

```
\newcommand\predglshook[1]{}
```

`@@dgl`s Used by all the `\dgl`s-like commands to find the first match.

```

\newcommand*{\@@dgl@}[3]{%
\@glxtr@get@prefixedlabel{#2}%
\ifx\@glxtr@prefixedlist\@empty
\predglshook{\@gls@thislabel}%
\let\@dgl@@next#3%
\else
\let\@dgl@@next\@glxtr@dgl@nomatch
\fi
\new@ifnextchar[{\@dgl@@next{#1}{\@gls@thislabel}}%
{\@dgl@@next{#1}{\@gls@thislabel}}{}%
}

```

`\dgl`s Like `\gls` but tries the prefixes. (Can't use `\pgls` as that's provided by glossaries-prefix.) Since this command is designed for bib2gls's dual entry system, the “d” stands for “dual”.

```
\newrobustcmd*\dgl{\@gls@hyp@opt\dgl}
```

`\@dgl`s

```
\newcommand*{\@dgl}[2][\@@dgl@{#1}{#2}{\@gls@}]
```

`\dgl`spl

```
\newrobustcmd*\dglspl{\@gls@hyp@opt\dglspl}
```

`\@dgl`spl

```
\newcommand*{\@dglspl}[2][\@@dgl@{#1}{#2}{\@glspl@}]
```

`\dGls`

```

\newrobustcmd*\dGls{\@gls@hyp@opt\dGls}
\glsmfuaddmap\dgl{\dGls}

```

`\@dGls`

```
\newcommand*{\@dGls}[2][\@@dgl@{#1}{#2}{\@dGls@}]
```

```

\@dGlspl
\newrobustcmd*{\dGlspl}{\@gls@hyp@opt\@dGlspl}
\glsmfuaddmap{\dGlspl}{\dGlspl}

\@dGlspl
\newcommand*{\@dGlspl}[2][\@{\@dgls@{#1}{#2}}{\@Glspl@}]

\dGLS
\newrobustcmd*{\dGLS}{\@gls@hyp@opt\@dGLS}
\glsmfublocker{\dGLS}

\@dGLS
\newcommand*{\@dGLS}[2][\@{\@dgls@{#1}{#2}}{\@GLS@}]

\dGLSpl
\newrobustcmd*{\dGLSpl}{\@gls@hyp@opt\@dGLSpl}
\glsmfublocker{\dGLSpl}

\@dGLSpl
\newcommand*{\@dGLSpl}[2][\@{\@dgls@{#1}{#2}}{\@GLSpl@}]

\dglslink Like \glslink but tries the prefixes.
\newrobustcmd*{\dglslink}{\@gls@hyp@opt\@dglslink}

\predglslinkhook Hook for use at the start of the \dglslink and \dglsdisp. The argument is
the found prefixed label. Not used if no match found.
\newcommand\predglslinkhook[1]{

\@dglslink
\newcommand*{\@dglslink}[3][\%
\@glsxtr@get@prefixedlabel{#2}%
\predglslinkhook{\@gls@thislabel}%
\glslink[#1]{\@gls@thislabel}{#3}%
}

\dGlslink Sentence-case version to provide a mapping.
\newrobustcmd*{\dGlslink}{\@gls@hyp@opt\@dGlslink}
\glsmfuaddmap{\dGlslink}{\dGlslink}

\@dGlslink
\newcommand*{\@dGlslink}[3][\%
\dglslink[#1]{#2}{\glssentencecase{#3}}%
}

\dglsdisp Like \glsdisp but tries the prefixes.
\newrobustcmd*{\dglsdisp}{\@gls@hyp@opt\@dglsdisp}

```

`\@dglstdisp` Like `\glstdisp` but tries the prefixes.

```
\newcommand*{\@dglstdisp}[3][]{%
  \@glstr@get@prefixedlabel{#2}%
  \predglslinkhook{\@gls@thislabel}%
  \glstdisp[#1]{\@gls@thislabel}{#3}%
}
```

`\dGlsdisp` Sentence-case version to provide a mapping.

```
\newrobustcmd*{\dGlsdisp}{\@gls@hyp@opt\dGlsdisp}
\glsmfuaddmap{\dglstdisp}{\dGlsdisp}
```

`\@dGlsdisp`

```
\newcommand*{\@dGlsdisp}[3][]{%
  \dglstdisp[#1]{#2}{\glssentencecase{#3}}%
}
```

Similar to the above but searches for a match with the given field set.

`\glstr@get@prefixedlabel@field` The second argument is the field's internal label.

```
\newcommand*{\@glstr@get@prefixedlabel@field}[2]{%
  \protected@edef\dglstfieldcurrentfieldlabel{#2}%
  \let\dglstfieldactualfieldlabel\dglstfieldcurrentfieldlabel
```

Grouping is used in case of a nested for loop.

```
\begingroup
```

Initialise to the unprefix label in the event that the list is empty.

```
\protected@edef\@gls@thislabel{#1}%
```

Save the first label.

```
\let\@glstr@prefixedfirstlabel\@gls@thislabel
\def\@glstr@set@prefixedfirstlabel{%
  \let\@glstr@prefixedfirstlabel\@gls@thislabel
  \let\@glstr@set@prefixedfirstlabel\relax
}%
```

Initialise fallback label.

```
\let\@gls@fallbacklabel\relax
```

List of labels in the event that no combination is found.

```
\let\@glstr@prefixedlist\@empty
```

Iterate over all labels.

```
\count@=0\relax
\@for\@glstr@prefix:=\@glstr@labelprefixes\do
{%
  \advance\count@ by 1\relax
  \protected@edef\@gls@thislabel{\@glstr@prefix#1}%
  \glstr@set@prefixedfirstlabel
```

Check if this label exists.

```
\ifglstryexists{\@gls@thislabel}%
{%
```


Found a label that exists. Has the field been set?

```
\ifcsvoid{glo@\glsdetoklabel{\@gls@thislabel}#2}%
{%
```

Field hasn't been set. Has a fallback been set yet?

```
\ifx\@gls@fallbacklabel\relax
\ifcsvoid
{glo@\glsdetoklabel{\@gls@thislabel}\dglsfieldfallbackfieldlabel}%
{%
  \GlossariesExtraInfo{Found entry '@gls@thislabel' that
    matches prefix '@glsxtr@prefix' but field '#2' not set
    and fallback field '\dglsfieldfallbackfieldlabel' not set}%
}%
{%
  \let\@gls@fallbacklabel\@gls@thislabel
  \GlossariesExtraInfo{Found entry '@gls@thislabel' that
    matches prefix '@glsxtr@prefix' but field '#2' not set.
    Fallback field '\dglsfieldfallbackfieldlabel' is set
    so setting fallback entry to '@gls@fallbacklabel' with
    field '\dglsfieldfallbackfieldlabel'}%
}%
\else
  \GlossariesExtraInfo{Found entry '@gls@thislabel' that
    matches prefix '@glsxtr@prefix' but field '#2' not set.
    Fallback entry: '@gls@fallbacklabel'}%
\fi
```

Add to list. (A new entry with the desired field may have been added, so allow it to be selected.)

```
\ifdefempty\@glsxtr@prefixedlist
{\let\@glsxtr@prefixedlist\@gls@thislabel}%
{%
  \ifGlsXtrPrefixLabelFallbackLast
    \epreto\@glsxtr@prefixedlist{\expandonce\@gls@thislabel,}%
  \else
    \eappto\@glsxtr@prefixedlist{\, \expandonce\@gls@thislabel}%
  \fi
}%
}%
{%
  \@endfortrue
```

The field has been set. Clear the list.

```
\let\@glsxtr@prefixedlist\@empty
}%
}%
{%
```

Append or prepend to list.

```
\ifdefempty\@glsxtr@prefixedlist
{\let\@glsxtr@prefixedlist\@gls@thislabel}%
```

```

    {%
      \ifGlsXtrPrefixLabelFallbackLast
        \epreto\@glstr@prefixedlist{\expandonce\@gls@thislabel,}%
      \else
        \eappto\@glstr@prefixedlist{,\expandonce\@gls@thislabel}%
      \fi
    }%
  }%
}%
\if@endfor
Loop ended prematurely, which means label was found.
\else
Label not found. Was the fallback field found?
\ifx\@gls@fallbacklabel\relax
  \GlossariesExtraWarning{No fallback found for ‘#1’}%
No field fallback found.
\ifnum\count@>1\relax
  \ifGlsXtrPrefixLabelFallbackLast
    \else
Fallback on first label.
    \let\@gls@thislabel\@glstr@prefixedfirstlabel
    \fi
  \else
Only one prefix so assume that one.
    \let\@glstr@prefixedlist\@empty
    \fi
  \else
Fallback field was found. Use the fallback entry.
    \let\@gls@thislabel\@gls@fallbacklabel
    \let\dglsfieldactualfieldlabel\dglsfieldfallbackfieldlabel
Clear prefix candidate list.
    \let\@glstr@prefixedlist\@empty
    \fi
  \fi

\edef\@glo@tmp{\endgroup
\noexpand\def\noexpand\@glstr@prefixedlist{\expandonce\@glstr@prefixedlist}%
\noexpand\def\noexpand\@gls@thislabel{\expandonce\@gls@thislabel}%
\noexpand\def\noexpand\dglsfieldactualfieldlabel
{\expandonce\dglsfieldactualfieldlabel}%
}%
\@glo@tmp
}

```

`\predglsfieldhook` Hook for use at the start of the `\dglsfield`-like commands. The argument is the found prefixed label. Not used if no match found.

```
\newcommand\predglsfieldhook[1]{}
```

`\@@dgl@s@@field{<options>}{<label>}{<field>}{<cs>}`

```
\newcommand*{\@@dgl@s@@field}[4]{%
  \@glstr@get@prefixedlabel@field{#2}{#3}%
  \ifx\@glstr@prefixedlist\@empty
    \predgl$fieldhook{\@gl@s@thislabel}%
    \let\@dgl@s@@next#4%
  \else
    \let\@dgl@s@@next\@glstr@dgl$nomatch
  \fi
  \new@ifnextchar[{\@dgl@s@@next{#1}{\@gl@s@thislabel}}{%
    {\@dgl@s@@next{#1}{\@gl@s@thislabel}[]}%
  }
}
```

`\dgl$fieldcurrentfieldlabel` Set by the `\dgl$field` commands to the current field label. This is the field requested in the argument of `\dgl$field`.

```
\newcommand*{\dgl$fieldcurrentfieldlabel}{}%
```

`\dgl$fieldfallbackfieldlabel` The field to use if the required field isn't set.

```
\newcommand*{\dgl$fieldfallbackfieldlabel}{text}%
```

`\dgl$fieldactualfieldlabel` This is the field that's actually used.

```
\newcommand*{\dgl$fieldactualfieldlabel}{\dgl$fieldcurrentfieldlabel}%
```

`\dgl$field[<options>]{<label>}{<field>}[<insert>]`

```
\newrobustcmd*{\dgl$field}{\@gl@s@hyp@opt\dgl$field}
```

`\@dgl$field`

```
\newcommand*{\@dgl$field}[3][]{%
  \@@dgl@s@@field{#1}{#2}{#3}{\@dgl@s@field}%
}
```

`\@dgl@s@field`

```
\def\@dgl@s@field#1#2[#3]{%
  \@gl@s@field@link{#1}{#2}{\glstr@usefield{#2}{\dgl$fieldactualfieldlabel}#3}%
}
```

`\dGlsfield[<options>]{<label>}{<field>}[<insert>]`

```
\newrobustcmd*{\dGlsfield}{\@gl@s@hyp@opt\dGlsfield}
\glsmfuaddmap{\dgl$field}{\dGlsfield}
```

`\@dGlsfield`

```
\newcommand*{\@dGlsfield}[3][]{%
  \@@dgl@s@@field{#1}{#2}{#3}{\@dGls@field}%
}
```

```
\@dGls@field
\def\@dGls@field#1#2[#3]{%
  \@gls@field@link{#1}{#2}{\Glsxtrusefield{#2}{\dglstfieldactualfieldlabel}{#3}}%
}
```

```
\dGlsfield[\langle options \rangle]{\langle label \rangle}{\langle field \rangle}[\langle insert \rangle]
```

```
\dGLSfield
\newrobustcmd*{\dGLSfield}{\@gls@hyp@opt\dGLSfield}
\glsmfublocker{\dGLSfield}
```

```
\@dGLSfield
\newcommand*{\@dGLSfield}[3][ ]{%
  \@dglst@field{#1}{#2}{#3}{\@dGLS@field}%
}
```

```
\@dGLS@field
\def\@dGLS@field#1#2[#3]{%
  \@gls@field@link{#1}{#2}{\Glsxtrusefield{#2}{\dglstfieldactualfieldlabel}{#3}}%
}
```

```
\@d@inner@glsfield{\langle default options \rangle}{\langle field \rangle}{\langle modifier \rangle}
[\langle options \rangle]{\langle label \rangle}[\langle insert \rangle]
```

```
\@d@inner@glsfield
\newrobustcmd*{\@d@inner@glsfield}[2]{%
  \ifstrempy{#1}
  {\def\@d@inner@glsfield@opts{}}%
  {\def\@d@inner@glsfield@opts{#1},}%
  \def\dglstfieldcurrentfieldlabel{#2}%
  \@gls@hyp@opt\@d@inner@glsfield
}
```

```
\@d@inner@glsfield
\newcommand*{\@d@inner@glsfield}[2][ ]{%
  \expandafter\@dglst@field\expandafter
  {\@d@inner@glsfield@opts#1}{#2}{\dglstfieldcurrentfieldlabel}{\@dglstfield}}

```

```
\@d@inner@Glsfield
\newrobustcmd*{\@d@inner@Glsfield}[2]{%
  \ifstrempy{#1}
  {\def\@d@inner@glsfield@opts{}}%
  {\def\@d@inner@glsfield@opts{#1},}%
  \def\dglstfieldcurrentfieldlabel{#2}%
  \@gls@hyp@opt\@d@inner@Glsfield
}
```

```
\d@inner@Glsfield
\newcommand*\d@inner@Glsfield}[2][]{%
\expandafter\@dgls@@field\expandafter
{\d@inner@glsgfield@opts#1}{#2}{\dglsfieldcurrentfielddlabel}{\@dGls@field}}
```

```
\d@inner@GLSfield
\newrobustcmd*\d@inner@GLSfield}[2]{%
\ifstrempy{#1}
{\def\d@inner@glsgfield@opts{}}%
{\def\d@inner@glsgfield@opts{#1,}}%
\def\dglsfieldcurrentfielddlabel{#2}%
\@gls@hyp@opt\d@inner@GLSfield
}
```

```
\d@inner@GLSfield
\newcommand*\d@inner@GLSfield}[2][]{%
\expandafter\@dgls@@field\expandafter
{\d@inner@glsgfield@opts#1}{#2}{\dglsfieldcurrentfielddlabel}{\@dGLS@field}}
```

```
\newdglsgfield[\langle options \rangle]{\langle field \rangle}{\langle cs \rangle}
```

```
\newrobustcmd*\newdglsgfield}[3][]{%
\newrobustcmd*{#3}{\d@inner@glsgfield{#1}{#2}}%
}
```

```
\newdglsgfieldlike[\langle options \rangle]{\langle field \rangle}{\langle cs \rangle}{\langle Cs \rangle}{\langle CS \rangle}
```

```
\newrobustcmd*\newdglsgfieldlike}[5][]{%
\newrobustcmd*{#3}{\d@inner@glsgfield{#1}{#2}}%
\newrobustcmd*{#4}{\d@inner@Glsfield{#1}{#2}}%
\newrobustcmd*{#5}{\d@inner@GLSfield{#1}{#2}}%
\glsmfuaddmap{#3}{#4}%
\glsmfublocker{#5}%
}
```

Multi (compound/combined) entry commands used by bib2gls.

```
\glsxtrmultientryadjustedname{\langle list1 \rangle}{\langle name \rangle}{\langle list2 \rangle}
{\langle label \rangle}
```

\glsxtrmultientryadjustedname

This command is used by bib2gls when it adjusts the name field of an entry that's been identified as a main entry in the multi-entry set *label*.

The final argument *label* is the multi-entry label from which the set was obtained. The first argument *list1* is the list of other labels that come before

the main label. The third argument (*list2*) is the remaining list of other labels. The *<name>* argument is the previous name before adjustment.

```
\newrobustcmd*{\glxstrmultientryadjustedname}[4]{%
  \bgroup
  \let\@glxstrmultientryadjustednamesep\glxstrmultientryadjustednamesep
  \let\@glxstrmultientryadjustednamepresep\glxstrmultientryadjustednamepresep
  \let\@glxstrmultientryadjustednamepostsep\glxstrmultientryadjustednamepostsep
  \let\@glxstrmultientryadjustednameother\glxstrmultientryadjustednameother
  \let\@glxstrmultientryadjustednamefmt\glxstrmultientryadjustednamefmt
  \let\@glxstrmultientryadjustednamefirstother\glxstrmultientryadjustednameother
  \let\@glxstrmultientryadjustednamefirstfmt\glxstrmultientryadjustednamefmt
  \@glxstrmultientryadjustedname{#1}{#2}{#3}{#4}%
  \egroup
}
```

`\glxstrmultientryadjustedname` First letter upper case

```
\newrobustcmd*{\Glsxstrmultientryadjustedname}[4]{%
  \bgroup
  \let\@glxstrmultientryadjustednamesep\glxstrmultientryadjustednamesep
  \let\@glxstrmultientryadjustednamepresep\glxstrmultientryadjustednamepresep
  \let\@glxstrmultientryadjustednamepostsep\glxstrmultientryadjustednamepostsep
  \let\@glxstrmultientryadjustednameother\glxstrmultientryadjustednameother
  \let\@glxstrmultientryadjustednamefmt\glxstrmultientryadjustednamefmt
  \let\@glxstrmultientryadjustednamefirstother\Glsxstrmultientryadjustednameother
  \let\@glxstrmultientryadjustednamefirstfmt\Glsxstrmultientryadjustednamefmt
  \@glxstrmultientryadjustedname{#1}{#2}{#3}{#4}%
  \egroup
}
\glsmfuaddmap{\glxstrmultientryadjustedname}{\Glsxstrmultientryadjustedname}
```

`\GlsXtrmultientryadjustedname` Title case

```
\newrobustcmd*{\GlsXtrmultientryadjustedname}[4]{%
  \bgroup
  \let\@glxstrmultientryadjustednamesep\glxstrmultientryadjustednamesep
  \let\@glxstrmultientryadjustednamepresep\glxstrmultientryadjustednamepresep
  \let\@glxstrmultientryadjustednamepostsep\glxstrmultientryadjustednamepostsep
  \let\@glxstrmultientryadjustednameother\GlsXtrmultientryadjustednameother
  \let\@glxstrmultientryadjustednamefmt\GlsXtrmultientryadjustednamefmt
  \let\@glxstrmultientryadjustednamefirstother\GlsXtrmultientryadjustednameother
  \let\@glxstrmultientryadjustednamefirstfmt\GlsXtrmultientryadjustednamefmt
  \@glxstrmultientryadjustedname{#1}{#2}{#3}{#4}%
  \egroup
}
\glsmfublocker{\GlsXtrmultientryadjustedname}
```

`\GLSxtrmultientryadjustedname` All caps.

```
\newrobustcmd*{\GLSxtrmultientryadjustedname}[4]{%
  \bgroup
  \let\@glxstrmultientryadjustednamesep\glxstrmultientryadjustednamesep
```

```

\let\@glxstrmultientryadjustednamepresep\glxstrmultientryadjustednamepresep
\let\@glxstrmultientryadjustednamepostsep\glxstrmultientryadjustednamepostsep
\let\@glxstrmultientryadjustednameother\GLSxtrmultientryadjustednameother
\let\@glxstrmultientryadjustednamefmt\GLSxtrmultientryadjustednamefmt
\let\@glxstrmultientryadjustednamefirstother\GLSxtrmultientryadjustednameother
\let\@glxstrmultientryadjustednamefirstfmt\GLSxtrmultientryadjustednamefmt
\@glxstrmultientryadjustedname{#1}{#2}{#3}{#4}%
\egroup
}
\glsmfublocker{\GLSxtrmultientryadjustedname}

\glxstrmultientryadjustedname

\newcommand*{\@glxstrmultientryadjustedname}[4]{%
  \letcs\mglscurrentmainlabel{\@glsc@combined@#4@main}%
  \letcs\mglscurrentmainlist{\@glsc@combined@#4@list}%
  \letcs\mglscurrentmainoptions{\@glsc@combined@#4@options}%
  \ifblank{#1}%
  {%
    \@glxstrmultientryadjustednamefirstfmt{#2}%
  }%
  {%
    \def\@mgls@previouslabel{}%
    \let\@glsc@xtradjustedother\@glxstrmultientryadjustednamefirstother
    \@for\mglscurrentlabel:=#1\do{%
      \ifx\@mgls@previouslabel\empty
      \else
        \@glxstrmultientryadjustednamesep{\@mgls@previouslabel}{\mglscurrentlabel}%
      \fi
      \@glsc@xtradjustedother{\mglscurrentlabel}%
      \let\@mgls@previouslabel\mglscurrentlabel
      \let\@glsc@xtradjustedother\@glxstrmultientryadjustednameother
    }%
    \@glxstrmultientryadjustednamepresep{\@mgls@previouslabel}{\mglscurrentmainlabel}%
    \@glxstrmultientryadjustednamefmt{#2}%
  }%
  \ifblank{#3}%
  {}%
  {%
    \let\@mgls@previouslabel\mglscurrentmainlabel
    \let\@glsc@xtrmultientryadjustednamesep\@glxstrmultientryadjustednamepostsep
    \@for\mglscurrentlabel:=#3\do{%
      \@glsc@xtrmultientryadjustednamesep{\@mgls@previouslabel}{\mglscurrentlabel}%
      \@glxstrmultientryadjustednameother{\mglscurrentlabel}%
      \let\@mgls@previouslabel\mglscurrentlabel
      \let\@glsc@xtrmultientryadjustednamesep\@glxstrmultientryadjustednamesep
    }%
  }%
}

\glxstrmultientryadjustednamesep

```

```

\newcommand*\glxstrmultientryadjustednamesep{\glsccombinedfirstsepfirst}

multientryadjustednamepresep Separator before main name.
\newcommand*\glxstrmultientryadjustednamepresep{\glxstrmultientryadjustednamesep}

ltientryadjustednamepostsep Separator after main name.
\newcommand*\glxstrmultientryadjustednamepostsep{\glxstrmultientryadjustednamesep}

trmultientryadjustednamefmt
\newcommand*\glxstrmultientryadjustednamefmt[1]{#1}

multientryadjustednameother
\newcommand*\glxstrmultientryadjustednameother[1]{\glsentryname{#1}}

trmultientryadjustednamefmt
\newcommand*\Glsxtrmultientryadjustednamefmt[1]{\glssentencecase{#1}}

multientryadjustednameother
\newcommand*\Glsxtrmultientryadjustednameother[1]{\Glsentryname{#1}}

multientryadjustednameother
\newcommand*\GlsXtrmultientryadjustednameother[1]{%
\glsentrytitlecase{#1}{name}}

trmultientryadjustednamefmt
\ifdef\glscapitalisewords
{%
\newcommand*\GlsXtrmultientryadjustednamefmt[1]{\glscapitalisewords{#1}}
}
{
\newcommand*\GlsXtrmultientryadjustednamefmt[1]{\capitalisewords{#1}}
}

multientryadjustednameother
\newcommand*\GLSxtrmultientryadjustednameother[1]{%
\glssupercase{\glsentryname{#1}}}

trmultientryadjustednamefmt
\newcommand*\GLSxtrmultientryadjustednamefmt[1]{\glssupercase{#1}}

```

Provide missing Greek letters for use in maths mode. These commands are recognised by `bib2gls` and will be mapped to the Mathematical Greek Italic letters. This ensures that the Greek letters that have the same shape as Latin letters are kept with the other mathematical Greek letters for sorting purposes. The \LaTeX version of these commands (provided here) use an upright font for capitals and italic for lower case to provide a better match with the other Greek symbols provided by the kernel.


```

\Alpha
\providecommand*\Alpha{\mathrm{A}}

\Beta
\providecommand*\Beta{\mathrm{B}}

\Epsilon
\providecommand*\Epsilon{\mathrm{E}}

\Zeta
\providecommand*\Zeta{\mathrm{Z}}

\Eta
\providecommand*\Eta{\mathrm{H}}

\Iota
\providecommand*\Iota{\mathrm{I}}

\Kappa
\providecommand*\Kappa{\mathrm{K}}

\Mu
\providecommand*\Mu{\mathrm{M}}

\Nu
\providecommand*\Nu{\mathrm{N}}

\Omicron
\providecommand*\Omicron{\mathrm{O}}

\Rho
\providecommand*\Rho{\mathrm{P}}

\Tau
\providecommand*\Tau{\mathrm{T}}

\Chi
\providecommand*\Chi{\mathrm{X}}

\Digamma
\providecommand*\Digamma{\mathrm{F}}

\omicron
\providecommand*\omicron{\mathit{o}}

```

Provide corresponding upright characters if `upgreek` has been loaded. (The upper case characters are the same as above.)

```

\@ifpackageloaded{upgreek}%
{

```

```

\Upalpha
\providecommand*\Upalpha{\mathrm{A}}

\Upbeta
\providecommand*\Upbeta{\mathrm{B}}

\Upepsilon
\providecommand*\Upepsilon{\mathrm{E}}

\Upzeta
\providecommand*\Upzeta{\mathrm{Z}}

\Upeta
\providecommand*\Upeta{\mathrm{H}}

\Upiota
\providecommand*\Upiota{\mathrm{I}}

\Upkappa
\providecommand*\Upkappa{\mathrm{K}}

\Upmu
\providecommand*\Upmu{\mathrm{M}}

\Upnu
\providecommand*\Upnu{\mathrm{N}}

\Upomicron
\providecommand*\Upomicron{\mathrm{O}}

\Uprho
\providecommand*\Uprho{\mathrm{P}}

\Uptau
\providecommand*\Uptau{\mathrm{T}}

\Upchi
\providecommand*\Upchi{\mathrm{X}}

\upomicron
\providecommand*\upomicron{\mathrm{o}}

}%
{}% upgreek.sty not loaded

```

This package provides some basic rules, but it's not intended for complete coverage of all locales. The CLDR should provide the appropriate locale-sensitive rules. These macros are primarily to help construct custom rules to include, for example, Greek maths symbols mixed with Latin. For the full rule syntax, see the Java API for [RuleBaseCollator](#)

If you want to provide a rule-block for a particular locale to allow for customization within that locale, create a file called `glossariesxtr-<tag>.ldf` (where *<tag>* identifies the locale) and add similar commands. See the description of `\IfTrackedLanguageFileExists` in the `tracklang` manual for the allowed forms of *<tag>*. The simplest is to just use the root language label or ISO code. The file will then be automatically loaded by `glossaries-extra` if the document has support for that language.

When combining these blocks of rules, remember to separate them with the appropriate character. For example:

```
%sort-rule={\glxtrcontrolrules
% ;\glxtrspacerules
% ;\glxtrnonprintablerules
% ;\glxtrcombiningdiacriticrules
% ;\glxtrhyphenrules
% <\glxtrgeneralpuncrules
% <\glxtrdigitrules
% <\glxtrfractionrules
% <\glxtrGeneralLatinIVrules
% <\glxtrMathItalicGreekIrules
%}
%
```

`\glxtrIgnorableRules` A shortcut command for common ignorable characters.

```
\newcommand{\glxtrIgnorableRules}{%
\glxtrcontrolrules
\string;\glxtrspacerules
\string;\glxtrnonprintablerules
}
```

`\glxtrGeneralInitRules` A shortcut command for common initial rules for ignorables, diacritics, punctuation and digits.

```
\newcommand{\glxtrGeneralInitRules}{%
\glxtrIgnorableRules
\string;\glxtrcombiningdiacriticrules
\string;\glxtrhyphenrules
\string<\glxtrgeneralpuncrules
\string<\glxtrdigitrules
\string<\glxtrfractionrules
}
```

`\glxtrGeneralPuncRules` A shortcut command for common punctuation and digits.

```

\newcommand{\glxtrGeneralPuncRules}{%
\glxtrgeneralpuncmarksrules
\string<\glxtrgeneralpuncdotrules
\string<\glxtrgeneralpuncaccentsrules
\string<\glxtrgeneralpuncquoterules
\string<\glxtrgeneralpuncbracketrules
\string<\glxtrgeneralpuncsignrules
\string<\glxtrcurrencyrules
\string<\glxtrgeneralpuncIIrules
\string<\glxtrdigitrules
\string<\glxtrfractionrules
}

```

\glxtrcontrolrules These are control characters that are usually placed at the start of a rule in the ‘ignored characters’ section. These control characters are unlikely to appear in any entry fields but are provided for completeness. (They may appear with the marker commands provided with `--datatool-sort-markers` which emulates the marker commands provided by `datatool-base` for use in the sort hook, in which case those particular control codes shouldn’t be ignored.) `\string` is used for punctuation characters in case they’ve been made active.

```

\newcommand*{\glxtrcontrolrules}{%
\string'\glshex 200B\string'\string=\glshex 200C\string=\glshex 200D
\string=\glshex 200E\string=\glshex 200F\string=\glshex 0000\string=\glshex 0001
\string=\glshex 0002\string=\glshex 0003\string=\glshex 0004\string=\glshex 0005
\string=\glshex 0006\string=\glshex 0007\string=\glshex 0008
\string=\string'\glshex 0009\string'\string=\string'\glshex 000B\string'
\string=\glshex 000E\string=\glshex 000F\string=\string'\glshex
0010\string'\string=\glshex 0011
\string=\glshex 0012\string=\glshex 0013\string=\glshex 0014\string=\glshex 0015
\string=\glshex 0016\string=\glshex 0017\string=\glshex 0018\string=\glshex 0019
\string=\glshex 001A\string=\glshex 001B\string=\glshex 001C\string=\glshex 001D
\string=\glshex 001E\string=\glshex 001F\string=\glshex 007F\string=\glshex 0080
\string=\glshex 0081\string=\glshex 0082\string=\glshex 0083\string=\glshex 0084
\string=\glshex 0085\string=\glshex 0086\string=\glshex 0087\string=\glshex 0088
\string=\glshex 0089\string=\glshex 008A\string=\glshex 008B\string=\glshex 008C
\string=\glshex 008D\string=\glshex 008E\string=\glshex 008F\string=\glshex 0090
\string=\glshex 0091\string=\glshex 0092\string=\glshex 0093\string=\glshex 0094
\string=\glshex 0095\string=\glshex 0096\string=\glshex 0097\string=\glshex 0098
\string=\glshex 0099\string=\glshex 009A\string=\glshex 009B\string=\glshex 009C
\string=\glshex 009D\string=\glshex 009E\string=\glshex 009F
}

```

\glxtrcontrolIrules Subset of control rules. Doesn’t include 0, 1C, 1D, 1E, 1F, and 7F.

```

\newcommand*{\glxtrcontrolIrules}{%
\string'\glshex 200B\string'\string=\glshex 200C\string=\glshex 200D
\string=\glshex 200E\string=\glshex 200F\string=\glshex 0001
\string=\glshex 0002\string=\glshex 0003\string=\glshex 0004\string=\glshex 0005
\string=\glshex 0006\string=\glshex 0007\string=\glshex 0008
\string=\string'\glshex 0009\string'\string=\string'\glshex 000B\string'

```

```

\string=\glshex 000E\string=\glshex 000F\string=\string'\glshex
0010\string'\string=\glshex 0011
\string=\glshex 0012\string=\glshex 0013\string=\glshex 0014\string=\glshex 0015
\string=\glshex 0016\string=\glshex 0017\string=\glshex 0018\string=\glshex 0019
\string=\glshex 001A\string=\glshex 001B\string=\glshex 0080
\string=\glshex 0081\string=\glshex 0082\string=\glshex 0083\string=\glshex 0084
\string=\glshex 0085\string=\glshex 0086\string=\glshex 0087\string=\glshex 0088
\string=\glshex 0089\string=\glshex 008A\string=\glshex 008B\string=\glshex 008C
\string=\glshex 008D\string=\glshex 008E\string=\glshex 008F\string=\glshex 0090
\string=\glshex 0091\string=\glshex 0092\string=\glshex 0093\string=\glshex 0094
\string=\glshex 0095\string=\glshex 0096\string=\glshex 0097\string=\glshex 0098
\string=\glshex 0099\string=\glshex 009A\string=\glshex 009B\string=\glshex 009C
\string=\glshex 009D\string=\glshex 009E\string=\glshex 009F
}

```

`\glxtrcontrolIIrules` Subset of ordered control rules (information separators). Doesn't include 7F.

```

\newcommand*{\glxtrcontrolIIrules}{%
\glshex 001C\string<\glshex 001D
\string<\glshex 001E\string<\glshex 001F
}

```

`\glxtrspacerules` These are space characters.

```

\newcommand*{\glxtrspacerules}{%
\string' \string'\string;
\string'\glshex 00A0\string'\string;
\string'\glshex 2000\string'\string;
\string'\glshex 2001\string'\string;
\string'\glshex 2002\string'\string;
\string'\glshex 2003\string'\string;
\string'\glshex 2004\string'\string;
\string'\glshex 2005\string'\string;
\string'\glshex 2006\string'\string;
\string'\glshex 2007\string'\string;
\string'\glshex 2008\string'\string;
\string'\glshex 2009\string'\string;
\string'\glshex 200A\string'\string;
\string'\glshex 3000\string'
}

```

`\glxtrnonprintablerules` These are non-printable characters (BOM, tabs, line feed and carriage return).

```

\newcommand*{\glxtrnonprintablerules}{%
\string'\glshex FEFF\string'\string;
\string'\glshex 000A\string'\string;
\string'\glshex 0009\string'\string;
\string'\glshex 000C\string'\string;
\string'\glshex 000B\string'
}

```

`\glxtrcombiningdiacriticrules` Combining diacritic marks. This is split into multiple macros.

```

\newcommand*{\glxstrcombiningdiacriticrules}{%
\glxstrcombiningdiacriticIrules\string;
\glxstrcombiningdiacriticIIrules\string;
\glxstrcombiningdiacriticIIIrules\string;
\glxstrcombiningdiacriticIVrules
}

```

glxstrcombiningdiacriticIrules First set of combining diacritic marks.

```

\newcommand*{\glxstrcombiningdiacriticIrules}{%
\glshex 0301\string;% combining acute
\glshex 0300\string;% combining grave
\glshex 0306\string;% combining breve
\glshex 0302\string;% combining circumflex
\glshex 030C\string;% combining caron
\glshex 030A\string;% combining ring
\glshex 030D\string;% combining vertical line above
\glshex 0308\string;% combining diaeresis
\glshex 030B\string;% combining double acute
\glshex 0303\string;% combining tilde
\glshex 0307\string;% combining dot above
\glshex 0304% combining macron
}

```

glxstrcombiningdiacriticIIrules Second set of combining diacritic marks.

```

\newcommand*{\glxstrcombiningdiacriticIIrules}{%
\glshex 0337\string;% combining short solidus overlay
\glshex 0327\string;% combining cedilla
\glshex 0328\string;% combining ogonek
\glshex 0323\string;% combining dot below
\glshex 0332\string;% combining low line
\glshex 0305\string;% combining overline
\glshex 0309\string;% combining hook above
\glshex 030E\string;% combining double vertical line above
\glshex 030F\string;% combining double grave accent
\glshex 0310\string;% combining candrabindu
\glshex 0311\string;% combining inverted breve
\glshex 0312\string;% combining turned comma above
\glshex 0313\string;% combining comma above
\glshex 0314\string;% combining reversed comma above
\glshex 0315\string;% combining comma above right
\glshex 0316\string;% combining grave accent below
\glshex 0317% combining acute accent below
}

```

glxstrcombiningdiacriticIIIrules Third set of combining diacritic marks.

```

\newcommand*{\glxstrcombiningdiacriticIIIrules}{%
\glshex 0318\string;% combining left tack below
\glshex 0319\string;% combining right tack below
\glshex 031A\string;% combining left angle above
}

```

```

\glshex 031B\string;% combining horn
\glshex 031C\string;% combining left half ring below
\glshex 031D\string;% combining up tack below
\glshex 031E\string;% combining down tack below
\glshex 031F\string;% combining plus sign below
\glshex 0320\string;% combining minus sign below
\glshex 0321\string;% combining palatalized hook below
\glshex 0322\string;% combining retroflex hook below
\glshex 0324\string;% combining diaeresis below
\glshex 0325\string;% combining ring below
\glshex 0326\string;% combining comma below
\glshex 0329\string;% combining vertical line below
\glshex 032A\string;% combining bridge below
\glshex 032B\string;% combining inverted double arch below
\glshex 032C\string;% combining caron below
\glshex 032D\string;% combining circumflex accent below
\glshex 032E\string;% combining breve below
\glshex 032F\string;% combining inverted breve below
\glshex 0330\string;% combining tilde below
\glshex 0331\string;% combining macron below
\glshex 0333\string;% combining double low line
\glshex 0334\string;% combining tilde overlay
\glshex 0335\string;% combining short stroke overlay
\glshex 0336\string;% combining long stroke overlay
\glshex 0338\string;% combining long solidus overlay
\glshex 0339\string;% combining combining right half ring below
\glshex 033A\string;% combining inverted bridge below
\glshex 033B\string;% combining square below
\glshex 033C\string;% combining seagull below
\glshex 033D\string;% combining x above
\glshex 033E\string;% combining vertical tilde
\glshex 033F\string;% combining double overline
\glshex 0342\string;% combining Greek perispomeni
\glshex 0344\string;% combining Greek dialytika tonos
\glshex 0345\string;% combining Greek ypogegrammeni
\glshex 0360\string;% combining double tilde
\glshex 0361\string;% combining double inverted breve
\glshex 0483\string;% combining Cyrillic titlo
\glshex 0484\string;% combining Cyrillic palatalization
\glshex 0485\string;% combining Cyrillic dasia pneumata
\glshex 0486% combining Cyrillic psili pneumata
}

```

trcombiningdiacriticIVrules Fourth set of combining diacritic marks.

```

\newcommand*{\glxtrcombiningdiacriticIVrules}{%
\glshex 20D0\string;% combining left harpoon above
\glshex 20D1\string;% combining right harpoon above
\glshex 20D2\string;% combining long vertical line overlay
\glshex 20D3\string;% combining short vertical line overlay
\glshex 20D4\string;% combining anticlockwise arrow above
}

```

```

\glshex 20D5\string;% combining clockwise arrow above
\glshex 20D6\string;% combining left arrow above
\glshex 20D7\string;% combining right arrow above
\glshex 20D8\string;% combining ring overlay
\glshex 20D9\string;% combining clockwise ring overlay
\glshex 20DA\string;% combining anticlockwise ring overlay
\glshex 20DB\string;% combining three dots above
\glshex 20DC\string;% combining four dots above
\glshex 20DD\string;% combining enclosing circle
\glshex 20DE\string;% combining enclosing square
\glshex 20DF\string;% combining enclosing diamond
\glshex 20E0\string;% combining enclosing circle backslash
\glshex 20E1% combining left right arrow above
}

```

`\glxtrhyphenrules` Hyphens.

```

\newcommand*{\glxtrhyphenrules}{%
\glxtrhyphenrules\string;% hyphens
\glxtrminusrules% minus signs
}

```

`\glxtrhyphenrules` Textual hyphens.

```

\newcommand*{\glxtrhyphenrules}{%
\string'\string-\string'\string;% ASCII hyphen
\glshex 00AD\string;% soft hyphen
\glshex 2010\string;% hyphen
\glshex 2011\string;% non-breaking hyphen
\glshex 2012\string;% figure dash
\glshex 2013\string;% en dash
\glshex 2014\string;% em dash
\glshex 2015% horizontal bar
}

```

`\glxtrhyphenIIrules` Alternative rule for textual hyphens.

```

\newcommand*{\glxtrhyphenIIrules}{%
\string'\string-\string'% ASCII hyphen
\string<\glshex 00AD% soft hyphen
\string<\glshex 2010% hyphen
\string<\glshex 2011% non-breaking hyphen
\string<\glshex 2012% figure dash
\string<\glshex 2013% en dash
\string<\glshex 2014% em dash
\string<\glshex 2015% horizontal bar
}

```

`\glxtrminusrules` Minus signs.

```

\newcommand*{\glxtrminusrules}{%
\glshex 2212\string=\glshex 207B\string=\glshex 208B% minus sign
}

```



```

\glxstrgeneralpuncrules General punctuation.
    \newcommand*{\glxstrgeneralpuncrules}{%
        \glxstrgeneralpuncIrules
        \string<\glxstrcurrencyrules
        \string<\glxstrgeneralpuncIIrules
    }

\glxstrgeneralpuncIrules First set of general punctuation.
    \newcommand*{\glxstrgeneralpuncIrules}{%
        \glxstrgeneralpuncmarksrules
        \string<\glxstrgeneralpuncaccentsrules
        \string<\glxstrgeneralpuncquoterules
        \string<\glxstrgeneralpuncbracketrules
        \string<\glxstrgeneralpuncsignrules
    }

\glxstrgeneralpuncmarksrules Punctuation marks subset.
    \newcommand*{\glxstrgeneralpuncmarksrules}{%
        \string'\glshex 005F\string'% underscore
        \string<\glshex 00AF\string'% macron
        \string<\string'\glshex 002C\string'% comma
        \string<\string'\glshex 003B\string'% semi-colon
        \string<\string'\glshex 003A\string'% colon
        \string<\string'\glshex 0021\string'% exclamation mark
        \string<\glshex 00A1\string'% inverted exclamation mark
        \string<\string'\glshex 003F\string'% question mark
        \string<\glshex 00BF\string'% inverted question mark
        \string<\string'\glshex 002F\string'% solidus
        \string<\string'\glshex 002E\string'% full stop
    }

\glxstrgeneralpuncdotrules Punctuation marks subset: dots.
    \newcommand*\glxstrgeneralpuncdotrules{%
        \glshex 2024% one dot leader
        \string<\glshex 2025% two dot leader
        \string<\glshex 2026% horizontal ellipsis
        \string<\glshex 204F% reversed semicolon
        \string<\glshex 205A% vertical two dots
        \string<\glshex 205D% vertical three dots
        \string<\glshex 205E% vertical four dots
        \string<\glshex 2056% three dot punctuation
        \string<\glshex 2058% four dot punctuation
        \string<\glshex 2059% five dot punctuation
        \string<\glshex 205B% four dot mark
        \string<\glshex 203B% reference mark
        \string<\glshex 203C% dotted cross
    }

\glxstrgeneralpuncaccentsrules Punctuation marks subset: accent characters.

```

```

\newcommand*{\glxtrgeneralpuncaccentsrules}{%
\glshex 00B4% acute accent
\string<\string'\glshex 0060\string'% grave accent
\string<\string'\glshex 005E\string'% circumflex accent
\string<\glshex 00A8% diaersis
\string<\string'\glshex 007E\string'% tilde
\string<\glshex 00B7% middle dot
\string<\glshex 00B8% cedilla
}

\glxtrgeneralpuncquoterules Punctuation marks subset: quotes.
\newcommand*{\glxtrgeneralpuncquoterules}{%
\string'\glshex 0027\string'% straight apostrophe
\string<\string'\glshex 0022\string'% straight double quote
\string<\glshex 00AB% left guillemet
\string<\glshex 00BB% right guillemet
}

\glxtrgeneralpuncbracketrules Punctuation marks subset: brackets. May be redefined to include extra bracket
subsets.
\newcommand*{\glxtrgeneralpuncbracketrules}{%
\glxtrgeneralpuncbracketIrules
}

\glxtrgeneralpuncbracketIrules First set of bracket rules (general brackets).
\newcommand*{\glxtrgeneralpuncbracketIrules}{%
\string'\glshex 0028\string'% left parenthesis
\string=\glshex 207D\string=\glshex 208D% super/subscript left parenthesis
\string<\string'\glshex 0029\string'% right parenthesis
\string=\glshex 207E\string=\glshex 208E% super/subscript right parenthesis
\string<\string'\glshex 005B\string'% left square bracket
\string<\string'\glshex 005D\string'% right square bracket
\string<\string'\glshex 007B\string'% left curly bracket
\string<\string'\glshex 007D\string'% right curly bracket
v1.56 added:
\string<\glshex 2045% left square bracket with quill
\string<\glshex 2046% right square bracket with quill
\string<\glshex 2329% left angle bracket
\string<\glshex 232A% right angle bracket
}

\glxtrgeneralpuncbracketIIrules Second set of bracket rules (miscellaneous mathematical symbols-A).
\newcommand*{\glxtrgeneralpuncbracketIIrules}{%
\glshex 27E6% mathematical left white square bracket
\string<\glshex 27E7% mathematical right white square bracket
\string<\glshex 27E8% mathematical left angle bracket
\string<\glshex 27E9% mathematical right angle bracket
\string<\glshex 27EA% mathematical left chevron bracket
\string<\glshex 27EB% mathematical right chevron bracket

```

```

\string<\glshex 27EC% mathematical left white tortoise shell bracket
\string<\glshex 27ED% mathematical right white tortoise shell bracket
\string<\glshex 27EE% mathematical left flattened parenthesis
\string<\glshex 27EF% mathematical right flattened parenthesis
}

```

rgeneralpuncbracketIIIrules Third set of bracket rules (miscellaneous mathematical symbols-B).

```

\newcommand*\glxtrgeneralpuncbracketIIIrules{%
\glshex 2983% left white curly bracket
\string<\glshex 2984% right white curly bracket
\string<\glshex 2985% left white parenthesis
\string<\glshex 2986% right white parenthesis
\string<\glshex 2987% left image bracket
\string<\glshex 2988% right image bracket
\string<\glshex 2989% left binding bracket
\string<\glshex 298A% right binding bracket
\string<\glshex 298B% left square bracket with underbar
\string<\glshex 298C% right square bracket with underbar
\string<\glshex 298D% left square bracket with top tick
\string<\glshex 298E% right square bracket with bottom tick
\string<\glshex 298F% left square bracket with bottom tick
\string<\glshex 2990% right square bracket with top tick
\string<\glshex 2991% left angle bracket with dot
\string<\glshex 2992% right angle bracket with dot
\string<\glshex 2993% left arc less-than bracket
\string<\glshex 2994% right arc greater-than bracket
\string<\glshex 2995% double left arc less-than bracket
\string<\glshex 2996% double right arc greater-than bracket
\string<\glshex 2997% left black tortoise shell bracket
\string<\glshex 2998% right black tortoise shell bracket
\string<\glshex 29FC% left curved angle bracket
\string<\glshex 29FD% right curved angle bracket
}

```

trgeneralpuncbracketIVrules Fourth set of bracket rules (dingbat brackets). Quotation marks not included.
They should go with other quote marks,

```

\newcommand*\glxtrgeneralpuncbracketIVrules{%
\glshex 2768% medium left parenthesis ornament
\string<\glshex 2769% medium right parenthesis ornament
\string<\glshex 276A% medium flattened left parenthesis ornament
\string<\glshex 276B% medium flattened right parenthesis ornament
\string<\glshex 276C% medium left angle bracket ornament
\string<\glshex 276D% medium right angle bracket ornament
\string<\glshex 2770% heavy left angle bracket ornament
\string<\glshex 2771% heavy right angle bracket ornament
\string<\glshex 2772% light left tortoise shell bracket ornament
\string<\glshex 2773% light right tortoise shell bracket ornament
\string<\glshex 2774% medium left curly bracket ornament
\string<\glshex 2775% medium right curly bracket ornament
}

```

\glxtrgeneralpuncsignrules Punctuation marks subset: signs.

```
\newcommand*{\glxtrgeneralpuncsignrules}{%
\glshex 00A7% section sign
\string<\glshex 00B6% pilcrow sign
\string<\glshex 00A9% copyright sign
\string<\glshex 00AE% registered sign
\string<\string'\glshex 0040\string'% at sign
}
```

\glxtrcurrencyrules General punctuation.

```
\newcommand*{\glxtrcurrencyrules}{%
\glshex 00A4% currency sign
\string<\glshex 0E3F% Thai currency symbol baht
\string<\glshex 00A2% cent sign
\string<\glshex 20A1% colon sign
\string<\glshex 20A2% cruzeiro sign
\string<\string'\glshex 0024\string'% dollar sign
\string<\glshex 20AB% dong sign
\string<\glshex 20AC% euro sign
\string<\glshex 20A3% French franc sign
\string<\glshex 20A4% lira sign
\string<\glshex 20A5% mill sign
\string<\glshex 20A6% naira sign
\string<\glshex 20A7% peseta sign
\string<\glshex 00A3% pound sign
\string<\glshex 20A8% rupee sign
\string<\glshex 20AA% new sheqel sign
\string<\glshex 20A9% won sign
\string<\glshex 00A5% yen sign
}
```

\glxtrgeneralpuncIIrules Second set of general punctuation.

```
\newcommand*{\glxtrgeneralpuncIIrules}{%
\string'\glshex 002A\string'% asterisk
\string<\string'\glshex 005C\string'% backslash
\string<\string'\glshex 0026\string'% ampersand
\string<\string'\glshex 0023\string'% hash sign
\string<\string'\glshex 0025\string'% percent sign
\string<\string'\glshex 002B\string'% plus sign
\string=>\glshex 207A\string=>\glshex 208A% super/subscript plus sign
\string<\glshex 00B1% plus-minus sign
\string<\glshex 00F7% division sign
\string<\glshex 00D7% multiplication sign
\string<\string'\glshex 003C\string'% less-than sign
\string<\string'\glshex 003D\string'% equals sign
\string<\string'\glshex 003E\string'% greater-than sign
\string<\glshex 00AC% not sign
\string<\string'\glshex 007C\string'% vertical bar (pipe)
\string<\glshex 00A6% broken bar
}
```

```

\string<\glshex 00B0% degree sign
\string<\glshex 00B5% micron sign
}

```

\glxtrgeneralpuncIIIrules Alternative set of general punctuation.

```

\newcommand*{\glxtrgeneralpuncIIIrules}{%
\string'\glshex 002A\string'% asterisk
\string<\string'\glshex 005C\string'% backslash
\string<\string'\glshex 0026\string'% ampersand
\string<\string'\glshex 0023\string'% hash sign
\string<\string'\glshex 0025\string'% percent sign
\string<\glxtrhyphenIIrules % hyphens
\string<\glshex 2052% commercial minus sign
\string<\glxtrminusrules % minus signs
\string<\string'\glshex 002B\string'% plus sign
\string=\glshex 207A\string=\glshex 208A% super/subscript plus sign
\string<\glshex 00B1% plus-minus sign
\string<\glshex 00F7% division sign
\string<\glshex 00D7% multiplication sign
\string<\string'\glshex 003C\string'% less-than sign
\string<\string'\glshex 003D\string'% equals sign
\string<\string'\glshex 003E\string'% greater-than sign
\string<\glshex 00AC% not sign
\string<\string'\glshex 007C\string'% vertical bar (pipe)
\string<\glshex 00A6% broken bar
\string<\glshex 00B0% degree sign
\string<\glshex 00B5% micron sign
}

```

\glxtrGeneralLatinIrules Basic Latin alphabet.

```

\newcommand*{\glxtrGeneralLatinIrules}{%
\glxtrLatinA
\string<b,B%
\string<c,C%
\string<d,D%
\string<\glxtrLatinE
\string<f,F%
\string<g,G%
\string<\glxtrLatinH
\string<\glxtrLatinI
\string<j,J%
\string<\glxtrLatinK
\string<\glxtrLatinL
\string<\glxtrLatinM
\string<\glxtrLatinN
\string<\glxtrLatinO
\string<\glxtrLatinP
\string<q,Q%
\string<r,R%
\string<\glxtrLatinS

```

```

\string<\glxtrLatinT
\string<u,U%
\string<v,V%
\string<w,W%
\string<\glxtrLatinX
\string<y,Y%
\string<z,Z
}

```

`\glxtrGeneralLatinIIrules` General Latin alphabet (eth between D and E, ð treated as SS).

```

\newcommand*{\glxtrGeneralLatinIIrules}{%
\glxtrLatinA
\string<b,B%
\string<c,C%
\string<d,D%
\string<\glxtrLatinEth
\string<\glxtrLatinE
\string<f,F%
\string<g,G%
\string<\glxtrLatinH
\string<\glxtrLatinI
\string<j,J%
\string<\glxtrLatinK
\string<\glxtrLatinL
\string<\glxtrLatinM
\string<\glxtrLatinN
\string<\glxtrLatinO
\string<\glxtrLatinP
\string<q,Q%
\string<r,R%
\string<\glxtrLatinS
\string& SS \string, \glxtrLatinEszettSs
\string<\glxtrLatinT
\string<u,U%
\string<v,V%
\string<w,W%
\string<\glxtrLatinX
\string<y,Y%
\string<z,Z%
}

```

`\glxtrGeneralLatinIIIrules` General Latin alphabet (eth between D and E, ð treated as SZ).

```

\newcommand*{\glxtrGeneralLatinIIIrules}{%
\glxtrLatinA
\string<b,B%
\string<c,C%
\string<d,D%
\string<\glxtrLatinEth
\string<\glxtrLatinE
\string<f,F%

```

```

\string<g,G%
\string<\glxtrLatinH
\string<\glxtrLatinI
\string<j,J%
\string<\glxtrLatinK
\string<\glxtrLatinL
\string<\glxtrLatinM
\string<\glxtrLatinN
\string<\glxtrLatinO
\string<\glxtrLatinP
\string<q,Q%
\string<r,R%
\string<\glxtrLatinS
\string& SZ, \glxtrLatinEszettSz
\string<\glxtrLatinT
\string<u,U%
\string<v,V%
\string<w,W%
\string<\glxtrLatinX
\string<y,Y%
\string<z,Z%
}

```

`\glxtrGeneralLatinIVrules` General Latin alphabet (Æ treated as AE and Ætreated as OE, Þtreated as TH, ð treated as SS, eth between D and E).

```

\newcommand*{\glxtrGeneralLatinIVrules}{%
\glxtrLatinA
\string& AE , \glxtrLatinAELigature
\string<b,B%
\string<c,C%
\string<d,D%
\string<\glxtrLatinEth
\string<\glxtrLatinE
\string<f,F%
\string<g,G%
\string<\glxtrLatinH
\string<\glxtrLatinI
\string<j,J%
\string<\glxtrLatinK
\string<\glxtrLatinL
\string<\glxtrLatinM
\string<\glxtrLatinN
\string<\glxtrLatinO
\string& OE , \glxtrLatinOELigature
\string<\glxtrLatinP
\string<q,Q%
\string<r,R%
\string<\glxtrLatinS
\string& SS , \glxtrLatinEszettSs
\string<\glxtrLatinT

```

```

\string& th =\glshex 00DE
\string& TH =\glshex 00FE
\string<u,U%
\string<v,V%
\string<w,W%
\string<\glxtrLatinX
\string<y,Y%
\string<z,Z%
}

```

`\glxtrGeneralLatinVrules` General Latin alphabet (eth between D and E, ß treated as SS, P treated as TH).

```

\newcommand*{\glxtrGeneralLatinVrules}{%
\glxtrLatinA
\string<b,B%
\string<c,C%
\string<d,D%
\string<\glxtrLatinEth
\string<\glxtrLatinE
\string<f,F%
\string<g,G%
\string<\glxtrLatinH
\string<\glxtrLatinI
\string<j,J%
\string<\glxtrLatinK
\string<\glxtrLatinL
\string<\glxtrLatinM
\string<\glxtrLatinN
\string<\glxtrLatinO
\string<\glxtrLatinP
\string<q,Q%
\string<r,R%
\string<\glxtrLatinS
\string& SS , \glxtrLatinEszettSs
\string<\glxtrLatinT
\string& th =\glshex 00DE
\string& TH =\glshex 00FE
\string<u,U%
\string<v,V%
\string<w,W%
\string<\glxtrLatinX
\string<y,Y%
\string<z,Z%
}

```

`\glxtrGeneralLatinVrules` General Latin alphabet (eth between D and E, ß treated as SZ, P treated as TH).

```

\newcommand*{\glxtrGeneralLatinVrules}{%
\glxtrLatinA

```



```

\string<b,B%
\string<c,C%
\string<d,D%
\string<\glxtrLatinEth
\string<\glxtrLatinE
\string<f,F%
\string<g,G%
\string<\glxtrLatinH
\string<\glxtrLatinI
\string<j,J%
\string<\glxtrLatinK
\string<\glxtrLatinL
\string<\glxtrLatinM
\string<\glxtrLatinN
\string<\glxtrLatinO
\string<\glxtrLatinP
\string<q,Q%
\string<r,R%
\string<\glxtrLatinS
\string& SZ , \glxtrLatinEszettSz
\string<\glxtrLatinT
\string& th =\glshex 00DE
\string& TH =\glshex 00FE
\string<u,U%
\string<v,V%
\string<w,W%
\string<\glxtrLatinX
\string<y,Y%
\string<z,Z%
}

```

`\glxtrGeneralLatinVIIrules` General Latin alphabet (Æ between A and B, eth between D and E, insular G as G, (E between O and P, long S equivalent to S, Þ between T and U and wynn as W).

```

\newcommand*{\glxtrGeneralLatinVIIrules}{%
\glxtrLatinA
\string<\glxtrLatinAELigature
\string<b,B%
\string<c,C%
\string<d,D%
\string<\glxtrLatinEth
\string<\glxtrLatinE
\string<f,F%
\string<\glxtrLatinInsularG
\string<\glxtrLatinH
\string<\glxtrLatinI
\string<j,J%
\string<\glxtrLatinK
\string<\glxtrLatinL
\string<\glxtrLatinM

```

```

\string<\glxtrLatinN
\string<\glxtrLatinO
\string<\glxtrLatinOELigature
\string<\glxtrLatinP
\string<q,Q%
\string<r,R%
\string<\glshex 017F=\glxtrLatinS % s and long s
\string<\glxtrLatinT
\string<\glxtrLatinThorn
\string<u,U%
\string<v,V%
\string< w\string=\glshex 01BF, W\string=\glshex 01F7
\string<\glxtrLatinX
\string<y,Y%
\string<z,Z%
}

```

`\glxtrGeneralLatinVIIIrules` General Latin alphabet (Æ treated as AE and Æ treated as OE, Þ treated as TH, ð treated as SS, eth treated as D, Ø treated as O, Ł treated as L).

```

\newcommand*{\glxtrGeneralLatinVIIIrules}{%
\glxtrLatinA
\string& AE , \glxtrLatinAELigature
\string<b,B%
\string<c,C%
\string<\glshex 00F0\string;d,\glshex 00D0\string;D% D and eth
\string<\glxtrLatinE
\string<f,F%
\string<g,G%
\string<\glxtrLatinH
\string<\glxtrLatinI
\string<j,J%
\string<\glxtrLatinK
\string<\glshex 0142\string=\glxtrLatinL\string=\glshex 0141% L and \L
\string<\glxtrLatinM
\string<\glxtrLatinN
\string<\glshex 00F8\string=\glxtrLatinO\string=\glshex 00D8% O and \O
\string& OE , \glxtrLatinOELigature
\string<\glxtrLatinP
\string<q,Q%
\string<r,R%
\string<\glxtrLatinS
\string& SS , \glxtrLatinEszettSs
\string<\glxtrLatinT
\string& th =\glshex 00DE
\string& TH =\glshex 00FE
\string<u,U%
\string<v,V%
\string<w,W%
\string<\glxtrLatinX
\string<y,Y%
}

```

```

\string<z,Z%
}

```

Fragments.

`\glstrGeneralLatinAtoMrules` Basic Latin alphabet A–M.

```

\newcommand*{\glstrGeneralLatinAtoMrules}{%
\glstrLatinA
\string<b,B%
\string<c,C%
\string<d,D%
\string<\glstrLatinE
\string<f,F%
\string<g,G%
\string<\glstrLatinH
\string<\glstrLatinI
\string<j,J%
\string<\glstrLatinK
\string<\glstrLatinL
\string<\glstrLatinM
}

```

`\glstrGeneralLatinNtoZrules` Basic Latin alphabet N–Z.

```

\newcommand*{\glstrGeneralLatinNtoZrules}{%
\string<\glstrLatinN
\string<\glstrLatinO
\string<\glstrLatinP
\string<q,Q%
\string<r,R%
\string<\glstrLatinS
\string<\glstrLatinT
\string<u,U%
\string<v,V%
\string<w,W%
\string<\glstrLatinX
\string<y,Y%
\string<z,Z
}

```

`\glstrGeneralLatinAtoGrules` Basic Latin alphabet A–G.

```

\newcommand*{\glstrGeneralLatinAtoGrules}{%
\glstrLatinA
\string<b,B%
\string<c,C%
\string<d,D%
\string<\glstrLatinE
\string<f,F%
\string<g,G%
}

```

```

\glxtrGeneralLatinHtoMrules Basic Latin alphabet H–M.
    \newcommand*{\glxtrGeneralLatinHtoMrules}{%
        \string<\glxtrLatinH
        \string<\glxtrLatinI
        \string<j,J%
        \string<\glxtrLatinK
        \string<\glxtrLatinL
        \string<\glxtrLatinM
    }

\glxtrGeneralLatinNtoSrules Basic Latin alphabet N–S.
    \newcommand*{\glxtrGeneralLatinNtoSrules}{%
        \string<\glxtrLatinN
        \string<\glxtrLatinO
        \string<\glxtrLatinP
        \string<q,Q%
        \string<r,R%
        \string<\glxtrLatinS
    }

\glxtrGeneralLatinTtoZrules Basic Latin alphabet T–Z.
    \newcommand*{\glxtrGeneralLatinTtoZrules}{%
        \string<\glxtrLatinT
        \string<u,U%
        \string<v,V%
        \string<w,W%
        \string<\glxtrLatinX
        \string<y,Y%
        \string<z,Z
    }

\glxtrLatinA
    \newcommand*{\glxtrLatinA}{%
        a\string=\glshex 00AA\string=\glshex 2090,A
    }

\glxtrLatinE
    \newcommand*{\glxtrLatinE}{%
        e\string=\glshex 2091,E
    }

\glxtrLatinH
    \newcommand*{\glxtrLatinH}{%
        h\string=\glshex 2095,H
    }

\glxtrLatinI
    \newcommand*{\glxtrLatinI}{%
        i\string=\glshex 2071,I
    }

```

```

\glxtrLatinK
    \newcommand*{\glxtrLatinK}{%
        k\string=\glshex 2096,K
    }

\glxtrLatinL
    \newcommand*{\glxtrLatinL}{%
        l\string=\glshex 2097,L
    }

\glxtrLatinM
    \newcommand*{\glxtrLatinM}{%
        m\string=\glshex 2098,M
    }

\glxtrLatinN
    \newcommand*{\glxtrLatinN}{%
        n\string=\glshex 207F\string=\glshex 2099,N
    }

\glxtrLatinO
    \newcommand*{\glxtrLatinO}{%
        o\string=\glshex 00BA\string=\glshex 2092,O
    }

\glxtrLatinP
    \newcommand*{\glxtrLatinP}{%
        p\string=\glshex 209A,P
    }

\glxtrLatinS
    \newcommand*{\glxtrLatinS}{%
        s\string=\glshex 209B,S
    }

\glxtrLatinT
    \newcommand*{\glxtrLatinT}{%
        t\string=\glshex 209C,T
    }

\glxtrLatinX
    \newcommand*{\glxtrLatinX}{%
        x\string=\glshex 2093,X
    }

\glxtrLatinSchwa Latin schwa (lower case, subscript and upper case).
    \newcommand*{\glxtrLatinSchwa}{%
        \glshex 0259\string=\glshex 2094,\glshex 018F
    }

```

```

\glxtrLatinEszettSs SS=ss
    \newcommand*{\glxtrLatinEszettSs}{%
    \glshex 00DF% eszett
    \string=\glshex 017Fs % "long S"s
    }

\glxtrLatinEszettSz SS=sz
    \newcommand*{\glxtrLatinEszettSz}{%
    \glshex 00DF% eszett
    \string= \glshex 017Fz % "long S"z
    }

\glxtrLatinEth
    \newcommand*{\glxtrLatinEth}{%
    \glshex 00F0,\glshex 00D0% eth
    }

\glxtrLatinThorn
    \newcommand*{\glxtrLatinThorn}{%
    \glshex 00FE,\glshex 00DE% thorn
    }

\glxtrLatinAELigature
    \newcommand*{\glxtrLatinAELigature}{%
    \glshex 00E6,\glshex 00C6% AE-ligature
    }

\glxtrLatinOELigature
    \newcommand*{\glxtrLatinOELigature}{%
    \glshex 0153,\glshex 0152% OE-ligature
    }

\glxtrLatinAA
    \newcommand*{\glxtrLatinAA}{%
    \glshex 00E5=a\glshex 030A,% \aa
    \glshex 00C5=A\glshex 030A% \AA
    }

\glxtrLatinWynn
    \newcommand*{\glxtrLatinWynn}{%
    \glshex 01BF,\glshex 01F7% wynn
    }

\glxtrLatinInsularG
    \newcommand*{\glxtrLatinInsularG}{%
    \glshex 1D79,\glshex A77D% insular G
    \string; g, G
    }

```

```

\glxtrLatinOslash
\newcommand*{\glxtrLatinOslash}{%
\glshex 00F8,\glshex 00D8% \o, \O
}

```

```

\glxtrLatinLslash
\newcommand*{\glxtrLatinLslash}{%
\glshex 0142,\glshex 0141% \l, \L
}

```

`\glxtrMathUpGreekIrules` Includes digamma between epsilon and zeta.

```

\newcommand*{\glxtrMathUpGreekIrules}{%
\glxtrUpAlpha
\string<\glxtrUpBeta
\string<\glxtrUpGamma
\string<\glxtrUpDelta
\string<\glxtrUpEpsilon
\string<\glxtrUpDigamma
\string<\glxtrUpZeta
\string<\glxtrUpEta
\string<\glxtrUpTheta
\string<\glxtrUpIota
\string<\glxtrUpKappa
\string<\glxtrUpLambda
\string<\glxtrUpMu
\string<\glxtrUpNu
\string<\glxtrUpXi
\string<\glxtrUpOmicron
\string<\glxtrUpPi
\string<\glxtrUpRho
\string<\glxtrUpSigma
\string<\glxtrUpTau
\string<\glxtrUpUpsilon
\string<\glxtrUpPhi
\string<\glxtrUpChi
\string<\glxtrUpPsi
\string<\glxtrUpOmega
}

```

`\glxtrMathUpGreekIIrules` Doesn't include digamma.

```

\newcommand*{\glxtrMathUpGreekIIrules}{%
\glxtrUpAlpha
\string<\glxtrUpBeta
\string<\glxtrUpGamma
\string<\glxtrUpDelta
\string<\glxtrUpEpsilon
\string<\glxtrUpZeta
\string<\glxtrUpEta
\string<\glxtrUpTheta

```

```

\string<\glxtrUpIota
\string<\glxtrUpKappa
\string<\glxtrUpLambda
\string<\glxtrUpMu
\string<\glxtrUpNu
\string<\glxtrUpXi
\string<\glxtrUpOmicron
\string<\glxtrUpPi
\string<\glxtrUpRho
\string<\glxtrUpSigma
\string<\glxtrUpTau
\string<\glxtrUpUpsilon
\string<\glxtrUpPhi
\string<\glxtrUpChi
\string<\glxtrUpPsi
\string<\glxtrUpOmega
}

```

`\glxtrMathItalicGreekIrules` Includes (upright) digamma between epsilon and zeta (there isn't an italic digamma), so don't mix with `\glxtrMathUpGreekIrules` or there may be unexpected results.

```

\newcommand*{\glxtrMathItalicGreekIrules}{%
\glxtrMathItalicAlpha
\string<\glxtrMathItalicBeta
\string<\glxtrMathItalicGamma
\string<\glxtrMathItalicDelta
\string<\glxtrMathItalicEpsilon
\string<\glxtrUpDigamma
\string<\glxtrMathItalicZeta
\string<\glxtrMathItalicEta
\string<\glxtrMathItalicTheta
\string<\glxtrMathItalicIota
\string<\glxtrMathItalicKappa
\string<\glxtrMathItalicLambda
\string<\glxtrMathItalicMu
\string<\glxtrMathItalicNu
\string<\glxtrMathItalicXi
\string<\glxtrMathItalicOmicron
\string<\glxtrMathItalicPi
\string<\glxtrMathItalicRho
\string<\glxtrMathItalicSigma
\string<\glxtrMathItalicTau
\string<\glxtrMathItalicUpsilon
\string<\glxtrMathItalicPhi
\string<\glxtrMathItalicChi
\string<\glxtrMathItalicPsi
\string<\glxtrMathItalicOmega
}

```


`\glxstrMathItalicGreekIIrules` Doesn't include digamma.

```
\newcommand*{\glxstrMathItalicGreekIIrules}{%
  \glxstrMathItalicAlpha
  \string<\glxstrMathItalicBeta
  \string<\glxstrMathItalicGamma
  \string<\glxstrMathItalicDelta
  \string<\glxstrMathItalicEpsilon
  \string<\glxstrMathItalicZeta
  \string<\glxstrMathItalicEta
  \string<\glxstrMathItalicTheta
  \string<\glxstrMathItalicIota
  \string<\glxstrMathItalicKappa
  \string<\glxstrMathItalicLambda
  \string<\glxstrMathItalicMu
  \string<\glxstrMathItalicNu
  \string<\glxstrMathItalicXi
  \string<\glxstrMathItalicOmicron
  \string<\glxstrMathItalicPi
  \string<\glxstrMathItalicRho
  \string<\glxstrMathItalicSigma
  \string<\glxstrMathItalicTau
  \string<\glxstrMathItalicUpsilon
  \string<\glxstrMathItalicPhi
  \string<\glxstrMathItalicChi
  \string<\glxstrMathItalicPsi
  \string<\glxstrMathItalicOmega
}
```

`\glxstrMathItalicUpperGreekIrules` Upper case only (includes upright digamma).

```
\newcommand*{\glxstrMathItalicUpperGreekIrules}{%
  \glshex 1D6E2% upper case alpha (maths italic)
  \string<\glshex 1D6E3% upper case beta (maths italic)
  \string<\glshex 1D6E4% upper case gamma (maths italic)
  \string<\glshex 1D6E5% upper case delta (maths italic)
  \string<\glshex 1D6E6% upper case epsilon (maths italic)
  \string<\glshex 03DC% upper case digamma
  \string<\glshex 1D6E7% upper case zeta (maths italic)
  \string<\glshex 1D6E8% upper case eta (maths italic)
  \string<\glshex 1D6E9% upper case theta (maths italic)
  \string=<\glshex 1D6F3% upper case theta variant (maths italic)
  \string<\glshex 1D6EA% upper case iota (maths italic)
  \string<\glshex 1D6EB% upper case kappa (maths italic)
  \string<\glshex 1D6EC% upper case lambda (maths italic)
  \string<\glshex 1D6ED% upper case mu (maths italic)
  \string<\glshex 1D6EE% upper case nu (maths italic)
  \string<\glshex 1D6EF% upper case xi (maths italic)
  \string<\glshex 1D6F0% upper case omicron (maths italic)
  \string<\glshex 1D6F1% upper case pi (maths italic)
  \string<\glshex 1D6F2% upper case rho (maths italic)
  \string<\glshex 1D6F4% upper case sigma (maths italic)
```

```

\string<\glshex 1D6F5% upper case tau (maths italic)
\string<\glshex 1D6F6% upper case upsilon (maths italic)
\string<\glshex 1D6F7% upper case phi (maths italic)
\string<\glshex 1D6F8% upper case chi (maths italic)
\string<\glshex 1D6F9% upper case psi (maths italic)
\string<\glshex 1D6FA% upper case omega (maths italic)
}

```

MathItalicUpperGreekIIrules Upper case only (doesn't include upright digamma).

```

\newcommand*{\glxtrMathItalicUpperGreekIIrules}{%
\glshex 1D6E2% upper case alpha (maths italic)
\string<\glshex 1D6E3% upper case beta (maths italic)
\string<\glshex 1D6E4% upper case gamma (maths italic)
\string<\glshex 1D6E5% upper case delta (maths italic)
\string<\glshex 1D6E6% upper case epsilon (maths italic)
\string<\glshex 1D6E7% upper case zeta (maths italic)
\string<\glshex 1D6E8% upper case eta (maths italic)
\string<\glshex 1D6E9% upper case theta (maths italic)
\string=<\glshex 1D6F3% upper case theta variant (maths italic)
\string<\glshex 1D6EA% upper case iota (maths italic)
\string<\glshex 1D6EB% upper case kappa (maths italic)
\string<\glshex 1D6EC% upper case lambda (maths italic)
\string<\glshex 1D6ED% upper case mu (maths italic)
\string<\glshex 1D6EE% upper case nu (maths italic)
\string<\glshex 1D6EF% upper case xi (maths italic)
\string<\glshex 1D6F0% upper case omicron (maths italic)
\string<\glshex 1D6F1% upper case pi (maths italic)
\string<\glshex 1D6F2% upper case rho (maths italic)
\string<\glshex 1D6F4% upper case sigma (maths italic)
\string<\glshex 1D6F5% upper case tau (maths italic)
\string<\glshex 1D6F6% upper case upsilon (maths italic)
\string<\glshex 1D6F7% upper case phi (maths italic)
\string<\glshex 1D6F8% upper case chi (maths italic)
\string<\glshex 1D6F9% upper case psi (maths italic)
\string<\glshex 1D6FA% upper case omega (maths italic)
}

```

MathItalicLowerGreekIrules Lower case only (includes upright digamma).

```

\newcommand*{\glxtrMathItalicLowerGreekIrules}{%
\glshex 1D6FC% lower case alpha (maths italic)
\string<\glshex 1D6FD% lower case beta (maths italic)
\string<\glshex 1D6FE% lower case gamma (maths italic)
\string<\glshex 1D6FF% lower case delta (maths italic)
\string<\glshex 1D700% lower case epsilon (maths italic)
\string=<\glshex 1D716% lower case epsilon variant (maths italic)
\string<\glshex 03DD% lower case digamma
\string<\glshex 1D701% lower case zeta (maths italic)
\string<\glshex 1D702% lower case eta (maths italic)
\string<\glshex 1D703% lower case theta (maths italic)
\string=<\glshex 1D717% lower case theta variant (maths italic)
}

```

```

\string<\glshex 1D704% lower case iota (maths italic)
\string<\glshex 1D705% lower case kappa (maths italic)
\string=\glshex 1D718% lower case kappa variant (maths italic)
\string<\glshex 1D706% lower case lambda (maths italic)
\string<\glshex 1D707% lower case mu (maths italic)
\string<\glshex 1D708% lower case nu (maths italic)
\string<\glshex 1D709% lower case xi (maths italic)
\string<\glshex 1D70A% lower case omicron (maths italic)
\string<\glshex 1D70B% lower case pi (maths italic)
\string=\glshex 1D71B% lower case pi variant (maths italic)
\string<\glshex 1D70C% lower case rho (maths italic)
\string=\glshex 1D71A% lower case rho variant (maths italic)
\string<\glshex 1D70D% lower case final sigma (maths italic)
\string=\glshex 1D70E% lower case sigma (maths italic)
\string<\glshex 1D70F% lower case tau (maths italic)
\string<\glshex 1D710% lower case upsilon (maths italic)
\string<\glshex 1D711% lower case phi (maths italic)
\string=\glshex 1D719% lower case phi variant (maths italic)
\string<\glshex 1D712% lower case chi (maths italic)
\string<\glshex 1D713% lower case psi (maths italic)
\string<\glshex 1D714% lower case omega (maths italic)
}

```

MathItalicLowerGreekIIrules Lower case only (doesn't includes upright digamma).

```

\newcommand*{\glxtrMathItalicLowerGreekIIrules}{%
\glshex 1D6FC% lower case alpha (maths italic)
\string<\glshex 1D6FD% lower case beta (maths italic)
\string<\glshex 1D6FE% lower case gamma (maths italic)
\string<\glshex 1D6FF% lower case delta (maths italic)
\string<\glshex 1D700% lower case epsilon (maths italic)
\string=\glshex 1D716% lower case epsilon variant (maths italic)
\string<\glshex 1D701% lower case zeta (maths italic)
\string<\glshex 1D702% lower case eta (maths italic)
\string<\glshex 1D703% lower case theta (maths italic)
\string=\glshex 1D717% lower case theta variant (maths italic)
\string<\glshex 1D704% lower case iota (maths italic)
\string<\glshex 1D705% lower case kappa (maths italic)
\string=\glshex 1D718% lower case kappa variant (maths italic)
\string<\glshex 1D706% lower case lambda (maths italic)
\string<\glshex 1D707% lower case mu (maths italic)
\string<\glshex 1D708% lower case nu (maths italic)
\string<\glshex 1D709% lower case xi (maths italic)
\string<\glshex 1D70A% lower case omicron (maths italic)
\string<\glshex 1D70B% lower case pi (maths italic)
\string=\glshex 1D71B% lower case pi variant (maths italic)
\string<\glshex 1D70C% lower case rho (maths italic)
\string=\glshex 1D71A% lower case rho variant (maths italic)
\string<\glshex 1D70D% lower case final sigma (maths italic)
\string=\glshex 1D70E% lower case sigma (maths italic)
\string<\glshex 1D70F% lower case tau (maths italic)
}

```

```

\string<\glshex 1D710% lower case upsilon (maths italic)
\string<\glshex 1D711% lower case phi (maths italic)
\string=\glshex 1D719% lower case phi variant (maths italic)
\string<\glshex 1D712% lower case chi (maths italic)
\string<\glshex 1D713% lower case psi (maths italic)
\string<\glshex 1D714% lower case omega (maths italic)
}

```

`\glsxtrMathGreekIrules` Includes both upright and italic with digamma between epsilon and zeta.

```

\newcommand*{\glsxtrMathGreekIrules}{%
\glsxtrMathItalicAlpha
\string;\glsxtrUpAlpha
\string<\glsxtrMathItalicBeta
\string;\glsxtrUpBeta
\string<\glsxtrMathItalicGamma
\string;\glsxtrUpGamma
\string<\glsxtrMathItalicDelta
\string;\glsxtrUpDelta
\string<\glsxtrMathItalicEpsilon
\string;\glsxtrUpEpsilon
\string<\glsxtrUpDigamma
\string<\glsxtrMathItalicZeta
\string;\glsxtrUpZeta
\string<\glsxtrMathItalicEta
\string;\glsxtrUpEta
\string<\glsxtrMathItalicTheta
\string;\glsxtrUpTheta
\string<\glsxtrMathItalicIota
\string;\glsxtrUpIota
\string<\glsxtrMathItalicKappa
\string;\glsxtrUpKappa
\string<\glsxtrMathItalicLambda
\string;\glsxtrUpLambda
\string<\glsxtrMathItalicMu
\string;\glsxtrUpMu
\string<\glsxtrMathItalicNu
\string;\glsxtrUpNu
\string<\glsxtrMathItalicXi
\string;\glsxtrUpXi
\string<\glsxtrMathItalicOmicron
\string;\glsxtrUpOmicron
\string<\glsxtrMathItalicPi
\string;\glsxtrUpPi
\string<\glsxtrMathItalicRho
\string;\glsxtrUpRho
\string<\glsxtrMathItalicSigma
\string;\glsxtrUpSigma
\string<\glsxtrMathItalicTau
\string;\glsxtrUpTau
\string<\glsxtrMathItalicUpsilon

```

```

\string;\glxtrUpUpsilon
\string<\glxtrMathItalicPhi
\string;\glxtrUpPhi
\string<\glxtrMathItalicChi
\string;\glxtrUpChi
\string<\glxtrMathItalicPsi
\string;\glxtrUpPsi
\string<\glxtrMathItalicOmega
\string;\glxtrUpOmega
}

```

`\glxtrMathGreekIIrules` Includes both upright and italic (digamma not included).

```

\newcommand*{\glxtrMathGreekIIrules}{%
\glxtrMathItalicAlpha
\string;\glxtrUpAlpha
\string<\glxtrMathItalicBeta
\string;\glxtrUpBeta
\string<\glxtrMathItalicGamma
\string;\glxtrUpGamma
\string<\glxtrMathItalicDelta
\string;\glxtrUpDelta
\string<\glxtrMathItalicEpsilon
\string;\glxtrUpEpsilon
\string<\glxtrMathItalicZeta
\string;\glxtrUpZeta
\string<\glxtrMathItalicEta
\string;\glxtrUpEta
\string<\glxtrMathItalicTheta
\string;\glxtrUpTheta
\string<\glxtrMathItalicIota
\string;\glxtrUpIota
\string<\glxtrMathItalicKappa
\string;\glxtrUpKappa
\string<\glxtrMathItalicLambda
\string;\glxtrUpLambda
\string<\glxtrMathItalicMu
\string;\glxtrUpMu
\string<\glxtrMathItalicNu
\string;\glxtrUpNu
\string<\glxtrMathItalicXi
\string;\glxtrUpXi
\string<\glxtrMathItalicOmicron
\string;\glxtrUpOmicron
\string<\glxtrMathItalicPi
\string;\glxtrUpPi
\string<\glxtrMathItalicRho
\string;\glxtrUpRho
\string<\glxtrMathItalicSigma
\string;\glxtrUpSigma
\string<\glxtrMathItalicTau

```

```

\string;\glxtrUpTau
\string<\glxtrMathItalicUpsilon
\string;\glxtrUpUpsilon
\string<\glxtrMathItalicPhi
\string;\glxtrUpPhi
\string<\glxtrMathItalicChi
\string;\glxtrUpChi
\string<\glxtrMathItalicPsi
\string;\glxtrUpPsi
\string<\glxtrMathItalicOmega
\string;\glxtrUpOmega
}

\glxtrUpAlpha
\newcommand*{\glxtrUpAlpha}{%
\glshex 03B1,% lower case alpha
\glshex 0391% upper case alpha
}

\glxtrUpBeta
\newcommand*{\glxtrUpBeta}{%
\glshex 03B2,% lower case beta
\glshex 0392% upper case beta
}

\glxtrUpGamma
\newcommand*{\glxtrUpGamma}{%
\glshex 03B3,% lower case gamma
\glshex 0393% upper case gamma
}

\glxtrUpDelta
\newcommand*{\glxtrUpDelta}{%
\glshex 03B4,% lower case delta
\glshex 0394% upper case delta
}

\glxtrUpEpsilon
\newcommand*{\glxtrUpEpsilon}{%
\glshex 03B5% lower case epsilon
\string=\glshex 03F5,% lower case epsilon variant
\glshex 0395% upper case epsilon
}

\glxtrUpDigamma
\newcommand*{\glxtrUpDigamma}{%
\glshex 03DD,% lower case digamma
\glshex 03DC% upper case digamma
}

```

```

\glxtrUpZeta
\newcommand*\glxtrUpZeta{%
  \glshex 03B6,% lower case zeta
  \glshex 0396% upper case zeta
}

\glxtrUpEta
\newcommand*\glxtrUpEta{%
  \glshex 03B7,% lower case eta
  \glshex 0397% upper case eta
}

\glxtrUpTheta
\newcommand*\glxtrUpTheta{%
  \glshex 03B8% lower case theta
  \string=\glshex 03D1,% lower case theta variant
  \glshex 0398% upper case theta
}

\glxtrUpIota
\newcommand*\glxtrUpIota{%
  \glshex 03B9,% lower case iota
  \glshex 0399% upper case iota
}

\glxtrUpKappa
\newcommand*\glxtrUpKappa{%
  \glshex 03BA% lower case kappa
  \string=\glshex 03F0,% lower case kappa variant
  \glshex 039A% upper case kappa
}

\glxtrUpLambda
\newcommand*\glxtrUpLambda{%
  \glshex 03BB,% lower lambda
  \glshex 039B% upper case lambda
}

\glxtrUpMu
\newcommand*\glxtrUpMu{%
  \glshex 03BC,% lower case mu
  \glshex 039C% upper case mu
}

\glxtrUpNu
\newcommand*\glxtrUpNu{%
  \glshex 03BD,% lower case nu
  \glshex 039D% upper case nu
}

```

```

\glxstrUpXi
\newcommand*\glxstrUpXi}{%
\glshex 03BE,% lower case xi
\glshex 039E% upper case xi
}

\glxstrUpOmicron
\newcommand*\glxstrUpOmicron}{%
\glshex 03BF,% lower case omicron
\glshex 039F% upper case omicron
}

\glxstrUpPi
\newcommand*\glxstrUpPi}{%
\glshex 03C0% lower case pi
\string=\glshex 03D6,% lower case pi variant
\glshex 03A0% upper case pi
}

\glxstrUpRho
\newcommand*\glxstrUpRho}{%
\glshex 03C1% lower case rho
\string=\glshex 03F1,% lower case rho variant
\glshex 03A1% upper case rho
}

\glxstrUpSigma
\newcommand*\glxstrUpSigma}{%
\glshex 03C2% lower case sigma
\string=\glshex 03C3,% lower case sigma
\glshex 03A3% upper case sigma
}

\glxstrUpTau
\newcommand*\glxstrUpTau}{%
\glshex 03C4,% lower case tau
\glshex 03A4% upper case tau
}

\glxstrUpUpsilon
\newcommand*\glxstrUpUpsilon}{%
\glshex 03C5,% lower case upsilon
\glshex 03A5% upper case upsilon
}

\glxstrUpPhi
\newcommand*\glxstrUpPhi}{%
\glshex 03C6% lower case phi

```



```

\string=\glshex 03D5,% lower case phi variant
\glshex 03A6% upper case phi
}

\glsxtrUpChi
\newcommand*{\glsxtrUpChi}{%
\glshex 03C7,% lower case chi
\glshex 03A7% upper case chi
}

\glsxtrUpPsi
\newcommand*{\glsxtrUpPsi}{%
\glshex 03C8,% lower case psi
\glshex 03A8% upper case psi
}

\glsxtrUpOmega
\newcommand*{\glsxtrUpOmega}{%
\glshex 03C9,% lower case omega
\glshex 03A9% upper case omega
}

\glsxtrMathItalicAlpha
\newcommand*{\glsxtrMathItalicAlpha}{%
\glshex 1D6FC,% lower case alpha (maths italic)
\glshex 1D6E2% upper case alpha (maths italic)
}

\glsxtrMathItalicBeta
\newcommand*{\glsxtrMathItalicBeta}{%
\glshex 1D6FD,% lower case beta (maths italic)
\glshex 1D6E3% upper case beta (maths italic)
}

\glsxtrMathItalicGamma
\newcommand*{\glsxtrMathItalicGamma}{%
\glshex 1D6FE,% lower case gamma (maths italic)
\glshex 1D6E4% upper case gamma (maths italic)
}

\glsxtrMathItalicDelta
\newcommand*{\glsxtrMathItalicDelta}{%
\glshex 1D6FF,% lower case delta (maths italic)
\glshex 1D6E5% upper case delta (maths italic)
}

\glsxtrMathItalicEpsilon
\newcommand*{\glsxtrMathItalicEpsilon}{%
\glshex 1D700% lower case epsilon (maths italic)

```

```

\string=\glshex 1D716,% lower case epsilon variant (maths italic)
\glshex 1D6E6% upper case epsilon (maths italic)
}

```

`\glsxtrMathItalicZeta`

```

\newcommand*{\glsxtrMathItalicZeta}{%
\glshex 1D701,% lower case zeta (maths italic)
\glshex 1D6E7% upper case zeta (maths italic)
}

```

`\glsxtrMathItalicEta`

```

\newcommand*{\glsxtrMathItalicEta}{%
\glshex 1D702,% lower case eta (maths italic)
\glshex 1D6E8% upper case eta (maths italic)
}

```

`\glsxtrMathItalicTheta`

```

\newcommand*{\glsxtrMathItalicTheta}{%
\glshex 1D703% lower case theta (maths italic)
\string=\glshex 1D717,% lower case theta variant (maths italic)
\glshex 1D6E9% upper case theta (maths italic)
\string=\glshex 1D6F3% upper case theta variant (maths italic)
}

```

`\glsxtrMathItalicIota`

```

\newcommand*{\glsxtrMathItalicIota}{%
\glshex 1D704,% lower case iota (maths italic)
\glshex 1D6EA% upper case iota (maths italic)
}

```

`\glsxtrMathItalicKappa`

```

\newcommand*{\glsxtrMathItalicKappa}{%
\glshex 1D705% lower case kappa (maths italic)
\string=\glshex 1D718,% lower case kappa variant (maths italic)
\glshex 1D6EB% upper case kappa (maths italic)
}

```

`\glsxtrMathItalicLambda`

```

\newcommand*{\glsxtrMathItalicLambda}{%
\glshex 1D706,% lower case lambda (maths italic)
\glshex 1D6EC% upper case lambda (maths italic)
}

```

`\glsxtrMathItalicMu`

```

\newcommand*{\glsxtrMathItalicMu}{%
\glshex 1D707,% lower case mu (maths italic)
\glshex 1D6ED% upper case mu (maths italic)
}

```

```

\glxtrMathItalicNu
\newcommand*\glxtrMathItalicNu{%
  \glshex 1D708,% lower case nu (maths italic)
  \glshex 1D6EE% upper case nu (maths italic)
}

\glxtrMathItalicXi
\newcommand*\glxtrMathItalicXi{%
  \glshex 1D709,% lower case xi (maths italic)
  \glshex 1D6EF% upper case xi (maths italic)
}

\glxtrMathItalicOmicron
\newcommand*\glxtrMathItalicOmicron{%
  \glshex 1D70A,% lower case omicron (maths italic)
  \glshex 1D6F0% upper case omicron (maths italic)
}

\glxtrMathItalicPi
\newcommand*\glxtrMathItalicPi{%
  \glshex 1D70B% lower case pi (maths italic)
  \string=\glshex 1D71B,% lower case pi variant (maths italic)
  \glshex 1D6F1% upper case pi (maths italic)
}

\glxtrMathItalicRho
\newcommand*\glxtrMathItalicRho{%
  \glshex 1D70C% lower case rho (maths italic)
  \string=\glshex 1D71A,% lower case rho variant (maths italic)
  \glshex 1D6F2% upper case rho (maths italic)
}

\glxtrMathItalicSigma
\newcommand*\glxtrMathItalicSigma{%
  \glshex 1D70D% lower case final sigma (maths italic)
  \string=\glshex 1D70E,% lower case sigma (maths italic)
  \glshex 1D6F4% upper case sigma (maths italic)
}

\glxtrMathItalicTau
\newcommand*\glxtrMathItalicTau{%
  \glshex 1D70F,% lower case tau (maths italic)
  \glshex 1D6F5% upper case tau (maths italic)
}

\glxtrMathItalicUpsilon
\newcommand*\glxtrMathItalicUpsilon{%
  \glshex 1D710,% lower case upsilon (maths italic)
  \glshex 1D6F6% upper case upsilon (maths italic)
}

```

```

\glxtrMathItalicPhi
\newcommand*{\glxtrMathItalicPhi}{%
  \glshex 1D711% lower case phi (maths italic)
  \string=\glshex 1D719,% lower case phi variant (maths italic)
  \glshex 1D6F7% upper case phi (maths italic)
}

\glxtrMathItalicChi
\newcommand*{\glxtrMathItalicChi}{%
  \glshex 1D712,% lower case chi (maths italic)
  \glshex 1D6F8% upper case chi (maths italic)
}

\glxtrMathItalicPsi
\newcommand*{\glxtrMathItalicPsi}{%
  \glshex 1D713,% lower case psi (maths italic)
  \glshex 1D6F9% upper case psi (maths italic)
}

\glxtrMathItalicOmega
\newcommand*{\glxtrMathItalicOmega}{%
  \glshex 1D714,% lower case omega (maths italic)
  \glshex 1D6FA% upper case omega (maths italic)
}

\glxtrMathItalicPartial
\newcommand*{\glxtrMathItalicPartial}{%
  \glshex 1D715% partial differential (maths italic)
}

\glxtrMathItalicNabla
\newcommand*{\glxtrMathItalicNabla}{%
  \glshex 1D6FB% nabla (maths italic)
}

\glxtrdigitrules Digits from the Basic Latin set and subscript and superscript digit rules.
\newcommand*{\glxtrdigitrules}{%
  0\string=\glshex 2080\string=\glshex 2070
  \string<1\string=\glshex 2081\string=\glshex 00B9
  \string<2\string=\glshex 2082\string=\glshex 00B2
  \string<3\string=\glshex 2083\string=\glshex 00B3
  \string<4\string=\glshex 2084\string=\glshex 2074
  \string<5\string=\glshex 2085\string=\glshex 2075
  \string<6\string=\glshex 2086\string=\glshex 2076
  \string<7\string=\glshex 2087\string=\glshex 2077
  \string<8\string=\glshex 2088\string=\glshex 2078
  \string<9\string=\glshex 2089\string=\glshex 2079
}

```

`\glxtrBasicDigitrules` Digits from the Basic Latin set.

```
\newcommand*{\glxtrBasicDigitrules}{%
  0\string<1\string<2\string<3\string<4%
  \string<5\string<6\string<7\string<8\string<9%
}
```

`\glxtrSubScriptDigitrules` Subscript digits.

```
\newcommand*{\glxtrSubScriptDigitrules}{%
  \glshex 2080% subscript 0
  \string<\glshex 2081% subscript 1
  \string<\glshex 2082% subscript 2
  \string<\glshex 2083% subscript 3
  \string<\glshex 2084% subscript 4
  \string<\glshex 2085% subscript 5
  \string<\glshex 2086% subscript 6
  \string<\glshex 2087% subscript 7
  \string<\glshex 2088% subscript 8
  \string<\glshex 2089% subscript 9
}
```

`\glxtrSuperScriptDigitrules` Superscript digits.

```
\newcommand*{\glxtrSuperScriptDigitrules}{%
  \glshex 2070% superscript 0
  \string<\glshex 00B9% superscript 1
  \string<\glshex 00B2% superscript 2
  \string<\glshex 00B3% superscript 3
  \string<\glshex 2074% superscript 4
  \string<\glshex 2075% superscript 5
  \string<\glshex 2076% superscript 6
  \string<\glshex 2077% superscript 7
  \string<\glshex 2078% superscript 8
  \string<\glshex 2079% superscript 9
}
```

`\glxtrfractionrules` Vulgar fractions.

```
\newcommand*{\glxtrfractionrules}{%
  \glshex 215F% fraction numerator one (1/)
  \string<\glshex 2189% zero thirds (0/3 = 0)
  \string<\glshex 2152% one tenth (1/10 = 0.1)
  \string<\glshex 2151% one ninth (1/9 ~ 0.111)
  \string<\glshex 215B% one eighth (1/8 = 0.125)
  \string<\glshex 2150% one seventh (1/7 ~ 0.143)
  \string<\glshex 2159% one sixth (1/6 ~ 0.167)
  \string<\glshex 2155% one fifth (1/5 = 0.2)
  \string<\glshex 00BC% one quarter (1/4 = 0.25)
  \string<\glshex 2153% one third (1/3 ~ 0.333)
  \string<\glshex 215C% three eighths (3/8 = 0.375)
  \string<\glshex 2156% two fifths (2/5 = 0.4)
  \string<\glshex 00BD% one half (1/2 = 0.5)
}
```

```

\string<\glshex 2157% three fifths (3/5 = 0.6)
\string<\glshex 215D% five eighths (5/8 = 0.625)
\string<\glshex 2154% two thirds (2/3 ~ 0.667)
\string<\glshex 00BE% three quarters (3/4 = 0.75)
\string<\glshex 2158% four fifths (4/5 = 0.8)
\string<\glshex 215A% five sixths (5/6 ~ 0.833)
\string<\glshex 215E% seven eighths (7/8 = 0.875)
}

```

`\@glxtrdialecthook` Check for scripts associated with the document dialects.

```

\renewcommand{\@glxtrdialecthook}{%
  \ifundef\CurrentTrackedScript
  {%
    \TrackLangIfHasDefaultScript{\CurrentTrackedLanguage}%
    {%
      \edef\CurrentTrackedScript{%
        \TrackLangGetDefaultScript\CurrentTrackedLanguage}%
      }%
    }%
  }%
  {}%
\ifdef\CurrentTrackedScript
{%
  \let\gls@orgTrackLangRequireDialectPrefix\TrackLangRequireDialectPrefix
  \def\TrackLangRequireDialectPrefix{glossariesxtr-}%
  \let\CurrentTrackedTag\CurrentTrackedScript
  \IfFileExists{\TrackLangRequireDialectPrefix\CurrentTrackedTag.ldf}
  {\RequireGlossariesExtraLang{\CurrentTrackedTag}}%
  {}%
  \let\TrackLangRequireDialectPrefix\gls@orgTrackLangRequireDialectPrefix
}%
{}%
}

```

If `\glsxtr@loaddialect` has been defined, then `glossaries-extra-bib2gls` has been loaded after `glossaries-extra`. (For example, through `\glossariesextrasetup`.) Not recommended, but if this has been done try to find the associated language resources.

```

\ifdef\glsxtr@loaddialect
{%
  \ifpackageloaded{tracklang}
  {%
    \AnyTrackedLanguages
    {%
      \ForEachTrackedDialect{\this@dialect}{\glsxtr@loaddialect}%
    }%
  }%
}
{}

```

```
}
{}
```

4 Style Adjustments (glossaries-extra-stylemods.sty)

This package adjusts the predefined styles so that they include the post description hook. Also, some other minor adjustments may be made to make existing styles more flexible.

4.1 Package Initialisation

First identify package:

```
\NeedsTeXFormat{LaTeX2e}
```

Rollback releases:

```
\DeclareRelease{v1.48}{2021-11-22}{glossaries-extra-stylemods-2021-11-22.sty}
\DeclareCurrentRelease{1.9}{2025-11-03}
```

Declare package:

```
\ProvidesPackage{glossaries-extra-stylemods}[2026/03/06 v2.0 (NLCT)]
```

Provide package options to automatically load required predefined styles. The simplest method is to just test for the existence of the file `glossary-<option>.sty`. Packages can't be loaded whilst the options are being processed, so save the list in `\@glxtr@loadstyles`.

```
\@glxtr@loadstyles
\newcommand*{\@glxtr@loadstyles}{%
all Provide all known styles.
\DeclareOption{all}{%
\appto\@glxtr@loadstyles{%
\RequirePackage{glossary-inline}%
\RequirePackage{glossary-list}%
\RequirePackage{glossary-tree}%
\RequirePackage{glossary-mcols}%
\RequirePackage{glossary-long}%
\RequirePackage{glossary-longragged}%
\RequirePackage{glossary-longbooktabs}%
\RequirePackage{glossary-super}%
\RequirePackage{glossary-superragged}%
\RequirePackage{glossary-bookindex}%
\RequirePackage{glossary-longextra}%
\RequirePackage{glossary-topic}%
\RequirePackage{glossary-table}%
}
}
```

```

\DeclareOption*{%
  \IfFileExists{glossary-\CurrentOption.sty}
  {\eappto\@glstrloadstyles{%
    \noexpand\RequirePackage{glossary-\CurrentOption}}}%
  }%
  {%
    \PackageError{glossaries-extra-styles}%
    {Unknown option ‘\CurrentOption’}{}%
  }%
}

```

Process the package options:

```
\ProcessOptions
```

Load the required packages:

```
\@glstrloadstyles
```

Adjust the styles so that they all have the post description hook. Also, instead of having a hard-coded `\space` before the location, use:

`\glstrprelocation` This uses `\providecommand` as the same command is also provided by `glossary-bookindex`.

```
\providecommand*\glstrprelocation{\space}
```

In case we have an old version of `glossaries`:

`\renewglossarystyle`

```

\providecommand{\renewglossarystyle}[2]{%
  \ifcsundef{@glstyle@#1}%
  {%
    \PackageError{glossaries-extra}{Glossary style ‘#1’ isn’t already defined}{}%
  }%
  {%
    \csdef{@glstyle@#1}{#2}%
  }%
}

```

4.2 List-Like Styles

The list-like styles mostly already use the post description hook. Only the `listdotted` style need modifying to add this.

```

\ifdef{\@glstyle@listdotted}
{%
  \renewglossarystyle{listdotted}{%
    \setglossarystyle{list}%
    \renewcommand*\glossentry}[2]{%
      \item[]\makebox[\glslistdottedwidth][l]{%
        \glstryitem{##1}%
        \glstarget{##1}{\glossentryname{##1}}%
        \unskip\leaders\hbox to 2.9mm{\hss.}\hfill\strut}%
        \glossentrydesc{##1}\glspostdescription}%
      }%
    }%
}

```



```

\renewcommand*{\subglossentry}[3]{%
\item[]\makebox[\glslistdottedwidth][l]{%
\glssubentryitem{##2}%
\glstarget{##2}{\glossentryname{##2}}%
\unskip\leaders\hbox to 2.9mm{\hss.}\hfill\strut}%
\glossentrydesc{##2}\glspostdescription}%
}
}
{%

```

Assume the style isn't required if it hasn't already been defined.

```

}
```

The `sublistdotted` style doesn't display the description for top-level entries. Sub-level entries use the `listdottedstyle`.

The other list styles would be easier to adapt if the space before the number list wasn't hard coded.

```

\ifdef{\@glsstyle@list}
{%

```

`\glslistprelocation` Space before number list for top-level entries.

```

\newcommand{\glslistprelocation}{\glstrprelocation}
```

`\glslistchildprelocation` Space before number list for child entries.

```

\newcommand{\glslistchildprelocation}{\glslistprelocation}
```

`\glslistchildpostlocation` Full stop after number list.

```

\newcommand{\glslistchildpostlocation}{.}
```

`\glslistdesc`

```

\newcommand{\glslistdesc}[1]{\glossentrydesc{#1}\glspostdescription}
```

`\glslistgroupskip`

```

\newcommand{\glslistgroupskip}{\nobreak\indexspace\nobreak}
```

`\glslistitem`

```

\newcommand{\glslistitem}[1]{%
\item[\glssentryitem{#1}%
\glstarget{#1}{\glossentryname{#1}}]%
}

```

`\glslistinit` This command was only added to `glossary-list` v4.48 so provide it if it hasn't been defined:

```

\providecommand{\glslistinit}{%
\ifdef\GetTitleStringDisableCommands
{%
\GetTitleStringSetup{expand}%
\GetTitleStringDisableCommands{%
\let\glssentryitem\@gobble

```

```

\let\glstarget\@secondoftwo
\let\glossentryname\glslistexpandedname
\let\glslistgroupheaderfmt\@firstofone
\let\glsgetgrouptitle\@firstofone

```

Technically this has an optional argument but it's not used in the list styles.

```

\let\glsnavhypertarget\@secondoftwo
\let\glsnavigation\relax
}%
}%
{}%
}

```

`\glslistexpandedname` This command was only added to glossary-list v4.48 so provide it if it hasn't been defined. The original definition uses `\glsunexpandedfieldvalue` which was added to glossaries v4.48 (so if `\glslistexpandedname` hasn't been defined then neither will `\glsunexpandedfieldvalue`).

```

\providecommand{\glslistexpandedname}[1]{%
\ifcsname glo@\glsdetoklabel{#1}@name\endcsname
\expandafter\expandonce\csname glo@\glsdetoklabel{#1}@name\expandafter\endcsname
\fi
}

```

Redefine list to use these commands.

```

\renewglossarystyle{list}{%
\renewenvironment{theglossary}{%
{\glslistinit\begin{description}}{\end{description}}%
\renewcommand*{\glossaryheader}{}%
\renewcommand*{\glsgroupheading}[1]{}%

```

Sub-groups are only supported with `\printunsrtglossary`. This does nothing as the sub-entries don't have the name displayed for the list styles.

```

\renewcommand*{\glssubgroupheading}[4]{}%
\renewcommand*{\glossentry}[2]{%
\glslistitem{##1}\glslistdesc{##1}\glslistprelocation ##2}%
\renewcommand*{\subglossentry}[3]{%
\glssubentryitem{##2}%
\glstarget{##2}{\strut}\space
\glslistdesc{##2}%
\glslistchildprelocation ##3\glslistchildpostlocation}%
\renewcommand*{\glsgroupskip}{\ifglsnogroupskip\else\glslistgroupskip\fi}%
}
}
{}

```

Similarly for `altlist`. Since it requires `list`, the new commands should have been defined above.

```

\ifdef{\@glsstyle@altlist}
{%

```

`\glsaltlistitem`

```

\newcommand{\glsaltlistitem}[1]{%
  \glslistitem{#1}%
  \mbox{ }\par\nobreak\@afterheading
}

\renewglossarystyle{altlist}{%
  \setglossarystyle{list}%
  \renewcommand*{\glossentry}[2]{%
    \glsaltlistitem{##1}%
    \glslistdesc{##1}\glslistprelocation ##2}%
  \renewcommand{\subglossentry}[3]{%
    \par
    \glssubentryitem{##2}%
    \glstarget{##2}{\strut}\glslistdesc{##2}%
    \glslistchildprelocation ##3}%
  }
}
{}

```

Redefine `listgroup` so that it discourages a break after group headings.

```

\ifdef{\@glsstyle@listgroup}
{%

```

`\glslistgroupheaderitem`

```

\newcommand{\glslistgroupheaderitem}[2]{\item[{#2}]}

```

`\glslistgroupafterheader`

```

\newcommand{\glslistgroupafterheader}{%
  \mbox{ }\par\nobreak\@afterheading
}

\renewglossarystyle{listgroup}{%
  \setglossarystyle{list}%
  \renewcommand*{\glsgroupheading}[1]{%
    \glslistgroupheaderitem{##1}{\glslistgroupheaderfmt{\glsgetgrouptitle{##1}}}%
    \glslistgroupafterheader
  }%
}
}
{}

```

Similarly for `listhypergroup`.

```

\ifdef{\@glsstyle@listhypergroup}
{%
  \renewglossarystyle{listhypergroup}{%
    \setglossarystyle{list}%
    \renewcommand*{\glossaryheader}{%
      \glslistnavigationitem{\glsnavigation}}%
    \renewcommand*{\glsgroupheading}[1]{%

```

```

        \glslistgroupheaderitem{##1}{\glslistgroupheaderfmt
        {\glsnavhypertarget{##1}{\glsgetgrouptitle{##1}}}}}%
        \glslistgroupafterheader
    }%
}
}
{}

```

Similarly for `altlistgroup`.

```

\ifdef{\@glsstyle@altlistgroup}
{%
    \renewglossarystyle{altlistgroup}{%
        \setglossarystyle{altlist}%
        \renewcommand*{\glsgroupheading}[1]{%
            \glslistgroupheaderitem{##1}%
            {\glslistgroupheaderfmt{\glsgetgrouptitle{##1}}}%
            \glslistgroupafterheader
        }%
    }
}
{}

```

Similarly for `altlisthypergroup`.

```

\ifdef{\@glsstyle@altlisthypergroup}
{%
    \renewglossarystyle{altlisthypergroup}{%
        \setglossarystyle{altlist}%
        \renewcommand*{\glossaryheader}{%
            \glslistnavigationitem{\glsnavigation}}%
        \renewcommand*{\glsgroupheading}[1]{%
            \glslistgroupheaderitem{##1}{\glslistgroupheaderfmt
            {\glsnavhypertarget{##1}{\glsgetgrouptitle{##1}}}}}%
            \glslistgroupafterheader
        }%
    }
}
{}

```

4.3 Longtable Styles

The three and four column styles require adjustment to add the post-description hook. The two column styles need the hard-coded `\space` changed to `\glstrprelocation`.

```

\ifcsdef{@glsstyle@long}
{%
    \renewglossarystyle{long}{%
        \renewenvironment{theglossary}%
            {\begin{longtable}{\lp{\glsdescwidth}}}%
            {\end{longtable}}%
        \renewcommand*{\glossaryheader}{}%
    }
}

```

```
\renewcommand*{\glsgroupheading}[1]{}
```

Sub-groups are only supported with `\printunsrtglossary`. This does nothing as the sub-entries don't have the name displayed for the long styles.

```
\renewcommand*{\glssubgroupheading}[4]{}%
\renewcommand{\glossentry}[2]{%
  \glentryitem{##1}\glstarget{##1}{\glossentryname{##1}} &
  \glossentrydesc{##1}\glspostdescription
  \glstrprelocation ##2\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
  &
  \glssubentryitem{##2}%
  \glstarget{##2}{\strut}\glossentrydesc{##2}\glspostdescription
  \glstrprelocation ##3\tabularnewline
}%
\ifglsgroupskip
  \renewcommand*{\glsgroupskip}{}%
\else
  \renewcommand*{\glsgroupskip}{ & \tabularnewline}%
\fi
}
}
{}
```

Three column style:

```
\ifcsdef{@glstyle@long3col}
{%
  \renewglossarystyle{long3col}{%
    \renewenvironment{theglossary}%
      {\begin{longtable}{lp{\glwdwidth}p{\glpagelistwidth}}}%
      {\end{longtable}}%
    \renewcommand*{\glossaryheader}{}%
    \renewcommand*{\glsgroupheading}[1]{}%
  }
}
```

Sub-groups are only supported with `\printunsrtglossary`. This does nothing as the sub-entries don't have the name displayed for the long styles.

```
\renewcommand*{\glssubgroupheading}[4]{}%
\renewcommand{\glossentry}[2]{%
  \glentryitem{##1}\glstarget{##1}{\glossentryname{##1}} &
  \glossentrydesc{##1}\glspostdescription & ##2\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
  &
  \glssubentryitem{##2}%
  \glstarget{##2}{\strut}\glossentrydesc{##2}\glspostdescription &
  ##3\tabularnewline
}%
}
```

Conditional needs to be outside of `\glsgroupskip` otherwise it can cause “Incomplete `\iftrue`” errors.

```

\ifglsgroupskip
\renewcommand*{\glsgroupskip}{}%
\else
\renewcommand*{\glsgroupskip}{& &\tabularnewline}%
\fi
}
}
{}

```

Four column style:

```

\ifcsdef{@glstyle@long4col}
{%
\renewglossarystyle{long4col}{%
\renewenvironment{theglossary}%
{\begin{longtable}{llll}}%
{\end{longtable}}%
\renewcommand*{\glossaryheader}{}%
\renewcommand*{\glsgroupheading}[1]{}%

```

Sub-groups are only supported with `\printunsrtglossary`. This does nothing as the sub-entries don't have the name displayed for the long styles.

```

\renewcommand*{\glssubgroupheading}[4]{}%
\renewcommand{\glossentry}[2]{%
\glstryitem{##1}\glstarget{##1}{\glossentryname{##1}} &
\glossentrydesc{##1}\glspostdescription &
\glossentrysymbol{##1} &
##2\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
&
\glssubentryitem{##2}%
\glstarget{##2}{\strut}\glossentrydesc{##2}\glspostdescription &
\glossentrysymbol{##2} & ##3\tabularnewline
}%

\ifglsgroupskip
\renewcommand*{\glsgroupskip}{}%
\else
\renewcommand*{\glsgroupskip}{& & &\tabularnewline}%
\fi
}
}
{}

```

The styles in `glossary-longbooktabs` are all based on the styles in `glossary-long`, so no adjustments are needed for that package.

4.4 Long Ragged Styles

The three and four column styles require adjustment for the post-description hook, but not the two column styles. However, the two-column styles need to

have `\space` replaced with `\glstrprelocation`.

```
\ifcsdef{@glsstyle@longragged}
{%
  \renewglossarystyle{longragged}{%
    \renewenvironment{theglossary}%
      {\begin{longtable}{l>{\raggedright}p{\glsdescwidth}}}%
      {\end{longtable}}%
    \renewcommand*{\glossaryheader}{}%
    \renewcommand*{\glsgroupheading}[1]{}%

```

Sub-groups are only supported with `\printunsrtglossary`. This does nothing as the sub-entries don't have the name displayed for the longragged styles.

```
  \renewcommand*{\glssubgroupheading}[4]{}%
  \renewcommand{\glossentry}[2]{%
    \glssentryitem{##1}\glstarget{##1}{\glossentryname{##1}} &
    \glossentrydesc{##1}\glspostdescription\glstrprelocation ##2%
    \tabularnewline
  }%
  \renewcommand{\subglossentry}[3]{%
    &
    \glssubentryitem{##2}%
    \glstarget{##2}{\strut}\glossentrydesc{##2}%
    \glspostdescription\glstrprelocation ##3%
    \tabularnewline
  }%
  \ifglsnogroupskip
    \renewcommand*{\glsgroupskip}{}%
  \else
    \renewcommand*{\glsgroupskip}{ & \tabularnewline}%
  \fi
}
}
{}

```

Three and four column styles don't use `\glstrprelocation` since the number list is in its own column.

```
\ifcsdef{@glsstyle@longragged3col}
{%
  \renewglossarystyle{longragged3col}{%
    \renewenvironment{theglossary}%
      {\begin{longtable}{l>{\raggedright}p{\glsdescwidth}%
        >{\raggedright}p{\glspagelistwidth}}}%
      {\end{longtable}}%
    \renewcommand*{\glossaryheader}{}%
    \renewcommand*{\glsgroupheading}[1]{}%

```

Sub-groups are only supported with `\printunsrtglossary`. This does nothing as the sub-entries don't have the name displayed for the longragged styles.

```
  \renewcommand*{\glssubgroupheading}[4]{}%
  \renewcommand{\glossentry}[2]{%

```

```

\glentryitem{##1}\glstarget{##1}{\glossentryname{##1}} &
\glossentrydesc{##1}\glspostdescription & ##2\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
  &
  \glssubentryitem{##2}%
  \glstarget{##2}{\strut}\glossentrydesc{##2}\glspostdescription &
  ##3\tabularnewline
}%

\ifglsnogroupskip
  \renewcommand*{\glsgroupskip}{}%
\else
  \renewcommand*{\glsgroupskip}{& & \tabularnewline}%
\fi
}
}
{}

```

Four column style:

```

\ifcsdef{@glstyle@altlongragged4col}
{%
  \renewglossarystyle{altlongragged4col}{%
    \renewenvironment{theglossary}%
      {\begin{longtable}{l>{\raggedright}p{\glstdescwidth}l%
        >{\raggedright}p{\glspagelistwidth}}}%
      {\end{longtable}}%
    \renewcommand*{\glossaryheader}{}%
    \renewcommand*{\glsgroupheading}[1]{}%

```

Sub-groups are only supported with `\printunsrtglossary`. This does nothing as the sub-entries don't have the name displayed for the longragged styles.

```

\renewcommand*{\glssubgroupheading}[4]{}%
\renewcommand{\glossentry}[2]{%
  \glentryitem{##1}\glstarget{##1}{\glossentryname{##1}} &
  \glossentrydesc{##1}\glspostdescription & \glossentrysymbol{##1} &
  ##2\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
  &
  \glssubentryitem{##2}%
  \glstarget{##2}{\strut}\glossentrydesc{##2}\glspostdescription &
  \glossentrysymbol{##2} & ##3\tabularnewline
}%

\ifglsnogroupskip
  \renewcommand*{\glsgroupskip}{}%
\else
  \renewcommand*{\glsgroupskip}{& & \tabularnewline}%
\fi
}

```



```
}
{}
```

4.5 Supertabular Styles

The three and four column styles require adjustment to add the post-description hook. The two column styles need the hard-coded `\space` changed to `\glstrprelocation`.

```
\ifcsdef{@glsstyle@super}
{%
  \renewglossarystyle{super}{%
    \renewenvironment{theglossary}%
      {\tablehead{}\tabletail}%
      \begin{supertabular}{lp{\glstdescwidth}}%
      {\end{supertabular}}%
    \renewcommand*{\glossaryheader}{}%
    \renewcommand*{\glsgroupheading}[1]{}%

```

Sub-groups are only supported with `\printunsrtglossary`. This does nothing as the sub-entries don't have the name displayed for the super styles.

```
  \renewcommand*{\glssubgroupheading}[4]{}%
  \renewcommand{\glossentry}[2]{%
    \glssentryitem{##1}\glstarget{##1}{\glossentryname{##1}} &
    \glossentrydesc{##1}\glspostdescription
    \glstrprelocation ##2\tabularnewline
  }%
  \renewcommand{\subglossentry}[3]{%
    &
    \glssubentryitem{##2}%
    \glstarget{##2}{\strut}\glossentrydesc{##2}\glspostdescription
    \glstrprelocation ##3\tabularnewline
  }%
  \ifglsgroupskip
    \renewcommand*{\glsgroupskip}{}%
  \else
    \renewcommand*{\glsgroupskip}{& \tabularnewline}%
  \fi
}
}
{}
```

Three column style:

```
\ifcsdef{@glsstyle@super3col}
{%
  \renewglossarystyle{super3col}{%
    \renewenvironment{theglossary}%
      {\tablehead{}\tabletail}%
      \begin{supertabular}{lp{\glstdescwidth}p{\glspagelistwidth}}%
      {\end{supertabular}}%
    \renewcommand*{\glossaryheader}{}%

```

```
\renewcommand*{\glsgroupheading}[1]{}%
```

Sub-groups are only supported with \printunsrtglossary. This does nothing as the sub-entries don't have the name displayed for the super styles.

```
\renewcommand*{\glssubgroupheading}[4]{}%
\renewcommand{\glossentry}[2]{%
  \glentryitem{##1}\glstarget{##1}{\glossentryname{##1}} &
  \glossentrydesc{##1}\glspostdescription & ##2\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
  &
  \glssubentryitem{##2}%
  \glstarget{##2}{\strut}\glossentrydesc{##2}\glspostdescription &
  ##3\tabularnewline
}%

\ifglsgroupskip
\renewcommand*{\glsgroupskip}{}%
\else
\renewcommand*{\glsgroupskip}{ & \tabularnewline}%
\fi
}
}
{}
```

Four column styles:

```
\ifcsdef{@glstyle@super4col}
{%
\renewglossarystyle{super4col}{%
\renewenvironment{theglossary}%
{\tablehead{ }\tabletail{ }}%
\begin{supertabular}{llll}{%
\end{supertabular}}%
\renewcommand*{\glossaryheader}{}%
\renewcommand*{\glsgroupheading}[1]{}%
```

Sub-groups are only supported with \printunsrtglossary. This does nothing as the sub-entries don't have the name displayed for the super styles.

```
\renewcommand*{\glssubgroupheading}[4]{}%
\renewcommand{\glossentry}[2]{%
  \glentryitem{##1}\glstarget{##1}{\glossentryname{##1}} &
  \glossentrydesc{##1}\glspostdescription &
  \glossentrysymbol{##1} & ##2\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
  &
  \glssubentryitem{##2}%
  \glstarget{##2}{\strut}\glossentrydesc{##2}\glspostdescription &
  \glossentrysymbol{##2} & ##3\tabularnewline
}%
```

```

\ifglsnogroupskip
\renewcommand*{\glsgroupskip}{}%
\else
\renewcommand*{\glsgroupskip}{& & \tabularnewline}%
\fi
}
}
{}

```

4.6 Super Ragged Styles

The three and four column styles require adjustment for the post-description hook, but not the two column styles. However, the two-column styles need to have `\space` replaced with `\glstrprelocation`.

```

\ifcsdef{@glstyle@superragged}
{%
\renewglossarystyle{superragged}{%
\renewenvironment{theglossary}%
{\tablehead{}\tabletail{}}%
\begin{supertabular}{1>\raggedright}p{\glsdscwidth}}}%
{\end{supertabular}}%
\renewcommand*{\glossaryheader}{}%
\renewcommand*{\glsgroupheading}[1]{}%

```

Sub-groups are only supported with `\printunsrtglossary`. This does nothing as the sub-entries don't have the name displayed for the super styles.

```

\renewcommand*{\glssubgroupheading}[4]{}%
\renewcommand{\glossentry}[2]{%
\glssentryitem{##1}\glstarget{##1}{\glossentryname{##1}} &
\glossentrydesc{##1}\glspostdescription\glstrprelocation ##2%
\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
&
\glssubentryitem{##2}%
\glstarget{##2}{\strut}\glossentrydesc{##2}\glspostdescription
\glstrprelocation ##3%
\tabularnewline
}%
\ifglsnogroupskip
\renewcommand*{\glsgroupskip}{}%
\else
\renewcommand*{\glsgroupskip}{& \tabularnewline}%
\fi
}
}
{}

```

Three column style:

```

\ifcsdef{@glstyle@superragged3col}

```

```
{%
\renewglossarystyle{superragged3col}{%
\renewenvironment{theglossary}%
{\tablehead{}\tabletail}%
\begin{supertabular}{1>{\raggedright}p{\glsdescwidth}%
>{\raggedright}p{\glspagelistwidth}}}%
{\end{supertabular}}%
\renewcommand*{\glossaryheader}{}%
\renewcommand*{\glsgroupheading}[1]{}%

```

Sub-groups are only supported with `\printunsrtglossary`. This does nothing as the sub-entries don't have the name displayed for the super styles.

```
\renewcommand*{\gls subgroupheading}[4]{}%
\renewcommand{\glossentry}[2]{%
\glsentryitem{##1}\glstarget{##1}{\glossentryname{##1}} &
\glossentrydesc{##1}\glspostdescription &
##2\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
&
\gls subentryitem{##2}%
\glstarget{##2}{\strut}\glossentrydesc{##2}\glspostdescription &
##3\tabularnewline
}%

\ifglsnogroupskip
\renewcommand*{\gls groupskip}{}%
\else
\renewcommand*{\gls groupskip}{ & \tabularnewline}%
\fi
}
}
{}

```

Four columns:

```
\ifcsdef{@glsstyle@altsuperragged4col}
{%
\renewglossarystyle{altsuperragged4col}{%
\renewenvironment{theglossary}%
{\tablehead{}\tabletail}%
\begin{supertabular}{1>{\raggedright}p{\glsdescwidth}1%
>{\raggedright}p{\glspagelistwidth}}}%
{\end{supertabular}}%
\renewcommand*{\glossaryheader}{}%
\renewcommand{\glossentry}[2]{%
\glsentryitem{##1}\glstarget{##1}{\glossentryname{##1}} &
\glossentrydesc{##1}\glspostdescription &
\glossentrysymbol{##1} & ##2\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
&

```

```

\glssubentryitem{##2}%
\glstarget{##2}{\strut}\glossentrydesc{##2}\glspostdescription &
\glossentrysymbol{##2} & ##3\tabularnewline
}%

\ifglsnogroupskip
\renewcommand*{\glsgroupskip}{}%
\else
\renewcommand*{\glsgroupskip}{& & \tabularnewline}%
\fi
}
}
{}

```

4.7 Inline Style

The inline style is dealt with slightly differently. The `\glspostdescription` hook is actually in `\glspostinline`, which is called at the end of the glossary. The original definition of `\glspostinline` also includes a space, which is unnecessary. Here, instead of redefining the inline style, just redefine `\glspostinline` and `\glsinlinedescformat`.

```

\ifdef{\@glstyle@inline}
{%
\renewcommand*{\glspostinline}{.\spacefactor\sffcode{\.}

```

Just use `\glsxtrpostdescription` instead of `\glspostdescription`.

```

\renewcommand*{\glsinlinedescformat}[3]{%
\space#1\glsxtrpostdescription}
\renewcommand*{\glsinlinesubdescformat}[3]{%
#1\glsxtrpostdescription}

```

The default settings don't show the location lists, so there's no adjustment for `\glsxtrprelocation`.

```

}
{}

```

4.8 Tree Styles

Redefine both `\glstreenamefmt` and `\glstreegroupheaderfmt` in terms of `\glstreedefaultnamefmt` to make it easier to change both at the same time or only change one without affecting the other.

```

\ifdef\glstreenamefmt
{

```

```

\glstreedefaultnamefmt

```

```

\newcommand{\glstreedefaultnamefmt}[1]{\textbf{#1}}

```

```

\glstreenamefmt

```

```

\renewcommand{\glstreenamefmt}[1]{\glstreedefaultnamefmt{#1}}

```

`\glstreegroupheaderfmt` This command was only introduced to glossary-tree v4.22, so it may not be defined.

```
\def\glstreegroupheaderfmt#1{\glstreedefaultnamefmt{#1}}
```

`\glstreenavigationfmt` This command was only introduced to glossary-tree v4.22, so it may not be defined.

```
\def\glstreenavigationfmt#1{\glstreedefaultnamefmt{#1}}
```

`\glstreePreHeader` Takes the label as the first argument and title as the second argument so this can be modified to add a bookmark.

```
\newcommand{\glstreePreHeader}[2]{}
```

`\glstreeSubPreHeader`

```
\glstreeSubPreHeader{<previous group level>}{<level>}
{<parent label>}{<group label>}{<title>}
```

```
\newcommand{\glstreeSubPreHeader}[5]{}
}
```

```
{}
```

The index style is redefined so that the space before the number list isn't hard coded.

```
\ifdef{\@glsstyle@index}
{
```

`\glstreeprelocation` The space before the number list for top-level entries. This is shared by the other tree styles.

```
\newcommand*\glstreeprelocation{\glstxtrprelocation}
```

`\glstreechildprelocation` The space before the number list for child entries. This is shared by the other tree styles.

```
\newcommand*\glstreechildprelocation{\glstreeprelocation}
```

Don't prohibit a page break at the start of a new group if there's no header.

`\glstreegroupskip`

```
\newcommand{\glstreegroupskip}{\indexspace}
```

`\glstreegroupheaderskip` This doesn't include `\@afterheading` as it can cause interference with some styles.

```
\newcommand{\glstreegroupheaderskip}{\nopagebreak\glstreegroupskip\nobreak}
```

Modify the index style.

```
\renewglossarystyle{index}{%
\renewenvironment{theglossary}%
{\setlength{\parindent}{0pt}%
\setlength{\parskip}{0pt plus 0.3pt}%
```

```

\let\item\glstreeitem
\let\subitem\glstreesubitem
\let\subsubitem\glstreesubsubitem
}%
{\par}%
\renewcommand*{\glossaryheader}{}%
\renewcommand*{\glsgroupheading}[1]{}%

```

Sub-groups are only supported with `\printunsrtglossary`.

```

\renewcommand*{\glssubgroupheading}[4]{}%
\renewcommand*{\glossentry}[2]{%
  \item\glstreeitem{##1}%
  \glstreenamefmt{\glstarget{##1}{\glossentryname{##1}}}%
  \glstreesymbol{##1}%
  \glstreeDescLoc{##1}{##2}%
}%
\renewcommand{\subglossentry}[3]{%
  \ifcase##1\relax
    \item
  \or
    \subitem
    \glssubentryitem{##2}%
  \else
    \subsubitem
  \fi
  \glstreenamefmt{\glstarget{##2}{\glossentryname{##2}}}%
  \glstreechildsymbol{##2}%
  \glstreeChildDescLoc{##2}{##3}%
}%
\renewcommand*{\glsgroupskip}{\ifglsnogroupskip\else\glstreegroupskip\fi}%
}
}
{}

```

The `indexgroup` style is redefined to discourage a page break after the heading.

```

\ifdef{\@glsstyle@indexgroup}
{%

```

Provide formatting command for sub-headings to make it easier to adjust.

```

\glsindexsubgroupitem{<previous group level>}{<level>}
{<parent label>}{<group label>}{<title>}

```

`\glsindexsubgroupitem`

```

\newcommand*{\glsindexsubgroupitem}[5]{%
  \ifcase#2\relax

```

This case shouldn't occur as `\glsgroupheading` will be used instead, but include for completeness.

```

\item \glstreegroupheaderfmt{#5}%
\glstreegroupheaderskip
\or
\smallskip
\subitem \glstreegroupheaderfmt{#5}%
\smallskip
\else
\smallskip
\subsubitem \glstreegroupheaderfmt{#5}%
\smallskip
\fi
}

\renewglossarystyle{indexgroup}{%
\setglossarystyle{index}%
}

Group heading.
\renewcommand*{\glsgroupheading}[1]{%
\glstrgetgrouptitle{##1}{\glstr@grptitle}%
\glstreePreHeader{##1}{\glstr@grptitle}%
\item\glstreegroupheaderfmt{\glstr@grptitle}%
\glstreegroupheaderskip\@afterheading
}%

Sub-groups are only supported with \printunsrtglossary.
\renewcommand*{\glssubgroupheading}[4]{%
\glstrgetgrouptitle{##4}{\glstr@grptitle}%
\glstreeSubPreHeader{##1}{##2}{##3}{##4}{\glstr@grptitle}%
\glindexsubgroupitem{##1}{##2}{##3}{##4}{\glstr@grptitle}%
\@afterheading
}%
}
}
{}

Similarly for indexhypergroup.
\ifdef{\@glstyle@indexhypergroup}
{%
\renewglossarystyle{indexhypergroup}{%
\setglossarystyle{index}%
\renewcommand*{\glossaryheader}{%
\item\glstreenavigationfmt{\glstr@navigation}%
\glstreegroupheaderskip\@afterheading}%
}
}

Group heading.
\renewcommand*{\glsgroupheading}[1]{%
\glstrgetgrouptitle{##1}{\glstr@grptitle}%
\glstreePreHeader{##1}{\glstr@grptitle}%
\item\glstreegroupheaderfmt
{\glstr@navigationtarget{##1}{\glstr@grptitle}}%
\glstreegroupheaderskip\@afterheading}%

```


Sub-groups are only supported with `\printunsrtglossary`.

```
\renewcommand*{\glssubgroupheading}[4]{%
  \glstrgetgrouptitle{##4}{\glstr@grptitle}%
  \glstreeSubPreHeader{##1}{##2}{##3}{##4}{\glstr@grptitle}%
  \glindexsubgroupitem{##1}{##2}{##3}{##4}%
  {\glsnahypertarget{##4}{\glstr@grptile}}}%
  \@afterheading
}%
}%
}
```

Adjust tree style to remove hard coded space before number list.

```
\ifdef{\@glstyle@tree}
{%
```

The original `alttree` style doesn't use `\glstreepredesc` but since v1.42 the modified style (below) has switched to using `\glstreeDescLoc` so provide an alternative that can be used with `alttree`.

```
\glxtrtreepredesc
```

```
\newcommand{\glxtrtreepredesc}{\glstreepredesc}
```

```
\glxtrtreechildpredesc
```

```
\newcommand{\glxtrtreechildpredesc}{\glstreechildpredesc}
```

Provide a command for use with the tree styles that displays the pre-description separator, the description and post-description hook.

```
\glstreedesc
```

```
\newcommand{\glstreedesc}[1]{%
  \glxtrtreepredesc\glossentrydesc{#1}\glspostdescription
}
```

```
\glstreeDescLoc{<label>}{<location>}
```

```
\glstreeDescLoc
```

This checks for the description and symbol. If both are missing, a different separator may be required. For example, a comma and space if there's no description or symbol but just a space if either of those fields are present.

```
\newcommand{\glstreeDescLoc}[2]{%
  \ifglshasdesc{#1}%
  {\glstreedesc{#1}\glstreeprelocation}%
  {\ifglshassymbol{#1}{\glstreeprelocation}{\glstreeNoDescSymbolPreLocation}}%
  #2%
}
```

```
\glstreeNoDescSymbolPreLocation
```

```
treeNoDescSymbolPreLocation
```

```
\newcommand{\glstreeNoDescSymbolPreLocation}{\space}
```

Similarly for the symbol.

```
\glstreesymbol
```

```
\newcommand{\glstreesymbol}[1]{%
  \ifglshassymbol{#1}{\space(\glossentrysymbol{#1})}{}%
}%
```

And for the child entries:

```
\glstreechilddesc
```

```
\newcommand{\glstreechilddesc}[1]{%
  \glstxttreechildpredesc\glossentrydesc{#1}\glspostdescription
}%
```

```
\glstreeChildDescLoc
```

```
\newcommand{\glstreeChildDescLoc}[2]{%
  \ifglshasdesc{#1}%
  {\glstreechilddesc{#1}\glstreechildprelocation}%
  {\ifglshassymbol{#1}{\glstreechildprelocation}%
   {\glstreeNoDescSymbolPreLocation}%
  }%
  #2%
}%
```

`\glstreechildsymbol` This just behaves in the same way as the top-level.

```
\newcommand{\glstreechildsymbol}[1]{%
  \glstreesymbol{#1}%
}%
```

Redefine tree style.

```
\renewglossarystyle{tree}{%
  \renewenvironment{theglossary}%
  {\setlength{\parindent}{0pt}%
   \setlength{\parskip}{0pt plus 0.3pt}}%
  {}%
  \renewcommand*{\glossaryheader}{}%
```

Group heading.

```
\renewcommand*{\glsgroupheading}[1]{}%
```

Sub-groups are only supported with `\printunsrtglossary`.

```
\renewcommand*{\glssubgroupheading}[4]{}%
```

Top level entry.

```
\renewcommand{\glossentry}[2]{%
  \hangindent0pt\relax
  \parindent0pt\relax
  \glstentryitem{##1}\glstreenamefmt{\glstarget{##1}{\glossentryname{##1}}}%
  \glstreesymbol{##1}%
  \glstreeDescLoc{##1}{##2}\par
}%
```

Sub entries.

```
\renewcommand{\subglossentry}[3]{%
  \hangindent##1\glstreeindent\relax
  \parindent##1\glstreeindent\relax
  \ifnum##1=1\relax
    \glssubentryitem{##2}%
  \fi
  \glstreenamelfmt{\glstarget{##2}{\glossentryname{##2}}}%
  \glstreechildsymbol{##2}%
  \glstreeChildDescLoc{##2}{##3}\par
}%
\renewcommand*{\glsgroupskip}{\ifglsgnোগroupskip\else\glstreegroupskip\fi}%
}%
{}
}
```

The `treegroup` style is redefined to discourage a page break after the heading.

```
\ifdef{\@glstyle@treegroup}
{%
```

Provide formatting command for sub-headings to make it easier to adjust.

```
\glstreesubgroupitem{<previous group level>}{<level>}
{<parent label>}{<group label>}{<title>}
```

`\glstreesubgroupitem`

```
\newcommand*{\glstreesubgroupitem}[5]{%
  \par\smallskip\noindent\hspace{#2\glstreeindent}%
  \glstreegroupheaderfmt{#5}\smallskip\par
}
```

Redefine `treegroup` style.

```
\renewglossarystyle{treegroup}{%
  \setglossarystyle{tree}%
}
```

Group heading.

```
\renewcommand{\glsgroupheading}[1]{%
  \glstrgetgrouptitle{##1}{\glstr@grptitle}%
  \glstreePreHeader{##1}{\glstr@grptitle}%
  \par\noindent\glstreegroupheaderfmt{\glstr@grptitle}%
  \glstreegroupheaderskip\@afterheading}%
}
```

Sub-groups are only supported with `\printunsrtglossary`.

```
\renewcommand*{\glssubgroupheading}[4]{%
  \glstrgetgrouptitle{##4}{\glstr@grptitle}%
  \glstreeSubPreHeader{##1}{##2}{##3}{##4}{\glstr@grptitle}%
  \glstreesubgroupitem{##1}{##2}{##3}{##4}{\glstr@grptitle}%
}%
}
```

```
}
{}
```

Similarly for treehypergroup

```
\ifdef{\@glsstyle@treehypergroup}
{%
  \renewglossarystyle{treehypergroup}{%
    \setglossarystyle{tree}%
    \renewcommand*{\glossaryheader}{%
      \par\noindent\glstreenavigationfmt{\glsnavigation}%
      \glstreegroupheaderskip\@afterheading}%

```

Group heading.

```
\renewcommand*{\glsgroupheading}[1]{%
  \glsxtrgetgrouptitle{##1}{\glsxtr@grptitle}%
  \glstreePreHeader{##1}{\glsxtr@grptitle}%
  \par\noindent
  \glstreegroupheaderfmt
    {\glsnavhypertarget{##1}{\glsxtr@grptitle}}%
  \glstreegroupheaderskip\@afterheading}%

```

Sub-groups are only supported with \printunsrtglossary.

```
\renewcommand*{\glssubgroupheading}[4]{%
  \glsxtrgetgrouptitle{##4}{\glsxtr@grptitle}%
  \glstreeSubPreHeader{##1}{##2}{##3}{##4}{\glsxtr@grptitle}%
  \glstreesubgroupitem{##1}{##2}{##3}{##4}%
    {\glsnavhypertarget{##4}{\glsxtr@grptitle}}%
  }%
}

```

```
}
{}
```

Adjust treenoname style to remove hard coded space before number list.

```
\ifdef{\@glsstyle@treenoname}
{%

```

Provide a command for use with the treenoname styles that displays the pre-description separator, the description and post-description hook.

```
\glstreenonamedesc
  \newcommand{\glstreenonamedesc}[1]{%
    \glstreepredesc\glossentrydesc{#1}\glspostdescription
  }%

```

Similarly for the symbol.

```
\glstreenonamesymbol
  \newcommand{\glstreenonamesymbol}[1]{%
    \ifglshassymbol{#1}{\space\glossentrysymbol{#1}}{}}%
  }%

```

`\glstreenonameDescLoc`

```
\newcommand{\glstreenonameDescLoc}[2]{%
  \glstreenonamedesc{#1}\glstreeprelocation#2%
}
```

`\glstreenonamechilddesc` The child entry doesn't have the pre-description separator as the name isn't displayed.

```
\newcommand{\glstreenonamechilddesc}[1]{%
  \glossentrydesc{#1}\glspostdescription
}%
```

`\glstreenonameChildDescLoc`

```
\newcommand{\glstreenonameChildDescLoc}[2]{%
  \glstreenonamechilddesc{#1}\glstreechildprelocation#2%
}
```

Redefine treenoname style

```
\renewglossarystyle{treenoname}{%
  \renewenvironment{theglossary}%
    {\setlength{\parindent}{0pt}%
     \setlength{\parskip}{0pt plus 0.3pt}}%
    {}%
  \renewcommand*{\glossaryheader}{}%
}
```

Group heading.

```
\renewcommand*{\glsgroupheading}[1]{}%
```

Sub-groups are only supported with `\printunsrtglossary`.

```
\renewcommand*{\glssubgroupheading}[4]{}%
\renewcommand{\glossentry}[2]{%
  \hangindent0pt\relax
  \parindent0pt\relax
  \glstryitem{##1}\glstreenamefmt{\glstarget{##1}{\glossentryname{##1}}}%
  \glstreenonamesymbol{##1}%
}
```

```
\glstreenonameDescLoc{##1}{##2}\par
}%
```

```
\renewcommand{\subglossentry}[3]{%
  \hangindent##1\glstreeindent\relax
  \parindent##1\glstreeindent\relax
  \ifnum##1=1\relax
    \glssubentryitem{##2}%
  \fi
  \glstarget{##2}{\strut}%
  \glstreenonameChildDescLoc{##2}{##3}\par
}%
```

```
\renewcommand*{\glsgroupskip}{\ifglsgnোগroupskip\else\glstreegroupskip\fi}%
```

```
}
}
{}
}
```

The `treenonamegroup` style is redefined to discourage a page break after the heading. There are no sub-groups as sub-entries don't have the name shown.

```
\ifdef{\@glsstyle@treenonamegroup}
{%
  \renewglossarystyle{treenonamegroup}{%
    \setglossarystyle{treenoname}%
    \renewcommand{\glsgroupheading}[1]{%
      \glstrgetgrouptitle{##1}{\glstr@grptitle}%
      \glstreePreHeader{##1}{\glstr@grptitle}%
      \par\noindent\glstreegroupheaderfmt{\glstr@grptitle}%
      \glstreegroupheaderskip\@afterheading
    }%
  }
}
{}

```

Similarly for `treenonamehypergroup`

```
\ifdef{\@glsstyle@treenonamehypergroup}
{%
  \renewglossarystyle{treenonamehypergroup}{%
    \setglossarystyle{treenoname}%
    \renewcommand*\{\glossaryheader}{%
      \par\noindent\glstreenavigationfmt{\glsnavigation}%
      \glstreegroupheaderskip\@afterheading}%
    \renewcommand*\{\glsgroupheading}[1]{%
      \glstrgetgrouptitle{##1}{\glstr@grptitle}%
      \glstreePreHeader{##1}{\glstr@grptitle}%
      \par\noindent
      \glstreegroupheaderfmt{\glsnavhypertarget{##1}{\glstr@grptitle}}%
      \glstreegroupheaderskip\@afterheading}%
    }
  }
}
{}

```

Version 1.6: Check for the existence of new function added to `glossary-tree` v4.59.

```
\ExplSyntaxOn
\cs_if_exist:NT \glossaries_tree_set_widest_name:nn
{

```

`\gglissetwidest`

```
\NewDocumentCommand \gglissetwidest { 0{0} m }
{
  \glossaries_tree_gset_widest_name:nn { #1 } { #2 }
}

```

`\eglssetwidest` Locally set expanded value. NB protected expansion is required in case of fragile commands.

```
\NewDocumentCommand \eglssetwidest { 0{0} m }
{

```

```

\int_compare:nNnT
{ #1 } > { \l__glossaries_tree_max_known_level_int }
{
  \int_set:Nn \l__glossaries_tree_max_known_level_int { #1 }
}
\protected@csedef { @glswidestname \romannumeral #1 } { #2 }
}

```

`\xglissetwidest` Globally set expanded value. NB protected expansion is required in case of fragile commands.

```

\NewDocumentCommand \xglissetwidest { 0{0} m }
{
  \int_compare:nNnT
  { #1 } > { \l__glossaries_tree_max_known_level_int }
  {
    \int_gset:Nn \l__glossaries_tree_max_known_level_int { #1 }
  }
  \protected@csxdef { @glswidestname \romannumeral #1 } { #2 }
}

```

Only set if wider than the current value.

```

\cs_new:Nn \__glossaries_extra_update_widest:Nnn
{
  \ifcsundef { @glswidestname \romannumeral #2 }
  { #1 [ #2 ] { #3 } }
  {
    \exp_args:NNv \glsmeasurewidth \l__glossaries_tmpa_dim
    { @glswidestname \romannumeral #2 }
    \glsmeasurewidth \l__glossaries_tmpb_dim { #3 }
    \dim_compare:nNnT
    { \l__glossaries_tmpb_dim } > { \l__glossaries_tmpa_dim }
    {
      #1 [ #2 ] { #3 }
    }
  }
}

```

`\glsupdatewidest` Only sets if new value is wider than old value.

```

\NewDocumentCommand \glsupdatewidest { 0{0} m }
{
  \__glossaries_extra_update_widest:Nnn
  \glissetwidest { #1 } { #2 }
}

```

`\gglsupdatewidest` As above but global definition.

```

\NewDocumentCommand \gglsupdatewidest { 0{0} m }
{
  \__glossaries_extra_update_widest:Nnn
  \gglssetwidest { #1 } { #2 }
}

```

`\eglsupdatewidest` As `\glsupdatewidest` but expands value.

```
\NewDocumentCommand \eglsupdatewidest { 0{0} m }
{
  \__glossaries_extra_update_widest:Nnn
  \eglssetwidest { #1 } { #2 }
}
```

`\xglsupdatewidest` As above but global.

```
\NewDocumentCommand \xglsupdatewidest { 0{0} m }
{
  \__glossaries_extra_update_widest:Nnn
  \xglssetwidest { #1 } { #2 }
}

\ExplSyntaxOff
```

The `alttree` style is redefined to make it easier to made minor adjustments.

```
\ifdef{\@glsstyle@alttree}
{%
```

Only redefine this style if it's already been defined.

`\glsalttreepredesc`

```
\newcommand{\glsalttreepredesc}{}
```

`\glsalttreechildpredesc`

```
\newcommand{\glsalttreechildpredesc}{\glsalttreepredesc}
```

```
\glsxtralttreeSymbolDescLocation{<label>}{<location
list>}
```

`\glsxtralttreeSymbolDescLocation`

Layout the symbol, description and location for top-level entries.

```
\newcommand{\glsxtralttreeSymbolDescLocation}[2]{%
  {%
    \let\par\glsxtrAltTreePar

    \let\glsxtrtreepredesc\glsalttreepredesc
    \let\glsxtrtreechildpredesc\glsalttreechildpredesc
    \ifgls hassymbol{#1}{(\glossentrysymbol{#1})\space}{}%

    \glstreeDescLoc{#1}{#2}\par
  }%
}
```

`\glsxtrAltTreeIndent` Paragraph indent for subsequent paragraphs in multi-paragraph descriptions.

```
\newlength\glsxtrAltTreeIndent
```


`\glxtrAltTreePar` Multi-paragraph descriptions need to keep the hanging indent.

```
\newcommand{\glxtrAltTreePar}{%
  @@par
  \glxtrAltTreeSetHangIndent
  \setlength{\parindent}{\dimexpr\hangindent+\glxtrAltTreeIndent}%
}
```

```
\glxtralttreeSubSymbolDescLocation{<level>}{<label>}
{<location
list>}
```

`alttreeSubSymbolDescLocation`

Layout the symbol, description and location for sub-entries. Defaults to the same as the top-level.

```
\newcommand{\glxtralttreeSubSymbolDescLocation}[3]{%
  \glxtralttreeSymbolDescLocation{#2}{#3}%
}
```

`\glxtrtreetopindent` The original style has to keep computing the width of the name at each entry. This register allows the style to compute it once for the top-level at the start of the glossary.

```
\newlength\glxtrtreetopindent
```

`\glxtralttreeInit` User-level initialisation for the alttree style.

```
\newcommand*{\glxtralttreeInit}{%
  \glsmesurewidth{\glxtrtreetopindent}{\glstreenamfmt{\glsggetwidestname\space}}%
  \glxtrAltTreeIndent=\parindent
}
```

Older definitions. Now use `\ProvideDocumentCommand` to provide fallback definitions if an older version of glossary-tree is installed.

Globally set the widest value.

```
\ProvideDocumentCommand\gglsetwidest{0{0}m}{%
  \csgdef{@glswidestname\romannumeral#1}{#2}%
}
```

Local protected expansion:

```
\ProvideDocumentCommand\eglssetwidest{0{0}m}{%
  \protected@csgdef{@glswidestname\romannumeral#1}{#2}%
}
```

Like the above but uses `\protected@csxdef`.

```
\ProvideDocumentCommand\xglssetwidest{0{0}m}{%
  \protected@csxdef{@glswidestname\romannumeral#1}{#2}%
}
```

Only sets if new value is wider than old value.

```
\ProvideDocumentCommand\glsupdatewidest{0{0}m}{%
  \ifcsundef{@glswidestname\romannumeral#1}%
}
```

```

{ \csdef{@glswidestname\romannumeral#1}{#2}}%
{%
  \settowidth{\dimen@}{\csuse{@glswidestname\romannumeral#1}}%
  \settowidth{\dimen@ii}{#2}%
  \ifdim\dimen@ii>\dimen@
    \csdef{@glswidestname\romannumeral#1}{#2}%
  \fi
}%
}

```

As above but global definition.

```

\ProvideDocumentCommand\gglupdatewidest{0{0}m}{%
  \ifcsundef{@glswidestname\romannumeral#1}%
  {\csgdef{@glswidestname\romannumeral#1}{#2}}%
  {%
    \settowidth{\dimen@}{\csuse{@glswidestname\romannumeral#1}}%
    \settowidth{\dimen@ii}{#2}%
    \ifdim\dimen@ii>\dimen@
      \csgdef{@glswidestname\romannumeral#1}{#2}%
    \fi
  }%
}

```

As `\glsupdatewidest` but expands value.

```

\ProvideDocumentCommand\eglsupdatewidest{0{0}m}{%
  \ifcsundef{@glswidestname\romannumeral#1}%
  {\protected@csdef{@glswidestname\romannumeral#1}{#2}}%
  {%
    \settowidth{\dimen@}{\csuse{@glswidestname\romannumeral#1}}%
    \settowidth{\dimen@ii}{#2}%
    \ifdim\dimen@ii>\dimen@
      \protected@csdef{@glswidestname\romannumeral#1}{#2}%
    \fi
  }%
}

```

```

\ProvideDocumentCommand\xglsupdatewidest{0{0}m}{%
  \ifcsundef{@glswidestname\romannumeral#1}%
  {\protected@csxdef{@glswidestname\romannumeral#1}{#2}}%
  {%
    \settowidth{\dimen@}{\csuse{@glswidestname\romannumeral#1}}%
    \settowidth{\dimen@ii}{#2}%
    \ifdim\dimen@ii>\dimen@
      \protected@csxdef{@glswidestname\romannumeral#1}{#2}%
    \fi
  }%
}

```

`\glsgetwidestname` Provide a user-level macro to obtain the widest top-level name.

```

\newcommand*{\glsgetwidestname}{\@glswidestname}

```

`\glsgetwidestsubname` Provide a user-level macro to obtain the widest sub-entry name.

```
\newcommand*\glsgetwidestsubname}[1]{%
  \ifcsundef{@glswidestname\romannumeral#1}%
  {\@glswidestname}%
  {\csuse{@glswidestname\romannumeral#1}}%
}
```

`\glsFindWidestTopLevelName` CamelCase is easier for long command names. Provide a CamelCase synonym of `\glsfindwidesttoplevelname`.

```
\let\glsFindWidestTopLevelName\glsfindwidesttoplevelname
```

`\glsFindWidestUsedTopLevelName` Like `\glsfindwidesttoplevelname` but has an additional check that the entry has been used. Only useful if the glossaries occur at the end of the document, in which case this command should go at the start of the glossary. Alternatively, place at the end of the document and save for the next run.

```
\newrobustcmd*\glsFindWidestUsedTopLevelName}[1][\@glo@types]{%
  \dimen@=0pt\relax
  \gls@tmplen=0pt\relax
  \foralllglossaries[#1]{\@gls@type}%
  {%
    \forglentries[\@gls@type]{\@glo@label}%
    {%
      \ifglused{\@glo@label}%
      {%
        \ifglshasparent{\@glo@label}%
        {}%
        {%
          \glsmeasurewidth{\dimen@}%
          {\glstreenamfmt{\glstentryname{\@glo@label}}}%
          \ifdim\dimen@>\gls@tmplen
            \gls@tmplen=\dimen@
            \eglssetwidest{\glstentryname{\@glo@label}}%
          \fi
        }%
      }%
    }%
  }%
}
```

`\glsFindWidestUsedAnyName` Like the above but doesn't check the parent key. Useful if all levels should have the same width for the name.

```
\newrobustcmd*\glsFindWidestUsedAnyName}[1][\@glo@types]{%
  \dimen@=0pt\relax
  \gls@tmplen=0pt\relax
  \foralllglossaries[#1]{\@gls@type}%
  {%
    \forglentries[\@gls@type]{\@glo@label}%
    {%
```

```

\ifglsused{\@glo@label}%
{%
  \glsmeasurewidth{\dimen@}%
  {\glstreenamefmt{\glentryname{\@glo@label}}}%
  \ifdim\dimen@>\gls@tmplen
    \gls@tmplen=\dimen@
    \eglssetwidest{\glentryname{\@glo@label}}%
  \fi
}%
}%
}%
}

```

`\glsFindWidestAnyName` Like the above but doesn't check if the entry has been used.

```

\newrobustcmd*{\glsFindWidestAnyName}[1][\@glo@types]{%
  \dimen@=0pt\relax
  \gls@tmplen=0pt\relax
  \forallglossaries[#1]{\@gls@type}%
  {%
    \forglsentries[\@gls@type]{\@glo@label}%
    {%
      \glsmeasurewidth{\dimen@}%
      {\glstreenamefmt{\glentryname{\@glo@label}}}%
      \ifdim\dimen@>\gls@tmplen
        \gls@tmplen=\dimen@
        \eglssetwidest{\glentryname{\@glo@label}}%
      \fi
    }%
  }%
}

```

`\glsFindWidestUsedLevelTwo` This is like `\glsFindWidestUsedTopLevelName` but also sets the first two sub-levels as well. Any entry that has a great-grandparent is ignored.

```

\newrobustcmd*{\glsFindWidestUsedLevelTwo}[1][\@glo@types]{%
  \dimen@=0pt\relax
  \dimen@i=0pt\relax
  \dimen@ii=0pt\relax
  \forallglossaries[#1]{\@gls@type}%
  {%
    \forglsentries[\@gls@type]{\@glo@label}%
    {%
      \ifglsused{\@glo@label}%
      {%
        \ifglshasparent{\@glo@label}%
        {%
          \protected@edef\@glo@parent{\csuse{glo@\glsdetoklabel}{\@glo@label}@parent}}%
          \ifglshasparent{\@glo@parent}%
          {%

```

```

\protected@edef\@glo@parent{\csuse{glo@glstdetoklabel{\@glo@parent}@parent}}%
\ifglshasparent{\@glo@parent}%
{%
  \glsmmeasurewidth{\gls@tmplen}%
  {\glstreenamefmt{\glstentryname{\@glo@label}}}%
  \ifdim\gls@tmplen>\dimen@ii
    \dimen@ii=\gls@tmplen
    \eglssetwidest[2]{\glstentryname{\@glo@label}}%
  \fi
}%
}%
{%
  \glsmmeasurewidth{\gls@tmplen}%
  {\glstreenamefmt{\glstentryname{\@glo@label}}}%
  \ifdim\gls@tmplen>\dimen@i
    \dimen@i=\gls@tmplen
    \eglssetwidest[1]{\glstentryname{\@glo@label}}%
  \fi
}%
}%
{%
  \glsmmeasurewidth{\gls@tmplen}%
  {\glstreenamefmt{\glstentryname{\@glo@label}}}%
  \ifdim\gls@tmplen>\dimen@
    \dimen@=\gls@tmplen
    \eglssetwidest{\glstentryname{\@glo@label}}%
  \fi
}%
}%
}%
}%
}

```

`\glsFindWidestLevelTwo` This is like `\glsFindWidestUsedLevelTwo` but doesn't check if the entry has been used.

```

\newrobustcmd*{\glsFindWidestLevelTwo}[1][\@glo@types]{%
  \dimen@=0pt\relax
  \dimen@i=0pt\relax
  \dimen@ii=0pt\relax
  \foralllglossaries[#1]{\@gls@type}%
  {%
    \forglstentries[\@gls@type]{\@glo@label}%
    {%
      \ifglshasparent{\@glo@label}%
      {%
        \protected@edef\@glo@parent{\csuse{glo@glstdetoklabel{\@glo@label}@parent}}%
        \ifglshasparent{\@glo@parent}%

```

```

{%
\protected@edef\@glo@parent{\csuse{glo@glstetoklabel{\@glo@parent}@parent}}%
\ifglshasparent{\@glo@parent}%
}%
{%
\glsmeasurewidth{\gls@tmplen}%
{\glstreenamefmt{\glstentryname{\@glo@label}}}%
\ifdim\gls@tmplen>\dimen@ii
\dimen@ii=\gls@tmplen
\eglssetwidest[2]{\glstentryname{\@glo@label}}%
\fi
}%
}%
{%
\glsmeasurewidth{\gls@tmplen}%
{\glstreenamefmt{\glstentryname{\@glo@label}}}%
\ifdim\gls@tmplen>\dimen@i
\dimen@i=\gls@tmplen
\eglssetwidest[1]{\glstentryname{\@glo@label}}%
\fi
}%
}%
{%
\glsmeasurewidth{\gls@tmplen}%
{\glstreenamefmt{\glstentryname{\@glo@label}}}%
\ifdim\gls@tmplen>\dimen@
\dimen@=\gls@tmplen
\eglssetwidest{\glstentryname{\@glo@label}}%
\fi
}%
}%
}%
}

```

FindWidestUsedAnyNameSymbol Like the `\glsFindWidestUsedAnyName` but also measures the symbol. The length of the widest symbol is stored in the second argument should be a length register.

```

\newrobustcmd*{\glsFindWidestUsedAnyNameSymbol}[2][\@glo@types]{%
\dimen@=0pt\relax
\gls@tmplen=0pt\relax
#2=0pt\relax
\foralllglossaries[#1]{\@gls@type}%
{%
\forglstentries[\@gls@type]{\@glo@label}%
{%
\ifglssused{\@glo@label}%
{%
\glsmeasurewidth{\dimen@}%
{\glstreenamefmt{\glstentryname{\@glo@label}}}%
\ifdim\dimen@>\gls@tmplen

```

```

        \gls@tmplen=\dimen@
        \eglssetwidest{\glsentryname{\@glo@label}}%
    \fi
    \glsmeasurewidth{\dimen@}%
    {\glsentrysymbol{\@glo@label}}%
    \ifdim\dimen@>#2\relax
        #2=\dimen@
    \fi
} %
{} %
} %
} %
}

```

`\glsFindWidestAnyNameSymbol` Like the above but doesn't check if the entry has been used.

```

\newrobustcmd*{\glsFindWidestAnyNameSymbol}[2][\@glo@types]{%
    \dimen@=0pt\relax
    \gls@tmplen=0pt\relax
    #2=0pt\relax
    \foralllglossaries[#1]{\@gls@type}%
    {%
        \forglsentries[\@gls@type]{\@glo@label}%
        {%
            \glsmeasurewidth{\dimen@}%
            {\glstreenamfmt{\glsentryname{\@glo@label}}}%
            \ifdim\dimen@>\gls@tmplen
                \gls@tmplen=\dimen@
                \eglssetwidest{\glsentryname{\@glo@label}}%
            \fi
            \glsmeasurewidth{\dimen@}%
            {\glsentrysymbol{\@glo@label}}%
            \ifdim\dimen@>#2\relax
                #2=\dimen@
            \fi
        }%
    }%
}

```

`\glsFindWidestUsedAnyNameSymbolLocation` Like the `\glsFindWidestUsedAnyNameSymbol` but also measures the location list. This requires `\glsentrynumberlist`. The length of the widest symbol is stored in the second argument should be a length register. The length of the widest location list is stored in the third argument, which should also be a length register.

```

\newrobustcmd*{\glsFindWidestUsedAnyNameSymbolLocation}[3][\@glo@types]{%
    \dimen@=0pt\relax
    \gls@tmplen=0pt\relax
    #2=0pt\relax
    #3=0pt\relax
    \foralllglossaries[#1]{\@gls@type}%

```

```

{%
\for glsentries [\@gls@type]{\@glo@label}%
{%
\if glsused{\@glo@label}%
{%
\glsmmeasurewidth{\dimen@}%
{\glstreenamfmt{\glstryname{\@glo@label}}}%
\ifdim\dimen@>\gls@tmplen
\gls@tmplen=\dimen@
\eglssetwidest{\glstryname{\@glo@label}}%
\fi
\glsmmeasurewidth{\dimen@}%
{\glstrysymbol{\@glo@label}}%
\ifdim\dimen@>#2\relax
#2=\dimen@
\fi
\glsmmeasurewidth{\dimen@}%
{\GlsXtrFormatLocationList{\glstrynumberlist{\@glo@label}}}%
\ifdim\dimen@>#3\relax
#3=\dimen@
\fi
}%
}%
}%
}

```

WidestAnyNameSymbolLocation Like the `\glsFindWidestUsedAnyNameSymbol` but doesn't check if the entry has been used.

```

\newrobustcmd*{\glsFindWidestAnyNameSymbolLocation}[3][\@glo@types]{%
\dimen@=0pt\relax
\gls@tmplen=0pt\relax
#2=0pt\relax
#3=0pt\relax
\forall glossaries[#1]{\@gls@type}%
{%
\for glsentries [\@gls@type]{\@glo@label}%
{%
\glsmmeasurewidth{\dimen@}%
{\glstreenamfmt{\glstryname{\@glo@label}}}%
\ifdim\dimen@>\gls@tmplen
\gls@tmplen=\dimen@
\eglssetwidest{\glstryname{\@glo@label}}%
\fi
\glsmmeasurewidth{\dimen@}%
{\glstrysymbol{\@glo@label}}%
\ifdim\dimen@>#2\relax
#2=\dimen@
\fi
\glsmmeasurewidth{\dimen@}%

```



```

        {\GlsXtrFormatLocationList{\glsentrynumberlist{\@glo@label}}}%
\ifdim\dimen@>#3\relax
    #3=\dimen@
\fi
}%
}%
}

```

`\newrobustcmd*{\glsFindWidestUsedAnyNameLocation}` Like the `\glsFindWidestUsedAnyNameSymbolLocation` but doesn't measure the symbol. The length of the widest location list is stored in the second argument, which should be a length register.

```

\newrobustcmd*{\glsFindWidestUsedAnyNameLocation}[2][\@glo@types]{%
\dimen@=0pt\relax
\gls@tmplen=0pt\relax
#2=0pt\relax
\foralllglossaries[#1]{\@gls@type}%
{%
\forallglsentries[\@gls@type]{\@glo@label}%
{%
\ifglsused{\@glo@label}%
{%
\glsmeasurewidth{\dimen@}%
{\glstreenamefmt{\glsentryname{\@glo@label}}}%
\ifdim\dimen@>\gls@tmplen
\gls@tmplen=\dimen@
\eglissetwidest{\glsentryname{\@glo@label}}%
\fi
\glsmeasurewidth{\dimen@}%
{\GlsXtrFormatLocationList{\glsentrynumberlist{\@glo@label}}}%
\ifdim\dimen@>#2\relax
#2=\dimen@
\fi
}%
}%
}%
}%
}

```

`\glsFindWidestAnyNameLocation` Like the `\glsFindWidestAnyNameLocation` but doesn't check the first use flag.

```

\newrobustcmd*{\glsFindWidestAnyNameLocation}[2][\@glo@types]{%
\dimen@=0pt\relax
\gls@tmplen=0pt\relax
#2=0pt\relax
\foralllglossaries[#1]{\@gls@type}%
{%
\forallglsentries[\@gls@type]{\@glo@label}%
{%
\glsmeasurewidth{\dimen@}%
{\glstreenamefmt{\glsentryname{\@glo@label}}}%

```

```

\ifdim\dimen@>\gls@tmplen
\gls@tmplen=\dimen@
\eglssetwidest{\glsentryname{\@glo@label}}}%
\fi
\glsmeasurewidth{\dimen@}%
{\GlsXtrFormatLocationList{\glsentrynumberlist{\@glo@label}}}%
\ifdim\dimen@>#2\relax
#2=\dimen@
\fi
}%
}%
}

```

`\glsxtrComputeTreeIndent` Compute the value of `\glstreeindent`. Argument is the entry label. (Ignored in default definition, but this command may be redefined to take the particular entry into account.) Note that the sub-levels modify `\glstreeindent`.

```

\newcommand*{\glsxtrComputeTreeIndent}[1]{%
\glstreeindent=\glsxtrtreetopindent\relax
}

```

```

\glsxtrComputeTreeSubIndent{<level>}{<label>}{<register>}

```

`\glsxtrComputeTreeSubIndent`

Compute the indent for the sub-entries. The first argument is the level, the second argument is the entry label and the third argument is the length register used to store the computed indent.

```

\newcommand*{\glsxtrComputeTreeSubIndent}[3]{%
\ifcsundef{@glswidestname\romannumeral#1}%
{%
\glsmeasurewidth{#3}{\glstreenamefmt{\@glswidestname\space}}%
}%
{%
\glsmeasurewidth{#3}{\glstreenamefmt{%
\csname @glswidestname\romannumeral#1\endcsname\space}}%
}%
}

```

`\glsxtrAltTreeSetHangIndent` Set `\hangindent` for top-level entries:

```

\newcommand*{\glsxtrAltTreeSetHangIndent}{\hangindent\glstreeindent}

```

`\glsxtrAltTreeSetSubHangIndent` Set `\hangindent` for sub-entries:

```

\newcommand*{\glsxtrAltTreeSetSubHangIndent}[1]{\hangindent\glstreeindent}

```

Redefine `almtree`:

```

\renewglossarystyle{almtree}{%
\renewenvironment{theglossary}%
{%
\glsxtralmtreeInit

```

```

\def\@gls@prevlevel{-1}%
\mbox{}\par}%
{\par}%
\renewcommand*{\glossaryheader}{}%
\renewcommand*{\glsgroupheading}[1]{}%

```

Sub-groups are only supported with \printunsrtglossary.

```

\renewcommand*{\glssubgroupheading}[4]{}%
\renewcommand{\glossentry}[2]{%
\ifnum\@gls@prevlevel=0\relax
\else
\glstrComputerTreeIndent{##1}%
\fi
\parindent\glstreeindent
\glstrAltTreeSetHangIndent
\makebox[Opt][r]%
{%
\glstreenamebox{\glstreeindent}%
{%
\glssentryitem{##1}%
\glstreenamefmt{\glstarget{##1}{\glossentryname{##1}}}%
}%
}%
\glstralttreeSymbolDescLocation{##1}{##2}%
\def\@gls@prevlevel{0}%
}
\renewcommand{\subglossentry}[3]{%
\ifnum##1=1\relax
\glssubentryitem{##2}%
\fi
\ifnum\@gls@prevlevel=##1\relax
\else
\glstrComputerTreeSubIndent{##1}{##2}{\gls@tmplen}%
\ifnum\@gls@prevlevel<##1\relax
\setlength\glstreeindent\gls@tmplen
\addtolength\glstreeindent\parindent
\parindent\glstreeindent
\else
\ifnum\@gls@prevlevel=0\relax
\glstrComputerTreeIndent{##2}%
\else
\glstrComputerTreeSubIndent{\@gls@prevlevel}{##2}{\glstreeindent}%
\fi
\addtolength\parindent{-\glstreeindent}%
\setlength\glstreeindent\parindent
\fi
\fi
\glstrAltTreeSetSubHangIndent{##1}%
\makebox[Opt][r]{\glstreenamebox{\gls@tmplen}{%
\glstreenamefmt{\glstarget{##2}{\glossentryname{##2}}}}}%

```

```

\glxtralttreeSubSymbolDescLocation{##1}{##2}{##3}%
\def\@gls@prevlevel{##1}%
}%
\renewcommand*\{gls@groupskip}{\ifglsnogroupskip\else\glstreegroupskip\fi}%
}
}%
{%
}

```

Redefine `alttreegroup` so that it discourages a break after group headings.

```

\ifdef{\@glsstyle@alttreegroup}
{

```

```

\glsalttreesubgroupheader{\previous group level}{\group
level}{\parent label}{\group label}{\title}{\width}

```

`\glsalttreesubgroupitem`

```

\newcommand*\{glsalttreesubgroupheader}[6]{%
\par\smallskip
\makebox[0pt][r]{\glstreenamebox{#6}%
{\glstreegroupheaderfmt{#5}}}%
\smallskip\par
}

\renewglossarystyle{alttreegroup}{%
\setglossarystyle{alttree}%
\renewcommand{\gls@groupheading}[1]{\par
\def\@gls@prevlevel{-1}%
\hangindent0pt\relax
\parindent0pt\relax
\glxtrgetgrouptitle{##1}{\glxtr@grptitle}%
\glstreePreHeader{##1}{\glxtr@grptitle}%
\glstreegroupheaderfmt{\glxtr@grptitle}%

```

Can't use `\@afterheading` here as it messes with the first item of the group.

```

\glstreegroupheaderskip
}%

```

Sub-groups are only supported with `\printunsrtglossary`.

```

\renewcommand*\{glssubgroupheading}[4]{%
\glxtrgetgrouptitle{##4}{\glxtr@grptitle}%
\glstreeSubPreHeader{##1}{##2}{##3}{##4}{\glxtr@grptitle}%

```

This is similar to `\subglossentry`

```

\ifnum\@gls@prevlevel=##2\relax
\else
\ifcsundef{\@gls@widestname\romannumeral##2}%
{%
\glsmeasurewidth{\gls@tmplen}{\glstreenamefmt{\@gls@widestname\space}}%
}%

```

```

{
  \glsmeasurewidth{\gls@tmplen}{\glstreenamefmt{
    \csname @glswidestname\romannumeral##2\endcsname\space}}%
}
\ifnum\@gls@prevlevel<##2\relax
  \setlength\glstreeindent\gls@tmplen
  \addtolength\glstreeindent\parindent
  \parindent\glstreeindent
\else
  \ifnum\@gls@prevlevel=0\relax
    \glstrComputeTreeIndent{##2}%
  \else
    \ifcsundef{@glswidestname\romannumeral##2}%
    {
      \glsmeasurewidth{\glstreeindent}{\glstreenamefmt{\@glswidestname\space}}%
    }%
    {
      \glsmeasurewidth{\glstreeindent}{\glstreenamefmt{
        \csname @glswidestname\romannumeral##2\endcsname\space}}%
    }%
  \fi
  \addtolength\parindent{-\glstreeindent}%
  \setlength\glstreeindent\parindent
\fi
\fi
\glstrAltTreeSetSubHangIndent{##2}%
\glsalttreesubgroupheader{##1}{##2}{##3}{##4}{\glstr@grptitle}{\gls@tmplen}%
\def\@gls@prevlevel{##2}%
\par
}%
}%
}%
}

```

Similarly for `alttreehypergroup`.

```

\ifdef{\@glsstyle@alttreehypergroup}
{
  \renewglossarystyle{alttreehypergroup}{%
    \setglossarystyle{alttree}%
    \renewcommand*\glossaryheader{%
      \par
      \def\@gls@prevlevel{-1}%
      \hangindent0pt\relax
      \parindent0pt\relax
      \glstreenavigationfmt{\glsnavigation}%

```

Can't use `\@afterheading` here as it messes with the first item of the group.

```

  \glstreegroupheaderskip
}%
\renewcommand*\glsgroupheading}[1]{%

```

```

\glxstrgetgrouptitle{##1}{\glxstr@grptitle}%
\glstreePreHeader{##1}{\glxstr@grptitle}%
\par
\def\@gls@prevlevel{-1}%
\hangindent0pt\relax
\parindent0pt\relax
\glstreegroupheaderfmt{\glsnavhypertarget{##1}{\glxstr@grptitle}}%

```

Can't use \@afterheading here as it messes with the first item of the group.

```

\glstreegroupheaderskip
}%

```

Sub-groups are only supported with \printunsrtglossary.

```

\renewcommand*{\glssubgroupheading}[4]{%
\glxstrgetgrouptitle{##4}{\glxstr@grptitle}%
\glstreeSubPreHeader{##1}{##2}{##3}{##4}{\glxstr@grptitle}%

```

This is similar to \subglossentry

```

\ifnum\@gls@prevlevel=##2\relax
\else
\ifcsundef{\@glswidestname\romannumeral##2}%
{%
\glsmeasurewidth{\gls@tmplen}{\glstreenamefmt{\@glswidestname\space}}%
}%
{%
\glsmeasurewidth{\gls@tmplen}{\glstreenamefmt{%
\csname \@glswidestname\romannumeral##2\endcsname\space}}%
}%
\ifnum\@gls@prevlevel<##2\relax
\setlength\glstreeindent\gls@tmplen
\addtolength\glstreeindent\parindent
\parindent\glstreeindent
\else
\ifnum\@gls@prevlevel=0\relax
\glxstrComputeTreeIndent{##2}%
\else
\ifcsundef{\@glswidestname\romannumeral##2}%
{%
\glsmeasurewidth{\glstreeindent}{\glstreenamefmt{\@glswidestname\space}}%
}%
{%
\glsmeasurewidth{\glstreeindent}{\glstreenamefmt{%
\csname \@glswidestname\romannumeral##2\endcsname\space}}%
}%
\fi
\addtolength\parindent{-\glstreeindent}%
\setlength\glstreeindent\parindent
\fi
\fi
\glxstrAltTreeSetSubHangIndent{##2}%
\glsalttreesubgroupheader{##1}{##2}{##3}{##4}%

```

```

        {\glsnahypertarget{##4}{\glstr@grptitle}}{\glstmplen}%
\def\@glsprevlevel{##2}%
\par
}%
}
}%
{%
}

```

4.9 Multicolumn Styles

Adjust `mcolindexgroup` to discourage page breaks after the group headings.

```

\ifdef{\@glstyle@mcolindexgroup}
{%
\renewglossarystyle{mcolindexgroup}{%
\setglossarystyle{mcolindex}%

```

Group heading as indexgroup.

```

\renewcommand*\glsgroupheading}[1]{%
\glstrgetgrouptitle{##1}{\glstr@grptitle}%
\glstreePreHeader{##1}{\glstr@grptitle}%
\item\glstreegroupheaderfmt{\glstr@grptitle}%
\glstreegroupheaderskip\@afterheading
}%

```

Sub-groups are only supported with `\printunsrtglossary`.

```

\renewcommand*\glssubgroupheading}[4]{%
\glstrgetgrouptitle{##4}{\glstr@grptitle}%
\glstreeSubPreHeader{##1}{##2}{##3}{##4}{\glstr@grptitle}%
\glindexsubgroupitem{##1}{##2}{##3}{##4}{\glstr@grptitle}%
\@afterheading
}%
}
}%
{%
}

```

Similarly for `mcolindexhypergroup`.

```

\ifdef{\@glstyle@mcolindexhypergroup}
{%
\renewglossarystyle{mcolindexhypergroup}{%
\setglossarystyle{mcolindex}%
\renewcommand*\glossaryheader{%
\item\glstreenavigationfmt{\glsnavigation}%
\glstreegroupheaderskip\@afterheading
}%

```

Group heading.

```

\renewcommand*\glsgroupheading}[1]{%
\glstrgetgrouptitle{##1}{\glstr@grptitle}%

```

```

\glstreePreHeader{##1}{\glstr@grptitle}%
\item\glstreegroupheaderfmt
  {\glsnahypertarget{##1}{\glstr@grptitle}}%
\glstreegroupheaderskip\@afterheading
}%

```

Sub-groups are only supported with \printunsrtglossary.

```

\renewcommand*\glssubgroupheading}[4]{%
  \glstrgetgrouptitle{##4}{\glstr@grptitle}%
  \glstreeSubPreHeader{##1}{##2}{##3}{##4}{\glstr@grptitle}%
  \glindexsubgroupitem{##1}{##2}{##3}{##4}%
  {\glsnahypertarget{##4}{\glstr@grptitle}}%
  \@afterheading
}%
}
}%
{%
}

```

Similarly for mcolindexspannav.

```

\ifdef{\@glstyle@mcolindexspannav}
{%
  \renewglossarystyle{mcolindexspannav}{%
    \setglossarystyle{index}%
    \renewenvironment{theglossary}%
    {%
      \begin{multicols}{\glsmcols}[\noindent\glstreenavigationfmt{\glsnavigation}]%
      \setlength{\parindent}{0pt}%
      \setlength{\parskip}{0pt plus 0.3pt}%
      \let\item\glstreeitem}%
    {\end{multicols}}%
  }%
}

```

Group heading.

```

\renewcommand*\glsgroupheading}[1]{%
  \glstrgetgrouptitle{##1}{\glstr@grptitle}%
  \glstreePreHeader{##1}{\glstr@grptitle}%
  \item\glstreegroupheaderfmt
    {\glsnahypertarget{##1}{\glstr@grptitle}}%
  \glstreegroupheaderskip\@afterheading
}%

```

Sub-groups are only supported with \printunsrtglossary.

```

\renewcommand*\glssubgroupheading}[4]{%
  \glstrgetgrouptitle{##4}{\glstr@grptitle}%
  \glstreeSubPreHeader{##1}{##2}{##3}{##4}{\glstr@grptitle}%
  \glindexsubgroupitem{##1}{##2}{##3}{##4}%
  {\glsnahypertarget{##4}{\glstr@grptitle}}%
  \@afterheading
}%
}
}%

```



```
{%
}
```

Similarly for mcoltreegroup.

```
\ifdef{\@glsstyle@mcoltreegroup}
{%
  \renewglossarystyle{mcoltreegroup}{%
    \setglossarystyle{mcoltree}%
```

Group heading.

```
\renewcommand{\glsgroupheading}[1]{%
  \glsxtrgetgrouptitle{##1}{\glsxtr@grptitle}%
  \glstreePreHeader{##1}{\glsxtr@grptitle}%
  \par\noindent\glstreegroupheaderfmt{\glsxtr@grptitle}%
  \glstreegroupheaderskip\@afterheading
}%
```

Sub-groups are only supported with \printunsrtglossary.

```
\renewcommand*\glssubgroupheading[4]{%
  \glsxtrgetgrouptitle{##4}{\glsxtr@grptitle}%
  \glstreeSubPreHeader{##1}{##2}{##3}{##4}{\glsxtr@grptitle}%
  \glstreesubgroupitem{##1}{##2}{##3}{##4}{\glsxtr@grptitle}%
}%
}
}%
{%
}
```

Similarly for mcoltreehypergroup.

```
\ifdef{\@glsstyle@mcoltreehypergroup}
{%
  \renewglossarystyle{mcoltreehypergroup}{%
    \setglossarystyle{mcoltree}%
    \renewcommand*\glossaryheader{%
      \par\noindent\glstreenavigationfmt{\glsnavigation}%
      \glstreegroupheaderskip
    }%
```

Group heading.

```
\renewcommand*\glsgroupheading[1]{%
  \glsxtrgetgrouptitle{##1}{\glsxtr@grptitle}%
  \glstreePreHeader{##1}{\glsxtr@grptitle}%
  \par\noindent
  \glstreegroupheaderfmt{\glsnavhypertarget{##1}{\glsxtr@grptitle}}%
  \glstreegroupheaderskip\@afterheading
}%
```

Sub-groups are only supported with \printunsrtglossary.

```
\renewcommand*\glssubgroupheading[4]{%
  \glsxtrgetgrouptitle{##4}{\glsxtr@grptitle}%
  \glstreeSubPreHeader{##1}{##2}{##3}{##4}{\glsxtr@grptitle}%
  \glstreesubgroupitem{##1}{##2}{##3}{##4}%
```

```

        {\glsnavhypertarget{##4}{\glsxtr@grptitle}}%
    }%
}
}%
{%
}

```

Similarly for `mcoltreesspannav`.

```

\ifdef{\@glsstyle@mcoltreesspannav}
{%
  \renewglossarystyle{mcoltreesspannav}{%
    \setglossarystyle{tree}%
    \renewenvironment{theglossary}%
    {%
      \begin{multicols}{\glsmlcols}%
        [noindent\glstreenavigationfmt{\glsnavigation}]%
      \setlength{\parindent}{0pt}%
      \setlength{\parskip}{0pt plus 0.3pt}%
    }%
    {\end{multicols}}%
  }

```

Group heading.

```

  \renewcommand*{\glsgroupheading}[1]{%
    \glsxtrgetgrouptitle{##1}{\glsxtr@grptitle}%
    \glstreePreHeader{##1}{\glsxtr@grptitle}%
    \par\noindent
    \glstreegroupheaderfmt{\glsnavhypertarget{##1}{\glsxtr@grptitle}}%
    \glstreegroupheaderskip\@afterheading
  }%

```

Sub-groups are only supported with `\printunsrtglossary`.

```

  \renewcommand*{\glssubgroupheading}[4]{%
    \glsxtrgetgrouptitle{##4}{\glsxtr@grptitle}%
    \glstreeSubPreHeader{##1}{##2}{##3}{##4}{\glsxtr@grptitle}%
    \glstreesubgroupitem{##1}{##2}{##3}{##4}%
    {\glsnavhypertarget{##4}{\glsxtr@grptitle}}%
  }%
}
}%
{%
}

```

Similarly for `mcoltreenonamegroup`. There are no sub-groups for this style as it doesn't show the name of the child entries.

```

\ifdef{\@glsstyle@mcoltreenonamegroup}
{%
  \renewglossarystyle{mcoltreenonamegroup}{%
    \setglossarystyle{mcoltreenoname}%
    \renewcommand{\glsgroupheading}[1]{%
      \glsxtrgetgrouptitle{##1}{\glsxtr@grptitle}%
      \glstreePreHeader{##1}{\glsxtr@grptitle}%
    }

```

```

        \par\noindent\glstreegroupheaderfmt{\glstr@grptitle}%
        \glstreegroupheaderskip\@afterheading
    }%
}
}%
{%
}

```

Similarly for mcoltreenonamehypergroup.

```

\ifdef{\@glsstyle@mcoltreenonamehypergroup}
{%
    \renewglossarystyle{mcoltreenonamehypergroup}{%
        \setglossarystyle{mcoltreenoname}%
        \renewcommand*\glossaryheader{%
            \par\noindent\glstreenavigationfmt{\glsnavigation}%
            \glstreegroupheaderskip
        }%
        \renewcommand*\glsgroupheading[1]{%
            \glstrgetgrouptitle{##1}{\glstr@grptitle}%
            \glstreePreHeader{##1}{\glstr@grptitle}%
            \par\noindent
            \glstreegroupheaderfmt{\glsnavhypertarget{##1}{\glstr@grptitle}}%
            \glstreegroupheaderskip\@afterheading}%
        }
    }%
}%
{%
}

```

Similarly for mcoltreenonamespannav.

```

\ifdef{\@glsstyle@mcoltreenonamespannav}
{%
    \renewglossarystyle{mcoltreenonamespannav}{%
        \setglossarystyle{treenoname}%
        \renewenvironment{theglossary}%
        {%
            \begin{multicols}{\glsncols}%
                [\noindent\glstreenavigationfmt{\glsnavigation}]%
            \setlength{\parindent}{0pt}%
            \setlength{\parskip}{0pt plus 0.3pt}%
        }%
        {\end{multicols}}%
        \renewcommand*\glsgroupheading[1]{%
            \glstrgetgrouptitle{##1}{\glstr@grptitle}%
            \glstreePreHeader{##1}{\glstr@grptitle}%
            \par\noindent
            \glstreegroupheaderfmt{\glsnavhypertarget{##1}{\glstr@grptitle}}%
            \glstreegroupheaderskip\@afterheading}%
        }
    }%
}%
{%
}

```

mcocalttree needs adjusting so that it uses \glxstralttreeInit This doesn't use \mbox{}\par which would unbalance the top of the columns.

```
\ifdef{\@glsstyle@mcocalttree}
{%
  \renewglossarystyle{mcocalttree}{%
    \setglossarystyle{alttree}%
    \renewenvironment{theglossary}%
    {%
      \glxstralttreeInit
      \def\@gls@prevlevel{-1}%
      \begin{multicols}{\glsmcols}%
    }%
    {\par\end{multicols}}}%
  }
}%
{%
}
```

Redefine mcocalttreegroup to discourage page breaks after the group headings.

```
\ifdef{\@glsstyle@mcocalttreegroup}
{%
  \renewglossarystyle{mcocalttreegroup}{%
    \setglossarystyle{mcocalttree}%
    \renewcommand{\glsgroupheading}[1]{%
      \glxstrgetgrouptitle{##1}{\glxstr@grptitle}%
      \glstreePreHeader{##1}{\glxstr@grptitle}%
      \par
      \def\@gls@prevlevel{-1}%
      \hangindent0pt\relax
      \parindent0pt\relax
      \glstreegroupheaderfmt{\glxstr@grptitle}%
      \glstreegroupheaderskip
    }%
  }
```

Sub-groups are only supported with \printunsrtglossary.

```
\renewcommand*\glssubgroupheading[4]{%
  \glxstrgetgrouptitle{##4}{\glxstr@grptitle}%
  \glstreeSubPreHeader{##1}{##2}{##3}{##4}{\glxstr@grptitle}%
}
```

This is similar to \subglossentry

```
\ifnum\@gls@prevlevel=##2\relax
\else
  \ifcsundef{@glswidestname\romannumeral##2}%
  {%
    \glsmeasurewidth{\gls@tmplen}{\glstreenamefmt{\@glswidestname\space}}%
  }%
  {%
    \glsmeasurewidth{\gls@tmplen}{\glstreenamefmt{
      \csname @glswidestname\romannumeral##2\endcsname\space}}%
  }%
  \ifnum\@gls@prevlevel<##2\relax
```

```

\setlength\glstreeindent\gls@tmplen
\addtolength\glstreeindent\parindent
\parindent\glstreeindent
\else
\ifnum\@gls@prevlevel=0\relax
\glstrComputerTreeIndent{##2}%
\else
\ifcsundef{@glswidestname\romannumeral##2}%
{%
\glsmeasurewidth{\glstreeindent}{\glstreenamefmt{\@glswidestname\space}}%
}%
{%
\glsmeasurewidth{\glstreeindent}{\glstreenamefmt{
\csname @glswidestname\romannumeral##2\endcsname\space}}%
}%
\fi
\addtolength\parindent{-\glstreeindent}%
\setlength\glstreeindent\parindent
\fi
\fi
\glstrAltTreeSetSubHangIndent{##2}%
\glsalttreesubgroupheader{##1}{##2}{##3}{##4}{\glstr@grptitle}{\gls@tmplen}%
\def\@gls@prevlevel{##2}%
\par
}%
}
}%
{%
}

```

Similarly for mcolalttreehypergroup.

```

\ifdef{\@glsstyle@mcolalttreehypergroup}
{%
\renewglossarystyle{mcolalttreehypergroup}{%
\setglossarystyle{mcolalttree}%
\renewcommand*\glossaryheader{%
\par
\def\@gls@prevlevel{-1}%
\hangindent0pt\relax
\parindent0pt\relax
\glstreenavigationfmt{\glsnavigation}%
\glstreegroupheaderskip
}%
\renewcommand*\glsgroupheading}[1]{%
\glstrgetgrouptitle{##1}{\glstr@grptitle}%
\glstreePreHeader{##1}{\glstr@grptitle}%
\par
\def\@gls@prevlevel{-1}%
\hangindent0pt\relax
\parindent0pt\relax

```

```

\glstreegroupheaderfmt{\glsnahypertarget{##1}{\glstr@grptitle}}%
\glstreegroupheaderskip
}%

```

Sub-groups are only supported with \printunsrtglossary.

```

\renewcommand*{\glssubgroupheading}[4]{%
\glstrgetgrouptitle{##4}{\glstr@grptitle}%
\glstreeSubPreHeader{##1}{##2}{##3}{##4}{\glstr@grptitle}%

```

This is similar to \subglossentry

```

\ifnum\@gls@prevlevel=##2\relax
\else
\ifcsundef{@glswidestname\romannumeral##2}%
{%
\glsmeasurewidth{\gls@tmplen}{\glstreenamefmt{\@glswidestname\space}}%
}%
{%
\glsmeasurewidth{\gls@tmplen}{\glstreenamefmt{%
\csname @glswidestname\romannumeral##2\endcsname\space}}%
}%
\ifnum\@gls@prevlevel<##2\relax
\setlength\glstreeindent\gls@tmplen
\addtolength\glstreeindent\parindent
\parindent\glstreeindent
\else
\ifnum\@gls@prevlevel=0\relax
\glstrComputeTreeIndent{##2}%
\else
\ifcsundef{@glswidestname\romannumeral##2}%
{%
\glsmeasurewidth{\glstreeindent}{\glstreenamefmt{\@glswidestname\space}}%
}%
{%
\glsmeasurewidth{\glstreeindent}{\glstreenamefmt{%
\csname @glswidestname\romannumeral##2\endcsname\space}}%
}%
\fi
\addtolength\parindent{-\glstreeindent}%
\setlength\glstreeindent\parindent
\fi
\fi
\glstrAltTreeSetSubHangIndent{##2}%
\glsalttreesubgroupheader{##1}{##2}{##3}{##4}%
{\glsnahypertarget{##4}{\glstr@grptitle}}{\gls@tmplen}%
\def\@gls@prevlevel{##2}%
\par
}%
}
}%
{%
}

```

Similarly for mcolalttreespannav.

```
\ifdef{\@glsstyle@mcolalttreespannav}
{%
  \renewglossarystyle{mcolalttreespannav}{%
    \setglossarystyle{alttree}%
    \renewenvironment{theglossary}%
    {%
      \glstralttreeInit
      \def\@gls@prevlevel{-1}%
      \begin{multicols}{\glsmcols}%
        [\noindent\glstreenavigationfmt{\glsnavigation}}%
      }%
    }\par\end{multicols}}%
  \renewcommand*{\glsgroupheading}[1]{%
    \glstrgetgrouptitle{##1}{\glstr@grptitle}%
    \glstreePreHeader{##1}{\glstr@grptitle}%
    \par
    \def\@gls@prevlevel{-1}%
    \hangindentOpt\relax
    \parindentOpt\relax
    \glstreegroupheaderfmt{\glsnavhypertarget{##1}{\glstr@grptitle}}%
    \glstreegroupheaderskip
  }%
}
```

Sub-groups are only supported with \printunsrtglossary.

```
\renewcommand*{\glssubgroupheading}[4]{%
  \glstrgetgrouptitle{##4}{\glstr@grptitle}%
  \glstreeSubPreHeader{##1}{##2}{##3}{##4}{\glstr@grptitle}%
}
```

This is similar to \subglossentry

```
\ifnum\@gls@prevlevel=##2\relax
\else
  \ifcsundef{@glswidestname\romannumeral##2}%
  {%
    \glsmeasurewidth{\gls@tmplen}{\glstreenamefmt{\@glswidestname\space}}%
  }%
  {%
    \glsmeasurewidth{\gls@tmplen}{\glstreenamefmt{%
      \csname @glswidestname\romannumeral##2\endcsname\space}}%
  }%
  \ifnum\@gls@prevlevel<##2\relax
    \setlength\glstreeindent\gls@tmplen
    \addtolength\glstreeindent\parindent
    \parindent\glstreeindent
  \else
    \ifnum\@gls@prevlevel=0\relax
      \glstrComputeTreeIndent{##2}%
    \else
      \ifcsundef{@glswidestname\romannumeral##2}%
      {%

```

```

        \glsmeasurewidth{\glstreeindent}{\glstreenamefmt{\@glswidestname\space}}%
    }%
    {%
        \glsmeasurewidth{\glstreeindent}{\glstreenamefmt{%
            \csname @glswidestname\romannumeral##2\endcsname\space}}%
        }%
    \fi
    \addtolength\parindent{-\glstreeindent}%
    \setlength\glstreeindent\parindent
\fi
\fi
\glsxtrAltTreeSetSubHangIndent{##2}%
\glsalttreesubgroupheader{##1}{##2}{##3}{##4}%
    {\glsnavhypertarget{##4}{\glsxtr@grptitle}}{\gls@tmplen}%
\def\@gls@prevlevel{##2}%
\par
}%
}
}%
{%
}

Reset the default style
\ifx\@glossary@default@style\relax
\else
    \setglossarystyle{\@glsxtr@current@style}
\fi

```

5 bookindex style (glossary-bookindex.sty)

\NeedsTeXFormat{LaTeX2e}

Rollback releases:

\DeclareRelease{v1.48}{2021-11-22}{glossary-bookindex-2021-11-22.sty}

\DeclareCurrentRelease{1.9}{2025-11-03}

Declare package:

\ProvidesPackage{glossary-bookindex}[2026/03/06 v2.0 (NLCT)]

Load required packages.

\RequirePackage{multicol}

\RequirePackage{glossary-tree}

\glsxtrbookindexcols Number of columns.

\newcommand{\glsxtrbookindexcols}{2}

\glsxtrbookindextarget Create the target for top-level items.

\newcommand*{\glsxtrbookindextarget}[2]{\gls@target{#1}{#2}}

\glsxtrbookindexsubtarget Create the target for child items.

\newcommand*{\glsxtrbookindexsubtarget}[2]{\glsxtrbookindextarget{#1}{#2}}

`\glsxtrbookindexname` Format used for top-level entries. (Argument is the label.)
`\newcommand*{\glsxtrbookindexname}[1]{\glossentryname{#1}}`

`\glsxtrbookindexsubname` Format used for sub entries.
`\newcommand*{\glsxtrbookindexsubname}[1]{\glsxtrbookindexname{#1}}`

`\glsxtrprelocation` Provide in case glossaries-stylemods isn't loaded.
`\providecommand*{\glsxtrprelocation}{\space}`

`\glsxtrbookindexprelocation` Separator used before location list for top-level entries. Version 1.22 has removed the `\ifglsnopostdot` check since this style doesn't display the description.
`\newcommand*{\glsxtrbookindexprelocation}[1]{%`
`\glsxtrifhasfield{location}{#1}%`
`{,\glsxtrprelocation}%`
`{\glsxtrprelocation}%`
`}`

`\glsxtrbookindexsubprelocation` Separator used before location list for sub-entries.
`\newcommand*{\glsxtrbookindexsubprelocation}[1]{%`
`\glsxtrbookindexprelocation{#1}%`
`}`

`\glsxtrbookindexlocation` `\glsxtrbookindexlocation{\label}{\location}`
Displays the location.
`\newcommand*{\glsxtrbookindexlocation}[2]{#2}`

`\glsxtrbookindexsublocation` `\glsxtrbookindexlocation{\label}{\location}`
Displays the location for sub-entries.
`\newcommand*{\glsxtrbookindexsublocation}{\glsxtrbookindexlocation}`

`\glsxtrbookindexparentchildsep` Separator used between top-level parent and child entry.
`\newcommand{\glsxtrbookindexparentchildsep}{\nopagebreak}`

`\glsxtrbookindexparentsubchildsep` Separator used between sub-level parent and child entry.
`\newcommand{\glsxtrbookindexparentsubchildsep}{\glsxtrbookindexparentchildsep}`

`\glsxtrbookindexbetween` Between two top-level entries identified by the labels in the arguments.
`\newcommand{\glsxtrbookindexbetween}[2]{}`

`\glsxtrbookindexsubbetween` Between two level 1 entries identified by the labels in the arguments.
`\newcommand{\glsxtrbookindexsubbetween}[2]{}`

`\glxtrbookindexsubsubbetween` Between two level 2 entries identified by the labels in the arguments.
`\newcommand{\glxtrbookindexsubsubbetween}[2]{}`

`\glxtrbookindexatendgroup` At the end of a letter group. The argument is the label of the last top-level entry.
`\newcommand{\glxtrbookindexatendgroup}[1]{}`

`\glxtrbookindexsubatendgroup` At the end of a letter group. The argument is the label of the last level 1 entry.
`\newcommand{\glxtrbookindexsubatendgroup}[1]{}`

`\glxtrbookindexsubsubatendgroup` At the end of a letter group. The argument is the label of the last level 2 entry.
`\newcommand{\glxtrbookindexsubsubatendgroup}[1]{}`

`\glxtrbookindexgroupskip` Group separator.
`\newcommand{\glxtrbookindexgroupskip}{\ifglsnogroupskip\else\indexspace\fi}`

`\glxtrbookindexpregroupskip` After group header. The argument is the skip that would normally be inserted if there wasn't a group header.
`\newcommand{\glxtrbookindexpregroupskip}[1]{#1}`

`\glxtrbookindexpostgroupskip` After group header.
`\newcommand{\glxtrbookindexpostgroupskip}{\indexspace}`

`\glxtrbookindexpresubgroupskip{\langle default \rangle}{\langle prev group level \rangle}{\langle group level \rangle}`

`\glxtrbookindexpresubgroupskip` Before sub-group separator. The first argument is the skip that would normally be used at this point if there wasn't a header.
`\newcommand{\glxtrbookindexpresubgroupskip}[3]{\par\medskip}`

`\glxtrbookindexpostsubgroupskip` After sub-group separator.
`\newcommand{\glxtrbookindexpostsubgroupskip}[2]{\par\medskip}`

`\glxtrbookindexsubsubitem` Sub-sub item and lower. The argument is the level, which will be 2 or more.
`\newcommand{\glxtrbookindexsubsubitem}[1]{\glstreesubsubitem}`

Format group title.

`\glxtrbookindexformatheader` Group header.
`\newcommand*{\glxtrbookindexformatheader}[1]{%`
`\par{\centering\glstreegroupheaderfmt{#1}\par}%`
`}`

Format sub-group title.

`\glstrbookindexformatsubheader` Sub-group header. This defaults to the same format as the top-level group.

```
\newcommand*{\glstrbookindexformatsubheader}[5]{%
\ifnum#2>1\relax
\glstrbookindexsubsubitem{#2}\glstreegroupheaderfmt{#5}%
\else
\glstreesubitem\glstreegroupheaderfmt{#5}%
\fi
}
```

`\glstrbookindexbookmark` Book mark group heading if supported.

```
\ifdef\pdfbookmark
{%
\newcommand*{\glstrbookindexbookmark}[2]{%
\ifdefstring{\@@glossarysec}{chapter}%
{\pdfbookmark[1]{#1}{#2}}%
{\pdfbookmark[2]{#1}{#2}}%
}
}
{%
\newcommand*{\glstrbookindexbookmark}[2]{}
```

`\glstrbookindexsubbookmark` Book mark sub-group heading if supported.

```
\ifdef\pdfbookmark
{%
\newcommand*{\glstrbookindexsubbookmark}[3]{%
\ifdefstring{\@@glossarysec}{chapter}%
{\expandafter\pdfbookmark\expandafter[\number\numexpr#1+1]{#3}{#2}}%
{\expandafter\pdfbookmark\expandafter[\number\numexpr#1+2]{#3}{#2}}%
}
}
{%
\newcommand*{\glstrbookindexsubbookmark}[3]{}
```

`\glstrbookindexbookmarkprefix` Make the bookmark label prefix used for letter groups depend on the glossary label (instead of original hardcoded “index.”).

```
\newcommand*{\glstrbookindexbookmarkprefix}{\currentglossary.}
```

`\glstrbookindexcolspread`

```
\newcommand*{\glstrbookindexcolspread}{}
```

`\glstrbookindexmulticolenv`

```
\newcommand*{\glstrbookindexmulticolenv}{multicols}
```

`bookindex` Define the style.

```
\newglossarystyle{bookindex}{%
\setglossarystyle{index}%
\renewenvironment{theglossary}%
```

```

{%
\ifnum\glstrbookindexcols>1\relax
\ifdefempty\glstrbookindexcolspread
{%
\edef\glstr@beginbookindex{%
\noexpand\begin{\glstrbookindexmulticolseenv}
{\glstrbookindexcols}%
}%
}%
{%
\edef\glstr@beginbookindex{%
\noexpand\begin{\glstrbookindexmulticolseenv}%
{\glstrbookindexcols}[\glstrbookindexcolspread]%
}%
}%
\else
\def\glstr@beginbookindex{}%
\fi
\glstr@beginbookindex
\setlength{\parindent}{0pt}%
\setlength{\parskip}{0pt plus 0.3pt}%
\let\@glstr@bookindex@sep\glstrbookindexparentchildsep
\let\@glstr@bookindex@subsep\glstrbookindexparentsubchildsep
\let\@glstr@bookindex@between\@gobble
\let\@glstr@bookindex@subbetween\@gobble
\let\@glstr@bookindex@subsubbetween\@gobble
\let\@glstr@bookindex@atendgroup\relax
\let\@glstr@bookindex@subatendgroup\relax
\let\@glstr@bookindex@subsubatendgroup\relax
\let\@glstr@bookindexgroupskip\relax
}%
{%

```

Do end group hooks.

```

\@glstr@bookindex@subsubatendgroup
\@glstr@bookindex@subatendgroup
\@glstr@bookindex@atendgroup

```

End multicol environment.

```

\ifnum\glstrbookindexcols>1\relax
\edef\glstr@endbookindex{%
\noexpand\end{\glstrbookindexmulticolseenv}%
}%
\else
\def\glstr@endbookindex{}%
\fi
\glstr@endbookindex
}%

```

Use ragged right as columns are likely to be narrow and indexes tend not to be fully justified.

```

\renewcommand*{\glossaryheader}{\raggedright}%
Top level entry format.
\renewcommand*{\glossentry}[2]{%
Do separator.
\@glsxtr@bookindex@between{##1}%
Update separators.
\let\@glsxtr@bookindex@sep\glsxtrbookindexparentchildsep
\let\@glsxtr@bookindex@subsep\glsxtrbookindexparentsubchildsep
\let\@glsxtr@bookindex@subbetween\@gobble
\let\@glsxtr@bookindex@subsubbetween\@gobble
The second argument of \glsxtrbookindexbetween will be supplied as the
argument to \@glsxtr@bookindex@between.
\protected@edef\@glsxtr@bookindex@between{%
\noexpand\glsxtrbookindexbetween{##1}%
}%
\protected@edef\@glsxtr@bookindex@atendgroup{%
\noexpand\glsxtrbookindexatendgroup{##1}%
}%
\let\@glsxtr@bookindex@subatendgroup\relax
\let\@glsxtr@bookindex@subsubatendgroup\relax
Format entry.
\glstreeitem
\glsentryitem{##1}%
\glsxtrbookindextarget{##1}{\glsxtrbookindexname{##1}}%
\glsxtrbookindexprelocation{##1}%
\glsxtrbookindexlocation{##1}{##2}%
}%
\renewcommand{\subglossentry}[3]{%
\ifcase##1\relax
Level 0 (shouldn't happen as that's formatted with \glossentry).
\glstreeitem
\or
Level 1.
\@glsxtr@bookindex@sep
\@glsxtr@bookindex@subbetween{##2}%
\let\@glsxtr@bookindex@sep\relax
Update separators.
\let\@glsxtr@bookindex@subsubbetween\@gobble
\let\@glsxtr@bookindex@subsep\glsxtrbookindexparentsubchildsep
\edef\@glsxtr@bookindex@subbetween{%
\noexpand\glsxtrbookindexsubbetween{##2}%
}%
\edef\@glsxtr@bookindex@atsubendgroup{%
\noexpand\glsxtrbookindexatsubendgroup{##1}%
}%

```

Start sub-item.

```
\glstreesubitem
\glssubentryitem{##2}%
\else
```

All other levels.

```
\@glxtr@bookindex@subsep
\@glxtr@bookindex@subsubbetween{##2}%
```

Update separators.

```
\let\@glxtr@bookindex@subsep\relax
\edef\@glxtr@bookindex@subsubbetween{%
  \noexpand\glxtrbookindexsubsubbetween{##2}%
}%
\edef\@glxtr@bookindex@atsubsubendgroup{%
  \noexpand\glxtrbookindexatsubsubendgroup{##1}%
}%
```

Start sub-sub-item.

```
\glxtrbookindexsubsubitem{##1}%
\fi
```

Format entry.

```
\glxtrbookindexsubtarget{##2}{\glxtrbookindexsubname{##2}}%
\glxtrbookindexsubprelocation{##2}%
\glxtrbookindexsublocation{##2}{##3}%
}%
```

The group skip is moved to the group heading to avoid interfering with the end letter group hooks.

```
\renewcommand*{\glsgroupskip}{}%
```

Group heading format.

```
\renewcommand*{\glsgroupheading}[1]{%
```

Do end group hooks.

```
\@glxtr@bookindex@subsubatendgroup
\@glxtr@bookindex@subatendgroup
\@glxtr@bookindex@atendgroup
\glxtrbookindexpregroupskip\@glxtr@bookindexgroupskip
```

Update separators.

```
\let\@glxtr@bookindexgroupskip\glxtrbookindexgroupskip
\let\@glxtr@bookindex@between\@gobble
\let\@glxtr@bookindex@atendgroup\relax
\let\@glxtr@bookindex@subatendgroup\relax
\let\@glxtr@bookindex@subsubatendgroup\relax
```

Fetch the group title from the label supplied in #1.

```
\glxtrgetgrouptitle{##1}{\glxtrcurrentgrptitle}%
```

Do the PDF bookmark if supported.

```
\glxtrbookindexbookmark{\glxtrcurrentgrptitle}{\glxtrbookindexbookmarkprefix##1}%
```

Format the group title.

```
\glxtrbookindexformatheader{\glxtrcurrentgrptitle}%
\nopagebreak\glxtrbookindexpostgroupskip\nopagebreak\@afterheading
}%
```

Sub-groups are only supported with `\printunsrtglossary`.

```
\renewcommand*{\glssubgroupheading}[4]{%
```

Do end group hooks.

```
\@glxtr@bookindex@subsubatendgroup
\@glxtr@bookindex@subatendgroup
\@glxtr@bookindex@atendgroup
\glxtrbookindexpresubgroupskip\@glxtr@bookindexgroupskip{##1}{##2}%
```

Update separators.

```
\let\@glxtr@bookindexgroupskip\glxtrbookindexgroupskip
\let\@glxtr@bookindex@between\@gobble
\let\@glxtr@bookindex@atendgroup\relax
\let\@glxtr@bookindex@subatendgroup\relax
\let\@glxtr@bookindex@subsubatendgroup\relax
```

Get group title.

```
\glxtrgetgrouptitle{##4}{\glxtrcurrentgrptitle}%
```

Do the PDF bookmark if supported.

```
\glxtrbookindexsubbookmark{##2}{##4}{\glxtrcurrentgrptitle}%
```

Format the group title.

```
\glxtrbookindexformatsubheader{##1}{##2}{##3}{##4}{\glxtrcurrentgrptitle}%
\nopagebreak\glxtrbookindexpostsubgroupskip{##1}{##2}\nopagebreak\@afterheading
}
}
```

Some supplementary commands that may be useful. These store the entry label for the current page. Since the page number is needed in the control sequence, this uses `\glxtrbookindexthepage` instead of `\thepage` in case the page numbering has been set to something that contains formatting commands.

`\glxtrbookindexthepage` The `\@printglossary` sets `\currentglossary` to the current glossary label. This is used as a prefix in case the page number is reset.

```
\newcommand{\glxtrbookindexthepage}{%
\ifdef\currentglossary{\currentglossary.\arabic{page}}{\arabic{page}}%
}
```

`\glxtrbookindexmarkentry` Writes entry information to the `.aux` file. The argument is the entry label.

```
\newcommand*{\glxtrbookindexmarkentry}[1]{%
\protected@write\@auxout
{\let\glxtrbookindexthepage\relax}%
{\string\glxtr@setbookindexmark{\glxtrbookindexthepage}{#1}}%
}
```

```

\glsxtr@setbookindexmark

\newcommand*{\glsxtr@setbookindexmark}[2]{%
  \ifcsundef{glsxtr@idxfirstmark@#1}%
  {\csgdef{glsxtr@idxfirstmark@#1}{#2}}%
  {}%
  \csgdef{glsxtr@idxlastmark@#1}{#2}%
}

glsxtrbookindexfirstmarkfmt

\newcommand*{\glsxtrbookindexfirstmarkfmt}[1]{%
  \glsentryname{#1}%
}

\glsxtrbookindexfirstmark

\newcommand*{\glsxtrbookindexfirstmark}{%
  \letcs{\glsxtr@label}{glsxtr@idxfirstmark@\glsxtrbookindexthepage}%
  \ifdef\glsxtr@label
  {\glsxtrbookindexfirstmarkfmt{\glsxtr@label}}%
  {}%
}

\glsxtrbookindexlastmarkfmt

\newcommand*{\glsxtrbookindexlastmarkfmt}[1]{%
  \glsentryname{#1}%
}

\glsxtrbookindexlastmark

\newcommand*{\glsxtrbookindexlastmark}{%
  \letcs{\glsxtr@label}{glsxtr@idxlastmark@\glsxtrbookindexthepage}%
  \ifdef\glsxtr@label
  {\glsxtrbookindexlastmarkfmt{\glsxtr@label}}%
  {}%
}

```

6 longextra styles (glossary-longextra.sty)

Provides additional long styles.

```
\NeedsTeXFormat{LaTeX2e}
```

Rollback releases:

```
\DeclareRelease{v1.48}{2021-11-22}{glossary-longextra-2021-11-22.sty}
\DeclareCurrentRelease{1.9}{2025-11-03}
```

Declare package:

```
\ProvidesPackage{glossary-longextra}[2026/03/06 v2.0 (NLCT)]
```

Load required packages.

```
\RequirePackage{glossary-longbooktabs}
```


`\glslongextraNameFmt{⟨label⟩}`

Governs the way the name is displayed.

```
\newcommand{\glslongextraNameFmt}[1]{%
  \glsentryitem{#1}\glstarget{#1}{\glossentryname{#1}}%
}
```

`\glslongextraDescFmt{⟨label⟩}`

Governs the way the description is displayed.

```
\newcommand{\glslongextraDescFmt}[1]{%
  \glossentrydesc{#1}\glspostdescription
}
```

`\glslongextraSymbolFmt{⟨label⟩}`

Governs the way the symbol is displayed.

```
\newcommand{\glslongextraSymbolFmt}[1]{\glossentrysymbol{#1}}
```

`\glslongextraSymbolTargetFmt{⟨label⟩}`

Governs the way the symbol is displayed if it needs to include the target.

```
\newcommand{\glslongextraSymbolTargetFmt}[1]{%
  \glsentryitem{#1}\glstarget{#1}{\glslongextraSymbolFmt{#1}}%
}
```

`\glslongextraSymbolOrName{⟨label⟩}`

Governs the way the symbol is displayed if it needs to include the target.

```
\newcommand{\glslongextraSymbolOrName}[1]{%
  \ifglshassymbol{#1}%
  {\glslongextraSymbolTargetFmt{#1}}%
  {\glslongextraNameFmt{#1}}%
}
```

`\glslongextraLocationFmt{⟨label⟩}{⟨location list⟩}`

Governs the way the location is displayed.

```
\newcommand{\glslongextraLocationFmt}[2]{#2}
```

<code>\glslongextraShortTargetFmt</code>	<div><code>\glslongextraShortTargetFmt{<label>}</code></div> <p>Governs the way the short form is displayed if it needs to include the target.</p> <pre> \newcommand{\glslongextraShortTargetFmt}[1]{% \glsentryitem{#1}\glstarget{#1}{\glsxtrshort[noindex,hyper=false]{#1}}}% \glsxtrpostnamehook{#1}% }</pre>
<code>\glslongextraLongFmt</code>	<div><code>\glslongextraLongFmt{<label>}</code></div> <p>Governs the way the long form is displayed.</p> <pre> \newcommand{\glslongextraLongFmt}[1]{% {\glsxtrlong[noindex,hyper=false]{#1}}\glspostdescription }</pre>
<code>\glslongextraSubNameFmt</code>	<div><code>\glslongextraSubNameFmt{<level>}{<label>}</code></div> <p>Governs the way the child name is displayed. Just does the sub-entry counter, if enabled, and the target.</p> <pre> \newcommand{\glslongextraSubNameFmt}[2]{% \glssubentryitem{#2}\glstarget{#2}{\strut}% }</pre>
<code>\glslongextraSubDescFmt</code>	<div><code>\glslongextraSubDescFmt{<level>}{<label>}</code></div> <p>Governs the way the child description is displayed.</p> <pre> \newcommand{\glslongextraSubDescFmt}[2]{% \glslongextraDescFmt{#2}% }</pre>
<code>\glslongextraSubSymbolFmt</code>	<div><code>\glslongextraSubSymbolFmt{<level>}{<label>}</code></div> <p>Governs the way the child symbol is displayed.</p> <pre> \newcommand{\glslongextraSubSymbolFmt}[2]{% \glslongextraSymbolFmt{#2}% }</pre>
<code>\glslongextraSubSymbolTargetFmt</code>	<div><code>\glslongextraSubSymbolTargetFmt{<level>}{<label>}</code></div> <p>Governs the way the child symbol is displayed if the target is required.</p>

```
\newcommand{\glslongextraSubSymbolTargetFmt}[2]{%
  \glssubentryitem{#2}\glstarget{#2}{\glslongextraSymbolFmt{#2}}%
}
```

```
\glslongextraSubSymbolOrName{<level>}{<label>}
```

`\glslongextraSubSymbolOrName`

Shows the symbol or the name (if the symbol isn't set) as the target for sub-entries.

```
\newcommand{\glslongextraSubSymbolOrName}[2]{%
  \ifglshassymbol{#2}%
  {\glslongextraSubSymbolTargetFmt{#1}{#2}}%
  {\glslongextraSubNameFmt{#1}{#2}}%
}
```

```
\glslongextraSubShortTargetFmt{<level>}{<label>}
```

`\glslongextraSubShortTargetFmt`

Governs the way the short form is displayed if it needs to include the target.

```
\newcommand{\glslongextraSubShortTargetFmt}[2]{%
  \glssubentryitem{#2}\glstarget{#2}{\glxtrshort[noindex,hyper=false]{#2}}%
  \glxtrpostnamehook{#2}%
}
```

```
\glslongextraSubLongFmt{<label>}
```

`\glslongextraSubLongFmt`

Governs the way the long form is displayed.

```
\newcommand{\glslongextraSubLongFmt}[2]{\glslongextraLongFmt{#2}}
```

```
\glslongextraSubLocationFmt{<level>}{<label>}{<location
list>}
```

`\glslongextraSubLocationFmt`

Governs the way the child location list is displayed.

```
\newcommand{\glslongextraSubLocationFmt}[3]{#3}
```

`\glslongextraNameAlign` Alignment for the name column.

```
\newcommand{\glslongextraNameAlign}{l}
```

`\glslongextraDescAlign` Alignment for the description column.

```
\newcommand{\glslongextraDescAlign}{>\raggedrightp{\glsdescwidth}}
```

`\glslongextraSymbolAlign` Alignment for the symbol column.

```
\newcommand{\glslongextraSymbolAlign}{c}
```

`\glslongextraSymbolNameAlign` Alignment for the symbol column when it's being used instead of the name.
`\newcommand{\glslongextraSymbolNameAlign}{1}`

`\glslongextraLocationAlign` Alignment for the location column.
`\newcommand{\glslongextraLocationAlign}{>\raggedright}p{\glspagelistwidth}`

`\glslongextraGroupHeading` Used to format the letter group headings. The first argument is the number of columns in the table. The second is the group *label* (not the title).
`\newcommand{\glslongextraGroupHeading}[2]{}`

`\glslongextraSubGroupHeading{<number of columns>}{<prev
group level>}{<group
level>}{<parent entry>}{<group label>}`

`\glslongextraSubGroupHeading`
`\newcommand*{\glslongextraSubGroupHeading}[5]{}`

`\glslongextraHeaderFormat` Format for the column headers.
`\newcommand{\glslongextraHeaderFmt}[1]{\textbf{#1}}`

`\glslongextraNameDescHeader`
`\newcommand{\glslongextraNameDescHeader}{%`
`\glslongextraNameDescTabularHeader\endhead`
`\glslongextraNameDescTabularFooter\endfoot`
`}`

`\glslongextraNameDescTabularHeader`
`\newcommand{\glslongextraNameDescTabularHeader}{%`
`\toprule`
`\glslongextraHeaderFmt\entryname &`
`\glslongextraHeaderFmt\descriptionname\tabularnewline`
`\midrule`
`}`

`\glslongextraNameDescTabularFooter`
`\newcommand{\glslongextraNameDescTabularFooter}{%`
`\bottomrule`
`}`

Unlike the `alttree` style, there aren't different widths for the hierarchical levels.

`\glslongextraSetWidest` Provide in case the tree styles haven't been loaded.
`\newcommand*{\glslongextraSetWidest}[1]{%`
`\def\@glslongextrawidestname{#1}%`
`}`

`\@glslongextrawidestname` Pick up the widest name from the `alttree` style if it has been set. (Will expand to nothing otherwise.)

```
\newcommand*{\@glslongextrawidestname}{\csuse{@glswidestname}}
```

`\glslongextraUpdateWidest`

```
\newcommand*{\glslongextraUpdateWidest}[1]{%
  \ifundef\@glslongextrawidestname
  {\def\@glslongextrawidestname{#1}}%
  {%
    \glsmeasurewidth{\dimen@}{\@glslongextrawidestname}%
    \glsmeasurewidth{\dimen@ii}{#1}%
    \ifdim\dimen@ii>\dimen@
    \def\@glslongextrawidestname{#1}%
    \fi
  }%
}
```

`\glslongextraUpdateWidestChild{<level>}{<text>}`

`\glslongextraUpdateWidestChild`

Used by `\glsxtrSetWidest` in `glossaries-extra-bib2gls`. Does nothing by default, since the default action in these styles is to omit the child name. If the child name should be displayed, then this needs to be redefined to use `\glslongextraUpdateWidest`.

```
\newcommand*{\glslongextraUpdateWidestChild}[2]{}%
```

`\glslongextraSetDescWidth` Computes the value of `\glsdescwidth` for the styles that only have name and description columns.

```
\newcommand{\glslongextraSetDescWidth}{%
  \glsmeasurewidth{\gls@tmplen}{\glslongextraHeaderFmt\entryname}%
  Has the widest name been set.
  \glsmeasurewidth{\dimen@}{\glsnamefont{\@glslongextrawidestname}}%
  \ifdim\dimen@>\gls@tmplen
    \gls@tmplen=\dimen@
  \fi
  Description width is \linewidth less 4\tabcolsep less the width of the name column.
  \setlength{\glsdescwidth}{\dimexpr\linewidth-4\tabcolsep-\gls@tmplen}%
}
```

`\glslongextraSymSetDescWidth` Computes the value of `\glsdescwidth` for the styles that only have name, symbol and description columns.

```
\newcommand{\glslongextraSymSetDescWidth}{%
  Work out the size for just the name and description style.
  \glslongextraSetDescWidth
```

Now work out the symbol column width. This is assuming that the column title will be the widest text in the column.

```
\glsmeasurewidth{\gls@tmplen}{\glslongextraHeaderFmt\symbolname}%
```

Subtract 2\tabcolsep and the symbol header width.

```
\setlength{\glsdescwidth}{\dimexpr\glsdescwidth-2\tabcolsep-\gls@tmplen}%
}
```

glslongextraSymNoNameSetDescWidth Computes the value of \glsdescwidth for the styles that only have symbol and description columns.

```
\newcommand{\glslongextraSymNoNameSetDescWidth}{%
```

Now work out the symbol column width. This is assuming that the column title will be the widest text in the column.

```
\glsmeasurewidth{\gls@tmplen}{\glslongextraHeaderFmt\symbolname}%
```

Subtract 4\tabcolsep and the symbol header width.

```
\setlength{\glsdescwidth}{\dimexpr\linewidth-4\tabcolsep-\gls@tmplen}%
}
```

glslongextraLocSetDescWidth Computes the value of \glsdescwidth for the styles that only have name, location and description columns.

```
\newcommand{\glslongextraLocSetDescWidth}{%
```

Work out the size for just the name and description style.

```
\glslongextraSetDescWidth
```

Subtract 2\tabcolsep and the location list column width.

```
\setlength{\glsdescwidth}{\dimexpr\glsdescwidth-2\tabcolsep-\glspagelistwidth}%
}
```

glslongextraSymLocSetDescWidth Computes the value of \glsdescwidth for the styles that have name, symbol, location and description columns.

```
\newcommand{\glslongextraSymLocSetDescWidth}{%
```

Work out the size for just the name, symbol and description style.

```
\glslongextraSymSetDescWidth
```

Subtract 2\tabcolsep and the location list column width.

```
\setlength{\glsdescwidth}{\dimexpr\glsdescwidth-2\tabcolsep-\glspagelistwidth}%
}
```

glslongextraShortNoNameSetDescWidth Computes the value of \glsdescwidth for the styles that only have short and long columns. The long form will essentially be treated like a description column.

```
\newcommand{\glslongextraShortNoNameSetDescWidth}{%
```

Now work out the short column width. This is assuming that the column title will be the widest text in the column.

```
\glsmeasurewidth{\gls@tmplen}{\glslongextraHeaderFmt\glslongextraShortHeader}%
```

Subtract 4\tabcolsep and the above header width.

```
\setlength{\glsdescwidth}{\dimexpr\linewidth-4\tabcolsep-\gls@tmplen}%
}
```

`\ifGlsLongExtraUseTabular` If true use `tabular` instead of `longtable`. Obviously only intended for short glossaries that can fit into a single page.

```

\newif\ifGlsLongExtraUseTabular
\GlsLongExtraUseTabularfalse

```

`\glslongextraTabularVAlign` Only used with the `tabular` setting.

```

\newcommand*{\glslongextraTabularVAlign}{c}

```

`long-name-desc` Two column style with multi-lined descriptions and header. This is similar to the `longragged-booktabs` style.

```

\newglossarystyle{long-name-desc}%
{%
  \ifGlsLongExtraUseTabular
  \renewenvironment{theglossary}%
  {%
    \glslongextraSetDescWidth
    \edef\@glslongextra@begintab{%
      \noexpand\begin{tabular}\@glslongextraTabularVAlign{%
        \expandonce\glslongextraNameAlign
        \expandonce\glslongextraDescAlign}}%
    \@glslongextra@begintab
  }%
  {%
    \glslongextraNameDescTabularFooter
    \end{tabular}%
  }%
  \renewcommand*{\glossaryheader}{\glslongextraNameDescTabularHeader}%
\else
\renewenvironment{theglossary}%
{%
  \glspatchLToutput
  \glslongextraSetDescWidth
  \edef\@glslongextra@begintab{%
    \noexpand\begin{longtable}{%
      \expandonce\glslongextraNameAlign
      \expandonce\glslongextraDescAlign}}%
  \@glslongextra@begintab
}%
  {\end{longtable}}%
  \renewcommand*{\glossaryheader}{\glslongextraNameDescHeader}%
\fi
\renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{2}{##1}}%

```

Sub-groups are only supported with `\printunsrtglossary`.

```

\renewcommand*{\glssubgroupheading}{\glslongextraSubGroupHeading{2}}%

```

Top-level entry.

```

\renewcommand{\glossentry}[2]{%
  \glslongextraNameFmt{##1} &
  \glslongextraDescFmt{##1}\tabularnewline
}

```

```

}%
Child entry.
\renewcommand{\subglossentry}[3]{%
  \glslongextraSubNameFmt{##1}{##2}
  &
  \glslongextraSubDescFmt{##1}{##2}%
  \tabularnewline
}%
\ifglsgnogroupskip
  \renewcommand*{\glsgroupskip}{}%
\else
  \renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
}

```

extraNameDescLocationHeader

```

\newcommand{\glslongextraNameDescLocationHeader}{%
  \glslongextraNameDescLocationTabularHeader\endhead
  \glslongextraNameDescLocationTabularFooter\endfoot
}

```

meDescLocationTabularHeader

```

\newcommand{\glslongextraNameDescLocationTabularHeader}{%
  \toprule
  \glslongextraHeaderFmt\entryname &
  \glslongextraHeaderFmt\descriptionname &
  \glslongextraHeaderFmt\pagelistname\tabularnewline
  \midrule
}

```

meDescLocationTabularFooter

```

\newcommand{\glslongextraNameDescLocationTabularFooter}{%
  \bottomrule
}

```

long-name-desc-loc Three columns: name, description and location list.

```

\newglossarystyle{long-name-desc-loc}%
{%
  \ifGlsLongExtraUseTabular
  \renewenvironment{theglossary}%
  {%
    \glslongextraLocSetDescWidth
    \edef\@glslongextra@begintab{%
      \noexpand\begin{tabular}\@glslongextraTabularVAlign{%
        \expandonce\glslongextraNameAlign
        \expandonce\glslongextraDescAlign
        \expandonce\glslongextraLocationAlign
      }}%
    \@glslongextra@begintab
  }
}

```



```

}%
{%
  \glslongextraNameDescLocationTabularFooter
  \end{tabular}%
}%
\renewcommand*{\glossaryheader}{\glslongextraNameDescLocationTabularHeader}%
\else
\renewenvironment{theglossary}%
{%
  \glspatchLToutput
  \glslongextraLocSetDescWidth
  \edef\@glslongextra@begintab{%
    \noexpand\begin{longtable}{%
      \expandonce\glslongextraNameAlign
      \expandonce\glslongextraDescAlign
      \expandonce\glslongextraLocationAlign
    }}%
  \@glslongextra@begintab
}%
{\end{longtable}}%
\renewcommand*{\glossaryheader}{\glslongextraNameDescLocationHeader}%
\fi
\renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{3}{##1}}%
Sub-groups are only supported with \printunsrtglossary.
\renewcommand*{\glssubgroupheading}{\glslongextraSubGroupHeading{3}}%
\renewcommand{\glossentry}[2]{%
  \glslongextraNameFmt{##1} &
  \glslongextraDescFmt{##1} &
  \glslongextraLocationFmt{##1}{##2}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
  \glslongextraSubNameFmt{##1}{##2}&
  \glslongextraSubDescFmt{##1}{##2}&
  \glslongextraSubLocationFmt{##1}{##2}{##3}%
  \tabularnewline
}%
\ifglsgroupskip
  \renewcommand*{\glsgroupskip}{}%
\else
  \renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
}

\glslongextraDescNameHeader

\newcommand{\glslongextraDescNameHeader}{%
  \glslongextraDescNameTabularHeader\endhead
  \glslongextraDescNameTabularFooter\endfoot
}

```

gextraDescNameTabularHeader

```
\newcommand{\glslongextraDescNameTabularHeader}{%
\toprule
\glslongextraHeaderFmt\descriptionname&
\glslongextraHeaderFmt\entryname \tabularnewline
\midrule
}
```

gextraDescNameTabularFooter

```
\newcommand{\glslongextraDescNameTabularFooter}{%
\bottomrule
}
```

long-desc-name Like name-desc but swaps the columns.

```
\newglossarystyle{long-desc-name}%
{%
\ifGlsLongExtraUseTabular
\renewenvironment{theglossary}%
{%
\glslongextraSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{tabular}[\glslongextraTabularVAlign]{%
\expandonce\glslongextraDescAlign
\expandonce\glslongextraNameAlign}}%
\@glslongextra@begintab
}%
{%
\glslongextraDescNameTabularFooter
\end{tabular}%
}%
\renewcommand*\{\glossaryheader}{\glslongextraDescNameTabularHeader}%
\else
\renewenvironment{theglossary}%
{%
\glspatchLToutput
\glslongextraSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{longtable}{%
\expandonce\glslongextraDescAlign
\expandonce\glslongextraNameAlign}}%
\@glslongextra@begintab
}%
{\end{longtable}}%
\renewcommand*\{\glossaryheader}{\glslongextraDescNameHeader}%
\fi
\renewcommand*\{\glsgroupheading}[1]{\glslongextraGroupHeading{2}{##1}}%
```

Sub-groups are only supported with \printunsrtglossary.

```
\renewcommand*\{\glssubgroupheading}{\glslongextraSubGroupHeading{2}}%
\renewcommand{\glossentry}[2]{%
```

```

\glslongextraDescFmt{##1} &
\glslongextraNameFmt{##1}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
\glslongextraSubDescFmt{##1}{##2} &
\glslongextraSubNameFmt{##1}{##2}\tabularnewline
}%
\ifglsgroupskip
\renewcommand*{\glsgroupskip}{}%
\else
\renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
}

```

extraLocationDescNameHeader

```

\newcommand{\glslongextraLocationDescNameHeader}{%
\glslongextraLocationDescNameTabularHeader\endhead
\glslongextraLocationDescNameTabularFooter\endfoot
}

```

locationDescNameTabularHeader

```

\newcommand{\glslongextraLocationDescNameTabularHeader}{%
\toprule
\glslongextraHeaderFmt\pagelistname&
\glslongextraHeaderFmt\descriptionname&
\glslongextraHeaderFmt\entryname \tabularnewline
\midrule
}

```

locationDescNameTabularFooter

```

\newcommand{\glslongextraLocationDescNameTabularFooter}{%
\bottomrule
}

```

long-loc-desc-name Three columns: location, description and name.

```

\newglossarystyle{long-loc-desc-name}%
{%
\ifGlsLongExtraUseTabular
{%
\glslongextraLocSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{tabular}[\glslongextraTabularVAlign]{%
\expandonce\glslongextraLocationAlign
\expandonce\glslongextraDescAlign
\expandonce\glslongextraNameAlign}}%
\@glslongextra@begintab
}%
}%
\glslongextraLocationDescNameTabularFooter

```

```

\end{tabular}%
}%
\renewcommand*{\glossaryheader}{\glslongextraLocationDescNameTabularHeader}%
\else
\renewenvironment{theglossary}%
{
\glspatchLToutput
\glslongextraLocSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{longtable}{%
\expandonce\glslongextraLocationAlign
\expandonce\glslongextraDescAlign
\expandonce\glslongextraNameAlign}}%
\@glslongextra@begintab
}%
{\end{longtable}}%
\renewcommand*{\glossaryheader}{\glslongextraLocationDescNameHeader}%
\fi
\renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{3}{##1}}%
Sub-groups are only supported with \printunsrtglossary.
\renewcommand*{\glssubgroupheading}{\glslongextraSubGroupHeading{3}}%
\renewcommand{\glossentry}[2]{%
\glslongextraLocationFmt{##1}{##2} &
\glslongextraDescFmt{##1} &
\glslongextraNameFmt{##1}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
\glslongextraSubLocationFmt{##1}{##2}{##3} &
\glslongextraSubDescFmt{##1}{##2} &
\glslongextraSubNameFmt{##1}{##2}\tabularnewline
}%
\ifglsgnognroupskip
\renewcommand*{\glsgroupskip}{}%
\else
\renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
}

```

glslongextraNameDescSymHeader

```

\newcommand{\glslongextraNameDescSymHeader}{%
\glslongextraNameDescSymTabularHeader\endhead
\glslongextraNameDescSymTabularFooter\endfoot
}

```

glslongextraNameDescSymTabularHeader

```

\newcommand{\glslongextraNameDescSymTabularHeader}{%
\toprule
\glslongextraHeaderFmt\entryname &
\glslongextraHeaderFmt\descriptionname &

```

```

\glslongextraHeaderFmt\symbolname\tabularnewline
\midrule
}

```

extraNameDescSymTabularFooter

```

\newcommand{\glslongextraNameDescSymTabularFooter}{%
\bottomrule
}

```

long-name-desc-sym Three column style with symbol in the third column.

```

\newglossarystyle{long-name-desc-sym}%
{%
\ifGlsLongExtraUseTabular
\renewenvironment{theglossary}%
{%
\glslongextraSymSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{tabular}[\glslongextraTabularVAlign]{%
\expandonce\glslongextraNameAlign
\expandonce\glslongextraDescAlign
\expandonce\glslongextraSymbolAlign
}}%
\@glslongextra@begintab
}%
{%
\glslongextraNameDescSymTabularFooter
\end{tabular}%
}%
\renewcommand*{\glossaryheader}{\glslongextraNameDescSymTabularHeader}%
\else
\renewenvironment{theglossary}%
{%
\glspatchLToutput
\glslongextraSymSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{longtable}{%
\expandonce\glslongextraNameAlign
\expandonce\glslongextraDescAlign
\expandonce\glslongextraSymbolAlign
}}%
\@glslongextra@begintab
}%
{\end{longtable}}%
\renewcommand*{\glossaryheader}{\glslongextraNameDescSymHeader}%
\fi
\renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{3}{##1}}%

```

Sub-groups are only supported with \printunsrtglossary.

```

\renewcommand*{\glssubgroupheading}{\glslongextraSubGroupHeading{3}}%
\renewcommand{\glossentry}[2]{%

```

```

\glslongextraNameFmt{##1} &
\glslongextraDescFmt{##1} &
\glslongextraSymbolFmt{##1}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
\glslongextraSubNameFmt{##1}{##2} &
\glslongextraSubDescFmt{##1}{##2} &
\glslongextraSubSymbolFmt{##1}{##2}%
\tabularnewline
}%
\ifglsgnogroupskip
\renewcommand*{\glsgroupskip}{}%
\else
\renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
}

```

raNameDescSymLocationHeader

```

\newcommand{\glslongextraNameDescSymLocationHeader}{%
\glslongextraNameDescSymLocationTabularHeader\endhead
\glslongextraNameDescSymLocationTabularFooter\endfoot
}

```

DescSymLocationTabularHeader

```

\newcommand{\glslongextraNameDescSymLocationTabularHeader}{%
\toprule
\glslongextraHeaderFmt\entryname &
\glslongextraHeaderFmt\descriptionname &
\glslongextraHeaderFmt\symbolname &
\glslongextraHeaderFmt\pagelistname\tabularnewline
\midrule
}

```

DescSymLocationTabularFooter

```

\newcommand{\glslongextraNameDescSymLocationTabularFooter}{%
\bottomrule
}

```

long-name-desc-sym-loc Four columns: name, description and location

```

\newglossarystyle{long-name-desc-sym-loc}%
{%
\ifGlsLongExtraUseTabular
\renewenvironment{theglossary}%
{%
\glslongextraSymLocSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{tabular}[\glslongextraTabularVAlign]{%
\expandonce\glslongextraNameAlign
\expandonce\glslongextraDescAlign

```

```

        \expandonce\glslongextraSymbolAlign
        \expandonce\glslongextraLocationAlign
    }}%
    \@glslongextra@begintab
}%
{%
    \glslongextraNameDescSymLocationTabularFooter
    \end{tabular}%
}%
\renewcommand*{\glossaryheader}{\glslongextraNameDescSymLocationTabularHeader}%
\else
\renewenvironment{theglossary}%
{%
    \glspatchLToutput
    \glslongextraSymLocSetDescWidth
    \edef\@glslongextra@begintab{%
        \noexpand\begin{longtable}{%
            \expandonce\glslongextraNameAlign
            \expandonce\glslongextraDescAlign
            \expandonce\glslongextraSymbolAlign
            \expandonce\glslongextraLocationAlign
        }}%
    \@glslongextra@begintab
}%
{\end{longtable}}%
\renewcommand*{\glossaryheader}{\glslongextraNameDescSymLocationHeader}%
\fi
\renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{4}{##1}}%
Sub-groups are only supported with \printunsrtglossary.
\renewcommand*{\glssubgroupheading}{\glslongextraSubGroupHeading{4}}%
\renewcommand{\glossentry}[2]{%
    \glslongextraNameFmt{##1} &
    \glslongextraDescFmt{##1} &
    \glslongextraSymbolFmt{##1}&
    \glslongextraLocationFmt{##1}{##2}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
    \glslongextraSubNameFmt{##1}{##2} &
    \glslongextraSubDescFmt{##1}{##2} &
    \glslongextraSubSymbolFmt{##1}{##2}&
    \glslongextraSubLocationFmt{##1}{##2}{##3}%
    \tabularnewline
}%
\ifglsnogroupskip
\renewcommand*{\glsgroupskip}{}%
\else
\renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
}

```

glslongextraNameSymDescHeader

```
\newcommand{\glslongextraNameSymDescHeader}{%
\glslongextraNameSymDescTabularHeader\endhead
\glslongextraNameSymDescTabularFooter\endfoot
}
```

glslongextraNameSymDescTabularHeader

```
\newcommand{\glslongextraNameSymDescTabularHeader}{%
\toprule
\glslongextraHeaderFmt\entryname &
\glslongextraHeaderFmt\symbolname &
\glslongextraHeaderFmt\descriptionname\tabularnewline
\midrule
}
```

glslongextraNameSymDescTabularFooter

```
\newcommand{\glslongextraNameSymDescTabularFooter}{%
\bottomrule
}
```

long-name-sym-desc Three column style with symbol in the second column.

```
\newglossarystyle{long-name-sym-desc}%
{%
\ifGlsLongExtraUseTabular
\renewenvironment{theglossary}%
{%
\glslongextraSymSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{tabular}[\glslongextraTabularVAlign]{%
\expandonce\glslongextraNameAlign
\expandonce\glslongextraSymbolAlign
\expandonce\glslongextraDescAlign
}}%
\@glslongextra@begintab
}%
{%
\glslongextraNameSymDescTabularFooter
\end{tabular}%
}%
\renewcommand*{\glossaryheader}{\glslongextraNameSymDescTabularHeader}%
\else
\renewenvironment{theglossary}%
{%
\glspatchLToutput
\glslongextraSymSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{longtable}{%
\expandonce\glslongextraNameAlign
\expandonce\glslongextraSymbolAlign
```



```

\expandonce\glslongextraDescAlign
}}%
\@glslongextra@begintab
}%
{\end{longtable}}%
\renewcommand*{\glossaryheader}{\glslongextraNameSymDescHeader}%
\fi
\renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{3}{##1}}%
Sub-groups are only supported with \printunsrtglossary.
\renewcommand*{\glssubgroupheading}{\glslongextraSubGroupHeading{3}}%
\renewcommand{\glossentry}[2]{%
\glslongextraNameFmt{##1} &
\glslongextraSymbolFmt{##1} &
\glslongextraDescFmt{##1}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
\glslongextraSubNameFmt{##1}{##2} &
\glslongextraSubSymbolFmt{##1}{##2} &
\glslongextraSubDescFmt{##1}{##2}\tabularnewline
}%
\ifglsnogroupskip
\renewcommand*{\glsgroupskip}{}%
\else
\renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
}

```

raNameSymDescLocationHeader

```

\newcommand{\glslongextraNameSymDescLocationHeader}{%
\glslongextraNameSymDescLocationTabularHeader\endhead
\glslongextraNameSymDescLocationTabularFooter\endfoot
}

```

ymDescLocationTabularHeader

```

\newcommand{\glslongextraNameSymDescLocationTabularHeader}{%
\toprule
\glslongextraHeaderFmt\entryname &
\glslongextraHeaderFmt\symbolname &
\glslongextraHeaderFmt\descriptionname &
\glslongextraHeaderFmt\pagelistname\tabularnewline
\midrule
}

```

ymDescLocationTabularFooter

```

\newcommand{\glslongextraNameSymDescLocationTabularFooter}{%
\bottomrule
}

```

long-name-sym-desc-loc Four column style with symbol in the second column.

```

\newglossarystyle{long-name-sym-desc-loc}%
{%
  \ifGlsLongExtraUseTabular
    \renewenvironment{theglossary}%
    {%
      \glslongextraSymLocSetDescWidth
      \edef\@glslongextra@begintab{%
        \noexpand\begin{tabular}[\glslongextraTabularVAlign]{%
          \expandonce\glslongextraNameAlign
          \expandonce\glslongextraSymbolAlign
          \expandonce\glslongextraDescAlign
          \expandonce\glslongextraLocationAlign
        }}%
      \@glslongextra@begintab
    }%
    {%
      \glslongextraNameSymDescLocationTabularFooter
      \end{tabular}%
    }%
    \renewcommand*\{glossaryheader\}{\glslongextraNameSymDescLocationTabularHeader}%
  \else
    \renewenvironment{theglossary}%
    {%
      \glspatchLToutput
      \glslongextraSymLocSetDescWidth
      \edef\@glslongextra@begintab{%
        \noexpand\begin{longtable}{%
          \expandonce\glslongextraNameAlign
          \expandonce\glslongextraSymbolAlign
          \expandonce\glslongextraDescAlign
          \expandonce\glslongextraLocationAlign
        }}%
      \@glslongextra@begintab
    }%
    {\end{longtable}}%
    \renewcommand*\{glossaryheader\}{\glslongextraNameSymDescLocationHeader}%
  \fi
  \renewcommand*\{glsgroupheading\}[1]{\glslongextraGroupHeading{4}{##1}}%
  Sub-groups are only supported with \printunsrtglossary.
  \renewcommand*\{glssubgroupheading\}{\glslongextraSubGroupHeading{4}}%
  \renewcommand{\glossentry}[2]{%
    \glslongextraNameFmt{##1} &
    \glslongextraSymbolFmt{##1} &
    \glslongextraDescFmt{##1} &
    \glslongextraLocationFmt{##1}{##2}\tabularnewline
  }%
  \renewcommand{\subglossentry}[3]{%
    \glslongextraSubNameFmt{##1}{##2} &
    \glslongextraSubSymbolFmt{##1}{##2} &

```

```

\glslongextraSubDescFmt{##1}{##2} &
\glslongextraSubLocationFmt{##1}{##2}{##3}\tabularnewline
}%
\ifglsgnogroupskip
\renewcommand*{\glsgroupskip}{}%
\else
\renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
}

```

glslongextraSymDescNameHeader

```

\newcommand{\glslongextraSymDescNameHeader}{%
\glslongextraSymDescNameTabularHeader\endhead
\glslongextraSymDescNameTabularFooter\endfoot
}

```

glslongextraSymDescNameTabularHeader

```

\newcommand{\glslongextraSymDescNameTabularHeader}{%
\toprule
\glslongextraHeaderFmt\symbolname &
\glslongextraHeaderFmt\descriptionname &
\glslongextraHeaderFmt\entryname\tabularnewline
\midrule
}

```

glslongextraSymDescNameTabularFooter

```

\newcommand{\glslongextraSymDescNameTabularFooter}{%
\bottomrule
}

```

long-sym-desc-name Three column style with symbol in the first column, description in the second and name in the third.

```

\newglossarystyle{long-sym-desc-name}%
{%
\ifGlsLongExtraUseTabular
\renewenvironment{theglossary}%
{%
\glslongextraSymSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{tabular}[\glslongextraTabularVAlign]{%
\expandonce\glslongextraSymbolAlign
\expandonce\glslongextraDescAlign
\expandonce\glslongextraNameAlign
}}%
\@glslongextra@begintab
}%
{%
\glslongextraSymDescNameTabularFooter
\end{tabular}%
}

```

```

    }%
    \renewcommand*{\glossaryheader}{\glslongextraSymDescNameTabularHeader}%
  \else
    \renewenvironment{theglossary}%
    {%
      \glspatchLToutput
      \glslongextraSymSetDescWidth
      \edef\@glslongextra@begintab{%
        \noexpand\begin{longtable}{%
          \expandonce\glslongextraSymbolAlign
          \expandonce\glslongextraDescAlign
          \expandonce\glslongextraNameAlign
        }}%
      \@glslongextra@begintab
    }%
    {\end{longtable}}%
    \renewcommand*{\glossaryheader}{\glslongextraSymDescNameHeader}%
  \fi
  \renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{3}{##1}}%
  Sub-groups are only supported with \printunsrtglossary.
  \renewcommand*{\glssubgroupheading}{\glslongextraSubGroupHeading{3}}%
  \renewcommand{\glossentry}[2]{%
    \glslongextraSymbolFmt{##1} &
    \glslongextraDescFmt{##1} &
    \glslongextraNameFmt{##1}\tabularnewline
  }%
  \renewcommand{\subglossentry}[3]{%
    \glslongextraSubSymbolFmt{##1}{##2} &
    \glslongextraSubDescFmt{##1}{##2} &
    \glslongextraSubNameFmt{##1}{##2}\tabularnewline
  }%
  \ifglsgnognroupskip
    \renewcommand*{\glsgroupskip}{}%
  \else
    \renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
  \fi
}

\newcommand{\glslocationSymDescNameHeader}{%
  \glslongextraLocationSymDescNameTabularHeader\endhead
  \glslongextraLocationSymDescNameTabularFooter\endfoot
}

\newcommand{\glslocationSymDescNameTabularHeader}{%
  \toprule
  \glslongextraHeaderFmt\pagelistname &
  \glslongextraHeaderFmt\symbolname &

```

```

\glslongextraHeaderFmt\descriptionname &
\glslongextraHeaderFmt\entryname\tabularnewline
\midrule
}

```

ionSymDescNameTabularFooter

```

\newcommand{\glslongextraLocationSymDescNameTabularFooter}{%
\bottomrule
}

```

long-loc-sym-desc-name Four column style with location list, symbol, description and name.

```

\newglossarystyle{long-loc-sym-desc-name}%
{%
\ifGlsLongExtraUseTabular
\renewenvironment{theglossary}%
{%
\glslongextraSymLocSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{tabular}[\glslongextraTabularVAlign]{%
\expandonce\glslongextraLocationAlign
\expandonce\glslongextraSymbolAlign
\expandonce\glslongextraDescAlign
\expandonce\glslongextraNameAlign
}}%
\@glslongextra@begintab
}%
{%
\glslongextraLocationSymDescNameTabularFooter
\end{tabular}%
}%
\renewcommand*{\glossaryheader}{\glslongextraLocationSymDescNameTabularHeader}%
\else
\renewenvironment{theglossary}%
{%
\glspatchLToutput
\glslongextraSymLocSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{longtable}{%
\expandonce\glslongextraLocationAlign
\expandonce\glslongextraSymbolAlign
\expandonce\glslongextraDescAlign
\expandonce\glslongextraNameAlign
}}%
\@glslongextra@begintab
}%
{\end{longtable}}%
\renewcommand*{\glossaryheader}{\glslongextraLocationSymDescNameHeader}%
\fi
\renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{4}{##1}}%

```

Sub-groups are only supported with `\printunsrtglossary`.

```
\renewcommand*{\glssubgroupheading}{\glslongextraSubGroupHeading{4}}%
\renewcommand{\glossentry}[2]{%
  \glslongextraLocationFmt{##1}{##2} &
  \glslongextraSymbolFmt{##1} &
  \glslongextraDescFmt{##1} &
  \glslongextraNameFmt{##1}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
  \glslongextraSubLocationFmt{##1}{##2}{##3} &
  \glslongextraSubSymbolFmt{##1}{##2} &
  \glslongextraSubDescFmt{##1}{##2} &
  \glslongextraSubNameFmt{##1}{##2}\tabularnewline
}%
\ifglsgroupskip
  \renewcommand*{\glsgroupskip}{}%
\else
  \renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
}
```

`glslongextraDescSymNameHeader`

```
\newcommand{\glslongextraDescSymNameHeader}{%
  \glslongextraDescSymNameTabularHeader\endhead
  \glslongextraDescSymNameTabularFooter\endfoot
}
```

`glslongextraDescSymNameTabularHeader`

```
\newcommand{\glslongextraDescSymNameTabularHeader}{%
  \toprule
  \glslongextraHeaderFmt\descriptionname &
  \glslongextraHeaderFmt\symbolname &
  \glslongextraHeaderFmt\entryname\tabularnewline
  \midrule
}
```

`glslongextraDescSymNameTabularFooter`

```
\newcommand{\glslongextraDescSymNameTabularFooter}{%
  \bottomrule
}
```

`long-desc-sym-name` Three column style with description in the first column, symbol in the second and name in the third.

```
\newglossarystyle{long-desc-sym-name}%
{%
  \ifGlsLongExtraUseTabular
    \renewenvironment{theglossary}%
    {%
      \glslongextraSymSetDescWidth
```

```

\edef\@glslongextra@begintab{%
  \noexpand\begin{tabular}[\@glslongextraTabularVAlign]{%
    \expandonce\glslongextraDescAlign
    \expandonce\glslongextraSymbolAlign
    \expandonce\glslongextraNameAlign
  }}%
\@glslongextra@begintab
}%
{%
  \glslongextraDescSymNameTabularFooter
  \end{tabular}%
}%
\renewcommand*{\glossaryheader}{\glslongextraDescSymNameTabularHeader}%
\else
\renewenvironment{theglossary}%
{%
  \glspatchLToutput
  \glslongextraSymSetDescWidth
  \edef\@glslongextra@begintab{%
    \noexpand\begin{longtable}{%
      \expandonce\glslongextraDescAlign
      \expandonce\glslongextraSymbolAlign
      \expandonce\glslongextraNameAlign
    }}%
  \@glslongextra@begintab
}%
{\end{longtable}}%
\renewcommand*{\glossaryheader}{\glslongextraDescSymNameHeader}%
\fi
\renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{3}{##1}}%
Sub-groups are only supported with \printunsrtglossary.
\renewcommand*{\glssubgroupheading}{\glslongextraSubGroupHeading{3}}%
\renewcommand{\glossentry}[2]{%
  \glslongextraDescFmt{##1} &
  \glslongextraSymbolFmt{##1} &
  \glslongextraNameFmt{##1}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
  \glslongextraSubDescFmt{##1}{##2} &
  \glslongextraSubSymbolFmt{##1}{##2} &
  \glslongextraSubNameFmt{##1}{##2}\tabularnewline
}%
\ifglsnogroupskip
\renewcommand*{\glsgroupskip}{}%
\else
\renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
}

```

raLocationDescSymNameHeader

```
\newcommand{\glslongextraLocationDescSymNameHeader}{%
\glslongextraLocationDescSymNameTabularHeader\endhead
\glslongextraLocationDescSymNameTabularFooter\endfoot
}
```

ionDescSymNameTabularHeader

```
\newcommand{\glslongextraLocationDescSymNameTabularHeader}{%
\toprule
\glslongextraHeaderFmt\pagelistname &
\glslongextraHeaderFmt\descriptionname &
\glslongextraHeaderFmt\symbolname &
\glslongextraHeaderFmt\entryname\tabularnewline
\midrule
}
```

ionDescSymNameTabularFooter

```
\newcommand{\glslongextraLocationDescSymNameTabularFooter}{%
\bottomrule
}
```

long-loc-desc-sym-name Four column style with location list, description, symbol and name.

```
\newglossarystyle{long-loc-desc-sym-name}{%
{%
\ifGlsLongExtraUseTabular
\renewenvironment{theglossary}{%
{%
\glslongextraSymLocSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{tabular}[\glslongextraTabularVAlign]{%
\expandonce\glslongextraLocationAlign
\expandonce\glslongextraDescAlign
\expandonce\glslongextraSymbolAlign
\expandonce\glslongextraNameAlign
}}%
\@glslongextra@begintab
}%
{%
\glslongextraLocationDescSymNameTabularFooter
\end{tabular}%
}%
\renewcommand*\glossaryheader{\glslongextraLocationDescSymNameTabularHeader}%
\else
\renewenvironment{theglossary}{%
{%
\glspatchLToutput
\glslongextraSymLocSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{longtable}{%
```



```

\expandonce\glslongextraLocationAlign
\expandonce\glslongextraDescAlign
\expandonce\glslongextraSymbolAlign
\expandonce\glslongextraNameAlign
}}%
\@glslongextra@begintab
}%
{\end{longtable}}%
\renewcommand*{\glossaryheader}{\glslongextraLocationDescSymNameHeader}%
\fi
\renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{4}{##1}}%
Sub-groups are only supported with \printunsrtglossary.
\renewcommand*{\glssubgroupheading}{\glslongextraSubGroupHeading{4}}%
\renewcommand{\glossentry}[2]{%
\glslongextraLocationFmt{##1}{##2} &
\glslongextraDescFmt{##1} &
\glslongextraSymbolFmt{##1} &
\glslongextraNameFmt{##1}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
\glslongextraSubLocationFmt{##1}{##2}{##3} &
\glslongextraSubDescFmt{##1}{##2} &
\glslongextraSubSymbolFmt{##1}{##2} &
\glslongextraSubNameFmt{##1}{##2}\tabularnewline
}%
\ifglsgroupskip
\renewcommand*{\glsgroupskip}{}%
\else
\renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
}

```

`long-sym-desc` Two column style with symbol in the first column and description in the second. The name isn't shown unless the symbol is missing.

```

\newglossarystyle{long-sym-desc}%
{%
\ifGlsLongExtraUseTabular
\renewenvironment{theglossary}%
{%
\glslongextraSymNoNameSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{tabular}{\glslongextraTabularVAlign}{%
\expandonce\glslongextraSymbolNameAlign
\expandonce\glslongextraDescAlign
}}%
\@glslongextra@begintab
}%
{%
\glslongextraSymDescTabularFooter

```

```

\end{tabular}}%
}%
\renewcommand*{\glossaryheader}{\glslongextraSymDescTabularHeader}%
\else
\renewenvironment{theglossary}%
{
\glspatchLToutput
\glslongextraSymNoNameSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{longtable}{%
\expandonce\glslongextraSymbolNameAlign
\expandonce\glslongextraDescAlign
}}%
\@glslongextra@begintab
}%
{\end{longtable}}}%
\renewcommand*{\glossaryheader}{\glslongextraSymDescHeader}%
\fi
\renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{3}{##1}}%

```

Sub-groups are only supported with \printunsrtglossary.

```

\renewcommand*{\glssubgroupheading}{\glslongextraSubGroupHeading{3}}%
\renewcommand{\glossentry}[2]{%
\glslongextraSymbolOrName{##1} &
\glslongextraDescFmt{##1}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
\glslongextraSubSymbolOrName{##1}{##2} &
\glslongextraSubDescFmt{##1}{##2}\tabularnewline
}%
\ifglsgroupskip
\renewcommand*{\glsgroupskip}{}%
\else
\renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
}

```

\glslongextraSymDescHeader

```

\newcommand{\glslongextraSymDescHeader}{%
\glslongextraSymDescTabularHeader\endhead
\glslongextraSymDescTabularFooter\endfoot
}

```

ngextraSymDescTabularHeader

```

\newcommand{\glslongextraSymDescTabularHeader}{%
\toprule
\glslongextraHeaderFmt\symbolname &
\glslongextraHeaderFmt\descriptionname\tabularnewline
\midrule
}

```

ngextraSymDescTabularFooter

```
\newcommand{\glslongextraSymDescTabularFooter}{%
\bottomrule
}
```

long-desc-sym Two column style with description in the first column and symbol in the second.
The name isn't shown.

```
\newglossarystyle{long-desc-sym}%
{%
\ifGlsLongExtraUseTabular
\renewenvironment{theglossary}%
{%
\glslongextraSymNoNameSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{tabular}[\glslongextraTabularVAlign]{%
\expandonce\glslongextraDescAlign
\expandonce\glslongextraSymbolNameAlign
}}%
\@glslongextra@begintab
}%
{%
\glslongextraDescSymTabularFooter
\end{tabular}%
}%
\renewcommand*{\glossaryheader}{\glslongextraDescSymTabularHeader}%
\else
\renewenvironment{theglossary}%
{%
\glspatchLToutput
\glslongextraSymNoNameSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{longtable}{%
\expandonce\glslongextraDescAlign
\expandonce\glslongextraSymbolNameAlign
}}%
\@glslongextra@begintab
}%
{\end{longtable}}%
\renewcommand*{\glossaryheader}{\glslongextraDescSymHeader}%
\fi
\renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{3}{##1}}%
```

Sub-groups are only supported with \printunsrtglossary.

```
\renewcommand*{\glssubgroupheading}{\glslongextraSubGroupHeading{3}}%
\renewcommand{\glossentry}[2]{%
\glslongextraDescFmt{##1} &
\glslongextraSymbolOrName{##1}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
\glslongextraSubDescFmt{##1}{##2} &
```

```

\glslongextraSubSymbolOrName{##1}{##2}\tabularnewline
}%
\ifglsnogroupskip
\renewcommand*{\glsgroupskip}{}%
\else
\renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
}

```

```

\glslongextraDescSymHeader

\newcommand{\glslongextraDescSymHeader}{%
\glslongextraDescSymTabularHeader\endhead
\glslongextraDescSymTabularFooter\endfoot
}

```

```

\glslongextraDescSymTabularHeader

\newcommand{\glslongextraDescSymTabularHeader}{%
\toprule
\glslongextraHeaderFmt\descriptionname &
\glslongextraHeaderFmt\symbolname\tabularnewline
\midrule
}

```

```

\glslongextraDescSymTabularFooter

\newcommand{\glslongextraDescSymTabularFooter}{%
\bottomrule
}

```

abbr-short-long Two column style with the short field in the first column and the long field in the second. The name, symbol and description aren't shown (although the abbreviation style may mean that they will happen to be shown if they are the same as the short or long field).

```

\newglossarystyle{abbr-short-long}{%
{%
\ifGlsLongExtraUseTabular
\renewenvironment{theglossary}{%
{%
\glslongextraShortNoNameSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{tabular}[\glslongextraTabularVAlign]{%
\expandonce\glslongextraNameAlign
\expandonce\glslongextraDescAlign
}}%
\@glslongextra@begintab
}%
{%
\glslongextraShortLongTabularFooter
\end{tabular}%
}%
}

```

```

\renewcommand*{\glossaryheader}{\glslongextraShortLongTabularHeader}%
\else
\renewenvironment{theglossary}%
{
  \glspatchLToutput
  \glslongextraShortNoNameSetDescWidth
  \edef\@glslongextra@begintab{%
    \noexpand\begin{longtable}{%
      \expandonce\glslongextraNameAlign
      \expandonce\glslongextraDescAlign
    }}%
  \@glslongextra@begintab
}%
{\end{longtable}}%
\renewcommand*{\glossaryheader}{\glslongextraShortLongHeader}%
\fi
\renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{3}{##1}}%
Sub-groups are only supported with \printunsrtglossary.
\renewcommand*{\glssubgroupheading}{\glslongextraSubGroupHeading{3}}%
\renewcommand{\glossentry}[2]{%
  \ifglshasshort{##1}%
  {\glslongextraShortTargetFmt{##1}}%
  {\glslongextraNameFmt{##1}}%
  &
  \ifglshaslong{##1}%
  {\glslongextraLongFmt{##1}}%
  {\glslongextraDescFmt{##1}}%
  \tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
  \ifglshasshort{##2}%
  {\glslongextraSubShortTargetFmt{##1}{##2}}%
  {\glslongextraSubNameFmt{##1}{##2}}%
  &
  \ifglshaslong{##2}%
  {\glslongextraSubLongFmt{##1}{##2}}%
  {\glslongextraSubDescFmt{##1}{##2}}%
  \tabularnewline
}%
\ifglsnogroupskip
\renewcommand*{\glsgroupskip}{}%
\else
\renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
}

\glslongextraShortLongHeader

\newcommand{\glslongextraShortLongHeader}{%
\glslongextraShortLongTabularHeader\endhead

```

```

\glslongextraShortLongTabularFooter\endfoot
}

\glslongextraShortHeader
\newcommand{\glslongextraShortHeader}{\entryname}

\glslongextraLongHeader
\newcommand{\glslongextraLongHeader}{\descriptionname}

\glslongextraShortLongTabularHeader
\newcommand{\glslongextraShortLongTabularHeader}{%
\toprule
\glslongextraHeaderFmt\glslongextraShortHeader &
\glslongextraHeaderFmt\glslongextraLongHeader\tabularnewline
\midrule
}

\glslongextraShortLongTabularFooter
\newcommand{\glslongextraShortLongTabularFooter}{%
\bottomrule
}

abbr-long-short Two column style with the short field in the first column and the long field
in the second. The name, symbol and description aren't shown (although the
abbreviation style may mean that they will happen to be shown if they are the
same as the short or long field).
\newglossarystyle{abbr-long-short}{%
{%
\ifGlsLongExtraUseTabular
\renewenvironment{theglossary}{%
{%
\glslongextraShortNoNameSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{tabular}[\glslongextraTabularVAlign]{%
\expandonce\glslongextraDescAlign
\expandonce\glslongextraNameAlign
}}%
\@glslongextra@begintab
}%
{%
\glslongextraLongShortTabularFooter
\end{tabular}%
}%
\renewcommand*{\glossaryheader}{\glslongextraLongShortTabularHeader}%
\else
\renewenvironment{theglossary}{%
{%
\glspatchLToutput
\glslongextraShortNoNameSetDescWidth

```

```

\edef\@glslongextra@begintab{%
\noexpand\begin{longtable}{%
\expandonce\glslongextraDescAlign
\expandonce\glslongextraNameAlign
}}%
\@glslongextra@begintab
}%
{\end{longtable}}%
\renewcommand*\{glossaryheader}\{glslongextraLongShortHeader}%
\fi
\renewcommand*\{glsgroupheading}[1]\{glslongextraGroupHeading{3}{##1}}%

```

Sub-groups are only supported with \printunsrtglossary.

```

\renewcommand*\{glssubgroupheading}\{glslongextraSubGroupHeading{3}}%
\renewcommand{\glossentry}[2]{%
\ifglshaslong{##1}%
{\glslongextraLongFmt{##1}}%
{\glslongextraDescFmt{##1}}%
&
\ifglshasshort{##1}%
{\glslongextraShortTargetFmt{##1}}%
{\glslongextraNameFmt{##1}}%
\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
\ifglshaslong{##2}%
{\glslongextraSubLongFmt{##1}{##2}}%
{\glslongextraSubDescFmt{##1}{##2}}%
&
\ifglshasshort{##2}%
{\glslongextraSubShortTargetFmt{##1}{##2}}%
{\glslongextraSubNameFmt{##1}{##2}}%
\tabularnewline
}%
\ifglsnogroupskip
\renewcommand*\{glsgroupskip}\{}%
\else
\renewcommand*\{glsgroupskip}\{glspenaltygroupskip}%
\fi
}

```

glslongextraLongShortHeader

```

\newcommand{\glslongextraLongShortHeader}{%
\glslongextraLongShortTabularHeader\endhead
\glslongextraLongShortTabularFooter\endfoot
}

```

extraLongShortTabularHeader

```

\newcommand{\glslongextraLongShortTabularHeader}{%
\toprule

```

```

\glslongextraHeaderFmt\glslongextraLongHeader &
\glslongextraHeaderFmt\glslongextraShortHeader\tabularnewline
\midrule
}

\glslongextraLongShortTabularFooter

\newcommand{\glslongextraLongShortTabularFooter}{%
\bottomrule
}

\glslongextraCustomIField

\newcommand{\glslongextraCustomIField}{useri}

\glslongextraCustomIHeader

\newcommand{\glslongextraCustomIHeader}{%
\MFUsentencecase{\glslongextraCustomIField}}

\glslongextraCustomIFmt

\newcommand{\glslongextraCustomIFmt}[1]{%
\glsxtrusefield{#1}{\glslongextraCustomIField}%
}

\glslongextraSubCustomIFmt

\newcommand{\glslongextraSubCustomIFmt}[2]{%
\glslongextraCustomIFmt{#2}%
}

\glslongextraCustomIIField

\newcommand{\glslongextraCustomIIField}{userii}

\glslongextraCustomIIHeader

\newcommand{\glslongextraCustomIIHeader}{%
\MFUsentencecase{\glslongextraCustomIIField}}

\glslongextraCustomIIFmt

\newcommand{\glslongextraCustomIIFmt}[1]{%
\glsxtrusefield{#1}{\glslongextraCustomIIField}%
}

\glslongextraSubCustomIIFmt

\newcommand{\glslongextraSubCustomIIFmt}[2]{%
\glslongextraCustomIIFmt{#2}%
}

\glslongextraCustomIIIField

\newcommand{\glslongextraCustomIIIField}{useriii}

```



```

\glslongextraCustomIIHeader
    \newcommand{\glslongextraCustomIIHeader}{%
        \MFUsentencecase{\glslongextraCustomIIField}}

\glslongextraCustomIIIFmt
    \newcommand{\glslongextraCustomIIIFmt}[1]{%
        \glsxtrusefield{#1}{\glslongextraCustomIIField}%
    }

\glslongextraSubCustomIIIFmt
    \newcommand{\glslongextraSubCustomIIIFmt}[2]{%
        \glslongextraCustomIIIFmt{#2}%
    }

\glslongextraCustomIAlign Alignment for the custom1 column.
    \newcommand{\glslongextraCustomIAlign}{l}

\glslongextraCustomIIAlign Alignment for the custom2 column.
    \newcommand{\glslongextraCustomIIAlign}{l}

\glslongextraCustomIIIAAlign Alignment for the custom3 column.
    \newcommand{\glslongextraCustomIIIAAlign}{l}

\glslongextraCustomTabularFooter
    \newcommand{\glslongextraCustomTabularFooter}{%
        \bottomrule
    }

\glslongextraNameCustomIHeader
    \newcommand{\glslongextraNameCustomIHeader}{%
        \glslongextraNameCustomITabularHeader\endhead
        \glslongextraCustomTabularFooter\endfoot
    }

\glslongextraNameCustomITabularHeader
    \newcommand{\glslongextraNameCustomITabularHeader}{%
        \toprule
        \glslongextraHeaderFmt\entryname &
        \glslongextraHeaderFmt{\glslongextraCustomIHeader}%
        \tabularnewline\midrule
    }

\glslongextraCustomINameHeader
    \newcommand{\glslongextraCustomINameHeader}{%
        \glslongextraCustomINameTabularHeader\endhead
        \glslongextraCustomTabularFooter\endfoot
    }

```

```

extraCustomINameTabularHeader

\newcommand{\glslongextraCustomINameTabularHeader}{%
\toprule
\glslongextraHeaderFmt{\glslongextraCustomIHeader} &
\glslongextraHeaderFmt\entryname
\tabularnewline\midrule
}

glslongextraNameCustomIIHeader

\newcommand{\glslongextraNameCustomIIHeader}{%
\glslongextraNameCustomIITabularHeader\endhead
\glslongextraCustomTabularFooter\endfoot
}

raNameCustomIITabularHeader

\newcommand{\glslongextraNameCustomIITabularHeader}{%
\toprule
\glslongextraHeaderFmt\entryname &
\glslongextraHeaderFmt{\glslongextraCustomIHeader} &
\glslongextraHeaderFmt{\glslongextraCustomIIHeader}%
\tabularnewline\midrule
}

glslongextraCustomIINameHeader

\newcommand{\glslongextraCustomIINameHeader}{%
\glslongextraCustomIINameTabularHeader\endhead
\glslongextraCustomTabularFooter\endfoot
}

raCustomIINameTabularHeader

\newcommand{\glslongextraCustomIINameTabularHeader}{%
\toprule
\glslongextraHeaderFmt{\glslongextraCustomIHeader} &
\glslongextraHeaderFmt{\glslongextraCustomIIHeader} &
\glslongextraHeaderFmt\entryname
\tabularnewline\midrule
}

ongextraNameCustomIIIHeader

\newcommand{\glslongextraNameCustomIIIHeader}{%
\glslongextraNameCustomIIITabularHeader\endhead
\glslongextraCustomTabularFooter\endfoot
}

raNameCustomIIITabularHeader

\newcommand{\glslongextraNameCustomIIITabularHeader}{%
\toprule
\glslongextraHeaderFmt\entryname &
\glslongextraHeaderFmt{\glslongextraCustomIHeader} &

```

```

\glslongextraHeaderFmt{\glslongextraCustomIIHeader} &
\glslongextraHeaderFmt{\glslongextraCustomIIIHeader}%
\tabularnewline\midrule
}

```

ongextraCustomNameIIIHeader

```

\newcommand{\glslongextraCustomIIINameHeader}{%
\glslongextraCustomIIINameTabularHeader\endhead
\glslongextraCustomTabularFooter\endfoot
}

```

aCustomIIINameTabularHeader

```

\newcommand{\glslongextraCustomIIINameTabularHeader}{%
\toprule
\glslongextraHeaderFmt{\glslongextraCustomIHeader} &
\glslongextraHeaderFmt{\glslongextraCustomIIHeader} &
\glslongextraHeaderFmt{\glslongextraCustomIIIHeader} &
\glslongextraHeaderFmt\entryname
\tabularnewline\midrule
}

```

long-name-custom1 Two column style with custom 1 field in the second column.

```

\newglossarystyle{long-name-custom1}{%
{%
\ifGlsLongExtraUseTabular
\renewenvironment{theglossary}{%
{%
\edef\@glslongextra@begintab{%
\noexpand\begin{tabular}[\glslongextraTabularVAlign]{%
\expandonce\glslongextraNameAlign
\expandonce\glslongextraCustomIAlign
}}%
\@glslongextra@begintab
}%
{%
\glslongextraCustomTabularFooter
\end{tabular}%
}%
\renewcommand*{\glossaryheader}{\glslongextraNameCustomITabularHeader}%
\else
\renewenvironment{theglossary}{%
{%
\glspatchLToutput
\edef\@glslongextra@begintab{%
\noexpand\begin{longtable}{%
\expandonce\glslongextraNameAlign
\expandonce\glslongextraCustomIAlign
}}%
\@glslongextra@begintab

```

```

    }%
    {\end{longtable}}}%
    \renewcommand*{\glossaryheader}{\glslongextraNameCustomIHeader}%
  \fi
  \renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{2}{##1}}%
Sub-groups are only supported with \printunsrtglossary.
  \renewcommand*{\glssubgroupheading}{\glslongextraSubGroupHeading{2}}%
  \renewcommand{\glossentry}[2]{%
    \glslongextraNameFmt{##1} &
    \glslongextraCustomIFmt{##1}\tabularnewline
  }%
  \renewcommand{\subglossentry}[3]{%
    \glslongextraSubNameFmt{##1}{##2} &
    \glslongextraSubCustomIFmt{##1}{##2}\tabularnewline
  }%
  \ifglsgnogroupskip
    \renewcommand*{\glsgroupskip}{}%
  \else
    \renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
  \fi
}

```

long-custom1-name Two column style with custom 1 field in the first column.

```

\newglossarystyle{long-custom1-name}%
{%
  \ifGlsLongExtraUseTabular
    \renewenvironment{theglossary}%
    {%
      \edef\@glslongextra@begintab{%
        \noexpand\begin{tabular}[\glslongextraTabularVAlign]{%
          \expandonce\glslongextraCustomIAlign
          \expandonce\glslongextraNameAlign
        }}%
      \@glslongextra@begintab
    }%
    {%
      \glslongextraCustomTabularFooter
      \end{tabular}%
    }%
    \renewcommand*{\glossaryheader}{\glslongextraCustomINameTabularHeader}%
  \else
    \renewenvironment{theglossary}%
    {%
      \glspatchLToutput
      \edef\@glslongextra@begintab{%
        \noexpand\begin{longtable}{%
          \expandonce\glslongextraCustomIAlign
          \expandonce\glslongextraNameAlign
        }}%
    }%
  \fi
}

```

```

        \@glslongextra@begintab
    }%
    {\end{longtable}}%
    \renewcommand*{\glossaryheader}{\glslongextraCustomINameHeader}%
\fi
\renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{2}{##1}}%
Sub-groups are only supported with \printunsrtglossary.
\renewcommand*{\glssubgroupheading}{\glslongextraSubGroupHeading{2}}%
\renewcommand{\glossentry}[2]{%
    \glslongextraCustomIFmt{##1} &
    \glslongextraNameFmt{##1}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
    \glslongextraSubCustomIFmt{##1}{##2} &
    \glslongextraSubNameFmt{##1}{##2}\tabularnewline
}%
\ifglsgnোগroupskip
    \renewcommand*{\glsgroupskip}{}%
\else
    \renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
}

```

long-name-custom2 Three column style with custom 1 field in the second column and custom 2 field in the third column.

```

\newglossarystyle{long-name-custom2}%
{%
    \ifGlsLongExtraUseTabular
    \renewenvironment{theglossary}%
    {%
        \edef\@glslongextra@begintab{%
            \noexpand\begin{tabular}[\glslongextraTabularVAlign]{%
                \expandonce\glslongextraNameAlign
                \expandonce\glslongextraCustomIAlign
                \expandonce\glslongextraCustomIIAlign
            }%
        }
        \@glslongextra@begintab
    }%
    {%
        \glslongextraCustomTabularFooter
        \end{tabular}%
    }%
    \renewcommand*{\glossaryheader}{\glslongextraNameCustomIITabularHeader}%
\else
\renewenvironment{theglossary}%
{%
    \glspatchLToutput
    \edef\@glslongextra@begintab{%
        \noexpand\begin{longtable}{%

```

```

        \expandonce\glslongextraNameAlign
        \expandonce\glslongextraCustomIAlign
        \expandonce\glslongextraCustomIIAlign
    }}%
    \@glslongextra@begintab
}%
{\end{longtable}}%
\renewcommand*{\glossaryheader}{\glslongextraNameCustomIIHeader}%
\fi
\renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{3}{##1}}%
Sub-groups are only supported with \printunsrtglossary.
\renewcommand*{\glssubgroupheading}{\glslongextraSubGroupHeading{3}}%
\renewcommand{\glossentry}[2]{%
    \glslongextraNameFmt{##1} &
    \glslongextraCustomIFmt{##1}&
    \glslongextraCustomIIFmt{##1}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
    \glslongextraSubNameFmt{##1}{##2} &
    \glslongextraSubCustomIFmt{##1}{##2} &
    \glslongextraSubCustomIIFmt{##1}{##2}\tabularnewline
}%
\ifglsnogroupskip
    \renewcommand*{\glsgroupskip}{}%
\else
    \renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
}

```

long-custom2-name As long-name-custom2 but with the name column at the end.

```

\newglossarystyle{long-custom2-name}%
{%
    \ifGlsLongExtraUseTabular
    \renewenvironment{theglossary}%
    {%
        \edef\@glslongextra@begintab{%
            \noexpand\begin{tabular}[\glslongextraTabularVAlign]{%
                \expandonce\glslongextraCustomIAlign
                \expandonce\glslongextraCustomIIAlign
                \expandonce\glslongextraNameAlign
            }}%
        \@glslongextra@begintab
    }%
    {%
        \glslongextraCustomTabularFooter
        \end{tabular}%
    }%
    \renewcommand*{\glossaryheader}{\glslongextraCustomIINameTabularHeader}%
\else

```

```

\renewenvironment{theglossary}%
{
  \glspatchLToutput
  \edef\@glslongextra@begintab{%
    \noexpand\begin{longtable}{%
      \expandonce\glslongextraCustomIAlign
      \expandonce\glslongextraCustomIIAlign
      \expandonce\glslongextraNameAlign
    }}%
  \@glslongextra@begintab
}%
\end{longtable}}%
\renewcommand*{\glossaryheader}{\glslongextraCustomINameHeader}%
\fi
\renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{3}{##1}}%
Sub-groups are only supported with \printunsrtglossary.
\renewcommand*{\glssubgroupheading}{\glslongextraSubGroupHeading{3}}%
\renewcommand{\glossentry}[2]{%
  \glslongextraCustomIFmt{##1}&
  \glslongextraCustomIIFmt{##1} &
  \glslongextraNameFmt{##1}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
  \glslongextraSubCustomIFmt{##1}{##2} &
  \glslongextraSubCustomIIFmt{##1}{##2} &
  \glslongextraSubNameFmt{##1}{##2}\tabularnewline
}%
\ifglsgnognogroupskip
  \renewcommand*{\glsgroupskip}{}%
\else
  \renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
}

```

long-name-custom3 Four column style with custom 1 field in the second column, custom 2 field in the third column and custom 3 field in the fourth column.

```

\newglossarystyle{long-name-custom3}%
{
  \ifGlsLongExtraUseTabular
  \renewenvironment{theglossary}%
  {
    \edef\@glslongextra@begintab{%
      \noexpand\begin{tabular}[\glslongextraTabularVAlign]{%
        \expandonce\glslongextraNameAlign
        \expandonce\glslongextraCustomIAlign
        \expandonce\glslongextraCustomIIAlign
        \expandonce\glslongextraCustomIIFmt{##1}&
        \expandonce\glslongextraCustomIIFmt{##1} &
        \expandonce\glslongextraSubNameFmt{##1}{##2} &
        \expandonce\glslongextraSubNameFmt{##1}{##2} &
        \expandonce\glslongextraSubNameFmt{##1}{##2} &
        \expandonce\glslongextraSubNameFmt{##1}{##2} &
      }}%
    \@glslongextra@begintab
  }
  \ifglsgnognogroupskip
    \renewcommand*{\glsgroupskip}{}%
  \else
    \renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
  \fi
}

```

```

}%
{%
  \glslongextraCustomTabularFooter
  \end{tabular}%
}%
\renewcommand*{\glossaryheader}{\glslongextraNameCustomIIITabularHeader}%
\else
\renewenvironment{theglossary}%
{%
  \glspatchLToutput
  \edef\@glslongextra@begintab{%
    \noexpand\begin{longtable}%
    \expandonce\glslongextraNameAlign
    \expandonce\glslongextraCustomIIAlign
    \expandonce\glslongextraCustomIIIAAlign
    \expandonce\glslongextraCustomIIIIAlign
  }%
  \@glslongextra@begintab
}%
{\end{longtable}}%
\renewcommand*{\glossaryheader}{\glslongextraNameCustomIIHeader}%
\fi
\renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{4}{##1}}%
Sub-groups are only supported with \printunsrtglossary.
\renewcommand*{\glssubgroupheading}{\glslongextraSubGroupHeading{4}}%
\renewcommand{\glossentry}[2]{%
  \glslongextraNameFmt{##1} &
  \glslongextraCustomIFmt{##1}&
  \glslongextraCustomIIFmt{##1}&
  \glslongextraCustomIIIFmt{##1}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
  \glslongextraSubNameFmt{##1}{##2} &
  \glslongextraSubCustomIFmt{##1}{##2} &
  \glslongextraSubCustomIIFmt{##1}{##2} &
  \glslongextraSubCustomIIIFmt{##1}{##2}\tabularnewline
}%
\ifglsnogroupskip
\renewcommand*{\glsgroupskip}{}%
\else
\renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
}

```

long-custom3-name As long-name-custom3 but with the name in the end column.

```

\newglossarystyle{long-custom3-name}%
{%
  \ifGlsLongExtraUseTabular
  \renewenvironment{theglossary}%

```



```

{%
\edef\@glslongextra@begintab{%
\noexpand\begin{tabular}[\@glslongextraTabularVAlign]{%
\expandonce\@glslongextraCustomIAlign
\expandonce\@glslongextraCustomIIAlign
\expandonce\@glslongextraCustomIIIAlign
\expandonce\@glslongextraNameAlign
}}%
\@glslongextra@begintab
}%
{%
\@glslongextraCustomTabularFooter
\end{tabular}%
}%
\renewcommand*{\glossaryheader}{\@glslongextraCustomIIIINameTabularHeader}%
\else
\renewenvironment{theglossary}%
{%
\glspatchLToutput
\edef\@glslongextra@begintab{%
\noexpand\begin{longtable}{%
\expandonce\@glslongextraCustomIAlign
\expandonce\@glslongextraCustomIIAlign
\expandonce\@glslongextraCustomIIIAlign
\expandonce\@glslongextraNameAlign
}}%
\@glslongextra@begintab
}%
{\end{longtable}}%
\renewcommand*{\glossaryheader}{\@glslongextraCustomIIIINameHeader}%
\fi
\renewcommand*{\glsgroupheading}[1]{\@glslongextraGroupHeading{4}{##1}}%
Sub-groups are only supported with \printunsrtglossary.
\renewcommand*{\glssubgroupheading}{\@glslongextraSubGroupHeading{4}}%
\renewcommand{\glossentry}[2]{%
\@glslongextraCustomIFmt{##1}&
\@glslongextraCustomIIFmt{##1}&
\@glslongextraCustomIIIFmt{##1} &
\@glslongextraNameFmt{##1}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
\@glslongextraSubCustomIFmt{##1}{##2} &
\@glslongextraSubCustomIIFmt{##1}{##2} &
\@glslongextraSubCustomIIIFmt{##1}{##2} &
\@glslongextraSubNameFmt{##1}{##2}\tabularnewline
}%
\ifglsnogroupskip
\renewcommand*{\glsgroupskip}{}%
\else

```

```

        \renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
    \fi
}

\longextraCustomISetDescWidth Computes the value of \glsdescwidth for the styles that have name, custom1
and description columns.
    \newcommand{\glslongextraCustomISetDescWidth}{%
Work out the size for just the name and description style.
    \glslongextraSetDescWidth
Now work out the custom1 column width. This is assuming that the column
title will be the widest text in the column.
    \glsmeasurewidth{\gls@tmplen}{\glslongextraHeaderFmt\glslongextraCustomIHeader}%
Subtract 2\tabcolsep and the custom1 header width.
    \setlength{\glsdescwidth}{\dimexpr\glsdescwidth-2\tabcolsep-\gls@tmplen}%
    }

\longextraCustomIISetDescWidth Computes the value of \glsdescwidth for the styles that have name, custom1,
custom2 and description columns.
    \newcommand{\glslongextraCustomIISetDescWidth}{%
    \glslongextraCustomISetDescWidth
    \glsmeasurewidth{\gls@tmplen}{\glslongextraHeaderFmt\glslongextraCustomIIHeader}%
    \setlength{\glsdescwidth}{\dimexpr\glsdescwidth-2\tabcolsep-\gls@tmplen}%
    }

\longextraCustomIIISetDescWidth Computes the value of \glsdescwidth for the styles that have name, custom1,
custom2 and description columns.
    \newcommand{\glslongextraCustomIIISetDescWidth}{%
    \glslongextraCustomIISetDescWidth
    \glsmeasurewidth{\gls@tmplen}{\glslongextraHeaderFmt\glslongextraCustomIIHeader}%
    \setlength{\glsdescwidth}{\dimexpr\glsdescwidth-2\tabcolsep-\gls@tmplen}%
    }

\longextraNameCustomIDescHeader
    \newcommand{\glslongextraNameCustomIDescHeader}{%
    \glslongextraNameCustomIDescTabularHeader\endhead
    \glslongextraCustomTabularFooter\endfoot
    }

\nameCustomIDescTabularHeader
    \newcommand{\glslongextraNameCustomIDescTabularHeader}{%
    \toprule
    \glslongextraHeaderFmt\entryname &
    \glslongextraHeaderFmt{\glslongextraCustomIHeader} &
    \glslongextraHeaderFmt\descriptionname
    \tabularnewline\midrule
    }

```

extraNameCustomIIDescHeader

```
\newcommand{\glslongextraNameCustomIIDescHeader}{%
\glslongextraNameCustomIIDescTabularHeader\endhead
\glslongextraCustomTabularFooter\endfoot
}
```

meCustomIIDescTabularHeader

```
\newcommand{\glslongextraNameCustomIIDescTabularHeader}{%
\toprule
\glslongextraHeaderFmt\entryname &
\glslongextraHeaderFmt{\glslongextraCustomIHeader} &
\glslongextraHeaderFmt{\glslongextraCustomIIHeader} &
\glslongextraHeaderFmt\descriptionname
\tabularnewline\midrule
}
```

extraNameCustomIIIDescHeader

```
\newcommand{\glslongextraNameCustomIIIDescHeader}{%
\glslongextraNameCustomIIIDescTabularHeader\endhead
\glslongextraCustomTabularFooter\endfoot
}
```

neCustomIIIDescTabularHeader

```
\newcommand{\glslongextraNameCustomIIIDescTabularHeader}{%
\toprule
\glslongextraHeaderFmt\entryname &
\glslongextraHeaderFmt{\glslongextraCustomIHeader} &
\glslongextraHeaderFmt{\glslongextraCustomIIHeader} &
\glslongextraHeaderFmt{\glslongextraCustomIIIHeader} &
\glslongextraHeaderFmt\descriptionname
\tabularnewline\midrule
}
```

long-name-custom1-desc Three column style with custom 1 field in the second column and the description in the third.

```
\newglossarystyle{long-name-custom1-desc}%
{%
\ifGlsLongExtraUseTabular
\renewenvironment{theglossary}%
{%
\glslongextraCustomISetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{tabular}{\glslongextraTabularVAlign}{%
\expandonce\glslongextraNameAlign
\expandonce\glslongextraCustomIAlign
\expandonce\glslongextraDescAlign
}}%
\@glslongextra@begintab
}%
}
```

```

    {%
      \glslongextraCustomTabularFooter
    \end{tabular}%
  }%
\renewcommand*{\glossaryheader}{\glslongextraNameCustomIDescTabularHeader}%
\else
\renewenvironment{theglossary}%
{%
  \glspatchLToutput
  \glslongextraCustomISetDescWidth
  \edef\@glslongextra@begintab{%
    \noexpand\begin{longtable}{%
      \expandonce\glslongextraNameAlign
      \expandonce\glslongextraCustomIAlign
      \expandonce\glslongextraDescAlign
    }}%
  \@glslongextra@begintab
}%
{\end{longtable}}%
\renewcommand*{\glossaryheader}{\glslongextraNameCustomIDescHeader}%
\fi
\renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{3}{##1}}%
Sub-groups are only supported with \printunsrtglossary.
\renewcommand*{\glssubgroupheading}{\glslongextraSubGroupHeading{3}}%
\renewcommand{\glossentry}[2]{%
  \glslongextraNameFmt{##1} &
  \glslongextraCustomIFmt{##1}&
  \glslongextraDescFmt{##1}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
  \glslongextraSubNameFmt{##1}{##2} &
  \glslongextraSubCustomIFmt{##1}{##2}&
  \glslongextraSubDescFmt{##1}{##2}\tabularnewline
}%
\ifglsnogroupskip
\renewcommand*{\glsgroupskip}{}%
\else
\renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
}

```

`long-name-custom2-desc` Four column style with custom 1 field in the second column, custom 2 field in the third column and the description in the fourth.

```

\newglossarystyle{long-name-custom2-desc}%
{%
  \ifGlsLongExtraUseTabular
  \renewenvironment{theglossary}%
  {%
    \glslongextraCustomIISetDescWidth

```

```

\edef\@glslongextra@begintab{%
  \noexpand\begin{tabular}[\@glslongextraTabularVAlign]{%
    \expandonce\@glslongextraNameAlign
    \expandonce\@glslongextraCustomIAlign
    \expandonce\@glslongextraCustomIIAlign
    \expandonce\@glslongextraDescAlign
  }}%
\@glslongextra@begintab
}%
{%
  \glslongextraCustomTabularFooter
  \end{tabular}%
}%
\renewcommand*{\glossaryheader}{\@glslongextraNameCustomIIDescTabularHeader}%
\else
\renewenvironment{theglossary}%
{%
  \glspatchLToutput
  \glslongextraCustomIISetDescWidth
  \edef\@glslongextra@begintab{%
    \noexpand\begin{longtable}{%
      \expandonce\@glslongextraNameAlign
      \expandonce\@glslongextraCustomIAlign
      \expandonce\@glslongextraCustomIIAlign
      \expandonce\@glslongextraDescAlign
    }}%
  \@glslongextra@begintab
}%
{\end{longtable}}%
\renewcommand*{\glossaryheader}{\@glslongextraNameCustomIIDescHeader}%
\fi
\renewcommand*{\glsgroupheading}[1]{\@glslongextraGroupHeading{4}{##1}}%
Sub-groups are only supported with \printunsrtglossary.
\renewcommand*{\glssubgroupheading}{\@glslongextraSubGroupHeading{4}}%
\renewcommand{\glossentry}[2]{%
  \glslongextraNameFmt{##1} &
  \glslongextraCustomIFmt{##1}&
  \glslongextraCustomIIFmt{##1}&
  \glslongextraDescFmt{##1}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
  \glslongextraSubNameFmt{##1}{##2} &
  \glslongextraSubCustomIFmt{##1}{##2}&
  \glslongextraSubCustomIIFmt{##1}{##2}&
  \glslongextraSubDescFmt{##1}{##2}\tabularnewline
}%
\ifglsnogroupskip
  \renewcommand*{\glsgroupskip}{}%
\else

```

```

        \renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
    \fi
}

```

long-name-custom3-desc Five column style with custom 1 field in the second column, custom 2 field in the third column, custom 3 field in the fourth column, and the description in the fifth.

```

\newglossarystyle{long-name-custom3-desc}%
{%
  \ifGlsLongExtraUseTabular
    \renewenvironment{theglossary}%
    {%
      \glslongextraCustomIIISetDescWidth
      \edef\@glslongextra@begintab{%
        \noexpand\begin{tabular}[\glslongextraTabularVAlign]{%
          \expandonce\glslongextraNameAlign
          \expandonce\glslongextraCustomIAlign
          \expandonce\glslongextraCustomIIAlign
          \expandonce\glslongextraCustomIIIAlign
          \expandonce\glslongextraDescAlign
        }}%
      \@glslongextra@begintab
    }%
    {%
      \glslongextraCustomTabularFooter
      \end{tabular}%
    }%
    \renewcommand*{\glossaryheader}{\glslongextraNameCustomIIIDescTabularHeader}%
  \else
    \renewenvironment{theglossary}%
    {%
      \glspatchLToutput
      \glslongextraCustomIIISetDescWidth
      \edef\@glslongextra@begintab{%
        \noexpand\begin{longtable}{%
          \expandonce\glslongextraNameAlign
          \expandonce\glslongextraCustomIAlign
          \expandonce\glslongextraCustomIIAlign
          \expandonce\glslongextraCustomIIIAlign
          \expandonce\glslongextraDescAlign
        }}%
      \@glslongextra@begintab
    }%
    {\end{longtable}}%
    \renewcommand*{\glossaryheader}{\glslongextraNameCustomIIIDescHeader}%
  \fi
  \renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{5}{##1}}%

```

Sub-groups are only supported with \printunsrtglossary.

```

\renewcommand*{\glssubgroupheading}{\glslongextraSubGroupHeading{5}}%

```

```

\renewcommand{\glossentry}[2]{%
  \glslongextraNameFmt{##1} &
  \glslongextraCustomIFmt{##1}&
  \glslongextraCustomIIFmt{##1}&
  \glslongextraCustomIIIFmt{##1}&
  \glslongextraDescFmt{##1}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
  \glslongextraSubNameFmt{##1}{##2} &
  \glslongextraSubCustomIFmt{##1}{##2}&
  \glslongextraSubCustomIIFmt{##1}{##2}&
  \glslongextraSubCustomIIIFmt{##1}{##2}&
  \glslongextraSubDescFmt{##1}{##2}\tabularnewline
}%
\ifglsnogroupskip
  \renewcommand*{\glsgroupskip}{}%
\else
  \renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
}

```

extraDescCustomINameHeader

```

\newcommand{\glslongextraDescCustomINameHeader}{%
  \glslongextraDescCustomINameTabularHeader\endhead
  \glslongextraCustomTabularFooter\endfoot
}

```

DescCustomINameTabularHeader

```

\newcommand{\glslongextraDescCustomINameTabularHeader}{%
  \toprule
  \glslongextraHeaderFmt\descriptionname &
  \glslongextraHeaderFmt{\glslongextraCustomIHeader} &
  \glslongextraHeaderFmt\entryname
  \tabularnewline\midrule
}

```

extraDescCustomINameHeader

```

\newcommand{\glslongextraDescCustomINameHeader}{%
  \glslongextraDescCustomINameTabularHeader\endhead
  \glslongextraCustomTabularFooter\endfoot
}

```

DescCustomINameTabularHeader

```

\newcommand{\glslongextraDescCustomINameTabularHeader}{%
  \toprule
  \glslongextraHeaderFmt\descriptionname &
  \glslongextraHeaderFmt{\glslongextraCustomIHeader} &
  \glslongextraHeaderFmt{\glslongextraCustomIIHeader} &
  \glslongextraHeaderFmt\entryname
}

```

```

        \tabularnewline\midrule
    }

extraDescCustomIINameHeader

\newcommand{\glslongextraDescCustomIINameHeader}{%
\glslongextraDescCustomIINameTabularHeader\endhead
\glslongextraCustomTabularFooter\endfoot
}

cCustomIINameTabularHeader

\newcommand{\glslongextraDescCustomIINameTabularHeader}{%
\toprule
\glslongextraHeaderFmt\descriptionname &
\glslongextraHeaderFmt{\glslongextraCustomIHeader} &
\glslongextraHeaderFmt{\glslongextraCustomIIHeader} &
\glslongextraHeaderFmt{\glslongextraCustomIIIHeader} &
\glslongextraHeaderFmt\entryname
\tabularnewline\midrule
}

```

long-desc-custom1-name As long-name-custom1-desc but with the name and description columns the other way around.

```

\newglossarystyle{long-desc-custom1-name}%
{%
\ifGlsLongExtraUseTabular
\renewenvironment{theglossary}%
{%
\glslongextraCustomISetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{tabular}[\glslongextraTabularVAlign]{%
\expandonce\glslongextraDescAlign
\expandonce\glslongextraCustomIAlign
\expandonce\glslongextraNameAlign
}}%
\@glslongextra@begintab
}%
{%
\glslongextraCustomTabularFooter
\end{tabular}%
}%
\renewcommand*{\glossaryheader}{\glslongextraDescCustomINameTabularHeader}%
\else
\renewenvironment{theglossary}%
{%
\glspatchLToutput
\glslongextraCustomISetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{longtable}{%
\expandonce\glslongextraDescAlign

```



```

        \expandonce\glslongextraCustomIAlign
        \expandonce\glslongextraNameAlign
    }}%
    \@glslongextra@begintab
}%
{\end{longtable}}}%
\renewcommand*{\glossaryheader}{\glslongextraDescCustomINameHeader}%
\fi
\renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{3}{##1}}%
Sub-groups are only supported with \printunsrtglossary.
\renewcommand*{\glssubgroupheading}{\glslongextraSubGroupHeading{3}}%
\renewcommand{\glossentry}[2]{%
    \glslongextraDescFmt{##1} &
    \glslongextraCustomIFmt{##1}&
    \glslongextraNameFmt{##1}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
    \glslongextraSubDescFmt{##1}{##2} &
    \glslongextraSubCustomIFmt{##1}{##2}&
    \glslongextraSubNameFmt{##1}{##2}\tabularnewline
}%
\ifglsnogroupskip
    \renewcommand*{\glsgroupskip}{}%
\else
    \renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
}

```

long-desc-custom2-name As long-name-custom2-desc but with the name and description columns the other way around.

```

\newglossarystyle{long-desc-custom2-name}%
{%
    \ifGlsLongExtraUseTabular
    \renewenvironment{theglossary}%
    {%
        \glslongextraCustomIISetDescWidth
        \edef\@glslongextra@begintab{%
            \noexpand\begin{tabular}[\glslongextraTabularVAlign]{%
                \expandonce\glslongextraDescAlign
                \expandonce\glslongextraCustomIAlign
                \expandonce\glslongextraCustomIIAlign
                \expandonce\glslongextraNameAlign
            }}%
        \@glslongextra@begintab
    }%
    {%
        \glslongextraCustomTabularFooter
        \end{tabular}%
    }%
}

```

```

\renewcommand*{\glossaryheader}{\glslongextraDescCustomINameTabularHeader}%
\else
\renewenvironment{theglossary}%
{
  \glspatchLToutput
  \glslongextraCustomIISetDescWidth
  \edef\@glslongextra@begintab{%
    \noexpand\begin{longtable}{%
      \expandonce\glslongextraDescAlign
      \expandonce\glslongextraCustomIAlign
      \expandonce\glslongextraCustomIISetDescWidth
      \expandonce\glslongextraNameAlign
    }}%
    \@glslongextra@begintab
  }%
  {\end{longtable}}%
\renewcommand*{\glossaryheader}{\glslongextraDescCustomINameHeader}%
\fi
\renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{4}{##1}}%
Sub-groups are only supported with \printunsrtglossary.
\renewcommand*{\glssubgroupheading}{\glslongextraSubGroupHeading{4}}%
\renewcommand{\glossentry}[2]{%
  \glslongextraDescFmt{##1} &
  \glslongextraCustomIFmt{##1}&
  \glslongextraCustomIIFmt{##1}&
  \glslongextraNameFmt{##1}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
  \glslongextraSubDescFmt{##1}{##2} &
  \glslongextraSubCustomIFmt{##1}{##2}&
  \glslongextraSubCustomIIFmt{##1}{##2}&
  \glslongextraSubNameFmt{##1}{##2}\tabularnewline
}%
\ifglsgroupskip
\renewcommand*{\glsgroupskip}{}%
\else
\renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
}

```

`long-desc-custom3-name` As long-name-custom-desc but with the name and description columns switched.

```

\newglossarystyle{long-desc-custom3-name}%
{
  \ifGlsLongExtraUseTabular
  \renewenvironment{theglossary}%
  {
    \glslongextraCustomIIISetDescWidth
    \edef\@glslongextra@begintab{%
      \noexpand\begin{tabular}[\glslongextraTabularVAlign]{%

```

```

        \expandonce\glslongextraDescAlign
        \expandonce\glslongextraCustomIAlign
        \expandonce\glslongextraCustomIIAlign
        \expandonce\glslongextraCustomIIIAlign
        \expandonce\glslongextraNameAlign
    }}%
    \@glslongextra@begintab
}%
{%
    \glslongextraCustomTabularFooter
    \end{tabular}%
}%
\renewcommand*{\glossaryheader}{\glslongextraDescCustomIINameTabularHeader}%
\else
\renewenvironment{theglossary}%
{%
    \glspatchLToutput
    \glslongextraCustomIIISetDescWidth
    \edef\@glslongextra@begintab{%
        \noexpand\begin{longtable}{%
            \expandonce\glslongextraDescAlign
            \expandonce\glslongextraCustomIAlign
            \expandonce\glslongextraCustomIIAlign
            \expandonce\glslongextraCustomIIIAlign
            \expandonce\glslongextraNameAlign
        }}%
    \@glslongextra@begintab
}%
{\end{longtable}}%
\renewcommand*{\glossaryheader}{\glslongextraDescCustomIINameHeader}%
\fi
\renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{5}{##1}}%
Sub-groups are only supported with \printunsrtglossary.
\renewcommand*{\glssubgroupheading}{\glslongextraSubGroupHeading{5}}%
\renewcommand{\glossentry}[2]{%
    \glslongextraDescFmt{##1} &
    \glslongextraCustomIFmt{##1}&
    \glslongextraCustomIIFmt{##1}&
    \glslongextraCustomIIIFmt{##1}&
    \glslongextraNameFmt{##1}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
    \glslongextraSubDescFmt{##1}{##2} &
    \glslongextraSubCustomIFmt{##1}{##2}&
    \glslongextraSubCustomIIFmt{##1}{##2}&
    \glslongextraSubCustomIIIFmt{##1}{##2}&
    \glslongextraSubNameFmt{##1}{##2}\tabularnewline
}%
\ifglsnogroupskip

```

```

\renewcommand*{\glsgroupskip}{}%
\else
\renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
}

```

7 topic styles (glossary-topic.sty)

Provides “topic” styles where top-level entries are considered a topic.

```
\NeedsTeXFormat{LaTeX2e}
```

Rollback releases:

```

\DeclareRelease{v1.48}{2021-11-22}{glossary-topic-2021-11-22.sty}
\DeclareCurrentRelease{1.9}{2025-11-03}

```

Declare package:

```
\ProvidesPackage{glossary-topic}[2026/03/06 v2.0 (NLCT)]
```

Load required package.

```
\RequirePackage{multicol}
```

The top-level entries act like headers. If the top-level entry has a description it’s placed below the name.

topic

```

\newglossarystyle{topic}{%
\renewenvironment{theglossary}%
{%
\glstopicInit
\def\glstopic@prechildren{}%
\def\glstopic@prevlevel{-1}%
}%
{\par}%
\renewcommand*{\glossaryheader}{}%
\renewcommand*{\glsgroupheading}[1]{%
\def\glstopic@prevlevel{-1}%
\glstopicGroupHeading{##1}%
}%

```

Sub-groups are only supported with `\printunsrtglossary`.

```

\renewcommand*{\glssubgroupheading}{\glstopicSubGroupHeading}%
\renewcommand{\glossentry}[2]{%
\hangindent0pt\relax
\parindent\glstopicParIndent\relax
\glstopicItem{##1}{##2}%

```

If there isn’t a description, penalise a page break.

```

\ifglshasdesc{##1}%
{%
\def\glstopic@prechildren{}%
}%

```

```

    {%
      \def\glstopic@prechildren{\nopagebreak}%
    }%
  }%
\renewcommand{\subglossentry}[3]{%
  \ifnum\glstopic@prevlevel=0\relax\glstopic@prechildren\fi
  \def\glstopic@prevlevel{##1}%
  Grouping is added to scope the effect of \everypar.
  \begingroup
  \glstopicAssignSubIndent{##1}%
  \glstopicSubItem{##1}{##2}{##3}%

  \par
  \endgroup
}%
\renewcommand*{\glsgroupskip}{}%
}

```

`\glstopicGroupHeading`

`\glstopicGroupHeading{<group label>}`

May be redefined if letter group headings are required. For example:

```

%\renewcommand*{\glstopicGroupHeading}[1]{%
%  \glstrgetgrouptitle{#1}{\thisgrptitle}%
%  \section*{\thisgrptitle}%
%}
%

\newcommand*{\glstopicGroupHeading}[1]{}

```

`\glstopicSubGroupHeading`

`\glstopicSubGroupHeading{<prev group level>}{<group level>}{<parent entry>}{<group label>}`

```

\newcommand*{\glstopicSubGroupHeading}[4]{%
  \begingroup
  \glspare\glstopicPreSkip\glspare\noindent
  \glstrgetgrouptitle{#4}{\glstopicSubgrouptitle}%
  \glstopicAssignSubIndent{#2}%
  \glstopicSubItemBox{#2}{\glstopicTitleFont{\glstopicSubgrouptitle}}%
  \glstopicSubItemSep
  \glspare\nobreak\glstopicPostSkip
  \par
  \endgroup
}

```

```
\glstopicItem{<label>}{<location list>}
```

\glstopicItem

```
\newcommand*{\glstopicItem}[2]{%
  \glsparencount\glstopicPreSkip\glsparencount\noindent
  \glstopicMarker{#1}%
  \glstopicTitleFont
  {%
    \glentryitem{#1}\glstarget{#1}{\glstopicTitle{#1}}%
  }%
  \ifglshasdesc{#1}%
  {\glsparencount\glstopicMidSkip\glsparencount\nobreak
    \@afterheading\glstopicDesc{#1}\glsparencount\glstopicPostSkip
  }%
  {\glsparencount\glstopicPostSkip}%
  \glstopicLoc{#1}{#2}%
}
```

\glstopicMarker May be used to insert a bookmark etc if required.

```
\newcommand*{\glstopicMarker}[1]{}
```

\glstopicName

```
\newcommand*{\glstopicName}[1]{\Glossentryname{#1}%
  \ifglshassymbol{#1}{\space\Glossentrysymbol{#1}}{}}%
```

\glstopicTitleFont

```
\newcommand*{\glstopicTitleFont}[1]{\textbf{\large #1}}
```

\glstopicDesc

```
\newcommand*{\glstopicDesc}[1]{\Glossentrydesc{#1}\glstopicPostDescription}
```

\glstopicLoc

```
\newcommand*{\glstopicLoc}[2]{}
```

\glstopicParIndent

```
\newlength\glstopicParIndent
\setlength\glstopicParIndent{20pt}
```

\glstopicSubIndent

```
\newlength\glstopicSubIndent
\setlength\glstopicSubIndent{20pt}
```

\glstopicInit

```
\newcommand{\glstopicInit}{}%
```

`\glstopicAssignSubIndent{<level>}`

`\glstopicAssignSubIndent`

Used to set the indentation for sub-levels.

```
\newcommand*{\glstopicAssignSubIndent}[1]{%
    \par
    \parindent\dimexpr#1\glstopicSubIndent-\glstopicSubIndent\relax
    \glstopicAssignWidest{#1}%
    \glstopicsubitemhangindent=\dimexpr\parindent+\glstopicwidest\relax
    \hangindent\glstopicsubitemhangindent\relax

    \everypar{\hangindent\glstopicsubitemhangindent\relax
        \parindent\dimexpr\glstopicSubItemParIndent+\glstopicsubitemhangindent\relax}%
}
```

`\glstopicsubitemhangindent`

```
\newlength\glstopicsubitemhangindent
```

`\glstopicSubItemParIndent`

```
\newlength\glstopicSubItemParIndent
\glstopicSubItemParIndent\parindent
```

`\glstopicwidest`

```
\newlength\glstopicwidest
```

`\glstopicAssignWidest{<level>}`

`\glstopicAssignWidest`

Used in the definition of `\glstopicAssignSubIndent` to set the indentation from the widest name for the given level. This will require `glossary-tree` to set the values.

```
\newcommand*{\glstopicAssignWidest}[1]{%
    \ifcsundef{@glswidestlength\romannumeral#1}%
    {%
        \ifcsdef{@glswidestname\romannumeral#1}%
        {%
            \glsmasurewidth{\glstopicwidest}{%
                \glstopicSubNameFont{\csuse{@glswidestname\romannumeral#1}}%
                \glstopicSubItemSep
            }%
        }%
        {\setlength{\glstopicwidest}{0pt}}%
    }
```

Save the value so that it doesn't have to keep being recalculated.

```
\csedef{@glswidestlength\romannumeral#1}{\the\glstopicwidest}%
}%
{\setlength{\glstopicwidest}{\csuse{@glswidestlength\romannumeral#1}}}%
}
```

```

\glstopicPreSkip
\newcommand*{\glstopicPreSkip}{\medskip}

\glstopicMidSkip
\newcommand*{\glstopicMidSkip}{\smallskip}

\glstopicPostSkip
\newcommand*{\glstopicPostSkip}{\smallskip}

\glstopicSubItem
\newcommand*{\glstopicSubItem}[3]{%
  \glstopicSubItemBox{#1}{\glstopicSubNameFont{\glentryitem{#2}%
    \glstarget{#2}{\glossentryname{#2}}}%
    \glstopicSubItemSep
  }%
  \ifglshassymbol{#2}{(\glossentrysymbol{#2})\space}{}%
  \ifglshasdesc{#2}%
    {\glossentrydesc{#2}\glspostdescription\glstopicSubPreLocSep}{}%
    \glstopicSubLoc{#2}{#3}%
  }

\glstopicSubItemSep
\newcommand*{\glstopicSubItemSep}{\quad}

\glstopicSubItemBox
\newcommand*{\glstopicSubItemBox}[2]{%
  \ifdim\glstopicwidest>0pt\relax\makebox[\glstopicwidest][l]{#2}\else#2\fi
}

\glstopicSubNameFont
\newcommand*{\glstopicSubNameFont}[1]{\textbf{#1}}

\glstopicSubPreLocSep
\newcommand*{\glstopicSubPreLocSep}{\space}

\glstopicSubLoc
\newcommand*{\glstopicSubLoc}[2]{#2}

\glstopicCols
\newcommand*{\glstopicCols}{2}

```



```

\glstopicColsEnv
\newcommand*{\glstopicColsEnv}{multicols}

topicmcols
\newglossarystyle{topicmcols}{%
\renewenvironment{theglossary}%
{%
\glstopicInit
\def\glstopic@prechildren{}%
\def\glstopic@postchildren{}%
\def\glstopic@prevlevel{-1}%
}%
{%
\ifnum\glstopic@prevlevel>0\relax\glstopic@postchildren\fi
\par
}%
\renewcommand*{\glossaryheader}{}%
\renewcommand*{\glsgroupheading}[1]{%
\ifnum\glstopic@prevlevel>0\relax\glstopic@postchildren\fi
\def\glstopic@prevlevel{-1}%
\glstopicGroupHeading{##1}%
}%
Sub-groups are only supported with \printunsrtglossary.
\renewcommand*{\glssubgroupheading}{\glstopicSubGroupHeading}%
\renewcommand{\glossentry}[2]{%
\ifnum\glstopic@prevlevel>0\relax\glstopic@postchildren\fi
\def\glstopic@prevlevel{0}%
\hangindent0pt\relax
\parindent\glstopicParIndent\relax
\glstopicItem{##1}{##2}%
\ifnum\glstopicCols>1\relax
If there isn't a description, penalise a page break.
\ifglshasdesc{##1}%
{%
\edef\glstopic@prechildren{%
\noexpand\begin{\glstopicColsEnv}{\glstopicCols}%
}%
}%
{%
\edef\glstopic@prechildren{%
\noexpand\nopagebreak
\noexpand\begin{\glstopicColsEnv}{\glstopicCols}%
}%
}%
\edef\glstopic@postchildren{\noexpand\end{\glstopicColsEnv}}%
\fi
}%
\renewcommand{\subglossentry}[3]{%

```

```

\ifnum\glstopic@prevlevel=0\relax\glstopic@prechildren\fi
\def\glstopic@prevlevel{##1}%
\glstopicAssignSubIndent{##1}%
\glstopicSubItem{##1}{##2}{##3}%
}%
\renewcommand*{\glsgroupskip}{}%
}

```

8 table styles (glossary-table.sty)

Intended for use with bib2gls. This is still experimental.

```
\NeedsTeXFormat{LaTeX2e}
```

Declare package:

```
\ProvidesPackage{glossary-table}[2026/03/06 v2.0 (NLCT)]
```

Load required packages.

```

\RequirePackage{longtable}
\RequirePackage{array}
\RequirePackage{booktabs}

```

Check if `\gls@start@measuring` has been defined (introduced to glossaries v4.51). This package also requires `\ifglsfieldvoid` which was added to glossaries v4.50.

```

\ifdef\gls@start@measuring
{}
{\PackageError{glossary-table}%
{glossaries.sty v4.51+ required. Please update glossaries.sty}
{Your version of glossaries.sty is too old. Minimum version 4.51 required}
}

```

`\glstableblockperrowcount` Number of blocks (entries) per row.

```

\newcount\glstableblockperrowcount
\glstableblockperrowcount=2\relax

```

Add a key to allow this value to be changed.

```
\define@key{printglosstable}{blocks}{\glstableblockperrowcount=#1\relax}
```

`\glstablecurrentblockindex` Keep track of current block (entry) index.

```
\newcount\glstablecurrentblockindex
```

`\glstabletotalcols` Total number of columns. This will be updated at the start of `\printunsrtable`, but is a user level command so that it can be used in any hooks.

```

\newcount\glstabletotalcols
\glstabletotalcols=4\relax

```

`\glstablenameheader`

```
\newcommand{\glstablenameheader}{\entryname}
```

```

\glstabledescheader
\newcommand{\glstabledescheader}{\descriptionname}

\glstableotherheader
\newcommand{\glstableotherheader}{\MFUsentencecase{\glstableotherfield}}

\glstablesymbolheader
\newcommand{\glstablesymbolheader}{\symbolname}

Provide boolean option to suppress header.
\define@boolkey{printglosstable}{header}[true]{}
\KV@printglosstable@headertrue
Provide boolean option to suppress rules.
\define@boolkey{printglosstable}{rules}[true]{}
\KV@printglosstable@rulestrue
Provide boolean option to suppress caption.
\define@boolkey{printglosstable}{caption}[true]{}
\KV@printglosstable@captiontrue
\define@key{printglosstable}{blocksep}{\renewcommand{\glstable@blockalignsep}{#1}}

\glstable@blockalignsep Alignment spec between blocks.
\newcommand{\glstable@blockalignsep}{}

\glstablesubentryalign
\newcommand{\glstablesubentryalign}{%
\glstableleftalign{\dimexpr\glstablesubentrywidth-\tabcolsep}@{}}

\glstablesubentrywidth
\newcommand{\glstablesubentrywidth}{\glstabledescwidth}

glstablesubentries (env.)
\newenvironment{glstablesubentries}%
{%
\protected@edef\@gls@dotabular{%
\noexpand\begin{tabular}[t]{\glstablesubentryalign}}%
\@gls@dotabular
}%
{\end{tabular}}

\glstablePreChildren
\newcommand{\glstablePreChildren}{\glstableifpar{\par}}

\glstableblocksubentrysep
\newcommand{\glstableblocksubentrysep}{\glstablnewline}

```

Provide boolean option to allow paragraph cells.

```
\define@choicekey{printglosstable}{par}
[{\glstable@par@val\glstable@par@n}
{false,justified,ragged}
{%
  \ifcase\glstable@par@n
    \renewcommand{\glstable@parcase}[3]{##1}%
  \or
    \renewcommand{\glstable@parcase}[3]{##2}%
  \or
    \renewcommand{\glstable@parcase}[3]{##3}%
  \fi
}
```

`\glstable@parcase`

```
\newcommand{\glstable@parcase}[3]{#1}
```

`\glstableifpar`

```
\newcommand{\glstableifpar}[1]{\glstable@parcase{}{#1}{#1}}
```

`\glstableleftalign`

```
\newcommand{\glstableleftalign}[1]{%
\glstable@parcase{l}{p{#1}}{>{\protect\raggedright}p{#1}}%
}
```

`\glstablerightalign`

```
\newcommand{\glstablerightalign}[1]{%
\glstable@parcase{r}{p{#1}}{>{\protect\raggedleft}p{#1}}%
}
```

`\glstablecenteralign`

```
\newcommand{\glstablecenteralign}[1]{%
\glstable@parcase{c}{p{#1}}{>{\protect\centering}p{#1}}%
}
```

`\glstablenamecolalign` The alignment for the name column.

```
\newcommand{\glstablenamecolalign}{\glstableleftalign{\glstablenamewidth}}
```

`\glstabledesccolalign` The alignment for the description column.

```
\newcommand{\glstabledesccolalign}{\glstableleftalign{\glstabledesccolwidth}}
```

`\glstableothercolalign` The alignment for the description column.

```
\newcommand{\glstableothercolalign}{\glstableleftalign{\glstableotherwidth}}
```

`\glstablesymbolcolalign` The alignment for the symbol column.

```
\newcommand{\glstablesymbolcolalign}{\glstablecenteralign{\glstablesymbolwidth}}
```

```

\glstableNameTarget
    \newcommand{\glstableNameTarget}[1]{%
        \glstarget{#1}{\glstableName{#1}}%
    }

\glstableNameFmt
    \newcommand{\glstableNameFmt}[1]{#1}

\glstableName Entry item needs to be included in measuring to ensure there's enough room
for it as well.
    \newcommand{\glstableName}[1]{%
        \glentryitem{#1}%
        \glstableNameFmt{\glossentryname{#1}}%
    }

\glstableSubNameTarget
    \newcommand{\glstableSubNameTarget}[1]{%
        \glstarget{#1}{\glstableSubName{#1}}%
    }

\glstableSubNameFmt
    \newcommand{\glstableSubNameFmt}[1]{#1}

\glstableSubName
    \newcommand{\glstableSubName}[1]{%
        \glssubentryitem{#1}%
        \glstableSubNameFmt{\glossentryname{#1}}%
    }

\glstableotherfield
    \newcommand{\glstableotherfield}{}

\glstableifhasotherfield
    \newcommand{\glstableifhasotherfield}[3]{%
        \ifdefvoid\glstableotherfield
        {#3}%
        {%
            \ifglstablevoid{\glstableotherfield}{#1}{#3}{#2}%
        }%
    }

    Add an extra key to allow this value to be changed.
    \define@key{printglosstable}{other}{\renewcommand{\glstableotherfield}{#1}}

\glstableOther
    \newcommand{\glstableOther}[1]{%
        \glstableOtherFmt{\glstableotherfield{#1}}%
    }

\glstableOtherFmt
    \newcommand{\glstableOtherFmt}[1]{#1}

```

```

\glstableSubOther
\newcommand{\glstableSubOther}[1]{\glstableOther{#1}}

\glstableOtherWithSep
\newcommand{\glstableOtherWithSep}[3]{%
\glstableifhasotherfield{#2}%
{#1\glstableOther{#2}#3}%
}%

\glstableSubOtherWithSep
\newcommand{\glstableSubOtherWithSep}[3]{%
\glstableifhasotherfield{#2}%
{#1\glstableSubOther{#2}#3}%
}%

\glstableNameSingleFmt
\newcommand{\glstableNameSingleFmt}[1]{%
\glstableNameTarget{#1}%
\ifglshasdesc{#1}%
{%
Has description.
\glstableNameSinglePostName
\glstableNameSingleSuppl
{%
\ifglshassymbol{#1}%
{\glstableSymbol{#1}\glstableNameSingleSymSep}%
}%
\glstableOtherWithSep{}{#1}{\glstableOtherSep}%
\glstableDesc{#1}%
}%
}%
}%

No description.
\ifglshassymbol{#1}%
{%
Has symbol
\glstableNameSinglePostName
\glstableNameSingleSuppl
{%
\glstableSymbol{#1}%
\glstableifhasotherfield{#1}%
}%
}

```

```

\glstableNameSingleSymSep\glstableOther{#1}%
}%
{}%
}%
}%
{}%

```

No description or symbol.

```

\glstableifhasotherfield{#1}%
{}%

```

Has other but no description or symbol

```

\glstableNameSinglePostName
\glstableNameSingleSuppl{\glstableOther{#1}}%
}%
{}%

```

No description, symbol or other.

```

}%
}%
}%
}

```

\glstableNameSingleSuppl

```

\newcommand{\glstableNameSingleSuppl}[1]{(#1)}

```

\glstableNameSinglePostName

```

\newcommand{\glstableNameSinglePostName}{ }

```

\glstableNameSingleSymSep

```

\newcommand{\glstableNameSingleSymSep}{ }

```

\glstableOtherSep

```

\newcommand{\glstableOtherSep}{, }

```

\glstableSubOtherSep

```

\newcommand{\glstableSubOtherSep}{\glstableOtherSep}

```

\glstableSubDescSep

```

\newcommand{\glstableSubDescSep}{\glstableSubOtherSep}

```

\glstableSubNameSingleFmt

```

\newcommand{\glstableSubNameSingleFmt}[1]{%
\glstableSubNameTarget{#1}%

\ifglshasdesc{#1}%
{}%

\ifglshassymbol{#1}%
{}%
\glstableifhasotherfield{#1}%
{}%
}

```

Description, symbol and other

```
\glstableNameSinglePostSubName
\glstableNameSingleSubSuppl
{%
  \glstableSubSymbol{#1}%
  \glstableNameSingleSymSep
  \glstableSubOtherWithSep{#{1}}{\glstableSubOtherSep}%
  \glstableSubDesc{#1}%
}%
}%
{%
```

Description and symbol but no other.

```
\glstableNameSinglePostSubName
\glstableNameSingleSubSuppl
{%
  \glstableSubSymbol{#1}%
  \glstableNameSingleSymSep
  \glstableSubDesc{#1}%
}%
}%
}%
{%
```

Description but no symbol.

```
\glstableNameSinglePostSubName
\glstableNameSingleSubSuppl
{%
  \glstableSubOtherWithSep{#{1}}{\glstableSubOtherSep}%
  \glstableSubDesc{#1}%
}%
}%
}%
{%
```

No description.

```
\ifglshassymbol{#1}%
{%
```

No description but has symbol.

```
\glstableNameSinglePostSubName
\glstableNameSingleSubSuppl
{%
  \glstableifhasotherfield{#1}%
  {%
```

No description, but has symbol and other.

```
\glstableSubSymbol{#1}\glstableNameSingleSymSep
\glstableSubOther{#1}%
}%
{%
```


No description or other but has symbol.

```

\glstableSubSymbol{#1}%
}%
}%
}%
{%
\glstableifhasotherfield{#1}%
{%

```

No description or symbol but has other.

```

\glstableNameSinglePostSubName
\glstableNameSingleSubSuppl{\glstableSubOther{#1}}%
}%
{%

```

No description, symbol or other.

```

}%
}%
}%
}

```

\glstableNameSingleSubSuppl

```

\newcommand{\glstableNameSingleSubSuppl}[1]{#1}

```

\glstableNameSinglePostSubName

```

\newcommand{\glstableNameSinglePostSubName}{ }

```

\glstableSubSep

```

\newcommand{\glstableSubSep}{\space}

```

\glstableSubNameSep

```

\newcommand{\glstableSubNameSep}{}

```

\glstableNameNoDesc

```

\newcommand{\glstableNameNoDesc}[1]{%
\glstableNameTarget{#1}%
\glstableOtherWithSep{\glstableSubNameSep}{##1}{}%
}

```

\glstableSubNameNoDesc

```

\newcommand{\glstableSubNameNoDesc}[1]{%
\glstableSubNameTarget{#1}%
\glstableSubOtherWithSep{\glstableSubNameSep}{#1}{}%
}

```

\glstableSubNameSymbolNoDesc

```

\newcommand{\glstableSubNameSymbolNoDesc}[1]{%
\glstableSubNameTarget{#1}%
\glstableifhasotherfield{#1}%
}

```

```

        {%
        \glstableSubOther{#1}%
        \ifglshassymbol{#1}%
        {\glstableSubOtherSep\glstableSubSymbol{#1}}%
        {}%
        }%
        {%
        \ifglshassymbol{#1}%
        {\glstableSubSymbol{#1}}%
        {}%
        }%
    }

\glstableSymbolFmt
\newcommand{\glstableSymbolFmt}[1]{#1}

\glstableSymbol
\newcommand{\glstableSymbol}[1]{\glstableSymbolFmt{\glossentrysymbol{#1}}}

\glstableSubSymbolFmt
\newcommand{\glstableSubSymbolFmt}[1]{\glstableSymbolFmt{#1}}

\glstableSubSymbol
\newcommand{\glstableSubSymbol}[1]{\glstableSubSymbolFmt{\glossentrysymbol{#1}}}

\glstableSubSymbolWithSep
\newcommand{\glstableSubSymbolWithSep}[3]{%
\ifglshassymbol{#2}%
{#1\glstableSubSymbol{#2}#3}%
}%

\glstableSymbolNameTarget Where the symbol takes place of the name.
\newcommand{\glstableSymbolNameTarget}[1]{%
\glstarget{#1}{\glstableSymbolName{#1}}%
}

\glstableSymbolNameFmt
\newcommand{\glstableSymbolNameFmt}[1]{%
\glstableSymbolFmt{#1}%
}

\glstableSymbolName
\newcommand{\glstableSymbolName}[1]{%
\glstentryitem{#1}\glstableSymbolNameFmt{\glossentrysymbol{#1}}%
}

```

```

\glstableSubSymbolNameTarget Where the symbol takes place of the name.
    \newcommand{\glstableSubSymbolNameTarget}[1]{%
    \glstarget{#1}{\glstableSubSymbolName{#1}}%
    }

\glstableSubSymbolNameFmt
    \newcommand{\glstableSubSymbolNameFmt}[1]{

\glstableSubSymbolName
    \newcommand{\glstableSubSymbolName}[1]{%
    \glssubentryitem{#1}\glstableSubSymbolNameFmt{\glossentrysymbol{#1}}%
    }

    \glstableDesc
    \newcommand{\glstableDesc}[1]{%
    \glstableDescFmt{\glossentrydesc{#1}\glspostdescription}%
    }

    \glstableDescFmt
    \newcommand{\glstableDescFmt}[1]{#1}

\glstableDescWithOther
    \newcommand{\glstableDescWithOther}[1]{%
    \glstableifhasotherfield{#1}%
    {%
    \glstableOther{#1}%
    \ifglshasdesc{#1}{\glstableOtherSep\glstableDesc{#1}}{}}%
    }%
    {%
    \ifglshasdesc{#1}{\glstableDesc{#1}}{}}%
    }%
    }

\glstableSubDescFmt
    \newcommand{\glstableSubDescFmt}[1]{\glstableDescFmt{#1}}

\glstableSubDesc
    \newcommand{\glstableSubDesc}[1]{%
    \glstableSubDescFmt{\glossentrydesc{#1}\glspostdescription}%
    }

\glstableSubDescWithOther
    \newcommand{\glstableSubDescWithOther}[1]{\glstableDescWithOther{#1}}

\glstableSubDescSymbolOther
    \newcommand{\glstableSubDescSymbolOther}[1]{%
    \ifglshasdesc{#1}%
    {%

```

```

\glstableSubDesc{#1}%
\ifglshassymbol{#1}%
{%
  \glstableSubDescSep
  \glstableSubSymbol{#1}%
  \glstableSubOtherWithSep{\glstableSubSep}{#1}{}%
}%
{%
  \glstableSubOtherWithSep{\glstableSubOtherSep}{#1}{}%
}%
}%
{%
  \ifglshassymbol{#1}%
  {%
    \glstableSubSymbol{#1}%
    \glstableSubOtherWithSep{\glstableSubSep}{#1}{}%
  }%
  {\glstableSubOther{#1}}%
}%
}

\glstableOtherNoDesc
\newcommand{\glstableOtherNoDesc}[1]{%
  \glstableOtherIfSet{#1}%
}

\glstableOtherIfSet
\newcommand{\glstableOtherIfSet}[1]{%
  \glstableifhasotherfield{#1}{\glstableOther{#1}}{}%
}

\glstableSubOtherNoDesc
\newcommand{\glstableSubOtherNoDesc}[1]{%
  \glstableOtherNoDesc{#1}%
}

\glstableSubOtherIfSet
\newcommand{\glstableSubOtherIfSet}[1]{%
  \glstableOtherIfSet{#1}%
}

\glstableHeaderFmt
\newcommand{\glstableHeaderFmt}[1]{\textbf{#1}}

\define@key{printglosstable}{block-style}
{\glstablesetstyle{#1}}

\glstablecolsperblock Number of columns per block (entry). Assigned by block style.
\newcount\glstablecolsperblock
\glstablecolsperblock=2\relax

```

`\glstableblockheader` The column header, which may cover multiple columns. Redefined by block style.

```
\newcommand{\glstableblockheader}{}

\glstableblockalign The column alignment specs for the block. Redefined by the block style.
\newcommand{\glstableblockalign}{}

\glstableblockentry The entry item, which may cover multiple columns. Redefined by block style.
\newcommand{\glstableblockentry}[1]{}

\glstableblocksubentry The sub-entry is in a single column of the block (requires children to be saved)
Redefined by block style.
\newcommand{\glstableblocksubentry}[1]{}

\glstableinitlengthupdates Block style command.
\newcommand{\glstableinitlengthupdates}{}

\glstablelengthupdate Block style command.
\newcommand{\glstablelengthupdate}[1]{}

\glstablefinishlengthupdates Block style command.
\newcommand{\glstablefinishlengthupdates}{}

\glstablesetstyle
\newcommand{\glstablesetstyle}[1]{%
  \ifcsdef{@glstable@style@#1}%
    {\csuse{@glstable@style@#1}}%
    {\PackageError{glossary-table}{Unknown style ‘#1’}{}%
  }

\glstablenewstyle
\newcommand{\glstablenewstyle}[2]{%
  \ifcsdef{@glstable@style@#1}%
    {\PackageError{glossary-table}{style ‘#1’ already defined}{}%
    {\csdef{@glstable@style@#1}{#2}}%
  }

  Provide some common layouts.

name-desc
\glstablenewstyle{name-desc}{%
2 columns per block (name, description).
\glstablecolsperblock=2\relax
```

Initialise length registers (need to calculate max name width if par align).

```
\renewcommand{\glstableinitlengthupdates}{%
  \ifKV@printglosstable@header
    \glsmasurewidth{\glstablenamewidth}%
    {\glstableHeaderFmt\glstablenameheader}%
  \else
    \setlength{\glstablenamewidth}{0pt}%
  \fi
  \setlength{\glstabledescwidth}{0pt}%
}%
```

Update width in unsrt hook.

```
\renewcommand{\glstablelengthupdate}[1]{%
  \glstablemeasureandupdate{\glstablenamewidth}{\glstableName{##1}}%
}%
```

Finally set the description width to the remaining available.

```
\renewcommand{\glstablefinishlengthupdates}{%
  \setlength{\glstabledescwidth}{\dimexpr\glstableblockwidth
    - \glstablenamewidth}%
  \ifdim\glstabledescwidth<0pt\relax
    \setlength{\glstablenamewidth}{\dimexpr0.5\glstableblockwidth}%
    \setlength{\glstabledescwidth}{\glstablenamewidth}%
  \fi
}%
```

How to format the top-level entry in the block.

```
\renewcommand{\glstableblockentry}[1]{%
  \glstableNameTarget{##1} &
  \glstableDescWithOther{##1}%
  \glstableChildEntries{##1}%
}%
```

How to format the entry's children.

```
\renewcommand{\glstableblocksubentry}[1]{%
  \glstableSubNameTarget{##1}\glstableSubNameSep
  \glstableSubDescWithOther{##1}%
}%
```

Available width for child entries.

```
\renewcommand{\glstablesubentrywidth}{\glstabledescwidth}
```

How to format the block's header row, if required.

```
\renewcommand{\glstableblockheader}{%
  \glstableHeaderFmt\glstablenameheader &
  \glstableHeaderFmt\glstabledescheader}%
```

Set the block's column alignments.

```
\renewcommand{\glstableblockalign}{\glstablenamecolalign\glstabledesccolalign}%
}
```

Set the default style.

```
\glstablesetstyle{name-desc}
```

`\glstablenewstyle{name}{%`
1 columns per block (name optionally with symbol and description).
`\glstablecolspanblock=1\relax`
Initialise length registers (no calculation required, column width same as block width).
`\renewcommand{\glstableinitlengthupdates}{}%`
No measuring required.
`\renewcommand{\glstablelengthupdate}[1]{}%`
Set the name width to the amount available.
`\renewcommand{\glstablefinishlengthupdates}{%`
`\setlength{\glstablenamewidth}{\glstableblockwidth}%`
`}%`
How to format the top-level entry in the block.
`\renewcommand{\glstableblockentry}[1]{%`
`\glstableNameSingleFmt{##1}%`
`\glstableChildEntries{##1}%`
`}%`
How to format the entry's children.
`\renewcommand{\glstableblocksubentry}[1]{%`
`\glstableSubNameSingleFmt{##1}%`
Available width for child entries.
`\renewcommand{\glstablesubentrywidth}{\glstableblockwidth}`
How to format the block's header row, if required.
`\renewcommand{\glstableblockheader}{%`
`\glstableHeaderFmt\glstablenameheader}%`
Set the block's column alignments.
`\renewcommand{\glstableblockalign}{\glstablenamecolalign}%`
`}`

```

\glstablerenewstyle{name-symbol}{%
2 columns per block (name and symbol).

\glstablecolsperblock=2\relax

Initialise length registers (need to calculate max symbol width if par align).
This assumes the symbol requires the minimal width and any leftover can be
assigned to the name.

\renewcommand{\glstableinitlengthupdates}{%
\ifKV@printglosstable@header
\glsmesurewidth{\glstablesymbolwidth}%
{\glstableHeaderFmt\glstablesymbolheader}%
\else

```

```

        \setlength{\glstablesymbolwidth}{0pt}%
    \fi
    \setlength{\glstablenamewidth}{0pt}%
}%

```

Update widths in unsrt hook.

```

\renewcommand{\glstablelengthupdate}[1]{%
    \glstablemeasureandupdate{\glstablesymbolwidth}{\glstableSymbol{##1}}%
}%

```

Finally set the name width to the remaining available.

```

\renewcommand{\glstablefinishlengthupdates}{%
    \setlength{\glstablenamewidth}{\dimexpr\glstableblockwidth
    - \glstablesymbolwidth}%
    \ifdim\glstablenamewidth<0pt\relax
        \setlength{\glstablenamewidth}{\dimexpr0.5\glstableblockwidth}%
        \setlength{\glstablesymbolwidth}{\glstablenamewidth}%
    \fi
}%

```

How to format the top-level entry in the block. v1.50 child entries now in name column.

```

\renewcommand{\glstableblockentry}[1]{%
    \glstableNameNoDesc{##1}%
    \glstableChildEntries{##1}%
    & \glstableSymbol{##1}%
}

```

How to format the entry's children.

```

\renewcommand{\glstableblocksubentry}[1]{%
    \glstableSubNameSymbolNoDesc{##1}%
}

```

Available width for child entries.

```

\renewcommand{\glstablesubentrywidth}{\glstablenamewidth}

```

How to format the block's header row, if required.

```

\renewcommand{\glstableblockheader}{%
    \glstableHeaderFmt\glstablenameheader &
    \glstableHeaderFmt\glstablesymbolheader}%

```

Set the block's column alignments.

```

\renewcommand{\glstableblockalign}{\glstablenamecolalign\glstablesymbolcolalign}%
}

```

desc-name

```

\glstableneverstyle{desc-name}{%

```

2 columns per block (description, name).

```

\glstablecolsperblock=2\relax

```

Initialise length registers (need to calculate max name width if par align).

```

\renewcommand{\glstableinitlengthupdates}{%
    \ifKV@printglosstable@header
        \glstablemeasurewidth{\glstablenamewidth}%
    }
}

```



```

        {\glstableHeaderFmt\glstablenameheader}%
    \else
        \setlength{\glstablenamewidth}{0pt}%
    \fi
    \setlength{\glstabledescwidth}{0pt}%
}%

```

Update width in unsrt hook.

```

\renewcommand{\glstablelengthupdate}[1]{%
    \glstablemeasureandupdate{\glstablenamewidth}{\glstableName{##1}}%
}%

```

Finally set the description width to the remaining available.

```

\renewcommand{\glstablefinishlengthupdates}{%
    \setlength{\glstabledescwidth}{\dimexpr\glstableblockwidth
    - \glstablenamewidth}%
    \ifdim\glstabledescwidth<0pt\relax
        \setlength{\glstablenamewidth}{\dimexpr0.5\glstableblockwidth}%
        \setlength{\glstabledescwidth}{\glstablenamewidth}%
    \fi
}%

```

How to format the top-level entry in the block. v1.50 child entries now in description column

```

\renewcommand{\glstableblockentry}[1]{%
    \glstableDescWithOther{##1}%
    \glstableChildEntries{##1}%
    &
    \glstableNameTarget{##1}%
}%

```

How to format the entry's children.

```

\renewcommand{\glstableblocksubentry}[1]{%
    \glstableSubDescWithOther{##1}\glstableSubNameSep
    \glstableSubNameTarget{##1}%
}%

```

Available width for child entries.

```

\renewcommand{\glstablesubentrywidth}{\glstabledescwidth}

```

How to format the block's header row, if required.

```

\renewcommand{\glstableblockheader}{%
    \glstableHeaderFmt\glstabledescheader &
    \glstableHeaderFmt\glstablenameheader
}%

```

Set the block's column alignments.

```

\renewcommand{\glstableblockalign}{\glstabledesccolalign\glstablenamecolalign}%
}

```

symbol-name

```

\glstablenustyle{symbol-name}{%

```

2 columns per block (symbol, name).

```
\glstablecolsperblock=2\relax
```

Initialise length registers (need to calculate max symbol width if par align).

```
\renewcommand{\glstableinitlengthupdates}{%
  \ifKV@printglosstable@header
    \glsmasurewidth{\glstablesymbolwidth}%
    {\glstableHeaderFmt\glstablesymbolheader}%
  \else
    \setlength{\glstablesymbolwidth}{0pt}%
  \fi
  \setlength{\glstablenamewidth}{0pt}%
}%
```

Update widths in unsrt hook.

```
\renewcommand{\glstablelengthupdate}[1]{%
  \glstablemeasureandupdate{\glstablesymbolwidth}{\glstableSymbol{##1}}%
}%
```

Finally set the name width to the remaining available.

```
\renewcommand{\glstablefinishlengthupdates}{%
  \setlength{\glstablenamewidth}{\dimexpr\glstableblockwidth
    - \glstablesymbolwidth}%
  \ifdim\glstablenamewidth<0pt\relax
    \setlength{\glstablenamewidth}{\dimexpr0.5\glstableblockwidth}%
    \setlength{\glstablesymbolwidth}{\glstablenamewidth}%
  \fi
}%
```

How to format the top-level entry in the block.

```
\renewcommand{\glstableblockentry}[1]{%
  \glstableSymbol{##1} &
  \glstableNameNoDesc{##1}%
  \glstableChildEntries{##1}%
%
}%
```

How to format the entry's children.

```
\renewcommand{\glstableblocksubentry}[1]{%
  \glstableSubSymbolWithSep{##1}{\glstableSubSep}%
  \glstableSubNameNoDesc{##1}%
}%
```

Available width for child entries.

```
\renewcommand{\glstablesubentrywidth}{\glstablenamewidth}
```

How to format the block's header row, if required.

```
\renewcommand{\glstableblockheader}{%
  \glstableHeaderFmt\glstablesymbolheader &
  \glstableHeaderFmt\glstablenameheader
}%
```

Set the block's column alignments.

```
\renewcommand{\glstableblockalign}{\glstablesymbolcolalign\glstablenamecolalign}%
}
```

name-symbol-desc

```
\glstablenuwstyle{name-symbol-desc}{%
```

3 columns per block (name, symbol, description).

```
\glstablecolsperblock=3\relax
```

Initialise length registers (need to calculate max name and symbol widths if par align).

```
\renewcommand{\glstableinitlengthupdates}{%
\ifKV@printglosstable@header
\glsmesurewidth{\glstablenuwwidth}%
{\glstableHeaderFmt\glstablenuwheader}%
\glsmesurewidth{\glstablesymbolwidth}%
{\glstableHeaderFmt\glstablesymbolheader}%
\else
\setlength{\glstablenuwwidth}{0pt}%
\setlength{\glstablesymbolwidth}{0pt}%
\fi
\setlength{\glstabledescwidth}{0pt}%
}%
```

Update widths in unsrt hook.

```
\renewcommand{\glstablelengthupdate}[1]{%
\glstablemeasureandupdate{\glstablenuwwidth}{\glstableName{##1}}%
\glstablemeasureandupdate{\glstablesymbolwidth}{\glstableSymbol{##1}}%
}%
```

Finally set the description width to the remaining available.

```
\renewcommand{\glstablefinishlengthupdates}{%
\setlength{\glstabledescwidth}{\dimexpr\glstableblockwidth
- \glstablesymbolwidth - \glstablenuwwidth}%
\ifdim\glstabledescwidth<0pt\relax
\setlength{\glstablenuwwidth}{\dimexpr0.5\glstableblockwidth
- 0.5\glstablesymbolwidth}%
\setlength{\glstabledescwidth}{\glstablenuwwidth}%
\fi
}%
```

How to format the top-level entry in the block.

```
\renewcommand{\glstableblockentry}[1]{%
\glstableNameTarget{##1} &
\glstableSymbol{##1} &
\glstableDescWithOther{##1}%
\glstableChildEntries{##1}%
}%
```

How to format the entry's children.

```
\renewcommand{\glstableblocksubentry}[1]{%
```

```

\glstableSubNameTarget{##1}\glstableSubNameSep
\glstableSubSymbolWithSep{##1}\glstableSubSep}%
\glstableSubDescWithOther{##1}%
}%

```

Available width for child entries.

```

\renewcommand{\glstabsubentrywidth}{\glstabdescwidth}

```

How to format the block's header row, if required.

```

\renewcommand{\glstableblockheader}{%
\glstableHeaderFmt\glstablenameheader &
\glstableHeaderFmt\glstablesymbolheader &
\glstableHeaderFmt\glstabledescheader}%

```

Set the block's column alignments.

```

\renewcommand{\glstableblockalign}{%
\glstablenamecolalign\glstablesymbolcolalign\glstabledesccolalign}%
}

```

name-other-desc

```

\glstablenewstyle{name-other-desc}{%

```

3 columns per block (name, other, description).

```

\glstablecolsperblock=3\relax

```

Initialise length registers (need to calculate max name and other widths if par align).

```

\renewcommand{\glstableinitlengthupdates}{%
\ifKV@printglosstable@header
\glsmesurewidth{\glstablenamewidth}%
{\glstableHeaderFmt\glstablenameheader}%
\glsmesurewidth{\glstableotherwidth}%
{\glstableHeaderFmt\glstableotherheader}%
\else
\setlength{\glstablenamewidth}{0pt}%
\setlength{\glstableotherwidth}{0pt}%
\fi
\setlength{\glstabledesccolalign}{0pt}%
}%

```

Update widths in unsrt hook.

```

\renewcommand{\glstablelengthupdate}[1]{%
\glstablemeasureandupdate{\glstablenamewidth}{\glstableName{##1}}%
\glstablemeasureandupdate{\glstableotherwidth}{\glstableOther{##1}}%
}%

```

Finally set the description width to the remaining available.

```

\renewcommand{\glstablefinishlengthupdates}{%
\setlength{\glstabledesccolalign}{\dimexpr\glstableblockwidth
- \glstableotherwidth - \glstablenamewidth}%
\ifdim\glstabledesccolalign<0pt\relax
\setlength{\glstablenamewidth}{\dimexpr0.5\glstableblockwidth

```

```

- 0.5\glstableotherwidth}%
\setlength{\glstabledescwidth}{\glstablenamewidth}%
\fi
}%

```

How to format the top-level entry in the block.

```

\renewcommand{\glstableblockentry}[1]{%
\glstableNameTarget{##1} &
\glstableOther{##1} &
\glstableDesc{##1}%
\glstableChildEntries{##1}%
}%

```

How to format the entry's children.

```

\renewcommand{\glstableblocksubentry}[1]{%
\glstableSubNameTarget{##1}\glstableSubNameSep
\glstableSubOtherWithSep{##1}{\glstableSubOtherSep}%
\glstableSubDesc{##1}%
}%

```

Available width for child entries.

```

\renewcommand{\glstablesubentrywidth}{\glstabledescwidth}

```

How to format the block's header row, if required.

```

\renewcommand{\glstableblockheader}{%
\glstableHeaderFmt\glstablenameheader &
\glstableHeaderFmt\glstableotherheader &
\glstableHeaderFmt\glstabledescheader}%

```

Set the block's column alignments.

```

\renewcommand{\glstableblockalign}{%
\glstablenamecolalign\glstableothercolalign\glstabledesccolalign}%
}

```

desc-other-name As name-other-desc but with the end columns switched.

```

\glstablenuwstyle{desc-other-name}{%
\glstablesetstyle{name-other-desc}%
}

```

How to format the top-level entry in the block.

```

\renewcommand{\glstableblockentry}[1]{%
\glstableDesc{##1}%
\glstableChildEntries{##1} &
\glstableOther{##1} &
\glstableNameTarget{##1}%
}%

```

How to format the entry's children.

```

\renewcommand{\glstableblocksubentry}[1]{%
\glstableSubDesc{##1}%
\glstableSubOtherWithSep\glstableSubOtherSep{##1}{}%
\glstableSubNameSep
\glstableSubNameTarget{##1}%
}%

```

How to format the block's header row, if required.

```
\renewcommand{\glstableblockheader}{%
  \glstableHeaderFmt\glstabledescheader &
  \glstableHeaderFmt\glstableotherheader &
  \glstableHeaderFmt\glstablenameheader
}%
```

Set the block's column alignments.

```
\renewcommand{\glstableblockalign}{%
  \glstabledesccolalign
  \glstableothercolalign
  \glstablenamecolalign
}%
}
```

name-symbol-other-desc

```
\glstablenewstyle{name-symbol-other-desc}{%
```

4 columns per block (name, symbol, other, description).

```
\glstablecolspersblock=4\relax
```

Initialise length registers (need to calculate max name, symbol and other widths if par align).

```
\renewcommand{\glstableinitlengthupdates}{%
  \ifKV@printglosstable@header
    \glsmasurewidth{\glstablenamewidth}%
    {\glstableHeaderFmt\glstablenameheader}%
    \glsmasurewidth{\glstablesymbolwidth}%
    {\glstableHeaderFmt\glstablesymbolheader}%
    \glsmasurewidth{\glstableotherwidth}%
    {\glstableHeaderFmt\glstableotherheader}%
  \else
    \setlength{\glstablenamewidth}{0pt}%
    \setlength{\glstablesymbolwidth}{0pt}%
    \setlength{\glstableotherwidth}{0pt}%
  \fi
  \setlength{\glstabledescwidth}{0pt}%
}%
```

Update widths in unsrt hook.

```
\renewcommand{\glstablelengthupdate}[1]{%
  \glstablemeasureandupdate{\glstablenamewidth}{\glstableName{##1}}%
  \glstablemeasureandupdate{\glstablesymbolwidth}{\glstableSymbol{##1}}%
  \glstablemeasureandupdate{\glstableotherwidth}{\glstableOther{##1}}%
}%
```

Finally set the description width to the remaining available.

```
\renewcommand{\glstablefinishlengthupdates}{%
  \setlength{\glstabledescwidth}{\dimexpr\glstableblockwidth
    - \glstablesymbolwidth - \glstablenamewidth - \glstableotherwidth}%
  \ifdim\glstabledescwidth<0pt\relax
```

Not enough room so balance them out evenly.

```

\setlength{\glstablenamewidth}{\dimexpr0.25\glstableblockwidth}%
\setlength{\glstablesymbolwidth}{\glstablenamewidth}%
\setlength{\glstableotherwidth}{\glstablenamewidth}%
\setlength{\glstabledescwidth}{\glstablenamewidth}%
\fi
}%

```

How to format the top-level entry in the block.

```

\renewcommand{\glstableblockentry}[1]{%
\glstableNameTarget{##1} &
\glstableSymbol{##1} &
\glstableOther{##1} &
\glstableDesc{##1}%
\glstableChildEntries{##1}%
}%

```

How to format the entry's children.

```

\renewcommand{\glstableblocksubentry}[1]{%
\glstableSubNameTarget{##1}\glstableSubNameSep
\glstableSubSymbolWithSep{}{##1}{\glstableSubSep}%
\glstableSubOtherWithSep{}{##1}{\glstableSubOtherSep}%
\glstableSubDesc{##1}%
}

```

Available width for child entries.

```

\renewcommand{\glstablesubentrywidth}{\glstabledescwidth}

```

How to format the block's header row, if required.

```

\renewcommand{\glstableblockheader}{%
\glstableHeaderFmt\glstablenameheader &
\glstableHeaderFmt\glstablesymbolheader &
\glstableHeaderFmt\glstableotherheader &
\glstableHeaderFmt\glstabledescheader}%

```

Set the block's column alignments.

```

\renewcommand{\glstableblockalign}{%
\glstablenamecolalign
\glstablesymbolcolalign
\glstableothercolalign
\glstabledesccolalign}%
}

```

name-desc-symbol

```

\glstableneverstyle{name-desc-symbol}{%

```

3 columns per block (name, description, symbol).

```

\glstablecolsperblock=3\relax

```

Initialise length registers (need to calculate max name and symbol widths if par align).

```

\renewcommand{\glstableinitlengthupdates}{%
\ifKV@printglosstable@header

```

```

\glsmasurewidth{\glstabilenamewidth}%
  {\glstableHeaderFmt\glstabilenameheader}%
\glsmasurewidth{\glstablesymbolwidth}%
  {\glstableHeaderFmt\glstablesymbolheader}%
\else
  \setlength{\glstabilenamewidth}{0pt}%
  \setlength{\glstablesymbolwidth}{0pt}%
\fi
\setlength{\glstabledescwidth}{0pt}%
}%

```

Update widths in unsrt hook.

```

\renewcommand{\glstablelengthupdate}[1]{%
  \glstablemeasureandupdate{\glstabilenamewidth}{\glstableName{##1}}%
  \glstablemeasureandupdate{\glstablesymbolwidth}{\glstableSymbol{##1}}%
}%

```

Finally set the description width to the remaining available.

```

\renewcommand{\glstablefinishlengthupdates}{%
  \setlength{\glstabledescwidth}{\dimexpr\glstableblockwidth
    - \glstablesymbolwidth - \glstabilenamewidth}%
  \ifdim\glstabledescwidth<0pt\relax
    \setlength{\glstabilenamewidth}{\dimexpr0.5\glstableblockwidth
      - 0.5\glstablesymbolwidth}%
    \setlength{\glstabledescwidth}{\glstabilenamewidth}%
  \fi
}%

```

How to format the top-level entry in the block. v1.50 child entries in description column.

```

\renewcommand{\glstableblockentry}[1]{%
  \glstableNameTarget{##1} &
  \glstableDescWithOther{##1}%
  \glstableChildEntries{##1}%
  &
  \glstableSymbol{##1}%
}%

```

How to format the entry's children.

```

\renewcommand{\glstableblocksubentry}[1]{%
  \glstableSubNameTarget{##1}\glstableSubNameSep
  \glstableSubDescWithOther{##1}%
  \glstableSubSymbolWithSep{\glstableSubSep}{##1}{}%
}%

```

Available width for child entries.

```

\renewcommand{\glstablesubentrywidth}{\glstabledescwidth}

```

How to format the block's header row, if required.

```

\renewcommand{\glstableblockheader}{%
  \glstableHeaderFmt\glstabilenameheader &
  \glstableHeaderFmt\glstabledescheader &
}

```



```

\glstableHeaderFmt\glstablesymbolheader
}%

```

Set the block's column alignments.

```

\renewcommand{\glstableblockalign}{%
\glstablenamecolalign\glstabledesccolalign\glstablesymbolcolalign}%
}

```

desc-symbol-other-name As name-symbol-other-desc but with the end columns switched.

```

\glstablenustyle{desc-symbol-other-name}{%
\glstablesetstyle{name-symbol-other-desc}%

```

How to format the top-level entry in the block.

```

\renewcommand{\glstableblockentry}[1]{%
\glstableDesc{##1}%
\glstableChildEntries{##1} &
\glstableSymbol{##1} &
\glstableOther{##1} &
\glstableNameTarget{##1}%
}%

```

How to format the entry's children.

```

\renewcommand{\glstableblocksubentry}[1]{%
\glstableSubDescSymbolOther{##1}%
\glstableSubNameSep
\glstableSubNameTarget{##1}%
}%

```

How to format the block's header row, if required.

```

\renewcommand{\glstableblockheader}{%
\glstableHeaderFmt\glstabledescheader &
\glstableHeaderFmt\glstablesymbolheader &
\glstableHeaderFmt\glstableotherheader &
\glstableHeaderFmt\glstablenameheader
}%

```

Set the block's column alignments.

```

\renewcommand{\glstableblockalign}{%
\glstabledesccolalign
\glstablesymbolcolalign
\glstableothercolalign
\glstablenamecolalign
}%
}

```

desc-other-symbol-name As name-symbol-other-desc but column order is description, other, symbol and name.

```

\glstablenustyle{desc-other-symbol-name}{%
\glstablesetstyle{name-symbol-other-desc}%

```

How to format the top-level entry in the block.

```
\renewcommand{\glstableblockentry}[1]{%
  \glstableDesc{##1}%
  \glstableChildEntries{##1} &
  \glstableOther{##1} &
  \glstableSymbol{##1} &
  \glstableNameTarget{##1}%
}%
```

How to format the entry's children.

```
\renewcommand{\glstableblocksubentry}[1]{%
  \glstableSubDesc{##1}%
  \glstableSubOtherWithSep{\glstableSubOtherSep}{##1}{}%
  \glstableSubSymbolWithSep{\glstableSubSep}{##1}{}%
  \glstableSubNameSep
  \glstableSubNameTarget{##1}%
}%
```

How to format the block's header row, if required.

```
\renewcommand{\glstableblockheader}{%
  \glstableHeaderFmt\glstabledescheader &
  \glstableHeaderFmt\glstableotherheader &
  \glstableHeaderFmt\glstablesymbolheader &
  \glstableHeaderFmt\glstablenameheader
}%
```

Set the block's column alignments.

```
\renewcommand{\glstableblockalign}{%
  \glstabledesccolalign
  \glstableothercolalign
  \glstablesymbolcolalign
  \glstablenamecolalign
}%
}
```

name-other-symbol-desc As name-symbol-other-desc but column order is name, other, symbol and description.

```
\glstablenustyle{name-other-symbol-desc}{%
  \glstablesetstyle{name-symbol-other-desc}%
}
```

How to format the top-level entry in the block.

```
\renewcommand{\glstableblockentry}[1]{%
  \glstableNameTarget{##1} &
  \glstableOther{##1} &
  \glstableSymbol{##1} &
  \glstableDesc{##1}%
  \glstableChildEntries{##1}%
}%
```

How to format the entry's children.

```
\renewcommand{\glstableblocksubentry}[1]{%
  \glstableSubDesc{##1}%
  \glstableSubOtherWithSep{\glstableSubOtherSep}{##1}{}%
  \glstableSubSymbolWithSep{\glstableSubSep}{##1}{}%
  \glstableSubNameSep
  \glstableSubNameTarget{##1}%
}%
```

```

\glstableSubNameTarget{##1}\glstableSubNameSep
\glstableSubOtherWithSep{##1}\glstableSubOtherSep}%
\glstableSubSymbolWithSep{##1}\glstableSubSep}%
\glstableSubDesc{##1}%
}%

```

How to format the block's header row, if required.

```

\renewcommand{\glstableblockheader}{%
\glstableHeaderFmt\glstablenameheader &
\glstableHeaderFmt\glstableotherheader &
\glstableHeaderFmt\glstablesymbolheader &
\glstableHeaderFmt\glstabledescheader
}%

```

Set the block's column alignments.

```

\renewcommand{\glstableblockalign}{%
\glstablenamecolalign
\glstableothercolalign
\glstablesymbolcolalign
\glstabledesccolalign
}%
}

```

name-other As name-desc but the other field is put in the description column.

```

\glstablenewstyle{name-other}{%
2 columns per block (name, other).
\glstablecolsperblock=2\relax

```

Initialise length registers (need to calculate max name width if par align).

```

\renewcommand{\glstableinitlengthupdates}{%
\ifKV@printglosstable@header
\glsmeasurewidth{\glstablenamewidth}%
{\glstableHeaderFmt\glstablenameheader}%
\else
\setlength{\glstablenamewidth}{0pt}%
\fi
\setlength{\glstableotherwidth}{0pt}%
}%

```

Update width in unsrt hook.

```

\renewcommand{\glstablelengthupdate}[1]{%
\glstablemeasureandupdate{\glstablenamewidth}{\glstableName{##1}}%
}%

```

Finally set the other width to the remaining available.

```

\renewcommand{\glstablefinishlengthupdates}{%
\setlength{\glstableotherwidth}{\dimexpr\glstableblockwidth
- \glstablenamewidth}%
\ifdim\glstableotherwidth<0pt\relax
\setlength{\glstablenamewidth}{\dimexpr0.5\glstableblockwidth}%
\setlength{\glstableotherwidth}{\glstablenamewidth}%

```

```

\fi
}%

```

How to format the top-level entry in the block.

```

\renewcommand{\glstableblockentry}[1]{%
  \glstableNameTarget{##1} & \glstableOtherNoDesc{##1}%
  \glstableChildEntries{##1}%
}%

```

How to format the entry's children.

```

\renewcommand{\glstableblocksubentry}[1]{%
  \glstableSubNameTarget{##1}\glstableSubNameSep \glstableSubOtherNoDesc{##1}}%

```

Available width for child entries.

```

\renewcommand{\glstablesubentrywidth}{\glstableotherwidth}

```

How to format the block's header row, if required.

```

\renewcommand{\glstableblockheader}{%
  \glstableHeaderFmt\glstableNameheader &
  \glstableHeaderFmt\glstableOtherheader}%

```

Set the block's column alignments.

```

\renewcommand{\glstableblockalign}{\glstableNamecolalign\glstableOthercolalign}%
}

```

other-name

```

\glstableNewstyle{other-name}{%

```

2 columns per block (other, name).

```

\glstablecolsperblock=2\relax

```

Initialise length registers (need to calculate max name width if par align).

```

\renewcommand{\glstableinitlengthupdates}{%
  \ifKV@printglosstable@header
    \glsmasurewidth{\glstableNamewidth}%
    {\glstableHeaderFmt\glstableNameheader}%
  \else
    \setlength{\glstableNamewidth}{0pt}%
  \fi
  \setlength{\glstableOtherwidth}{0pt}%
}%

```

Update width in unsrt hook.

```

\renewcommand{\glstablelengthupdate}[1]{%
  \glstablemeasureandupdate{\glstableNamewidth}{\glstableName{##1}}%
}%

```

Finally set the other width to the remaining available.

```

\renewcommand{\glstablefinishlengthupdates}{%
  \setlength{\glstableOtherwidth}{\dimexpr\glstableblockwidth
    - \glstableNamewidth}%
  \ifdim\glstableOtherwidth<0pt\relax
    \setlength{\glstableNamewidth}{\dimexpr0.5\glstableblockwidth}%
  \fi
}

```

```

        \setlength{\glstableotherwidth}{\glstablenamewidth}%
    \fi
}%

```

How to format the top-level entry in the block. v1.50 child entries in other column.

```

\renewcommand{\glstableblockentry}[1]{%
    \glstableOtherNoDesc{##1}%
    \glstableChildEntries{##1}%
    &
    \glstableNameTarget{##1}}%

```

How to format the entry's children.

```

\renewcommand{\glstableblocksubentry}[1]{%
    \glstableSubOtherNoDesc{##1}\glstableSubNameSep
    \glstableSubNameTarget{##1}}%

```

Available width for child entries.

```

\renewcommand{\glstablesubentrywidth}{\glstableotherwidth}

```

How to format the block's header row, if required.

```

\renewcommand{\glstableblockheader}{%
    \glstableHeaderFmt\glstableotherheader &
    \glstableHeaderFmt\glstablenameheader}%

```

Set the block's column alignments.

```

\renewcommand{\glstableblockalign}{\glstableothercolalign\glstablenamecolalign}%
}

```

symbol-other As name-other but the use the symbol in place of the name.

```

\glstableneverstyle{symbol-other}{%

```

2 columns per block (symbol, other).

```

\glstablecolsperblock=2\relax

```

Initialise length registers (need to calculate max symbol width if par align).

```

\renewcommand{\glstableinitlengthupdates}{%
    \ifKV@printglosstable@header
        \glsmasurewidth{\glstablesymbolwidth}%
        {\glstableHeaderFmt\glstablesymbolheader}%
    \else
        \setlength{\glstablesymbolwidth}{0pt}%
    \fi
    \setlength{\glstableotherwidth}{0pt}%
}%

```

Update width in unsrt hook.

```

\renewcommand{\glstablelengthupdate}[1]{%
    \glstablemeasureandupdate{\glstablesymbolwidth}{\glstableSymbolName{##1}}%
}%

```

Finally set the other width to the remaining available.

```
\renewcommand{\glstablefinishlengthupdates}{%
\setlength{\glstableotherwidth}{\dimexpr\glstableblockwidth
- \glstablesymbolwidth}%
\ifdim\glstableotherwidth<0pt\relax
\setlength{\glstablesymbolwidth}{\dimexpr0.5\glstableblockwidth}%
\setlength{\glstableotherwidth}{\glstablesymbolwidth}%
\fi
}%
```

How to format the top-level entry in the block.

```
\renewcommand{\glstableblockentry}[1]{%
\glstableSymbolNameTarget{##1} & \glstableOtherNoDesc{##1}%
\glstableChildEntries{##1}%
}%
```

How to format the entry's children.

```
\renewcommand{\glstableblocksubentry}[1]{%
\glstableSubSymbolNameTarget{##1}\glstableSubNameSep
\glstableSubOtherNoDesc{##1}}%
```

Available width for child entries.

```
\renewcommand{\glstablesubentrywidth}{\glstableotherwidth}
```

How to format the block's header row, if required.

```
\renewcommand{\glstableblockheader}{%
\glstableHeaderFmt\glstablesymbolheader &
\glstableHeaderFmt\glstableotherheader}%
```

Set the block's column alignments.

```
\renewcommand{\glstableblockalign}{\glstablesymbolcolalign\glstableothercolalign}%
}
```

other-symbol

```
\glstablenustyle{other-symbol}{%
```

2 columns per block (other-symbol).

```
\glstablecolspblock=2\relax
```

Initialise length registers (need to calculate max symbol width if par align).

```
\renewcommand{\glstableinitlengthupdates}{%
\ifKV@printglosstable@header
\glsmasurewidth{\glstablesymbolwidth}%
{\glstableHeaderFmt\glstablesymbolheader}%
\else
\setlength{\glstablesymbolwidth}{0pt}%
\fi
\setlength{\glstableotherwidth}{0pt}%
}%
```

Update width in unsrt hook.

```
\renewcommand{\glstablelengthupdate}[1]{%
\glstablemeasureandupdate{\glstablesymbolwidth}{\glstableSymbolName{##1}}%
}%
```

Finally set the other width to the remaining available.

```
\renewcommand{\glstablefinishlengthupdates}{%
  \setlength{\glstableotherwidth}{\dimexpr\glstableblockwidth
    - \glstablesymbolwidth}%
  \ifdim\glstableotherwidth<0pt\relax
    \setlength{\glstablesymbolwidth}{\dimexpr0.5\glstableblockwidth}%
    \setlength{\glstableotherwidth}{\glstablesymbolwidth}%
  \fi
}%
```

How to format the top-level entry in the block. v1.50 child entries in other column.

```
\renewcommand{\glstableblockentry}[1]{%
  \glstableOtherNoDesc{##1}%
  \glstableChildEntries{##1}%
  & \glstableSymbolNameTarget{##1}}%
```

How to format the entry's children.

```
\renewcommand{\glstableblocksubentry}[1]{%
  \glstableSubOtherWithSep{##1}{\glstableSubSep}%
  \glstableSubSymbol{##1}%
  \glstableSubNameSep
  \glstableSubSymbolNameTarget{##1}}%
```

Available width for child entries.

```
\renewcommand{\glstablesubentrywidth}{\glstableotherwidth}
```

How to format the block's header row, if required.

```
\renewcommand{\glstableblockheader}{%
  \glstableHeaderFmt\glstableotherheader &
  \glstableHeaderFmt\glstablesymbolheader}%
```

Set the block's column alignments.

```
\renewcommand{\glstableblockalign}{\glstableothercolalign\glstablesymbolcolalign}%
}
```

`\glstablecaption`

```
\glstablecaption{<toc title>}{<title>}{<label code>}
```

The `<label code>` will be `\@@glossaryseclabel`.

```
\newcommand{\glstablecaption}[3]{%
  \caption[#1]{#3#2}%
}
```

`\glstablepostnextcaption`

```
\newcommand{\glstablepostnextcaption}{ (\MFUsentencecase{\glxstrcontinuedname})}
```

`\glstabenextcaption`

```
\glstabenextcaption{<toc title>}{<title>}
```

```
\newcommand{\glstabenextcaption}[2]{%
\caption[]{\#1\glstablepostnextcaption}%
}
```

```
\glstablefoot
\glstablefoot{\glstablefoot{\langle preamble \rangle}}
```

```
\newcommand{\glstablefoot}[1]{}
```

```
\glstablelastfoot
\glstablelastfoot{\glstablelastfoot{\langle preamble \rangle}}
```

```
\newcommand{\glstablelastfoot}[1]{\glstablerowspan{\#1}}
```

```
\glstablehead
\glstablehead{\glstablehead{\langle preamble \rangle}}
```

```
\newcommand{\glstablehead}[1]{}
```

```
\glstablefirsthead
\glstablefirsthead{\glstablefirsthead{\langle preamble \rangle}}
```

```
\newcommand{\glstablefirsthead}[1]{\glstablerowspan{\#1}}
```

```
\glstablepostpreambleskip
```

```
\newlength\glstablepostpreambleskip
\setlength\glstablepostpreambleskip{5pt}
```

```
\glstableprepostambleskip
```

```
\newlength\glstableprepostambleskip
\setlength\glstableprepostambleskip{5pt}
```

```
\glstablefootstrut
```

```
\newcommand{\glstablefootstrut}{%
\rule{0pt}{\dimexpr\baselineskip+\glstableprepostambleskip}%
}
```

```
\glstablerowspan
\glstablerowspan{\glstablerowspan{\langle text \rangle}}
```

```
\newcommand{\glstablerowspan}[1]{%
\multicolumn{\glstabletotalcols}{c}{\parbox{\glstablespanwidth}{\#1}}%
}
```


`\glstabspanwidth` This will be updated if column widths are measured. This width doesn't include `\tabcolsep` on either side. The default is to use `\LTcapwidth`, which may not be the same size as the table.

```
\newcommand{\glstabspanwidth}{\LTcapwidth}
```

`\glstable@begin`

```
\newcommand{\glstable@begin}{%
  \PackageError{glossary-table}{table style can only be used with
  \string\printunsrttable}{}%
}
```

`\glstable@filter` Filter all child entries, but take level offset into account and apply custom handler.

```
\newcommand{\glstable@filter}[1]{%
  \ifnum\glscurrententrylevel>0\relax
    \printunsrtglossaryskipentry
  \else
    \glstableiffilter{#1}%
    {\printunsrtglossaryskipentry}%
    {%
      \glstable@calclengths{\glstablelengthupdate{#1}}%
    }%
  \fi
}
```

`\glstableiffilter`

```
\newcommand{\glstableiffilter}[3]{#3}
```

`\glstablenamewidth`

```
\newlength\glstablenamewidth
```

`\glstableblockwidth` Maximum width available for each block.

```
\newlength\glstableblockwidth
```

`\glstabledescwidth`

```
\newlength\glstabledescwidth
```

`\glstablesymbolwidth`

```
\newlength\glstablesymbolwidth
```

`\glstableotherwidth`

```
\newlength\glstableotherwidth
```

```
\glstableifmeasuring{<true>}{<false>}
```

`\glstableifmeasuring`

```
\newcommand{\glstableifmeasuring}[2]{#2}
```

```

\glstable@stepentry
    \newcommand{\glstable@stepentry}[1]{%
        \ifglstepentrycounter
            \stepcounter{glossaryentry}%
        \fi
    }

\glstable@stepsubentry
    \newcommand{\glstable@stepsubentry}[1]{%
        \ifglssubentrycounter
            \stepcounter{glossarysubentry}%
        \fi
    }

\glstablemeasureandupdate
    \glstablemeasureandupdate{\len reg}{\text}
    \newcommand{\glstablemeasureandupdate}[2]{%
        Measure.
        \glsmasurewidth{\dimen@}{#2}%
        Update if wider.
        \ifdim\dimen@>#1\relax
            \setlength{#1}{\dimen@}%
        \fi
    }

\glstable@ifhaspreamble
    \newcommand{\glstable@ifhaspreamble}[2]{%
        \ifdefempty\glossarypreamble
            {#2}%
        {%
            \ifx\@glstable@defaultpreamble\glossarypreamble
                \ifcvoid{\glossarypreamble@\currentglossary}{#2}{#1}%
            \else
                #1%
            \fi
        }%
    }

    Need the type, preamble and postamble.
    \define@key{printglosstable}{type}{\renewcommand{\@glo@type}{#1}}
    \define@key{printglosstable}{preamble}{\renewcommand{\glossarypreamble}{#1}}
    \define@key{printglosstable}{postamble}{\renewcommand{\glossarypostamble}{#1}}
    Allow localised initialisation.

\glstable@init
    \newcommand\glstable@init{}

```

```
\define@cmdkey{printglosstable}[glstable@]{init}{}
```

The default setting is groups=false, unlike the usual default for \printunsrtglossary. Support for groups isn't fully implemented.

```
\define@choicekey{printglosstable}{groups}
[ \glstable@groups@val \glstable@groups@n ]
{false,true,noskip,addskip}[true]%
{%
  \ifcase \glstable@groups@n \relax
  \let \glstable@groupheading \gobble
  \glstr@printgloss@groups false
  \or
  \let \glstable@groupheading \glstablegroupheading
  \glstr@printgloss@groups true
  \or
  \let \glstable@groupheading \glstablegroupheading
  \glstr@printgloss@groups true
  \glsnogroupskip true
  \or
  \let \glstable@groupheading \glstablegroupheading
  \glstr@printgloss@groups true
  \glsnogroupskip false
  \fi
}
```

```
\glstable@groupheading
```

```
\newcommand{\glstable@groupheading}[1]{}%
```

\glstablegroupheading This isn't quite working as it puts a spurious line above if it occurs at the start of a new row.

```
\newcommand{\glstablegroupheading}[1]{%
  \multicolumn{\glstabletotalcols}{c}{%
    \glstrgetgrouptitle{#1}{\glstrcurrentgrptitle}%
    \glstableGroupHeaderFmt\glstrcurrentgrptitle
  }%
  \glstablePostGroupNewLine
}
```

```
\glstablePostGroupNewLine
```

```
\newcommand{\glstablePostGroupNewLine}{\glstblenewline*}
```

```
\glstableGroupHeaderFmt
```

```
\newcommand{\glstableGroupHeaderFmt}{\glstableHeaderFmt}
```

```
\glstable@preentryhook
```

```
\newcommand{\glstable@preentryhook}[1]{%
  \if \glstable@afterheading
  \else
  \advance \glstablecurrentblockindex by 1 \relax
}
```

```

\ifnum\glstablecurrentblockindex<\glstableblockperrowcount
\appto#1{&}%
\else
\appto#1{\glstablnewline}%
\fi
\fi
}

```

\glstablnewline

```

\newcommand{\glstablnewline}{\tabularnewline}

```

\glstable@postentryhook

```

\newcommand{\glstable@postentryhook}[1]{%
\ifnum\glstableblockperrowcount=\glstablecurrentblockindex
\glstablecurrentblockindex=0\relax
\fi
\@glstable@afterheadingfalse
}

```

\glstable@grouphook

```

\newcommand{\glstable@grouphook}[1]{%
\if@glstable@afterheading
\else
\preto#1{\glstablnewline}%
\advance\glstablecurrentblockindex by 1\relax
\ifnum\glstablecurrentblockindex<\glstableblockperrowcount\relax
\expandafter\glstable@n@to@amps\expandafter
{\numexpr\glstableblockperrowcount-\glstablecurrentblockindex}%
{\preto}{#1}%
\fi
\fi
\glstablecurrentblockindex=0\relax
\@glstable@afterheadingtrue
}

```

\glstable@finish

```

\newcommand{\glstable@finish}[1]{%
\if@glstable@afterheading
\else
\advance\glstablecurrentblockindex by 1\relax
\ifnum\glstablecurrentblockindex<\glstableblockperrowcount\relax
\expandafter\glstable@n@to@amps\expandafter
{\numexpr\glstableblockperrowcount-\glstablecurrentblockindex}%
{\appto}{#1}%
\fi
\fi
}

```

\@glstable@defaultpreamble

```

\let\@glstable@defaultpreamble\glossarypreamble

```

```

\@glstable@clearpage
\newcommand{\@glstable@clearpage}{}

\@glstable@clearpage@iflt Clear page if less than given length available.
\newcommand{\@glstable@clearpage@iflt}[1]{%
  \par
  \ifdim #1>\dimexpr\pagegoal-\pagetotal\relax
    \clearpage
  \fi
}

  Allow \clearpage to be inserted.
\define@key{printglosstable}{clearpage}[true]{%
  \ifstrequal{#1}{true}%
  {%
    \renewcommand{\@glstable@clearpage}{\clearpage}%
  }%
  {%
    \ifstrequal{#1}{false}%
    {%
      \renewcommand{\@glstable@clearpage}{}%
    }%
    {%
      \renewcommand{\@glstable@clearpage}{\@glstable@clearpage@iflt{#1}}%
    }%
  }%
}

\if@glstable@afterheading
\newif\if@glstable@afterheading

\printunsrtable
\NewDocumentCommand\printunsrtable{0{}}{%
  \bgroup
  Initialise glossary type.
  \def\@glo@type{\glsdefaulttype}%
  Initialise title.
  \def\glossarytitle{%
    \ifcsdef{@glo@type@\@glo@type @title}%
    {\csuse{@glo@type@\@glo@type @title}}%
    {\glossaryname}%
  }%
  \def\glossarytoctitle{\glossarytitle}%
  Initialise preamble.
  \let\glossarypreamble\@glstable@defaultpreamble
  Initialise groups=false.
  \glstr@printgloss@groupsfalse

```

Initialise nogroupskip=true.

```
\glsnogroupskiptrue
```

Set table keys.

```
\setkeys*{printglosstable}{#1}%
```

```
%\changes{1.50}{2022-11-08}{added check for caption and floats options}
```

If this table should have a caption, check the floats package option to determine whether or not to switch counter. Can be counteracted by redefining `\glscounter` in init code.

```
\ifKV@printglosstable@caption
```

```
\if@glstr@floats
```

```
\renewcommand{\glscounter}{table}%
```

```
\fi
```

```
\fi
```

Initialisation hook.

```
\glstable@init
```

Should lengths be calculated?

```
\let\glstable@calclengths\glstableifpar
```

Has nogroupskip=false been used?

```
\ifglsnogroupskip
```

```
\else
```

```
\ifundef\glspenaltygroupskip
```

```
{%
```

```
\PackageError{glossary-table}{\string\printunsrtable[nogroupskip=false]  
requires glossary-longbooktabs.sty}%
```

```
{You need to load glossary-longbooktabs.sty in addition to  
loading glossary-table.sty if you want the group skip}%
```

```
\glsnogroupskiptrue
```

```
}%
```

```
{\glspatchLToutput}%
```

```
\fi
```

```
\let\currentglossary\@glo@type
```

```
\protected@edef\glstable@opts{type=\@glo@type,style=table}%
```

```
\ifdefempty\XKV@rm{}{\epreto\glstable@opts{\expandonce\XKV@rm,}}%
```

Calculate the total number of columns.

```
\glstabletotalcols=\numexpr\glstablecolsperblock*\glstableblockperrowcount\relax
```

If the widest name is non-void, calculate the remaining width available for the blocks. 1pt is subtracted to allow for rounding errors.

```
\glstable@calclengths
```

```
{%
```

```
\edef\glstablespanwidth{\dimexpr\linewidth-2\tabcolsep-1pt}%
```

```
\glstableblockwidth=\dimexpr
```

```
(\linewidth-\glstabletotalcols\tabcolsep-\glstabletotalcols\tabcolsep)
```

```
/\glstableblockperrowcount-1pt
```

```
\relax
```

```
\glstableinitlengthupdates
```

```
}%
```

Build the header row.

```
\def\glstable@alignment{}%
\ifKV@printglosstable@rules
  \def\glstable@header{\toprule}%
\else
  \def\glstable@header{}%
\fi
\global\glstablecurrentblockindex=0\relax
\loop
```

Add to alignment spec.

```
\ifnum\glstablecurrentblockindex>0\relax
\protected@eappto\glstable@alignment{\glstable@blockalignsep}%
\fi
\protected@eappto\glstable@alignment{\glstableblockalign}%
\ifKV@printglosstable@header
```

Add to header.

```
\ifnum\glstablecurrentblockindex>0\relax
\appto\glstable@header{&}%
\fi
\appto\glstable@header{\expandonce\glstableblockheader}%
\fi
```

Increment loop counter

```
\advance\glstablecurrentblockindex by 1\relax
\ifnum\glstablecurrentblockindex<\glstableblockperrowcount
\repeat
\ifKV@printglosstable@header
```

Append cr to header.

```
\appto\glstable@header{\glstablnewline}%
\ifKV@printglosstable@rules
\appto\glstable@header{\midrule}%
\fi
\fi
\protected@edef\glstable@begin{%
\noexpand\begin{longtable}{\expandonce\glstable@alignment}%
}%
```

Use `\expandafter` after to allow an empty `\glossarytoctitle` to prevent the caption from being added to the table of contents.

```
\ifKV@printglosstable@caption
\appto\glstable@begin{%
\expandafter\glstablecaption\expandafter
{\glossarytoctitle}{\glossarytitle}%
{\@@glossaryseclabel}%
\glstablnewline
}%
\fi
```

```

\glstable@ifhaspreamble
{%
  \eappto\glstable@begin{%
    \noexpand\glstablefirsthead
    {\expandonce\glossarypreamble}%
    \noexpand\glstablnewline[\glstablepostpreambleskip]%
    \expandonce\glstable@header
    \noexpand\endfirsthead
  }%
  \ifKV@printglosstable@caption
    \appto\glstable@begin{%
      \expandafter\glstablnextcaption\expandafter
      {\glossarytoctitle}{\glossarytitle}%
      \glstablnewline
    }%
  \fi
  \ifx\glstablehead\@gobble
  \else
    \eappto\glstable@begin{%
      \noexpand\glstablehead{\expandonce\glossarypreamble}%
      \noexpand\glstablnewline[\glstablepostpreambleskip]%
    }%
  \fi
}%
{%
  \eappto\glstable@begin{%
    \expandonce\glstable@header
    \noexpand\endfirsthead
  }%
  \ifKV@printglosstable@caption
    \appto\glstable@begin{%
      \expandafter\glstablnextcaption\expandafter
      {\glossarytoctitle}{\glossarytitle}%
      \glstablnewline
    }%
  \fi
}%
\appto\glstable@begin{%
  \expandonce\glstable@header
  \noexpand\endhead
}%

```

```
\ifdefined\glossarypostamble
{%
```

```
\ifKV@printglosstable@rules
  \appto\glsstable@begin{\bottomrule\endfoot}%
```



```

\fi
}
{%
\ifKV@printglosstable@rules
\ea\pto\glstable@begin{%
\noexpand\bottomrule
\noexpand\glstablefoot
{\noexpand\glstablefootstrut\expandonce\glossarypostamble}%
\noexpand\glstablnewline
\noexpand\endfoot
\noexpand\bottomrule
\noexpand\glstablelastfoot
{\noexpand\glstablefootstrut\expandonce\glossarypostamble}%
\noexpand\glstablnewline
\noexpand\endlastfoot
}%
\else
\ea\pto\glstable@begin{%
\noexpand\glstablefoot{\expandonce\glossarypostamble}%
\noexpand\glstablnewline[\glstableprepostambleskip]%
\noexpand\endfoot
\noexpand\glstablelastfoot{\expandonce\glossarypostamble}%
\noexpand\glstablnewline[\glstableprepostambleskip]%
\noexpand\endlastfoot
}%
\fi
}%

```

Set up filtering.

```
\let\printunsrtglossaryentryprocesshook\glstable@filter
```

Use the hooks to add tab and new lines to avoid awkward conditionals within longtable.

```

\renewcommand{\printunsrtglossarypreentryprocesshook}{%
\glstable@preentryhook
}%
\renewcommand{\printunsrtglossarypostentryprocesshook}{%
\glstable@postentryhook
}%
\renewcommand{\printunsrtglossarygrouphook}{%
\glstable@grouphook
}%
\renewcommand{\printunsrtglossarypreend}{%
\glstable@finish
}%

```

Disable preamble and postamble commands as their content has already been added to the table specs.

```

\let\glossarypostamble\relax
\let\glossarypreamble\relax

```

Disable the section command as the title and toc title are now in the caption.

```
\renewcommand{\glossarysection}[2][{}]{}
```

Used in hooks.

```
\glstablecurrentblockindex=0\relax
\@glstable@afterheadingtrue
```

Clear page if required.

```
\@glstable@clearpage
```

Finish updating lengths in hook.

```
\let\glstable@org@predoglossary\printunsrtglossarypredoglossary
\renewcommand{\printunsrtglossarypredoglossary}
{%
  \glstable@calclengths{\glstablefinishlengthupdates}%
  \glstable@org@predoglossary
}%
```

The glossary will be empty on the first L^AT_EX run as the entries won't be defined until bib2gls has selected them.

```
\glsxtrifemptyglossary{\currentglossary}
{%
  \GlossariesExtraWarning{Glossary ‘\currentglossary’ is empty}%
```

Just do the table header and footer to allow it to be added to the list of tables and have the label added to the aux file.

```
\edef\@glxtr@tmp{\noexpand\setkeys{printgloss}{\expandonce\glstable@opts}}%
\@glxtr@tmp
\glstable@begin% \begin{longtable}{specs}
\end{longtable}%
}%
{%
  \expandafter\printunsrtglossary\expandafter[\glstable@opts]\relax
}%
\egroup
}
```

`\glstableiffilterchild`

```
\newcommand{\glstableiffilterchild}[3]{#3}
```

`\glstable@child`

```
\newcommand{\glstable@child}[1]{%
  \glstableiffilterchild{#1}{}%
  {%
    \ifdefempty\glstable@dochildren{%
      \appto\glstable@dochildren{\glstableblocksubentrysep}}%
    \appto\glstable@dochildren{\glstableblocksubentry{#1}}%
  }%
}
```

`\glstableChildEntries`

```
\newcommand{\glstableChildEntries}[1]{%
\def\glstable@dochildren{%
\GlsXtrIfFieldNonZero*{childcount}{#1}%
{%
\glstrfieldforlistloop{#1}{childlist}{\glstable@child}%
\ifdefempty\glstable@dochildren
{}%
}%
\preto\glstable@dochildren{%
\glstablePreChildren
\begin{glstablesubentries}%
}%
\appto\glstable@dochildren{\end{glstablesubentries}}%
}%
}%
{}%
\glstable@dochildren
}
```

`\glstable@n@amps` Removed.

`\glstable@n@to@amps`

```
\newcommand{\glstable@n@to@amps}[3]{%
\ifnum#1>0\relax
\count@=0\relax
\loop
\advance\count@ by 1\relax
#2#3{&}%
\ifnum\count@<#1
\repeat
\fi
}
```

`\glstablefinishrow` Removed in v1.50.

`table`

```
\newglossarystyle{table}%
{%
\renewenvironment{theglossary}%
{%
\glstable@begin
}
{%
\end{longtable}%
}%
\renewcommand*{\glossaryheader}{}%
\renewcommand*{\glsgroupheading}[1]{\glstable@groupheading{#1}}%
\renewcommand*{\glssubgroupheading}[4]{}%
\ifglsnogroupskip
```

```

\renewcommand*{\glsgroupskip}{}%
\else
\renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
\renewcommand{\glossentry}[2]{%
\glstableblockentry{##1}%
v1.50: \glstableChildEntries moved to block style and conditionals moved
to processing hooks.
}%
\renewcommand{\subglossentry}[3]{}%
}

```

9 Rollback Files

9.1 Rollback v1.48 (glossaries-extra-2021-11-22.sty)

Version 1.48 preserved for rollback.

```

\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{glossaries-extra}[2021/11/22 v1.48 (NLCT)]
\RequirePackage{xkeyval}
\RequirePackage{etoolbox}
\@ifpackageloaded{glossaries}
{%
\newcommand{\glsxtr@doooption}[1]{\setupglossaries{##1}}%
\let\@glsxtr@declareoption\@gls@declareoption
}
{%
\newcommand{\glsxtr@doooption}[1]{%
\PassOptionsToPackage{##1}{glossaries}%
}%
\PassOptionsToPackage{toc}{glossaries}
\PassOptionsToPackage{nopostdot}{glossaries}
\PassOptionsToPackage{noredefwarn}{glossaries}
\@ifpackageloaded{polyglossia}%
{}%
{%
\@ifpackageloaded{babel}%
{\PassOptionsToPackage{translate=babel}{glossaries}}%
{}%
}%
\newcommand*{\@glsxtr@declareoption}[2]{%
\DeclareOptionX{##1}{##2}%
\DeclareOption{##1}{##2}%
}
}
\newcommand*{\glsxtrundefaction}[2]{%
\@glsxtrundeftag\PackageError{glossaries-extra}{##1}{##2}%
}

```

```

\newcommand*\glxtr@warnonexistsordo}[1]{%
\newcommand*\glxtrundefrag}{??}
\newcommand*\glxtrundefrag}{%
\newcommand*\glxtr@warn@undefaction}[2]{%
  \glxtrundefrag\GlossariesExtraWarning{#1}%
}
\newcommand*\glxtr@err@undefaction}[2]{%
  \glxtrundefrag\PackageError{glossaries-extra}{#1}{#2}%
}
\newcommand*\glxtr@warn@onexistsordo}[1]{%
  \GlossariesExtraWarning{string#1\space hasn't been defined, so
  some errors won't be converted to warnings.
  (This most likely means your version of
  glossaries.sty is below version 4.19.)}%
}

\newcommand*\glxtr@redef@forlgsentries}{%
\newcommand*\glxtr@do@redef@forlgsentries}{%
  \renewcommand*\forlgsentries}[3][\glstypedefaulttype]{%
    \protected@edef\@glo@list{\csname glolist@##1\endcsname}%
    \ifdefstring{\@glo@list}{,}%
    {%
      \GlossariesExtraWarning{No entries defined in glossary '##1'}%
    }%
    {%
      \for##2:=\@glo@list\do
      {%
        \ifdefempty{##2}{}{##3}%
      }%
    }%
  }%
}%
\define@choicekey{glossaries-extra.sty}{undefaction}{%
  [\glxtr@undefaction@val\glxtr@undefaction@nr]{%
    {warn,error}%
    {%
      \ifcase\glxtr@undefaction@nr\relax
        \let\glxtrundefaction\glxtr@warn@undefaction
        \let\glxtr@warnonexistsordo\glxtr@warn@onexistsordo
        \let\glxtr@redef@forlgsentries\glxtr@do@redef@forlgsentries
      \or
        \let\glxtrundefaction\glxtr@err@undefaction
        \let\glxtr@warnonexistsordo\gobble
        \let\glxtr@redef@forlgsentries\relax
      \fi
    }
  }
\newcommand*\glxtr@record}[3]{%
\newcommand*\glxtr@recordsee}[2]{%
\newcommand*\glxtr@defaultnumberformat}{\glstypedefaultnumberformat}%
\newcommand*\GlsXtrSetDefaultNumberFormat}[1]{%

```

```

\renewcommand*{\@glsxtr@defaultnumberformat}{#1}%
}%
\newcommand*{\@glsxtr@do@record@wrglossary}[1]{%
\beginingroup
\ifKV@glslink@noindex
\else
\protected@edef\@gls@label{\glsdetoklabel{#1}}%
\let\glslabel\@gls@label
\glswriteentry{#1}%
{%
\ifdefempty{\@glsxtr@thevalue}%
{%
\ifx\@glsxtr@org@theHvalue\@glsxtr@theHvalue
\else
\let\theHglsentrycounter\@glsxtr@theHvalue
\fi
\glsxtr@saveentrycounter
\let\@do@wrglossary\@glsxtr@dorecord
}%
{%
\let\theHgsentrycounter\@glsxtr@thevalue
\let\theHgsentrycounter\@glsxtr@theHvalue
\let\@do@wrglossary\@glsxtr@dorecordnodefer
}%
\ifx\@glsxtr@record@setting\@glsxtr@record@setting@alsoindex
\glsxtr@do@wrglossary{#1}%
\else
\@glsxtrwrglossmark
\glsxtr@inc@wrglossaryctr{#1}%
\@do@wrglossary
\fi
}%
\fi
\endgroup
}
\newcommand*{\glsxtr@do@alsoindex@wrglossary}[1]{%
\glsxtr@do@wrglossary{#1}%
\@glsxtr@do@record@wrglossary{#1}%
}
\newcommand*{\@glsxtr@record}[3]{%
\protected@edef\@gls@label{\glsdetoklabel{#2}}%
\let\glslabel\@gls@label
\ifglsentryexists{#2}{%
{%
\@glsxtrwrglossmark
\beginingroup
\let\@glsnumberformat\@glsxtr@defaultnumberformat
\def\@glsxtr@thevalue{%
\def\@glsxtr@theHvalue{\@glsxtr@thevalue}%
\let\@glsxtr@org@theHvalue\@glsxtr@theHvalue

```

```

\let\@gls@counter\glscounter
\if@glsxtr@equations
  \@glsxtr@use@equation@counter
\fi
\@gls@setdefault@glslink@opts
\csuse{@glsxtr@#3@prekeys}%
\setkeys{#3}{#1}%
\glsxtr@do@autoadd{#3}%
\csuse{@glsxtr@#3@postkeys}%
\glsxtr@inc@wrglossaryctr{#2}%
\ifKV@glslink@noindex
\else
  \glswriteentry{#2}%
  {%
    \ifdefempty{\@glsxtr@thevalue}%
    {%
      \ifx\@glsxtr@org@theHvalue\@glsxtr@theHvalue
      \else
        \let\theHglentrycounter\@glsxtr@theHvalue
      \fi
      \glsxtr@saveentrycounter
      \let\@do@wrglossary\@glsxtr@dorecord
    }%
    {%
      \let\theHglentrycounter\@glsxtr@thevalue
      \let\theHglentrycounter\@glsxtr@theHvalue
      \let\@do@wrglossary\@glsxtr@dorecordnodefer
    }%
    \ifx\@glsxtr@record@setting\@glsxtr@record@setting@alsoindex
      \glsxtr@do@wrglossary{#2}%
    \else
      \@do@wrglossary
    \fi
  }%
\fi
\endgroup
}%
}
\newcommand{\@glsxtr@glslink@prekeys}{\glslinkpresetkeys}
\newcommand{\@glsxtr@glslink@postkeys}{\glslinkpostsetkeys}
\newcommand{\@glsxtr@glossadd@prekeys}{\glsaddpresetkeys}
\newcommand{\@glsxtr@glossadd@postkeys}{\glsaddpostsetkeys}
\newcommand*\@glsxtr@dorecord{%
  \global\let\@glsrecordlocref\theHglentrycounter
  \let\@glsxtr@orgprefix\@glo@counterprefix
  \ifx\theHglentrycounter\theHglentrycounter
    \def\@glo@counterprefix{}%
  \else
    \protected@edef\@glsxtr@theentrycounter{\theHglentrycounter}%
    \protected@edef\@glsxtr@theHentrycounter{\theHglentrycounter}%
  \fi
}

```

```

\@onelevel@sanitize\@glxtr@theentrycounter
\@onelevel@sanitize\@glxtr@theHentrycounter
\protected@edef\@do@gl@getcounterprefix{\noexpand\@gl@getcounterprefix
  {\@glxtr@theentrycounter}{\@glxtr@theHentrycounter}}%
}%
\@do@gl@getcounterprefix
\fi
\ifx\@glxtr@record@setting\@glxtr@record@setting@nameref
\@glxtr@do@nameref@record
  {\@gl@label}{\@glo@counterprefix}{\@gl@counter}{\@gl@numberformat}%
  {\@gl@recordlocref}}%
\else
\protected@write\@auxout{}\string\@glxtr@record
  {\@gl@label}{\@glo@counterprefix}{\@gl@counter}{\@gl@numberformat}%
  {\@gl@recordlocref}}%
\fi
\@glxtr@counterrecordhook
\let\@glo@counterprefix\@glxtr@orgprefix
}
\newcommand*\@glxtr@dorecordnodefer{%
\ifx\theglsentrycounter\theHglentrycounter
\ifx\@glxtr@record@setting\@glxtr@record@setting@nameref
\@glxtr@do@nameref@record
  {\@gl@label}{\@gl@counter}{\@gl@numberformat}%
  {\theglsentrycounter}}%
\else
\protected@write\@auxout{}\string\@glxtr@record
  {\@gl@label}{\@gl@counter}{\@gl@numberformat}%
  {\theglsentrycounter}}%
\fi
\else
\edef\@do@gl@getcounterprefix{\noexpand\@gl@getcounterprefix
  {\theglsentrycounter}{\theHglentrycounter}}%
}%
\@do@gl@getcounterprefix
\ifx\@glxtr@record@setting\@glxtr@record@setting@nameref
\@glxtr@do@nameref@record
  {\@gl@label}{\@glo@counterprefix}{\@gl@counter}%
  {\@gl@numberformat}{\theglsentrycounter}}%
\else
\protected@write\@auxout{}\string\@glxtr@record
  {\@gl@label}{\@glo@counterprefix}{\@gl@counter}{\@gl@numberformat}%
  {\theglsentrycounter}}%
\fi
\fi
\@glxtr@counterrecordhook
}
\newcommand{\@glxtr@ifnum@mmode}[2]{%
\ifmmode
\ifst@rred

```



```

#2%
\else
\if@display #1\else #2\fi
\fi
\else
#2%
\fi
}
\newcommand*{\@glxtr@do@nameref@record}[5]{%
\gls@ifnotmeasuring
{%
\protected@write\@auxout{}\string\glxtr@record@nameref
{#1}{#2}{#3}{#4}{#5}%
{\csuse{@currentlabelname}}{\csuse{@currentHref}}%
{\theHglentrycounter}}%
}%
}
\newcommand*{\@glxtr@recordcounter}{%
\@glxtr@noop@recordcounter
}
\newcommand*{\@glxtr@noop@recordcounter}[1]{%
\PackageError{glossaries-extra}{\string\GlsXtrRecordCounter\space
requires record=only or record=hybrid package option}{}%
}
\newcommand*{\@glxtr@op@recordcounter}[1]{%
\protected@eappto\@glxtr@counterrecordhook{\noexpand\@glxtr@docounterrecord{#1}}%
}
\newcommand*{\@glxtr@recordsee}[2]{%
\@glxtr@wrglossmark
\def\@gls@xref{#2}%
\@onelevel@sanitize\@gls@xref
\protected@write\@auxout{}\string\glxtr@recordsee{#1}{\@gls@xref}}%
}
\newcommand{\printunsrtglossaryunit}{%
\print@noop@unsrtglossaryunit
}
\newcommand*{\glxtr@setup@record}{\let\@do@wrglossary\glxtr@do@wrglossary}
\newcommand*{\glxtr@indexonly@saveentrycounter}{%
\ifKV@glslink@noindex
\else
\glxtr@saveentrycounter
\fi
}
\newcommand*{\glxtr@addloclistfield}{%
\key@ifundefined{glossentry}{loclist}%
{%
\define@key{glossentry}{loclist}{\def\@glo@loclist{##1}}%
\appto\@gls@keymap{,{loclist}{loclist}}%
\appto\@newglossaryentryprehook{\def\@glo@loclist{}}%
\appto\@newglossaryentryposthook{%

```

```

        \gls@assign@field{\@glo@label}{loclist}{\@glo@loclist}%
    }%
    \glssetnoexpandfield{loclist}%
}%
{}%
\key@ifundefined{glossentry}{location}%
{%
    \define@key{glossentry}{location}{\def\@glo@location{##1}}%
    \appto\@gls@keymap{,{location}{location}}%
    \appto\@newglossaryentryprehook{\def\@glo@location{}}%
    \appto\@newglossaryentryposthook{%
        \gls@assign@field{\@glo@label}{location}{\@glo@location}%
    }%
    \glssetnoexpandfield{location}%
}%
{}%
\key@ifundefined{glossentry}{group}%
{%
    \define@key{glossentry}{group}{\def\@glo@group{##1}}%
    \appto\@gls@keymap{,{group}{group}}%
    \appto\@newglossaryentryprehook{\def\@glo@group{}}%
    \appto\@newglossaryentryposthook{%
        \gls@assign@field{\@glo@label}{group}{\@glo@group}%
    }%
    \glssetnoexpandfield{group}%
}%
{}%
}
\newcommand*{\@glsxtr@record@setting}{off}
\newcommand*{\@glsxtr@record@setting@alsoindex}{alsoindex}
\newcommand*{\@glsxtr@record@setting@only}{only}
\newcommand*{\@glsxtr@record@setting@nameref}{nameref}
\newcommand*{\@glsxtr@if@record@only}[2]{%
    \ifx\@glsxtr@record@setting\@glsxtr@record@setting@only
        #1%
    \else
        \ifx\@glsxtr@record@setting\@glsxtr@record@setting@nameref
            #1%
        \else
            #2%
        \fi
    \fi
}%
\newcommand*{\@glsxtr@record@setting@off}{off}
\newcommand\@glsxtr@warn@hybrid@noprintgloss{%
    \ifdefstring{\@glo@types}{,}%
    {%
        \GlossariesExtraWarningNoLine{No glossaries have been defined}%
    }%
}%

```

```

\GlossariesExtraWarningNoLine{No \string\printglossary\space
or \string\printglossaries\space
found. ^^JYou have requested the hybrid setting
record=\@glxtr@record@setting\space which requires a
combination of bib2gls (to fetch entries) and makeindex/xindy
(to sort and collate the entries). If you only want to use
bib2gls then change the option to record=only or record=nameref}%
}%
}
\newcommand*{\@glxtr@record@only@setup}{%
\def\glxtr@setup@record{%
\@glxtr@autoseeindexfalse
\let\@do@seeglossary\@glxtr@recordsee
\let\@glxtr@record\@glxtr@record
\let\@do@wrglossary\@glxtr@do@record@wrglossary
\let\@glx@saveentrycounter\relax
\let\glxtrundefaction\@glxtr@warn@undefaction
\let\glxtr@warnonexistsordo\@glxtr@warn@onexistsordo
\glxtr@addloclistfield
\renewcommand*{\@glxtr@autoindexcrossrefs}{}%
\let\@glxtr@recordcounter\@glxtr@op@recordcounter
\def\printunsrtglossaryunit{\print@op@unsrtglossaryunit}%
\def\glxtrsetaliasnoindex{}%
\ifdef\@glx@setupsort@none{\@glx@setupsort@none}{}%
\def\glxtrNoGlossaryWarning{\@glxtr@record@noglossarywarning}%
\RequirePackage{glossaries-extra-bib2gls}[=v1.48]%
}%
}
\define@choicekey{glossaries-extra.sty}{record}
[{\@glxtr@record@setting\glxtr@record@nr}%
{off,only,alsoindex,nameref,hybrid}%
[only]%
{%
\ifcase\glxtr@record@nr\relax
\def\glxtr@setup@record{%
\renewcommand*{\@do@seeglossary}{\@glxtr@do@seeglossary}%
\renewcommand*{\@glxtr@record}[3]{}%
\let\@do@wrglossary\glxtr@do@wrglossary
\let\@glx@saveentrycounter\glxtr@indexonly@saveentrycounter
\let\glxtrundefaction\@glxtr@err@undefaction
\let\glxtr@warnonexistsordo\@gobble
\let\@glxtr@recordcounter\@glxtr@noop@recordcounter
\def\printunsrtglossaryunit{\print@noop@unsrtglossaryunit}%
\undef\glxtrsetaliasnoindex
}%
\or
\@glxtr@record@only@setup
\or
\def\glxtr@setup@record{%
\renewcommand*{\@glxtr@record@setting@alsoindex}{alsoindex}%

```

```

\renewcommand*{\@do@seeglossary}{\@glxtr@dosee@alsoindex@glossary}%
\let\@glxtr@record\@glxtr@record
\let\@do@wrglossary\glxtr@do@alsoindex@wrglossary
\let\@glxtr@saveentrycounter\glxtr@indexonly@saveentrycounter
\let\glxtrundefaction\@glxtr@warn@undefaction
\let\glxtr@warnonexistssordo\@glxtr@warn@onexistssordo
\glxtr@addloclistfield
\let\@glxtr@recordcounter\@glxtr@op@recordcounter
\def\printunsrtglossaryunit{\print@op@unsrtglossaryunit}%
\undef\glxtrsetaliasnoindex
}%
\or
\@glxtr@record@only@setup
\ifundef\hyperlink
{\GlossariesExtraWarning{You have requested record=nameref but
the document doesn't support hyperlinks}}%
{}%
\or
\def\glxtr@setup@record{%
\renewcommand*{\@glxtr@record@setting@alsoindex}{hybrid}%
\renewcommand*{\@do@seeglossary}{\@glxtr@dosee@alsoindex@glossary}%
\let\@glxtr@record\@glxtr@record
\let\@do@wrglossary\glxtr@do@alsoindex@wrglossary
\let\@glxtr@saveentrycounter\glxtr@indexonly@saveentrycounter
\let\glxtrundefaction\@glxtr@warn@undefaction
\let\glxtr@warnonexistssordo\@glxtr@warn@onexistssordo
\glxtr@addloclistfield
\let\@glxtr@recordcounter\@glxtr@op@recordcounter
\def\printunsrtglossaryunit{\print@op@unsrtglossaryunit}%
\undef\glxtrsetaliasnoindex
}%
\fi
}
\newcommand*{\@glxtr@docdefval}{0}
\newcommand*{\if@glxtrdocdef}{\ifnum\@glxtr@docdefval>0 }
\newcommand*{\@glxtrdocdeftrue}{\def\@glxtr@docdefval{1}}
\newcommand*{\@glxtrdocdeffalse}{\def\@glxtr@docdefval{0}}
\define@choicekey{glossaries-extra.sty}{docdef}
[\@glxtr@docdefsetting\@glxtr@docdefval]%
{false,true,restricted,atom}[true]%
{%
\ifnum\@glxtr@docdefval>1\relax
\renewcommand*{\@glxtrdocdef}{\glxtrdocdef}%
\else
\renewcommand*{\@glxtrdocdef}{\glxtrdocdef}%
\fi
}
\newcommand*{\if@glxtrdocdefrestricted}{\ifnum\@glxtr@docdefval>1 }
\newcommand*{\@glxtrdocdefrestricted}{\glxtrdocdefrestricted}%
\define@boolkey{glossaries-extra.sty}{\glxtr}{indexcrossrefs}[true]{%

```

```

\if@glxtrindexcrossrefs
\else
\renewcommand*{\@glxtr@autoindexcrossrefs}{}%
\fi
}
\@glxtrindexcrossrefsfalse
\newcommand*{\@glxtr@autoindexcrossrefs}{\@glxtrindexcrossrefstrue}
\define@boolkey{glossaries-extra.sty}{@glxtr@}{autoseeindex}[true]{%
}
\@glxtr@autoseeindextrue
\define@boolkey{glossaries-extra.sty}{@glxtr@}{equations}[true]{%
}
\@glxtr@equationsfalse
\let\glxtr@float\@float
\let\glxtr@dblfloat\@dblfloat
\define@boolkey{glossaries-extra.sty}{@glxtr@}{floats}[true]{%
\if@glxtr@floats
\renewcommand*{\@float}[1]{\renewcommand{\glscounter}{##1}\glxtr@float{##1}}%
\renewcommand*{\@dblfloat}[1]{\renewcommand{\glscounter}{##1}\glxtr@dblfloat{##1}}%
\else
\let\@float\glxtr@float
\let\@dblfloat\glxtr@dblfloat
\fi
}
\@glxtr@floatsfalse
\newcommand*{\GlossariesExtraWarning}[1]{\PackageWarning{glossaries-extra}{#1}}
\newcommand*{\GlossariesExtraWarningNoLine}[1]{%
\PackageWarningNoLine{glossaries-extra}{#1}}
\@glxtr@declareoption{nowarn}{%
\let\GlossariesExtraWarning\@gobble
\let\GlossariesExtraWarningNoLine\@gobble
\glxtr@doption{nowarn}%
}
\newcommand*{\@glxtr@defpostpunc}{%
\@glxtr@declareoption{postdot}{%
\glxtr@doption{nopostdot=false}%
\renewcommand*{\@glxtr@defpostpunc}{%
\renewcommand*{\glspostdescription}{%
\ifglsnopostdot\else.\spacefactor\sfcode'\. \fi}%
}%
}%
}
\define@choicekey{glossaries-extra.sty}{nopostdot}{true,false}[true]{%
\glxtr@doption{nopostdot=#1}%
\renewcommand*{\@glxtr@defpostpunc}{%
\renewcommand*{\glspostdescription}{%
\ifglsnopostdot\else.\spacefactor\sfcode'\. \fi}%
}%
}
\define@key{glossaries-extra.sty}{postpunc}{%

```

```

\glstr@dooption{nopostdot=false}%
\ifstrequal{#1}{dot}%
{%
  \renewcommand*{\@glstr@defpostpunc}{%
    \renewcommand*{\glspostdescription}{.\spacefactor\sfcode'\. }%
  }%
}%
{%
  \ifstrequal{#1}{comma}%
  {%
    \renewcommand*{\@glstr@defpostpunc}{%
      \renewcommand*{\glspostdescription}{,}%
    }%
  }%
  {%
    \ifstrequal{#1}{none}%
    {%
      \glstr@dooption{nopostdot=true}%
      \renewcommand*{\@glstr@defpostpunc}{%
        \renewcommand*{\glspostdescription}{}%
      }%
    }%
    {%
      \renewcommand*{\@glstr@defpostpunc}{%
        \renewcommand*{\glspostdescription}{#1}%
      }%
    }%
  }%
}%
}
\newcommand*{\glstrabbrvtype}{\glstrdefaulttype}
\newcommand*{\@glstr@abbreviationsdef}{}

\newcommand*{\@glstr@doabbreviationsdef}{%
  \@ifpackageloaded{babel}%
  {\providecommand{\abbreviationsname}{\acronymname}}%
  {\providecommand{\abbreviationsname}{Abbreviations}}%
  \newglossary[glg-abr]{abbreviations}{glg-abr}{glo-abr}{\abbreviationsname}%
  \renewcommand*{\glstrabbrvtype}{abbreviations}%
  \newcommand*{\printabbreviations}[1][1]{%
    \printglossary[type=\glstrabbrvtype,##1]%
  }%
  \disable@keys{glossaries-extra.sty}{abbreviations}%
  \ifglstracronym
  \else
    \renewcommand*{\acronymtype}{\glstrabbrvtype}%
  \fi
}%
\@glstr@declareoption{abbreviations}{%
  \let\@glstr@abbreviationsdef\@glstr@doabbreviationsdef

```

```

}
\newcommand*{\GlsXtrDefineAbbreviationShortcuts}{%
  \newcommand*{\ab}{\cgl{s}}%
  \newcommand*{\abp}{\cgl{s}pl}%
  \newcommand*{\as}{\gl{s}trshort}%
  \newcommand*{\asp}{\gl{s}trshortpl}%
  \newcommand*{\al}{\gl{s}trlong}%
  \newcommand*{\alp}{\gl{s}trlongpl}%
  \newcommand*{\af}{\gl{s}trfull}%
  \newcommand*{\afp}{\gl{s}trfullpl}%
  \newcommand*{\Ab}{\cGl{s}}%
  \newcommand*{\Abp}{\cGl{s}pl}%
  \newcommand*{\As}{\Gl{s}trshort}%
  \newcommand*{\Asp}{\Gl{s}trshortpl}%
  \newcommand*{\Al}{\Gl{s}trlong}%
  \newcommand*{\Alp}{\Gl{s}trlongpl}%
  \newcommand*{\Af}{\Gl{s}trfull}%
  \newcommand*{\Afp}{\Gl{s}trfullpl}%
  \newcommand*{\AB}{\cGL{S}}%
  \newcommand*{\ABP}{\cGL{S}pl}%
  \newcommand*{\AS}{\GL{S}trshort}%
  \newcommand*{\ASP}{\GL{S}trshortpl}%
  \newcommand*{\AL}{\GL{S}trlong}%
  \newcommand*{\ALP}{\GL{S}trlongpl}%
  \newcommand*{\AF}{\GL{S}trfull}%
  \newcommand*{\AFP}{\GL{S}trfullpl}%
  \providecommand*{\newabbr}{\newabbreviation}%
  \let\GlsXtrDefineAbbreviationShortcuts\relax
}
\newcommand*{\GlsXtrDefineAcShortcuts}{%
  \newcommand*{\ac}{\cgl{s}}%
  \newcommand*{\acp}{\cgl{s}pl}%
  \newcommand*{\acs}{\gl{s}trshort}%
  \newcommand*{\acsp}{\gl{s}trshortpl}%
  \newcommand*{\acl}{\gl{s}trlong}%
  \newcommand*{\aclp}{\gl{s}trlongpl}%
  \newcommand*{\acf}{\gl{s}trfull}%
  \newcommand*{\acfp}{\gl{s}trfullpl}%
  \newcommand*{\Ac}{\cGl{s}}%
  \newcommand*{\Acp}{\cGl{s}pl}%
  \newcommand*{\Acs}{\Gl{s}trshort}%
  \newcommand*{\Acsp}{\Gl{s}trshortpl}%
  \newcommand*{\Acl}{\Gl{s}trlong}%
  \newcommand*{\Aclp}{\Gl{s}trlongpl}%
  \newcommand*{\Acf}{\Gl{s}trfull}%
  \newcommand*{\Acfp}{\Gl{s}trfullpl}%
  \newcommand*{\AC}{\cGL{S}}%
  \newcommand*{\ACP}{\cGL{S}pl}%
  \newcommand*{\ACS}{\GL{S}trshort}%
  \newcommand*{\ACSP}{\GL{S}trshortpl}%

```

```

\newcommand*{\ACL}{\GLSxtrlong}%
\newcommand*{\ACLP}{\GLSxtrlongpl}%
\newcommand*{\ACF}{\GLSxtrfull}%
\newcommand*{\ACFP}{\GLSxtrfullpl}%
\providecommand*{\newabbr}{\newabbreviation}%
\let\GlsXtrDefineAcShortcuts\relax
}
\newcommand*{\GlsXtrDefineOtherShortcuts}{%
\newcommand*{\newentry}{\newglossaryentry}%
\ifdef\printsymbols
{%
\newcommand*{\newsym}{\glxtrnewsymbol}%
}%
\ifdef\printnumbers
{%
\newcommand*{\newnum}{\glxtrnewnumber}%
}%
\let\GlsXtrDefineOtherShortcuts\relax
}
\newcommand*{@glxtr@setupshortcuts}{}
\newcommand*{@glxtr@shortcutsval}{\ifglacrshortcutsacro\else none\fi}%
\define@choicekey{glossaries-extra.sty}{shortcuts}%
[{\glxtr@shortcutsval\glxtr@shortcutsnr}]%
{acronyms,acro,abbreviations,abbr,other,all,true,ac,none,false}[true]{%
\ifcase\glxtr@shortcutsnr\relax % acronyms
\renewcommand*{@glxtr@setupshortcuts}{%
\glacrshortcutstrue
\DefineAcronymSynonyms
}%
\or % acro
\renewcommand*{@glxtr@setupshortcuts}{%
\glacrshortcutstrue
\DefineAcronymSynonyms
}%
\or % abbreviations
\renewcommand*{@glxtr@setupshortcuts}{%
\GlsXtrDefineAbbreviationShortcuts
}%
\or % abbr
\renewcommand*{@glxtr@setupshortcuts}{%
\GlsXtrDefineAbbreviationShortcuts
}%
\or % other
\renewcommand*{@glxtr@setupshortcuts}{%
\GlsXtrDefineOtherShortcuts
}%
\or % all
\renewcommand*{@glxtr@setupshortcuts}{%
\glacrshortcutstrue
\GlsXtrDefineAcShortcuts
}

```



```

        \GlsXtrDefineAbbreviationShortcuts
        \GlsXtrDefineOtherShortcuts
    }%
\or % true
    \renewcommand*{\@glstr@setupshortcuts}{%
        \glsacrshortcutstrue
        \GlsXtrDefineAcShortcuts
        \GlsXtrDefineAbbreviationShortcuts
        \GlsXtrDefineOtherShortcuts
    }%
\or % ac
    \renewcommand*{\@glstr@setupshortcuts}{%
        \glsacrshortcutstrue
        \GlsXtrDefineAcShortcuts
    }%
\else % none, false
    \renewcommand*{\@glstr@setupshortcuts}{}%
\fi
}
\newcommand*{\@glstr@doaccsupp}{}
\@glstr@declareoption{accsupp}{%
    \renewcommand*{\@glstr@doaccsupp}{\RequirePackage{glossaries-accsupp}}}
\newcommand*{\@glstr@doloadprefix}{}
\@glstr@declareoption{prefix}{%
    \renewcommand*{\@glstr@doloadprefix}{\RequirePackage{glossaries-prefix}}}
\newcommand{\glstrNoGlossaryWarning}[1]{%
    \GlossariesExtraWarning{Glossary ‘#1’ is missing}%
    \@glstr@defaultnoglossarywarning{#1}%
}
\define@choicekey{glossaries-extra.sty}{nomissingglstext}
[{\@glstr@nomissingglstextval\@glstr@nomissingglstextnr}]%
{true,false}[true]{%
    \ifcase\@glstr@nomissingglstextnr\relax % true
        \renewcommand{\glstrNoGlossaryWarning}[1]{\null}%
    \else % false
        \renewcommand{\glstrNoGlossaryWarning}[1]{%
            \@glstr@defaultnoglossarywarning{#1}%
        }%
    \fi
}
}
\newcommand*{\@glstr@redefstyles}{}
\define@key{glossaries-extra.sty}{stylemods}[default]{%
    \ifstrequal{#1}{default}%
    {%
        \renewcommand*{\@glstr@redefstyles}{%
            \RequirePackage{glossaries-extra-stylemods}}%
    }%
    {%
        \ifstrequal{#1}{all}%
        {%

```

```

\renewcommand*{\@glsxtr@redefstyles}{%
  \PassOptionsToPackage{all}{glossaries-extra-stylemods}%
  \RequirePackage{glossaries-extra-stylemods}%
}%
}%
{%
\renewcommand*{\@glsxtr@redefstyles}{}%
\@for\@glsxtr@tmp:=#1\do{%
  \IfFileExists{glossary-\@glsxtr@tmp.sty}%
  {%
    \eappto\@glsxtr@redefstyles{%
      \noexpand\RequirePackage{glossary-\@glsxtr@tmp}}%
    }%
  {%
    \PackageError{glossaries-extra}%
    {Glossaries style package ‘glossary-\@glsxtr@tmp.sty’
     doesn’t exist (did you mean to use the ‘style’ key?)}%
    {The list of values (#1) in the ‘stylemods’ key should
     match the glossary-xxx.sty files provided with
     glossaries.sty}%
  }%
}%
\appto\@glsxtr@redefstyles{\RequirePackage{glossaries-extra-stylemods}[=v1.48]}%
}
}%
}
\newcommand*{\@glsxtr@do@style}{%
\define@key{glossaries-extra.sty}{style}{%
\renewcommand*{\@glsxtr@do@style}{%
  \setkeys{glossaries.sty}{style={#1}}%
  \setglossarystyle{#1}%
}%
}%
}
\newcommand*{\@glsxtr@inc@wrglossaryctr}[1]{%
\newcommand*{\GlsXtrInternalLocationHyperlink}[3]{%
  \glsxtrhyperlink{#1#2#3}{#3}%
}
\newcommand*{\@glsxtr@wrglossary@locationhyperlink}[3]{%
  \pageref{wrglossary.#3}%
}
\@glsxtr@declareoption{indexcounter}{%
  \glsxtr@doooption{counter=wrglossary}%
  \ifundef\c@wrglossary
  {%
    \newcounter{wrglossary}%
    \renewcommand{\thewrglossary}{\arabic{wrglossary}}%
  }%
  {}%
}
\renewcommand*{\@glsxtr@inc@wrglossaryctr}[1]{%
  \ifdefstring\@gls@counter{wrglossary}%

```

```

    {%
      \refstepcounter{wrglossary}%
      \label{wrglossary.\thewrglossary}%
    }%
  }%
}
\renewcommand*{\GlsXtrInternalLocationHyperlink}[3]{%
  \ifdefstring\glsentrycounter{wrglossary}%
  {%
    \@glsxtr@wrglossary@locationhyperlink{##1}{##2}{##3}%
  }%
  {\glsxtrhyperlink{##1##2##3}{##3}}%
}%
}
\newcommand*{\@glsxtrwrglossmark}{}
\newcommand*{\@glsxtrwrglossmark}{}
\AtBeginDocument{\renewcommand*{\@glsxtrwrglossmark}{\@glsxtrwrglossmark}}
\newcommand*{\glsxtrwrglossmark}{\ensuremath{\cdot}}
\newcommand\@glsxtr@doshowtarget[2]{#2}
\define@choicekey{glossaries-extra.sty}{debug}
[\@glsxtr@debugval\@glsxtr@debugnr]%
{true,false,showtargets,showwrgloss,all,showaccsupp}[true]{%
  \ifcase\@glsxtr@debugnr\relax % true
    \glsxtr@doooption{debug=true}%
    \renewcommand*{\@glsxtrwrglossmark}{}%
  \or % false
    \glsxtr@doooption{debug=false}%
    \renewcommand*{\@glsxtrwrglossmark}{}%
    \let\@glsxtr@doshowtarget\@secondoftwo
  \or % showtargets
    \glsxtr@doooption{debug=showtargets}%
    \def\@glsxtr@doshowtarget{\@glsxtrshowtargetleft}%
  \or % showwrgloss
    \glsxtr@doooption{debug=true}%
    \renewcommand*{\@glsxtrwrglossmark}{\glsxtrwrglossmark}%
  \or % all
    \glsxtr@doooption{debug=showtargets,debug=showaccsupp}%
    \renewcommand*{\@glsxtrwrglossmark}{\glsxtrwrglossmark}%
    \def\@glsxtr@doshowtarget{\@glsxtrshowtargetleft}%
  \or % showaccsupp
    \glsxtr@doooption{debug=showaccsupp}%
  \fi
}
\newcommand*{\glsxtrshowtargetouter}{\glsshowtargetouter}
\newcommand*{\glsxtrshowtargetinner}[1]{\glsshowtargetinner{#1}}
\newcommand{\@glsxtrshowtargetleft}[2]{\@glsshowtarget{#1}#2\@glsxtrshowtargetmark}%
\newcommand{\@glsxtrshowtargetright}[2]{\@glsxtrshowtargetmark#2\@glsshowtarget{#1}}%
\newcommand{\@glsxtrshowtargetmark}{}%
\define@choicekey{glossaries-extra.sty}{showtargets}
[\@glsxtr@showtargetsval\@glsxtr@showtargetsnr]%

```

```

{left,right,innerleft,inerright,annoteleft,annoteright}%
{%
\glxtr@doooption{debug=showtargets}%
\ifcase\@glxtr@showtargets\relax
\def\@glxtr@doshowtarget{\@glxtr@showtargetleft}%
\def\glxtr@showtargetouter{\glsshowtargetouter}%
\def\glxtr@showtargetinner{\glsshowtargetinner}%
\let\@glxtr@showtargetmark\empty
\or
\def\@glxtr@doshowtarget{\@glxtr@showtargetright}%
\def\glxtr@showtargetouter{\glsshowtargetouter}%
\def\glxtr@showtargetinner{\glsshowtargetinner}%
\let\@glxtr@showtargetmark\empty
\or
\def\@glxtr@doshowtarget{\@glxtr@showtargetleft}%
\def\glxtr@showtargetouter{\glxtr@showtargetinner}%
\def\glxtr@showtargetinner{\glsshowtargetinnersymleft}%
\let\@glxtr@showtargetmark\empty
\or
\def\@glxtr@doshowtarget{\@glxtr@showtargetright}%
\def\glxtr@showtargetouter{\glxtr@showtargetinner}%
\def\glxtr@showtargetinner{\glsshowtargetinnersymright}%
\let\@glxtr@showtargetmark\empty
\or
\def\@glxtr@doshowtarget{\@glxtr@showtargetleft}%
\def\glxtr@showtargetouter{\glxtr@showtargetinner}%
\def\glxtr@showtargetinner{\glsshowtargetinnersymleft}%
\def\@glxtr@showtargetmark{\@glsshowtargetmarkfmt\glxtr@showtargetsymbolright}%
\or
\def\@glxtr@doshowtarget{\@glxtr@showtargetright}%
\def\glxtr@showtargetouter{\glxtr@showtargetinner}%
\def\glxtr@showtargetinner{\glsshowtargetinnersymright}%
\def\@glxtr@showtargetmark{\@glsshowtargetmarkfmt\glxtr@showtargetsymbolleft}%
\fi
}
\DeclareOptionX*{%
\expandafter\glxtr@doooption\expandafter{\CurrentOption}}
\ProcessOptionsX
\RequirePackage{glossaries}
\@glxtr@doaccsupp
\@glxtr@doloadprefix
\@glxtr@defpostpunc
\def\glsdoshowtarget{\@glxtr@doshowtarget}
\newcommand{\glxtr@showtargetsymbolright}{\tiny$\triangleleft$}%
\newcommand{\glxtr@showtargetsymbolleft}{\tiny$\triangleright$}%
\providecommand*{\glsshowtargetinner}[1]{\glsshowtargetfont [1]}
\providecommand*{\glsshowtargetfont}{\ttfamily\footnotesize}
\newcommand*{\glsshowtargetinnersymleft}[1]{%
\glsshowtargetinner{#1}\allowbreak\glxtr@showtargetsymbolleft}
\newcommand*{\glsshowtargetinnersymright}[1]{%

```

```

\glxtrshowtargetsymbolright\allowbreak\glsshowtargetinner{#1}}
\providecommand*{\glsshowtargetouter}[1]{%
\glsshowtargetsymbol\marginpar{\glsshowtargetsymbol\glsshowtargetfont #1}}
\providecommand*{\@glsshowtarget}[1]{%
\def\glsshowtarget#1{%
\glxtrtitleorpdforheading
{%
\ifmode
\nfss@text{\glxtrshowtargetinner{#1}}%
\else
\ifinner
\glxtrshowtargetinner{#1}%
\else
\glxtrshowtargetouter{#1}%
\fi
\fi
}%
{[#1]}%
{\protect\glsshowtargetinner{#1}}}%
}
\newcommand*{\@glsshowtargetmarkfmt}[1]{%
\glxtrtitleorpdforheading
{%
\ifmode \nfss@text{#1}\else #1\fi
}%
}%
{\ifmode \nfss@text{#1}\else #1\fi}%
}
\let\@glxtr@org@doseeglossary\@do@seeglossary
\newcommand*{\@glxtr@doseeglossary}[2]{%
\glsdoifexists{#1}%
{%
\@glxtrwrglossmark
\@glxtr@org@doseeglossary{#1}{#2}%
}%
}
\newcommand*{\@glxtr@dosee@alsoindex@glossary}[2]{%
\@glxtr@recordsee{#1}{#2}%
\@glxtr@doseeglossary{#1}{#2}%
}
\let\@glxtr@org@gloautosee\@glo@autosee
\if@glxtr@autoseeindex
\else
\ifdef\@glxtr@org@gloautosee
{%
{\PackageError{glossaries-extra}{‘autoseeindex=false’ package
option requires at least v4.30 of glossaries.sty}%
{You need to update the glossaries.sty package}%
}
\fi

```

```

\ifdef\@glo@autosee
{%
  \renewcommand*{\@glo@autosee}{%
    \if@glxtr@autoseeindex\@glxtr@org@gloautosee\fi}%
}%
{}
\renewcommand*{\gls@checkseeallowed}{%
  \if@glxtr@autoseeindex\@gls@see@noindex\fi
}
\@glxtr@abbreviationsdef
\let\@glxtr@abbreviationsdef\relax
\@glxtr@setupshortcuts
\@glxtr@redef@for@gl@sentries
\renewcommand{\glxtr@doption}[1]{\setupglossaries{#1}}%
\disable@keys{glossaries-extra.sty}{accsupp}
\newcommand*{\glossariesextrasetup}[1]{%
  \let\glxtr@setup@record\relax
  \let\@glxtr@setupshortcuts\relax
  \let\@glxtr@redef@for@gl@sentries\relax
  \let\@glxtr@doloadprefix\relax
  \setkeys{glossaries-extra.sty}{#1}%
  \@glxtr@abbreviationsdef
  \let\@glxtr@abbreviationsdef\relax
  \@glxtr@setupshortcuts
  \glxtr@setup@record
  \@glxtr@redef@for@gl@sentries
  \@glxtr@doloadprefix
}
\let\glxtr@org@@do@wrglossary\@do@wrglossary
\newcommand*{\glxtr@@do@wrglossary}[1]{%
  \@glxtrwrglossmark
  \glxtr@inc@wrglossaryctr{#1}%
  \glxtr@org@@do@wrglossary{#1}%
}
\let\glxtr@saveentrycounter\@gls@saveentrycounter
\let\@gls@saveentrycounter\glxtr@indexonly@saveentrycounter
\renewcommand*{\@gls@getcounterprefix[2]{%
  \protected@edef\@gls@thisloc{#1}\protected@edef\@gls@thisHloc{#2}%
  \ifx\@gls@thisloc\@gls@thisHloc
    \def\@glo@counterprefix{}%
  \else
    \def\@gls@get@counterprefix##1.#1##2\end@getprefix{%
      \def\@glo@tmp{##2}%
      \ifx\@glo@tmp\@empty
        \def\@glo@counterprefix{}%
      \else
        \def\@glo@counterprefix{##1}%
      \fi
    }%
    \@gls@get@counterprefix#2.#1\end@getprefix

```

```

\ifx\@glo@counterprefix\@empty
\ifx\@glsxtr@record@setting\@glsxtr@record@setting@nameref
\else
\GlossariesExtraWarning{Hyper target ‘#2’ can’t be formed by
prefixing^^Jlocation ‘#1’. You need to modify the
definition of \string\theH\@gls@counter^^Jotherwise you
will get the warning: “‘name{\@gls@counter.#1}’ has been^^J
referenced but does not exist”%
\ifx\@glsxtr@record@setting\@glsxtr@record@setting@only
. You may want to consider using record=nameref instead%
\fi}%
\fi
\fi
\fi
}
\newcommand*{\@glsxtrdialecthook}{}
\glsxtr@setup@record
\AtBeginDocument{%
\disable@keys{glossaries-extra.sty}{abbreviations,docdef,record}%
\def\@glsxtrundeftag{\glsxtrundeftag}%
}
\newcommand*{\GlsXtrIfUnusedOrUndefined}[3]{%
\ifglentryexists{#1}%
{\ifbool{glo@\glsdetoklabel{#1}@flag}{#3}{#2}}%
{#2}%
}
\ifdef\s@ifglossaryexists
{}
{
\renewcommand{\ifglossaryexists}{%
\@ifstar\s@ifglossaryexists\@ifglossaryexists
}
\newcommand{\@ifglossaryexists}[3]{%
\ifcsundef{@glotype@#1@out}{#3}{#2}%
}
\newcommand{\s@ifglossaryexists}[3]{%
\ifcsundef{glolist@#1}{#3}{#2}%
}
}
}
\newcommand{\glsxtrifemptyglossary}[3]{%
\ifcsdef{glolist@#1}%
{%
\ifcsstring{glolist@#1}{,}{#2}{#3}%
}%
{%
\glsxtrundefaction{Glossary type ‘#1’ doesn’t exist}{}%
#2%
}%
}
}
\newcommand*{\glsxtrifkeydefined}[3]{%

```

```

\key@ifundefined{glossentry}{#1}{#3}{#2}%
}
\newcommand*{\glxstrprovidestoragekey}{%
  \ifstar\@glxstrprovide@storagekey\@glxstrprovide@storagekey
}
\newcommand*{\@glxstrprovide@storagekey}[3]{%
  \key@ifundefined{glossentry}{#1}%
  {%
    \define@key{glossentry}{#1}{\csdef{@glo@#1}{##1}}%
    \appto\@gls@keymap{, {#1}{#1}}%
    \appto\@newglossaryentryprehook{\csdef{@glo@#1}{#2}}%
    \appto\@newglossaryentryposthook{%
      \letcs{@glo@tmp}{@glo@#1}%
      \gls@assign@field{#2}{\@glo@label}{#1}{\@glo@tmp}%
    }%
    \ifblank{#3}
    {}%
    {%
      \newcommand*{#3}[1]{\@gls@entry@field{##1}{#1}}%
    }%
  }%
  {%
    \ifblank{#3}
    {}%
    {%
      \providecommand*{#3}[1]{\@gls@entry@field{##1}{#1}}%
    }%
  }%
}
\newcommand*{\s@glxstrprovide@storagekey}[1]{%
  \key@ifundefined{glossentry}{#1}%
  {%
    \expandafter\newcommand\expandafter*\expandafter
    {\csname gls@assign@#1@field\endcsname}[2]{%
      \@gls@expand@field{##1}{#1}{##2}%
    }%
  }%
  {}%
  \@glxstrprovide@addstoragekey{#1}%
}
\newcommand{\GlsXtrFmtField}{useri}
\newcommand{\GlsXtrFmtDefaultOptions}{noindex}
\newrobustcmd*{\glxstrfmt}{\@ifstar\s@glxstrfmt\@glxstrfmt}
\newcommand*{\@glxstrfmt}[3][\@glxstrfmt]{#1}{#2}{#3}{}}
\newcommand*{\s@glxstrfmt}[3][\@glxstrfmt]{#1}{#2}{#3}{}}
\new@ifnextchar[{\s@glxstrfmt}{#1}{#2}{#3}}{
  {\@glxstrfmt}{#1}{#2}{#3}{}}%
}
\def\s@glxstrfmt#1#2#3[#4]{\@glxstrfmt{#1}{#2}{#3}{#4}}
\newcommand*{\@glxstrfmt}[4]{%

```



```

\begingroup
\def\glslabel{#2}%
\glsdoifexistsordo{#2}%
{%
\ifglshasfield{\GlsXtrFmtField}{#2}%
{%
\let\do@glsl@link@checkfirsthyper\relax
\expandafter\@glsl@link\expandafter[\GlsXtrFmtDefaultOptions,#1]{#2}%
{\glstrfmtdisplay{\glscurrentfieldvalue}{#3}{#4}}%
}%
{\glstrfmtdisplay{@firstofone}{#3}{#4}}%
}%
{%
\begingroup
\@glsl@setdefault@glslink@opts
\setkeys{glslink}{\GlsXtrFmtDefaultOptions,#1}%
\ifKV@glslink@noindex\else\glssadd{#2}\fi
\endgroup
\glstrfmtdisplay{@firstofone}{#3}{#4}%
}%
\endgroup
}
\newcommand{\glstrfmtdisplay}[3]{\csuse{#1}{#2}#3}
\ifdef\texorpdfstring
{
\newcommand*{\glxtrententryfmt}[2]{%
\texorpdfstring{\@glxtrententryfmt{#1}{#2}}{\glstrpdfentryfmt{#1}{#2}}%
}
}
{
\newcommand*{\glxtrententryfmt}{\@glxtrententryfmt}
}
\newcommand*{\glstrpdfentryfmt}[2]{#2}
\newrobustcmd*{\@glxtrententryfmt}[2]{%
{%
\protected@edef\glslabel{#1}%
\glsdoifexistsordo{#1}%
{%
\ifglshasfield{\GlsXtrFmtField}{#1}%
{%
\csuse{\glscurrentfieldvalue}{#2}%
}%
{#2}%
}%
{#2}%
}%
}
\newcommand*{\glstrfieldlistadd}[3]{%
\listcsadd{glo@glsdetoklabel{#1}@#2}{#3}%
}

```

```

\newcommand*\glstrfieldlistgadd}[3]{%
  \listcsgadd{glo@\glstetoklabel{#1}@#2}{#3}%
}
\newcommand*\glstrfieldlistseadd}[3]{%
  \listcseadd{glo@\glstetoklabel{#1}@#2}{#3}%
}
\newcommand*\glstrfieldlistxadd}[3]{%
  \listcsxadd{glo@\glstetoklabel{#1}@#2}{#3}%
}
\newcommand*\glstrfielddolistloop}[2]{%
  \dolistcsloop{glo@\glstetoklabel{#1}@#2}%
}
\newcommand*\glstrfieldforlistloop}[3]{%
  \forlistcsloop{#3}{glo@\glstetoklabel{#1}@#2}%
}
\newrobustcmd*\glstrfieldformatlist}[2]{%
  \begingroup
  \def\@dtl@formatlist@itemsep{}%
  \def\@dtl@formatlist@lastitem{}%
  \def\@dtl@formatlist@prelastitem{}%
  \def\@dtl@formatlist@prelastitemsep{}%
  \forlistcsloop{\@dtl@formatlist@handler}{glo@\glstetoklabel{#1}@#2}%
  \@dtl@formatlist@prelastitem\@dtl@formatlist@lastitem
  \endgroup
}
\newcommand*\glstrfieldifinlist}[5]{%
  \ifinlistcs{#3}{glo@\glstetoklabel{#1}@#2}{#4}{#5}%
}
\newcommand*\glstrfieldxifinlist}[5]{%
  \xifinlistcs{#3}{glo@\glstetoklabel{#1}@#2}{#4}{#5}%
}
\newcommand*\glstrforcsvfield{%
  \@ifstar\s@glstrforcsvfield\@glstrforcsvfield
}
\newcommand*\@glstrforcsvfield}[3]{%
  \@glstrifhasfield{#2}{#1}%
  {%
    \let\glstrendfor\@endfortrue
    \@for\@glstr@label:=\glscurrentfieldvalue\do
      {\expandafter#3\expandafter{\@glstr@label}}}%
  }%
}
\newcommand*\s@glstrforcsvfield}[3]{%
  \s@glstrifhasfield{#2}{#1}%
  {%
    \let\glstrendfor\@endfortrue
    \@for\@glstr@label:=\glscurrentfieldvalue\do
      {\expandafter#3\expandafter{\@glstr@label}}}%
  }%
}

```

```

\newrobustcmd*{\glstriffieldformatcsvlist}[2]{%
  \@glstrifhasfield{#2}{#1}%
  {\@dtlformatlist\glscurrentfieldvalue}%
  }%
}
\newcommand*{\GlsXtrIfFieldValueInCsvList}{%
  \ifstar\s@GlsXtrIfFieldValueInCsvList\@GlsXtrIfFieldValueInCsvList
}
\newcommand*{\@GlsXtrIfFieldValueInCsvList}[5]{%
  \@glstrifhasfield{#2}{#1}%
  {%
    \expandafter\DTLifinlist\expandafter{\glscurrentfieldvalue}%
    {#3}{#4}{#5}%
  }%
  {#5}%
}
\newcommand*{\s@GlsXtrIfFieldValueInCsvList}[5]{%
  \s@glstrifhasfield{#2}{#1}%
  {%
    \expandafter\DTLifinlist\expandafter{\glscurrentfieldvalue}%
    {#3}{#4}{#5}%
  }%
  {#5}%
}
\newcommand*{\GlsXtrIfValueInFieldCsvList}{%
  \ifstar\s@GlsXtrIfValueInFieldCsvList\@GlsXtrIfValueInFieldCsvList
}
\newcommand*{\@GlsXtrIfValueInFieldCsvList}[5]{%
  \@glstrifhasfield{#2}{#1}%
  {%
    \DTLifinlist{#3}{\glscurrentfieldvalue}{#4}{#5}%
  }%
  {#5}%
}
\newcommand*{\s@GlsXtrIfValueInFieldCsvList}[5]{%
  \s@glstrifhasfield{#2}{#1}%
  {%
    \DTLifinlist{#3}{\glscurrentfieldvalue}{#4}{#5}%
  }%
  {#5}%
}
\newcommand*{\xGlsXtrIfValueInFieldCsvList}{%
  \ifstar\s@xGlsXtrIfValueInFieldCsvList\@xGlsXtrIfValueInFieldCsvList
}
\newcommand*{\@xGlsXtrIfValueInFieldCsvList}[5]{%
  \@glstrifhasfield{#2}{#1}%
  {%
    \protected@edef\@gls@tmp{#3}%
    \expandafter\DTLifinlist\expandafter{\@gls@tmp}{\glscurrentfieldvalue}{#4}{#5}%
  }%
}

```

```

{#5}%
}
\newcommand*{\s@GlsXtrIfValueInFieldCsvList}[5]{%
\s@glxtrifhasfield{#2}{#1}%
{%
\protected@edef\@glstmp{#3}%
\expandafter\DTLifinlist\expandafter{\@glstmp}{\glscurrentfieldvalue}{#4}{#5}%
}%
{#5}%
}
\newrobustcmd{\glxtrifhasfield}{%
\@ifstar{\s@glxtrifhasfield}{\@glxtrifhasfield}%
}
\newcommand{\@glxtrifhasfield}[4]{%
{\s@glxtrifhasfield{#1}{#2}{#3}{#4}}%
}
\newcommand{\s@glxtrifhasfield}[4]{%
\letcs{\glscurrentfieldvalue}{glo@\glsetoklabel{#2}@#1}%
\ifundef\glscurrentfieldvalue
{#4}%
{%
\ifdefempty\glscurrentfieldvalue{#4}{#3}%
}%
}
}
\newcommand{\GlsXtrIfFieldNonZero}{%
\@ifstar\s@GlsXtrIfFieldNonZero\@GlsXtrIfFieldNonZero
}
\newcommand{\@GlsXtrIfFieldNonZero}[4]{%
\@GlsXtrIfFieldCmpNum{#1}{#2}{=}{0}{#4}{#3}%
}
\newcommand{\s@GlsXtrIfFieldNonZero}[4]{%
\s@GlsXtrIfFieldCmpNum{#1}{#2}{=}{0}{#4}{#3}%
}
\newcommand{\GlsXtrIfFieldEqNum}{%
\@ifstar\s@GlsXtrIfFieldEqNum\@GlsXtrIfFieldEqNum
}
\newcommand{\@GlsXtrIfFieldEqNum}[5]{%
\@GlsXtrIfFieldCmpNum{#1}{#2}{=}{#3}{#4}{#5}%
}
\newcommand{\s@GlsXtrIfFieldEqNum}[5]{%
\s@GlsXtrIfFieldCmpNum{#1}{#2}{=}{#3}{#4}{#5}%
}
\newcommand{\GlsXtrIfFieldCmpNum}{%
\@ifstar\s@GlsXtrIfFieldCmpNum\@GlsXtrIfFieldCmpNum
}
\newcommand{\@GlsXtrIfFieldCmpNum}[6]{%
{%
\letcs{\glscurrentfieldvalue}{glo@\glsetoklabel{#2}@#1}%
\ifundef\glscurrentfieldvalue
{\def\glscurrentfieldvalue{0}}%
}

```

```

    {%
    \ifdefempty\glscurrentfieldvalue
    {\def\glscurrentfieldvalue{0}}%
    {}%
    }%
    \ifnum\glscurrentfieldvalue#3#4\relax #5\else #6\fi
  }%
}
\newcommand{\s@GlsXtrIfFieldCmpNum}[6]{%
  \letcs{\glscurrentfieldvalue}{glo@\glsdetoklabel{#2}@#1}%
  \ifundef\glscurrentfieldvalue
  {\def\glscurrentfieldvalue{0}}%
  {%
  \ifdefempty\glscurrentfieldvalue
  {\def\glscurrentfieldvalue{0}}%
  {}%
  }%
  \ifnum\glscurrentfieldvalue#3#4\relax #5\else #6\fi
}
\newcommand{\GlsXtrIfFieldUndef}[2]{%
  \ifcsundef{glo@\glsdetoklabel{#2}@#1}%
}
\newcommand*{\glsxtrusefield}[2]{%
  \@gls@entry@field{#1}{#2}%
}
\ifdef\texorpdfstring
{
  \newcommand*{\Glsxtrusefield}[2]{%
    \texorpdfstring
    {\@Gls@entry@field{#1}{#2}}
    {\@gls@entry@field{#1}{#2}}%
  }
}
{
  \newcommand*{\Glsxtrusefield}[2]{%
    \@Gls@entry@field{#1}{#2}%
  }
}
\ifdef\texorpdfstring
{
  \newcommand*{\GLSxtrusefield}[2]{%
    \texorpdfstring
    {\glsdoifexists{#1}{\mfirstucMakeUppercase{\@gls@entry@field{#1}{#2}}}}%
    {\@gls@entry@field{#1}{#2}}%
  }
}
{
  \newcommand*{\GLSxtrusefield}[2]{%
    \glsdoifexists{#1}{\mfirstucMakeUppercase{\@gls@entry@field{#1}{#2}}}%
  }
}

```

```

}
\newcommand*{\glstrentryparentname}[1]{%
  \ifcsdef{glo@\glstdetoklabel{#1}@parent}%
    {\csuse{glo@\csuse{glo@\glstdetoklabel{#1}@parent}@name}}%
  }%
}
\newcommand*{\glstrdeffield}[2]{\csdef{glo@\glstdetoklabel{#1}@#2}}
\newcommand*{\glstrdeffield}[2]{\protected@csdef{glo@\glstdetoklabel{#1}@#2}}
\newcommand*{\glstrapptocsvfield}[3]{%
  \ifcsdef{glo@\glstdetoklabel{#1}@#2}%
    {\csappto{glo@\glstdetoklabel{#1}@#2}{, #3}}%
    {\csdef{glo@\glstdetoklabel{#1}@#2}{#3}}%
}
\newcommand*{\glstrsetfieldifexists}[3]{\glstdoifexists{#1}{#3}}
\newrobustcmd*{\GlsXtrSetField}[3]{%
  \glstrsetfieldifexists{#1}{#2}%
  {\csdef{glo@\glstdetoklabel{#1}@#2}{#3}}%
}
\newrobustcmd*{\GlsXtrLetField}[3]{%
  \glstrsetfieldifexists{#1}{#2}%
  {\cslet{glo@\glstdetoklabel{#1}@#2}{#3}}%
}
\newrobustcmd*{\csGlsXtrLetField}[3]{%
  \glstrsetfieldifexists{#1}{#2}%
  {\csletcs{glo@\glstdetoklabel{#1}@#2}{#3}}%
}
\newrobustcmd*{\GlsXtrLetFieldToField}[4]{%
  \glstrsetfieldifexists{#1}{#2}%
  {\csletcs{glo@\glstdetoklabel{#1}@#2}{glo@\glstdetoklabel{#3}@#4}}%
}
\newrobustcmd*{\gGlsXtrSetField}[3]{%
  \glstrsetfieldifexists{#1}{#2}%
  {\csgdef{glo@\glstdetoklabel{#1}@#2}{#3}}%
}
\newrobustcmd*{\xGlsXtrSetField}[3]{%
  \glstrsetfieldifexists{#1}{#2}%
  {\protected@csxdef{glo@\glstdetoklabel{#1}@#2}{#3}}%
}
\newrobustcmd*{\eGlsXtrSetField}[3]{%
  \glstrsetfieldifexists{#1}{#2}%
  {\protected@csedef{glo@\glstdetoklabel{#1}@#2}{#3}}%
}
\newcommand*{\GlsXtrIfFieldEqStr}{%
  \@ifstar\sGlsXtrIfFieldEqStr\@GlsXtrIfFieldEqStr
}
\newrobustcmd*{\@GlsXtrIfFieldEqStr}[5]{%
  \@glstrifhasfield{#1}{#2}%
  {%
    \ifdefstring{\glscurrentfieldvalue}{#3}{#4}{#5}%
  }%
}

```

```

    {#5}%
}
\newrobustcmd*{\s@GlsXtrIfFieldEqStr}[5]{%
  \s@glstrifhasfield{#1}{#2}%
  {%
    \ifdefstring{\glscurrentfieldvalue}{#3}{#4}{#5}%
  }%
  {#5}%
}
\newcommand*{\GlsXtrIfFieldEqXpStr}{%
  \ifstar\s@GlsXtrIfFieldEqXpStr\@GlsXtrIfFieldEqXpStr
}
\newrobustcmd*{\@GlsXtrIfFieldEqXpStr}[5]{%
  \@glstrifhasfield{#1}{#2}%
  {%
    \protected@edef\@gls@tmp{#3}%
    \ifdefequal{\glscurrentfieldvalue}{\@gls@tmp}{#4}{#5}%
  }%
  {#5}%
}
\newrobustcmd*{\s@GlsXtrIfFieldEqXpStr}[5]{%
  \s@glstrifhasfield{#1}{#2}%
  {%
    \protected@edef\@gls@tmp{#3}%
    \ifdefequal{\glscurrentfieldvalue}{\@gls@tmp}{#4}{#5}%
  }%
  {#5}%
}
\newcommand*{\GlsXtrIfXpFieldEqXpStr}{%
  \ifstar\s@GlsXtrIfXpFieldEqXpStr\@GlsXtrIfXpFieldEqXpStr
}
\newrobustcmd*{\@GlsXtrIfXpFieldEqXpStr}[5]{%
  \@glstrifhasfield{#1}{#2}%
  {%
    \protected@edef\@gls@tmp{\glscurrentfieldvalue}%
    \let\glscurrentfieldvalue\@gls@tmp
    \protected@edef\@gls@tmp{#3}%
    \ifdefequal{\glscurrentfieldvalue}{\@gls@tmp}{#4}{#5}%
  }%
  {#5}%
}
\newrobustcmd*{\s@GlsXtrIfXpFieldEqXpStr}[5]{%
  \s@glstrifhasfield{#1}{#2}%
  {%
    \protected@edef\@gls@tmp{\glscurrentfieldvalue}%
    \let\glscurrentfieldvalue\@gls@tmp
    \protected@edef\@gls@tmp{#3}%
    \ifdefequal{\glscurrentfieldvalue}{\@gls@tmp}{#4}{#5}%
  }%
  {#5}%
}

```

```

}
\ifdef\foreignlanguage
{
  \ifdef\GetTrackedDialectFromLanguageTag
  {
    \newcommand{\GlsXtrForeignText}[2]{%
      \let\@glstr@org@currentfieldvalue\glscurrentfieldvalue
      \glstrifhasfield{\GlsXtrForeignTextField}{#1}%
      {%
        \expandafter\GetTrackedDialectFromLanguageTag\expandafter
        {\glscurrentfieldvalue}{\@glstr@dialect}%
        \let\@glstr@locale\glscurrentfieldvalue
        \let\glscurrentfieldvalue\@glstr@org@currentfieldvalue
        \ifdefempty\@glstr@dialect
        {%
          \ifundef\TrackedDialectClosestSubMatch
          {%
            \GlossariesExtraWarning{Can't obtain dialect label
              (tracklang v1.3.6+ required)}%
          }%
          {\let\@glstr@dialect\TrackedDialectClosestSubMatch}%
        }%
        {%
          \ifdefempty\@glstr@dialect
          {%
            }%
          }%
          {%
            \ifcsundef{captions\@glstr@dialect}{}%
            {%
              \IfTrackedDialectHasMapping{\@glstr@dialect}%
              {%
                \edef\@glstr@dialect{%
                  \GetTrackedDialectToMapping{\@glstr@dialect}}%
                \ifcsundef{captions\@glstr@dialect}{}%
                {%
                  \ifcsundef{captions\@tracklang@lang}{}%
                  {%
                    \let\@glstr@dialect\@tracklang@lang
                  }%
                }%
              }%
            }%
            {%
              \ifcsundef{captions\@tracklang@lang}{}%
              {%
                \let\@glstr@dialect\@tracklang@lang
              }%
            }%
          }%
        }%
        \ifdefempty\@glstr@dialect

```



```

        {%
          \GlsXtrUnknownDialectWarning{\@glstr@locale}{\@tracklang@lang}%
          #2%
        }%
        {\foreignlanguage{\@glstr@dialect}{#2}}%
      }%
      {#2}% key not set
    }
  }
  {
    \newcommand{\GlsXtrForeignText}[2]{%
      \GlossariesExtraWarning{Can't encapsulate foreign text:
        tracklang v1.3.6+ required}%
      #2%
    }
  }
}
{
  \newcommand{\GlsXtrForeignText}[2]{#2}
}
\newcommand*{\GlsXtrForeignTextField}[userii]{
\newcommand*{\GlsXtrUnknownDialectWarning}[2]{%
  \GlossariesExtraWarning{Can't determine valid dialect label
    for locale '#1' (root language: #2)}%
}
\ifdef\GlsEntryCounterLabelPrefix
{%
  \newcommand*{\glstrpageref}[1]{%
    \ifglentrycounter
      \pageref{\GlsEntryCounterLabelPrefix\glsdetoklabel{#1}}%
    \else
      \ifglssubentrycounter
        \pageref{\GlsEntryCounterLabelPrefix\glsdetoklabel{#1}}%
      \else
        \gls{#1}%
      \fi
    \fi
  }
}%
{%
  \newcommand*{\glstrpageref}[1]{%
    \ifglentrycounter
      \pageref{glentry-\glsdetoklabel{#1}}%
    \else
      \ifglssubentrycounter
        \pageref{glentry-\glsdetoklabel{#1}}%
      \else
        \gls{#1}%
      \fi
    \fi
  }
}

```

```

    }
}%
\newcommand{\apptoglossarypreamble}[2][\glsdefaultttype]{%
  \ifcsdef{glolist@#1}%
  {%
    \ifcsundef{@glossarypreamble@#1}%
    {\csdef{@glossarypreamble@#1}{}}%
  }%
  \csappto{@glossarypreamble@#1}{#2}%
}%
{%
  \GlossariesExtraWarning{Glossary ‘#1’ is not defined}%
}%
}
\newcommand{\preglossarypreamble}[2][\glsdefaultttype]{%
  \ifcsdef{glolist@#1}%
  {%
    \ifcsundef{@glossarypreamble@#1}%
    {\csdef{@glossarypreamble@#1}{}}%
  }%
  \cspreto{@glossarypreamble@#1}{#2}%
}%
{%
  \GlossariesExtraWarning{Glossary ‘#1’ is not defined}%
}%
}
\ifdef\@gls@entry@field
{
  \renewcommand*{\@gls@entry@field}[2]{\csuse{glo@\glsdetoklabel{#1}@#2}}
}
{}
\renewcommand*{\ifglsused}[3]{%
  \glsdoifexists{#1}{\ifbool{glo@\glsdetoklabel{#1}@flag}{#2}{#3}}%
}
\renewcommand*{\longnewglossaryentry}{%
  \@ifstar\@glsxtr@s@longnewglossaryentry\@glsxtr@longnewglossaryentry
}
\newcommand{\@glsxtr@s@longnewglossaryentry}[3]{%
  \glsdoifnoexists{#1}%
  {%
    \bgroup
    \let\@org@newglossaryentryprehook\@newglossaryentryprehook
    \long\def\@newglossaryentryprehook{%
      \long\def\@glo@desc{#3}%
      \@org@newglossaryentryprehook
    }%
    \renewcommand*{\gls@assign@desc}[1]{%
      \global\cslet{glo@\glsdetoklabel{#1}@desc}{\@glo@desc}%
      \global\cslet{glo@\glsdetoklabel{#1}@descplural}{\@glo@descplural}%
    }
  }
}

```

```

        \gls@defglossaryentry{#1}{#2}%
    \egroup
}%
}
\newcommand{\@glsxtr@longnewglossaryentry}[3]{%
    \glsdoifnoexists{#1}%
    {%
        \bgroup
        \let\@org@newglossaryentryprehook\@newglossaryentryprehook
        \long\def\@newglossaryentryprehook{%
            \long\def\@glo@desc{#3\glsxtrpostlongdescription}%
            \@org@newglossaryentryprehook
        }%
        \renewcommand*\@gls@assign@desc[1]{%
            \global\cslet{glo@\glsdetoklabel{#1}@desc}{\@glo@desc}%
            \global\cslet{glo@\glsdetoklabel{#1}@descplural}{\@glo@descplural}%
        }
        \gls@defglossaryentry{#1}{#2}%
    \egroup
}%
}
\newcommand*\@glsxtrpostlongdescription{\leavevmode\unskip\nopostdesc}
\renewcommand{\@newignoredglossary}{%
    \@ifstar\glsxtr@s@newignoredglossary\glsxtr@org@newignoredglossary
}
\newcommand*\@glsxtr@org@newignoredglossary[1]{%
    \ifcsdef{glolist@#1}
    {%
        \glsxtrundefaction{Glossary type ‘#1’ already exists}{}%
    }%
    {%
        \ifdefempty\@ignored@glossaries
        {%
            \protected@edef\@ignored@glossaries{#1}%
        }%
        {%
            \protected@eappto\@ignored@glossaries{, #1}%
        }%
        \csgdef{glolist@#1}{,}%
        \ifcsundef{gls@#1@entryfmt}%
        {%
            \defglsentryfmt[1]{\glsentryfmt}%
        }%
        {}%
        \ifdefempty\@gls@nohyperlist
        {%
            \renewcommand*\@gls@nohyperlist{#1}%
        }%
        {%
            \protected@eappto\@gls@nohyperlist{, #1}%
        }%
    }%
}

```

```

    }%
  }%
}
\newcommand*{\glxtr@s@newignoredglossary}[1]{%
  \ifcsdef{glolist@#1}
  {%
    \glxtrundefaction{Glossary type ‘#1’ already exists}{}%
  }%
  {%
    \ifdefempty\@ignored@glossaries
    {%
      \protected@edef\@ignored@glossaries{#1}%
    }%
    {%
      \protected@eappto\@ignored@glossaries{,#1}%
    }%
    \csgdef{glolist@#1}{,}%
    \ifcsundef{gls@#1@entryfmt}%
    {%
      \defglssentryfmt[#1]{\glssentryfmt}%
    }%
    {}%
  }%
}
\glsifusetranslator
{%
  \renewcommand*{\glssettoctitle}[1]{%
    \ifcsdef{gls@tr@set@#1@toctitle}%
    {%
      \csuse{gls@tr@set@#1@toctitle}%
    }%
    {%
      \ifcsdef{@glotype@#1@title}%
      {\def\glossarytoctitle{\csname @glotype@#1@title\endcsname}}%
      {\def\glossarytoctitle{\glossarytitle}}%
    }%
  }%
}
{
  \renewcommand*{\glssettoctitle}[1]{%
    \ifcsdef{@glotype@#1@title}%
    {\def\glossarytoctitle{\csname @glotype@#1@title\endcsname}}%
    {\def\glossarytoctitle{\glossarytitle}}%
  }
}
\newcommand{\provideignoredglossary}{%
  \@ifstar\glxtr@s@provideignoredglossary\glxtr@provideignoredglossary
}
\newcommand*{\glxtr@provideignoredglossary}[1]{%
  \ifcsdef{glolist@#1}

```

```

{}%
{%
  \ifdefempty\@ignored@glossaries
  {%
    \protected@edef\@ignored@glossaries{#1}%
  }%
  {%
    \protected@eappto\@ignored@glossaries{, #1}%
  }%
  \csgdef{glolist@#1}{,}%
  \ifcsundef{gls@#1@entryfmt}%
  {%
    \defglsentryfmt[#1]{\glsentryfmt}%
  }%
  {}%
  \ifdefempty\@gls@nohyperlist
  {%
    \renewcommand*{\@gls@nohyperlist}{#1}%
  }%
  {%
    \protected@eappto\@gls@nohyperlist{, #1}%
  }%
}%
}
\newcommand*{\glsxtr@s@provideignoredglossary}[1]{%
  \ifcsdef{glolist@#1}
  {}%
  {%
    \ifdefempty\@ignored@glossaries
    {%
      \protected@edef\@ignored@glossaries{#1}%
    }%
    {%
      \protected@eappto\@ignored@glossaries{, #1}%
    }%
    \csgdef{glolist@#1}{,}%
    \ifcsundef{gls@#1@entryfmt}%
    {%
      \defglsentryfmt[#1]{\glsentryfmt}%
    }%
    {}%
  }%
}
\newcommand*{\glsxtr@copytoglossary}[2]{%
  \glsdoifexists{#1}%
  {%
    \ifcsdef{glolist@#2}
    {%
      \protected@eappto{glolist@#2}{#1,}%
    }%
  }%
}

```

```

    {%
      \glstrundefaction{Glossary type '#2' doesn't exist}{}%
    }%
  }%
}
\renewcommand{\glsdoifexists}[2]{%
  \ifglstryexists{#1}{#2}%
  {%
    \protected@edef\glslabel{\glsdetoklabel{#1}}%
    \glstrundefaction{Glossary entry '\glslabel'
      has not been defined}{You need to define a glossary entry before
      you can reference it.}%
  }%
}
\renewcommand{\glsdoifnoexists}[2]{%
  \ifglstryexists{#1}{%
    \glstrundefaction{Glossary entry '\glsdetoklabel{#1}'
      has already been defined}{}}{#2}%
}
\ifdef\glsdoifexistsordo
{%
  \renewcommand{\glsdoifexistsordo}[3]{%
    \ifglstryexists{#1}{#2}%
    {%
      \glstrundefaction{Glossary entry '\glsdetoklabel{#1}'
        has not been defined}{You need to define a glossary entry
        before you can use it.}%
      #3%
    }%
  }%
}
{%
  \glsxtr@warnonexistsordo\glsdoifexistsordo
  \newcommand{\glsdoifexistsordo}[3]{%
    \ifglstryexists{#1}{#2}%
    {%
      \glstrundefaction{Glossary entry '\glsdetoklabel{#1}'
        has not been defined}{You need to define a glossary entry
        before you can use it.}%
      #3%
    }%
  }%
}
\ifdef\doifglossarynoexistsordo
{%
  \renewcommand{\doifglossarynoexistsordo}[3]{%
    \ifglossaryexists*{#1}%
    {%
      \glstrundefaction{Glossary type '#1' already exists}{}%
      #3%
    }%
  }%
}

```

```

    }%
    {#2}%
  }%
}
{%
\glstr@warnonexistsordo\doifglossarynoexistsordo
\newcommand{\doifglossarynoexistsordo}[3]{%
  \ifglossaryexists*{#1}%
  {%
    \glstrundefaction{Glossary type ‘#1’ already exists}{}%
    #3%
  }%
  {#2}%
}%
}

\appto\newglossaryentryposthook{%
  \ifdefvoid\@glo@see
  {\csxdef{glo@\@glo@label @see}{}}%
  {%
    \csxdef{glo@\@glo@label @see}{\@glo@see}%
    \if\glstr@autoseeindex
    \glstr@autoindexcrossrefs
    \fi
  }%
}
\appto\@gls@keymap{,{see}{see}}
\newcommand*{\glstrusesee}[1]{%
  \glstoifexists{#1}%
  {%
    \letcs{\@glo@see}{glo\@glstoklabel{#1}@see}%
    \ifdefempty\@glo@see
    {}%
    {%
      \expandafter\glstr@usesee\@glo@see\end@glstr@usesee
    }%
  }%
}
\newcommand*{\glstr@usesee}[1][\@seenname]{%
  \@glstr@usesee{#1}%
}
\def\@glstr@usesee[#1]#2\end@glstr@usesee{%
  \glstruseseeformat{#1}{#2}%
}
\newcommand*{\glstruseseeformat}[2]{%
  \glseeformat{#1}{#2}{}%
}
\renewcommand*{\glseeitemformat}[1]{%
  \ifglshashshort{#1}{\glsfmttext{#1}}{\glsfmtname{#1}}%
}

```

```

\newcommand*{\glxtrhiername}[1]{%
  \glsdoifexists{#1}%
  {%
    \glxtrifhasfield{parent}{#1}%
    {\glxtrhiername{\glscurrentfieldvalue}\glxtrhiernamesep}%
    {}%
    \ifglshasshort{#1}{\glsfmtext{#1}}{\glsfmtname{#1}}%
  }%
}
\newcommand*{\Glsxtrhiername}[1]{%
  \glsdoifexists{#1}%
  {%
    \glxtrifhasfield{parent}{#1}%
    {%
      \Glsxtrhiername{\glscurrentfieldvalue}\glxtrhiernamesep
      \ifglshasshort{#1}{\glsfmtext{#1}}{\glsfmtname{#1}}%
    }%
    {\ifglshasshort{#1}{\Glsfmtext{#1}}{\Glsfmname{#1}}}%
  }%
}
\newcommand*{\GlsXtrhiername}[1]{%
  \glsdoifexists{#1}%
  {%
    \glxtrifhasfield{parent}{#1}%
    {\GlsXtrhiername{\glscurrentfieldvalue}\glxtrhiernamesep}%
    {}%
    \ifglshasshort{#1}{\Glsfmtext{#1}}{\Glsfmname{#1}}%
  }%
}
\newcommand*{\GLSxtrhiername}[1]{%
  \glsdoifexists{#1}%
  {%
    \glxtrifhasfield{parent}{#1}%
    {%
      \GLSxtrhiername{\glscurrentfieldvalue}\glxtrhiernamesep
      \ifglshasshort{#1}{\glsfmtext{#1}}{\glsfmtname{#1}}%
    }%
    {\ifglshasshort{#1}{\GLSfmtext{#1}}{\GLSfmname{#1}}}%
  }%
}
\newcommand*{\GLSXTRhiername}[1]{%
  \glsdoifexists{#1}%
  {%
    \glxtrifhasfield{parent}{#1}%
    {\GLSXTRhiername{\glscurrentfieldvalue}\glxtrhiernamesep}%
    {}%
    \ifglshasshort{#1}{\GLSfmtext{#1}}{\GLSfmname{#1}}%
  }%
}
\newcommand*{\glxtrhiernamesep}{\,\,\small$\triangleright$}\,}

```



```

\newcommand*{\glxtruseealso}[1]{%
  \glsdofexists{#1}%
  {%
    \letcs{\@glo@see}{glo\glsdetoklabel{#1}@seealso}%
    \ifdefempty\@glo@see
    {}%
    {%
      \expandafter\glxtruseealsoformat\expandafter{\@glo@see}%
    }%
  }%
}
\newcommand*{\glxtrusealias}[1]{%
  \glsdofexists{#1}%
  {%
    \letcs{\@glo@see}{glo\glsdetoklabel{#1}@alias}%
    \ifdefempty\@glo@see
    {}%
    {%
      \glxtruseeeformat{\seename}{\@glo@see}%
    }%
  }%
}
\newcommand*{\glxtruseealsoformat}[1]{%
  \glseeeformat[\seeealsoname]{#1}{}%
}
\newrobustcmd{\glxtrseelist}[1]{%
  \protected@edef\@glo@tmp{\noexpand\glseeelist{#1}}\@glo@tmp
}
\renewrobustcmd*{\glseeelist}[1]{%
  \let\@gls@dolast\relax
  \let\@gls@donext\relax
  \let\@glsseeitem\@glxtr@seefirstitem
  \let\@glsseelastsep\glseeelastsep
  \@for\@gls@thislabel:=#1\do{%
    \ifx\@xfor@nextelement\@nnil
      \@gls@dolast
    \else
      \@gls@donext
    \fi
    \expandafter\@glsseeitem\expandafter{\@gls@thislabel}%
    \let\@gls@dolast\@glsseelastsep
    \let\@gls@donext\glseeesep
    \let\@glsseeitem\@glxtr@seeitem
    \let\@glsseelastsep\glseeelastoxfordsep
  }%
}
\newcommand*{\@glxtr@seeitem}[1]{%
  \glxtrifmulti{#1}{\mglseeitem{#1}}{\glseeitem{#1}}%
}
\newcommand*{\@glxtr@seefirstitem}[1]{%

```

```

\glxtrifmulti{#1}{\mglseeefirstitem{#1}}{\glseeefirstitem{#1}}%
}
\newcommand*{\mglseeitem}[1]{%
\mglename[all={noindex},setup={hyper=allmain}]{#1}%
}
\newcommand*{\mglseeefirstitem}{\mglseeitem}
\newcommand*{\glseeefirstitem}{\glseeitem}
\newcommand*{\glseeelastoxfordsep}{\glseeelastsep}
\ifdef\alsoname
{\providecommand{\seealsoname}{\alsoname}}
{\providecommand{\seealsoname}{see also}}
\ifdef\@xdycrossrefhook
{
\appto\@xdycrossrefhook{%
\write\glswrite{(define-crossref-class \string"seealso\string"
:unverified )}%
\write\glswrite{(markup-crossref-list
:class \string"seealso\string"^^J\space\space\space
:open \string"\string\glxtruseealsoformat\glsopenbrace\string"
:close \string"\glsclosebrace\string")}%
}
\appto\@xdylocationclassorder{\space\string"seealso\string"}
\newrobustcmd*{\glxtrindexseealso}[2]{%
\ifx\@glxtr@record@setting\@glxtr@record@setting@alsoindex
\@glxtr@recordsee{#1}{#2}%
\fi
\glsdoifexists{#1}%
{%
\@@glxtrwrglossmark
\def\@gls@xref{#2}%
\@onelevel@sanitize\@gls@xref
\@gls@checkmkidxchars\@gls@xref
\gls@glossary{\csname glo@#1@type\endcsname}{%
(indexentry
:tkey (\csname glo@#1@index\endcsname)
:xref (\string"\@gls@xref\string")
:attr \string"seealso\string"
)
}%
}%
}
}
{
\newrobustcmd*{\glxtrindexseealso}{\glsee[\seealsoname]}
}
\ifdef\gls@set@xr@key
{
\define@key{glossentry}{alias}{%
\gls@set@xr@key{alias}{\@glo@alias}{#1}%
}
}

```

```

\define@key{glossentry}{seealso}{%
  \gls@set@xr@key{seealso}{\@glo@seealso}{#1}%
}
\appto\@gls@keymap{,{alias}{alias},{seealso}{seealso}}
\appto\@newglossaryentryprehook{\def\@glo@alias{}\def\@glo@seealso{}}%
\appto\@newglossaryentryposthook{%
  \ifdefvoid\@glo@seealso
    {\csxdef{glo@\@glo@label @seealso}{}}%
    {%
      \csxdef{glo@\@glo@label @seealso}{\@glo@seealso}%
      \ifglstr@autoindex
        \glstr@autoindexcrossrefs
      \fi
    }%
  \ifdefvoid\@glo@alias
    {\csxdef{glo@\@glo@label @alias}{}}%
    {%
      \csxdef{glo@\@glo@label @alias}{\@glo@alias}%
    }%
  }
\newcommand*{\glstralias}[1]{\@gls@entry@field{#1}{alias}}
\newcommand*{\glstrseealsolabels}[1]{\@gls@entry@field{#1}{seealso}}
\appto\@glo@autohook{%
  \ifdefvoid\@glo@alias
    {%
      \ifdefvoid\@glo@seealso
        {}%
      {%
        \protected@edef\@do@glsee{\noexpand\glstrindexseealso
          {\@glo@label}{\@glo@seealso}}%
        \@do@glsee
      }%
    }%
  {%
    \ifdefvoid\@glo@see
      {%
        \protected@edef\@do@glsee{\noexpand\glsee{\@glo@label}{\@glo@alias}}%
        \@do@glsee
      }%
    {}%
  }%
}%
}
{
\glsaddstoragekey*{alias}{\glstralias}
\glsaddstoragekey*{seealso}{\glstrseealsolabels}
\appto\@newglossaryentryposthook{%
  \ifcsvoid{glo@\@glo@label @alias}%
  {%
    \ifcsvoid{glo@\@glo@label @seealso}%
  }
}

```

```

    {}%
    {%
      \protected@edef\@do@glsssee{\noexpand\glxtrindexseealso
        {\@glo@label}{\csuse{glo@\@glo@label @seealso}}}%
      \@do@glsssee
    }%
  }%
  {%
    \ifdefvoid\@glo@see
    {%
      \protected@edef\@do@glsssee{\noexpand\glsssee
        {\@glo@label}{\csuse{glo@\@glo@label @alias}}}%
      \@do@glsssee
    }%
    {}%
  }%
}
}
\AtEndDocument{\ifglxtrindexcrossrefs\glxtraddallcrossrefs\fi}
\newcommand*\glxtraddallcrossrefs{%
  \forallglossaries{\@glo@type}%
  {%
    \forglsentries[\@glo@type]{\@glo@label}%
    {%
      \ifglssused{\@glo@label}%
      {\expandafter\@glxtr@addunuseddxrefs\expandafter{\@glo@label}}}%
    }%
  }%
}
\newcommand*\@glxtr@addunuseddxrefs[1]{%
  \letcs{\@glo@see}{glo@\glsdetoklabel{#1}@see}%
  \ifdefvoid\@glo@see
  {}%
  {%
    \expandafter\glxtr@addunused\@glo@see\@end@glxtr@addunused
  }%
  \letcs{\@glo@see}{glo@\glsdetoklabel{#1}@seealso}%
  \ifdefvoid\@glo@see
  {}%
  {%
    \expandafter\glxtr@addunused\@glo@see\@end@glxtr@addunused
  }%
}
\newcommand*\glxtr@addunused[1][1]{%
  \@glxtr@addunused
}
\def\@glxtr@addunused#1\@end@glxtr@addunused{%
  \@for\@glxtr@label:=#1\do
  {%
    \glxtrifmulti\@glxtr@label

```

```

{%
  \letcs\@glsxtr@labellist{\@gls@combined@\@glsxtr@label @list}%
  \@for\@glsxtr@multilabel:=\@glsxtr@labellist\do
  {\@glsxtr@addunused\@glsxtr@multilabel\@end\@glsxtr@addunused}%
}%
{%
  \ifglsused{\@glsxtr@label}{}%
  {%
    \glsadd[format=glsxtrunusedformat]{\@glsxtr@label}%
    \glsunset{\@glsxtr@label}%
    \expandafter\@glsxtr@addunusedxrefs\expandafter{\@glsxtr@label}%
  }%
}%
}%
}
\newcommand*{\glsxtrunusedformat}[1]{\unskip}
\ifdef\gls@begindocdefs
{%
  \renewcommand*{\gls@begindocdefs}{%
    \ifnum\@glsxtr@docdefval=1\relax
      \@gls@enablesavenonumberlist
      \edef\@gls@restoreat{%
        \noexpand\catcode'\noexpand\@=\number\catcode'\@'\relax}%
      \makeatletter
      \InputIfFileExists{\jobname.glsdefs}{\@gls@restoreat}{\@gls@restoreat}
      \undef\@gls@restoreat
      \gls@defdocnewglossaryentry
    \else
      \ifnum\@glsxtr@docdefval=3\relax
        \@gls@enablesavenonumberlist
        \let\gls@checkseeallowed\relax
        \let\newglossaryentry\new@atom@glossaryentry
        \global\newwrite\@gls@deffile
        \immediate\openout\@gls@deffile=\jobname.glsdefs
        \forallglsentries{\@glsentry}{\@gls@writedef{\@glsentry}}%
      \fi
    \fi
  }
}
{%
  \ifnum\@glsxtr@docdefval=3\relax
    \PackageError{glossaries-extra}{Package option
      'docdef=\@glsxtr@docdefsetting' requires at least version 4.37
      of the base glossaries.sty package}{}
  \fi
}
\newrobustcmd{\new@atom@glossaryentry}[2]{%
  \gls@defglossaryentry{#1}{#2}%
  \@gls@writedef{#1}%
}

```

```

}
\let\glstr@orgmakenoidxglossaries\makenoidxglossaries
\renewcommand{\makenoidxglossaries}{%
  \@domakeglossaries
  {%
    \ifdefequal\glstr@record@setting\glstr@record@setting@off
    {%
      \glstr@orgmakenoidxglossaries
      \renewcommand{\do@seeglossary}[2]{%
        \@glstrwrglossmark
        \protected@edef\gls@label{\glsdetoklabel{##1}}%
        \protected@write\auxout{}{%
          \string\gls@reference
            {\csname glo@\gls@label @type\endcsname}%
            {\@gls@label}%
          {%
            \string\glsseeformat##2}%
          }%
        }%
      }%
    }%
    \ifglstrdocdefrestricted
      \renewcommand*{\@gls@reference}[3]{%
        \ifcsundef\glsref@##1{\csgdef\glsref@##1{}}{}%
        \ifinlistcs{##2}{\glsref@##1}%
        {}%
        {\listcsgadd\glsref@##1{##2}}%
        \ifcsundef{glo\glsdetoklabel{##2}@loclist}%
        {\csgdef{glo\glsdetoklabel{##2}@loclist}{}}%
        {}%
        \listcsgadd{glo\glsdetoklabel{##2}@loclist}{##3}%
      }%
    \else
      \@glstrdocdeffalse
    \fi
    \disable@keys{glossaries-extra}{docdef}%
  }%
  {%
    \PackageError{glossaries-extra}{\string\makenoidxglossaries\space
      not permitted\MessageBreak
      with record=\glstr@record@setting\space package option}%
    {You may only use \string\makenoidxglossaries\space with the
      record=off option}%
  }%
}
\renewcommand*{\gls@defdocnewglossaryentry}{%
  \ifcase\@glstr@docdefval
  \renewcommand*{\newglossaryentry}[2]{%
    \PackageError{glossaries-extra}{Glossary entries must
      be \MessageBreak defined in the preamble with \MessageBreak

```

```

package option 'docdef=false'\MessageBreak(consider using
'docdef=restricted')}{Move your glossary definitions to
the preamble. You can also put them in a \MessageBreak separate file
and load them with \string\loadglsentries.}%
}%
\or
\let\gls@checkseeallowed\relax
\let\newglossaryentry\newglossaryentry
\else
\let\gls@checkseeallowed\relax
\fi
}%
\newcommand*{\GlsXtrEnableOnTheFly}{%
\@ifstar\@sGlsXtrEnableOnTheFly\@GlsXtrEnableOnTheFly
}
\newcommand*{\@sGlsXtrEnableOnTheFly}{%
\renewcommand*{\glsdetoklabel}[1]{%
\expandafter\@glsxtr@ifcsstart\string##1 \@glsxtr@end@
{%
\expandafter\detokenize\expandafter{##1}%
}%
{\detokenize{##1}}}%
}%
\@GlsXtrEnableOnTheFly
}
\def\@glsxtr@ifcsstart#1#2\@glsxtr@end@#3#4{%
\expandafter\if\glsbackslash#1%
#3%
\else
#4%
\fi
}
\newcommand*{\glsxtrstarflywarn}{%
\GlossariesExtraWarning{Experimental starred version of
\string\GlsXtrEnableOnTheFly\space in use (please ensure you have
read the warnings in the glossaries-extra user manual)}%
}
\newcommand*{\@GlsXtrEnableOnTheFly}{%
\newcommand*{\glsxtrcat}{general}
\newcommand*{\glsxtr}[1][]{%
\def\glsxtr@keylist{##1}%
\@glsxtr
}
\newcommand*{\@glsxtr}[2][]{%
\ifglsentryexists{##2}%
{%
\ifblank{##1}{-}{\GlsXtrWarning{##1}{##2}}%
}%
{%
\gls@defglossaryentry{##2}{name={##2},category=\glsxtrcat,

```

```

        description={\nopostdesc},##1}%
    }%
    \expandafter\gls\expandafter[\glsxtr@keylist]{##2}%
}
\newcommand*\@Glsxtr}[1][]{%
    \def\glsxtr@keylist{##1}%
    \@Glsxtr
}
\newcommand*\@Glsxtr}[2][]{%
    \ifglsentryexists{##2}%
    {%
        \ifblank{##1}{-}{\GlsXtrWarning{##1}{##2}}%
    }%
    {%
        \gls@defglossaryentry{##2}{name={##2},category=\glsxtrcat,
            description={\nopostdesc},##1}%
    }%
    \expandafter\Gls\expandafter[\glsxtr@keylist]{##2}%
}
\newcommand*\glsxtrpl}[1][]{%
    \def\glsxtr@keylist{##1}%
    \@glsxtrpl
}
\newcommand*\@Glsxtrpl}[2][]{%
    \ifglsentryexists{##2}%
    {%
        \ifblank{##1}{-}{\GlsXtrWarning{##1}{##2}}%
    }%
    {%
        \gls@defglossaryentry{##2}{name={##2},category=\glsxtrcat,
            description={\nopostdesc},##1}%
    }%
    \expandafter\glspl\expandafter[\glsxtr@keylist]{##2}%
}
\newcommand*\Glsxtrpl}[1][]{%
    \def\glsxtr@keylist{##1}%
    \@Glsxtrpl
}
\newcommand*\@Glsxtrpl}[2][]{%
    \ifglsentryexists{##2}
    {%
        \ifblank{##1}{-}{\GlsXtrWarning{##1}{##2}}%
    }%
    {%
        \gls@defglossaryentry{##2}{name={##2},category=\glsxtrcat,
            description={\nopostdesc},##1}%
    }%
    \expandafter\Glspl\expandafter[\glsxtr@keylist]{##2}%
}
\newcommand*\GlsXtrWarning}[2]{%

```



```

\def\@glsxtr@optlist{##1}%
\@onelevel@sanitize\@glsxtr@optlist
\GlossariesExtraWarning{The options '\@glsxtr@optlist' have
been ignored for entry '##2' as it has already been defined}%
}
\renewcommand\@printglossary[2]{%
\def\@glsxtr@printglossopts{##1}%
\@glsxtr@orgprintglossary{##1}{##2}%
\def\@glsxtr{\@glsxtr@disabledflycommand\glsxtr}%
\def\@glsxtrpl{\@glsxtr@disabledflycommand\glsxtrpl}%
\def\@Glsxtr{\@glsxtr@disabledflycommand\Glsxtr}%
\def\@Glsxtrpl{\@glsxtr@disabledflycommand\Glsxtrpl}%
}
\newcommand*{\@glsxtr@disabledflycommand}[1]{%
\PackageError{glossaries-extra}%
{string##1\space can't be used after any of the \MessageBreak
glossaries have been displayed}%
{The on-the-fly commands enabled by
\string\GlsXtrEnableOnTheFly\space may only be used \MessageBreak
before the glossaries. If you want to use any entries \MessageBreak
after any of the glossaries, you must use the standard \MessageBreak
method of first defining the entry and then using the \MessageBreak
entry with commands like \string\gls}%
\@glsxtr@disabledflycommand
}%
\newcommand*{\@glsxtr@disabledflycommand}[2][{}]{##2}
\let\GlsXtrEnableOnTheFly\relax
}
\@onlypreamble\GlsXtrEnableOnTheFly
\newcommand*{\@glsxtr@current@style}{\@glossary@default@style}
\renewcommand*{\setglossarystyle}[1]{%
\ifcsundef{@glsstyle@#1}%
{%
\PackageError{glossaries-extra}{Glossary style '#1' undefined}{}%
}%
{%
\csname @glsstyle@#1\endcsname
\protected@edef\@glsxtr@current@style{#1}%
}%
\ifx\@glossary@default@style\relax
\protected@edef\@glossary@default@style{#1}%
\fi
}
\ifdef\@glossary@default@style
{}
{%
\let\@glossary@default@style\relax
}
\ifdef\glslistdottedwidth
{%

```

```

\ifdim\glslistdottedwidth=.5\hsize
  \setlength{\glslistdottedwidth}{-\dimexpr\maxdimen-1sp\relax}
  \AtBeginDocument{%
    \ifdim\glslistdottedwidth=-\dimexpr\maxdimen-1sp\relax
      \setlength{\glslistdottedwidth}{.5\columnwidth}%
    \fi
  }%
\fi
}
{}%
\ifdef\glsdescwidth
{%
  \ifdim\glsdescwidth=.6\hsize
    \setlength{\glsdescwidth}{-\dimexpr\maxdimen-1sp\relax}
    \AtBeginDocument{%
      \ifdim\glsdescwidth=-\dimexpr\maxdimen-1sp\relax
        \setlength{\glsdescwidth}{.6\columnwidth}%
      \fi
    }%
  \fi
}
{}%
\ifdef\glspagelistwidth
{%
  \ifdim\glspagelistwidth=.1\hsize
    \setlength{\glspagelistwidth}{-\dimexpr\maxdimen-1sp\relax}
    \AtBeginDocument{%
      \ifdim\glspagelistwidth=-\dimexpr\maxdimen-1sp\relax
        \setlength{\glspagelistwidth}{.1\columnwidth}%
      \fi
    }%
  \fi
}
{}%
\def\org@glossaryentrynumbers#1{#1\gls@save@numberlist{#1}}%
\ifx\org@glossaryentrynumbers\glossaryentrynumbers
  \glsnonumberlistfalse
  \renewcommand*{\glossaryentrynumbers}[1]{%
    \ifglsentryexists{\glscurrententrylabel}%
    {%
      \@glsxtrpreloctag
      \GlsXtrFormatLocationList{#1}%
      \@glsxtrpostloctag
      \gls@save@numberlist{#1}%
    }{}%
  }%
\else
  \glsnonumberlisttrue
  \renewcommand*{\glossaryentrynumbers}[1]{%
    \ifglsentryexists{\glscurrententrylabel}%

```

```

    {%
      \gls@save@numberlist{#1}%
    }{}%
  }%
\fi
\newcommand*{\GlsXtrFormatLocationList}[1]{#1}
\newcommand*{\GlsXtrEnablePreLocationTag}[2]{%
  \let\@glsxtrpreloctag\@glsxtrpreloctag
  \let\@glsxtrpostloctag\@glsxtrpostloctag
  \renewcommand*{\@glsxtr@pagetag}{#1}%
  \renewcommand*{\@glsxtr@pagetag}{#2}%
  \renewcommand*{\@glsxtr@savepreloctag}[2]{%
    \csgdef{\@glsxtr@preloctag@##1}{##2}%
  }%
  \renewcommand*{\@glsxtr@doloctag}{%
    \ifcsundef{\@glsxtr@preloctag@\glscurrententrylabel}%
    {%
      \GlossariesWarning{Missing pre-location tag for ‘\glscurrententrylabel’.
        Rerun required}%
    }%
    {%
      \csuse{\@glsxtr@preloctag@\glscurrententrylabel}%
    }%
  }%
}
\@onlypreamble\GlsXtrEnablePreLocationTag
\newcommand*{\@glsxtrpreloctag}{%
  \let\@glsxtr@org@delimN\delimN
  \let\@glsxtr@org@delimR\delimR
  \let\@glsxtr@org@glsignore\glsignore
  \gdef\@glsxtr@thisloctag{\@glsxtr@pagetag}%
  \renewcommand*{\delimN}{%
    \gdef\@glsxtr@thisloctag{\@glsxtr@pagetag}%
    \@glsxtr@org@delimN}%
  \renewcommand*{\delimR}{%
    \gdef\@glsxtr@thisloctag{\@glsxtr@pagetag}%
    \@glsxtr@org@delimR}%
  \renewcommand*{\glsignore}[1]{%
    \gdef\@glsxtr@thisloctag{\relax}%
    \@glsxtr@org@glsignore{##1}}%
  \@glsxtr@doloctag
}
\newcommand*{\@glsxtrpreloctag}{}
\newcommand*{\@glsxtr@pagetag}{}%
\newcommand*{\@glsxtr@pagetag}{}%
\newcommand*{\@glsxtrpostloctag}{%
  \let\delimN\@glsxtr@org@delimN
  \let\delimR\@glsxtr@org@delimR
  \let\glsignore\@glsxtr@org@glsignore
  \protected@write\@auxout{}%

```

```

        {\string\@glxtr@savepreloctag{\glscurrententrylabel}{\@glxtr@thisloctag}}%
    }
    \newcommand*{\@glxtrpostloctag}{%
    \newcommand*{\@glxtr@savepreloctag}[2]{%
    \protected@write\@auxout{}{%
        \string\providecommand\string\@glxtr@savepreloctag[2]{}%
    \newcommand*{\@glxtr@doloctag}{%
    \renewcommand*{\KV@printgloss@nonumberlist}[1]{%
        \XKV@plfalse
        \XKV@sttrue
        \XKV@checkchoice[\XKV@resa]{#1}{true,false}%
    }%
        \csname glsnonumberlist\XKV@resa\endcsname
        \ifglsnonumberlist
            \def\glossaryentrynumbers##1{\gls@save@numberlist{##1}}%
        \else
            \def\glossaryentrynumbers##1{%
                \@glxtrpreloctag
                \GlsXtrFormatLocationList{##1}%
                \@glxtrpostloctag
                \gls@save@numberlist{##1}%
            }%
        \fi
    }%
    }
    \renewcommand*{\glsentryfmt}{%
        \ifglshasshort{\glslabel}{\glssetabbrvfmt{\glscategory{\glslabel}}}{}%
        \glsifregular{\glslabel}%
        {\glsxtrregularfont{\glsgenentryfmt}}%
        {%
            \ifglshasshort{\glslabel}%
            {\glsxtrabbreviationfont{\glsxtrgenabbrvfmt}}%
            {\glsxtrregularfont{\glsgenentryfmt}}%
        }%
    }
    \newcommand*{\glsxtrregularfont}[1]{#1}
    \newcommand*{\glsxtrabbreviationfont}[1]{#1}
    \renewcommand{\@gls@field@link}[4][{}]{%
        \@glxtr@record{#2}{#3}{\glslink}%
        \glsdoifexists{#3}%
        {%
            \let\glsxtrorg@ifKV@glslink@hyper\ifKV@glslink@hyper
            \@gls@save@glslocal
            \let\do@gls@link@checkfirsthyper\@gls@link@nocheckfirsthyper
            \def\glscustomtext{#4}%
            \@glxtr@field@linkdefs
            #1%
            \@gls@link[#2]{#3}{#4}%
            \let\ifKV@glslink@hyper\glsxtrorg@ifKV@glslink@hyper
            \@gls@restore@glslocal
        }%
    }

```

```

\glspostlinkhook
}
\let\@glstr@org@gl@gl@
\def\@gl@#1#2{%
  \@glstr@record{#1}{#2}{glslink}%
  \@glstr@org@gl@{#1}{#2}%
}%
\let\@glstr@org@glpl@glpl@
\def\@glpl@#1#2{%
  \@glstr@record{#1}{#2}{glslink}%
  \@glstr@org@glpl@{#1}{#2}%
}%
\let\@glstr@org@gl@gl@
\def\@gl@#1#2{%
  \@glstr@record{#1}{#2}{glslink}%
  \@glstr@org@gl@{#1}{#2}%
}%
\let\@glstr@org@glpl@glpl@
\def\@glpl@#1#2{%
  \@glstr@record{#1}{#2}{glslink}%
  \@glstr@org@glpl@{#1}{#2}%
}%
\let\@glstr@org@gl@gl@
\def\@gl@#1#2{%
  \@glstr@record{#1}{#2}{glslink}%
  \@glstr@org@gl@{#1}{#2}%
}%
\let\@glstr@org@glpl@glpl@
\def\@glpl@#1#2{%
  \@glstr@record{#1}{#2}{glslink}%
  \@glstr@org@glpl@{#1}{#2}%
}%
\renewcommand*{\@glsdisp}[3][{}]{%
  \@glstr@record{#1}{#2}{glslink}%
  \glsdoifexists{#2}{%
    \let\do@gl@link@checkfirsthyper\@gl@link@checkfirsthyper
    \let\glsifplural\@secondoftwo
    \let\glscapscase\@firstofthree
    \def\glscustomtext{#3}%
    \def\glsinsert{}%
    \def\@glo@text{\csname gls@glstype @entryfmt\endcsname}%
    \@gl@link[#1]{#2}{\@glo@text}%
    \@gl@do@gl@unset{#2}%
  }%
  \glspostlinkhook
}
\renewcommand*{\@gl@link}[3][{}]{%
  \@glstr@record{#1}{#2}{glslink}%
  \glsdoifexistsordo{#2}%
  {%

```

```

\let\do@gl@link@checkfirsthyper\relax
\def\glscustomtext{#3}%
\@glxtr@field@linkdefs
\@gl@link[#1]{#2}{#3}%
}%
{%
\glstextformat{#3}%
}%
\glspostlinkhook
}
\newcommand*{\glxtrinitwrgloss}{%
\gl@ifattribute{\glslabel}{wrgloss}{after}%
{%
\glxtrinitwrglossbeforefalse
}%
{%
\glxtrinitwrglossbeforetrue
}%
}
\newif\ifglxtrinitwrglossbefore
\glxtrinitwrglossbeforetrue
\define@choicekey{glslink}{wrgloss}%
[\@glxtr@wrglossval\@glxtr@wrglossnr]%
{before,after}%
{%
\ifcase\@glxtr@wrglossnr\relax
\glxtrinitwrglossbeforetrue
\or
\glxtrinitwrglossbeforefalse
\fi
}
\define@key{glslink}{thevalue}{\def\@glxtr@thevalue{#1}}
\define@key{glslink}{theHvalue}{\def\@glxtr@theHvalue{#1}}
\define@boolkey{glslink}[glxtr@]{hyperoutside}{true}{}
\glxtr@hyperoutsidettrue
\define@key{glslink}{textformat}{%
\ifcsdef{#1}
{%
\letcs{\@glxtr@local@textformat}{#1}%
}%
{%
\PackageError{glossaries-extra}{Unknown control sequence name ‘#1’}{}%
}%
}
\define@key{glslink}{prefix}{\def\glolinkprefix{#1}}
\newcommand*{\glxtrinithyperoutside}{%
\gl@ifattribute{\glslabel}{hyperoutside}{false}%
{%
\glxtr@hyperoutsidetfalse
}%
}

```

```

{%
  \glxtr@hyperoutsidetrue
}%
}
\newcommand*{\glxtr@inc@linkcount}{%
\newcommand*{\glslinkpresetkeys}{%
\newrobustcmd*{\GlsXtrExpandedFmt}[2]{%
  \protected@edef\@glxtr@tmp{#2}%
  \expandafter#1\expandafter{\@glxtr@tmp}%
}
\newcommand*{\@glxtr@use@equation@counter}{%
  \@glxtr@ifnum@mmode{\def\@glsl@counter{equation}}{}}%
}
\newcommand*{\glxtr@do@autoadd}[1]{%
\newcommand*{\GlsXtrAutoAddOnFormat}[3][\glslabel]{%
  \renewcommand*{\glxtr@do@autoadd}[1]{%
    \begingroup
      \protected@edef\@glxtr@do@autoadd{%
        \noexpand\ifstrequal{##1}{\glslink}%
        {%
          \noexpand\DTLifinlist{\@glslnumberformat}{#2}{\noexpand\glssadd[format={\@glslnumberformat},%
          }%
          }%
        }%
      }%
      \@glxtr@do@autoadd
    \endgroup
  }%
}
\providecommand*{\glslinkwrcontent}[1][{\#1}]
\def\@glsl@link[#1]#2#3{%
  \leavevmode
  \protected@edef\glslabel{\glsdetoklabel{#2}}%
  \def\@glsl@link@opts{#1}%
  \let\@glsl@link@label\glslabel
  \let\@glslnumberformat\@glxtr@defaultnumberformat
  \protected@edef\@glsl@counter{\csname glo@\glslabel @counter\endcsname}%
  \protected@edef\glstype{\csname glo@\glslabel @type\endcsname}%
  \let\@org@ifKV@glslink@hyper\ifKV@glslink@hyper
  \@glsl@save@glsllocal
  \let\@glxtr@org@glolinkprefix\glolinkprefix
  \let\@glxtr@local@textformat\relax
  \def\@glxtr@thevalue{%
  \def\@glxtr@theHvalue{\@glxtr@thevalue}%
  \glxtr@initwrgloss
  \glxtr@inithyperoutside
  \@glsl@setdefault@glslink@opts
  \glxtr@inc@linkcount
  \if@glxtr@equations
    \@glxtr@use@equation@counter
  \fi

```

```

\do@gl:disablehyperinlist
\do@gl:link@checkfirsthyper
\gl:link@presetkeys
\setkeys{gl:link}{#1}%
\gl:extr@do@autoadd{gl:link}%
\gl:link@postsetkeys
\ifdefempty{\@gl:extr@thevalue}%
{%
  \@gl:saveentrycounter
}%
{%
  \let\thegl:entrycounter\@gl:extr@thevalue
  \def\theHgl:entrycounter{\@gl:extr@theHvalue}%
}%
\@gl:setsort{gl:label}%
\ifx\@gl:extr@local@textformat\relax
  \gl:hasattribute{gl:label}{textformat}%
  {%
    \protected@edef\@gl:extr@attrval{\gl:getattribute{gl:label}{textformat}}%
    \ifcsdef{\@gl:extr@attrval}%
    {%
      \letcs{\@gl:extr@textformat}{\@gl:extr@attrval}%
    }%
    {%
      \GlossariesExtraWarning{Unknown control sequence name
        '\@gl:extr@attrval' supplied in textformat attribute
        for entry 'gl:label'. Reverting to default \string\gl:textformat}%
      \let\@gl:extr@textformat\gl:textformat
    }%
  }%
  {%
    \let\@gl:extr@textformat\gl:textformat
  }%
\else
  \let\@gl:extr@textformat\@gl:extr@local@textformat
\fi
\gl:link@wrcontent
{%
  \ifgl:extr@initwrglossbefore
    \@do@wrglossary{#2}%
  \fi
  \ifKV@gl:link@hyper
    \ifgl:extr@hyperoutside
      \@gl:link{\gl:linkprefix\gl:label}{\@gl:extr@textformat{#3}}%
    \else
      \@gl:extr@textformat{\@gl:link{\gl:linkprefix\gl:label}{#3}}%
    \fi
  \else
    \ifgl:extr@hyperoutside
      \gl:donohyperlink{\gl:linkprefix\gl:label}{\@gl:extr@textformat{#3}}%
    \fi
  \fi
}

```



```

\else
  \@glsxtr@textformat{\glsdonohyperlink{\glslinkprefix\glslabel}{#3}}%
\fi
\fi
\ifglsxtrinitwrglossbefore
\else
  \@do@wrglossary{#2}%
\fi
}%
\let\glslinkprefix\@glsxtr@org@glslinkprefix
\let\ifKV@glslink@hyper\org@ifKV@glslink@hyper
\@gls@restore@glslocal
}
\define@key{glossadd}{thevalue}{\def\@glsxtr@thevalue{#1}}
\define@key{glossadd}{theHvalue}{\def\@glsxtr@theHvalue{#1}}
\newcommand*{\glsaddpresetkeys}{%

\newcommand*{\glsaddpostsetkeys}{%
\renewrobustcmd*{\glsadd}[2][\{%
  \glsxtrifinmark
  }{%
  {%
    \@gls@adjustmode
    \begingroup
    \@glsxtr@record{#1}{#2}{glossadd}%
    \glsdoifexists{#2}%
    {%
      \let\@glsnumberformat\@glsxtr@defaultnumberformat
      \protected@edef\@gls@counter{\csname glo@glsdetoklabel{#2}@counter\endcsname}%
      \def\@glsxtr@thevalue{}%
      \def\@glsxtr@theHvalue{\@glsxtr@thevalue}%
      \glsaddpresetkeys
      \setkeys{glossadd}{#1}%
      \glsaddpostsetkeys
      \ifdefempty{\@glsxtr@thevalue}%
      {%
        \@gls@saveentrycounter
      }%
      {%
        \let\theglsentrycounter\@glsxtr@thevalue
        \def\theHglentrycounter{\@glsxtr@theHvalue}%
      }%
      \@gls@setsort{#2}%
      \KV@glslink@noindexfalse
      \@do@wrglossary{#2}%
    }%
  }%
\endgroup
}%
}
\newrobustcmd{\glsaddeach}[2][\{%

```

```

\@for\@gls@thislabel:=#2\do{\glsadd[#1]{\@gls@thislabel}}%
}
\newcommand*{\@glsxtr@field@linkdefs}{%
\let\glsxtrifwasfirstuse\@secondoftwo
\let\glsifplural\@secondoftwo
\let\glsupcase\@firstofthree
\let\glsinsert\@empty
}
\newcommand*{\glsxtrassignfieldfont}[1]{%
\ifglsentryexists{#1}%
{%
\ifglsashashort{#1}%
{%
\glssetabbrvfmt{\glscategory{#1}}%
\glsifregular{#1}%
{\let\@gls@field@font\glsxtrregularfont}%
{\let\@gls@field@font\@firstofone}%
}%
{%
\glsifnotregular{#1}%
{\let\@gls@field@font\@firstofone}%
{\let\@gls@field@font\glsxtrregularfont}%
}%
}%
{%
\let\@gls@field@font\@gobble
}%
}
\def\@gls@text@#1#2[#3]{%
\glsxtrassignfieldfont{#2}%
\@gls@field@link{#1}{#2}{\@gls@field@font{\glsaccesstext{#2}#3}}%
}
\def\@GLStext@#1#2[#3]{%
\glsxtrassignfieldfont{#2}%
\@gls@field@link[\let\glsupcase\@thirdofthree]{#1}{#2}%
{\@gls@field@font{\GLSaccentstext{#2}\mfirstucMakeUppercase{#3}}}%
}
\def\@Gls@text@#1#2[#3]{%
\glsxtrassignfieldfont{#2}%
\@gls@field@link[\let\glsupcase\@secondofthree]{#1}{#2}%
{\@gls@field@font{\Glsaccentstext{#2}#3}}%
}
\newcommand*{\glsxtrchecknohyperfirst}[1]{%
\glsifattribute{#1}{nohyperfirst}{true}{\KV@glslink@hyperfalse}{}%
}
\def\@gls@first@#1#2[#3]{%
\glsxtrassignfieldfont{#2}%
\@gls@field@link
[\let\glsxtrifwasfirstuse\@firstoftwo
\glsxtrchecknohyperfirst{#2}%

```

```

]{#1}{#2}%
{\@gls@field@font{\glsaccessfirst{#2}#3}}%
}
\def\@Glsfirst@#1#2[#3]{%
\glsxtrassignfieldfont{#2}%
\@gls@field@link
[\let\glsxtrifwasfirstuse\@firstoftwo
\let\gls caps case\@secondofthree
\glsxtrchecknohyperfirst{#2}%
]%
{#1}{#2}{\@gls@field@font{\Glsaccessfirst{#2}#3}}%
}
\def\@GLSfirst@#1#2[#3]{%
\glsxtrassignfieldfont{#2}%
\@gls@field@link
[\let\glsxtrifwasfirstuse\@firstoftwo
\let\gls caps case\@thirdofthree
\glsxtrchecknohyperfirst{#2}%
]%
{#1}{#2}{\@gls@field@font{\GLSaccessfirst{#2}\mfirstucMakeUppercase{#3}}}%
}
\def\@glsplural@#1#2[#3]{%
\glsxtrassignfieldfont{#2}%
\@gls@field@link[\let\glsifplural\@firstoftwo]{#1}{#2}%
{\@gls@field@font{\glsaccessplural{#2}#3}}%
}
\def\@Glsplural@#1#2[#3]{%
\glsxtrassignfieldfont{#2}%
\@gls@field@link
[\let\glsifplural\@firstoftwo
\let\gls caps case\@secondofthree
]%
{#1}{#2}{\@gls@field@font{\Glsaccessplural{#2}#3}}%
}
\def\@GLSplural@#1#2[#3]{%
\glsxtrassignfieldfont{#2}%
\@gls@field@link
[\let\glsifplural\@firstoftwo
\let\gls caps case\@thirdofthree
]%
{#1}{#2}{\@gls@field@font{\GLSaccessplural{#2}\mfirstucMakeUppercase{#3}}}%
}
\def\@glsfirstplural@#1#2[#3]{%
\glsxtrassignfieldfont{#2}%
\@gls@field@link
[\let\glsxtrifwasfirstuse\@firstoftwo
\let\glsifplural\@firstoftwo
\glsxtrchecknohyperfirst{#2}%
]%
{#1}{#2}{\@gls@field@font{\glsaccessfirstplural{#2}#3}}%
}

```

```

}
\def\@Glsfirstplural@#1#2[#3]{%
  \glstrassignfieldfont{#2}%
  \@gls@field@link
  [\let\glstrifwasfirstuse\@firstoftwo
   \let\glsifplural\@firstoftwo
   \let\glscapscase\@secondofthree
   \glstrchecknohyperfirst{#2}%
  ]%
  {#1}{#2}{\@gls@field@font{\Glsaccessfirstplural{#2}#3}}%
}
\def\@GLSfirstplural@#1#2[#3]{%
  \glstrassignfieldfont{#2}%
  \@gls@field@link
  [\let\glstrifwasfirstuse\@firstoftwo
   \let\glsifplural\@firstoftwo
   \let\glscapscase\@thirdofthree
   \glstrchecknohyperfirst{#2}%
  ]%
  {#1}{#2}%
  {\@gls@field@font{\GLSaccessfirstplural{#2}\mfirstucMakeUppercase{#3}}}%
}
\def\@glsname@#1#2[#3]{%
  \glstrassignfieldfont{#2}%
  \@gls@field@link{#1}{#2}{\@gls@field@font{\glsaccessname{#2}#3}}%
}
\def\@Glsname@#1#2[#3]{%
  \glstrassignfieldfont{#2}%
  \@gls@field@link
  [\let\glscapscase\@secondoftwo]{#1}{#2}%
  {\@gls@field@font{\Glsaccessname{#2}#3}}%
}
\def\@GLSname@#1#2[#3]{%
  \glstrassignfieldfont{#2}%
  \@gls@field@link[\let\glscapscase\@thirdoftwo]%
  {#1}{#2}%
  {\@gls@field@font{\GLSaccessname{#2}\mfirstucMakeUppercase{#3}}}%
}
\def\@glsdesc@#1#2[#3]{%
  \glstrassignfieldfont{#2}%
  \@gls@field@link{#1}{#2}{\@gls@field@font{\glsaccessdesc{#2}#3}}%
}
\def\@Glsdesc@#1#2[#3]{%
  \glstrassignfieldfont{#2}%
  \@gls@field@link
  [\let\glscapscase\@secondoftwo]{#1}{#2}%
  {\@gls@field@font{\Glsaccessdesc{#2}#3}}%
}
\def\@GLSdesc@#1#2[#3]{%
  \glstrassignfieldfont{#2}%

```

```

\@gls@field@link[\let\glscapscase\@thirdoftwo]%
    {#1}{#2}{\@gls@field@font{\GLSaccessdesc{#2}\mfirstucMakeUppercase{#3}}}%
}
\def\@glsdescplural@#1#2[#3]{%
    \glstrassignfieldfont{#2}%
    \@gls@field@link
    [\let\glscapscase\@secondoftwo
    \let\glsifplural\@firstoftwo
    ]{#1}{#2}{\@gls@field@font{\glsaccessdescplural{#2}#3}}%
}
\def\@GLSdescplural@#1#2[#3]{%
    \glstrassignfieldfont{#2}%
    \@gls@field@link
    [\let\glscapscase\@secondoftwo
    \let\glsifplural\@firstoftwo
    ]{#1}{#2}{\@gls@field@font{\GLSaccessdescplural{#2}#3}}%
}
\def\@GLSdesc@#1#2[#3]{%
    \glstrassignfieldfont{#2}%
    \@gls@field@link
    [\let\glscapscase\@thirdoftwo
    \let\glsifplural\@firstoftwo
    ]%
    {#1}{#2}%
    {\@gls@field@font{\GLSaccessdescplural{#2}\mfirstucMakeUppercase{#3}}}%
}
\def\@glssymbol@#1#2[#3]{%
    \glstrassignfieldfont{#2}%
    \@gls@field@link{#1}{#2}{\@gls@field@font{\glsaccesssymbol{#2}#3}}%
}
\def\@GLssymbol@#1#2[#3]{%
    \glstrassignfieldfont{#2}%
    \@gls@field@link
    [\let\glscapscase\@secondoftwo]%
    {#1}{#2}{\@gls@field@font{\GLSaccesssymbol{#2}#3}}%
}
\def\@GLSsymbol@#1#2[#3]{%
    \glstrassignfieldfont{#2}%
    \@gls@field@link[\let\glscapscase\@thirdoftwo]%
    {#1}{#2}{\@gls@field@font{\GLSaccesssymbol{#2}\mfirstucMakeUppercase{#3}}}%
}
\def\@glssymbolplural@#1#2[#3]{%
    \glstrassignfieldfont{#2}%
    \@gls@field@link
    [\let\glscapscase\@secondoftwo
    \let\glsifplural\@firstoftwo
    ]{#1}{#2}{\@gls@field@font{\glsaccesssymbolplural{#2}#3}}%
}
\def\@GLssymbolplural@#1#2[#3]{%
    \glstrassignfieldfont{#2}%

```

```

\@gls@field@link
[\let\glscapscase\@secondoftwo
\let\glsifplural\@firstoftwo
]{#1}{#2}{\@gls@field@font{\Glsaccesssymbolplural{#2}#3}}%
}
\def\@GLSSymbol@#1#2[#3]{%
\glstrassignfieldfont{#2}%
\@gls@field@link
[\let\glscapscase\@thirdoftwo
\let\glsifplural\@firstoftwo
]%
{#1}{#2}%
{\@gls@field@font{\Glsaccesssymbolplural{#2}\mfirstucMakeUppercase{#3}}}%
}
\def\@Glsuseri@#1#2[#3]{%
\glstrassignfieldfont{#2}%
\@gls@field@link
[\let\glscapscase\@secondoftwo]{#1}{#2}%
{\@gls@field@font{\Glsentryuseri{#2}#3}}%
}
\def\@GLSuseri@#1#2[#3]{%
\glstrassignfieldfont{#2}%
\@gls@field@link[\let\glscapscase\@thirdoftwo]%
{#1}{#2}{\@gls@field@font{\mfirstucMakeUppercase{\glsentryuseri{#2}#3}}}%
}
\def\@Glsuserii@#1#2[#3]{%
\glstrassignfieldfont{#2}%
\@gls@field@link
[\let\glscapscase\@secondoftwo]%
{#1}{#2}{\@gls@field@font{\Glsentryuserii{#2}#3}}%
}
\def\@GLSuserii@#1#2[#3]{%
\glstrassignfieldfont{#2}%
\@gls@field@link[\let\glscapscase\@thirdoftwo]%
{#1}{#2}{\@gls@field@font{\mfirstucMakeUppercase{\glsentryuserii{#2}#3}}}%
}
\def\@Glsuseriii@#1#2[#3]{%
\glstrassignfieldfont{#2}%
\@gls@field@link
[\let\glscapscase\@secondoftwo]%
{#1}{#2}{\@gls@field@font{\Glsentryuseriii{#2}#3}}%
}
\def\@GLSuseriii@#1#2[#3]{%
\glstrassignfieldfont{#2}%
\@gls@field@link[\let\glscapscase\@thirdoftwo]%
{#1}{#2}{\@gls@field@font{\mfirstucMakeUppercase{\glsentryuseriii{#2}#3}}}%
}
\def\@Glsuseriv@#1#2[#3]{%
\glstrassignfieldfont{#2}%
\@gls@field@link

```

```

[\let\glscapscase\@secondoftwo]%
{#1}{#2}{\@gls@field@font{\Glsentryuseriv{#2}#3}}}%
}
\def\@GLSuseriv@#1#2[#3]{%
\glstrassignfieldfont{#2}%
\@gls@field@link[\let\glscapscase\@thirdoftwo]%
{#1}{#2}%
{\@gls@field@font{\mfirstucMakeUppercase{\glentryuseriv{#2}#3}}}%
}
\def\@GLSuseriv@#1#2[#3]{%
\glstrassignfieldfont{#2}%
\@gls@field@link
[\let\glscapscase\@secondoftwo]%
{#1}{#2}{\@gls@field@font{\Glsentryuseriv{#2}#3}}}%
}
\def\@GLSuseriv@#1#2[#3]{%
\glstrassignfieldfont{#2}%
\@gls@field@link[\let\glscapscase\@thirdoftwo]%
{#1}{#2}{\@gls@field@font{\mfirstucMakeUppercase{\glentryuseriv{#2}#3}}}%
}
\def\@GLSuseriv@#1#2[#3]{%
\glstrassignfieldfont{#2}%
\@gls@field@link
[\let\glscapscase\@secondoftwo]%
{#1}{#2}{\@gls@field@font{\Glsentryuseriv{#2}#3}}}%
}
\def\@GLSuseriv@#1#2[#3]{%
\glstrassignfieldfont{#2}%
\@gls@field@link[\let\glscapscase\@thirdoftwo]%
{#1}{#2}{\@gls@field@font{\mfirstucMakeUppercase{\glentryuseriv{#2}#3}}}%
}
\newcommand*{\@glsxtr@base@acrcmd@warn}[2]{%
\GlossariesExtraWarning{Base acronym command \string#1\space
should not be used with new abbreviation definitions. Use
\string#2\space instead}%
}
\let\@glsxtr@base@acrcmd\@glsxtr@base@acrcmd@warn
\def\@acrshort#1#2[#3]{%
\@glsxtr@base@acrcmd\acrshort\glsxtrshort
\glsdoifexists{#2}%
{%
\let\do@gls@link@checkfirsthyper\@gls@link@nocheckfirsthyper
\let\glsxtrifwasfirstuse\@secondoftwo
\let\glsifplural\@secondoftwo
\let\glscapscase\@firstofthree
\let\glsinsert\@empty
\def\glsustomtext{%
\acronymfont{\glsaccessshort{#2}}#3%
}%
\@gls@link[#1]{#2}{\csname gls@glstype @entryfmt\endcsname}%
}

```

```

}%
\glspostlinkhook
}
\def\@Acrshort#1#2[#3]{%
\@glstr@base@acrcmd\Acrshort\Glsxtrshort
\glsdoifexists{#2}%
{%
\let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
\let\glstrifwasfirstuse\@secondoftwo
\let\gl@ifplural\@secondoftwo
\let\glscapscase\@secondofthree
\let\glinsert\@empty
\def\glscustomtext{%
\acronymfont{\Glsaccessshort{#2}}#3%
}%
\@gl@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
}%
\glspostlinkhook
}
\def\@ACRshort#1#2[#3]{%
\@glstr@base@acrcmd\ACRshort\GLSxtrshort
\glsdoifexists{#2}%
{%
\let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
\let\glstrifwasfirstuse\@secondoftwo
\let\gl@ifplural\@secondoftwo
\let\glscapscase\@thirdofthree
\let\glinsert\@empty
\def\glscustomtext{%
\mfirstucMakeUppercase{\acronymfont{\Glsaccessshort{#2}}#3}%
}%
\@gl@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
}%
\glspostlinkhook
}
\def\@acrshortpl#1#2[#3]{%
\@glstr@base@acrcmd\acrshortpl\glstrshortpl
\glsdoifexists{#2}%
{%
\let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
\let\glstrifwasfirstuse\@secondoftwo
\let\gl@ifplural\@firstoftwo
\let\glscapscase\@firstofthree
\let\glinsert\@empty
\def\glscustomtext{%
\acronymfont{\Glsaccessshortpl{#2}}#3%
}%
\@gl@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
}%
\glspostlinkhook

```



```

}
\def\@Acrshortpl#1#2[#3]{%
  \@glxtr@base@acrcmd\Acrshortpl\Glsxtrshortpl
  \glsdoifexists{#2}%
  {%
    \let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
    \let\glxtrifwasfirstuse\@secondoftwo
    \let\glsifplural\@firstoftwo
    \let\glscapscase\@secondofthree
    \let\glsinsert\@empty
    \def\glscustomtext{%
      \acronymfont{\Glsaccessshortpl{#2}}#3%
    }%
    \@gl@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
  }%
  \glspostlinkhook
}
\def\@ACRshortpl#1#2[#3]{%
  \@glxtr@base@acrcmd\ACRshortpl\GLSxtrshortpl
  \glsdoifexists{#2}%
  {%
    \let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
    \let\glxtrifwasfirstuse\@secondoftwo
    \let\glsifplural\@firstoftwo
    \let\glscapscase\@thirdofthree
    \let\glsinsert\@empty
    \def\glscustomtext{%
      \mfirstucMakeUppercase{\acronymfont{\Glsaccessshortpl{#2}}#3}%
    }%
    \@gl@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
  }%
  \glspostlinkhook
}
\def\@acrlong#1#2[#3]{%
  \@glxtr@base@acrcmd\acrlong\glxtrlong
  \glsdoifexists{#2}%
  {%
    \let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
    \let\glxtrifwasfirstuse\@secondoftwo
    \let\glsifplural\@secondoftwo
    \let\glscapscase\@firstofthree
    \let\glsinsert\@empty
    \def\glscustomtext{%
      \acronymfont{\Glsaccesslong{#2}}#3%
    }%
    \@gl@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
  }%
  \glspostlinkhook
}
\def\@Acrlong#1#2[#3]{%

```

```

\@glxtr@base@acrcmd\Acrlong\Glsxtrlong
\glsdoifexists{#2}%
{%
  \let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
  \let\glxtrifwasfirstuse\@secondoftwo
  \let\gl@ifplural\@secondoftwo
  \let\glscapscase\@secondofthree
  \let\glinsert\@empty
  \def\glscustomtext{%
    \acronymfont{\Glsaccesslong{#2}}#3%
  }%
  \@gl@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
}%
\glspostlinkhook
}
\def\@ACRlong#1#2[#3]{%
  \@glxtr@base@acrcmd\ACRlong\GLSxtrlong
  \glsdoifexists{#2}%
  {%
    \let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
    \let\glxtrifwasfirstuse\@secondoftwo
    \let\gl@ifplural\@secondoftwo
    \let\glscapscase\@thirdofthree
    \let\glinsert\@empty
    \def\glscustomtext{%
      \mfirstucMakeUppercase{\acronymfont{\Glsaccesslong{#2}}#3}%
    }%
    \@gl@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
  }%
  \glspostlinkhook
}
\def\@acrlongpl#1#2[#3]{%
  \@glxtr@base@acrcmd\acrlongpl\glxtrlongpl
  \glsdoifexists{#2}%
  {%
    \let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
    \let\glxtrifwasfirstuse\@secondoftwo
    \let\gl@ifplural\@firstoftwo
    \let\glscapscase\@firstofthree
    \let\glinsert\@empty
    \def\glscustomtext{%
      \acronymfont{\Glsaccesslongpl{#2}}#3%
    }%
    \@gl@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
  }%
  \glspostlinkhook
}
\def\@Acrlongpl#1#2[#3]{%
  \@glxtr@base@acrcmd\Acrlongpl\Glsxtrlongpl
  \glsdoifexists{#2}%

```

```

{%
  \let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
  \let\glxtrifwasfirstuse\@secondoftwo
  \let\gl@ifplural\@firstoftwo
  \let\glscapscase\@secondofthree
  \let\glinsert\@empty
  \def\glscustomtext{%
    \acronymfont{\Glsaccesslongpl{#2}}#3%
  }%
  \@gl@link[#1]{#2}{\csname gls@glstype @entryfmt\endcsname}%
}%
\glspostlinkhook
}
\def\@ACRlongpl#1#2[#3]{%
  \@glxtr@base@acrcmd\ACRlongpl\GLSxtrlongpl
  \glsoifexists{#2}%
  {%
    \let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
    \let\glxtrifwasfirstuse\@secondoftwo
    \let\gl@ifplural\@firstoftwo
    \let\glscapscase\@thirdofthree
    \let\glinsert\@empty
    \def\glscustomtext{%
      \mfirstucMakeUppercase{\acronymfont{\Glsaccesslongpl{#2}}#3}%
    }%
    \@gl@link[#1]{#2}{\csname gls@glstype @entryfmt\endcsname}%
  }%
  \glspostlinkhook
}
\def\@acrfull#1#2[#3]{%
  \@glxtr@base@acrcmd\acrfull\glxtrfull
  \acrfullfmt{#1}{#2}{#3}%
}
\def\@Acrfull#1#2[#3]{%
  \@glxtr@base@acrcmd\Acrfull\Glsxtrfull
  \Acrfullfmt{#1}{#2}{#3}%
}
\def\@ACRfull#1#2[#3]{%
  \@glxtr@base@acrcmd\ACRfull\GLSxtrfull
  \ACRfullfmt{#1}{#2}{#3}%
}
\def\@acrfullpl#1#2[#3]{%
  \@glxtr@base@acrcmd\acrfullpl\glxtrfullpl
  \acrfullplfmt{#1}{#2}{#3}%
}
\def\@Acrfullpl#1#2[#3]{%
  \@glxtr@base@acrcmd\Acrfullpl\Glsxtrfullpl
  \Acrfullplfmt{#1}{#2}{#3}%
}
\def\@ACRfullpl#1#2[#3]{%

```

```

\@glstr@base@acrcmd\ACRfullpl\GLSxtrfullpl
\ACRfullplfmt{#1}{#2}{#3}%
}
\renewcommand*{\@glsaddkey}[7]{%
\key@ifundefined{glossentry}{#1}%
{%
\define@key{glossentry}{#1}{\csdef{@glo@#1}{##1}}%
\appto\@gls@keymap{,{#1}{#1}}%
\appto\@newglossaryentryprehook{\csdef{@glo@#1}{#2}}%
\appto\@newglossaryentryposthook{%
\letcs{\@glo@tmp}{@glo@#1}%
\gls@assign@field{#2}{\@glo@label}{#1}{\@glo@tmp}%
}%
\newcommand*{#3}[1]{\@gls@entry@field{##1}{#1}}%
\newcommand*{#4}[1]{\@Gls@entry@field{##1}{#1}}%
\ifcsdef{@gls@user@#1@}%
{%
\PackageError{glossaries}%
{Can't define '\string#5' as helper command
'\expandafter\string\csname @gls@user@#1@\endcsname' already
exists}%
{}%
}%
{%
\expandafter\newcommand\expandafter*\expandafter
{\csname @gls@user@#1\endcsname}[2][{}]{%
\new@ifnextchar[%
{\csuse{@gls@user@#1@}{##1}{##2}}%
{\csuse{@gls@user@#1@}{##1}{##2}[{}]}%
\csdef{@gls@user@#1@}##1##2[##3]{%
\@gls@field@link{##1}{##2}{#3{##2}##3}%
}%
\newrobustcmd*{#5}{%
\expandafter\@gls@hyp@opt\csname @gls@user@#1\endcsname}%
}%
\ifcsdef{@Gls@user@#1@}%
{%
\PackageError{glossaries}%
{Can't define '\string#6' as helper command
'\expandafter\string\csname @Gls@user@#1@\endcsname' already
exists}%
{}%
}%
{%
\expandafter\newcommand\expandafter*\expandafter
{\csname @Gls@user@#1\endcsname}[2][{}]{%
\new@ifnextchar[%
{\csuse{@Gls@user@#1@}{##1}{##2}}%
{\csuse{@Gls@user@#1@}{##1}{##2}[{}]}%
\csdef{@Gls@user@#1@}##1##2[##3]{%

```

```

\@gls@field@link[\let\glscapscase\@secondofthree]%
{##1}{##2}{#4{##2}##3}%
}%
\newrobustcmd*{#6}{%
\expandafter\@gls@hyp@opt\csname @Gls@user@#1\endcsname}%
}%
\ifcsdef{@Gls@user@#1@}%
{%
\PackageError{glossaries}%
{Can't define '\string#7' as helper command
'\expandafter\string\csname @Gls@user@#1\endcsname' already
exists}%
}%
}%
{%
\expandafter\newcommand\expandafter*\expandafter
{\csname @Gls@user@#1\endcsname}[2][{}]{%
\new@ifnextchar[%
{\csuse{@Gls@user@#1@}{##1}{##2}}%
{\csuse{@Gls@user@#1@}{##1}{##2}[]}}%
\csdef{@Gls@user@#1@}##1##2[##3]{%
\@gls@field@link[\let\glscapscase\@thirdofthree]%
{##1}{##2}{\mfirstucMakeUppercase{#3{##2}##3}}%
}%
\newrobustcmd*{#7}{%
\expandafter\@gls@hyp@opt\csname @Gls@user@#1\endcsname}%
}%
}%
{%
\PackageError{glossaries-extra}{Key '#1' already exists}{}%
}%
}
\providecommand*{\@gls@link@nocheckfirsthyper}{}
\let\@glstrifwasfirstuse\@gls@link@checkfirsthyper
\renewcommand*{\@gls@link@checkfirsthyper}{%
\ifglslabeled{\glslabel}%
{\let\glstrifwasfirstuse\@secondoftwo}
{\let\glstrifwasfirstuse\@firstoftwo}%
\protected@edef\glscategorylabel{\glscategory{\glslabel}}%
\ifglslabeled{\glslabel}%
{%
\glslifcategoryattribute{\glscategorylabel}{nohypernext}{true}%
{\KV@glslink@hyperfalse}{}%
}%
}%
\glslifcategoryattribute{\glscategorylabel}{nohyperfirst}{true}%
{\KV@glslink@hyperfalse}{}%
}%
\glslinkcheckfirsthyperhook
}

```

```

\ifdef\do@gl:disablehyperinlist
{%
\let\@gl:extr@do@gl:disablehyperinlist\do@gl:disablehyperinlist
\renewcommand*{\do@gl:disablehyperinlist}{%
\@gl:extr@do@gl:disablehyperinlist
\gl:ifattribute{\gl:label}{nohyper}{true}{\KV@gl:link@hyperfalse}{}%
}
}
{}
\define@boolkey{gl:link}{noindex}[true]{}
\KV@gl:link@noindexfalse
\providecommand*{\@gl:save@gl:local}{%
\let@if@org@KV@gl:link@local@ifKV@gl:link@local
}
\providecommand*{\@gl:restore@gl:local}{%
\ifKV@gl:link@local
\let\@gl:do@gl:sunset\gl:localunset
\else
\let\@gl:do@gl:sunset\gl:sunset
\fi
}
\providecommand*{\@gl:do@gl:sunset}[1]{\gl:sunset{#1}}
\ifdef\@gl:setdefault@gl:link@opts
{
\renewcommand*{\@gl:setdefault@gl:link@opts}{%
\KV@gl:link@noindexfalse
\@gl:extrasetaliasnoindex
}
}
{
\newcommand*{\@gl:setdefault@gl:link@opts}{%
\KV@gl:link@noindexfalse
\@gl:extrasetaliasnoindex
}
\preto\do@gl:disablehyperinlist{\@gl:setdefault@gl:link@opts}
}
\providecommand*{\gl:extrasetaliasnoindex}{%
\KV@gl:link@noindextrue
}
\newcommand*{\@gl:extrasetaliasnoindex}{%
\ifcvoid{glo@\gl:detoklabel{\gl:label}@alias}%
{}%
{%
\let\gl:extrindexaliased\@gl:extrindexaliased
\gl:extrasetaliasnoindex
\let\gl:extrindexaliased\@no@gl:extrindexaliased
}%
}
\newcommand{\@gl:extrindexaliased}{%
\ifKV@gl:link@noindex

```

```

\else
  \begingroup
  \let\@glsnumberformat\@glsxtr@defaultnumberformat
  \protected@edef\@gls@counter{\csname glo@glstetoklabel{\glslabel}@counter\endcsname}%
  \glsxtr@saveentrycounter
  \@@do@wrglossary{\glsxtralias{\glslabel}}%
  \endgroup
\fi
}
\newcommand{\@no@glsxtrindexaliased}{%
  \PackageError{glossaries-extra}{\string\glsxtrindexaliased\space
    not permitted outside definition of \string\glsxtrsetaliasnoindex}%
  {}%
}
\let\glsxtrindexaliased\@no@glsxtrindexaliased
\newcommand*{\GlsXtrSetDefaultGlsOpts}[1]{%
  \renewcommand*{\@gls@setdefault@glslink@opts}{%
    \setkeys{glslink}{#1}%
    \@glsxtrsetaliasnoindex
  }%
}
\newcommand*{\glsxtrifindexing}[2]{%
  \ifKV@glslink@noindex #2\else #1\fi
}
\renewcommand*{\glswriteentry}[2]{%
  \glsxtrifindexing
  {%
    \ifglsindexonlyfirst
      \GlsXtrIfUnusedOrUndefined{#1}
      {#2}%
      {\glsxtrdoautoindexname{#1}{dualindex}}%
    \else
      \glsifattribute{#1}{indexonlyfirst}{true}%
      {%
        \GlsXtrIfUnusedOrUndefined{#1}%
        {#2}%
        {\glsxtrdoautoindexname{#1}{dualindex}}%
      }%
      {#2}%
    \fi
  }%
  {}%
}
\appto\@@do@wrglossary{\@glsxtr@do@wrindex
  \glsxtrdowrglossaryhook{\@gls@label}%
}
\appto\gls@noidxglossary{\@glsxtr@do@wrindex
  \glsxtrdowrglossaryhook{\@gls@label}%
}
\newcommand*{\@glsxtr@do@wrindex}{%

```

```

\glstrdoautoindexname{\@gls@label}{dualindex}%
}
\newcommand*\glstrdowrglossaryhook}[1]{%
\newcommand*\@gls@alt@hyp@opt}[1]{%
\let\glslinkvar\@firstofthree
\let\@gls@hyp@opt@cs#1\relax
\@ifstar{\s@gls@hyp@opt}%
{\@ifnextchar+%
{\@firstoftwo{\p@gls@hyp@opt}}%
{%
\expandafter\@ifnextchar\@gls@alt@hyp@opt@char
{\@firstoftwo{\@alt@gls@hyp@opt}}%
{#1}%
}%
}%
}
\newcommand*\@alt@gls@hyp@opt}[1][1]{%
\let\glslinkvar\@firstofthree
\expandafter\@gls@hyp@opt@cs\expandafter[\@gls@alt@hyp@opt@keys,#1]}
\newcommand*\@gls@alt@hyp@opt@char{}
\newcommand*\@gls@alt@hyp@opt@keys{}
\newcommand*\GlsXtrSetAltModifier}[2]{%
\let\@gls@hyp@opt\@gls@alt@hyp@opt
\ifstrequal{#1}{+}%
{\PackageError{glossaries-extra}%
{Can't use '#1' as modifier (it's already in use)}{}}%
{%
\ifstrequal{#1}{*}%
{\PackageError{glossaries-extra}%
{Can't use '#1' as modifier (it's already in use)}{}}%
{}}%
}%
\def\@gls@alt@hyp@opt@char{#1}%
\def\@gls@alt@hyp@opt@keys{#2}%
\ifdefequal\@glstr@record@setting\@glstr@record@setting@off
{}%
{%
\protected@write\@auxout{}\string\providecommand{\string\@glstr@altmodifier}[1]{}%
\protected@write\@auxout{}\string\@glstr@altmodifier{#1}%
}%
}
\let\glstr@org@dohyperlink\glstdohyperlink
\ifdef\glssnavhyperlink
{
\renewcommand*\glssnavhyperlink}[3][\@glo@type]{%
\protected@edef\gls@grplabel{#2}\protected@edef\gls@grptitle{#3}%
{%
\let\glstrdohyperlink\glstr@org@dohyperlink
\@glslink{\glssnavhyperlinkname{#1}{#2}}{#3}%
}%
}

```



```

    }%
}
{}
\ifdef\@gls@navhypertarget
{}
{%
\renewcommand*\glsnavhypertarget{\protect\@gls@navhypertarget}
\newcommand*\@gls@navhypertarget[3][\@glo@type]{%
\glsnavhypertarget{#1}{#2}{#3}%
}
}%
\ifdef\@glsnavhypertarget
{%
\renewcommand*\@glsnavhypertarget[3]{%
\protected@write\@auxout{}\string\@gls@hypergroup{#1}{#2}}%
\@glsxtr@do@org@target{\glsnavhyperlinkname{#1}{#2}}{#3}%
\ifcsdef\@gls@hypergroup@list@#1{%
{%
\letcs\@gls@list{\@gls@hypergroup@list@#1}%
\protected@edef\@gls@thishypernavlabel{#2}%
\expandafter\DTLifinlist\expandafter{\@gls@thishypernavlabel}\@gls@list}%
}%
\GlossariesWarningNoLine{Navigation panel
for glossary type ‘#1’^^Jmissing group ‘#2’}%
\gdef\gls@hypergroup@prerun{%
\GlossariesWarningNoLine{Navigation panel
has changed. Rerun LaTeX}}%
}%
}%
}%
{}
\newcommand*\glsxtrdohyperlink[2]{%
\gls@hasattribute{\glslabel}{targeturl}%
{%
\gls@hasattribute{\glslabel}{targetname}%
{%
\gls@hasattribute{\glslabel}{targetcategory}%
{%
\hyperref{\gls@getattribute{\glslabel}{targeturl}}%
{\gls@getattribute{\glslabel}{targetcategory}}%
{\gls@getattribute{\glslabel}{targetname}}%
{\glsxtrprotectlinks#2}}%
}
}
}
}

```

```

}%
{%
  \hyperref{\glsgetattribute{\glslabel}{targeturl}}%
  {}%
  {\glsgetattribute{\glslabel}{targetname}}%
  {\{\glsxtrprotectlinks#2}}%
}%
}%
{%
  \href{\glsgetattribute{\glslabel}{targeturl}}%
  {\{\glsxtrprotectlinks#2}}%
}%
}%
{%
  \glsfieldfetch{\glslabel}{alias}{\gloaliaslabel}%
  \ifdefvoid\gloaliaslabel
  {%
    \glsxtrhyperlink{#1}{\{\glsxtrprotectlinks#2}}%
  }%
  {%
    \glsxtrifmulti\gloaliaslabel
    {%
      \letcs\gloaliaslabel{\gls@combined@\gloaliaslabel @main}%
    }%
    {}%
    \glsxtrhyperlink
    {\glolinkprefix\glsdetoklabel{\gloaliaslabel}}%
    {\{\glsxtrprotectlinks#2}}%
  }%
}%
}%
}

\newcommand{\glsxtrhyperlink}[2]{%
  \glsdoshowtarget{#1}{\hyperlink{#1}{#2}}%
}%
\renewrobustcmd*{\glshyperlink}[2][\glsentrytext{\@glo@label}]{%
  \glsdoifexists{#2}%
  {%
    \def\@glo@label{#2}%
    {\protected@edef\glslabel{#2}%
      \@glslink{\glolinkprefix\glslabel}{#1}}%
  }%
}
\renewcommand{\glsdisablehyper}{%
  \KV@glslink@hyperfalse
  \def\@glslink{\glsdonohyperlink}%
  \let\@gls@target\@secondoftwo
}
\renewcommand{\glsenablehyper}{%
  \KV@glslink@hypertrue

```

```

\def\@glslink{\glsxtrdohyperlink}%
\def\@glstarget{\glsdohypertarget}%
}
\def\glsdonohyperlink#1#2{{\glsxtrprotectlinks #2}}
\ifcsundef{hyperlink}%
{%
\def\@glslink{\glsdonohyperlink}
}%
{%
\def\@glslink{\glsxtrdohyperlink}
}
\newcommand*{\glsxtrprotectlinks}{%
\KV@glslink@hyperfalse
\KV@glslink@noindextrue
\let\@gls@\@glsxtr@p@text@
\let\@Gls@\@Glsxtr@p@text@
\let\@GLS@\@GLSxtr@p@text@
\let\@glspl@\@glsxtr@p@plural@
\let\@Glspl@\@Glsxtr@p@plural@
\let\@GLSpl@\@GLSxtr@p@plural@
\let\@glsxtrshort@\@glsxtr@p@short@
\let\@Glsxtrshort@\@Glsxtr@p@short@
\let\@GLSxtrshort@\@GLSxtr@p@short@
\let\@glsxtrlong@\@glsxtr@p@long@
\let\@Glsxtrlong@\@Glsxtr@p@long@
\let\@GLSxtrlong@\@GLSxtr@p@long@
\let\@glsxtrshortpl@\@glsxtr@p@shortpl@
\let\@Glsxtrshortpl@\@Glsxtr@p@shortpl@
\let\@GLSxtrshortpl@\@GLSxtr@p@shortpl@
\let\@glsxtrlongpl@\@glsxtr@p@longpl@
\let\@Glsxtrlongpl@\@Glsxtr@p@longpl@
\let\@GLSxtrlongpl@\@GLSxtr@p@longpl@
\let\@acrshort@\@glsxtr@p@acrshort@
\let\@Acrshort@\@Glsxtr@p@acrshort@
\let\@ACRshort@\@GLSxtr@p@acrshort@
\let\@acrshortpl@\@glsxtr@p@acrshortpl@
\let\@Acrshortpl@\@Glsxtr@p@acrshortpl@
\let\@ACRshortpl@\@GLSxtr@p@acrshortpl@
\let\@acrlong@\@glsxtr@p@acrlong@
\let\@Acrlong@\@Glsxtr@p@acrlong@
\let\@ACRlong@\@GLSxtr@p@acrlong@
\let\@acrlongpl@\@glsxtr@p@acrlongpl@
\let\@Acrlongpl@\@Glsxtr@p@acrlongpl@
\let\@ACRlongpl@\@GLSxtr@p@acrlongpl@
}
\def\@glsxtr@p@text@#1#2[#3]{{\@glstext@{#1}{#2}[#3]}}
\def\@Glsxtr@p@text@#1#2[#3]{{\@Glstext@{#1}{#2}[#3]}}
\def\@GLSxtr@p@text@#1#2[#3]{{\@GLStext@{#1}{#2}[#3]}}
\def\@glsxtr@p@plural@#1#2[#3]{{\@glsplural@{#1}{#2}[#3]}}
\def\@Glsxtr@p@plural@#1#2[#3]{{\@Glsplural@{#1}{#2}[#3]}}

```

```

\def\@GLSxtr@p@plural@#1#2[#3]{\@GLSplural@{#1}{#2}[#3]}
\def\@GLSxtr@p@short@#1#2[#3]{%
  {%
    \glsssetabbrvfmt{\glscategory{#2}}%
    \glssabbrvfont{\glssentryshort{#2}}#3%
  }%
}
\def\@GLSxtr@p@short@#1#2[#3]{%
  {%
    \glsssetabbrvfmt{\glscategory{#2}}%
    \glssabbrvfont{\glssentryshort{#2}}#3%
  }%
}
\def\@GLSxtr@p@short@#1#2[#3]{%
  {%
    \glsssetabbrvfmt{\glscategory{#2}}%
    \mfirstucMakeUppercase{\glssabbrvfont{\glssentryshort{#2}}#3}%
  }%
}
\def\@GLSxtr@p@shortpl@#1#2[#3]{%
  {%
    \glsssetabbrvfmt{\glscategory{#2}}%
    \glssabbrvfont{\glssentryshortpl{#2}}#3%
  }%
}
\def\@GLSxtr@p@shortpl@#1#2[#3]{%
  {%
    \glsssetabbrvfmt{\glscategory{#2}}%
    \glssabbrvfont{\glssentryshortpl{#2}}#3%
  }%
}
\def\@GLSxtr@p@shortpl@#1#2[#3]{%
  {%
    \glsssetabbrvfmt{\glscategory{#2}}%
    \mfirstucMakeUppercase{\glssabbrvfont{\glssentryshortpl{#2}}#3}%
  }%
}
\def\@GLSxtr@p@long@#1#2[#3]{\glssentrylong{#2}#3}
\def\@GLSxtr@p@long@#1#2[#3]{\glssentrylong{#2}#3}
\def\@GLSxtr@p@long@#1#2[#3]{%
  {\mfirstucMakeUppercase{\glsslongfont{\glssentrylong{#2}}#3}}
\def\@GLSxtr@p@longpl@#1#2[#3]{\glssentrylongpl{#2}#3}
\def\@GLSxtr@p@longpl@#1#2[#3]{\glsslongfont{\glssentrylongpl{#2}}#3}
\def\@GLSxtr@p@longpl@#1#2[#3]{%
  {\mfirstucMakeUppercase{\glsslongfont{\glssentrylongpl{#2}}#3}}
\def\@GLSxtr@p@acrshort@#1#2[#3]{\acronymfont{\glssentryshort{#2}}#3}
\def\@GLSxtr@p@acrshort@#1#2[#3]{\acronymfont{\glssentryshort{#2}}#3}
\def\@GLSxtr@p@acrshort@#1#2[#3]{%
  {\mfirstucMakeUppercase{\acronymfont{\glssentryshort{#2}}#3}}
\def\@GLSxtr@p@acrshortpl@#1#2[#3]{\acronymfont{\glssentryshortpl{#2}}#3}

```

```

\def\@Glsxtr@p@acrshortpl@#1#2[#3]{\acronymfont{\Glsentryshortpl{#2}#3}}
\def\@GLSxtr@p@acrshortpl@#1#2[#3]{%
  {\mfirstucMakeUppercase{\acronymfont{\Glsentryshortpl{#2}#3}}}
\def\@glxtr@p@acrlong@#1#2[#3]{\Glsentrylong{#2}#3}}
\def\@Glsxtr@p@acrlong@#1#2[#3]{\Glsentrylong{#2}#3}}
\def\@GLSxtr@p@acrlong@#1#2[#3]{%
  {\mfirstucMakeUppercase{\Glsentrylong{#2}#3}}}
\def\@glxtr@p@acrlongpl@#1#2[#3]{\Glsentrylongpl{#2}#3}}
\def\@Glsxtr@p@acrlongpl@#1#2[#3]{\Glsentrylongpl{#2}#3}}
\def\@GLSxtr@p@acrlongpl@#1#2[#3]{%
  {\mfirstucMakeUppercase{\Glsentrylongpl{#2}#3}}}
\newcommand*{\@glxtrp@opt}{hyper=false,noindex}
\newcommand*{\@glxtrsetpopts}[1]{%
  \renewcommand*{\@glxtrp@opt}{#1}%
}
\newcommand*{\@glossxtrsetpopts}{%
  \@glxtrsetpopts{noindex}%
}
\newrobustcmd*{\@@glxtrp}[2]{%
  {%
    \let\glspostlinkhook\relax
    \csname#1\expandafter\endcsname\expandafter[\@glxtrp@opt]{#2}[]%
  }%
}
\newrobustcmd*{\@glxtrp}[2]{%
  \ifcsdef{gls#1}%
  {%
    \@@glxtrp{gls#1}{#2}%
  }%
  {%
    \ifcsdef{glsxtr#1}%
    {%
      \@@glxtrp{glsxtr#1}{#2}%
    }%
    {%
      \PackageError{glossaries-extra}{‘#1’ not recognised by
        \string\glxtrp}{}%
    }%
  }%
}
\newrobustcmd*{\@Glsxtrp}[2]{%
  \ifcsdef{Gls#1}%
  {%
    \@@glxtrp{Gls#1}{#2}%
  }%
  {%
    \ifcsdef{Glsxtr#1}%
    {%
      \@@glxtrp{Glsxtr#1}{#2}%
    }%
  }%
}

```

```

    {%
      \PackageError{glossaries-extra}{‘#1’ not recognised by
        \string\Glsxtrp}{}%
    }%
  }%
}
\newrobustcmd*{\@GLSxtrp}[2]{%
  \ifcsdef{GLS#1}%
  {%
    \@glsxtrp{GLS#1}{#2}%
  }%
  {%
    \ifcsdef{GLSxtr#1}%
    {%
      \@glsxtrp{GLSxtr#1}{#2}%
    }%
    {%
      \PackageError{glossaries-extra}{‘#1’ not recognised by
        \string\GLSxtrp}{}%
    }%
  }%
}
\newrobustcmd*{\glsxtr@headentry@p}[2]{%
  \glsifattribute{#1}{headuc}{true}%
  {%
    \mfirstucMakeUppercase{\@gls@entry@field{#1}{#2}}%
  }%
  {%
    \@gls@entry@field{#1}{#2}%
  }%
}
\ifdef\texorpdfstring
{
  \newcommand{\glsxtrp}[2]{%
    \protect\NoCaseChange
    {%
      \protect\texorpdfstring
      {%
        \protect\glsxtrifinmark
        {%
          \ifcsdef{glsxtrhead#1}%
          {%
            {\protect\csuse{glsxtrhead#1}{#2}}%
          }%
          {%
            \glsxtr@headentry@p{#2}{#1}%
          }%
        }%
      }%
      {%
        \@glsxtrp{#1}{#2}%
      }%
    }%
  }%
}

```

```

        }%
    }%
    {%
        \protect\@gls@entry@field{#2}{#1}%
    }%
}%
}
}
{
    \newcommand{\glsxtrp}[2]{%
        \protect\NoCaseChange
        {%
            \protect\glsxtrifinmark
            {%
                \ifcsdef{glsxtrhead#1}%
                {%
                    {\protect\csuse{glsxtrhead#1}}%
                }%
                {%
                    \glsxtr@headentry@p{#2}{#1}%
                }%
            }%
            {%
                \@glsxtrp{#1}{#2}%
            }%
        }%
    }
}
\newcommand*{\glsps}{\glsxtrp{short}}
\newcommand*{\glspt}{\glsxtrp{text}}
\ifdef\texorpdfstring
{
    \newcommand{\Glsxtrp}[2]{%
        \protect\NoCaseChange
        {%
            \protect\texorpdfstring
            {%
                \protect\glsxtrifinmark
                {%
                    \ifcsdef{Glsxtrhead#1}%
                    {%
                        {\protect\csuse{Glsxtrhead#1}{#2}}%
                    }%
                    {%
                        \protect\@Gls@entry@field{#2}{#1}%
                    }%
                }%
            }%
            {%
                \@Glsxtrp{#1}{#2}%
            }%
        }%
    }
}

```

```

    }%
    {%
    \protect\@gls@entry@field{#2}{#1}%
    }%
  }%
}
}
{
  \newcommand{\Glsxtrp}[2]{%
    \protect\NoCaseChange
    {%
      \protect\glsxtrifinmark
      {%
        \ifcsdef{Glsxtrhead#1}%
        {%
          {\protect\cuse{Glsxtrhead#1}}%
        }%
        {%
          \protect\@Gls@entry@field{#2}{#1}%
        }%
      }%
      {%
        \@Glsxtrp{#1}{#2}%
      }%
    }%
  }
}
\ifdef\texorpdfstring
{
  \newcommand{\GLSxtrp}[2]{%
    \protect\NoCaseChange
    {%
      \protect\texorpdfstring
      {%
        \protect\glsxtrifinmark
        {%
          \ifcsdef{GLSxtr#1}%
          {%
            {\protect\GLSxtrshort[noindex,hyper=false]{#1}[]}%
          }%
          {%
            \protect\mfirstucMakeUppercase
            {%
              \protect\@gls@entry@field{#2}{#1}%
            }%
          }%
        }%
      }%
      {%
        \@GLSxtrp{#1}{#2}%
      }%
    }
  }
}

```



```

    }%
    {%
        \protect\@gls@entry@field{#2}{#1}%
    }%
}%
}
}
{
    \newcommand{\GLSxtrp}[2]{%
        \protect\NoCaseChange
        {%
            \protect\glsxtrifinmark
            {%
                \ifcsdef{GLSxtr#1}%
                {%
                    {\protect\GLSxtrshort[noindex,hyper=false]{#1}[]}%
                }%
                {%
                    \protect\mfirstucMakeUppercase
                    {%
                        \protect\@gls@entry@field{#2}{#1}%
                    }%
                }%
            }%
        }%
        {%
            \@GLSxtrp{#1}{#2}%
        }%
    }%
}
}
\newcommand*{\@glsxtr@unset}[1]{%
    \@glsunset{#1}%
    \glsxtrpostunset{#1}%
}%
\let\@glsunset\@glsxtr@unset
\newcommand*{\glsxtrpostunset}[1]{%
\newcommand*{\GlsXtrStartUnsetBuffering}{%
    \ifstar\s@GlsXtrStartUnsetBuffering\@GlsXtrStartUnsetBuffering
}
\newcommand*{\@GlsXtrStartUnsetBuffering}{%
    \let\@glsxtr@org@unset@buffer\@glsxtr@unset@buffer
    \def\@glsxtr@unset@buffer{}%
    \let\@glsunset\@glsxtrbuffer@unset
}
\newcommand*{\s@GlsXtrStartUnsetBuffering}{%
    \let\@glsxtr@org@unset@buffer\@glsxtr@unset@buffer
    \def\@glsxtr@unset@buffer{}%
    \let\@glsunset\@glsxtrbuffer@nodup@unset
}
\newcommand*{\@glsxtrbuffer@unset}[1]{%

```

```

\listxadd\@glxtr@unset@buffer{#1}%
}
\newcommand*{\@glxtrbuffer@nodup@unset}[1]{%
\expandafter\ifinlist\expandafter{#1}-{\@glxtr@unset@buffer}{}%
{\listxadd\@glxtr@unset@buffer{#1}}%
}
\newcommand*{\GlsXtrStopUnsetBuffering}{%
\ifstar\s@GlsXtrStopUnsetBuffering\@GlsXtrStopUnsetBuffering
}
\newcommand*{\@GlsXtrStopUnsetBuffering}{%
\let\@glsunset\@glxtr@unset
\forlistloop\@glsunset\@glxtr@unset@buffer
\let\@glxtr@unset@buffer\@glxtr@org@unset@buffer
}
\newcommand*{\s@GlsXtrStopUnsetBuffering}{%
\forlistloop\@glslounset\@glxtr@unset@buffer
\let\@glsunset\@glxtr@unset
}
\newcommand*{\GlsXtrDiscardUnsetBuffering}{%
\let\@glsunset\@glxtr@unset
\let\@glxtr@unset@buffer\@glxtr@org@unset@buffer
}
\newcommand*{\GlsXtrForUnsetBufferedList}[1]{%
\forlistloop#1\@glxtr@unset@buffer
}
\renewcommand*{\@glslounset}[1]{%
\@glslounset{#1}%
\glxtrpostlounset{#1}%
}%
\newcommand*{\glxtrpostlounset}[1]{}
\renewcommand*{\@glreset}[1]{%
\@glreset{#1}%
\glxtrpostreset{#1}%
}%
\newcommand*{\glxtrpostreset}[1]{}
\renewcommand*{\@glslounset}[1]{%
\@glslounset{#1}%
\glxtrpostlounset{#1}%
}%
\newcommand*{\glxtrpostlounset}[1]{}
\newcommand*{\glslounseteach}[1]{%
\gl@ifnotmeasuring
{%
\for\@gl@thislabel:=#1\do{%
\gl@ifexists{\@gl@thislabel}%
{%
\@glslounset{\@gl@thislabel}%
}%
}%
}%
}%

```

```

}
\newcommand*{\glslocalunseteach}[1]{%
  \gls@ifnotmeasuring
  {%
    \@for\@gls@thislabel:=#1\do{%
      \glsdoifexists{\@gls@thislabel}%
      {%
        \glslocalunset{\@gls@thislabel}%
      }%
    }%
  }%
}
}
\newcommand*{\GlsXtrEnableEntryCounting}[2]{%
  \glsenableentrycount
  \renewcommand*{\gls}{\cglsl}%
  \renewcommand*{\Gls}{\cGls}%
  \renewcommand*{\glspl}{\cglspl}%
  \renewcommand*{\Glspl}{\cGlspl}%
  \renewcommand*{\GLS}{\cGLS}%
  \renewcommand*{\GLSpl}{\cGLSpl}%
  \@glsxtr@setentrycountunsetattr{#1}{#2}%
  \let\GlsXtrEnableEntryCounting\@glsxtr@setentrycountunsetattr
  \renewcommand*{\GlsXtrEnableEntryUnitCounting}[3]{%
    \PackageError{glossaries-extra}{\string\GlsXtrEnableEntryUnitCounting\space
      can't be used with \string\GlsXtrEnableEntryCounting}%
    {Use one or other but not both commands}}%
}
\newcommand*{\@glsxtr@setentrycountunsetattr}[2]{%
  \@for\@glsxtr@cat:=#1\do
  {%
    \ifdefempty{\@glsxtr@cat}{}%
    {%
      \glssetcategoryattribute{\@glsxtr@cat}{entrycount}{#2}%
    }%
  }%
}
}
\renewcommand*{\glsenableentrycount}{%
  \appto\@newglossaryentry@defcounters{\@@newglossaryentry@defcounters}%
  \renewcommand*{\gls@defdocnewglossaryentry}{%
    \renewcommand*newglossaryentry[2]{%
      \PackageError{glossaries}{\stringnewglossaryentry\space
        may only be used in the preamble when entry counting has
        been activated}{If you use \string\glsenableentrycount\space
        you must place all entry definitions in the preamble not in
        the document environment}%
    }%
  }%
}
\newcommand*{\glsentrycurrcount}[1]{%
  \ifcsundef{glo@\glsdetoklabel{##1}@currcount}%
  {0}{\@gls@entry@field{##1}{currcount}}%
}

```

```

}%
\newcommand*{\glsentryprevcount}[1]{%
  \ifcsundef{glo@glsdetoklabel{##1}@prevcount}%
  {0}{\@gls@entry@field{##1}{prevcount}}%
}%
\let\@glsxtr@entrycount@org@unset\glsxtrpostunset
\renewcommand*{\glsxtrpostunset}[1]{%
  \@glsxtr@entrycount@org@unset{##1}%
  \@gls@increment@currcount{##1}%
}%
\let\@glsxtr@entrycount@org@localunset\glsxtrpostlocalunset
\renewcommand*{\glsxtrpostlocalunset}[1]{%
  \@glsxtr@entrycount@org@localunset{##1}%
  \@gls@local@increment@currcount{##1}%
}%
\let\@glsxtr@entrycount@org@reset\glsxtrpostreset
\renewcommand*{\glsxtrpostreset}[1]{%
  \@glsxtr@entrycount@org@reset{##1}%
  \csgdef{glo@glsdetoklabel{##1}@currcount}{0}%
}%
\let\@glsxtr@entrycount@org@localreset\glsxtrpostlocalreset
\renewcommand*{\glsxtrpostlocalreset}[1]{%
  \@glsxtr@entrycount@org@localreset{##1}%
  \csdef{glo@glsdetoklabel{##1}@currcount}{0}%
}%
\let\@cgls@\@cgls@
\let\@cglspl@\@cglspl@
\let\@cGls@\@cGls@
\let\@cGlspl@\@cGlspl@
\let\@cGLS@\@cGLS@
\let\@cGLSpl@\@cGLSpl@
\AtEndDocument{\@gls@write@entrycounts}%
\renewcommand*{\@gls@entry@count}[2]{%
  \csgdef{glo@glsdetoklabel{##1}@prevcount}{##2}%
}%
\let\glsenableentrycount\relax
\renewcommand*{\glsenableentryunitcount}{%
  \PackageError{glossaries-extra}{\string\glsenableentryunitcount\space
    can't be used with \string\glsenableentrycount}%
  {Use one or other but not both commands}%
}%
}
\renewcommand*{\@gls@write@entrycounts}{%
  \immediate\write\@auxout
  {\string\providecommand*{\string\@gls@entry@count}[2]{}}%
  \count@=0\relax
  \forallglsentries{\@glsentry}{%
    \gls@hasattribute{\@glsentry}{entrycount}%
    {%
      \ifglsused{\@glsentry}%

```

```

        {%
            \immediate\write\@auxout
            {\string\@gls@entry@count{\@glsentry}{\glsentrycurrcount{\@glsentry}}}%
        }%
        {}%
        \advance\count@ by \@ne
    }%
    {}%
}%
\ifnum\count@=0
    \GlossariesExtraWarningNoLine{Entry counting has been enabled
    \MessageBreak with \string\glsenableentrycount\space but the
    \MessageBreak attribute 'entrycount' hasn't
    \MessageBreak been assigned to any of the defined
    \MessageBreak entries}%
\fi
}
\newcommand*{\glstrifcounttrigger}[3]{%
    \glshasattribute{#1}{entrycount}%
    {%
        \ifnum\glsentryprevcount{#1}>\glsgetattribute{#1}{entrycount}\relax
        #3%
        \else
        #2%
        \fi
    }%
    {#3}%
}
\def\@cgls@#1#2[#3]{%
    \glstrifcounttrigger{#2}%
    {%
        \cglsformat{#2}{#3}%
        \glsunset{#2}%
    }%
    {%
        \@gls@{#1}{#2}[#3]%
    }%
}%
\def\@cglspl@#1#2[#3]{%
    \glstrifcounttrigger{#2}%
    {%
        \cglsplformat{#2}{#3}%
        \glsunset{#2}%
    }%
    {%
        \@glspl@{#1}{#2}[#3]%
    }%
}%
\def\@cGls@#1#2[#3]{%
    \glstrifcounttrigger{#2}%

```

```

    {%
      \cGlsformat{#2}{#3}%
      \glsunset{#2}%
    }%
    {%
      \@Gls@{#1}{#2}[#3]%
    }%
  }%
\def\@cGlspl@#1#2[#3]{%
  \glsxtrifcounttrigger{#2}%
  {%
    \cGlsplformat{#2}{#3}%
    \glsunset{#2}%
  }%
  {%
    \@Glspl@{#1}{#2}[#3]%
  }%
}%
\def\@cGLS@#1#2[#3]{%
  \glsxtrifcounttrigger{#2}%
  {%
    \cGLSformat{#2}{#3}%
    \glsunset{#2}%
  }%
  {%
    \@GLS@{#1}{#2}[#3]%
  }%
}%
\def\@cGLSpl@#1#2[#3]{%
  \glsxtrifcounttrigger{#2}%
  {%
    \cGLSplformat{#2}{#3}%
    \glsunset{#2}%
  }%
  {%
    \@GLSpl@{#1}{#2}[#3]%
  }%
}%
\def\@cglS@#1#2[#3]{\@gls@{#1}{#2}[#3]}
\def\@cGls@#1#2[#3]{\@Gls@{#1}{#2}[#3]}
\def\@cglSpl@#1#2[#3]{\@glSpl@{#1}{#2}[#3]}
\def\@cGlspl@#1#2[#3]{\@Glspl@{#1}{#2}[#3]}
\newrobustcmd*\cGLS{\@gls@hyp@opt\@cGLS}
\newcommand*\cGLS[2][{}]{%
  \new@ifnextchar[{\@cGLS@{#1}{#2}}{\@cGLS@{#1}{#2}[]}%
}
\def\@cGLS@#1#2[#3]{\@GLS@{#1}{#2}[#3]}
\newcommand*\cGLSformat[2]{%
  \expandafter\mfirstuc\MakeUppercase\expandafter{\cglSformat{#1}{#2}}%
}

```

```

\newrobustcmd*{\cGLSpl}{\@gls@hyp@opt\@cGLSpl}
\newcommand*{\@cGLSpl}[2][\%
  \new@ifnextchar[{\@cGLSpl@{#1}{#2}}{\@cGLSpl@{#1}{#2}[]}%
}
\def\@cGLSpl@#1#2[#3]{\@GLSpl@{#1}{#2}[#3]}
\newcommand*{\cGLSplformat}[2]{\%
  \expandafter\mfirstuc\MakeUppercase\expandafter{\cglsplformat{#1}{#2}}%
}
\renewcommand*{\cglformat}[2]{\%
  \glsifregular{#1}
  {\glsentryfirst{#1}}%
  {\ifglshaslong{#1}{\glsentrylong{#1}}{\glsentryfirst{#1}}#2}%
}
\renewcommand*{\cGlsformat}[2]{\%
  \glsifregular{#1}
  {\Glsentryfirst{#1}}%
  {\ifglshaslong{#1}{\Glsentrylong{#1}}{\Glsentryfirst{#1}}#2}%
}
\renewcommand*{\cglsplformat}[2]{\%
  \glsifregular{#1}
  {\glsentryfirstplural{#1}}%
  {\ifglshaslong{#1}{\glsentrylongpl{#1}}{\glsentryfirstplural{#1}}#2}%
}
\renewcommand*{\cGlsplformat}[2]{\%
  \glsifregular{#1}
  {\Glsentryfirstplural{#1}}%
  {\ifglshaslong{#1}{\Glsentrylongpl{#1}}{\Glsentryfirstplural{#1}}#2}%
}
\newcommand*{\@newglossaryentry@defunitcounters}{\%
  \protected@edef\@glo@countunit{\csuse{@glxtr@categoryattr@{\@glo@category @unitcount}}}%
  \ifdefvoid\@glo@countunit
  {}%
  {%
    \@glxtr@ifunitcounter{\@glo@countunit}%
    {}%
    {\expandafter\@glxtr@addunitcounter\expandafter{\@glo@countunit}}%
  }%
}
\newcommand*{\@glxtr@unitcountlist}{}
\newcommand*{\@glxtr@addunitcounter}[1]{\%
  \listadd{\@glxtr@unitcountlist}{#1}%
  \ifcsundef{glxtr@theunit@#1}
  {%
    \ifcsdef{theH#1}%
    {\csdef{glxtr@theunit@#1}{\csuse{theH#1}}}%
    {\csdef{glxtr@theunit@#1}{\csuse{the#1}}}%
  }%
  {}%
}
\newcommand*{\@glxtr@ifunitcounter}[3]{\%

```

```

\ifinlist{#1}{\@glxstr@unitcountlist}{#2}{#3}%
}
\newcommand*\@glxstr@currentunitcount[1]{%
  glo@\glsdetoklabel{#1}@currunit@\glsggetattribute{#1}{unitcount}.%
  \csuse{glxstr@theunit@\glsggetattribute{#1}{unitcount}}%
}
\newcommand*\@glxstr@previousunitcount[1]{%
  glo@\glsdetoklabel{#1}@prevunit@\glsggetattribute{#1}{unitcount}.%
  \csuse{glxstr@theunit@\glsggetattribute{#1}{unitcount}}%
}
\newcommand*\@glsg@increment@currunitcount[1]{%
  \glshasattribute{#1}{unitcount}%
  {%
    \protected@edef\@glxstr@csname{\@glxstr@currentunitcount{#1}}%
    \ifcsundef{\@glxstr@csname}%
    {%
      \csgdef{\@glxstr@csname}{1}%
      \listcsxadd
      {glo@\glsdetoklabel{#1}@unitlist}%
      {\glsggetattribute{#1}{unitcount}.%
        \csuse{glxstr@theunit@\glsggetattribute{#1}{unitcount}}}%
    }%
  }%
  {%
    \csxdef{\@glxstr@csname}%
    {\number\numexpr\csname\@glxstr@csname\endcsname+1}%
  }%
}%
{}%
}
\newcommand*\@glsg@local@increment@currunitcount[1]{%
  \glshasattribute{#1}{unitcount}%
  {%
    \protected@edef\@glxstr@csname{\@glxstr@currentunitcount{#1}}%
    \ifcsundef{\@glxstr@csname}%
    {%
      \csdef{\@glxstr@csname}{1}%
      \listcseadd
      {glo@\glsdetoklabel{#1}@unitlist}%
      {\glsggetattribute{#1}{unitcount}.%
        \csuse{glxstr@theunit@\glsggetattribute{#1}{unitcount}}}%
    }%
  }%
  {%
    \csedef{\@glxstr@csname}%
    {\number\numexpr\csname\@glxstr@csname\endcsname+1}%
  }%
}%
{}%
}

```



```

\newcommand*{\@glstr@currunitcount}[2]{%
\ifcsundef
{glo@\glstetoklabel{#1}@currunit@#2}%
{0}%
{\csuse{glo@\glstetoklabel{#1}@currunit@#2}}%
}%
\newcommand*{\@glstr@prevunitcount}[2]{%
\ifcsundef
{glo@\glstetoklabel{#1}@prevunit@#2}%
{0}%
{\csuse{glo@\glstetoklabel{#1}@prevunit@#2}}%
}%
\newcommand*{\glsenableentryunitcount}{%
\appto\@newglossaryentry@defcounters{\@newglossaryentry@defunitcounters}%
\renewcommand*{\glstetoklabel@defdocnewglossaryentry}{%
\renewcommand*{\newglossaryentry}[2]{%
\PackageError{glossaries}{\string\newglossaryentry\space
may only be used in the preamble when entry counting has
been activated}{If you use \string\glsenableentryunitcount\space
you must place all entry definitions in the preamble not in
the document environment}%
}%
}%
\newcommand*{\glstetoklabel@currunitcount}[1]{%
\@glstr@currunitcount{##1}{\glstetoklabel{##1}{unitcount}}.%
\csuse{\glstr@theunit@\glstetoklabel{##1}{unitcount}}}%
}%
\newcommand*{\glstetoklabel@prevunitcount}[1]{%
\@glstr@prevunitcount{##1}{\glstetoklabel{##1}{unitcount}}.%
\csuse{\glstr@theunit@\glstetoklabel{##1}{unitcount}}}%
}%
\newcommand*{\glstetoklabel@prevtotalcount}[1]{%
\ifcsundef{glo@\glstetoklabel{##1}@prevunittotal}%
{0}%
{%
\number\csuse{glo@\glstetoklabel{##1}@prevunittotal}
}%
}%
\newcommand*{\glstetoklabel@prevmaxcount}[1]{%
\ifcsundef{glo@\glstetoklabel{##1}@prevunitmax}%
{0}%
{%
\number\csuse{glo@\glstetoklabel{##1}@prevunitmax}
}%
}%
\let\@glstr@entryunitcount@org@unset\glstrpostunset
\renewcommand*{\glstrpostunset}[1]{%
\@glstr@entryunitcount@org@unset{##1}%
\@glstetoklabel@currunitcount{##1}%
}%

```

```

\let\@glsxtr@entryunitcount@org@localunset\glsxtrpostlocalunset
\renewcommand*{\glsxtrpostlocalunset}[1]{%
  \@glsxtr@entryunitcount@org@localunset{##1}%
  \@gls@local@increment@currunitcount{##1}%
}%
\let\@glsxtr@entryunitcount@org@reset\glsxtrpostreset
\renewcommand*{\glsxtrpostreset}[1]{%
  \gls@hasattribute{##1}{unitcount}%
  {%
    \protected@edef\@glsxtr@csname{\@glsxtr@currentunitcount{##1}}%
    \ifcsundef{\@glsxtr@csname}%
    {}%
    {\csgdef{\@glsxtr@csname}{0}}%
  }%
  {}%
}%
\let\@glsxtr@entryunitcount@org@localreset\glsxtrpostlocalreset
\renewcommand*{\glsxtrpostlocalreset}[1]{%
  \@glsxtr@entryunitcount@org@localreset{##1}%
  \gls@hasattribute{##1}{unitcount}%
  {%
    \protected@edef\@glsxtr@csname{\@glsxtr@currentunitcount{##1}}%
    \ifcsundef{\@glsxtr@csname}%
    {}%
    {\csdef{\@glsxtr@csname}{0}}%
  }%
  {}%
}%
\let\@cgls@\@cgls@
\let\@cglspl@\@cglspl@
\let\@cGls@\@cGls@
\let\@cGlspl@\@cGlspl@
\let\@cGLS@\@cGLS@
\let\@cGLSpl@\@cGLSpl@
\AtEndDocument{\@gls@write@entryunitcounts}%
\renewcommand*{\@gls@entry@unitcount}[3]{%
  \csgdef{glo@glsdetoklabel{##1}@prevunit@##3}{##2}%
  \ifcsundef{glo@glsdetoklabel{##1}@prevunittotal}%
  {\csgdef{glo@glsdetoklabel{##1}@prevunittotal}{##2}}%
  {%
    \csxdef{glo@glsdetoklabel{##1}@prevunittotal}{%
      \number\numexpr\csuse{glo@glsdetoklabel{##1}@prevunittotal}+##2}%
    }%
    \ifcsundef{glo@glsdetoklabel{##1}@prevunitmax}%
    {\csgdef{glo@glsdetoklabel{##1}@prevunitmax}{##2}}%
    {%
      \ifnum\csuse{glo@glsdetoklabel{##1}@prevunitmax}<##2
      \csgdef{glo@glsdetoklabel{##1}@prevunitmax}{##2}%
      \fi
    }%
  }%

```

```

}%
\let\glsenableentryunitcount\relax
\renewcommand*{\glsenableentrycount}{%
  \PackageError{glossaries-extra}{\string\glsenableentrycount\space
    can't be used with \string\glsenableentryunitcount}%
  {Use one or other but not both commands}%
}%
}
\@onlypreamble\glsenableentryunitcount
\newcommand*{\@gls@entry@unitcount}[3]{%
\newcommand*{\@gls@write@entryunitcounts@do}[1]{%
  \immediate\write\@auxout
  {\string\@gls@entry@unitcount
   {\@glsentry}%
   {\@glsxtr@currunitcount{\@glsentry}{#1}%
   }%
   {#1}}%
}
\newcommand*{\@gls@write@entryunitcounts}{%
  \immediate\write\@auxout
  {\string\providecommand*{\string\@gls@entry@unitcount}[3]{}}%
  \count@=0\relax
  \forallglsentries{\@glsentry}{%
    \gls@hasattribute{\@glsentry}{unitcount}%
    {%
      \ifglsused{\@glsentry}%
      {%
        \forlistcsloop
        {\@gls@write@entryunitcounts@do}%
        {\glo@\glsdetoklabel{\@glsentry}@unitlist}%
      }%
    }%
    \advance\count@ by \@ne
  }%
}%
\ifnum\count@=0
  \GlossariesExtraWarningNoLine{Entry counting has been enabled
    \MessageBreak with \string\glsenableentryunitcount\space but the
    \MessageBreak attribute 'unitcount' hasn't
    \MessageBreak been assigned to any of the defined
    \MessageBreak entries}%
\fi
}
\newcommand*{\GlsXtrEnableEntryUnitCounting}[3]{%
  \glsenableentryunitcount
  \renewcommand*{\gls}{\cgl}%
  \renewcommand*{\Gls}{\cGls}%
  \renewcommand*{\glspl}{\cglspl}%
  \renewcommand*{\Glspl}{\cGlspl}%

```

```

\renewcommand*{\GLS}{\cGLS}%
\renewcommand*{\GLSpl}{\cGLSpl}%
\@glstr@setentryunitcountunsetattr{#1}{#2}{#3}%
\let\GlsXtrEnableEntryUnitCounting\@glstr@setentryunitcountunsetattr
\renewcommand*{\GlsXtrEnableEntryCounting}[2]{%
  \PackageError{glossaries-extra}{\string\GlsXtrEnableEntryCounting\space
    can't be used with \string\GlsXtrEnableEntryUnitCounting}%
  {Use one or other but not both commands}}%
}
\newcommand*{\@glstr@setentryunitcountunsetattr}[3]{%
  \@for\@glstr@cat:=#1\do
  {%
    \ifdefempty{\@glstr@cat}{}%
    {%
      \glsssetcategoryattribute{\@glstr@cat}{entrycount}{#2}%
      \glsssetcategoryattribute{\@glstr@cat}{unitcount}{#3}%
    }%
  }%
}
\renewcommand*{\SetGenericNewAcronym}{%
  \ifdefequal\@addtoacronymlists\@glstr@org@addtoacronymlists
  {}%
  {%
    \GlossariesWarning{\string\SetGenericNewAcronym\space used
      without restoring base acronym functions with
      \string\RestoreAcronyms}%
  }%
  \let\@Gls@entryname\@Gls@acrentryname
  \renewcommand{\newacronym}[4][{}]{%
    \ifdefempty{\@glssacronymlists}%
    {%
      \def\@glo@type{\acronymtype}%
      \setkeys{glossentry}{##1}%
      \DeclareAcronymList{\@glo@type}%
    }%
    {}%
    \glskeylisttok{##1}%
    \glslabeltok{##2}%
    \glsshorttok{##3}%
    \glslongtok{##4}%
    \newacronymhook
    \protected@edef\@do@newglossaryentry{%
      \noexpand\newglossaryentry{\the\glslabeltok}%
      {%
        type=\acronymtype,%
        name={\expandonce{\acronymentry{##2}}},%
        sort={\acronymssort{\the\glsshorttok}{\the\glslongtok}},%
        text={\the\glsshorttok},%
        short={\the\glsshorttok},%
        shortplural={\the\glsshorttok\noexpand\acrpluralsuffix},%

```

```

        long={\the\glslongtok},%
        longplural={\the\glslongtok\noexpand\acrpluralsuffix},%
        category=acronym,%
        \GenericAcronymFields,%
        \the\glskeylisttok
    }%
}%
\do@newglossaryentry
}%
\renewcommand*{\acrfullfmt}[3]{%
    \glslink[##1]{##2}{\genacrfullformat{##2}{##3}}}%
\renewcommand*{\Acrfullfmt}[3]{%
    \glslink[##1]{##2}{\Genacrfullformat{##2}{##3}}}%
\renewcommand*{\ACRfullfmt}[3]{%
    \glslink[##1]{##2}{%
        \mfirstucMakeUppercase{\genacrfullformat{##2}{##3}}}%
\renewcommand*{\acrfullplfmt}[3]{%
    \glslink[##1]{##2}{\genplacrfullformat{##2}{##3}}}%
\renewcommand*{\Acrfullplfmt}[3]{%
    \glslink[##1]{##2}{\Genplacrfullformat{##2}{##3}}}%
\renewcommand*{\ACRfullplfmt}[3]{%
    \glslink[##1]{##2}{%
        \mfirstucMakeUppercase{\genplacrfullformat{##2}{##3}}}%
\renewcommand*{\glsentryfull}[1]{\genacrfullformat{##1}{}}}%
\renewcommand*{\Glsentryfull}[1]{\Genacrfullformat{##1}{}}}%
\renewcommand*{\glsentryfullpl}[1]{\genplacrfullformat{##1}{}}}%
\renewcommand*{\Glsentryfullpl}[1]{\Genplacrfullformat{##1}{}}}%
}
\let\@glsxtr@org@setacronymstyle\setacronymstyle
\let\@glsxtr@org@newacronymstyle\newacronymstyle
\let\@glsxtr@acronymlists\@glsacronymlists
\let\@glsxtr@org@addtoacronymlists\@addtoacronymlists
\let\@glsxtr@org@setacronymlists\SetAcronymLists
\newcommand{\@glsxtr@abbrlists}{}
\newcommand*{\forallabbreviationlists}[2]{%
    \@for#1:=\@glsxtr@abbrlists\do{\ifdefempty{#1}{#2}}%
}
\newcommand*{\@glsxtr@addabbreviationlist}[1]{%
    \protected@edef\@glo@type{#1}%
    \ifdefempty\@glsxtr@abbrlists
    {\let\@glsxtr@abbrlists\@glo@type}%
    {%
        \ifdefequal\@glsxtr@abbrlists\@glo@type
        }%
    {%
        \expandafter\DTLifinlist\expandafter{\@glo@type}{\@glsxtr@abbrlists}{}%
        {\protected@eappto\@glsxtr@abbrlists{,\@glo@type}}%
    }%
}%
}
}

```

```

\renewcommand*{\forallacronyms}[2]{%
  \@glxtr@base@acrcmd\forallacronyms\forallabbreviationlists
  \@for#1:=\@glsacronymlists\do{\ifx#1@empty\else#2\fi}%
}
\newcommand*{\MakeAcronymsAbbreviations}{%
  \@for\@gls@type:=\@glsacronymlists\do{%
    \csgdef{gls@\@gls@type @entryfmt}{\glentryfmt}%
  }%
  \let\@glxtr@acronymlists\@glsacronymlists
  \let\@glsacronymlists@empty
  \let\@addtoacronymlists\@gobble
  \let\@SetAcronymLists\@gobble
  \let\@glxtr@base@acrcmd\@glxtr@base@acrcmd@warn
  \renewcommand*{\newacronym}[4][{}]{%
    \glxtr@newabbreviation{type=\acronymtype,category=acronym,##1}{##2}{##3}{##4}%
  }%
  \renewcommand*{\firstacronymfont}[1]{\glsfirstabbrvfont{##1}}%
  \renewcommand*{\acronymfont}[1]{\glsabbrvfont{##1}}%
  \renewcommand*{\setacronymstyle}[1]{%
    \PackageError{glossaries-extra}{\string\setacronymstyle{##1}
      unavailable.
      Use \string\setabbreviationstyle[acronym]\space instead.
      The original acronym interface can be restored with
      \string\RestoreAcronyms}{}%
  }%
  \renewcommand*{\newacronymstyle}[1]{%
    \GlossariesExtraWarning{New acronym style ‘##1’ won’t be
      available unless you restore the original acronym interface with
      \string\RestoreAcronyms}%
    \@glxtr@org@newacronymstyle{##1}%
  }%
}
\MakeAcronymsAbbreviations
\newcommand*{\RestoreAcronyms}{%
  \let\@glsacronymlists\@glxtr@acronymlists
  \let\@addtoacronymlists\@glxtr@org@addtoacronymlists
  \let\@SetAcronymLists\@glxtr@org@setacronymlists
  \let\@glxtr@base@acrcmd\@gobbletwo
  \@for\@gls@type:=\@glsacronymlists\do{%
    \SetDefaultAcronymDisplayStyle{\@gls@type}%
  }%
  \SetGenericNewAcronym
  \renewcommand*{\firstacronymfont}[1]{\acronymfont{##1}}%
  \renewcommand*{\acronymfont}[1]{##1}%
  \let\@setacronymstyle\@glxtr@org@setacronymstyle
  \let\@newacronymstyle\@glxtr@org@newacronymstyle
  \renewcommand*{\@gls@link@checkfirsthyper}{%
    \ifglused{\glslabel}%
    {\let\glxtrifwasfirstuse\@secondoftwo}
    {\let\glxtrifwasfirstuse\@firstoftwo}%
  }

```

```

\@glxtr@org@checkfirsthyper
}
\glsssetcategoryattribute{acronym}{regular}{false}%
\setacronymstyle{long-short}%
}
\renewcommand*{\glsacspace}[1]{%
\settowidth{\dimen@}{(\firstacronymfont{\glsentryshort{#1}})}%
\ifdim\dimen@<\glsacspacemax~\else\space\fi
}
\newcommand*{\glsacspacemax}{3em}
\newcommand*{\@glxtr@reg@glosslist}{}
\let\@glxtr@org@makeglossaries\makeglossaries
\providecommand\@makeglossaries@warn@noprntglossary{%
\ifdefstring{\@glo@types}{,}%
{%
\GlossariesWarningNoLine{No glossaries have been defined}%
}%
{%
\GlossariesWarningNoLine{No \string\printglossary\space
or \string\printglossaries\space
found. ^^J(Remove \string\makeglossaries\space if you
don't want any glossaries.) ^^JThis document will not
have a glossary}%
}%
}%
\providecommand{\@domakeglossaries}[1]{#1}
\renewcommand*{\makeglossaries}[1][]{%
\@domakeglossaries
{%
\@glxtr@if@record@only
{%
\PackageError{glossaries-extra}{\string\makeglossaries\space
not permitted\MessageBreak with record=\@glxtr@record@setting\space
package option}%
{You may only use \string\makeglossaries\space with
record=off or record=hybrid options}%
}%
{%
\ifblank{#1}%
{%
\@glxtr@org@makeglossaries
\ifx\@glxtr@record@setting\@glxtr@record@setting@alsoindex
\let\warn@noprntglossary\@glxtr@warn@hybrid@noprntgloss
\fi
}%
{%
\ifx\@glxtr@record@setting\@glxtr@record@setting@alsoindex
\PackageError{glossaries-extra}{\string\makeglossaries[#1]\space
not permitted\MessageBreak with record=\@glxtr@record@setting\space package option}%
{You may only use the hybrid \string\makeglossaries[...]\space with

```

```

        record=off option}%
\else
\ifdef\@gls@@automake@immediate{\@gls@@automake@immediate}{}%
\protected@edef\@glsxtr@reg@glosslist{#1}%
\ifundef\@gls@write{\@newwrite\@gls@write}{}%
\protected@write\@auxout{}{\string\providecommand
\string\@glsorder[1]{}}
\protected@write\@auxout{}{\string\providecommand
\string\@istfilename[1]{}}
\protected@write\@auxout{}{\string\@istfilename{\istfilename}}%
\protected@write\@auxout{}{\string\@glsorder{\glsorder}}
\protected@write\@auxout{}{\string\@glsxtr@makeglossaries{#1}}
\write\@auxout{\string\providecommand\string\@gls@reference[3]{}}%
\@for\@glo@type:=#1\do{%
\ifempty{\@glo@type}{\@makeglossary{\@glo@type}}%
}%
\renewcommand*\@newglossary[4][[]]{%
\PackageError{glossaries}{New glossaries
must be created before \string\makeglossaries}{You need
to move \string\makeglossaries\space after all your
\string\newglossary\space commands}}%
\let\@makeglossary\@gobble
\renewcommand\@makeglossaries[1][[]]{%
\@disable@onlypremakeg
\let\@gls@checkseeallowed\relax
\renewcommand*\@do@seeglossary[2]{%
\glsdoifexists{##1}%
{%
\protected@edef\@gls@label{\glsdetoklabel{##1}}%
\protected@edef\@gls@type{\csname glo@\@gls@label @type\endcsname}%
\expandafter\DTLifinlist\expandafter{\@gls@type}{\@glsxtr@reg@glosslist}%
{\@glsxtr@org@doseeglossary{##1}{##2}}%
}%
\@glsxtrwrglossmark
\protected@write\@auxout{}{%
\string\@gls@reference
{\@gls@type}{\@gls@label}{\string\glsseeformat##2}}%
}%
}%
}%
\let\@glsxtr@@do@@wrglossary\@do@@wrglossary
\def\@do@@wrglossary{%
\protected@edef\@gls@type{\csname glo@\@gls@label @type\endcsname}%
\expandafter\DTLifinlist\expandafter{\@gls@type}{\@glsxtr@reg@glosslist}%
{\@glsxtr@@do@@wrglossary}%
{\gls@noidxglossary}%
}%
\let\warn@nomakeglossaries\relax
\let\warn@noprntglossary\@makeglossaries@warn@noprntglossary

```



```

\renewcommand{\@gls@noref@warn}[1]{%
  \protected@edef\@gls@type{##1}%
  \expandafter\DTLifinlist\expandafter{\@gls@type}{\@glsxtr@reg@glosslist}%
  {%
    \GlossariesExtraWarning{Can't use
      \string\printnoidxglossary[type={\@gls@type}]
      when '\@gls@type' is listed in the optional argument of
      \string\makeglossaries}%
  }%
  {%
    \GlossariesWarning{Empty glossary for
      \string\printnoidxglossary[type={##1}].
      Rerun may be required (or you may have forgotten to use
      commands like \string\gls)}%
  }%
}%
\renewcommand*\@glsdisplaynumberlist[1]{%
  \expandafter\DTLifinlist\expandafter{##1}{\@glsxtr@reg@glosslist}%
  {\@glsxtr@idx@displaynumberlist{##1}}%
  {\@glsxtr@noidx@displaynumberlist{##1}}%
}%
\renewcommand*\@glsentrynumberlist[1]{%
  \expandafter\DTLifinlist\expandafter{##1}{\@glsxtr@reg@glosslist}%
  {\@glsxtr@idx@entrynumberlist{##1}}%
  {\@glsxtr@noidx@entrynumberlist{##1}}%
}%
\renewcommand*\@glsnumberlistloop[2]{%
  \expandafter\DTLifinlist\expandafter{##1}{\@glsxtr@reg@glosslist}%
  {%
    \PackageError{glossaries-extra}{\string\glsnumberlistloop\space
      not available for glossary '##1'}{%
    }%
    {\@glsxtr@noidx@numberlistloop{##1}{##2}}%
  }%
}%
\renewcommand*\@glsprestandardsort[3]{%
  \expandafter\DTLifinlist\expandafter{##2}{\@glsxtr@reg@glosslist}%
  {%
    \glsdosanitizesort
  }%
  {%
    \ifglssanitizesort
      \@gls@noidx@sanitizesort
    \else
      \@gls@noidx@nosanitizesort
    \fi
  }%
}%
\renewcommand*\new@glossaryentry[2]{%
  \PackageError{glossaries-extra}{Glossary entries must be defined
    in the preamble\MessageBreak when you use the optional argument

```

```

        of \string\makeglossaries}{Either move your definitions to the
        preamble or don't use the optional argument of
        \string\makeglossaries}%
    }%
    \let\@glo@assign@sortkey\@glxtr@mixed@assign@sortkey
    \renewcommand*{\@printgloss@setsort}{%
        \expandafter\@glxtr@gettype\expandafter,\@glxtr@printglossopts,%
        type=\glsdefaulttype,\@end@glxtr@gettype
    \def\@glo@sorttype{\@glo@default@sorttype}%
    }%
    \ifglautomake
        \renewcommand*{\@gls@doautomake}{%
            \for\@gls@type:=\@glxtr@reg@glosslist\do{%
                \ifdefempty{\@gls@type}{\@gls@automake{\@gls@type}}%
            }%
        }%
    \fi
    \ifdef\@glo@check@sortallowed{\@glo@check@sortallowed\makeglossaries}{}%
    \fi
    }%
    }%
    }
}
\ifdef\@printgloss@checkexists
{\newcommand{\glxtr@printgloss@checkexists}{\@printgloss@checkexists}}
{\newcommand{\glxtr@printgloss@checkexists}[2]{#2}}
\newcommand{\@glxtr@orgprintglossary}[2]{%
    \def\@glo@type{\glsdefaulttype}%
    \def\glossarytitle{%
        \ifcsdef{\@glo@type\@glo@type @title}%
        {\csuse{\@glo@type\@glo@type @title}}%
        {\glossaryname}}%
    \def\glossarytoctitle{\glossarytitle}%
    \let\org@glossarytitle\glossarytitle
    \def\@glossarystyle{%
        \ifx\@glossary@default@style\relax
            \GlossariesWarning{No default glossary style provided \MessageBreak
                for the glossary '\@glo@type'. \MessageBreak
                Using deprecated fallback. \MessageBreak
                To fix this set the style with \MessageBreak
                \string\setglossarystyle\space or use the \MessageBreak
                style key=value option}%
        \fi
    }%
    \def\gls@dotoc@title{\glssettoc@title{\@glo@type}}%
    \let\@org@glossaryentrynumbers\glossaryentrynumbers
    \bgroup
        \@printgloss@setsort
        \setkeys{printgloss}{#1}%
        \ifx\glossarytitle\org@glossarytitle

```

```

\else
  \cslet{@glo@type@{@glo@type @title}}{\glossarytitle}%
\fi
\let\currentglossary\@glo@type
\let\org@glossaryentrynumbers\glossaryentrynumbers
\let\glsnonextpages\@glsnonextpages
\let\glsnextpages\@glsnextpages
\glstractivatenopost
\gls@dotoc@title
\@glossarystyle
\let\gls@org@glossaryentryfield\glossentry
\let\gls@org@glossarysubentryfield\subglossentry
\renewcommand{\glossentry}[1]{%
  \protected@xdef\glscurrententrylabel{\glsdetoklabel{##1}}%
  \gls@org@glossaryentryfield{##1}%
}%
\renewcommand{\subglossentry}[2]{%
  \protected@xdef\glscurrententrylabel{\glsdetoklabel{##2}}%
  \gls@org@glossarysubentryfield{##1}{##2}%
}%
\@gls@preglossaryhook
\glstr@printgloss@checkexists{\@glo@type}{#2}%
\egroup
\global\let\glossaryentrynumbers\@org@glossaryentrynumbers
\global\let\warn@noprintglossary\relax
}
\newcommand*{\glstractivatenopost}{%
  \let\nopostdesc\@nopostdesc
  \let\glstrnopostpunc\@glstr@nopostpunc
}
\newrobustcmd*{\glstrnopostpunc}{}
\newcommand{\@glstr@nopostpunc}{%
  \let\@@glstr@org@postdescription\glspostdescription
  \ifglsnopostdot
    \renewcommand{\glspostdescription}{%
      \glsnopostdottrue
      \let\glspostdescription\@@glstr@org@postdescription
      \let\glstrrestorepostpunc\@glstr@restore@postpunc
      \glstrpostdescription
      \@glstr@nopostpunc@postdesc}%
    \else
      \renewcommand{\glspostdescription}{%
        \let\glspostdescription\@@glstr@org@postdescription
        \let\glstrrestorepostpunc\@glstr@restore@postpunc
        \glstrpostdescription
        \@glstr@nopostpunc@postdesc}%
      \fi
  \glsnopostdotfalse
}
\newcommand*{\@glstr@nopostpunc@postdesc}{}

```

```

\newcommand*{\@glxtr@restore@postpunc}{%
\def\@glxtr@nopostpunc@postdesc{%
\@glxtr@org@postdescription
\let\@glxtr@nopostpunc@postdesc\@empty
\let\glxtrrestorepostpunc\@empty
}%
}
\newcommand*{\glxtrrestorepostpunc}{}
\renewcommand{\@printglossary}[2]{%
\def\@glxtr@printglossopts{#1}%
\@glxtr@orgprintglossary{#1}{#2}%
}
\define@choicekey{printgloss}{target}
[\@glxtr@printglossval\@glxtr@printglossnr]%
{true,false}[true]%
{%
\ifcase\@glxtr@printglossnr
\def\@glstarget{\@glsdohypertarget}%
\else
\let\@glstarget\@secondoftwo
\fi
}
\newcommand{\@glxtr@hypernameprefix}{}
\define@key{printgloss}{targetnameprefix}{%
\renewcommand{\@glxtr@hypernameprefix}{#1}%
}
\define@key{printgloss}{prefix}{%
\renewcommand{\@glolinkprefix}{#1}%
}
\define@key{printgloss}{label}{%
\glxtrsetglossarylabel{#1}%
}
\newcommand{\glxtrsetglossarylabel}[1]{%
\renewcommand*{\@glossaryseclabel}{%
\protected@edef\@currentlabelname{\glossarytoctitle}%
\label{#1}%
}%
}
\newcount\@glxtr@leveloffset
\define@key{printgloss}{leveloffset}{%
\@glxtr@assign@leveloffset#1\relax
}
\newcommand*{\@glxtr@assign@leveloffset}{%
\@ifnextchar+{\p@glxtr@assign@leveloffset}{\np@glxtr@assign@leveloffset}%
}
\newcommand*{\p@glxtr@assign@leveloffset}[1]{%
\@ifnextchar+{\pp@glxtr@assign@leveloffset}{\np@glxtr@assign@leveloffset}%
}
\def\np@glxtr@assign@leveloffset#1\relax{\@glxtr@leveloffset=#1\relax}
\def\pp@glxtr@assign@leveloffset#1\relax{\advance\@glxtr@leveloffset by #1\relax}

```

```

\define@boolkey{printgloss}[glxtr@printgloss@]{groups}[true]{}
\glxtr@printgloss@groupstrue
\let\@glxtr@org@glsdohypertarget\glsdohypertarget
\renewcommand{\glsdohypertarget}[2]{%
  \@glxtr@org@glsdohypertarget{\@glxtr@hypernameprefix#1}{#2}%
}
\ifx\@glstarget\@glxtr@org@glsdohypertarget
\def\@glstarget{\glsdohypertarget}%
\fi
\newcommand{\@glxtr@do@org@target}[2]{%
  {%
    \let\glsdohypertarget\@glxtr@org@glsdohypertarget
    \@glstarget{#1}{#2}%
  }%
}
\newcommand*{\@glxtr@makeglossaries}[1]{}
\def\@glxtr@gettype#1,type=#2,#3\@end@glxtr@gettype{%
  \def\@glo@type{#2}%
}
\newcommand\@glxtr@mixed@assign@sortkey[1]{%
  \protected@edef\@glo@type{\@glo@type}%
  \expandafter\DTLifinlist\expandafter{\@glo@type}{\@glxtr@reg@glosslist}%
  {%
    \@glo@no@assign@sortkey{#1}%
  }%
  {%
    \@glo@assign@sortkey{#1}%
  }%
}
\let\@glxtr@idx@displaynumberlist\glsdisplaynumberlist
\newcommand*{\@glxtr@noidx@displaynumberlist}[1]{%
  \letcs{\@gls@loclist}{glo@\glsdetoklabel{#1}@loclist}%
  \ifdef\@gls@loclist
  {%
    \def\@gls@noidxloclist@sep{%
      \def\@gls@noidxloclist@sep{%
        \def\@gls@noidxloclist@sep{%
          \glsnumlistsep
        }%
        \def\@gls@noidxloclist@finalsep{\glsnumlistlastsep}%
      }%
    }%
    \def\@gls@noidxloclist@finalsep{}%
    \def\@gls@noidxloclist@prev{}%
    \forlistloop{\@gls@noidxdisplayloclisthandler}{\@gls@loclist}%
    \@gls@noidxloclist@finalsep
    \@gls@noidxloclist@prev
  }%
  {%
    \glxtrundeftag

```

```

\glsdoifexists{#1}%
{%
  \GlossariesWarning{Missing location list for ‘#1’. Either
    a rerun is required or you haven’t referenced the entry.}%
}%
}%
}%

\newcommand*{\@glsxtr@noidx@numberlistloop}[3]{%
  \letcs{\@gls@loclist}{glo@\glsdetoklabel{#1}@loclist}%
  \let\@gls@org@glsnoidxdisplayloc\glsnoidxdisplayloc
  \let\@gls@org@glsseeformat\glsseeformat
  \let\glsnoidxdisplayloc#2\relax
  \let\glsseeformat#3\relax
  \ifdef\@gls@loclist
  {%
    \forlistloop{\glsnoidxnumberlistloophandler}{\@gls@loclist}%
  }%
  {%
    \glsxtrundeftag
    \glsdoifexists{#1}%
    {%
      \GlossariesWarning{Missing location list for ‘##1’. Either
        a rerun is required or you haven’t referenced the entry.}%
    }%
  }%
  \let\glsnoidxdisplayloc\@gls@org@glsnoidxdisplayloc
  \let\glsseeformat\@gls@org@glsseeformat
}%

\newcommand*{\@glsxtr@noidx@entrynumberlist}[1]{%
  \letcs{\@gls@loclist}{glo@\glsdetoklabel{#1}@loclist}%
  \ifdef\@gls@loclist
  {%
    \glsnoidxloclist{\@gls@loclist}%
  }%
  {%
    \glsxtrundeftag
    \glsdoifexists{#1}%
    {%
      \GlossariesWarning{Missing location list for ‘#1’. Either
        a rerun is required or you haven’t referenced the entry.}%
    }%
  }%
}%

\newcommand*{\@glsxtr@idx@entrynumberlist}[1]{\glsentrynumberlist{#1}}
\renewcommand*{\@gls@noidx@getgrouptitle}[2]{%
  \protected@edef\@glsxtr@titlelabel{#1}%
  \ifdefvoid\@glsxtr@titlelabel
  {}%
  {%

```

```

\protected@edef\@glsxtr@titlelabel{\csuse{glsxtr@grouptitle@#1}}%
}%
\ifdefvoid{\@glsxtr@titlelabel}%
{%
\DTLifint{#1}%
{%
\ifnum#1<256\relax
\edef#2{\char#1\relax}%
\else
\edef#2{#1}%
\fi
}%
{%
\ifcsundef{#1groupname}%
{\def#2{#1}}%
{\letcs#2{#1groupname}}%
}%
}%
{%
\let#2\@glsxtr@titlelabel
}%
}
\let\glsxtr@org@getgrouptitle\@gls@getgrouptitle
\newrobustcmd{\glsxtrgetgrouptitle}[2]{%
\protected@edef\@glsxtr@titlelabel{glsxtr@grouptitle@#1}%
\@onelevel@sanitize\@glsxtr@titlelabel
\ifcsdef{\@glsxtr@titlelabel}
{\letcs{#2}{\@glsxtr@titlelabel}}%
{\glsxtr@org@getgrouptitle{#1}{#2}}%
}
\let\@gls@getgrouptitle\glsxtrgetgrouptitle
\newcommand{\glsxtrsetgrouptitle}[2]{%
\protected@edef\@glsxtr@titlelabel{glsxtr@grouptitle@#1}%
\@onelevel@sanitize\@glsxtr@titlelabel
\protected@csxdef{\@glsxtr@titlelabel}{#2}%
}
\newcommand{\glsxtrlocalsetgrouptitle}[2]{%
\protected@edef\@glsxtr@titlelabel{glsxtr@grouptitle@#1}%
\@onelevel@sanitize\@glsxtr@titlelabel
\protected@csedef{\@glsxtr@titlelabel}{#2}%
}
\renewcommand*{\glsnavigation}{%
\def\@gls@between{}%
\ifcsundef{\@gls@hypergroup\list\@glo@type}%
{%
\def\@gls@list{}%
}%
{%
\expandafter\let\expandafter\@gls@list
\csname @gls@hypergroup\list\@glo@type\endcsname

```

```

}%
\@for\@gls@tmp:=\@gls@list\do{%
  \@gls@between
  \glsxtrgetgrouptitle{\@gls@tmp}{\@gls@grptitle}%
  \glsnavhyperlink{\@gls@tmp}{\@gls@grptitle}%
  \let\@gls@between\glshypernavsep
}%
}
\renewcommand*{\@print@noidx@glossary}{%
  \ifcsdef{\@glsref@\@glo@type}%
  {%
    \ifcsdef{\@glo@sortmacro@\@glo@sorttype}%
    {%
      \csuse{\@glo@sortmacro@\@glo@sorttype}{\@glo@type}%
    }%
    {%
      \PackageError{glossaries}{Unknown sort handler ‘\@glo@sorttype’}{}%
    }%
    \glossarysection[\glossarytoctitle]{\glossarytitle}%
    \glossarypreamble
    \def\@gls@currentlettergroup{}%
    \begin{theglossary}%
      \glossaryheader
      \glsresetentrylist
      \forlistcsloop{\@gls@noidx@do}{\@glsref@\@glo@type}%
      \end{theglossary}%
      \glossarypostamble
    }%
    {%
      \glsxtrifemptyglossary{\@glo@type}%
      {}%
      {\glossarysection[\glossarytoctitle]{\glossarytitle}}%
      \@gls@noref@warn{\@glo@type}%
    }%
  }
}
\renewcommand*{\@glsnoidxdisplayloc}[4]{%
  \setentrycounter[#1]{#2}%
  \@glsxtr@display@loc#3\empty\end@glxtr@display@loc{#4}%
}
\def\@glsxtr@display@loc#1#2\end@glxtr@display@loc#3{%
  \ifx#1(\relax
    \glsxtrdisplaystartloc{#2}{#3}%
  \else
    \ifx#1)\relax
      \glsxtrdisplayendloc{#2}{#3}%
    \else
      \glsxtrdisplaysingleloc{#1#2}{#3}%
    \fi
  \fi
}

```



```

\newcommand*{\glxtrdisplaysingleloc}[2]{%
  \csuse{#1}{#2}%
}
\newcommand*{\glxtrdisplaystartloc}[2]{%
  \protected@edef\glxtrlocrangefmt{#1}%
  \ifx\glxtrlocrangefmt\empty
    \def\glxtrlocrangefmt{\glnumberformat}%
  \fi
  \expandafter\glxtrdisplaysingleloc
  \expandafter{\glxtrlocrangefmt}{#2}%
}
\newcommand*{\glxtrdisplayendloc}[2]{%
  \protected@edef\@glxtr@tmp{#1}%
  \ifdefempty{\@glxtr@tmp}{\def\@glxtr@tmp{\glnumberformat}}{}%
  \ifx\glxtrlocrangefmt\@glxtr@tmp
  \else
    \GlossariesExtraWarning{Mismatched end location range
      (start=\glxtrlocrangefmt, end=\@glxtr@tmp)}%
  \fi
  \expandafter\glxtrdisplayendlochook\expandafter{\@glxtr@tmp}{#2}%
  \expandafter\glxtrdisplaysingleloc
  \expandafter{\glxtrlocrangefmt}{#2}%
  \def\glxtrlocrangefmt{}%
}
\newcommand*{\glxtrdisplayendlochook}[2]{}
\newcommand*{\glxtrlocrangefmt}{}
\renewcommand*{\setentrycounter}[2][1]{%
  \def\glxtrcounterprefix{#1}%
  \ifx\glxtrcounterprefix\empty
    \def\@glo@counterprefix{.}%
  \else
    \def\@glo@counterprefix{.#1}%
  \fi
  \def\glsetentrycounter{#2}%
}
\def\@gls@removespaces#1 #2\@nil{%
  \toks@=\expandafter{\the\toks@#1}%
  \ifx\@#2\%
    \edef\@glo@tmp{\the\toks@}%
    \ifx\@glo@tmp\empty
    \else
      \expandafter\glxtrlocationhyperlink\expandafter
      \glsetentrycounter\expandafter\@glo@counterprefix\expandafter{\the\toks@}%
    \fi
  \else
    \@gls@ReturnAfterFi{%
      \@gls@removespaces#2\@nil
    }%
  \fi
}

```

```

\newcommand*{\glxtrlocationhyperlink}[3]{%
  \ifdefined\glxtrsupplocationurl
  {%
    \GlsXtrInternalLocationHyperlink{#1}{#2}{#3}%
  }%
  {%
    \hyperref{\glxtrsupplocationurl}{#1#2#3}{#3}%
  }%
}
\newcommand*{\glxtrsupphypernumber}[1]{%
  {%
    \glshasattribute{\glscurrententrylabel}{externalallocation}%
  {%
    \def\glxtrsupplocationurl{%
      \glsgotattribute{\glscurrententrylabel}{externalallocation}}%
    }%
  {%
    \def\glxtrsupplocationurl{%
    }%
    \glshypernumber{#1}%
  }%
}
\renewcommand{\@print@glossary}{%
  \makeatletter
  \@input@{\jobname.\csname @glo@type@\@glo@type @in\endcsname}%
  \IfFileExists{\jobname.\csname @glo@type@\@glo@type @in\endcsname}%
  {}%
  {\glxtrNoGlossaryWarning{\@glo@type}}%
  \ifglxindy
    \ifcsundef{@xdy@\@glo@type @language}%
    {%
      \edef\@do@auxoutstuff{%
        \noexpand\AtEndDocument{%
          \noexpand\immediate\noexpand\write\@auxout{%
            \string\providecommand\string\@xdylanguage[2]{}%
          }%
          \noexpand\immediate\noexpand\write\@auxout{%
            \string\@xdylanguage{\@glo@type}{\@xdy@main@language}%
          }%
        }%
      }%
    }%
  {%
    \edef\@do@auxoutstuff{%
      \noexpand\AtEndDocument{%
        \noexpand\immediate\noexpand\write\@auxout{%
          \string\providecommand\string\@xdylanguage[2]{}%
        }%
        \noexpand\immediate\noexpand\write\@auxout{%
          \string\@xdylanguage{\@glo@type}{\csname @xdy@\@glo@type
            @language\endcsname}%
        }%
      }%
    }%
  }%
}

```

```

}%
\do@auxoutstuff
\edef\do@auxoutstuff{%
  \noexpand\AtEndDocument{%
    \noexpand\immediate\noexpand\write\@auxout{%
      \string\providecommand\string\@gls@codepage[2]{}}%
    \noexpand\immediate\noexpand\write\@auxout{%
      \string\@gls@codepage{\@glo@type}{\@gls@codepage}}%
    }%
  }%
\do@auxoutstuff
\fi
\renewcommand*{\@warn@nomakeglossaries}{%
  \GlossariesWarningNoLine{\string\makeglossaries\space
    hasn't been used,^^Jthe glossaries will not be updated}%
}%
}
\newcommand{\GlsXtrNoGlsWarningHead}[2]{%
  This document is incomplete. The external file associated with
  the glossary '#1' (which should be called \texttt{#2})
  hasn't been created.%
}
\newcommand{\GlsXtrNoGlsWarningEmptyStart}{%
  This has probably happened because there are no entries defined
  in this glossary.%
}
\newcommand{\GlsXtrNoGlsWarningEmptyMain}{%
  If you don't want this glossary,
  add \texttt{nomain} to your package option list when you load
  \texttt{glossaries-extra.sty}. For example:%
}
\newcommand{\GlsXtrNoGlsWarningEmptyNotMain}[1]{%
  Did you forget to use \texttt{type=#1} when you defined your
  entries? If you tried to load entries into this glossary with
  \texttt{\string\loadglsentries} did you remember to use
  \texttt{[#1]} as the optional argument? If you did, check that
  the definitions in the file you loaded all had the type set
  to \texttt{\string\glsdefaulttype}.%
}
\newcommand{\GlsXtrNoGlsWarningCheckFile}[1]{%
  Check the contents of the file \texttt{#1}. If
  it's empty, that means you haven't indexed any of your entries in this
  glossary (using commands like \texttt{\string\gls} or
  \texttt{\string\glsadd}) so this list can't be generated.
  If the file isn't empty, the document build process hasn't been
  completed.%
}
\newcommand{\GlsXtrNoGlsWarningAutoMake}[1]{%
  You may need to rerun \LaTeX. If you already have, it may be that
  \TeX's shell escape doesn't allow you to run

```

```

\ifglxindy xindy\else makeindex\fi. Check the
transcript file \texttt{\jobname.log}. If the shell escape is
disabled, try one of the following:

\begin{itemize}
  \item Run the external (Lua) application:

      \texttt{makeglossaries-lite \string"\jobname\string"}

  \item Run the external (Perl) application:

      \texttt{makeglossaries \string"\jobname\string"}
\end{itemize}

Then rerun \LaTeX\ on this document.
\GlossariesExtraWarning{Rerun required to build the
glossary ‘#1’ or check TeX’s shell escape allows
you to run \ifglxindy xindy\else makeindex\fi}%
}
\newcommand{\GlsXtrNoGlsWarningMisMatch}{%
  You need to either replace \texttt{\string\makenoidxglossaries}
  with \texttt{\string\makeglossaries} or replace
  \texttt{\string\printglossary} (or \texttt{\string\printglossaries}) with
  \texttt{\string\printnoidxglossary}
  (or \texttt{\string\printnoidxglossaries}) and then rebuild
  this document.%
}
\newcommand{\GlsXtrNoGlsWarningBuildInfo}{%
  Try one of the following:
  \begin{itemize}
    \item Add \texttt{automake} to your package option list when you load
      \texttt{glossaries-extra.sty}. For example:

        \texttt{\string\usepackage[automake]%
          \glsopenbrace glossaries-extra\glsclosebrace}

    \item Run the external (Lua) application:

        \texttt{makeglossaries-lite.lua \string"\jobname\string"}

    \item Run the external (Perl) application:

        \texttt{makeglossaries \string"\jobname\string"}
  \end{itemize}

  Then rerun \LaTeX\ on this document.%
}
\newcommand{\GlsXtrRecordWarning}[1]{%
  \texttt{\string\printglossary} doesn’t work
  with the \texttt{record=@glxtr@record@setting} package option

```

```

use\par\texttt{\string\printunsrtglossary[type=#1]}\par
instead (or change the package option).%
}
\newcommand{\GlsXtrNoGlsWarningTail}{%
  This message will be removed once the problem has been fixed.%
}
\newcommand{\GlsXtrNoGlsWarningNoOut}[1]{%
  The file \texttt{#1} doesn't exist. This most likely means you haven't used
  \texttt{\string\makeglossaries} or you have used
  \texttt{\string\nofiles}. If this is just a draft version of the
  document, you can suppress this message using the
  \texttt{nomissingglstext} package option.%
}
\newcommand*{\@glstr@defaultnoglossarywarning}[1]{%
  \glossarysection[\glossarytoctitle]{\glossarytitle}
  \GlsXtrNoGlsWarningHead{#1}{\jobname.\csname @glotype@\@glo@type @in\endcsname}
  \par
  \glstrifemptyglossary{#1}%
  {%
    \GlsXtrNoGlsWarningEmptyStart\space
    \ifthenelse{\equal{#1}{main}}{\GlsXtrNoGlsWarningEmptyMain\par
    \medskip
    \noindent\texttt{\string\usepackage[nomain\ifglacronym ,acronym\fi]%
      \glspenbrace glossaries-extra\glsclosebrace}
    \medskip
    }%
    {\GlsXtrNoGlsWarningEmptyNotMain{#1}}%
  }%
  {%
    \IfFileExists{\jobname.\csname @glotype@\@glo@type @out\endcsname}
    {%
      \GlsXtrNoGlsWarningCheckFile
      {\jobname.\csname @glotype@\@glo@type @out\endcsname}

      \ifglautomake

      \GlsXtrNoGlsWarningAutoMake{#1}

    \else

      \ifthenelse{\equal{#1}{main}}{%
        {%
          \GlsXtrNoGlsWarningEmptyMain\par
          \medskip
          \noindent\texttt{\string\usepackage[nomain]%
            \glspenbrace glossaries-extra\glsclosebrace}
          \medskip
        }%
        {}%
      }%
    }%
  }%
}

```

```

\ifdefequal\makeglossaries\@no@makeglossaries
{%
  \GlsXtrNoGlsWarningMisMatch
}%
{%
  \GlsXtrNoGlsWarningBuildInfo
}%
\fi
}%
{%
  \GlsXtrNoGlsWarningNoOut
  {\jobname.\csname @glotype@\@glo@type @out\endcsname}%
}%
\par
\GlsXtrNoGlsWarningTail
}
\newcommand*{\@glxtr@record@noglossarywarning}[1]{%
  \GlossariesExtraWarning{\string\printglossary\space doesn't work\MessageBreak
with record=\@glxtr@record@setting\space package option\MessageBreak(use
\string\printunsrtglossary[type=#1])\MessageBreak
instead (or change the package option)}%
\glossarysection[\glossarytoctitle]{\glossarytitle}
\GlsXtrRecordWarning{#1}
\GlsXtrNoGlsWarningTail
}
\newcommand*{\GlsXtrDefaultResourceOptions}{}
\newcommand*{\glxtrresourcefile}[2][{}]{%
  \disable@keys{glossaries-extra.sty}{record}%
  \glxtr@writefields
  \ifdefempty\GlsXtrDefaultResourceOptions
  {%
    \protected@write\@auxout{\glxtrresourceinit}%
    {\string\glxtr@resource{#1}{#2}}%
  }%
  {%
    \protected@write\@auxout{\glxtrresourceinit}%
    {\string\glxtr@resource{\GlsXtrDefaultResourceOptions,#1}{#2}}%
  }%
  \let\@glxtr@org@see@noindex\@glxtr@see@noindex
  \let\@glxtr@see@noindex\relax
  \IfFileExists{#2.glstex}%
  {%
    \edef\@bibgls@restreat{\noexpand\catcode\noexpand'\noexpand\@=\number\catcode'\@}%
    \makeatletter
    \@input{#2.glstex}%
    \@bibgls@restreat
    \@glxtr@check@bibgls@nameref
  }%
  {%

```

```

    \GlossariesExtraWarning{No file ‘#2.glstex’}%
}%
\let\@gls@see@noindex\@glsxtr@org@see@noindex
}
\@onlypreamble\glsxtrresourcefile
\newcommand{\@glsxtr@check@bibgls@nameref}{%
  \ifx\@glsxtr@record@setting\@glsxtr@record@setting@nameref
    \ifdef\bibglshrefchar
      {}%
    {%
      \GlossariesExtraWarning{record=nameref requires at least
        version 1.8 of bib2gls}%
    }%
  \fi
  \let\@glsxtr@check@bibgls@nameref\relax
}
\newcommand*\@glsxtrresourceinit{}{}
\newcount\glsxtrresourcecount
\newcommand*\@GlsXtrLoadResources}[1][]{%
  \ifnum\glsxtrresourcecount=0\relax
    \glsxtrresourcefile[#1]{\jobname}%
  \else
    \glsxtrresourcefile[#1]{\jobname-\the\glsxtrresourcecount}%
  \fi
  \advance\glsxtrresourcecount by 1\relax
}
\newcommand*\@glsxtr@resource}[2]{}
\newcommand*\@glsxtr@fields}[1]{}
\newcommand*\@glsxtr@texencoding}[1]{}
\newcommand*\@glsxtr@langtag}[1]{}
\newcommand*\@glsxtr@pluralsuffixes}[4]{}
\newcommand*\@glsxtr@shortcutsval}[1]{}
\newcommand*\@glsxtr@linkprefix}[1]{}
\newcommand*\@glsxtr@writefields}{%
  \protected@write\@auxout{%
    {\string\providecommand*\@string\glsxtr@fields}[1]{}}%
  \protected@write\@auxout{%
    {\string\providecommand*\@string\glsxtr@resource}[2]{}}%
  \protected@write\@auxout{%
    {\string\providecommand*\@string\glsxtr@pluralsuffixes}[4]{}}%
  \protected@write\@auxout{%
    {\string\providecommand*\@string\glsxtr@shortcutsval}[1]{}}%
  \protected@write\@auxout{%
    {\string\providecommand*\@string\glsxtr@linkprefix}[1]{}}%
  \protected@write\@auxout{{\string\glsxtr@fields{\@gls@keymap}}}%
  \protected@write\@auxout{%
    {\string\providecommand*\@string\glsxtr@record}[5]{}}%
  \ifx\@glsxtr@record@setting\@glsxtr@record@setting@nameref
    \protected@write\@auxout{%
      {\string\providecommand*\@string\glsxtr@record@nameref}[8]{}%
    }%
  \fi
}

```

```

\fi
\ifdef\CurrentTrackedLanguageTag
{%
  \protected@write\@auxout{}\{%
    \string\glxtr@langtag{\CurrentTrackedLanguageTag}}%
  }%
}%
\protected@write\@auxout{}\{\string\glxtr@pluralsuffixes
  {\glspluralsuffix}{\abbrvpluralsuffix}{\acrpluralsuffix}%
  {\glxtrabbrvpluralsuffix}}%
\ifdef\inputencodingname
{%
  \protected@write\@auxout{}\{\string\glxtr@texencoding{\inputencodingname}}%
  }%
{%
  \@ifpackageloaded{fontspec}%
  {\protected@write\@auxout{}\{\string\glxtr@texencoding{utf8}}}%
  {}%
}%
\protected@write\@auxout{}\{\string\glxtr@shortcutsval{\@glxtr@shortcutsval}}%
\AtBeginDocument
  {\protected@write\@auxout{}\{\string\glxtr@linkprefix{\glolinkprefix}}}%
\let\glxtr@writefields\relax
\ifglautomake
  \IfFileExists{jobname.aux}%
  {\immediate\write18{bib2gls jobname}}{}%
  \ifx\@gls@doautomake\@gls@doautomake@err
    \let\@gls@doautomake\relax
  \fi
\fi
\@glxtr@if@record@only
{\ifdefstring\glsorder}{letter}%
  {\GlossariesExtraWarningNoLine{Package option ‘order=letter’ isn’t
    supported with ‘record=\@glxtr@record@setting’. Use ‘break-at=none’
    resource option instead}}%
  {}%
}%
}%
}
\newcommand*{\@gls@doautomake@err}{%
  \PackageError{glossaries}{You must use
  \string\makeglossaries\space with automake=true}
  {%
    Either remove the automake=true setting or
    add \string\makeglossaries\space to your document preamble.%
  }%
}
\newcommand*{\glxtr@record}[5]{%
\newcommand*{\glxtr@record@nameref}[8]{%
\newcommand*{\glxtr@counterrecord}[3]{%

```



```

\glxstrfieldlistgadd{#1}{record.#2}{#3}%
}
\newcommand*{\@glxstr@counterrecordhook}{%
\newcommand*{\GlsXtrRecordCounter}[1]{%
\@glxstr@recordcounter{#1}%
}
\@onlypreamble\GlsXtrRecordCounter
\newcommand*{\@glxstr@docounterrecord}[1]{%
\protected@write\@auxout{}\string\glxstr@counterrecord
{\@glsl@label}{#1}{\csuse{the#1}}}%
}
\newcommand*{\glxstrglossentry}[1]{%
\glxstrtitleorpdforheading
{\@glxstrglossentry{#1}}%
{\glsenentryname{#1}}%
{\glxstrheadname{#1}}%
}
\newrobustcmd*{\@glxstrglossentry}[1]{%
\glxstrtitleorpdforheading
{%
\glsoifexists{#1}%
{%
\begingroup
\protected@edef\glscurrententrylabel{\glsetoklabel{#1}}%
\protected@edef\currentglossary{\GlsXtrStandaloneGlossaryType}%
\ifglshasparent{#1}%
{\GlsXtrStandaloneSubEntryItem{#1}}%
{\glsenentryitem{#1}}%
\GlsXtrStandaloneEntryName{#1}%
\endgroup
}%
}%
{\glsenentryname{#1}}%
{\glxstrheadname{#1}}%
}
\newcommand*{\GlsXtrStandaloneEntryName}[1]{%
\glstarget{#1}{\glossentryname{#1}}%
}
\newcommand{\GlsXtrStandaloneGlossaryType}{\glsenentrytype{\glscurrententrylabel}}
\newcommand*{\GlsXtrStandaloneSubEntryItem}[1]{%
\GlsXtrIfFieldEqNum{level}{#1}{1}{\glssubentryitem{#1}}}%
}
\newcommand*{\glxstrglossentryother}[3]{%
\ifstrempy{#1}%
{%
\ifcsdef{glxstrhead#3}%
{%
\glxstrtitleorpdforheading
{\@glxstrglossentryother{#2}{#3}{#1}}%
{\@glsl@entry@field{#2}{#3}}%
}
}
}

```

```

        {\csuse{glsxtrhead#3}{#2}}%
    }%
    {%
        \glsxtrtitleorpdforheading
        {\@glsxtrglossentryother{#2}{#3}{#1}}%
        {\@gls@entry@field{#2}{#3}}%
        {\@gls@entry@field{\NoCaseChange{#2}}{#3}}%
    }%
}%
{%
    \glsxtrtitleorpdforheading
    {\@glsxtrglossentryother{#2}{#3}{#1}}%
    {\@gls@entry@field{#2}{#3}}%
    {#1}%
}%
}
\newrobustcmd*{\@glsxtrglossentryother}[3]{%
    \glsxtrtitleorpdforheading
    {%
        \glsdoifexists{#1}%
        {%
            \begingroup
                \protected@edef\glscurrententrylabel{\glsdetoklabel{#1}}%
                \protected@edef\currentglossary{\GlsXtrStandaloneGlossaryType}%
                \ifglshasparent{#1}%
                    {\GlsXtrStandaloneSubEntryItem{#1}}%
                    {\glsentryitem{#1}}%
                    \GlsXtrStandaloneEntryOther{#1}%
                \endgroup
            }%
        }%
        {\@gls@entry@field{#1}{#2}}%
        {#3}%
    }
}
\newcommand*{\GlsXtrStandaloneEntryOther}[2]{%
    \glstarget{#1}{\glossentrynameother{#1}{#2}}%
}
\ifdef\@printgloss@checkexists
{
    \newcommand*{\printunsrtglossary}{%
        \let\@printgloss@checkexists\@printgloss@checkexists@allowignored
        \@ifstar\s@printunsrtglossary\@printunsrtglossary
    }
}
{
    \newcommand*{\printunsrtglossary}{%
        \@ifstar\s@printunsrtglossary\@printunsrtglossary
    }
}
\newcommand*{\@printunsrtglossary}[1] [] {%

```

```

    \@printglossary{type=\glsdefaulttype,#1}{\@print@unsrt@glossary}%
}
\newcommand*{\s@printunsrtglossary}[2][\%
    \begin{group}
        #2%
        \@printglossary{type=\glsdefaulttype,#1}{\@print@unsrt@glossary}%
    \end{group}
}
\newcommand*{\printunsrtglossaries}{%
    \forallglossaries{\@glo@type}{\printunsrtglossary[type=\@glo@type]}%
}

\newcommand*{\@print@unsrt@glossary}{%
    \glossarysection[\glossarytoctitle]{\glossarytitle}%
    \glossarypreamble
    \glsxtrifemptyglossary{\@glo@type}%
    {%
        \GlossariesExtraWarning{No entries defined in glossary ‘\@glo@type’}%
    }%
    {%
        \key@ifundefined{glossentry}{group}%
        {\let\@gls@getgrouptitle\@gls@noidx@getgrouptitle}%
        {\let\@gls@getgrouptitle\@glsxtr@unsrt@getgrouptitle}%
        \def\@gls@currentlettergroup{}%
        \def\@glsxtr@doglossary{%
            \begin{theglossary}%
            \glossaryheader
            \glsresetentrylist
        }%
        \expandafter\@for\expandafter\glscurrententrylabel\expandafter
        : \expandafter=\csname glist@\@glo@type\endcsname\do{%
            \ifdefempty{\glscurrententrylabel}
            {}%
            {%
                \let\glsxtr@process\@firstofone
                \let\printunsrtglossaryskipentry
                    \@glsxtr@printunsrtglossaryskipentry
                \printunsrtglossaryentryprocesshook{\glscurrententrylabel}%
                \glsxtr@process
                {%
                    \ifglsxtr@printgloss@groups
                    \ifglshasparent{\glscurrententrylabel}{}%
                    {%
                        \@glsxtr@checkgroup\glscurrententrylabel
                        \expandafter\appto\expandafter\@glsxtr@doglossary\expandafter
                        {\@glsxtr@groupheading}%
                    }%
                }%
            }%
        }
        \fi
        \protected@eappto\@glsxtr@doglossary{%
            \noexpand\@printunsrt@glossary@handler{\glscurrententrylabel}}%
    }%
}

```

```

    }%
  }%
}%
\appto\@glsxtr@doglossary{\end{theglossary}}%
\printunsrtglossarypredoglossary
\@glsxtr@doglossary
}%
\glossarypostamble
}
\newcommand*{\printunsrtinnerglossary}[3][]{%
  \begingroup
  \def\@glsxtr@printglossopts{#1}%
  \def\@glo@type{\glsdefaulttype}%
  \setkeys{printgloss}[title,toctitle,style,numberedsection,sort,label]{#1}%
  \let\currentglossary\@glo@type
  #2%
  \@print@unsrt@innerglossary
  #3%
  \endgroup
}
\newenvironment{printunsrtglossarywrap}[1][]{%
  {%
    \def\@glsxtr@printglossopts{#1}%
    \def\@glo@type{\glsdefaulttype}%
    \def\glossarytitle{\csname @glo@type\@glo@type @title\endcsname}%
    \def\glossarytoctitle{\glossarytitle}%
    \let\org@glossarytitle\glossarytitle
    \def\@glossarystyle{%
      \ifx\@glossary@default@style\relax
        \GlossariesWarning{No default glossary style provided \MessageBreak
          for the glossary '@glo@type'. \MessageBreak
          Using deprecated fallback. \MessageBreak
          To fix this set the style with \MessageBreak
          \string\setglossarystyle\space or use the \MessageBreak
          style key=value option}%
      \fi
    }%
    \def\gls@dotoc@title{\glssettoctitle{\@glo@type}}%
    \let\@org@glossaryentrynumbers\glossaryentrynumbers
    \@printgloss@setsort
    \setkeys{printgloss}{#1}%
    \ifglossaryexists*\@glo@type}%
  {%
    \ifx\glossarytitle\org@glossarytitle
    \else
      \expandafter\let\csname @glo@type\@glo@type @title\endcsname
        \glossarytitle
    \fi
    \let\currentglossary\@glo@type
  }%
}

```

```

}%
\let\org@glossaryentrynumbers\glossaryentrynumbers
\let\glsnonextpages\@glsnonextpages
\let\glsnextpages\@glsnextpages
\let\nopostdesc\@nopostdesc
\gls@dotocitle
\@glossarystyle
\let\gls@org@glossaryentryfield\glossentry
\let\gls@org@glossarysubentryfield\subglossentry
\renewcommand{\glossentry}[1]{%
  \protected@xdef\glscurrententrylabel{\glsdetoklabel{##1}}%
  \gls@org@glossaryentryfield{##1}%
}%
\renewcommand{\subglossentry}[2]{%
  \protected@xdef\glscurrententrylabel{\glsdetoklabel{##2}}%
  \gls@org@glossarysubentryfield{##1}{##2}%
}%
\@gls@preglossaryhook
\glossarysection[\glossarytocitle]{\glossarytitle}%
\glossarypreamble
\begin{theglossary}%
\glossaryheader
\glsresetentrylist
}%
{%
  \end{theglossary}%
  \glossarypostamble
  \global\let\glossaryentrynumbers\@org@glossaryentrynumbers
  \global\let\warn@noprintglossary\relax
}
\newcommand*{\@print@unsrt@innerglossary}{%
  \glsxtrifemptyglossary{\@glo@type}%
  {%
    \GlossariesExtraWarning{No entries defined in glossary ‘\@glo@type’}%
  }%
  {%
    \key@ifundefined{glossentry}{group}%
    {\let\@gls@getgrouptitle\@gls@noidx@getgrouptitle}%
    {\let\@gls@getgrouptitle\@glsxtr@unsrt@getgrouptitle}%
    \def\@gls@currentlettergroup{}%
    \def\@glsxtr@doglossary{}%
    \expandafter\@for\expandafter\glscurrententrylabel\expandafter
      :\expandafter=\csname glist@\@glo@type\endcsname\do{%
        \ifdefempty{\glscurrententrylabel}
        {}%
        {%
          \let\glsxtr@process\@firstofone
          \let\printunsrtglossaryskipentry
            \@glsxtr@printunsrtglossaryskipentry
          \printunsrtglossaryentryprocesshook{\glscurrententrylabel}%

```

```

\glxtr@process
{%
  \ifglxtr@printgloss@groups
    \ifglshasparent{\glscurrententrylabel}{}%
    {%
      \@glxtr@checkgroup\glscurrententrylabel
      \expandafter\appto\expandafter\@glxtr@doglossary\expandafter
        {\@glxtr@groupheading}%
    }%
  \fi
  \protected@eappto\@glxtr@doglossary{%
    \noexpand\@printunsrt@glossary@handler{\glscurrententrylabel}}%
}%
}%
\printunsrtglossarypredoglossary
\@glxtr@doglossary
}%
}
\newcommand*{\printunsrtglossaryentryprocesshook}[1]{}
\newcommand*{\printunsrtglossaryskipentry}{%
  \PackageError{glossaries-extra}{\string\printunsrtglossaryskipentry\space
can only be used within \string\printunsrtglossaryentryprocesshook}{}%
}
\newcommand*{\@glxtr@printunsrtglossaryskipentry}{%
  \let\glxtr@process\@gobble
}
\newcommand*{\printunsrtglossarypredoglossary}{}
\newcommand{\@printunsrt@glossary@handler}[1]{%
  \protected@xdef\glscurrententrylabel{#1}%
  \printunsrtglossaryhandler\glscurrententrylabel
}
\newcommand{\printunsrtglossaryhandler}[1]{%
  \glxtrunsrtdo{#1}%
}
\newrobustcmd*{\glxtriflabelinlist}[4]{%
  \protected@edef\@glxtr@doiflabelinlist{\noexpand\@glx@ifinlist{#1}{#2}}%
  \@glxtr@doiflabelinlist{#3}{#4}%
}
\newcommand{\print@op@unsrtglossaryunit}[2][ ]{%
  \s@printunsrtglossary[type=\gldefaulttype,#1]{%
    \printunsrtglossaryunitsetup{#2}%
  }%
}
\newcommand*{\printunsrtglossaryunitsetup}[1]{%
  \renewcommand{\printunsrtglossaryhandler}[1]{%
    \glxtrfieldxifinlist{##1}{record.#1}{\csuse{the#1}}
    {\glxtrunsrtdo{##1}}%
  }%
}%

```

```

\ifcsundef{theH#1}%
{%
  \renewcommand*{\@glxtrhypernameprefix}{record.#1.\csuse{the#1}.\@gobble}%
}%
{%
  \renewcommand*{\@glxtrhypernameprefix}{record.#1.\csuse{theH#1}.\@gobble}%
}%
\renewcommand*{\glossarysection}[2][{}]{%
\appto\glossarypostamble{\glspare\medskip\glspare}%
}
\newcommand{\print@noop@unsrtglossaryunit}[2][{}]{%
\PackageError{glossaries-extra}{\string\printunsrtglossaryunit\space
requires the record=only or record=alsoindex package option}{}%
}
\newrobustcmd*{\@glxtr@unsrt@getgrouptitle}[2]{%
\protected@edef\@glxtr@titlelabel{\glxtr@grouptitle@#1}%
\@onelevel@sanitize\@glxtr@titlelabel
\ifcsdef{\@glxtr@titlelabel}
{\letcs{#2}{\@glxtr@titlelabel}}%
{\def#2{#1}}%
}
\newcommand{\glxtrunsrtdo}{\@glxtr@noidx@do}
\newcommand*{\glxtrgroupfield}{group}
\newcommand*{\@glxtr@checkgroup}[1]{%
\def\@glxtr@groupheading{%
\key@ifundefined{glossentry}{group}%
{%
\letcs{\@gls@sort}{glo@\glsdetoklabel{#1}@sort}%
\expandafter\glo@grabfirst\@gls@sort{}\@nil
}%
}%
\protected@edef\@glo@thislettergrp{%
\csuse{glo@\glsdetoklabel{#1}@\glxtrgroupfield}}%
}%
\ifdefequal{\@glo@thislettergrp}{\@gls@currentlettergroup}%
{}%
{%
\ifdefempty{\@gls@currentlettergroup}{}%
{\def\@glxtr@groupheading{\gls@groupskip}}%
\protected@eappto\@glxtr@groupheading{%
\noexpand\gls@groupheading{\expandonce\@glo@thislettergrp}%
}%
}%
\let\@gls@currentlettergroup\@glo@thislettergrp
}
\newcommand*{\GlsXtrLocationField}{location}
\newcommand{\@glxtr@noidx@do}[1]{%
\ifglstryexists{#1}%
{%
\global\letcs{\@gls@loclist}{glo@\glsdetoklabel{#1}@loclist}%

```

```

\global\letcs{\@gls@location}{glo@\glsdetoklabel{#1}@\GlsXtrLocationField}%
\gls@level=\numexpr\csuse{glo@\glsdetoklabel{#1}@level}+\@glsxtr@leveloffset\relax
\ifnum\gls@level>0
  \let\@glsxtr@ifischild\@firstoftwo
\else
  \let\@glsxtr@ifischild\@secondoftwo
\fi
\@glsxtr@ifischild
{%
  \ifdefvoid{\@gls@location}%
  {%
    \ifdefvoid{\@gls@loclist}%
    {%
      \expandafter\subglossentry\expandafter{\number\gls@level}{#1}{}%
    }%
    {%
      \expandafter\subglossentry\expandafter{\number\gls@level}{#1}%
      {%
        \glossaryentrynumbers{\glsnoidxloclist{\@gls@loclist}}%
      }%
    }%
  }%
  {%
    \expandafter\subglossentry\expandafter
      {\number\gls@level}{#1}{\glossaryentrynumbers{\@gls@location}}%
  }%
}%
{%
  \ifdefvoid{\@gls@location}%
  {%
    \ifdefvoid{\@gls@loclist}
    {%
      \glossentry{#1}{}%
    }%
    {%
      \glossentry{#1}%
      {%
        \glossaryentrynumbers{\glsnoidxloclist{\@gls@loclist}}%
      }%
    }%
  }%
  {%
    \glossentry{#1}%
    {%
      \glossaryentrynumbers{\@gls@location}%
    }%
  }%
}%
{}%

```



```

}
\newcount\@glxstrnewgls@inner
\newcommand*{\@glxstr@providenewgls}{%
  \protected@write\@auxout{}\string\providecommand{\string\@glxstr@newglslike}[2]{}%
  \let\@glxstr@providenewgls\relax
}
\newcommand{\glxstridentifyglslike}[2]{%
  \ifdefequal\@glxstr@record@setting\@glxstr@record@setting@off
  {}%
  {%
    \@glxstr@providenewgls
    \protected@write\@auxout{}\string\@glxstr@newglslike{#1}{\string#2}}%
  }%
}
\newcommand*{\@glxstrnewgls}[4]{%
  \ifdef{#3}%
  {%
    \PackageError{glossaries-extra}{Command \string#3\space already
defined}{}%
  }%
  {%
    \glxstridentifyglslike{#2}{#3}%
    \ifcsdef{@#4like@#2}%
    {%
      \advance\@glxstrnewgls@inner by \@ne
      \def\@glxstrnewgls@innercsname{@#4like\number\@glxstrnewgls@inner @#2}%
    }%
    {\def\@glxstrnewgls@innercsname{@#4like@#2}}%
    \expandafter\newrobustcmd\expandafter*\expandafter
    #3\expandafter{\expandafter\@glx@hyp@opt\csname\@glxstrnewgls@innercsname\endcsname}%
    \ifstrempy{#1}%
    {%
      \expandafter\newcommand\expandafter*\csname\@glxstrnewgls@innercsname\endcsname[2][]{%
        \new@ifnextchar[%
          {\csname @#4@\endcsname{##1}{#2##2}}%
          {\csname @#4@\endcsname{##1}{#2##2}[]}%
        }%
      }%
    }%
    {\expandafter\newcommand\expandafter*\csname\@glxstrnewgls@innercsname\endcsname[2][]{%
      \new@ifnextchar[%
        {\csname @#4@\endcsname{#1,##1}{#2##2}}%
        {\csname @#4@\endcsname{#1,##1}{#2##2}[]}%
      }%
    }%
  }%
}
\newrobustcmd*{\glxstrnewgls}[3][]{%
  \@glxstrnewgls{#1}{#2}{#3}{gls}%
}

```

```

\newrobustcmd*{\glsxtrnewglslike}[6] [] {%
  \@glsxtrnewgls{#1}{#2}{#3}{gls}%
  \@glsxtrnewgls{#1}{#2}{#4}{glspl}%
  \@glsxtrnewgls{#1}{#2}{#5}{Gls}%
  \@glsxtrnewgls{#1}{#2}{#6}{Glspl}%
}
\newrobustcmd*{\glsxtrnewGLSlike}[4] [] {%
  \@glsxtrnewgls{#1}{#2}{#3}{GLS}%
  \@glsxtrnewgls{#1}{#2}{#4}{GLSpl}%
}
\newrobustcmd*{\glsxtrnewrgls}[3] [] {%
  \@glsxtrnewgls{#1}{#2}{#3}{rgls}%
}
\newrobustcmd*{\glsxtrnewrglslike}[6] [] {%
  \@glsxtrnewgls{#1}{#2}{#3}{rgls}%
  \@glsxtrnewgls{#1}{#2}{#4}{rglspl}%
  \@glsxtrnewgls{#1}{#2}{#5}{rGls}%
  \@glsxtrnewgls{#1}{#2}{#6}{rGlspl}%
}
\newrobustcmd*{\glsxtrnewrGLSlike}[4] [] {%
  \@glsxtrnewgls{#1}{#2}{#3}{rGLS}%
  \@glsxtrnewgls{#1}{#2}{#4}{rGLSpl}%
}
\newcommand*{\GlsXtrTotalRecordCount}[1] {%
  \ifcsdef{glo@\glsdetoklabel{#1}@recordcount}%
  {\csname glo@\glsdetoklabel{#1}@recordcount\endcsname}%
  {0}%
}
\newcommand*{\GlsXtrRecordCount}[2] {%
  \ifcsdef{glo@\glsdetoklabel{#1}@recordcount.#2}%
  {\csname glo@\glsdetoklabel{#1}@recordcount.#2\endcsname}%
  {0}%
}
\newcommand*{\GlsXtrLocationRecordCount}[3] {%
  \ifcsdef{glo@\glsdetoklabel{#1}@recordcount.#2.\glsxtrdetoklocation{#3}}%
  {\csname glo@\glsdetoklabel{#1}@recordcount.#2.\glsxtrdetoklocation{#3}\endcsname}%
  {0}%
}
\newcommand*{\glsxtrdetoklocation}[1] {#1}
\newcommand*{\glsxtrenablerecordcount} {%
  \renewcommand*{\gls}{\rgls}%
  \renewcommand*{\Gls}{\rGls}%
  \renewcommand*{\glspl}{\rglspl}%
  \renewcommand*{\Glspl}{\rGlspl}%
  \renewcommand*{\GLS}{\rGLS}%
  \renewcommand*{\GLSpl}{\rGLSpl}%
}
\newcommand*{\glsxtrrecordtriggervalue}[1] {%
  \GlsXtrTotalRecordCount{#1}%
}

```

```

\newcommand*{\GlsXtrSetRecordCountAttribute}[2]{%
  \@for\@glstr@cat:=#1\do
  {%
    \ifdefempty{\@glstr@cat}{}%
    {%
      \glsssetcategoryattribute{\@glstr@cat}{recordcount}{#2}%
    }%
  }%
}
\newcommand*{\glstrifrecordtrigger}[3]{%
  \glshasattribute{#1}{recordcount}%
  {%
    \ifnum\glstrrecordtriggervalue{#1}>\glsggetattribute{#1}{recordcount}\relax
    #3%
    \else
    #2%
    \fi
  }%
  {#3}%
}
\newcommand*{\@glstr@rglstrigger@record}[3]{%
  \protected@edef\glslabel{\glsdetoklabel{#2}}%
  \let\@gls@link@label\glslabel
  \def\@glstr@thevalue{%
    \def\@glstr@theHvalue{\@glstr@thevalue}%
    \def\@glsnumberformat{glstriggerrecordformat}%
    \protected@edef\@gls@counter{\csname glo@\glslabel @counter\endcsname}%
    \protected@edef\glstype{\csname glo@\glslabel @type\endcsname}%
    \def\@glstr@thevalue{%
      \def\@glstr@theHvalue{\@glstr@thevalue}%
      \@gls@save@glslocal
      \glstrinitwrgloss
      \glslinkpresetkeys
      \setkeys{glslink}{#1}%
      \glslinkpostsetkeys
      \ifdefempty{\@glstr@thevalue}%
      {%
        \@gls@save@entrycounter
      }%
      {%
        \let\thegl@entrycounter\@glstr@thevalue
        \def\theHgl@entrycounter{\@glstr@theHvalue}%
      }%
      \glslinkwrcontent
      {%
        \ifglstrinitwrglossbefore
        \@do@wrglossary{#2}%
        \fi
        #3%
        \ifglstrinitwrglossbefore

```

```

\else
\do@wrglossary{#2}%
\fi
}%
\@gls@restore@glslocal
\@gls@do@glsunset{#2}%
}
\newcommand*{\glstriggerrecordformat}[1]{%
\newrobustcmd*{\rgls}{\@gls@hyp@opt\@rgls}
\newcommand*{\@rgls}[2][]{%
\new@ifnextchar[{\@rgls@{#1}{#2}}{\@rgls@{#1}{#2}[]}%
}
\def\@rgls@#1#2[#3]{%
\glstriferecordtrigger{#2}%
{%
\@glstr@rglstrigger@record{#1}{#2}{\rglsformat{#2}{#3}}%
}%
{%
\@gls@{#1}{#2}[#3]%
}%
}%
\newrobustcmd*{\rglspl}{\@gls@hyp@opt\@rglspl}
\newcommand*{\@rglspl}[2][]{%
\new@ifnextchar[{\@rglspl@{#1}{#2}}{\@rglspl@{#1}{#2}[]}%
}
\def\@rglspl@#1#2[#3]{%
\glstriferecordtrigger{#2}%
{%
\@glstr@rglstrigger@record{#1}{#2}{\rglsplformat{#2}{#3}}%
}%
{%
\@glspl@{#1}{#2}[#3]%
}%
}%
\newrobustcmd*{\rGls}{\@gls@hyp@opt\@rGls}
\newcommand*{\@rGls}[2][]{%
\new@ifnextchar[{\@rGls@{#1}{#2}}{\@rGls@{#1}{#2}[]}%
}
\def\@rGls@#1#2[#3]{%
\glstriferecordtrigger{#2}%
{%
\@glstr@rglstrigger@record{#1}{#2}{\rGlsformat{#2}{#3}}%
}%
{%
\@rGls@{#1}{#2}[#3]%
}%
}%
\newrobustcmd*{\rGlspl}{\@gls@hyp@opt\@rGlspl}
\newcommand*{\@rGlspl}[2][]{%
\new@ifnextchar[{\@rGlspl@{#1}{#2}}{\@rGlspl@{#1}{#2}[]}%
}

```

```

}
\def\@rGlspl@#1#2[#3]{%
  \glsxtrifrecordtrigger{#2}%
  {%
    \glsxtr@rglstrigger@record{#1}{#2}{\rGlsplformat{#2}{#3}}%
  }%
  {%
    \@Glspl@{#1}{#2}[#3]%
  }%
}%
\newrobustcmd*{\rGLS}{\@gls@hyp@opt\rGLS}
\newcommand*{\@rGLS}[2][{}]{%
  \new@ifnextchar[{\@rGLS@{#1}{#2}}{\@rGLS@{#1}{#2}[]}%
}
\def\@rGLS@#1#2[#3]{%
  \glsxtrifrecordtrigger{#2}%
  {%
    \glsxtr@rglstrigger@record{#1}{#2}{\rGLSformat{#2}{#3}}%
  }%
  {%
    \@GLS@{#1}{#2}[#3]%
  }%
}%
\newrobustcmd*{\rGLSpl}{\@gls@hyp@opt\rGLSpl}
\newcommand*{\@rGLSpl}[2][{}]{%
  \new@ifnextchar[{\@rGLSpl@{#1}{#2}}{\@rGLSpl@{#1}{#2}[]}%
}
\def\@rGLSpl@#1#2[#3]{%
  \glsxtrifrecordtrigger{#2}%
  {%
    \glsxtr@rglstrigger@record{#1}{#2}{\rGLSplformat{#2}{#3}}%
  }%
  {%
    \@GLSpl@{#1}{#2}[#3]%
  }%
}%
\newcommand*{\rglsformat}[2]{%
  \glsifregular{#1}
  {\glsentryfirst{#1}}%
  {\ifglshaslong{#1}{\glsentrylong{#1}}{\glsentryfirst{#1}}}%#2%
}
\newcommand*{\rglsplformat}[2]{%
  \glsifregular{#1}
  {\glsentryfirstplural{#1}}%
  {\ifglshaslong{#1}{\glsentrylongplural{#1}}{\glsentryfirstplural{#1}}}%#2%
}
\newcommand*{\rGlsformat}[2]{%
  \glsifregular{#1}
  {\Glsentryfirst{#1}}%
  {\ifglshaslong{#1}{\Glsentrylong{#1}}{\Glsentryfirst{#1}}}%#2%
}

```

```

}
\newcommand*{\rGlsplformat}[2]{%
  \glsifregular{#1}
  {\Glsentryfirstplural{#1}}%
  {\ifglshaslong{#1}{\Glsentrylongplural{#1}}{\Glsentryfirstplural{#1}}}\#2%
}
\newcommand*{\rGLSformat}[2]{%
  \expandafter\mfirstucMakeUppercase\expandafter{\rglsformat{#1}{#2}}%
}
\newcommand*{\rGLSplformat}[2]{%
  \expandafter\mfirstucMakeUppercase\expandafter{\rglsplformat{#1}{#2}}%
}
\newcommand{\@glsxtr@do@inc@linkcount}{%
  \glsifattribute{\glslabel}{linkcount}{true}%
  {%
    \ifcsdef{c@glsxtr@linkcount@\glslabel}{}%
    {%
      \newcounter{glsxtr@linkcount@\glslabel}%
      \glshasattribute{\glslabel}{linkcountmaster}%
      {%
        \begingroup
          \edef\@glo@tmp{\endgroup\noexpand\@addtoreset{glsxtr@linkcount@\glslabel}}%
          {\glsgetattribute{\glslabel}{linkcountmaster}}}%
        \@glo@tmp
      }%
    }%
  }%
  \glsxtrinclinkcounter{glsxtr@linkcount@\glslabel}%
}%
{}%
}
\newcommand*{\glsxtrinclinkcounter}[1]{\stepcounter{#1}}
\newcommand*{\GlsXtrLinkCounterValue}[1]{%
  \ifcsundef{c@glsxtr@linkcount@#1}{0}{\csname c@glsxtr@linkcount@#1\endcsname}%
}
\newcommand*{\GlsXtrTheLinkCounter}[1]{%
  \ifcsundef{theglsxtr@linkcount@#1}{0}%
  {\csname theglsxtr@linkcount@#1\endcsname}%
}
\newcommand*{\GlsXtrIfLinkCounterDef}[3]{%
  \ifcsundef{theglsxtr@linkcount@#1}{#3}{#2}%
}
\newcommand*{\GlsXtrLinkCounterName}[1]{glsxtr@linkcount@#1}
\newcommand*{\GlsXtrEnableLinkCounting}[2][{}]{%
  \let\glsxtr@inc@linkcount\@glsxtr@do@inc@linkcount
  \@for\@glsxtr@label:=#2\do
  {%
    \glssetcategoryattribute{\@glsxtr@label}{linkcount}{true}%
    \ifstrempy{#1}{}%
  }%
}

```

```

\ifcsundef{c@#1}%
{\@nocounterr{#1}}%
{\glsssetcategoryattribute{\@glstr@label}{linkcountmaster}{#1}}%
}%
}%
}
\@onlypreamble\GlsXtrEnableLinkCounting
\@ifpackageloaded{glossaries-accsupp}
{
\newcommand*{\glsaccessname}[1]{%
\glsnameaccessdisplay
{%
\glentryname{#1}%
}%
{#1}%
}
\newcommand*{\Glsaccessname}[1]{%
\glsnameaccessdisplay
{%
\Glentryname{#1}%
}%
{#1}%
}
\newcommand*{\GLSaccessname}[1]{%
\glsnameaccessdisplay
{%
\mfirstucMakeUppercase{\glentryname{#1}}%
}%
{#1}%
}
\newcommand*{\glsaccesstext}[1]{%
\glstextaccessdisplay
{%
\glentrytext{#1}%
}%
{#1}%
}
\newcommand*{\Glsaccesstext}[1]{%
\glstextaccessdisplay
{%
\Glentrytext{#1}%
}%
{#1}%
}
\newcommand*{\GLSaccesstext}[1]{%
\glstextaccessdisplay
{%
\mfirstucMakeUppercase{\glentrytext{#1}}%
}%
{#1}%
}

```

```

}
\newcommand*{\glsaccessplural}[1]{%
  \glspluralaccessdisplay
  {%
    \glentryplural{#1}%
  }%
  {#1}%
}
\newcommand*{\Glsaccessplural}[1]{%
  \glspluralaccessdisplay
  {%
    \Glsentryplural{#1}%
  }%
  {#1}%
}
\newcommand*{\GLSaccessplural}[1]{%
  \glspluralaccessdisplay
  {%
    \mfirstucMakeUppercase{\glentryplural{#1}}%
  }%
  {#1}%
}
\newcommand*{\glsaccessfirst}[1]{%
  \glsfirstaccessdisplay
  {%
    \glentryfirst{#1}%
  }%
  {#1}%
}
\newcommand*{\Glsaccessfirst}[1]{%
  \glsfirstaccessdisplay
  {%
    \Glsentryfirst{#1}%
  }%
  {#1}%
}
\newcommand*{\GLSaccessfirst}[1]{%
  \glsfirstaccessdisplay
  {%
    \mfirstucMakeUppercase{\glentryfirst{#1}}%
  }%
  {#1}%
}
\newcommand*{\glsaccessfirstplural}[1]{%
  \glsfirstpluralaccessdisplay
  {%
    \glentryfirstplural{#1}%
  }%
  {#1}%
}

```



```

\newcommand*\Glsaccessfirstplural}[1]{%
  \glsfirstpluralaccessdisplay
  {%
    \Glsentryfirstplural{#1}%
  }%
  {#1}%
}
\newcommand*\GLSaccessfirstplural}[1]{%
  \glsfirstpluralaccessdisplay
  {%
    \mfirstucMakeUppercase{\glsentryfirstplural{#1}}%
  }%
  {#1}%
}
\newcommand*\Glsaccesssymbol}[1]{%
  \glssymbolaccessdisplay
  {%
    \Glsentrysymbol{#1}%
  }%
  {#1}%
}
\newcommand*\GLSaccesssymbol}[1]{%
  \glssymbolaccessdisplay
  {%
    \Glsentrysymbol{#1}%
  }%
  {#1}%
}
\newcommand*\Glsaccesssymbolplural}[1]{%
  \glssymbolpluralaccessdisplay
  {%
    \Glsentrysymbolplural{#1}%
  }%
  {#1}%
}
\newcommand*\GLSaccesssymbolplural}[1]{%
  \glssymbolpluralaccessdisplay
  {%
    \Glsentrysymbolplural{#1}%
  }%
  {#1}%
}
\newcommand*\GLSaccesssymbolplural}[1]{%

```

```

\glssymbolpluralaccessdisplay
{%
  \mfirstucMakeUppercase{\glentrysymbolplural{#1}}%
}%
{#1}%
}
\newcommand*{\glsaccessdesc}[1]{%
  \glsdescriptionaccessdisplay
  {%
    \glentrydesc{#1}%
  }%
  {#1}%
}
\newcommand*{\Glsaccessdesc}[1]{%
  \glsdescriptionaccessdisplay
  {%
    \Glsentrydesc{#1}%
  }%
  {#1}%
}
\newcommand*{\GLSaccessdesc}[1]{%
  \glsdescriptionaccessdisplay
  {%
    \mfirstucMakeUppercase{\glentrydesc{#1}}%
  }%
  {#1}%
}
\newcommand*{\glsaccessdescplural}[1]{%
  \glsdescriptionpluralaccessdisplay
  {%
    \glentrydescplural{#1}%
  }%
  {#1}%
}
\newcommand*{\Glsaccessdescplural}[1]{%
  \glsdescriptionpluralaccessdisplay
  {%
    \Glsentrydescplural{#1}%
  }%
  {#1}%
}
\newcommand*{\GLSaccessdescplural}[1]{%
  \glsdescriptionpluralaccessdisplay
  {%
    \mfirstucMakeUppercase{\glentrydescplural{#1}}%
  }%
  {#1}%
}
\newcommand*{\glsaccessshort}[1]{%
  \glsshortaccessdisplay

```

```

    {%
      \glentryshort{#1}%
    }%
    {#1}%
  }
\newcommand*\{Glsaccessshort}[1]{%
  \glsshortaccessdisplay
  {%
    \glentryshort{#1}%
  }%
  {#1}%
}
\newcommand*\{GLSaccessshort}[1]{%
  \glsshortaccessdisplay
  {%
    \mfirstucMakeUppercase{\glentryshort{#1}}%
  }%
  {#1}%
}
\newcommand*\{glsaccessshortpl}[1]{%
  \glsshortpluralaccessdisplay
  {%
    \glentryshortpl{#1}%
  }%
  {#1}%
}
\newcommand*\{Glsaccessshortpl}[1]{%
  \glsshortpluralaccessdisplay
  {%
    \glentryshortpl{#1}%
  }%
  {#1}%
}
\newcommand*\{GLSaccessshortpl}[1]{%
  \glsshortpluralaccessdisplay
  {%
    \mfirstucMakeUppercase{\glentryshortpl{#1}}%
  }%
  {#1}%
}
\newcommand*\{glsaccesslong}[1]{%
  \glslongaccessdisplay{\glentrylong{#1}}{#1}%
}

\newcommand*\{Glsaccesslong}[1]{%
  \glslongaccessdisplay{\glentrylong{#1}}{#1}%
}
\newcommand*\{GLSaccesslong}[1]{%
  \glslongaccessdisplay
  {%

```

```

\mfirstucMakeUppercase{\glentrylong{#1}}%
}%
{#1}%
}
\newcommand*{\glsaccesslongpl}[1]{%
\glslongpluralaccessdisplay{\glentrylongpl{#1}}{#1}%
}

\newcommand*{\Glsaccesslongpl}[1]{%
\glslongpluralaccessdisplay{\Glsentrylongpl{#1}}{#1}%
}
\newcommand*{\GLSaccesslongpl}[1]{%
\glslongpluralaccessdisplay
{%
\mfirstucMakeUppercase{\glentrylongpl{#1}}%
}%
{#1}%
}
\define@key{glsxtrabbrv}{access}{%
\def\@gls@nameaccess{#1}%
}
\define@key{glsxtrabbrv}{textaccess}{%
\def\@gls@textaccess{#1}%
}
\define@key{glsxtrabbrv}{pluralaccess}{%
\def\@gls@pluralaccess{#1}%
}
\define@key{glsxtrabbrv}{firstaccess}{%
\def\@gls@firstaccess{#1}%
}
\define@key{glsxtrabbrv}{firstpluralaccess}{%
\def\@gls@firstpluralaccess{#1}%
}
\define@key{glsxtrabbrv}{shortaccess}{%
\def\@gls@shortaccess{#1}%
}
\define@key{glsxtrabbrv}{shortpluralaccess}{%
\def\@gls@shortaccesspl{#1}%
}
\define@key{glsxtrabbrv}{longaccess}{%
\def\@gls@longaccess{#1}%
}
\define@key{glsxtrabbrv}{shortlonglaccess}{%
\def\@gls@longaccesspl{#1}%
}
\newcommand*{\@gls@initaccesskeys}{%
\def\@gls@nameaccess{}%
\def\@gls@textaccess{}%
\def\@gls@pluralaccess{}%
\def\@gls@firstaccess{}%

```

```

\def\@gls@firstpluralaccess{%
\def\@gls@shortaccess{%
\def\@gls@shortaccesspl{%
\def\@gls@longaccess{%
\def\@gls@longaccesspl{%
}
\newcommand*{\@gls@ifaccessattribute@set}[3]{%
\glsifcategoryattribute{\glscategorylabel}{access#1}{true}%
{#2}%
{%
\glsifcategoryattribute{\glscategorylabel}{access#1}{false}%
{#3}%
{%
\glsifcategoryattribute{\glscategorylabel}{#1}{true}%
{#2}%
{#3}%
}%
}%
}
\def\glsdefaultshortaccess#1#2{#1 (#2)}
\newcommand{\glstrassignactualsetup}{%
\let\@empty
\let\emph\@firstofone
\let\textbf\@firstofone
\let\textmd\@firstofone
\let\textit\@firstofone
\let\textsl\@firstofone
\let\textsc\@firstofone
\let\textrm\@firstofone
\let\textsf\@firstofone
\let\texttt\@firstofone
}
\ifdef\pdfstringdef
{
\newcommand{\@gls@assign@actual}{%
\begingroup
\glstrassignactualsetup
\pdfstringdef\@gls@actualshort{\glstrorgshort}%
\pdfstringdef\@gls@actuaallong{\glstrorglong}%
\pdfstringdef\@gls@actualshortpl{\@gls@shortpl}%
\pdfstringdef\@gls@actuaallongpl{\@gls@longpl}%
\protected@edef\@gls@tmp{\endgroup
\def\noexpand\@gls@actualshort{\expandonce\@gls@actualshort}%
\def\noexpand\@gls@actuaallong{\expandonce\@gls@actuaallong}%
\def\noexpand\@gls@actualshortpl{\expandonce\@gls@actualshortpl}%
\def\noexpand\@gls@actuaallongpl{\expandonce\@gls@actuaallongpl}%
}%
\@gls@tmp
}
}
}

```

```

{
  \newcommand{\@gls@assign@actual}{%
    \begin{group}
      \glsxtrassignactualsetup
      \protected@edef\@gls@tmp{\end{group}
        \def\noexpand\@gls@actualshort{\glsxtrorgshort}%
        \def\noexpand\@gls@actuallong{\glsxtrorglong}%
        \def\noexpand\@gls@actualshortpl{\@gls@shortpl}%
        \def\noexpand\@gls@actuallongpl{\@gls@longpl}%
      }%
      \@gls@tmp
    }
  }
}
\newcommand{\@gls@setup@default@access}{%
  \@gls@assign@actual
  \ifdefempty\@gls@shortaccess
  {%
    \@gls@ifaccessattribute@set{insertdots}%
    {%
      \expandafter\@glsxtr@insertdots\expandafter\@gls@actualshort\expandafter
        {\@gls@actualshort}%
    }%
    {}%
  }
  \ifdefempty\@gls@longaccess
  {%
    \protected@edef\@gls@shortaccess{\glsdefaultshortaccess
      {\expandonce\@gls@actuallong}{\expandonce\@gls@actualshort}}%
    }%
    {%
      \protected@edef\@gls@shortaccess{\glsdefaultshortaccess
        {\expandonce\@gls@longaccess}{\expandonce\@gls@actualshort}}%
      }%
  }
  \eappto\ExtraCustomAbbreviationFields{shortaccess={\@gls@shortaccess},}%
  \ifdefempty\@gls@shortaccesspl
  {%
    \@gls@ifaccessattribute@set{aposplural}%
    {%
      \expandafter\def\expandafter\@gls@shortaccesspl\expandafter{%
        \@gls@actualshort'\glsxtrabbrvpluralsuffix}%
      }%
      {%
        \@gls@ifaccessattribute@set{noshortplural}%
        {%
          \let\@gls@shortaccesspl\@gls@shortaccess
        }%
        {%
          \let\@gls@shortaccesspl\@gls@actualshortpl
        }%
      }%
    }%
  }
  \ifdefempty\@gls@longaccesspl

```

```

{%
  \protected@edef\@gls@shortaccesspl{\glsdefaultshortaccess
    {\expandonce\@gls@actuallongpl}{\expandonce\@gls@actualshortpl}}%
}%
{%
  \protected@edef\@gls@shortaccesspl{\glsdefaultshortaccess
    {\expandonce\@gls@longaccesspl}{\expandonce\@gls@actualshort}}%
}%
\eaopto\ExtraCustomAbbreviationFields{shortpluralaccess={\@gls@shortaccesspl},}%
}%
{}%
}%
{%
  \ifdefempty\@gls@shortaccesspl
    {\let\@gls@shortaccesspl\@gls@shortaccess}%
  {}%
}%
\ifdefempty\@gls@nameaccess
{%
  \glsifcategoryattribute{\glscategorylabel}{nameshortaccess}{true}%
  {%
    \eaopto\ExtraCustomAbbreviationFields{access={\@gls@shortaccess},}%
  }%
  {}%
}%
{}%
\ifdefempty\@gls@textaccess
{%
  \glsifcategoryattribute{\glscategorylabel}{textshortaccess}{true}%
  {%
    \eaopto\ExtraCustomAbbreviationFields{textaccess={\@gls@shortaccess},}%
  }%
  {}%
}%
{}%
\ifdefempty\@gls@pluralaccess
{%
  \glsifcategoryattribute{\glscategorylabel}{textshortaccess}{true}%
  {%
    \eaopto\ExtraCustomAbbreviationFields{%
      pluralaccess={\@gls@shortaccesspl},%
    }%
  }%
  {}%
}%
{}%
\ifdefempty\@gls@firstaccess
{%
  \glsifcategoryattribute{\glscategorylabel}{firstshortaccess}{true}%
  {%

```

```

\ea\ExtraCustomAbbreviationFields{firstaccess={\@gls@shortaccess},}%
}%
{}%
}%
{}%
\ifdefempty\@gls@firstpluralaccess
{%
\glsifcategoryattribute{\gls@categorylabel}{firstshortaccess}{true}%
{%
\ea\ExtraCustomAbbreviationFields{
firstpluralaccess={\@gls@shortaccesspl},%
}%
}%
{}%
}%
{}%
}
\newcommand*{\glsxtrprovideaccsuppcmd}[2]{%
\ifcsundef{glsxtr#1#2accsup}%
{\csdef{glsxtr#1#2accsup}{\glsshortaccsup}}%
}%
}
\newcommand*{\glsxtrAccSuppAbbrSetNoLongAttrs}[1]{%
\glssetcategoryattribute{#1}{nameshortaccess}{true}%
\glssetcategoryattribute{#1}{firstshortaccess}{true}%
\glssetcategoryattribute{#1}{textshortaccess}{true}%
\glsxtrprovideaccsuppcmd{#1}{name}%
\glsxtrprovideaccsuppcmd{#1}{first}%
\glsxtrprovideaccsuppcmd{#1}{firstpl}%
\glsxtrprovideaccsuppcmd{#1}{text}%
\glsxtrprovideaccsuppcmd{#1}{plural}%
}
\newcommand*{\glsxtrAccSuppAbbrSetFirstLongAttrs}[1]{%
\glssetcategoryattribute{#1}{nameshortaccess}{true}%
\glssetcategoryattribute{#1}{textshortaccess}{true}%
\glsxtrprovideaccsuppcmd{#1}{name}%
\glsxtrprovideaccsuppcmd{#1}{text}%
\glsxtrprovideaccsuppcmd{#1}{plural}%
}
\newcommand*{\glsxtrAccSuppAbbrSetTextShortAttrs}[1]{%
\glssetcategoryattribute{#1}{textshortaccess}{true}%
\glsxtrprovideaccsuppcmd{#1}{text}%
\glsxtrprovideaccsuppcmd{#1}{plural}%
}
\newcommand*{\glsxtrAccSuppAbbrSetNameShortAttrs}[1]{%
\glssetcategoryattribute{#1}{nameshortaccess}{true}%
\glsxtrprovideaccsuppcmd{#1}{name}%
}
\newcommand*{\glsxtrAccSuppAbbrSetNameLongAttrs}[1]{%
\glssetcategoryattribute{#1}{firstshortaccess}{true}%

```



```

\glsssetcategoryattribute{#1}{textshortaccess}{true}%
\glstrprovideaccsuppcmd{#1}{first}%
\glstrprovideaccsuppcmd{#1}{firstpl}%
\glstrprovideaccsuppcmd{#1}{text}%
\glstrprovideaccsuppcmd{#1}{plural}%
}
}
{
\newcommand*{\glsaccessname}[1]{\glsentryname{#1}}
\newcommand*{\Glsaccessname}[1]{\Glsentryname{#1}}
\newcommand*{\GLSaccessname}[1]{%
\protect\mfirstucMakeUppercase{\glsentryname{#1}}}
\newcommand*{\glsaccessstext}[1]{\glsentrytext{#1}}
\newcommand*{\Glsaccessstext}[1]{\Glsentrytext{#1}}
\newcommand*{\GLSaccessstext}[1]{%
\protect\mfirstucMakeUppercase{\glsentrytext{#1}}}
\newcommand*{\glsaccessplural}[1]{\glsentryplural{#1}}
\newcommand*{\Glsaccessplural}[1]{\Glsentryplural{#1}}
\newcommand*{\GLSaccessplural}[1]{%
\protect\mfirstucMakeUppercase{\glsentryplural{#1}}}
\newcommand*{\glsaccessfirst}[1]{\glsentryfirst{#1}}
\newcommand*{\Glsaccessfirst}[1]{\Glsentryfirst{#1}}
\newcommand*{\GLSaccessfirst}[1]{%
\protect\mfirstucMakeUppercase{\glsentryfirst{#1}}}
\newcommand*{\glsaccessfirstplural}[1]{\glsentryfirstplural{#1}}
\newcommand*{\Glsaccessfirstplural}[1]{\Glsentryfirstplural{#1}}
\newcommand*{\GLSaccessfirstplural}[1]{%
\protect\mfirstucMakeUppercase{\glsentryfirstplural{#1}}}
\newcommand*{\glsaccesssymbol}[1]{\glsentrysymbol{#1}}
\newcommand*{\Glsaccesssymbol}[1]{\Glsentrysymbol{#1}}
\newcommand*{\GLSaccesssymbol}[1]{%
\protect\mfirstucMakeUppercase{\glsentrysymbol{#1}}}
\newcommand*{\glsaccesssymbolplural}[1]{\glsentrysymbolplural{#1}}
\newcommand*{\Glsaccesssymbolplural}[1]{\Glsentrysymbolplural{#1}}
\newcommand*{\GLSaccesssymbolplural}[1]{%
\protect\mfirstucMakeUppercase{\glsentrysymbolplural{#1}}}
\newcommand*{\glsaccessdesc}[1]{\glsentrydesc{#1}}
\newcommand*{\Glsaccessdesc}[1]{\Glsentrydesc{#1}}
\newcommand*{\GLSaccessdesc}[1]{%
\protect\mfirstucMakeUppercase{\glsentrydesc{#1}}}
\newcommand*{\glsaccessdescplural}[1]{\glsentrydescplural{#1}}
\newcommand*{\Glsaccessdescplural}[1]{\Glsentrydescplural{#1}}
\newcommand*{\GLSaccessdescplural}[1]{%
\protect\mfirstucMakeUppercase{\glsentrydescplural{#1}}}
\newcommand*{\glsaccessshort}[1]{\glsentryshort{#1}}
\newcommand*{\Glsaccessshort}[1]{\Glsentryshort{#1}}
\newcommand*{\GLSaccessshort}[1]{%
\protect\mfirstucMakeUppercase{\glsentryshort{#1}}}
\newcommand*{\glsaccessshortpl}[1]{\glsentryshortpl{#1}}
\newcommand*{\Glsaccessshortpl}[1]{\Glsentryshortpl{#1}}

```

```

\newcommand*{\GLSaccessshortpl}[1]{%
  \protect\mfirstucMakeUppercase{\glstentryshortpl{#1}}
\newcommand*{\glSaccesslong}[1]{\glstentrylong{#1}}
\newcommand*{\Glsaccesslong}[1]{\glstentrylong{#1}}
\newcommand*{\GLSaccesslong}[1]{%
  \protect\mfirstucMakeUppercase{\glstentrylong{#1}}
\newcommand*{\glSaccesslongpl}[1]{\glstentrylongpl{#1}}
\newcommand*{\Glsaccesslongpl}[1]{\glstentrylongpl{#1}}
\newcommand*{\GLSaccesslongpl}[1]{%
  \protect\mfirstucMakeUppercase{\glstentrylongpl{#1}}
\newcommand*{\@gls@initaccesskeys}{%
\newcommand{\@gls@setup@default@access}{%
\newcommand*{\glSxtrAccSuppAbbrSetNoLongAttrs}[1]{%
\newcommand*{\glSxtrAccSuppAbbrSetFirstLongAttrs}[1]{%
\newcommand*{\glSxtrAccSuppAbbrSetTextShortAttrs}[1]{%
\newcommand*{\glSxtrAccSuppAbbrSetNameShortAttrs}[1]{%
\newcommand*{\glSxtrAccSuppAbbrSetNameLongAttrs}[1]{%
}
\glsaddstoragekey{category}{general}{\glscategory}
\newcommand{\glSifcategory}[4]{%
  \ifglSfieldeq{#1}{category}{#2}{#3}{#4}%
}
\newcommand*{\glSsetcategoryattribute}[3]{%
  \csdef{@glSxtr@categoryattr@#1@#2}{#3}%
}
\newcommand*{\glSsetcategoriesattribute}[3]{%
  \@for\@gls@thiscatlabel:=#1\do{%
    \csgdef{@glSxtr@categoryattr@#1@#2@#3}{#3}%
  }%
}
\newcommand*{\glSsetcategoriesattributes}[3]{%
  {%
    \@for\@gls@thisattrlabel:=#2\do{%
      \glSsetcategoriesattribute{#1}{\@gls@thisattrlabel}{#3}%
    }%
  }%
}
\newcommand*{\glSgetcategoryattribute}[2]{%
  \csuse{@glSxtr@categoryattr@#1@#2}%
}
\newcommand*{\glSunsetcategoryattribute}[2]{%
  \csundef{@glSxtr@categoryattr@#1@#2}%
}
\newcommand*{\glShascategoryattribute}[4]{%
  \ifcvoid{@glSxtr@categoryattr@#1@#2}{#4}{#3}%
}
\newcommand*{\glSsetattribute}[3]{%
  \glSsetcategoryattribute{\glscategory{#1}}{#2}{#3}%
}
\newcommand*{\glSgetattribute}[2]{%

```

```

\glsgetcategoryattribute{\glscategory{#1}}{#2}%
}
\newcommand*{\glshasattribute}[4]{%
  \ifglentryexists{#1}%
  {\glshascategoryattribute{\glscategory{#1}}{#2}{#3}{#4}}%
  {#4}%
}
\newcommand{\glsifcategoryattribute}[5]{%
  \ifcsundef{@glsextr@categoryattr@@#1@#2}%
  {#5}%
  {\ifcsstring{@glsextr@categoryattr@@#1@#2}{#3}{#4}{#5}}%
}
\newcommand{\glsifattribute}[5]{%
  \ifglentryexists{#1}%
  {\glsifcategoryattribute{\glscategory{#1}}{#2}{#3}{#4}{#5}}%
  {#5}%
}
\glssetcategoryattribute{general}{regular}{true}
\glssetcategoryattribute{acronym}{regular}{true}
\newcommand*{\glssetregularcategory}[1]{%
  \glssetcategoryattribute{#1}{regular}{true}%
}
\newcommand{\glsifregularcategory}[3]{%
  \glsifcategoryattribute{#1}{regular}{true}{#2}{#3}%
}
\newcommand{\glsifnotregularcategory}[3]{%
  \glsifcategoryattribute{#1}{regular}{false}{#2}{#3}%
}
\newcommand{\glsifregular}[3]{%
  \glsifregularcategory{\glscategory{#1}}{#2}{#3}%
}
\newcommand{\glsifnotregular}[3]{%
  \glsifnotregularcategory{\glscategory{#1}}{#2}{#3}%
}
\newcommand{\glsforeachincategory}[5][\@glo@types]{%
  \foralllglossaries[#1]{#3}%
  {%
    \forallglentries[#3]{#4}%
    {%
      \glsifcategory{#4}{#2}{#5}{}%
    }%
  }%
}
\newcommand{\glsforeachwithattribute}[6][\@glo@types]{%
  \foralllglossaries[#1]{#4}%
  {%
    \forallglentries[#4]{#5}%
    {%
      \glsifattribute{#5}{#2}{#3}{#6}{}%
    }%
  }%
}

```

```

    }%
}
\ifdef\newterm
{%
  \renewcommand*\newterm}[2] [] {%
    \newglossaryentry{#2}%
      {type={index},category=index,name={#2},%
        description={\glstrpostdescription\nopostdesc},#1}%
  }
  \glsssetcategoryattribute{index}{regular}{true}
  \newcommand*\glstrpostdescindex{}
}
{}
\ifdef\printsymbols
{%
  \newcommand*\glstrnewsymbol}[3] [] {%
    \newglossaryentry{#2}{name={#3},sort={#2},type=symbols,category=symbol,#1}%
  }
  \glsssetcategoryattribute{symbol}{regular}{true}
  \newcommand*\glstrpostdescsymbol{}
}
{}
\ifdef\printnumbers
{%
\ifdef\printnumbers
  \newcommand*\glstrnewnumber}[3] [] {%
    \newglossaryentry{#2}{name={#3},sort={#2},type=numbers,category=number,#1}%
  }
  \glsssetcategoryattribute{number}{regular}{true}
  \newcommand*\glstrpostdescnumber{}
}
{}
\newcommand*\glstrsetcategory}[2] {%
  \@for\glstr@label:=#1\do
  {%
    \glsfieldxdef{\glstr@label}{category}{#2}%
  }%
}
\newcommand*\glstrsetcategoryforall}[2] {%
  \forallglossaries[#1]{\glstr@type}{%
    \forglsentries[\glstr@type]{\glstr@label}%
    {%
      \glsfieldxdef{\glstr@label}{category}{#2}%
    }%
  }%
}
\newcommand*\glstrfieldtitlecase}[2] {%
  \expandafter\glstrfieldtitlecasecs\expandafter
    {\csname glo@glsetoklabel{#1}@#2\endcsname}%
}

```

```

\ifdef\glscapitalisewords
{
  \newcommand*\glstrfieldtitlecasecs}[1]{%
    \expandafter\glscapitalisewords\expandafter{#1}}
}
{
  \newcommand*\glstrfieldtitlecasecs}[1]{\xcapitalisewords{#1}}
}
\@ifpackageloaded{glossaries-accsupp}
{
  \renewcommand*\glossentrydesc}[1]{%
    \glsoifexistsorwarn{#1}%
    {%
      \glsetabbrvfmt{\glscategory{#1}}%
      \glshasattribute{#1}{glossdescfont}%
      {%
        \protected@edef\@glstr@attrval{\glsetattribute{#1}{glossdescfont}}%
        \ifcsdef{\@glstr@attrval}%
        {%
          \letcs{\@glstr@glossdescfont}{\@glstr@attrval}%
        }%
        {%
          \GlossariesExtraWarning{Unknown control sequence name
            '@glstr@attrval' supplied in glossdescfont attribute
            for entry '#1'. Ignoring}%
          \let\@glstr@glossdescfont\@firstofone
        }%
      }%
    }%
    {\let\@glstr@glossdescfont\@firstofone}%
    \gl@ifattribute{#1}{glossdesc}{firstuc}%
    {%
      \@glstr@glossdescfont{\Glsaccessdesc{#1}}%
    }%
    {%
      \gl@ifattribute{#1}{glossdesc}{title}%
      {%
        \@glstr@do@titlecaps@warn
        \glsdescriptionaccessdisplay
        {%
          \@glstr@glossdescfont{\glstrfieldtitlecase{#1}{desc}}%
        }%
        {#1}%
      }%
    }%
    {\@glstr@glossdescfont{\Glsaccessdesc{#1}}%
    }%
  }%
}
}

```

```

{
  \renewcommand*{\glossentrydesc}[1]{%
    \glsdoifexistsorwarn{#1}%
    {%
      \glssetabbrvfmt{\glscategory{#1}}%
      \glshasattribute{#1}{glossdescfont}%
      {%
        \protected@edef\@glxtr@attrval{\glsgetattribute{#1}{glossdescfont}}%
        \ifcsdef{\@glxtr@attrval}%
        {%
          \letcs{\@glxtr@glossdescfont}{\@glxtr@attrval}%
        }%
        {%
          \GlossariesExtraWarning{Unknown control sequence name
            '\@glxtr@attrval' supplied in glossdescfont attribute
            for entry '#1'. Ignoring}%
          \let\@glxtr@glossdescfont\@firstofone
        }%
      }%
      {\let\@glxtr@glossdescfont\@firstofone}%
      \glsifattribute{#1}{glossdesc}{firstuc}%
      {%
        \@glxtr@glossdescfont{\Glsentrydesc{#1}}%
      }%
      {%
        \glsifattribute{#1}{glossdesc}{title}%
        {%
          \@glxtr@do@titlecaps@warn
          \@glxtr@glossdescfont{\glxtrfieldtitlecase{#1}{desc}}%
        }%
        {%
          \@glxtr@glossdescfont{\glsentrydesc{#1}}%
        }%
      }%
    }%
  }
}

\@ifpackageloaded{glossaries-accsupp}
{
  \renewcommand*{\glossentryname}[1]{%
    \@glsdoifexistsorwarn{#1}%
    {%
      \glssetabbrvfmt{\glscategory{#1}}%
      \glshasattribute{#1}{glossnamefont}%
      {%
        \protected@edef\@glxtr@attrval{\glsgetattribute{#1}{glossnamefont}}%
        \ifcsdef{\@glxtr@attrval}%
        {%
          \letcs{\@glxtr@glossnamefont}{\@glxtr@attrval}%
        }%
      }%
    }
  }
}

```

```

    {%
      \GlossariesExtraWarning{Unknown control sequence name
        '\@glsxtr@attrval' supplied in glossnamefont attribute
        for entry '#1'. Reverting to default \string\glsnamefont}%
      \let\@glsxtr@glossnamefont\glsnamefont
    }%
  }%
  {\let\@glsxtr@glossnamefont\glsnamefont}%
  \glsifattribute{#1}{glossname}{firstuc}%
  {%
    \glsnameaccessdisplay
    {%
      \@glsxtr@glossnamefont{\Glsentryname{#1}}%
    }%
    {#1}%
  }%
  {%
    \glsifattribute{#1}{glossname}{title}%
    {%
      \@glsxtr@do@titlecaps@warn
      \glsnameaccessdisplay
      {%
        \@glsxtr@glossnamefont{\glsxtrfieldtitlecase{#1}{name}}%
      }%
      {#1}%
    }%
    {%
      \glsifattribute{#1}{glossname}{uc}%
      {%
        \glsnameaccessdisplay
        {%
          \letcs{\glo@name}{glo@\glsdetoklabel{#1}@name}%
          \@glsxtr@glossnamefont{\mfirstucMakeUppercase{\glo@name}}%
        }%
        {#1}%
      }%
      {%
        \letcs{\glo@name}{glo@\glsdetoklabel{#1}@name}%
        \glsnameaccessdisplay
        {%
          \expandafter\@glsxtr@glossnamefont\expandafter{\glo@name}%
        }%
        {#1}%
      }%
    }%
  }%
  \glsxtrpostnamehook{#1}%
}%
}
}

```

```

{
  \renewcommand*{\glossentryname}[1]{%
    \@glsdoifexistsorwarn{#1}%
    {%
      \glsetabbrvfmt{\glscategory{#1}}%
      \glshasattribute{#1}{glossnamefont}%
      {%
        \protected@edef\@glxtr@attrval{\glsetattribute{#1}{glossnamefont}}%
        \ifcsdef{\@glxtr@attrval}%
        {%
          \letcs{\@glxtr@glossnamefont}{\@glxtr@attrval}%
        }%
        {%
          \GlossariesExtraWarning{Unknown control sequence name
            '\@glxtr@attrval' supplied in glossnamefont attribute
            for entry '#1'. Reverting to default \string\glsnamefont}%
          \let\@glxtr@glossnamefont\glsnamefont
        }%
      }%
      {\let\@glxtr@glossnamefont\glsnamefont}%
      \glsifattribute{#1}{glossname}{firstuc}%
      {%
        \@glxtr@glossnamefont{\Glsentryname{#1}}%
      }%
      {%
        \glsifattribute{#1}{glossname}{title}%
        {%
          \@glxtr@do@titlecaps@warn
          \@glxtr@glossnamefont{\glxtrfieldtitlecase{#1}{name}}%
        }%
        {%
          \glsifattribute{#1}{glossname}{uc}%
          {%
            \letcs{\glo@name}{glo@\glsetoklabel{#1}@name}%
            \@glxtr@glossnamefont{\mfirstucMakeUppercase{\glo@name}}%
          }%
          {%
            \letcs{\glo@name}{glo@\glsetoklabel{#1}@name}%
            \expandafter\@glxtr@glossnamefont\expandafter{\glo@name}%
          }%
        }%
      }%
      \glxtrpostnamehook{#1}%
    }%
  }
}
\@ifpackageloaded{glossaries-accsupp}
{
  \renewcommand*{\Glossentryname}[1]{%
    \@glsdoifexistsorwarn{#1}%

```



```

{
  {
    {
      \glsetabbrvfmt{\glscategory{#1}}%
      \glshasattribute{#1}{glossnamefont}%
    }
    {
      \protected@edef\@glxtr@attrval{\glsggetattribute{#1}{glossnamefont}}%
      \ifcsdef{\@glxtr@attrval}%
      {
        \letcs{\@glxtr@glossnamefont}{\@glxtr@attrval}%
      }
    }
    {
      \GlossariesExtraWarning{Unknown control sequence name
        '\@glxtr@attrval' supplied in glossnamefont attribute
        for entry '#1'. Reverting to default \string\glsgnamefont}%
      \let\@glxtr@glossnamefont\glsgnamefont
    }
  }
  {\let\@glxtr@glossnamefont\glsgnamefont}%
  \glsgnameaccessdisplay
  {
    \@glxtr@glossnamefont{\Glsentryname{#1}}%
  }
  {#1}%
  \glxtrpostnamehook{#1}%
}
}
{
  \renewcommand*{\Glsentryname}[1]{
    {
      \glsgdoifexistsorwarn{#1}%
    }
    {
      \glsetabbrvfmt{\glscategory{#1}}%
      \glshasattribute{#1}{glossnamefont}%
    }
    {
      \protected@edef\@glxtr@attrval{\glsggetattribute{#1}{glossnamefont}}%
      \ifcsdef{\@glxtr@attrval}%
      {
        \letcs{\@glxtr@glossnamefont}{\@glxtr@attrval}%
      }
    }
    {
      \GlossariesExtraWarning{Unknown control sequence name
        '\@glxtr@attrval' supplied in glossnamefont attribute
        for entry '#1'. Reverting to default \string\glsgnamefont}%
      \let\@glxtr@glossnamefont\glsgnamefont
    }
  }
  {\let\@glxtr@glossnamefont\glsgnamefont}%
  \@glxtr@glossnamefont{\Glsentryname{#1}}%
  \glxtrpostnamehook{#1}%
}
}

```

```

}
\newcommand*{\glxstrpostnamehook}[1]{%
  \let\@glsnumberformat\@glxstr@defaultnumberformat
  \glxstrdoautoindexname{#1}{indexname}%
  \glsextrapostnamehook{#1}%
  \csuse{glxstrpostname\glscategory{#1}}%
}
\newcommand*{\glsextrapostnamehook}[1]{}%
\newcommand*{\glstdefpostname}[2]{%
  \csdef{glxstrpostname#1}{#2}%
}
\@ifpackageloaded{glossaries-accsupp}
{
  \newcommand*{\glxstr@setaccessdisplay}[1]{%
    \ifcsdef{gls#1accessdisplay}%
    {\letcs\@glxstr@accessdisplay{gls#1accessdisplay}}%
    {%
      \protected@edef\@gls@thisval{#1}%
      \@for\@gls@map:=\@gls@keymap\do{%
        \protected@edef\@this@key{\expandafter\@secondoftwo\@gls@map}%
        \ifdefequal{\@this@key}{\@gls@thisval}%
        {%
          \protected@edef\@gls@thisval{\expandafter\@firstoftwo\@gls@map}%
          \@endfortrue
        }%
      }%
    }%
    \ifcsdef{gls\@gls@thisval accessdisplay}%
    {\letcs\@glxstr@accessdisplay{gls\@gls@thisval accessdisplay}}%
    {\let\@glxstr@accessdisplay\@firstoftwo}%
  }%
}
}
{%
  \newcommand*{\glxstr@setaccessdisplay}[1]{%
    \let\@glxstr@accessdisplay\@firstoftwo
  }
}
\newrobustcmd*{\glossentrynameother}[2]{%
  \@glsdoifexistsorwarn{#1}%
  {%
    \glxstr@setaccessdisplay{#2}%
    \glssetabbrvfmt{\glscategory{#1}}%
    \glshasattribute{#1}{glossnamefont}%
    {%
      \protected@edef\@glxstr@attrval{\glsggetattribute{#1}{glossnamefont}}%
      \ifcsdef{\@glxstr@attrval}%
      {%
        \letcs{\@glxstr@glossnamefont}{\@glxstr@attrval}%
      }%
    }%
  }%
}

```

```

\GlossariesExtraWarning{Unknown control sequence name
'\@glsxtr@attrval' supplied in glossnamefont attribute
for entry '#1'. Reverting to default \string\glsnamefont}%
\let\@glsxtr@glossnamefont\glsnamefont
}%
}%
{\let\@glsxtr@glossnamefont\glsnamefont}%
\glsifattribute{#1}{glossname}{firstuc}%
{%
\@glsxtr@accessdisplay
{\@glsxtr@glossnamefont{\@Gls@entry@field{#1}{#2}}}%
{#1}%
}%
{%
\glsifattribute{#1}{glossname}{title}%
{%
\@glsxtr@do@titlecaps@warn
\@glsxtr@accessdisplay
{\@glsxtr@glossnamefont{\glsxtrfieldtitlecase{#1}{#2}}}%
{#1}%
}%
{%
\glsifattribute{#1}{glossname}{uc}%
{%
\letcs{\glo@name}{glo@\glsdetoklabel{#1}@#2}%
\@glsxtr@accessdisplay
{\@glsxtr@glossnamefont{\mfirstucMakeUppercase{\glo@name}}}%
{#1}%
}%
{%
\letcs{\glo@name}{glo@\glsdetoklabel{#1}@#2}%
\@glsxtr@accessdisplay
{\expandafter\@glsxtr@glossnamefont\expandafter{\glo@name}}%
{#1}%
}%
}%
}%
\glsxtrpostnamehook{#1}%
}%
}
\newif\if@glsxtr@format@override
\@glsxtr@format@overridefalse
\@ifpackageloaded{hyperref}
{
\ifHy@hyperindex
\newcommand*{\GlsXtrEnableIndexFormatOverride}{%
\@glsxtr@format@overridetrue
\appto\theindex{\let\glsnumber\@firstofone}%
}
}
\else

```

```

\newcommand*{\GlsXtrEnableIndexFormatOverride}{%
  \@glsxtr@format@overridetrue
  \appto\theindex{\let\glsnumber\hyperpage}%
}
\fi
}
{
\newcommand*{\GlsXtrEnableIndexFormatOverride}{%
  \@glsxtr@format@overridetrue
}
}
\@onlypreamble\GlsXtrEnableIndexFormatOverride
\newcommand*{\glsxtrdoautoindexname}[2]{%
  \glsattribute{#1}{#2}%
  {%
    \@glsxtr@autoindex@setname{#1}%
    \protected@edef\@glsxtr@attrval{\glsgetattribute{#1}{#2}}%
    \if@glsxtr@format@override
      \ifx\@glsnumberformat\@glsxtr@defaultnumberformat
        \else
          \let\@glsxtr@attrval\@glsnumberformat
        \fi
      \fi
    \ifdefstring{\@glsxtr@attrval}{true}%
    {}%
    {\protected@eappto\@glo@name{\@glsxtr@autoindex@encap\@glsxtr@attrval}}%
    \expandafter\glsxtrautoindex\expandafter{\@glo@name}%
  }%
  {}%
}
\newcommand*{\glsxtrautoindex}{\index}
\newcommand*{\glsxtrautoindexesc}{%
  \@gls@checkmkidxchars\@glo@sort
  \@glsxtr@autoindex@doextra@esc\@glo@sort
}
\newcommand*{\@glsxtr@autoindex@setname}[1]{%
  \protected@edef\@glo@name{\glsxtrautoindexentry{#1}}%
  \glsxtrautoindexassignsort{\@glo@sort}{#1}%
  \glsxtrautoindexesc
  \epreto\@glo@name{\@glo@sort\@glsxtr@autoindex@at}%
}
\newcommand*{\glsxtrautoindexentry}[1]{\string\glsentryname{#1}}
\newcommand*{\glsxtrautoindexassignsort}[2]{%
  \glsletentryfield{#1}{#2}{sort}%
}
\newcommand*{\@glsxtr@autoindex@doextra@esc}[1]{%
  \ifx\@glsxtr@autoindex@esc\@gls@quotechar
  \else
    \def\@gls@checkedmkidx{%
    \edef\@glsxtr@checkspch{%

```

```

\noexpand\@glsxtr@autoindex@escquote\expandonce{#1}%
\noexpand\@empty\@glsxtr@autoindex@esc\noexpand\@nnil
\@glsxtr@autoindex@esc\noexpand\@empty\noexpand\@glsxtr@endescspch}%
\@glsxtr@checkspch
\let#1\@gls@checkedmkidx\relax
\fi
\ifx\@glsxtr@autoindex@at\@gls@actualchar
\else
\def\@gls@checkedmkidx{}%
\edef\@glsxtr@checkspch{%
\noexpand\@glsxtr@autoindex@escat\expandonce{#1}%
\noexpand\@empty\@glsxtr@autoindex@at\noexpand\@nnil
\@glsxtr@autoindex@at\noexpand\@empty\noexpand\@glsxtr@endescspch}%
\@glsxtr@checkspch
\let#1\@gls@checkedmkidx\relax
\fi
\ifx\@glsxtr@autoindex@level\@gls@levelchar
\else
\def\@gls@checkedmkidx{}%
\edef\@glsxtr@checkspch{%
\noexpand\@glsxtr@autoindex@esclevel\expandonce{#1}%
\noexpand\@empty\@glsxtr@autoindex@level\noexpand\@nnil
\@glsxtr@autoindex@level\noexpand\@empty\noexpand\@glsxtr@endescspch}%
\@glsxtr@checkspch
\let#1\@gls@checkedmkidx\relax
\fi
\ifx\@glsxtr@autoindex@encap\@gls@encapchar
\else
\def\@gls@checkedmkidx{}%
\edef\@glsxtr@checkspch{%
\noexpand\@glsxtr@autoindex@escencap\expandonce{#1}%
\noexpand\@empty\@glsxtr@autoindex@encap\noexpand\@nnil
\@glsxtr@autoindex@encap\noexpand\@empty\noexpand\@glsxtr@endescspch}%
\@glsxtr@checkspch
\let#1\@gls@checkedmkidx\relax
\fi
}
\newcommand*{\@glsxtr@autoindex@at}{%
\newcommand*{\GlsXtrSetActualChar}[1]{%
\gdef\@glsxtr@autoindex@at{#1}%
\def\@glsxtr@autoindex@escat##1##2##3\@glsxtr@endescspch{%
\@glsxtr@autoindex@escspch{#1}{\@glsxtr@autoindex@escat}{##1}{##2}{##3}%
}%
}
\@onlypreamble\GlsXtrSetActualChar
\makeatother
\GlsXtrSetActualChar{@}
\makeatletter
\newcommand*{\@glsxtr@autoindex@encap}{%
\newcommand*{\GlsXtrSetEncapChar}[1]{%

```

```

\gdef\@glsxtr@autoindex@encap{#1}%
\def\@glsxtr@autoindex@escencap##1#1##2#1##3\@glsxtr@endescspch{%
  \@glsxtr@autoindex@escspch{#1}{\@glsxtr@autoindex@escencap}{##1}{##2}{##3}%
}%
}
\GlsXtrSetEncapChar{||}
\@onlypreamble\GlsXtrSetEncapChar
\newcommand*{\@glsxtr@autoindex@level}{%
\newcommand*{\GlsXtrSetLevelChar}[1]{%
  \gdef\@glsxtr@autoindex@level{#1}%
  \def\@glsxtr@autoindex@esclevel##1#1##2#1##3\@glsxtr@endescspch{%
    \@glsxtr@autoindex@escspch{#1}{\@glsxtr@autoindex@esclevel}{##1}{##2}{##3}%
  }%
}
\GlsXtrSetLevelChar{!}
\@onlypreamble\GlsXtrSetLevelChar
\newcommand*{\@glsxtr@autoindex@esc}{"}
\newcommand*{\GlsXtrSetEscChar}[1]{%
  \gdef\@glsxtr@autoindex@esc{#1}%
  \def\@glsxtr@autoindex@escquote##1#1##2#1##3\@glsxtr@endescspch{%
    \@glsxtr@autoindex@escspch{#1}{\@glsxtr@autoindex@escquote}{##1}{##2}{##3}%
  }%
}
\GlsXtrSetEscChar{"}
\@onlypreamble\GlsXtrSetEscChar
\ifdef\actualchar
{\expandafter\GlsXtrSetActualChar\expandafter{\actualchar}}
{}
\ifdef\quotechar
{\expandafter\GlsXtrSetEscChar\expandafter{\quotechar}}
{}
\ifdef\levelchar
{\expandafter\GlsXtrSetLevelChar\expandafter{\levelchar}}
{}
\ifdef\encapchar
{\expandafter\GlsXtrSetEncapChar\expandafter{\encapchar}}
{}
\def\@glsxtr@gobbleto@endescspch#1\@glsxtr@endescspch{}
\newcommand*{\@glsxtr@autoindex@escspch}[5]{%
  \@gls@tmpb=\expandafter{\@gls@checkedmkidx}%
  \toks@={#3}%
  \ifx\@nnil#3\relax
    \def\@glsxtr@checkspch{\@glsxtr@gobbleto@endescspch#5\@glsxtr@endescspch}%
  \else
    \ifx\@nnil#4\relax
      \edef\@gls@checkedmkidx{\the\@gls@tmpb\the\toks@}%
      \def\@glsxtr@checkspch{\@glsxtr@gobbleto@endescspch
        #4#5\@glsxtr@endescspch}%
    \else
      \edef\@gls@checkedmkidx{\the\@gls@tmpb\the\toks@

```

```

        \@glxtr@autoindex@esc#1}%
        \def\@@glxtr@checkspch{#2#5#1\@nnil#1\@glxtr@endescspch}%
    \fi
\fi
\@@glxtr@checkspch
}
\renewcommand*{\Glossentrydesc}[1]{%
    \glsdoifexistsorwarn{#1}%
    {%
        \glssetabbrvfmt{\glscategory{#1}}%
        \Glsaccessdesc{#1}%
    }%
}
\ifdef\texorpdfstring
{
    \renewcommand*{\glossentrysymbol}[1]{%
        \texorpdfstring{\@glossentrysymbol{#1}}{\glstentrypdfsymbol{#1}}%
    }
}
{
    \renewcommand*{\glossentrysymbol}[1]{\@glossentrysymbol{#1}}
}
\newcommand{\glstentrypdfsymbol}[1]{\glstentrysymbol{#1}}
\newrobustcmd*{\@glossentrysymbol}[1]{%
    \glsdoifexistsorwarn{#1}%
    {%
        \begingroup
            \glssetabbrvfmt{\glscategory{#1}}%
            \glshasattribute{#1}{glosssymbolfont}%
            {%
                \protected@edef\@glxtr@attrval{\glsggetattribute{#1}{glosssymbolfont}}%
                \ifcsdef{\@glxtr@attrval}%
                {%
                    \letcs{\@glxtr@glosssymbolfont}{\@glxtr@attrval}%
                }%
                {%
                    \GlossariesExtraWarning{Unknown control sequence name
                        '\@glxtr@attrval' supplied in glosssymbolfont attribute
                        for entry '#1'. Ignoring}%
                    \let\@glxtr@glosssymbolfont\@firstofone
                }%
            }%
            {\let\@glxtr@glosssymbolfont\@firstofone}%
            \@glxtr@glosssymbolfont{\glsaccesssymbol{#1}}%
        \endgroup
    }%
}
\renewcommand*{\Glossentrysymbol}[1]{%
    \glsdoifexistsorwarn{#1}%
    {%

```

```

        \glsssetabbrvfmt{\glscategory{#1}}%
        \Glsaccesssymbol{#1}%
    }%
}
\newcommand*{\GlsXtrEnableInitialTagging}{%
    \ifstar\s@glsxtr@enabletagging\@glsxtr@enabletagging
}
\@onlypreamble\GlsXtrEnableInitialTagging
\newcommand*{\s@glsxtr@enabletagging}[2]{%
    \undef#2%
    \@glsxtr@enabletagging{#1}{#2}%
}
\newcommand*{\@glsxtr@enabletagging}[2]{%
    \@for\@glsxtr@cat:=#1\do
    {%
        \ifdefempty\@glsxtr@cat
        {%
            {\glsssetcategoryattribute{\@glsxtr@cat}{tagging}{true}}%
        }%
        \newrobustcmd*#2[1]{##1}%
        \def\@glsxtr@taggingcs{#2}%
        \renewcommand*\@glsxtr@activate@initialtagging{%
            \let#2\@glsxtr@tag
        }%
        \ifundef\@glspreglossaryhook
        {\GlossariesExtraWarning{Initial tagging requires at least
            glossaries.sty v4.19 to work correctly}}%
        {}%
    }
}
\ifundef\mfu@checkword@do
{
    \newcommand*{\mfu@checkword@do}[1]{%
        \ifdefstring{\mfu@checkword@arg}{#1}%
        {%
            \let\@mfu@domakefirstuc\@firstofone
            \listbreak
        }%
        {}%
    }
}
\ifundef\mfu@checkword
{
    \newcommand{\@glsxtr@do@titlecaps@warn}{%
        \GlossariesExtraWarning{mfistuc.sty too old. Title Caps
            support not available}%
        \let\@glsxtr@do@titlecaps@warn\relax
    }
}
{
    \renewcommand*{\mfu@checkword}[1]{%
        \def\mfu@checkword@arg{#1}%
    }
}

```



```

        \let\@mfu@domakefirstuc\makefirstuc
        \forlistloop\mfu@checkword@do\@mfu@nocaplist
    }
}
{}% no patch required
\newcommand*\@glstr@do@titlecaps@warn{}
\newcommand*\@glstr@activate@initialtagging{}
\newrobustcmd*\@glstr@tag}[1]{%
    \gl@ifattribute{\glcurrententrylabel}{tagging}{true}%
    {\glstrtagfont{#1}}{#1}%
}
\newcommand*\glstrtagfont}[1]{\underline{#1}}
\ifdef\@gls@preglossaryhook
{
    \renewcommand*\@gls@preglossaryhook{%
        \@glstr@activate@initialtagging
        \ifundef\@glstr@org@postdescription
        {%
            \let\@glstr@org@postdescription\glspostdescription
            \renewcommand*\glspostdescription{%
                \ifglentryexists{\glcurrententrylabel}%
                {%
                    \glstrpostdescription
                    \@glstr@org@postdescription
                }%
            }%
        }%
    }%
    {}%
    \glossxtrsetpopts
}%
}
{}
\newcommand*\glstrpostdescription{%
    \csuse{glstrpostdesc\glscategory{\glcurrententrylabel}}%
}
\newcommand*\glstrpostdescgeneral{}
\newcommand*\glstrpostdescstern{}
\newcommand*\glstrpostdescacronym{}
\newcommand*\glstrpostdescabbreviation{}
\newcommand*\glstdefpostdesc}[2]{%
    \csdef{glstrpostdesc#1}{#2}%
}
\renewcommand*\glspostlinkhook{%
    \ifglentryexists{\glslabel}{\glstrpostlinkhook}{}%
}
\newcommand*\glstrpostlinkhook{%
    \glstrdiscardperiod{\glslabel}%
    {\glstrpostlinkendsentence}%
}

```

```

{\glxtrifcustomdiscardperiod
  {\glxtrifperiod{\glxtrpostlinkendsentence}{\glxtrpostlink}}%
  {\glxtrpostlink}%
}%
}
\newcommand*{\glxtrifcustomdiscardperiod}[2]{#2}
\newcommand*{\glxtrpostlink}{%
  \csuse{\glxtrpostlink\glscategory{\glslabel}}%
}
\newcommand*{\glsdefpostlink}[2]{%
  \ifthenelse{\equal{#1}{}}{%
    {\PackageError{glossaries-extra}
      {Invalid empty category label in \string\glsdefpostlink}{}}%
    {\csdef{\glxtrpostlink#1}{#2}}%
  }
}
\newcommand*{\glxtrpostlinkendsentence}{%
  \ifcsdef{\glxtrpostlink\glscategory{\glslabel}}
  {%
    \csuse{\glxtrpostlink\glscategory{\glslabel}}%
    .\spacefactor\sfcode'\. \relax
  }%
  {%
    \spacefactor\sfcode'\. \relax
  }%
}
}
\newcommand*{\glxtrpostlinkAddDescOnFirstUse}{%
  \glxtrifwasfirstuse{\space\glxtrparen{\glssaccessdesc{\glslabel}}}{}%
}
\newcommand*{\glxtrpostlinkAddSymbolOnFirstUse}{%
  \glxtrifwasfirstuse
  {%
    \ifglshassymbol{\glslabel}%
    {\space\glxtrparen{\glssaccesssymbol{\glslabel}}}%
    {}%
  }%
  {}%
}
}
\newcommand*{\glxtrpostlinkAddSymbolDescOnFirstUse}{%
  \glxtrifwasfirstuse
  {%
    \space\glxtrparen
    {%
      \ifglshassymbol{\glslabel}%
      {\glssaccesssymbol{\glslabel}, }%
      {}%
      \glssaccessdesc{\glslabel}%
    }%
  }%
  {}%
}
}

```

```

\newcommand*{\glxtrdiscardperiod}[3]{%
\glxtrifwasfirstuse
{%
\glusifattribute{#1}{retainfirstuseperiod}{true}%
{#3}%
{%
\glusifattribute{#1}{discardperiod}{true}%
{%
\glusifplural
{%
\glusifattribute{#1}{pluraldiscardperiod}{true}%
{\glxtrifperiod{#2}{#3}}%
{#3}%
}%
{%
\glxtrifperiod{#2}{#3}%
}%
}%
{#3}%
}%
}%
{%
\glusifattribute{#1}{discardperiod}{true}%
{%
\glusifplural
{%
\glusifattribute{#1}{pluraldiscardperiod}{true}%
{\glxtrifperiod{#2}{#3}}%
{#3}%
}%
{%
\glxtrifperiod{#2}{#3}%
}%
}%
{#3}%
}%
}
\newcommand*{\glxtrifperiod}[1]{\new@ifnextchar.{\@firstoftwo{#1}}}
\newcommand*{\glxtr@punclist}{.,;?!}
\newcommand*{\glxtraddpunctuationmark}[1]{\appto\glxtr@punclist{#1}}
\newcommand*{\glxtrsetpunctuationmarks}[1]{\def\glxtr@punclist{#1}}
\newcommand*{\glxtrifnextpunc}[2]{%
\def\reserved@a{#1}%
\def\reserved@b{#2}%
\futurelet\@glspunc@token\glxtr@ifnextpunc
}
\newcommand*{\glxtr@ifnextpunc}{%
\glxtr@ifpunctoken{\@glspunc@token}{\let\reserved@b\reserved@a}{}%
\reserved@b
}

```

```

\newcommand*{\glstr@ifpunctoken}[1]{%
  \expandafter\@glstr@ifpunctoken\expandafter#1\glstr@punctlist\@nnil
}
\def\@glstr@ifpunctoken#1#2{%
  \let\reserved@d=#2%
  \ifx\reserved@d\@nnil
    \let\glstr@next\@glstr@notfoundinlist
  \else
    \ifx#1\reserved@d
      \let\glstr@next\@glstr@foundinlist
    \else
      \let\glstr@next\@glstr@ifpunctoken
    \fi
  \fi
  \glstr@next#1%
}
\def\@glstr@foundinlist#1\@nnil{\@firstoftwo}
\def\@glstr@notfoundinlist#1{\@secondoftwo}
\newcommand*{\glstr@dopostpunc}[1]{%
  \glstr@ifnextpunc{\@glstr@swaptwo{#1}}{#1}%
}
\newcommand*{\@glstr@swaptwo}[2]{#2#1}
\define@key{glstr@abbrv}{category}{%
  \protected@edef\glscategorylabel{#1}%
}
\define@key{glstr@abbrv}{shortplural}{%
  \def\@glsc@shortpl{#1}%
}
\define@key{glstr@abbrv}{longplural}{%
  \def\@glsc@longpl{#1}%
}
\newtoks\glsshortpltok
\newtoks\glslongpltok
\newcommand*{\@glstr@insertdots}[2]{%
  \def#1{%
    \@glstr@insert@dots#1#2\@nnil
  }
}
\newcommand*{\@glstr@insert@dots}[2]{%
  \ifx\@nnil#2\relax
    \let\@glstr@insert@dots@next\@gobble
  \else
    \ifx\relax#2\relax
      \else
        \appto#1{#2.}%
      \fi
    \let\@glstr@insert@dots@next\@glstr@insert@dots
  \fi
  \@glstr@insert@dots@next#1%
}
\newcommand*{\glstr@wordsep}{\space}

```

```

\newcommand*{\glxtrword}[1]{#1}
\newcommand*{\@glxtr@markwordseps}[2]{%
  \def#1{%
    \@glxtr@mark@wordseps#1#2 \@nnil
  }
\def\@glxtr@mark@wordseps#1#2 #3{%
  \ifdefempty{#1}%
    {\def#1{\protect\glxtrword{#2}}}%
    {\appto#1{\protect\glxtrwordsep\protect\glxtrword{#2}}}%
  \ifx\@nnil#3\relax
    \let\@glxtr@mark@wordseps@next\relax
  \else
    \def\@glxtr@mark@wordseps@next{%
      \@glxtr@mark@wordseps#1#3}%
    \fi
  \@glxtr@mark@wordseps@next
}
\newcommand*{\newabbreviation}[4][[]]{%
  \glxtr@newabbreviation{#1}{#2}{#3}{#4}%
}
\newcommand*{\glxtr@newabbreviation}[4]{%
  \glxtr@keylisttok{#1}%
  \glxtr@labeltok{#2}%
  \glxtr@shorttok{#3}%
  \glxtr@longtok{#4}%
  \def\glxtr@orgshort{#3}%
  \def\glxtr@orglong{#4}%
  \def\ExtraCustomAbbreviationFields{%
    \@glxtr@initaccesskeys
  \def\glxtr@categorylabel{abbreviation}%
  \setkeys*{\glxtr@abbrv}[shortplural,longplural]{#1}%
  \ifcsdef{\glxtr@current@glxtr@categorylabel}%
    {%
      \let\glxtr@orgwarndep\GlsXtrWarnDeprecatedAbbrStyle
      \let\GlsXtrWarnDeprecatedAbbrStyle\@gobbletwo
      \glxtr@applyabbrvstyle{\csname @glxtr@current@glxtr@categorylabel\endcsname}%
      \let\GlsXtrWarnDeprecatedAbbrStyle\@glxtr@orgwarndep
    }%
    {%
      \glxtr@applyabbrvstyle{\@glxtr@current@abbreviation}%
    }%
  \def\@glxtr@longpl{#4\glxtr@longplsuffix}%
  \let\@glxtr@default@longpl\@glxtr@longpl
  \glxtr@ifcategoryattribute{\glxtr@categorylabel}{markwords}{true}%
  {%
    \@glxtr@markwordseps\@glxtr@long{#4}%
    \expandafter\def\expandafter\@glxtr@longpl\expandafter
      {\@glxtr@long\glxtr@longplsuffix}%
    \let\@glxtr@default@longpl\@glxtr@longpl
    \expandafter\glxtr@longtok\expandafter{\@glxtr@long}%
  }%
}

```

```

}%
{}%
\glsifcategoryattribute{\glscategorylabel}{markshortwords}{true}%
{%
  \@glstr@markwordseps\@gls@short{#3}%
}%
{%
  \glsifcategoryattribute{\glscategorylabel}{insertdots}{true}%
  {%
    \@glstr@insertdots\@gls@short{#3}%
    \appto\@gls@short{\@}%
  }%
  {\def\@gls@short{#3}}%
}%
\glsifcategoryattribute{\glscategorylabel}{aposplural}{true}%
{%
  \expandafter\def\expandafter\@gls@shortpl\expandafter{\@gls@short
    '\abrvpluralsuffix}%
}%
{%
  \glsifcategoryattribute{\glscategorylabel}{noshortplural}{true}%
  {%
    \let\@gls@shortpl\@gls@short
  }%
  {%
    \expandafter\def\expandafter\@gls@shortpl\expandafter{\@gls@short
      \abrvpluralsuffix}%
  }%
}%
\expandafter\glsshorttok\expandafter{\@gls@short}%
\glstrnewabbrevpresetkeyhook{#1}{#2}{#3}%
\setkeys*{glstrabbrv}[category]{#1}%
\let\@gls@org@longpl\@gls@longpl
\let\@gls@org@shortpl\@gls@shortpl
\ifx\@gls@default@longpl\@gls@longpl
\else
  \glsifcategoryattribute{\glscategorylabel}{markwords}{true}%
  {%
    \expandafter\@glstr@markwordseps\expandafter\@gls@longpl\expandafter
      {\@gls@longpl}%
  }%
  {}%
\fi
\expandafter\glsshortpltok\expandafter{\@gls@shortpl}%
\expandafter\glslongpltok\expandafter{\@gls@longpl}%
\@gls@setup@default@access
\newabbreviationhook
\protected@edef\@do@newglossaryentry{%
  \noexpand\newglossaryentry{\the\glslabeltok}%
  {%

```

```

        type=\glxtrabbrvtype,%
        category=abbreviation,%
        short={\the\glsshorttok},%
        shortplural={\the\glsshortpltok},%
        long={\the\glslongtok},%
        longplural={\the\glslongpltok},%
        name={\the\glsshorttok},%
        \CustomAbbreviationFields,%
        \ExtraCustomAbbreviationFields
        \the\glskeylisttok
    }%
}%
\@do@newglossaryentry
\@glxtr@addabbreviationlist{\glstrytype{\the\glslabeltok}}%
\GlsXtrPostNewAbbreviation
}
\newcommand*{\glxtrnewabbrevpresetkeyhook}[3]{}
\newcommand*{\GlsXtrPostNewAbbreviation}{}
\newcommand*{\newabbreviationhook}{}
\newcommand*{\CustomAbbreviationFields}{}
\newcommand*{\glxtrparen}[1]{(#1)}
\newcommand*{\glxtrfullformat}[2]{%
    \glsfirstlongfont{\glsaccesslong{#1}}#2\glxtrfullsep{#1}%
    \glxtrparen{\protect\glsfirstabbrvfont{\glsaccessshort{#1}}}%
}
\newcommand*{\Glsxtrfullformat}[2]{%
    \glsfirstlongfont{\Glsaccesslong{#1}}#2\glxtrfullsep{#1}%
    \glxtrparen{\protect\glsfirstabbrvfont{\glsaccessshort{#1}}}%
}
\newcommand*{\glxtrfullplformat}[2]{%
    \glsfirstlongfont{\glsaccesslongpl{#1}}#2\glxtrfullsep{#1}%
    \glxtrparen{\protect\glsfirstabbrvfont{\glsaccessshortpl{#1}}}%
}
\newcommand*{\Glsxtrfullplformat}[2]{%
    \glsfirstlongfont{\Glsaccesslongpl{#1}}#2\glxtrfullsep{#1}%
    \glxtrparen{\protect\glsfirstabbrvfont{\glsaccessshortpl{#1}}}%
}
\newcommand*{\glxtrfullsep}[1]{\space}
\newcommand*{\glxtrinlinefullformat}{\glxtrfullformat}
\newcommand*{\Glsxtrinlinefullformat}{\Glsxtrfullformat}
\newcommand*{\glxtrinlinefullplformat}{\glxtrfullplformat}
\newcommand*{\Glsxtrinlinefullplformat}{\Glsxtrfullplformat}
\renewcommand*{\glstryfull}[1]{\glxtrinlinefullformat{#1}{}}
\renewcommand*{\Glsentryfull}[1]{\Glsxtrinlinefullformat{#1}{}}
\renewcommand*{\glstryfullpl}[1]{\glxtrinlinefullplformat{#1}{}}
\renewcommand*{\Glsentryfullpl}[1]{\Glsxtrinlinefullplformat{#1}{}}
\newcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvdefaultfont{#1}}
\newcommand*{\glsfirstabbrvdefaultfont}[1]{\glsabbrvdefaultfont{#1}}
\newcommand*{\glsabbrvfont}[1]{\glsabbrvdefaultfont{#1}}
\newcommand*{\glsabbrvdefaultfont}[1]{#1}

```

```

\newcommand*\glslongfont}[1]{\glslongdefaultfont{#1}}
\newcommand*\glslongdefaultfont}[1]{#1}
\newcommand*\glsfirstlongfont}[1]{\glslongfont{#1}}
\newcommand*\glsfirstlongdefaultfont}[1]{\glslongdefaultfont{#1}}
\newcommand*\glsxtrabbrvpluralsuffix{\glspluralsuffix}
\newcommand*\abbrvpluralsuffix{\glsxtrabbrvpluralsuffix}
\newrobustcmd*\glsxtrfull{\@gls@hyp@opt\@ns@glsxtrfull}
\newcommand*\ns@glsxtrfull[2][]{\%
  \new@ifnextchar[{\@glsxtr@full{#1}{#2}}{\@glsxtr@full{#1}{#2}[]}%
}
\def\@glsxtr@full#1#2[#3]{\%
  \@glsxtr@record{#1}{#2}{\glslink}%
  \glsdoifexists{#2}%
  {\%
    \glssetabbrvfmt{\glscategory{#2}}%
    \let\do@gls@link@checkfirsthyper\@gls@link@nocheckfirsthyper
    \let\glsifplural\@secondoftwo
    \let\glscapscase\@firstofthree
    \let\glsinsert\@empty
    \def\glscustomtext{\glsxtrinlinefullformat{#2}{#3}}%
    \glsxtrsetupfulldefs
    \@gls@link{#1}{#2}{\csname gls@\gls@type @entryfmt\endcsname}%
  }%
  \glspostlinkhook
}
\newcommand*\glsxtrsetupfulldefs{\%
  \let\glsxtrifwasfirstuse\@firstoftwo
}
\newrobustcmd*\Glsxtrfull{\@gls@hyp@opt\@ns@Glsxtrfull}
\newcommand*\ns@Glsxtrfull[2][]{\%
  \new@ifnextchar[{\@Glsxtr@full{#1}{#2}}{\@Glsxtr@full{#1}{#2}[]}%
}
\def\@Glsxtr@full#1#2[#3]{\%
  \glsdoifexists{#2}%
  {\%
    \glssetabbrvfmt{\glscategory{#2}}%
    \let\do@gls@link@checkfirsthyper\@gls@link@nocheckfirsthyper
    \let\glsifplural\@secondoftwo
    \let\glsapscase\@secondofthree
    \let\glsinsert\@empty
    \def\glscustomtext{\Glsxtrinlinefullformat{#2}{#3}}%
    \glsxtrsetupfulldefs
    \@gls@link{#1}{#2}{\csname gls@\gls@type @entryfmt\endcsname}%
  }%
  \glspostlinkhook
}
\newrobustcmd*\GLSxtrfull{\@gls@hyp@opt\@ns@GLSxtrfull}
\newcommand*\ns@GLSxtrfull[2][]{\%

```



```

\new@ifnextchar[{\@GLSxtr@full{#1}{#2}}%
        {\@GLSxtr@full{#1}{#2}[]}%
}
\def\@GLSxtr@full#1#2[#3]{%
\glsdoifexists{#2}%
{%
\glssetabbrvfmt{\glscategory{#2}}%
\let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
\let\glsifplural\@secondoftwo
\let\glscapscase\@thirdofthree
\let\glsinsert\@empty
\def\glscustomtext{\mfirstucMakeUppercase{\glsxtrinlinefullformat{#2}{#3}}}%
\glsxtrsetupfulldefs
\@gl@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
}%
\glspostlinkhook
}
\newrobustcmd*{\glsxtrfullpl}{\@gl@hyp@opt\ns@glsxtrfullpl}
\newcommand*\ns@glsxtrfullpl[2][]{%
\new@ifnextchar[{\@glsxtr@fullpl{#1}{#2}}%
        {\@glsxtr@fullpl{#1}{#2}[]}%
}
\def\@glsxtr@fullpl#1#2[#3]{%
\@glsxtr@record{#1}{#2}{glslink}%
\glsdoifexists{#2}%
{%
\glssetabbrvfmt{\glscategory{#2}}%
\let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
\let\glsifplural\@firstoftwo
\let\glscapscase\@firstofthree
\let\glsinsert\@empty
\def\glscustomtext{\glsxtrinlinefullplformat{#2}{#3}}%
\glsxtrsetupfulldefs
\@gl@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
}%
\glspostlinkhook
}
\newrobustcmd*{\Glsxtrfullpl}{\@gl@hyp@opt\ns@Glsxtrfullpl}
\newcommand*\ns@Glsxtrfullpl[2][]{%
\new@ifnextchar[{\@Glsxtr@fullpl{#1}{#2}}%
        {\@Glsxtr@fullpl{#1}{#2}[]}%
}
\def\@Glsxtr@fullpl#1#2[#3]{%
\@glsxtr@record{#1}{#2}{glslink}%
\glsdoifexists{#2}%
{%
\glssetabbrvfmt{\glscategory{#2}}%
\let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
\let\glsifplural\@firstoftwo
\let\glscapscase\@secondofthree

```

```

\let\glsinsert\@empty
\def\glscustomtext{\Glsxtrinlinefullplformat{#2}{#3}}%
\glsxtrsetupfulldefs
\@gls@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
}%
\glspostlinkhook
}
\newrobustcmd*{\Glsxtrfullpl}{\@gls@hyp@opt\@ns@Glsxtrfullpl}
\newcommand*\ns@Glsxtrfullpl[2][]{%
\new@ifnextchar[{\@Glsxtr@fullpl{#1}{#2}}%
{\@Glsxtr@fullpl{#1}{#2}[]}%
}
\def\@Glsxtr@fullpl#1#2[#3]{%
\@glsxtr@record{#1}{#2}{glslink}%
\glsdoifexists{#2}%
{%
\let\do@gls@link@checkfirsthyper\@gls@link@nocheckfirsthyper
\let\glsifplural\@firstoftwo
\let\glscapscase\@thirdofthree
\let\glsinsert\@empty
\def\glscustomtext{%
\mfirstucMakeUppercase{\glsxtrinlinefullplformat{#2}{#3}}}%
\glsxtrsetupfulldefs
\@gls@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
}%
\glspostlinkhook
}
\newrobustcmd*{\glsxtrshort}{\@gls@hyp@opt\@ns@glsxtrshort}
\newcommand*\ns@glsxtrshort[2][]{%
\new@ifnextchar[{\@glsxtrshort{#1}{#2}}{\@glsxtrshort{#1}{#2}[]}%
}
\def\@glsxtrshort#1#2[#3]{%
\@glsxtr@record{#1}{#2}{glslink}%
\glsdoifexists{#2}%
{%
\glssetabbrvfmt{\glscategory{#2}}%
\let\do@gls@link@checkfirsthyper\@gls@link@nocheckfirsthyper
\let\glsxtrifwasfirstuse\@secondoftwo
\let\glsifplural\@secondoftwo
\let\glscapscase\@firstofthree
\let\glsinsert\@empty
\def\glscustomtext{%
\glsabbrvfont{\glsaccessshort{#2}\ifglsxtrinsetinside#3\fi}%
\ifglsxtrinsetinside\else#3\fi
}%
\@gls@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
}%
\glspostlinkhook
}
\newrobustcmd*{\Glsxtrshort}{\@gls@hyp@opt\@ns@Glsxtrshort}

```

```

\newcommand*{\ns@Glsxtrshort}[2] [] {%
  \new@ifnextchar[{\@Glsxtrshort{#1}{#2}}{\@Glsxtrshort{#1}{#2} [] }%
}
\def\@Glsxtrshort#1#2[#3]{%
  \@glsxtr@record{#1}{#2}{glslink}%
  \glsdoifexists{#2}%
  {%
    \glssetabbrvfmt{\glscategory{#2}}%
    \let\do@glsl@link@checkfirsthyper\@glsl@link@nocheckfirsthyper
    \let\glsxtrifwasfirsttuse\@secondoftwo
    \let\glsifplural\@secondoftwo
    \let\glscapscase\@secondofthree
    \let\glsinsert\@empty
    \def\glscustomtext{%
      \glsabbrvfont{\Glsaccessshort{#2}}\ifglsxtrininsertinside#3\fi}%
      \ifglsxtrininsertinside\else#3\fi
    }%
    \@glsl@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
  }%
  \glspostlinkhook
}
\newrobustcmd*{\GLSxtrshort}{\@glshyp@opt\ns@GLSxtrshort}
\newcommand*{\ns@GLSxtrshort}[2] [] {%
  \new@ifnextchar[{\@GLSxtrshort{#1}{#2}}{\@GLSxtrshort{#1}{#2} [] }%
}
\def\@GLSxtrshort#1#2[#3]{%
  \@glsxtr@record{#1}{#2}{glslink}%
  \glsdoifexists{#2}%
  {%
    \glssetabbrvfmt{\glscategory{#2}}%
    \let\do@glsl@link@checkfirsthyper\@glsl@link@nocheckfirsthyper
    \let\glsxtrifwasfirsttuse\@secondoftwo
    \let\glsifplural\@secondoftwo
    \let\glscapscase\@thirdofthree
    \let\glsinsert\@empty
    \def\glscustomtext{%
      \mfirstucMakeUppercase
      {\glsabbrvfont{\Glsaccessshort{#2}}\ifglsxtrininsertinside#3\fi}%
      \ifglsxtrininsertinside\else#3\fi
    }%
    }%
    \@glsl@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
  }%
  \glspostlinkhook
}
\newrobustcmd*{\glsxtrlong}{\@glshyp@opt\ns@glsxtrlong}
\newcommand*{\ns@glsxtrlong}[2] [] {%
  \new@ifnextchar[{\@glsxtrlong{#1}{#2}}{\@glsxtrlong{#1}{#2} [] }%
}
\def\@glsxtrlong#1#2[#3]{%

```

```

\@glstr@record{#1}{#2}{glslink}%
\glsdoifexists{#2}%
{%
\let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
\let\glstrifwasfirstuse\@secondoftwo
\let\gl@ifplural\@secondoftwo
\let\glscapscase\@firstofthree
\let\glinsert\@empty
\def\glscustomtext{%
\glslongfont{\glaccesslong{#2}\ifglstrinsertinside#3\fi}%
\ifglstrinsertinside\else#3\fi
}%
\@gl@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
}%
\glspostlinkhook
}
\newrobustcmd*{\Glsxtrlong}{\@gl@hyp@opt\@ns@Glsxtrlong}
\newcommand*{\ns@Glsxtrlong}[2][]{%
\new@ifnextchar[{\@Glsxtrlong{#1}{#2}}{\@Glsxtrlong{#1}{#2}[]}%
}
\def\@Glsxtrlong#1#2[#3]{%
\@glstr@record{#1}{#2}{glslink}%
\glsdoifexists{#2}%
{%
\let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
\let\glstrifwasfirstuse\@secondoftwo
\let\gl@ifplural\@secondoftwo
\let\glscapscase\@secondofthree
\let\glinsert\@empty
\def\glscustomtext{%
\glslongfont{\Glsaccesslong{#2}\ifglstrinsertinside#3\fi}%
\ifglstrinsertinside\else#3\fi
}%
\@gl@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
}%
\glspostlinkhook
}
\newrobustcmd*{\GLSxtrlong}{\@gl@hyp@opt\@ns@GLSxtrlong}
\newcommand*{\ns@GLSxtrlong}[2][]{%
\new@ifnextchar[{\@GLSxtrlong{#1}{#2}}{\@GLSxtrlong{#1}{#2}[]}%
}
\def\@GLSxtrlong#1#2[#3]{%
\@glstr@record{#1}{#2}{glslink}%
\glsdoifexists{#2}%
{%
\let\do@gl@link@checkfirsthyper\@gl@link@nocheckfirsthyper
\let\glstrifwasfirstuse\@secondoftwo
\let\gl@ifplural\@secondoftwo
\let\glscapscase\@thirdofthree
\let\glinsert\@empty

```

```

\def\glscustomtext{%
  \mfirstucMakeUppercase
  {\glslongfont{\glsaccesslong{#2}\ifglxtrinsertinside#3\fi}%
   \ifglxtrinsertinside\else#3\fi
}%
}%
\@gls@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
}%
\glspostlinkhook
}
\newrobustcmd*{\glxtrshortpl}{\@gls@hyp@opt\@ns@glxtrshortpl}
\newcommand*{\ns@glxtrshortpl}[2][]{%
  \new@ifnextchar[{\@glxtrshortpl{#1}{#2}}{\@glxtrshortpl{#1}{#2}[]}%
}
\def\@glxtrshortpl#1#2[#3]{%
  \@glxtr@record{#1}{#2}{glslink}%
  \glsdoifexists{#2}%
  {%
    \glsssetabbrvfmt{\glscategory{#2}}%
    \let\do@gls@link@checkfirsthyper\@gls@link@nocheckfirsthyper
    \let\glxtrifwasfirstuse\@secondoftwo
    \let\glsifplural\@firstoftwo
    \let\glscapscase\@firstofthree
    \let\glsinsert\@empty
    \def\glscustomtext{%
      \glsabbrvfont{\glsaccessshortpl{#2}\ifglxtrinsertinside#3\fi}%
      \ifglxtrinsertinside\else#3\fi
    }%
    \@gls@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
  }%
  \glspostlinkhook
}
\newrobustcmd*{\Glsxtrshortpl}{\@gls@hyp@opt\@ns@Glsxtrshortpl}
\newcommand*{\ns@Glsxtrshortpl}[2][]{%
  \new@ifnextchar[{\@Glsxtrshortpl{#1}{#2}}{\@Glsxtrshortpl{#1}{#2}[]}%
}
\def\@Glsxtrshortpl#1#2[#3]{%
  \@glxtr@record{#1}{#2}{glslink}%
  \glsdoifexists{#2}%
  {%
    \glsssetabbrvfmt{\glscategory{#2}}%
    \let\do@gls@link@checkfirsthyper\@gls@link@nocheckfirsthyper
    \let\glxtrifwasfirstuse\@secondoftwo
    \let\glsifplural\@firstoftwo
    \let\glscapscase\@secondofthree
    \let\glsinsert\@empty
    \def\glscustomtext{%
      \glsabbrvfont{\Glsaccessshortpl{#2}\ifglxtrinsertinside#3\fi}%
      \ifglxtrinsertinside\else#3\fi
    }%
  }%

```

```

    \@gls@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
}%
\glspostlinkhook
}
\newrobustcmd*{\GLSxtrshortpl}{\@gls@hyp@opt\@ns@GLSxtrshortpl}
\newcommand*{\ns@GLSxtrshortpl}[2][{}]{%
  \new@ifnextchar[{\@GLSxtrshortpl{#1}{#2}}{\@GLSxtrshortpl{#1}{#2}[]}%
}
\def\@GLSxtrshortpl#1#2[#3]{%
  \@glsxtr@record{#1}{#2}{glslink}%
  \glsdoifexists{#2}%
  {%
    \glssetabbrvfmt{\glscategory{#2}}%
    \let\do@gls@link@checkfirsthyper\@gls@link@nocheckfirsthyper
    \let\glsxtrifwasfirstuse\@secondoftwo
    \let\glsifplural\@firstoftwo
    \let\gls caps case\@thirdofthree
    \let\glsinsert\@empty
    \def\gls custom text{%
      \mfirstucMakeUppercase
      {\glsabbrvfont{\glsaccessshortpl{#2}}\ifglsxtrininsertinside#3\fi}%
      \ifglsxtrininsertinside\else#3\fi
    }%
  }%
  \@gls@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
}%
\glspostlinkhook
}
\newrobustcmd*{\glsxtrlongpl}{\@gls@hyp@opt\@ns@glsxtrlongpl}
\newcommand*{\ns@glsxtrlongpl}[2][{}]{%
  \new@ifnextchar[{\@glsxtrlongpl{#1}{#2}}{\@glsxtrlongpl{#1}{#2}[]}%
}
\def\@glsxtrlongpl#1#2[#3]{%
  \@glsxtr@record{#1}{#2}{glslink}%
  \glsdoifexists{#2}%
  {%
    \let\do@gls@link@checkfirsthyper\@gls@link@nocheckfirsthyper
    \let\glsxtrifwasfirstuse\@secondoftwo
    \let\glsifplural\@firstoftwo
    \let\gls caps case\@firstofthree
    \let\glsinsert\@empty
    \def\gls custom text{%
      \gls long font{\glsaccesslongpl{#2}}\ifglsxtrininsertinside#3\fi}%
      \ifglsxtrininsertinside\else#3\fi
    }%
  }%
  \@gls@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
}%
\glspostlinkhook
}
\newrobustcmd*{\Glsxtrlongpl}{\@gls@hyp@opt\@ns@Glsxtrlongpl}

```

```

\newcommand*{\ns@Glsxtrlongpl}[2][{}]{%
  \new@ifnextchar[{\@Glsxtrlongpl{#1}{#2}}{\@Glsxtrlongpl{#1}{#2}[]}%
}
\def\@Glsxtrlongpl#1#2[#3]{%
  \@glsxtr@record{#1}{#2}{glslink}%
  \glsdoifexists{#2}%
  {%
    \let\do@gls@link@checkfirsthyper\@gls@link@nocheckfirsthyper
    \let\glsxtrifwasfirstuse\@secondoftwo
    \let\glsifplural\@firstoftwo
    \let\glscapscase\@secondofthree
    \let\glsinsert\@empty
    \def\glscustomtext{%
      \glslongfont{\@glsaccesslongpl{#2}\ifglsxtrininsertinside#3\fi}%
      \ifglsxtrininsertinside\else#3\fi
    }%
    \@gls@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
  }%
  \glspostlinkhook
}
\newrobustcmd*{\GLSxtrlongpl}{\@gls@hyp@opt\ns@GLSxtrlongpl}
\newcommand*{\ns@GLSxtrlongpl}[2][{}]{%
  \new@ifnextchar[{\@GLSxtrlongpl{#1}{#2}}{\@GLSxtrlongpl{#1}{#2}[]}%
}
\def\@GLSxtrlongpl#1#2[#3]{%
  \@glsxtr@record{#1}{#2}{glslink}%
  \glsdoifexists{#2}%
  {%
    \let\do@gls@link@checkfirsthyper\@gls@link@nocheckfirsthyper
    \let\glsxtrifwasfirstuse\@secondoftwo
    \let\glsifplural\@firstoftwo
    \let\glscapscase\@thirdofthree
    \let\glsinsert\@empty
    \def\glscustomtext{%
      \mfirstucMakeUppercase
      {\glslongfont{\@glsaccesslongpl{#2}\ifglsxtrininsertinside#3\fi}%
      \ifglsxtrininsertinside\else#3\fi
    }%
    \@gls@link[#1]{#2}{\csname gls@\glstype @entryfmt\endcsname}%
  }%
  \glspostlinkhook
}
\newcommand*{\glssetabbrvfmt}[1]{%
  \ifcsdef{@glsabbrv@current@#1}%
  {\glsxtr@applyabbrvfmt{\csname @glsabbrv@current@#1\endcsname}}%
  {\glsxtr@applyabbrvfmt{\@glsabbrv@current@abbreviation}}%
}
\newrobustcmd*{\glsuseabbrvfont}[2]{\@glssetabbrvfmt{#2}\glsabbrvfont{#1}}
\newrobustcmd*{\glsuselongfont}[2]{\@glssetabbrvfmt{#2}\glslongfont{#1}}

```

```

\newcommand*{\glxtrgenabbrvfmt}{%
  \ifdefempty\glscustomtext
  {%
    \ifglused\glslabel
    {%
      \glcifplural
      {%
        \glscapscase
        {%
          \glxtrsubsequentplfmt{\glslabel}{\glinsert}%
        }%
        {%
          \Glsxtrsubsequentplfmt{\glslabel}{\glinsert}%
        }%
        {%
          \mfirstucMakeUppercase
            {\glxtrsubsequentplfmt{\glslabel}{\glinsert}}}%
        }%
      }%
    }%
    {%
      \glscapscase
      {%
        \glxtrsubsequentfmt{\glslabel}{\glinsert}%
      }%
      {%
        \Glsxtrsubsequentfmt{\glslabel}{\glinsert}%
      }%
      {%
        \mfirstucMakeUppercase
          {\glxtrsubsequentfmt{\glslabel}{\glinsert}}}%
      }%
    }%
  }%
  {%
    \glcifplural
    {%
      \glscapscase
      {%
        \glxtrfullplformat{\glslabel}{\glinsert}%
      }%
      {%
        \Glsxtrfullplformat{\glslabel}{\glinsert}%
      }%
      {%
        \mfirstucMakeUppercase
          {\glxtrfullplformat{\glslabel}{\glinsert}}}%
      }%
    }%
  }%
  {%
    \glscapscase

```



```

        {%
            \glxtrfullformat{\glslabel}{\glsinsert}%
        }%
        {%
            \Glsxtrfullformat{\glslabel}{\glsinsert}%
        }%
        {%
            \mfirstucMakeUppercase
            {\glxtrfullformat{\glslabel}{\glsinsert}}}%
        }%
    }%
}%
}%
{%
    \glscustomtext
}%
}
\newcommand*{\glxtrs subsequentfmt}[2]{%
    \glsabbrvfont{\glsaccessshort{#1}\ifglxtrininsertinside #2\fi}%
    \ifglxtrininsertinside \else#2\fi
}
\let\glxtrdefaultsubsequentfmt\glxtrs subsequentfmt
\newcommand*{\glxtrs subsequentplfmt}[2]{%
    \glsabbrvfont{\glsaccessshortpl{#1}\ifglxtrininsertinside #2\fi}%
    \ifglxtrininsertinside \else#2\fi
}
\let\glxtrdefaultsubsequentplfmt\glxtrs subsequentplfmt
\newcommand*{\Glsxtrs subsequentfmt}[2]{%
    \glsabbrvfont{\Glsaccessshort{#1}\ifglxtrininsertinside #2\fi}%
    \ifglxtrininsertinside \else#2\fi
}
\let\Glsxtrdefaultsubsequentfmt\Glsxtrs subsequentfmt
\newcommand*{\Glsxtrs subsequentplfmt}[2]{%
    \glsabbrvfont{\Glsaccessshortpl{#1}\ifglxtrininsertinside #2\fi}%
    \ifglxtrininsertinside \else#2\fi
}
\let\Glsxtrdefaultsubsequentplfmt\Glsxtrs subsequentplfmt
\newcommand*{\setabbreviationstyle}[2][abbreviation]{%
    \ifcsundef{@glsabbrv@dispstyle@setup@#2}%
    {%
        \PackageError{glossaries-extra}{Undefined abbreviation style ‘#2’}{}%
    }%
    {%
        \ifcsstring{@glsabbrv@current@#1}{#2}%
        {%
        }%
        {%
            \def\@glxtr@dostylewarn{}%
            \glsforeachincategory{#1}{\@gls@type}{\@gls@label}%
            {%

```

```

\def\@glxtr@dostylewarn{\GlossariesWarning{Abbreviation
  style has been switched \MessageBreak
  for category ‘#1’, \MessageBreak
  but there have already been entries \MessageBreak
  defined for this category. Unwanted \MessageBreak
  side-effects may result}}%
\@endfortrue
}%
\@glxtr@dostylewarn
\csdef{@glxtr@current@#1}{#2}%
\protected@edef\glxtr@categorylabel{#1}%
\glxtr@applyabbrvstyle{#2}%
}%
}%
}
\newcommand*{\glxtr@applyabbrvstyle}[1]{%
  \csuse{@glxtr@dispstyle@setup@#1}%
  \csuse{@glxtr@dispstyle@fmts@#1}%
}
\newcommand*{\glxtr@applyabbrvfnt}[1]{%
  \csuse{@glxtr@dispstyle@fmts@#1}%
}
\newcommand*{\newabbreviationstyle}[3]{%
  \ifcsdef{@glxtr@dispstyle@setup@#1}
  {%
    \PackageError{glossaries-extra}{Abbreviation style ‘#1’ already
      defined}{}%
  }%
  {%
    \csdef{@glxtr@dispstyle@setup@#1}{%
      \renewcommand*{\GlsXtrPostNewAbbreviation}{}%
      #2}%
    \csdef{@glxtr@dispstyle@fmts@#1}{%
      \renewcommand*{\glxtrinlinefullformat}{\glxtrfullformat}%
      \renewcommand*{\Glsxtrinlinefullformat}{\Glsxtrfullformat}%
      \renewcommand*{\glxtrinlinefullplformat}{\glxtrfullplformat}%
      \renewcommand*{\Glsxtrinlinefullplformat}{\Glsxtrfullplformat}%
      \let\glxtrsubsequentfmt\glxtrdefaultsubsequentfmt
      \let\glxtrsubsequentplfmt\glxtrdefaultsubsequentplfmt
      \let\Glsxtrsubsequentfmt\Glsxtrdefaultsubsequentfmt
      \let\Glsxtrsubsequentplfmt\Glsxtrdefaultsubsequentplfmt
      #3}%
    }%
  }
}
\newcommand*{\renewabbreviationstyle}[3]{%
  \ifcsundef{@glxtr@dispstyle@setup@#1}
  {%
    \PackageError{glossaries-extra}{Abbreviation style ‘#1’ not defined}{}%
  }%
  {%

```

```

\csdef{@glsabbrv@dispstyle@setup@#1}{%
\renewcommand*{\GlsXtrPostNewAbbreviation}{}%
#2}%
\csdef{@glsabbrv@dispstyle@fmts@#1}{%
\renewcommand*{\glxtrinlinefullformat}{\glxtrfullformat}%
\renewcommand*{\glxtrinlinefullplformat}{\glxtrfullplformat}%
\renewcommand*{\glxtrinlinefullplformat}{\glxtrfullplformat}%
#3}%
}%
}
\newcommand*{\letabbreviationstyle}[2]{%
\csletcs{@glsabbrv@dispstyle@setup@#1}{@glsabbrv@dispstyle@setup@#2}%
\csletcs{@glsabbrv@dispstyle@fmts@#1}{@glsabbrv@dispstyle@fmts@#2}%
}
\newcommand*{@glsxtr@deprecated@abbrstyle}[2]{%
\csdef{@glsabbrv@dispstyle@setup@#1}{%
\GlsXtrWarnDeprecatedAbbrStyle{#1}{#2}%
\csuse{@glsabbrv@dispstyle@setup@#2}%
}%
\csletcs{@glsabbrv@dispstyle@fmts@#1}{@glsabbrv@dispstyle@fmts@#2}%
}
\newcommand*{\GlsXtrWarnDeprecatedAbbrStyle}[2]{%
\GlossariesExtraWarning{Deprecated abbreviation style name ‘#1’,
use ‘#2’ instead}%
}
\newcommand*{\GlsXtrUseAbbrStyleSetup}[1]{%
\ifcsundef{@glsabbrv@dispstyle@setup@#1}%
{%
\PackageError{glossaries-extra}%
{Unknown abbreviation style definitions ‘#1’}{}%
}%
}%
\csname @glsabbrv@dispstyle@setup@#1\endcsname
}%
}
\newcommand*{\GlsXtrUseAbbrStyleFmts}[1]{%
\ifcsundef{@glsabbrv@dispstyle@fmts@#1}%
{%
\PackageError{glossaries-extra}%
{Unknown abbreviation style formats ‘#1’}{}%
}%
}%
\csname @glsabbrv@dispstyle@fmts@#1\endcsname
}%
}
\newif\ifglxtrininsertinside
\glxtrininsertinsidefalse
\newcommand*{\glxtrlongshortname}{%
\protect\glsabbrvfont{\the\glsshorttok}%

```

```

}
\newabbreviationstyle{long-short}%
{%
  \glstrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glstrlongshortname},
    sort={\the\glsshorttok},
    first={\protect\glstrfirstlongfont{\the\glslongtok}%
      \protect\glstrfullsep{\the\glslabeltok}%
      \glstrparen{\protect\glstrfirstabbrvfont{\the\glsshorttok}}},%
    firstplural={\protect\glstrfirstlongfont{\the\glslongpltok}%
      \protect\glstrfullsep{\the\glslabeltok}%
      \glstrparen{\protect\glstrfirstabbrvfont{\the\glsshortpltok}}},%
    plural={\protect\glstrabbrvfont{\the\glsshortpltok}},%
    text={\protect\glstrabbrvfont{\the\glsshorttok}},%
    description={\the\glslongtok}}%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \glshasattribute{\the\glslabeltok}{regular}%
    {%
      \glsssetattribute{\the\glslabeltok}{regular}{false}%
    }%
  }%
}%
{%
  \renewcommand*{\abbrvpluralsuffix}{\glstrabbrvpluralsuffix}%
  \renewcommand*{\glstrabbrvfont}[1]{\glstrabbrvdefaultfont{##1}}%
  \renewcommand*{\glstrfirstabbrvfont}[1]{\glstrfirstabbrvdefaultfont{##1}}%
  \renewcommand*{\glstrfirstlongfont}[1]{\glstrfirstlongdefaultfont{##1}}%
  \renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%
  \renewcommand*{\glstrfullformat}[2]{%
    \glstrfirstlongfont{\glstraccesslong{##1}\ifglstrinsertinside##2\fi}%
    \ifglstrinsertinside\else##2\fi
    \glstrfullsep{##1}%
    \glstrparen{\glstrfirstabbrvfont{\glstraccessshort{##1}}}%
  }%
  \renewcommand*{\glstrfullplformat}[2]{%
    \glstrfirstlongfont{\glstraccesslongpl{##1}\ifglstrinsertinside##2\fi}%
    \ifglstrinsertinside\else##2\fi\glstrfullsep{##1}%
    \glstrparen{\glstrfirstabbrvfont{\glstraccessshortpl{##1}}}%
  }%
  \renewcommand*{\Glsxtrfullformat}[2]{%
    \glstrfirstlongfont{\glstraccesslong{##1}\ifglstrinsertinside##2\fi}%
    \ifglstrinsertinside\else##2\fi\glstrfullsep{##1}%
    \glstrparen{\glstrfirstabbrvfont{\glstraccessshort{##1}}}%
  }%
  \renewcommand*{\Glsxtrfullplformat}[2]{%
    \glstrfirstlongfont{\glstraccesslongpl{##1}\ifglstrinsertinside##2\fi}%
    \ifglstrinsertinside\else##2\fi\glstrfullsep{##1}%
    \glstrparen{\glstrfirstabbrvfont{\glstraccessshortpl{##1}}}%
  }%
}

```

```

}%
}
\setabbreviationstyle{long-short}
\newcommand*{\glxtrlongshortdescsort}{%
  \expandonce\glxtrorglong\space (\expandonce\glxtrorgshort)%
}
\newcommand*{\glxtrlongshortdescname}{%
  \protect\glslongfont{\the\glslongtok}
  \glxtrparen{\protect\glsabbrvfont{\the\glsshorttok}}%
}
\newabbreviationstyle{long-short-desc}%
{%
  \glxtrAccSuppAbbrSetTextShortAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glxtrlongshortdescname},
    sort={\glxtrlongshortdescsort},%
    first={\protect\glsfirstlongfont{\the\glslongtok}%
      \protect\glxtrfullsep{\the\glslabeltok}%
      \glxtrparen{\protect\glsfirstabbrvfont{\the\glsshorttok}}},%
    firstplural={\protect\glsfirstlongfont{\the\glslongpltok}%
      \protect\glxtrfullsep{\the\glslabeltok}%
      \glxtrparen{\protect\glsfirstabbrvfont{\the\glsshortpltok}}},%
    text={\protect\glsabbrvfont{\the\glsshorttok}},%
    plural={\protect\glsabbrvfont{\the\glsshortpltok}}%
  }%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \glshasattribute{\the\glslabeltok}{regular}%
    {%
      \glsssetAttribute{\the\glslabeltok}{regular}{false}%
    }%
    {}%
  }%
}%
{\GlsXtrUseAbbrStyleFmts{long-short}%
}
\newcommand*{\glxtrshortlongname}{%
  \protect\glsabbrvfont{\the\glsshorttok}%
}
\newabbreviationstyle{short-long}%
{%
  \glxtrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glxtrshortlongname},
    sort={\the\glsshorttok},
    description={\the\glslongtok},%
    first={\protect\glsfirstabbrvfont{\the\glsshorttok}%
      \protect\glxtrfullsep{\the\glslabeltok}%
      \glxtrparen{\protect\glsfirstlongfont{\the\glslongtok}}},%
    firstplural={\protect\glsfirstabbrvfont{\the\glsshortpltok}%

```

```

\protect\glxstrfullsep{\the\glslabeltok}%
\glxstrparen{\protect\glsfirstlongfont{\the\glslongpltok}}},%
text={\protect\glsabbrvfont{\the\glsshorttok}},%
plural={\protect\glsabbrvfont{\the\glsshortpltok}}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glshasattribute{\the\glslabeltok}{regular}%
{%
\glissetattribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%
{%
\renewcommand*{\abbrvpluralsuffix}{\glxtrabbrvpluralsuffix}%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvdefaultfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvdefaultfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%
\renewcommand*{\glxstrfullformat}[2]{%
\glsfirstabbrvfont{\glsaccessshort{##1}\ifglxtrininsertinside##2\fi}%
\ifglxtrininsertinside\else##2\fi
\glxstrfullsep{##1}%
\glxstrparen{\glsfirstlongfont{\glsaccesslong{##1}}}%
}%
\renewcommand*{\glxstrfullplformat}[2]{%
\glsfirstabbrvfont{\glsaccessshortpl{##1}\ifglxtrininsertinside##2\fi}%
\ifglxtrininsertinside\else##2\fi
\glxstrfullsep{##1}%
\glxstrparen{\glsfirstlongfont{\glsaccesslongpl{##1}}}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
\glsfirstabbrvfont{\Glsaccessshort{##1}\ifglxtrininsertinside##2\fi}%
\ifglxtrininsertinside\else##2\fi\glxstrfullsep{##1}%
\glxstrparen{\glsfirstlongfont{\glsaccesslong{##1}}}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
\glsfirstabbrvfont{\Glsaccessshortpl{##1}\ifglxtrininsertinside##2\fi}%
\ifglxtrininsertinside\else##2\fi\glxstrfullsep{##1}%
\glxstrparen{\glsfirstlongfont{\glsaccesslongpl{##1}}}%
}%
}
\newcommand*{\glxtrshortlongdescsort}{\the\glsshorttok}
\newcommand*{\glxtrshortlongdescname}{%
\protect\glsabbrvfont{\the\glsshorttok}
\glxstrparen{\protect\glslongfont{\the\glslongtok}}}%
}
\newabbreviationstyle{short-long-desc}%
{%
\glxtrAccSuppAbbrSetTextShortAttrs\glscategorylabel
\renewcommand*{\CustomAbbreviationFields}{%

```

```

name={\glxtrshortlongdescname},
sort={\glxtrshortlongdescsort},
first={\protect\glsfirstabbrvfont{\the\glsshorttok}%
\protect\glxtrfullsep{\the\glslabeltok}%
\glxtrparen{\protect\glsfirstlongfont{\the\glslongtok}}},%
firstplural={\protect\glsfirstabbrvfont{\the\glsshortpltok}%
\protect\glxtrfullsep{\the\glslabeltok}%
\glxtrparen{\protect\glsfirstlongfont{\the\glslongpltok}}},%
text={\protect\glsabbrvfont{\the\glsshorttok}},%
plural={\protect\glsabbrvfont{\the\glsshortpltok}}}%
}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glshasattribute{\the\glslabeltok}{regular}%
{%
\glissetattribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%
{\%
\GlsXtrUseAbbrStyleFmts{short-long}%
}
\newcommand*{\glsfirstlongfootnotefont}[1]{\glslongfootnotefont{#1}}%
\newcommand*{\glslongfootnotefont}[1]{\glslongdefaultfont{#1}}%
\newcommand*{\glxtrabbrvfootnote}[2]{\footnote{#2}}
\newcommand*{\glxtrfootnotename}{%
\protect\glsabbrvfont{\the\glsshorttok}%
}
\newabbreviationstyle{footnote}%
{%
\glxtrAccSuppAbbrSetNoLongAttrs\glscategorylabel
\renewcommand*{\CustomAbbreviationFields}{%
name={\glxtrfootnotename},
sort={\the\glsshorttok},
description={\the\glslongtok},%
first={\protect\glsfirstabbrvfont{\the\glsshorttok}%
\protect\glxtrabbrvfootnote{\the\glslabeltok}%
{\protect\glsfirstlongfootnotefont{\the\glslongtok}}},%
firstplural={\protect\glsfirstabbrvfont{\the\glsshortpltok}%
\protect\glxtrabbrvfootnote{\the\glslabeltok}%
{\protect\glsfirstlongfootnotefont{\the\glslongpltok}}},%
text={\protect\glsabbrvfont{\the\glsshorttok}},%
plural={\protect\glsabbrvfont{\the\glsshortpltok}}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glissetattribute{\the\glslabeltok}{nohyperfirst}{true}%
\glshasattribute{\the\glslabeltok}{regular}%
{%
\glissetattribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%

```

```

}%
}%
{%
\renewcommand*{\abbrevpluralsuffix}{\glstrabbrevpluralsuffix}%
\renewcommand*{\glabbrevfont}[1]{\glabbrevdefaultfont{##1}}%
\renewcommand*{\glfirstabbrevfont}[1]{\glfirstabbrevdefaultfont{##1}}%
\renewcommand*{\glfirstlongfont}[1]{\glfirstlongfootnotefont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongfootnotefont{##1}}%
\renewcommand*{\glstrfullformat}[2]{%
\glfirstabbrevfont{\glaccessshort{##1}}\ifglstrinsertinside##2\fi}%
\ifglstrinsertinside\else##2\fi
\protect\glstrabbrevfootnote{##1}%
{\glfirstlongfootnotefont{\glaccesslong{##1}}}%
}%
\renewcommand*{\glstrfullplformat}[2]{%
\glfirstabbrevfont{\glaccessshortpl{##1}}\ifglstrinsertinside##2\fi}%
\ifglstrinsertinside\else##2\fi
\protect\glstrabbrevfootnote{##1}%
{\glfirstlongfootnotefont{\glaccesslongpl{##1}}}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
\glfirstabbrevfont{\Glsaccessshort{##1}}\ifglstrinsertinside##2\fi}%
\ifglstrinsertinside\else##2\fi
\protect\glstrabbrevfootnote{##1}%
{\glfirstlongfootnotefont{\glaccesslong{##1}}}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
\glfirstabbrevfont{\Glsaccessshortpl{##1}}\ifglstrinsertinside##2\fi}%
\ifglstrinsertinside\else##2\fi
\protect\glstrabbrevfootnote{##1}%
{\glfirstlongfootnotefont{\glaccesslongpl{##1}}}%
}%
\renewcommand*{\glstrinlinefullformat}[2]{%
\glfirstabbrevfont{\glaccessshort{##1}}\ifglstrinsertinside##2\fi}%
\ifglstrinsertinside\else##2\fi\glstrfullsep{##1}%
\glstrparen{\glfirstlongfootnotefont{\glaccesslong{##1}}}%
}%
\renewcommand*{\glstrinlinefullplformat}[2]{%
\glfirstabbrevfont{\glaccessshortpl{##1}}\ifglstrinsertinside##2\fi}%
\ifglstrinsertinside\else##2\fi\glstrfullsep{##1}%
\glstrparen{\glfirstlongfootnotefont{\glaccesslongpl{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
\glfirstabbrevfont{\Glsaccessshort{##1}}\ifglstrinsertinside##2\fi}%
\ifglstrinsertinside\else##2\fi\glstrfullsep{##1}%
\glstrparen{\glfirstlongfootnotefont{\glaccesslong{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
\glfirstabbrevfont{\Glsaccessshortpl{##1}}\ifglstrinsertinside##2\fi}%
\ifglstrinsertinside\else##2\fi\glstrfullsep{##1}%

```



```

\glxtrparen{\glxfirstlongfootnotefont{\glaccesslongpl{##1}}}%
}%
}
\letabbreviationstyle{short-footnote}{footnote}
\newcommand*{\glxtrfootnotedesname}{%
  \protect\glxabbrvfont{\the\glsshorttok}%
  \protect\glxtrfullsep{\the\glslabeltok}%
  \protect\glxtrparen{\protect\glslongfont{\the\glslongtok}}%
}
\newcommand*{\glxtrfootnotedesort}{\the\glsshorttok}
\newabbreviationstyle{short-footnote-desc}{%
  {%
    \glxtrAccSuppAbbrSetNameLongAttrs\glscategorylabel
    \renewcommand*{\CustomAbbreviationFields}{%
      name={\glxtrfootnotedesname},
      sort={\glxtrfootnotedesort},
      first={\protect\glxfirstabbrvfont{\the\glsshorttok}%
        \protect\glxtrabbrvfootnote{\the\glslabeltok}%
        {\protect\glxfirstlongfootnotefont{\the\glslongtok}}},%
      firstplural={\protect\glxfirstabbrvfont{\the\glsshortpltok}%
        \protect\glxtrabbrvfootnote{\the\glslabeltok}%
        {\protect\glxfirstlongfootnotefont{\the\glslongpltok}}},%
      text={\protect\glxabbrvfont{\the\glsshorttok}},%
      plural={\protect\glxabbrvfont{\the\glsshortpltok}}}%
    \renewcommand*{\GlsXtrPostNewAbbreviation}{%
      \glsssetAttribute{\the\glslabeltok}{nohyperfirst}{true}%
      \glshasattribute{\the\glslabeltok}{regular}%
      {%
        \glsssetAttribute{\the\glslabeltok}{regular}{false}%
      }%
      {}%
    }%
  }%
}%
{\%
  \GlsXtrUseAbbrStyleFmts{footnote}%
}
\letabbreviationstyle{footnote-desc}{short-footnote-desc}
\newabbreviationstyle{postfootnote}{%
  {%
    \glxtrAccSuppAbbrSetNoLongAttrs\glscategorylabel
    \renewcommand*{\CustomAbbreviationFields}{%
      name={\glxtrfootnotename},
      sort={\the\glsshorttok},
      description={\the\glslongtok},%
      first={\protect\glxfirstabbrvfont{\the\glsshorttok}},%
      firstplural={\protect\glxfirstabbrvfont{\the\glsshortpltok}},%
      text={\protect\glxabbrvfont{\the\glsshorttok}},%
      plural={\protect\glxabbrvfont{\the\glsshortpltok}}}%
    \renewcommand*{\GlsXtrPostNewAbbreviation}{%
      \csdef{glxtrpostlink\glscategorylabel}{%

```

```

\glxstrifwasfirstuse
{%
  \glxtrdopostpunc{\protect\glxtrabbrvfootnote{\glslabel}%
    {\glsfirstlongfootnotefont{\glstrylong{\glslabel}}}}%
}%
{}%
}%
\glshasattribute{\the\glslabeltok}{regular}%
{%
  \glissetattribute{\the\glslabeltok}{regular}{false}%
}%
{}%
}%
\renewcommand*{\glxtrsetupfulldefs}{%
  \let\glxstrifwasfirstuse\@secondoftwo
}%
}%
{%
  \renewcommand*{\abbrvpluralsuffix}{\glxtrabbrvpluralsuffix}%
  \renewcommand*{\glxtrabbrvfont}[1]{\glxtrabbrvdefaultfont{##1}}%
  \renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvdefaultfont{##1}}%
  \renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongfootnotefont{##1}}%
  \renewcommand*{\glslongfont}[1]{\glslongfootnotefont{##1}}%
  \renewcommand*{\glxtrfullformat}[2]{%
    \glsfirstabbrvfont{\glssaccessshort{##1}\ifglxtrininsertinside##2\fi}%
    \ifglxtrininsertinside\else##2\fi
  }%
  \renewcommand*{\glxtrfullplformat}[2]{%
    \glsfirstabbrvfont{\glssaccessshortpl{##1}\ifglxtrininsertinside##2\fi}%
    \ifglxtrininsertinside\else##2\fi
  }%
  \renewcommand*{\Glsxtrfullformat}[2]{%
    \glsfirstabbrvfont{\Glsaccessshort{##1}\ifglxtrininsertinside##2\fi}%
    \ifglxtrininsertinside\else##2\fi
  }%
  \renewcommand*{\Glsxtrfullplformat}[2]{%
    \glsfirstabbrvfont{\Glsaccessshortpl{##1}\ifglxtrininsertinside##2\fi}%
    \ifglxtrininsertinside\else##2\fi
  }%
  \renewcommand*{\glxtrinlinefullformat}[2]{%
    \glsfirstabbrvfont{\glssaccessshort{##1}\ifglxtrininsertinside##2\fi}%
    \ifglxtrininsertinside\else##2\fi\glxtrfullsep{##1}%
    \glxtrparen{\glsfirstlongfootnotefont{\glssaccesslong{##1}}}%
  }%
  \renewcommand*{\glxtrinlinefullplformat}[2]{%
    \glsfirstabbrvfont{\glssaccessshortpl{##1}\ifglxtrininsertinside##2\fi}%
    \ifglxtrininsertinside\else##2\fi\glxtrfullsep{##1}%
    \glxtrparen{\glsfirstlongfootnotefont{\glssaccesslongpl{##1}}}%
  }%
  \renewcommand*{\Glsxtrinlinefullformat}[2]{%

```

```

\glsfirstabbrvfont{\Glsaccessshort{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\glsfirstlongfootnotefont{\Glsaccesslong{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
\glsfirstabbrvfont{\Glsaccessshortpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\glsfirstlongfootnotefont{\Glsaccesslongpl{##1}}}%
}%
}
\letabbreviationstyle{short-postfootnote}{postfootnote}
\newabbreviationstyle{short-postfootnote-desc}%
{%
\glsxtrAccSuppAbbrSetNameLongAttrs\glscategorylabel
\renewcommand*{\CustomAbbreviationFields}{%
name={\glsxtrfootnotedesname},
sort={\glsxtrfootnotedesort},
first={\protect\glsfirstabbrvfont{\the\glsshorttok}},%
firstplural={\protect\glsfirstabbrvfont{\the\glsshortpltok}},%
text={\protect\glsabbrvfont{\the\glsshorttok}},%
plural={\protect\glsabbrvfont{\the\glsshortpltok}}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\csdef{glxtrpostlink\glscategorylabel}{%
\glxtrifwasfirstuse
{%
\glxtrdopostpunc{\protect\glxtrabbrvfootnote{\glslabel}}%
{\glsfirstlongfootnotefont{\glstrylong{\glslabel}}}}}%
}%
}%
\glshasattribute{\the\glslabeltok}{regular}%
{%
\glissetattribute{\the\glslabeltok}{regular}{false}%
}%
}%
\renewcommand*{\glxtrsetupfulldefs}{%
\let\glxtrifwasfirstuse\@secondoftwo
}%
}%
{%
\GlsXtrUseAbbrStyleFmts{postfootnote}%
}
\letabbreviationstyle{postfootnote-desc}{short-postfootnote-desc}
\newcommand*{\glxtrshortnolongname}{%
\protect\glsabbrvfont{\the\glsshorttok}%
}
\newabbreviationstyle{short}%
{%
\glsxtrAccSuppAbbrSetNoLongAttrs\glscategorylabel

```

```

\renewcommand*{\CustomAbbreviationFields}{%
  name={\glstrshortnolongname},
  sort={\the\glsshorttok},
  first={\protect\glsfirstabbrvfont{\the\glsshorttok}},
  firstplural={\protect\glsfirstabbrvfont{\the\glsshortpltok}},
  text={\protect\glsabbrvfont{\the\glsshorttok}},
  plural={\protect\glsabbrvfont{\the\glsshortpltok}},
  description={\the\glslongtok}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glssetattribute{\the\glslabeltok}{regular}{true}}%
}%
{%
\renewcommand*{\abbrvpluralsuffix}{\glstrabbrvpluralsuffix}%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvdefaultfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvdefaultfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%
\renewcommand*{\glstrinlinefullformat}[2]{%
  \protect\glsfirstabbrvfont{\glsaccessshort{##1}}%
  \ifglstrinsertinside##2\fi}%
  \ifglstrinsertinside\else##2\fi\glstrfullsep{##1}%
  \glstrparen{\glsfirstlongfont{\glsaccesslong{##1}}}%
}%
\renewcommand*{\glstrinlinefullplformat}[2]{%
  \protect\glsfirstabbrvfont{\glsaccessshortpl{##1}}%
  \ifglstrinsertinside##2\fi}%
  \ifglstrinsertinside\else##2\fi\glstrfullsep{##1}%
  \glstrparen{\glsfirstlongfont{\glsaccesslongpl{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \protect\glsfirstabbrvfont{\glsaccessshort{##1}}%
  \ifglstrinsertinside##2\fi}%
  \ifglstrinsertinside\else##2\fi\glstrfullsep{##1}%
  \glstrparen{\glsfirstlongfont{\Glsaccesslong{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \protect\glsfirstabbrvfont{\glsaccessshortpl{##1}}%
  \ifglstrinsertinside##2\fi}%
  \ifglstrinsertinside\else##2\fi\glstrfullsep{##1}%
  \glstrparen{\glsfirstlongfont{\Glsaccesslongpl{##1}}}%
}%
\renewcommand*{\glstrfullformat}[2]{%
  \glsfirstabbrvfont{\glsaccessshort{##1}}\ifglstrinsertinside##2\fi}%
  \ifglstrinsertinside\else##2\fi
}%
\renewcommand*{\glstrfullplformat}[2]{%
  \glsfirstabbrvfont{\glsaccessshortpl{##1}}\ifglstrinsertinside##2\fi}%
  \ifglstrinsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullformat}[2]{%

```

```

\glsfirstabbrvfont{\glsaccessshort{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
\glsfirstabbrvfont{\glsaccessshortpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
}%
}
\setabbreviationstyle[acronym]{short}
\letabbreviationstyle{short-nolong}{short}
\newabbreviationstyle{short-nolong-noreg}%
{%
\GlsXtrUseAbbrStyleSetup{short-nolong}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glshasattribute{\the\glslabeltok}{regular}%
{%
\glssetattribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%
}%
{%
\GlsXtrUseAbbrStyleFmts{short-nolong}%
}
\newcommand*{\glxtrshortdescname}{%
\protect\glsabbrvfont{\the\glsshorttok}%
\protect\glxtrfullsep{\the\glslabeltok}%
\protect\glxtrparen{\protect\glslongfont{\the\glslongtok}}%
}
\newabbreviationstyle{short-desc}%
{%
\glxtrAccSuppAbbrSetNoLongAttrs\glscategorylabel
\renewcommand*{\CustomAbbreviationFields}{%
name={\glxtrshortdescname},
sort={\the\glsshorttok},
first={\protect\glsfirstabbrvfont{\the\glsshorttok}},
firstplural={\protect\glsfirstabbrvfont{\the\glsshortpltok}},
text={\protect\glsabbrvfont{\the\glsshorttok}},
plural={\protect\glsabbrvfont{\the\glsshortpltok}}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glssetattribute{\the\glslabeltok}{regular}{true}}%
}%
}%
\renewcommand*{\abbrvpluralsuffix}{\glxtrabbrvpluralsuffix}%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvdefaultfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvdefaultfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%
\renewcommand*{\glxtrinlinefullformat}[2]{%
\glsfirstabbrvfont{\glsaccessshort{##1}\ifglxtrinsertinside##2\fi}%

```

```

        \ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
        \glxtrparen{\glsfirstlongfont{\glsaccesslong{##1}}}%
    }%
\renewcommand*{\glxtrinlinefullplformat}[2]{%
    \glsfirstabbrvfont{\glsaccessshortpl{##1}\ifglxtrinsertinside##2\fi}%
    \ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
    \glxtrparen{\glsfirstlongfont{\glsaccesslongpl{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
    \glsfirstabbrvfont{\Glsaccessshort{##1}\ifglxtrinsertinside##2\fi}%
    \ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
    \glxtrparen{\glsfirstlongfont{\glsaccesslong{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
    \glsfirstabbrvfont{\Glsaccessshortpl{##1}\ifglxtrinsertinside##2\fi}%
    \ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
    \glxtrparen{\glsfirstlongfont{\glsaccesslongpl{##1}}}%
}%
\renewcommand*{\glxtrfullformat}[2]{%
    \glsfirstabbrvfont{\glsaccessshort{##1}\ifglxtrinsertinside##2\fi}%
    \ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\glxtrfullplformat}[2]{%
    \glsfirstabbrvfont{\glsaccessshortpl{##1}\ifglxtrinsertinside##2\fi}%
    \ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
    \glsfirstabbrvfont{\glsaccessshort{##1}\ifglxtrinsertinside##2\fi}%
    \ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
    \glsfirstabbrvfont{\glsaccessshortpl{##1}\ifglxtrinsertinside##2\fi}%
    \ifglxtrinsertinside\else##2\fi
}%
}
\letabbreviationstyle{short-nolong-desc}{short-desc}
\newabbreviationstyle{short-nolong-desc-noreg}%
{%
    \GlsXtrUseAbbrStyleSetup{short-nolong-desc}%
    \renewcommand*{\GlsXtrPostNewAbbreviation}{%
        \glshasattribute{\the\glslabeltok}{regular}%
        {%
            \glsssetattribute{\the\glslabeltok}{regular}{false}%
        }%
        {%
        }%
    }%
}%
}
\GlsXtrUseAbbrStyleFmts{short-nolong-desc}%
}

```

```

\newabbreviationstyle{nolong-short}%
{%
  \GlsXtrUseAbbrStyleSetup{short-nolong}%
}%
{%
  \GlsXtrUseAbbrStyleFmts{short-nolong}%
  \renewcommand*{\glxtrinlinefullformat}[2]{%
    \protect\glsfirstlongfont{\glsaccesslong{##1}}%
    \ifglxtrinsertinside##2\fi}%
    \ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
    \glxtrparen{\glsfirstabbrvfont{\glsaccessshort{##1}}}%
  }%
  \renewcommand*{\glxtrinlinefullplformat}[2]{%
    \protect\glsfirstlongfont{\glsaccesslongpl{##1}}%
    \ifglxtrinsertinside##2\fi}%
    \ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
    \glxtrparen{\glsfirstabbrvfont{\glsaccessshortpl{##1}}}%
  }%
  \renewcommand*{\Glsxtrinlinefullformat}[2]{%
    \protect\glsfirstlongfont{\glsaccesslong{##1}}%
    \ifglxtrinsertinside##2\fi}%
    \ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
    \glxtrparen{\glsfirstabbrvfont{\Glsaccessshort{##1}}}%
  }%
  \renewcommand*{\Glsxtrinlinefullplformat}[2]{%
    \protect\glsfirstlongfont{\glsaccesslongpl{##1}}%
    \ifglxtrinsertinside##2\fi}%
    \ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
    \glxtrparen{\glsfirstabbrvfont{\Glsaccessshortpl{##1}}}%
  }%
}
\newabbreviationstyle{nolong-short-noreg}%
{%
  \GlsXtrUseAbbrStyleSetup{nolong-short}%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \glshasattribute{\the\glslabeltok}{regular}%
    {%
      \glsssetAttribute{\the\glslabeltok}{regular}{false}%
    }%
    {}%
  }%
}%
{%
  \GlsXtrUseAbbrStyleFmts{nolong-short}%
}
\newcommand*{\glxtrlongnoshortdescname}{%
  \protect\glslongfont{\the\glslongtok}%
}
\newabbreviationstyle{long-desc}%
{%

```

```

\renewcommand*{\CustomAbbreviationFields}{%
  name={\glstrlongnoshortdescname},
  sort={\the\glslongtok},
  first={\protect\glsfirstlongfont{\the\glslongtok}},
  firstplural={\protect\glsfirstlongfont{\the\glslongpltok}},
  text={\glslongfont{\the\glslongtok}},
  plural={\glslongfont{\the\glslongpltok}}}%
}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glssetattribute{\the\glslabeltok}{regular}{true}}%
}%
{%
\renewcommand*{\abbrvpluralsuffix}{\glstrabbrvpluralsuffix}%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvdefaultfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvdefaultfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%
\renewcommand*{\glstrsubsequentfmt}[2]{%
  \glslongfont{\glsaccesslong{##1}\ifglstrinsertinside ##2\fi}%
  \ifglstrinsertinside \else##2\fi
}%
\renewcommand*{\glstrsubsequentplfmt}[2]{%
  \glslongfont{\glsaccesslongpl{##1}\ifglstrinsertinside ##2\fi}%
  \ifglstrinsertinside \else##2\fi
}%
\renewcommand*{\Glsxtrsubsequentfmt}[2]{%
  \glslongfont{\Glsaccesslong{##1}\ifglstrinsertinside ##2\fi}%
  \ifglstrinsertinside \else##2\fi
}%
\renewcommand*{\Glsxtrsubsequentplfmt}[2]{%
  \glslongfont{\Glsaccesslongpl{##1}\ifglstrinsertinside ##2\fi}%
  \ifglstrinsertinside \else##2\fi
}%
\renewcommand*{\glstrinlinefullformat}[2]{%
  \glsfirstlongfont{\glsaccesslong{##1}\ifglstrinsertinside##2\fi}%
  \ifglstrinsertinside\else##2\fi\glstrfullsep{##1}%
  \glstrparen{\protect\glsfirstabbrvfont{\glsaccessshort{##1}}}%
}%
\renewcommand*{\glstrinlinefullplformat}[2]{%
  \glsfirstlongfont{\glsaccesslongpl{##1}\ifglstrinsertinside##2\fi}%
  \ifglstrinsertinside\else##2\fi\glstrfullsep{##1}%
  \glstrparen{\protect\glsfirstabbrvfont{\glsaccessshortpl{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \glsfirstlongfont{\Glsaccesslong{##1}\ifglstrinsertinside##2\fi}%
  \ifglstrinsertinside\else##2\fi\glstrfullsep{##1}%
  \glstrparen{\protect\glsfirstabbrvfont{\glsaccessshort{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \glsfirstlongfont{\Glsaccesslongpl{##1}\ifglstrinsertinside##2\fi}%

```



```

\ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\protect\glsfirstabbrvfont{\glssaccessshortpl{##1}}}%
}%
\renewcommand*{\glxtrfullformat}[2]{%
\glsfirstlongfont{\glssaccesslong{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\glxtrfullplformat}[2]{%
\glsfirstlongfont{\glssaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
\glsfirstlongfont{\glssaccesslong{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
\glsfirstlongfont{\glssaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
}%
}
\letabbreviationstyle{long-noshort-desc}{long-desc}
\newabbreviationstyle{long-noshort-desc-noreg}%
{%
\GlsXtrUseAbbrStyleSetup{long-noshort-desc}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glshasattribute{\the\glslabeltok}{regular}%
{%
\glsssetAttribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%
}%
\GlsXtrUseAbbrStyleFmts{long-noshort-desc}%
}
\newcommand*{\glxtrlongnoshortname}{%
\protect\glssabbrvfont{\the\glssshorttok}%
}
\newabbreviationstyle{long}%
{%
\glxtrAccSuppAbbrSetNameShortAttrs\glscategorylabel
\renewcommand*{\CustomAbbreviationFields}{%
name={\glxtrlongnoshortname},
sort={\the\glssshorttok},
first={\protect\glsfirstlongfont{\the\glslongtok}},
firstplural={\protect\glsfirstlongfont{\the\glslongpltok}},
text={\glslongfont{\the\glslongtok}},
plural={\glslongfont{\the\glslongpltok}},%
description={\the\glslongtok}%
}%
}

```

```

\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glsssetattribute{\the\glslabeltok}{regular}{true}}%
}%
{%
  \GlsXtrUseAbbrStyleFmts{long-desc}%
}
\letabbreviationstyle{long-noshort}{long}
\newabbreviationstyle{long-noshort-noreg}%
{%
  \GlsXtrUseAbbrStyleSetup{long-noshort}%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \glshasattribute{\the\glslabeltok}{regular}%
    {%
      \glsssetattribute{\the\glslabeltok}{regular}{false}%
    }%
    {}%
  }%
}%
{%
  \GlsXtrUseAbbrStyleFmts{long-noshort}%
}
\newcommand*{\glsxtrscfont}[1]{\textsc{#1}}
\newcommand*{\glsabbrvscfont}{\glsxtrscfont}
\newcommand*{\glsxtrfirstscfont}[1]{\glsabbrvscfont{#1}}
\newcommand*{\glsfirstabbrvscfont}{\glsxtrfirstscfont}
\newcommand*{\glsxtrscsuffix}{\protect\glstextup{\glsxtrabbrvpluralsuffix}}
\newabbreviationstyle{long-short-sc}%
{%
  \glsxtrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glsxtrlongshortname},
    sort={\the\glsshorttok},
    first={\protect\glsfirstlongdefaultfont{\the\glslongtok}%
      \protect\glsxtrfullsep{\the\glslabeltok}%
      \glsxtrparen{\protect\glsfirstabbrvscfont{\the\glsshorttok}}},%
    firstplural={\protect\glsfirstlongdefaultfont{\the\glslongpltok}%
      \protect\glsxtrfullsep{\the\glslabeltok}%
      \glsxtrparen{\protect\glsfirstabbrvscfont{\the\glsshortpltok}}},%
    text={\protect\glsabbrvscfont{\the\glsshorttok}},%
    plural={\protect\glsabbrvscfont{\the\glsshortpltok}},%
    description={\the\glslongtok}}%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \glshasattribute{\the\glslabeltok}{regular}%
    {%
      \glsssetattribute{\the\glslabeltok}{regular}{false}%
    }%
    {}%
  }%
}%
{%

```

```

\renewcommand*{\abbrvpluralsuffix}{\glxtrscsuffix}%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvscfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvscfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%
\renewcommand*{\glxtrfullformat}[2]{%
  \glsfirstlongdefaultfont{\glsaccesslong{##1}\ifglxtrininsertinside##2\fi}%
  \ifglxtrininsertinside\else##2\fi
  \glxtrfullsep{##1}%
  \glxtrparen{\glsfirstabbrvscfont{\glsaccessshort{##1}}}%
}%
\renewcommand*{\glxtrfullplformat}[2]{%
  \glsfirstlongdefaultfont{\glsaccesslongpl{##1}\ifglxtrininsertinside##2\fi}%
  \ifglxtrininsertinside\else##2\fi\glxtrfullsep{##1}%
  \glxtrparen{\glsfirstabbrvscfont{\glsaccessshortpl{##1}}}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \glsfirstlongdefaultfont{\Glsaccesslong{##1}\ifglxtrininsertinside##2\fi}%
  \ifglxtrininsertinside\else##2\fi\glxtrfullsep{##1}%
  \glxtrparen{\glsfirstabbrvscfont{\glsaccessshort{##1}}}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \glsfirstlongdefaultfont{\Glsaccesslongpl{##1}\ifglxtrininsertinside##2\fi}%
  \ifglxtrininsertinside\else##2\fi\glxtrfullsep{##1}%
  \glxtrparen{\glsfirstabbrvscfont{\glsaccessshortpl{##1}}}%
}%
}
\newabbreviationstyle{long-short-sc-desc}%
{%
  \glxtrAccSuppAbbrSetTextShortAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glxtrlongshortdescname},
    sort={\glxtrlongshortdescsort},%
    first={\protect\glsfirstlongdefaultfont{\the\glslongtok}%
      \protect\glxtrfullsep{\the\glslabeltok}%
      \glxtrparen{\protect\glsfirstabbrvscfont{\the\glsshorttok}}},%
    firstplural={\protect\glsfirstlongdefaultfont{\the\glslongpltok}%
      \protect\glxtrfullsep{\the\glslabeltok}%
      \glxtrparen{\protect\glsfirstabbrvscfont{\the\glsshortpltok}}},%
    text={\protect\glsabbrvscfont{\the\glsshorttok}},%
    plural={\protect\glsabbrvscfont{\the\glsshortpltok}}%
  }%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \glshasattribute{\the\glslabeltok}{regular}%
    {%
      \glsssetAttribute{\the\glslabeltok}{regular}{false}%
    }%
    {}%
  }%
}%

```

```

{%
  \GlsXtrUseAbbrStyleFmts{long-short-sc}%
}
\newabbreviationstyle{short-sc-long}%
{%
  \glstrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glstrshortlongname},
    sort={\the\glsshorttok},
    description={\the\glslongtok},%
    first={\protect\glsfirstabbrvscfont{\the\glsshorttok}%
      \protect\glstrfullsep{\the\glslabeltok}%
      \glstrparen{\protect\glsfirstlongdefaultfont{\the\glslongtok}}},%
    firstplural={\protect\glsfirstabbrvscfont{\the\glsshortpltok}%
      \protect\glstrfullsep{\the\glslabeltok}%
      \glstrparen{\protect\glsfirstlongdefaultfont{\the\glslongpltok}}},%
    text={\protect\glsabbrvscfont{\the\glsshorttok}},%
    plural={\protect\glsabbrvscfont{\the\glsshortpltok}}}%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \glshasattribute{\the\glslabeltok}{regular}%
    {%
      \glsssetAttribute{\the\glslabeltok}{regular}{false}%
    }%
    {}%
  }%
}%
{%
  \renewcommand*{\abbrvpluralsuffix}{\glstrscsuffix}%
  \renewcommand*{\glsabbrvfont}[1]{\glsabbrvscfont{##1}}%
  \renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvscfont{##1}}%
  \renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongdefaultfont{##1}}%
  \renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%
  \renewcommand*{\glstrfullformat}[2]{%
    \glsfirstabbrvscfont{\glsaccessshort{##1}}\ifglstrinsertinside##2\fi%
    \ifglstrinsertinside\else##2\fi
    \glstrfullsep{##1}%
    \glstrparen{\glsfirstlongdefaultfont{\glsaccesslong{##1}}}%
  }%
  \renewcommand*{\glstrfullplformat}[2]{%
    \glsfirstabbrvscfont{\glsaccessshortpl{##1}}\ifglstrinsertinside##2\fi%
    \ifglstrinsertinside\else##2\fi
    \glstrfullsep{##1}%
    \glstrparen{\glsfirstlongdefaultfont{\glsaccesslongpl{##1}}}%
  }%
  \renewcommand*{\Glsxtrfullformat}[2]{%
    \glsfirstabbrvscfont{\Glsaccessshort{##1}}\ifglstrinsertinside##2\fi%
    \ifglstrinsertinside\else##2\fi\glstrfullsep{##1}%
    \glstrparen{\glsfirstlongdefaultfont{\glsaccesslong{##1}}}%
  }%
  \renewcommand*{\Glsxtrfullplformat}[2]{%

```

```

\glsfirstabbrvscfont{\Glsaccessshortpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\glsfirstlongdefaultfont{\Glsaccesslongpl{##1}}}%
}%
}
\newabbreviationstyle{short-sc-long-desc}%
{%
\glxtrAccSuppAbbrSetTextShortAttrs\glscategorylabel
\renewcommand*{\CustomAbbreviationFields}{%
name={\glxtrshortlongdescname},
sort={\glxtrshortlongdescsort},
first={\protect\glsfirstabbrvscfont{\the\glsshorttok}}%
\protect\glxtrfullsep{\the\glslabeltok}}%
\glxtrparen{\protect\glsfirstlongdefaultfont{\the\glslongtok}}},%
firstplural={\protect\glsfirstabbrvscfont{\the\glsshortpltok}}%
\protect\glxtrfullsep{\the\glslabeltok}}%
\glxtrparen{\protect\glsfirstlongdefaultfont{\the\glslongpltok}}},%
text={\protect\glsabbrvscfont{\the\glsshorttok}},%
plural={\protect\glsabbrvscfont{\the\glsshortpltok}}%
}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glshasattribute{\the\glslabeltok}{regular}%
{%
\glissetattribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%
{%
\GlsXtrUseAbbrStyleFmts{short-sc-long}%
}
\newabbreviationstyle{short-sc}%
{%
\glxtrAccSuppAbbrSetNoLongAttrs\glscategorylabel
\renewcommand*{\CustomAbbreviationFields}{%
name={\glxtrshortnolongname},
sort={\the\glsshorttok},
first={\protect\glsfirstabbrvscfont{\the\glsshorttok}},
firstplural={\protect\glsfirstabbrvscfont{\the\glsshortpltok}},
text={\protect\glsabbrvscfont{\the\glsshorttok}},
plural={\protect\glsabbrvscfont{\the\glsshortpltok}},
description={\the\glslongtok}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glissetattribute{\the\glslabeltok}{regular}{true}}%
}%
{%
\renewcommand*{\abbrvpluralsuffix}{\glxtrscsuffix}%
\renewcommand*{\glsabbrvfont[1]{\glsabbrvscfont{##1}}}%
\renewcommand*{\glsfirstabbrvfont[1]{\glsfirstabbrvscfont{##1}}}%
\renewcommand*{\glsfirstlongfont[1]{\glsfirstlongdefaultfont{##1}}}%

```

```

\renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%
\renewcommand*{\glsxtrinlinefullformat}[2]{%
  \protect\glsfirstabbrvscfont{\glsaccessshort{##1}}%
  \ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
  \glsxtrparen{\glsfirstlongdefaultfont{\glsaccesslong{##1}}}%
}%
\renewcommand*{\glsxtrinlinefullplformat}[2]{%
  \protect\glsfirstabbrvscfont{\glsaccessshortpl{##1}}%
  \ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
  \glsxtrparen{\glsfirstlongdefaultfont{\glsaccesslongpl{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \protect\glsfirstabbrvscfont{\Glsaccessshort{##1}}%
  \ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
  \glsxtrparen{\glsfirstlongdefaultfont{\glsaccesslong{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \protect\glsfirstabbrvscfont{\Glsaccessshortpl{##1}}%
  \ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
  \glsxtrparen{\glsfirstlongdefaultfont{\glsaccesslongpl{##1}}}%
}%
\renewcommand*{\glsxtrfullformat}[2]{%
  \glsfirstabbrvscfont{\glsaccessshort{##1}}\ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi
}%
\renewcommand*{\glsxtrfullplformat}[2]{%
  \glsfirstabbrvscfont{\glsaccessshortpl{##1}}\ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \glsfirstabbrvscfont{\glsaccessshort{##1}}\ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \glsfirstabbrvscfont{\glsaccessshortpl{##1}}\ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi
}%
}
\letabbreviationstyle{short-sc-nolong}{short-sc}
\newabbreviationstyle{short-sc-desc}%
{%
  \glsxtrAccSuppAbbrSetNameLongAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glsxtrshortdescname},
    sort={\the\glsshorttok},
    first={\protect\glsfirstabbrvscfont{\the\glsshorttok}},

```

```

firstplural={\protect\glsfirstabbrvscfont{\the\glsshortpltok}},
text={\protect\glsabbrvscfont{\the\glsshorttok}},
plural={\protect\glsabbrvscfont{\the\glsshortpltok}}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glssetattribute{\the\glslabeltok}{regular}{true}}%
}%
{%
\renewcommand*{\abbrvpluralsuffix}{\glxtrscsuffix}%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvscfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvscfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%
\renewcommand*{\glxtrinlinefullformat}[2]{%
\glsfirstabbrvscfont{\glsaccessshort{##1}\ifglxtrininsertinside##2\fi}%
\ifglxtrininsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\glsfirstlongdefaultfont{\glsaccesslong{##1}}}%
}%
\renewcommand*{\glxtrinlinefullplformat}[2]{%
\glsfirstabbrvscfont{\glsaccessshortpl{##1}\ifglxtrininsertinside##2\fi}%
\ifglxtrininsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\glsfirstlongdefaultfont{\glsaccesslongpl{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
\glsfirstabbrvscfont{\Glsaccessshort{##1}\ifglxtrininsertinside##2\fi}%
\ifglxtrininsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\glsfirstlongdefaultfont{\glsaccesslong{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
\glsfirstabbrvscfont{\Glsaccessshortpl{##1}\ifglxtrininsertinside##2\fi}%
\ifglxtrininsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\glsfirstlongdefaultfont{\glsaccesslongpl{##1}}}%
}%
\renewcommand*{\glxtrfullformat}[2]{%
\glsfirstabbrvscfont{\glsaccessshort{##1}\ifglxtrininsertinside##2\fi}%
\ifglxtrininsertinside\else##2\fi
}%
\renewcommand*{\glxtrfullplformat}[2]{%
\glsfirstabbrvscfont{\glsaccessshortpl{##1}\ifglxtrininsertinside##2\fi}%
\ifglxtrininsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
\glsfirstabbrvscfont{\glsaccessshort{##1}\ifglxtrininsertinside##2\fi}%
\ifglxtrininsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
\glsfirstabbrvscfont{\glsaccessshortpl{##1}\ifglxtrininsertinside##2\fi}%
\ifglxtrininsertinside\else##2\fi
}%
}%
\letabbreviationstyle{short-sc-nolong-desc}{short-sc-desc}

```

```

\newabbreviationstyle{nolong-short-sc}%
{%
  \GlsXtrUseAbbrStyleSetup{short-sc-nolong}%
}%
{%
  \GlsXtrUseAbbrStyleFmts{short-sc-nolong}%
  \renewcommand*{\glsxtrinlinefullformat}[2]{%
    \protect\glsfirstlongdefaultfont{\glssaccesslong{##1}%
      \ifglsxtrininsertinside##2\fi}%
    \ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
    \glsxtrparen{\glsfirstabbrvscfont{\glssaccessshort{##1}}}%
  }%
  \renewcommand*{\glsxtrinlinefullplformat}[2]{%
    \protect\glsfirstlongdefaultfont{\glssaccesslongpl{##1}%
      \ifglsxtrininsertinside##2\fi}%
    \ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
    \glsxtrparen{\glsfirstabbrvscfont{\glssaccessshortpl{##1}}}%
  }%
  \renewcommand*{\Glsxtrinlinefullformat}[2]{%
    \protect\glsfirstlongdefaultfont{\Glsaccesslong{##1}%
      \ifglsxtrininsertinside##2\fi}%
    \ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
    \glsxtrparen{\glsfirstabbrvscfont{\glssaccessshort{##1}}}%
  }%
  \renewcommand*{\Glsxtrinlinefullplformat}[2]{%
    \protect\glsfirstlongdefaultfont{\Glsaccesslongpl{##1}%
      \ifglsxtrininsertinside##2\fi}%
    \ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
    \glsxtrparen{\glsfirstabbrvscfont{\glssaccessshortpl{##1}}}%
  }%
}
\newabbreviationstyle{long-noshort-sc}%
{%
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glsxtrlongnoshortname},
    sort={\the\glssshorttok},
    first={\protect\glsfirstlongdefaultfont{\the\glslongtok}},
    firstplural={\protect\glsfirstlongdefaultfont{\the\glslongpltok}},
    text={\protect\glslongdefaultfont{\the\glslongtok}},
    plural={\protect\glslongdefaultfont{\the\glslongpltok}},%
    description={\the\glslongtok}%
  }%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \glsssetAttribute{\the\glslabeltok}{regular}{true}}%
}%
{%
  \renewcommand*{\abbrvpluralsuffix}{\glsxtrscsuffix}%
  \renewcommand*{\glsabbrvfont}[1]{\glsabbrvscfont{##1}}%
  \renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvscfont{##1}}%
  \renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongdefaultfont{##1}}%

```



```

\renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%
\renewcommand*{\glsxtrsubsequentfmt}[2]{%
  \glslongdefaultfont{\glsaccesslong{##1}\ifglsxtrininsertinside ##2\fi}%
  \ifglsxtrininsertinside \else##2\fi
}%
\renewcommand*{\glsxtrsubsequentplfmt}[2]{%
  \glslongdefaultfont{\glsaccesslongpl{##1}\ifglsxtrininsertinside ##2\fi}%
  \ifglsxtrininsertinside \else##2\fi
}%
\renewcommand*{\Glsxtrsubsequentfmt}[2]{%
  \glslongdefaultfont{\Glsaccesslong{##1}\ifglsxtrininsertinside ##2\fi}%
  \ifglsxtrininsertinside \else##2\fi
}%
\renewcommand*{\Glsxtrsubsequentplfmt}[2]{%
  \glslongdefaultfont{\Glsaccesslongpl{##1}\ifglsxtrininsertinside ##2\fi}%
  \ifglsxtrininsertinside \else##2\fi
}%
\renewcommand*{\glsxtrinlinefullformat}[2]{%
  \glsfirstlongdefaultfont{\glsaccesslong{##1}\ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
  \glsxtrparen{\protect\glsfirstabbrvscfont{\glsaccessshort{##1}}}%
}%
\renewcommand*{\glsxtrinlinefullplformat}[2]{%
  \glsfirstlongdefaultfont{\glsaccesslongpl{##1}\ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
  \glsxtrparen{\protect\glsfirstabbrvscfont{\glsaccessshortpl{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \glsfirstlongdefaultfont{\Glsaccesslong{##1}\ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
  \glsxtrparen{\protect\glsfirstabbrvscfont{\glsaccessshort{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \glsfirstlongdefaultfont{\Glsaccesslongpl{##1}\ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
  \glsxtrparen{\protect\glsfirstabbrvscfont{\glsaccessshortpl{##1}}}%
}%
\renewcommand*{\glsxtrfullformat}[2]{%
  \glsfirstlongdefaultfont{\glsaccesslong{##1}\ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi
}%
\renewcommand*{\glsxtrfullplformat}[2]{%
  \glsfirstlongdefaultfont{\glsaccesslongpl{##1}\ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \glsfirstlongdefaultfont{\glsaccesslong{##1}\ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%

```

```

\glsfirstlongdefaultfont{\glsaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
}%
}
\@glxtr@deprecated@abbrstyle{long-sc}{long-noshort-sc}
\newabbreviationstyle{long-noshort-sc-desc}%
{%
\GlsXtrUseAbbrStyleSetup{long-noshort-desc}%
}%
{%
\renewcommand*{\abbrvpluralsuffix}{\glxtrscsuffix}%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvscfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvscfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%
\renewcommand*{\glxtrsubsequentfmt}[2]{%
\glslongdefaultfont{\glsaccesslong{##1}\ifglxtrinsertinside ##2\fi}%
\ifglxtrinsertinside \else##2\fi
}%
\renewcommand*{\glxtrsubsequentplfmt}[2]{%
\glslongdefaultfont{\glsaccesslongpl{##1}\ifglxtrinsertinside ##2\fi}%
\ifglxtrinsertinside \else##2\fi
}%
\renewcommand*{\Glsxtrsubsequentfmt}[2]{%
\glslongdefaultfont{\Glsaccesslong{##1}\ifglxtrinsertinside ##2\fi}%
\ifglxtrinsertinside \else##2\fi
}%
\renewcommand*{\Glsxtrsubsequentplfmt}[2]{%
\glslongdefaultfont{\Glsaccesslongpl{##1}\ifglxtrinsertinside ##2\fi}%
\ifglxtrinsertinside \else##2\fi
}%
\renewcommand*{\glxtrinlinefullformat}[2]{%
\glsfirstlongdefaultfont{\glsaccesslong{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\protect\glsfirstabbrvscfont{\glsaccessshort{##1}}}%
}%
\renewcommand*{\glxtrinlinefullplformat}[2]{%
\glsfirstlongdefaultfont{\glsaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\protect\glsfirstabbrvscfont{\glsaccessshortpl{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
\glsfirstlongdefaultfont{\Glsaccesslong{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\protect\glsfirstabbrvscfont{\glsaccessshort{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
\glsfirstlongdefaultfont{\Glsaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\protect\glsfirstabbrvscfont{\glsaccessshortpl{##1}}}%
}%

```

```

}%
\renewcommand*{\glstrfullformat}[2]{%
  \glsfirstlongdefaultfont{\glssaccesslong{##1}\ifglstrinsertinside##2\fi}%
  \ifglstrinsertinside\else##2\fi
}%
\renewcommand*{\glstrfullplformat}[2]{%
  \glsfirstlongdefaultfont{\glssaccesslongpl{##1}\ifglstrinsertinside##2\fi}%
  \ifglstrinsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \glsfirstlongdefaultfont{\glssaccesslong{##1}\ifglstrinsertinside##2\fi}%
  \ifglstrinsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \glsfirstlongdefaultfont{\glssaccesslongpl{##1}\ifglstrinsertinside##2\fi}%
  \ifglstrinsertinside\else##2\fi
}%
}
\@glstr@deprecated@abbrstyle{long-desc-sc}{long-noshort-sc-desc}
\newabbreviationstyle{short-sc-footnote}%
{%
  \glstrAccSuppAbbrSetNoLongAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glstrfootnotename},
    sort={\the\glssshorttok},
    description={\the\glslongtok},%
    first={\protect\glsfirstabbrvscfont{\the\glssshorttok}%
      \protect\glstrabbrvfootnote{\the\glslabeltok}%
      {\protect\glsfirstlongfootnotefont{\the\glslongtok}}},%
    firstplural={\protect\glsfirstabbrvscfont{\the\glssshortpltok}%
      \protect\glstrabbrvfootnote{\the\glslabeltok}%
      {\protect\glsfirstlongfootnotefont{\the\glslongpltok}}},%
    text={\protect\glsabbrvscfont{\the\glssshorttok}},%
    plural={\protect\glsabbrvscfont{\the\glssshortpltok}}}%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \glsssetAttribute{\the\glslabeltok}{nohyperfirst}{true}%
    \glshasattribute{\the\glslabeltok}{regular}%
    {%
      \glsssetAttribute{\the\glslabeltok}{regular}{false}%
    }%
    {}%
  }%
}%
}%
{%
  \renewcommand*{\abbrvpluralsuffix}{\glstrscsuffix}%
  \renewcommand*{\glsabbrvfont}[1]{\glsabbrvscfont{##1}}%
  \renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvscfont{##1}}%
  \renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongfootnotefont{##1}}%
  \renewcommand*{\glslongfont}[1]{\glslongfootnotefont{##1}}%
  \renewcommand*{\glstrfullformat}[2]{%

```

```

\glsfirstabbrvscfont{\glsaccessshort{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
\protect\glxtrabbrvfootnote{##1}%
{\glsfirstlongfootnotefont{\glsaccesslong{##1}}}%
}%
\renewcommand*{\glxtrfullplformat}[2]{%
\glsfirstabbrvscfont{\glsaccessshortpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
\protect\glxtrabbrvfootnote{##1}%
{\glsfirstlongfootnotefont{\glsaccesslongpl{##1}}}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
\glsfirstabbrvscfont{\Glsaccessshort{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
\protect\glxtrabbrvfootnote{##1}%
{\glsfirstlongfootnotefont{\glsaccesslong{##1}}}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
\glsfirstabbrvscfont{\Glsaccessshortpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
\protect\glxtrabbrvfootnote{##1}%
{\glsfirstlongfootnotefont{\glsaccesslongpl{##1}}}%
}%
\renewcommand*{\glxtrinlinefullformat}[2]{%
\glsfirstabbrvscfont{\glsaccessshort{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\glsfirstlongfootnotefont{\glsaccesslong{##1}}}%
}%
\renewcommand*{\glxtrinlinefullplformat}[2]{%
\glsfirstabbrvscfont{\glsaccessshortpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\glsfirstlongfootnotefont{\glsaccesslongpl{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
\glsfirstabbrvscfont{\Glsaccessshort{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\glsfirstlongfootnotefont{\glsaccesslong{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
\glsfirstabbrvscfont{\Glsaccessshortpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\glsfirstlongfootnotefont{\glsaccesslongpl{##1}}}%
}%
}
\@glxtr@deprecated@abbrstyle{footnote-sc}{short-sc-footnote}
\newabbreviationstyle{short-sc-footnote-desc}%
{%
\glxtrAccSuppAbbrSetNameLongAttrs\glscategorylabel
\renewcommand*{\CustomAbbreviationFields}{%
name={\glxtrfootnotedescname},

```

```

sort={\glxtrfootnotedesort},
first={\protect\glsfirstabbrvscfont{\the\glsshorttok}%
\protect\glxtrabbrvfootnote{\the\glslabeltok}%
{\protect\glsfirstlongfootnotefont{\the\glslongtok}}},%
firstplural={\protect\glsfirstabbrvscfont{\the\glsshortpltok}%
\protect\glxtrabbrvfootnote{\the\glslabeltok}%
{\protect\glsfirstlongfootnotefont{\the\glslongpltok}}},%
text={\protect\glsabbrvscfont{\the\glsshorttok}},%
plural={\protect\glsabbrvscfont{\the\glsshortpltok}}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glssetattribute{\the\glslabeltok}{nohyperfirst}{true}%
\glsattribute{\the\glslabeltok}{regular}%
{%
\glssetattribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%
{%
\GlsXtrUseAbbrStyleFmts{short-sc-footnote}%
}
\newabbreviationstyle{short-sc-postfootnote}%
{%
\glxtrAccSuppAbbrSetNoLongAttrs\glscategorylabel
\renewcommand*{\CustomAbbreviationFields}{%
name={\glxtrfootnotename},
sort={\the\glsshorttok},
description={\the\glslongtok},%
first={\protect\glsfirstabbrvscfont{\the\glsshorttok}},%
firstplural={\protect\glsfirstabbrvscfont{\the\glsshortpltok}},%
text={\protect\glsabbrvscfont{\the\glsshorttok}},%
plural={\protect\glsabbrvscfont{\the\glsshortpltok}}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\csdef{glxtrpostlink\glscategorylabel}{%
\glxtrifwasfirstuse
{%
\glxtrdopostpunc{\protect\glxtrabbrvfootnote{\glslabel}%
{\glsfirstlongfootnotefont{\glsentrylong{\glslabel}}}}%
}%
}%
}%
\glsattribute{\the\glslabeltok}{regular}%
{%
\glssetattribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%
\renewcommand*{\glxtrsetupfulldefs}{%
\let\glxtrifwasfirstuse\@secondoftwo
}%

```

```

}%
{%
\renewcommand*{\abbrvpluralsuffix}{\glxtrscsuffix}%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvscfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvscfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongfootnotefont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongfootnotefont{##1}}%
\renewcommand*{\glxtrfullformat}[2]{%
\glsfirstabbrvscfont{\glssaccessshort{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\glxtrfullplformat}[2]{%
\glsfirstabbrvscfont{\glssaccessshortpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
\glsfirstabbrvscfont{\Glsaccessshort{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
\glsfirstabbrvscfont{\Glsaccessshortpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\glxtrinlinefullformat}[2]{%
\glsfirstabbrvscfont{\glssaccessshort{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\glsfirstlongfootnotefont{\glssaccesslong{##1}}}%
}%
\renewcommand*{\glxtrinlinefullplformat}[2]{%
\glsfirstabbrvscfont{\glssaccessshortpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\glsfirstlongfootnotefont{\glssaccesslongpl{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
\glsfirstabbrvscfont{\Glsaccessshort{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\glsfirstlongfootnotefont{\glssaccesslong{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
\glsfirstabbrvscfont{\Glsaccessshortpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\glsfirstlongfootnotefont{\glssaccesslongpl{##1}}}%
}%
}
\@glxtr@deprecated@abbrstyle{postfootnote-sc}{short-sc-postfootnote}
\newabbreviationstyle{short-sc-postfootnote-desc}%
{%
\glxtrAccSuppAbbrSetNameLongAttrs\glscategorylabel
\renewcommand*{\CustomAbbreviationFields}{%
name={\glxtrfootnotedesname},

```

```

sort={\glxtrfootnotedesort},
first={\protect\glsfirstabbrvscfont{\the\glsshorttok}},%
firstplural={\protect\glsfirstabbrvscfont{\the\glsshortpltok}},%
text={\protect\glsabbrvscfont{\the\glsshorttok}},%
plural={\protect\glsabbrvscfont{\the\glsshortpltok}}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\csdef{glxtrpostlink\glscategorylabel}{%
\glxtrifwasfirstuse
{%
\glxtrdopostpunc{\protect\glxtrabbrvfootnote{\glslabel}%
{\glsfirstlongfootnotefont{\glstrylong{\glslabel}}}}}%
}%
}%
\glshasattribute{\the\glslabeltok}{regular}%
{%
\glsssetAttribute{\the\glslabeltok}{regular}{false}%
}%
}%
\renewcommand*{\glxtrsetupfulldefs}{%
\let\glxtrifwasfirstuse\@secondoftwo
}%
}%
{%
\GlsXtrUseAbbrStyleFmts{short-sc-postfootnote}%
}
\newcommand*{\glxtrsmfont}[1]{\textsmaller{#1}}
\newcommand*{\glsabbrvsmfont}{\glxtrsmfont}
\newcommand*{\glxtrfirstsmfont}[1]{\glsabbrvsmfont{#1}}
\newcommand*{\glsfirstabbrvsmfont}{\glxtrfirstsmfont}
\newcommand*{\glxtrsmsuffix}{\glxtrabbrvpluralsuffix}
\newabbreviationstyle{long-short-sm}%
{%
\glxtrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
\renewcommand*{\CustomAbbreviationFields}{%
name={\glxtrlongshortname},
sort={\the\glsshorttok},
first={\protect\glsfirstlongdefaultfont{\the\glslongtok}%
\protect\glxtrfullsep{\the\glslabeltok}%
\glxtrparen{\protect\glsfirstabbrvsmfont{\the\glsshorttok}}},%
firstplural={\protect\glsfirstlongdefaultfont{\the\glslongpltok}%
\protect\glxtrfullsep{\the\glslabeltok}%
\glxtrparen{\protect\glsfirstabbrvsmfont{\the\glsshortpltok}}},%
text={\protect\glsabbrvsmfont{\the\glsshorttok}},%
plural={\protect\glsabbrvsmfont{\the\glsshortpltok}},%
description={\the\glslongtok}}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glshasattribute{\the\glslabeltok}{regular}%
{%

```

```

\glsssetAttribute{\the\glslabeltok}{regular}{false}%
}%
{}%
}%
}%
{%
\renewcommand*\glsabbrvfont[1]{\glsabbrvsmfont{##1}}%
\renewcommand*\glsfirstabbrvfont[1]{\glsfirstabbrvsmfont{##1}}%
\renewcommand*\abbrvpluralsuffix{\glsxtrsmsuffix}%
\renewcommand*\glsfirstlongfont[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*\glslongfont[1]{\glslongdefaultfont{##1}}%
\renewcommand*\glsxtrfullformat[2]{%
\glsfirstlongdefaultfont{\glsaccesslong{##1}\ifglsxtrininsertinside##2\fi}%
\ifglsxtrininsertinside\else##2\fi
\glsxtrfullsep{##1}%
\glsxtrparen{\glsfirstabbrvsmfont{\glsaccessshort{##1}}}%
}%
\renewcommand*\glsxtrfullplformat[2]{%
\glsfirstlongdefaultfont{\glsaccesslongpl{##1}\ifglsxtrininsertinside##2\fi}%
\ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
\glsxtrparen{\glsfirstabbrvsmfont{\glsaccessshortpl{##1}}}%
}%
\renewcommand*\Glsxtrfullformat[2]{%
\glsfirstlongdefaultfont{\Glsaccesslong{##1}\ifglsxtrininsertinside##2\fi}%
\ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
\glsxtrparen{\glsfirstabbrvsmfont{\glsaccessshort{##1}}}%
}%
\renewcommand*\Glsxtrfullplformat[2]{%
\glsfirstlongdefaultfont{\Glsaccesslongpl{##1}\ifglsxtrininsertinside##2\fi}%
\ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
\glsxtrparen{\glsfirstabbrvsmfont{\glsaccessshortpl{##1}}}%
}%
}
\newabbreviationstyle{long-short-sm-desc}%
{%
\glsxtrAccSuppAbbrSetTextShortAttrs\glscategorylabel
\renewcommand*\CustomAbbreviationFields{%
name={\glsxtrlongshortdescname},
sort={\glsxtrlongshortdescsort},%
first={\protect\glsfirstlongdefaultfont{\the\glslongtok}%
\protect\glsxtrfullsep{\the\glslabeltok}%
\glsxtrparen{\protect\glsfirstabbrvsmfont{\the\glsshorttok}}},%
firstplural={\protect\glsfirstlongdefaultfont{\the\glslongpltok}%
\protect\glsxtrfullsep{\the\glslabeltok}%
\glsxtrparen{\protect\glsfirstabbrvsmfont{\the\glsshortpltok}}},%
text={\protect\glsabbrvsmfont{\the\glsshorttok}},%
plural={\protect\glsabbrvsmfont{\the\glsshortpltok}}%
}%
\renewcommand*\GlsXtrPostNewAbbreviation{%
\glshasattribute{\the\glslabeltok}{regular}%

```



```

    {%
      \glsssetAttribute{\the\glslabeltok}{regular}{false}%
    }%
  {%
  }%
}%
{%
  \GlsXtrUseAbbrStyleFmts{long-short-sm}%
}
\newabbreviationstyle{short-sm-long}%
{%
  \glsxtrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glsxtrshortlongname},
    sort={\the\glssshorttok},
    description={\the\glslongtok},%
    first={\protect\glsfirstabbrvsmfont{\the\glssshorttok}%
      \protect\glsxtrfullsep{\the\glslabeltok}%
      \glsxtrparen{\protect\glsfirstlongdefaultfont{\the\glslongtok}}},%
    firstplural={\protect\glsfirstabbrvsmfont{\the\glssshortpltok}%
      \protect\glsxtrfullsep{\the\glslabeltok}%
      \glsxtrparen{\protect\glsfirstlongdefaultfont{\the\glslongpltok}}},%
    text={\protect\glsabbrvsmfont{\the\glssshorttok}},%
    plural={\protect\glsabbrvsmfont{\the\glssshortpltok}}}%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \glshasattribute{\the\glslabeltok}{regular}%
    {%
      \glsssetAttribute{\the\glslabeltok}{regular}{false}%
    }%
    {}%
  }%
}%
{%
  \renewcommand*\glsabbrvfont[1]{\glsabbrvsmfont{##1}}%
  \renewcommand*\glsfirstabbrvfont[1]{\glsfirstabbrvsmfont{##1}}%
  \renewcommand*{\abbrvpluralsuffix}{\glsxtrsmsuffix}%
  \renewcommand*\glsfirstlongfont[1]{\glsfirstlongdefaultfont{##1}}%
  \renewcommand*\glslongfont[1]{\glslongdefaultfont{##1}}%
  \renewcommand*\glsxtrfullformat[2]{%
    \glsfirstabbrvsmfont{\glsaccessshort{##1}\ifglsxtrininsertinside##2\fi}%
    \ifglsxtrininsertinside\else##2\fi
    \glsxtrfullsep{##1}%
    \glsxtrparen{\glsfirstlongdefaultfont{\glsaccesslong{##1}}}%
  }%
  \renewcommand*\glsxtrfullplformat[2]{%
    \glsfirstabbrvsmfont{\glsaccessshortpl{##1}\ifglsxtrininsertinside##2\fi}%
    \ifglsxtrininsertinside\else##2\fi
    \glsxtrfullsep{##1}%
    \glsxtrparen{\glsfirstlongdefaultfont{\glsaccesslongpl{##1}}}%
  }%
}

```

```

\renewcommand*{\Glsxtrfullformat}[2]{%
  \glsfirstabbrvsmfont{\Glsaccessshort{##1}\ifglxtrinsertinside##2\fi}%
  \ifglxtrinsertinside\else##2\fi\glsxtrfullsep{##1}%
  \glsxtrparen{\glsfirstlongdefaultfont{\Glsaccesslong{##1}}}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \glsfirstabbrvsmfont{\Glsaccessshortpl{##1}\ifglxtrinsertinside##2\fi}%
  \ifglxtrinsertinside\else##2\fi\glsxtrfullsep{##1}%
  \glsxtrparen{\glsfirstlongdefaultfont{\Glsaccesslongpl{##1}}}%
}%
}
\newabbreviationstyle{short-sm-long-desc}%
{%
  \glsxtrAccSuppAbbrSetTextShortAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glsxtrshortlongdescname},
    sort={\glsxtrshortlongdescsort},
    first={\protect\glsfirstabbrvsmfont{\the\glsshorttok}}%
      \protect\glsxtrfullsep{\the\glslabeltok}}%
      \glsxtrparen{\protect\glsfirstlongdefaultfont{\the\glslongtok}}},%
    firstplural={\protect\glsfirstabbrvsmfont{\the\glsshortpltok}}%
      \protect\glsxtrfullsep{\the\glslabeltok}}%
      \glsxtrparen{\protect\glsfirstlongdefaultfont{\the\glslongpltok}}},%
    text={\protect\glsabbrvsmfont{\the\glsshorttok}},%
    plural={\protect\glsabbrvsmfont{\the\glsshortpltok}}%
  }%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \glshasattribute{\the\glslabeltok}{regular}%
    {%
      \glissetattribute{\the\glslabeltok}{regular}{false}%
    }%
  }%
}%
{%
  \GlsXtrUseAbbrStyleFmts{short-sm-long}%
}
\newabbreviationstyle{short-sm}%
{%
  \glsxtrAccSuppAbbrSetNameLongAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glsxtrshortnolongname},
    sort={\the\glsshorttok},
    first={\protect\glsfirstabbrvsmfont{\the\glsshorttok}},
    firstplural={\protect\glsfirstabbrvsmfont{\the\glsshortpltok}},
    text={\protect\glsabbrvsmfont{\the\glsshorttok}},
    plural={\protect\glsabbrvsmfont{\the\glsshortpltok}},
    description={\the\glslongtok}}%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \glissetattribute{\the\glslabeltok}{regular}{true}}%
}

```

```

}%
{%
\renewcommand*\glsabbrvfont[1]{\glsabbrvsmfont{##1}}%
\renewcommand*\glsfirstabbrvfont[1]{\glsfirstabbrvsmfont{##1}}%
\renewcommand*\abbrvpluralsuffix{\glsxtrmsuffix}%
\renewcommand*\glsfirstlongfont[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*\glslongfont[1]{\glslongdefaultfont{##1}}%
\renewcommand*\glsxtrinlinefullformat}[2]{%
\protect\glsfirstabbrvsmfont{\glsaccessshort{##1}}%
\ifglsxtrininsertinside##2\fi}%
\ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
\glsxtrparen{\glsfirstlongdefaultfont{\glsaccesslong{##1}}}%
}%
\renewcommand*\glsxtrinlinefullplformat}[2]{%
\protect\glsfirstabbrvsmfont{\glsaccessshortpl{##1}}%
\ifglsxtrininsertinside##2\fi}%
\ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
\glsxtrparen{\glsfirstlongdefaultfont{\glsaccesslongpl{##1}}}%
}%
\renewcommand*\Glsxtrinlinefullformat}[2]{%
\protect\glsfirstabbrvsmfont{\Glsaccessshort{##1}}%
\ifglsxtrininsertinside##2\fi}%
\ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
\glsxtrparen{\glsfirstlongdefaultfont{\glsaccesslong{##1}}}%
}%
\renewcommand*\Glsxtrinlinefullplformat}[2]{%
\protect\glsfirstabbrvsmfont{\Glsaccessshortpl{##1}}%
\ifglsxtrininsertinside##2\fi}%
\ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
\glsxtrparen{\glsfirstlongdefaultfont{\glsaccesslongpl{##1}}}%
}%
\renewcommand*\glsxtrfullformat}[2]{%
\glsfirstabbrvsmfont{\glsaccessshort{##1}}\ifglsxtrininsertinside##2\fi}%
\ifglsxtrininsertinside\else##2\fi
}%
\renewcommand*\glsxtrfullplformat}[2]{%
\glsfirstabbrvsmfont{\glsaccessshortpl{##1}}\ifglsxtrininsertinside##2\fi}%
\ifglsxtrininsertinside\else##2\fi
}%
\renewcommand*\Glsxtrfullformat}[2]{%
\glsfirstabbrvsmfont{\glsaccessshort{##1}}\ifglsxtrininsertinside##2\fi}%
\ifglsxtrininsertinside\else##2\fi
}%
\renewcommand*\Glsxtrfullplformat}[2]{%
\glsfirstabbrvsmfont{\glsaccessshortpl{##1}}\ifglsxtrininsertinside##2\fi}%
\ifglsxtrininsertinside\else##2\fi
}%
}
\letabbreviationstyle{short-sm-nolong}{short-sm}
\newabbreviationstyle{short-sm-desc}%

```

```

{%
\glstrAccSuppAbbrSetNoLongAttrs\glscategorylabel
\renewcommand*{\CustomAbbreviationFields}{%
  name={\glstrshortdescname},
  sort={\the\glsshorttok},
  first={\protect\glsfirstabbrvsmfont{\the\glsshorttok}},
  firstplural={\protect\glsfirstabbrvsmfont{\the\glsshortpltok}},
  text={\protect\glsabbrvsmfont{\the\glsshorttok}},
  plural={\protect\glsabbrvsmfont{\the\glsshortpltok}}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glssetattribute{\the\glslabeltok}{regular}{true}}%
}%
{%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvsmfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvsmfont{##1}}%
\renewcommand*{\abbrvpluralsuffix}{\glstrmsuffix}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%
\renewcommand*{\glstrinlinefullformat}[2]{%
  \glsfirstabbrvsmfont{\glsaccessshort{##1}\ifglstrinsertinside##2\fi}%
  \ifglstrinsertinside\else##2\fi\glstrfullsep{##1}%
  \glstrparen{\glsfirstlongdefaultfont{\glsaccesslong{##1}}}%
}%
\renewcommand*{\glstrinlinefullplformat}[2]{%
  \glsfirstabbrvsmfont{\glsaccessshortpl{##1}\ifglstrinsertinside##2\fi}%
  \ifglstrinsertinside\else##2\fi\glstrfullsep{##1}%
  \glstrparen{\glsfirstlongdefaultfont{\glsaccesslongpl{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \glsfirstabbrvsmfont{\Glsaccessshort{##1}\ifglstrinsertinside##2\fi}%
  \ifglstrinsertinside\else##2\fi\glstrfullsep{##1}%
  \glstrparen{\glsfirstlongdefaultfont{\glsaccesslong{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \glsfirstabbrvsmfont{\Glsaccessshortpl{##1}\ifglstrinsertinside##2\fi}%
  \ifglstrinsertinside\else##2\fi\glstrfullsep{##1}%
  \glstrparen{\glsfirstlongdefaultfont{\glsaccesslongpl{##1}}}%
}%
\renewcommand*{\glstrfullformat}[2]{%
  \glsfirstabbrvsmfont{\glsaccessshort{##1}\ifglstrinsertinside##2\fi}%
  \ifglstrinsertinside\else##2\fi
}%
\renewcommand*{\glstrfullplformat}[2]{%
  \glsfirstabbrvsmfont{\glsaccessshortpl{##1}\ifglstrinsertinside##2\fi}%
  \ifglstrinsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \glsfirstabbrvsmfont{\glsaccessshort{##1}\ifglstrinsertinside##2\fi}%
  \ifglstrinsertinside\else##2\fi
}%

```

```

\renewcommand*{\Glsxtrfullplformat}[2]{%
  \glsfirstabbrvsmfont{\glsaccessshortpl{##1}\ifglxtrinsertinside##2\fi}%
  \ifglxtrinsertinside\else##2\fi
}%
}
\letabbreviationstyle{short-sm-nolong-desc}{short-sm-desc}
\newabbreviationstyle{nolong-short-sm}%
{%
  \GlsXtrUseAbbrStyleSetup{short-sm-nolong}%
}%
{%
  \GlsXtrUseAbbrStyleFmts{short-sm-nolong}%
  \renewcommand*{\glxtrinlinefullformat}[2]{%
    \protect\glsfirstlongdefaultfont{\glsaccesslong{##1}%
      \ifglxtrinsertinside##2\fi}%
    \ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
    \glxtrparen{\glsfirstabbrvsmfont{\glsaccessshort{##1}}}%
  }%
  \renewcommand*{\glxtrinlinefullplformat}[2]{%
    \protect\glsfirstlongdefaultfont{\glsaccesslongpl{##1}%
      \ifglxtrinsertinside##2\fi}%
    \ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
    \glxtrparen{\glsfirstabbrvsmfont{\glsaccessshortpl{##1}}}%
  }%
  \renewcommand*{\Glsxtrinlinefullformat}[2]{%
    \protect\glsfirstlongdefaultfont{\Glsaccesslong{##1}%
      \ifglxtrinsertinside##2\fi}%
    \ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
    \glxtrparen{\glsfirstabbrvsmfont{\glsaccessshort{##1}}}%
  }%
  \renewcommand*{\Glsxtrinlinefullplformat}[2]{%
    \protect\glsfirstlongdefaultfont{\Glsaccesslongpl{##1}%
      \ifglxtrinsertinside##2\fi}%
    \ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
    \glxtrparen{\glsfirstabbrvsmfont{\glsaccessshortpl{##1}}}%
  }%
}
\newabbreviationstyle{long-noshort-sm}%
{%
  \glxtrAccSuppAbbrSetNameShortAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glxtrlongnoshortname},
    sort={\the\glsshorttok},
    first={\protect\glsfirstlongdefaultfont{\the\glslongtok}},
    firstplural={\protect\glsfirstlongdefaultfont{\the\glslongpltok}},
    text={\protect\glslongdefaultfont{\the\glslongtok}},
    plural={\protect\glslongdefaultfont{\the\glslongpltok}},%
    description={\the\glslongtok}%
  }%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%

```

```

\glssetattribute{\the\glslabeltok}{regular}{true}}%
}%
{%
\renewcommand*\glsabbrvfont[1]{\glsabbrvsmfont{##1}}%
\renewcommand*\glsfirstabbrvfont[1]{\glsfirstabbrvsmfont{##1}}%
\renewcommand*\{abbrvpluralsuffix}{\glsxtrsmsuffix}%
\renewcommand*\{glsfirstlongfont}[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*\{glslongfont}[1]{\glslongdefaultfont{##1}}%
\renewcommand*\{glsxtrsubsequentfmt}[2]{%
\glslongdefaultfont{\glsaccesslong{##1}\ifglsxtrininsertinside ##2\fi}%
\ifglsxtrininsertinside \else##2\fi
}%
\renewcommand*\{glsxtrsubsequentplfmt}[2]{%
\glslongdefaultfont{\glsaccesslongpl{##1}\ifglsxtrininsertinside ##2\fi}%
\ifglsxtrininsertinside \else##2\fi
}%
\renewcommand*\{Glsxtrsubsequentfmt}[2]{%
\glslongdefaultfont{\Glsaccesslong{##1}\ifglsxtrininsertinside ##2\fi}%
\ifglsxtrininsertinside \else##2\fi
}%
\renewcommand*\{Glsxtrsubsequentplfmt}[2]{%
\glslongdefaultfont{\Glsaccesslongpl{##1}\ifglsxtrininsertinside ##2\fi}%
\ifglsxtrininsertinside \else##2\fi
}%
\renewcommand*\{glsxtrinlinefullformat}[2]{%
\glsfirstlongdefaultfont{\glsaccesslong{##1}\ifglsxtrininsertinside##2\fi}%
\ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
\glsxtrparen{\protect\glsfirstabbrvsmfont{\glsaccessshort{##1}}}%
}%
\renewcommand*\{glsxtrinlinefullplformat}[2]{%
\glsfirstlongdefaultfont{\glsaccesslongpl{##1}\ifglsxtrininsertinside##2\fi}%
\ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
\glsxtrparen{\protect\glsfirstabbrvsmfont{\glsaccessshortpl{##1}}}%
}%
\renewcommand*\{Glsxtrinlinefullformat}[2]{%
\glsfirstlongdefaultfont{\Glsaccesslong{##1}\ifglsxtrininsertinside##2\fi}%
\ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
\glsxtrparen{\protect\glsfirstabbrvsmfont{\glsaccessshort{##1}}}%
}%
\renewcommand*\{Glsxtrinlinefullplformat}[2]{%
\glsfirstlongdefaultfont{\Glsaccesslongpl{##1}\ifglsxtrininsertinside##2\fi}%
\ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
\glsxtrparen{\protect\glsfirstabbrvsmfont{\glsaccessshortpl{##1}}}%
}%
\renewcommand*\{glsxtrfullformat}[2]{%
\glsfirstlongdefaultfont{\glsaccesslong{##1}\ifglsxtrininsertinside##2\fi}%
\ifglsxtrininsertinside\else##2\fi
}%
\renewcommand*\{glsxtrfullplformat}[2]{%
\glsfirstlongdefaultfont{\glsaccesslongpl{##1}\ifglsxtrininsertinside##2\fi}%

```

```

\ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
\glsfirstlongdefaultfont{\glsaccesslong{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
\glsfirstlongdefaultfont{\glsaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
}%
}
\@glxtr@deprecated@abbrstyle{long-sm}{long-noshort-sm}
\newabbreviationstyle{long-noshort-sm-desc}%
{%
\GlsXtrUseAbbrStyleSetup{long-noshort-desc}%
}%
{%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvsmfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvsmfont{##1}}%
\renewcommand*{\abbrvpluralsuffix}{\glsxtrsmsuffix}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%
\renewcommand*{\glsxtrsubsequentfmt}[2]{%
\glslongdefaultfont{\glsaccesslong{##1}\ifglxtrinsertinside ##2\fi}%
\ifglxtrinsertinside \else##2\fi
}%
\renewcommand*{\glsxtrsubsequentplfmt}[2]{%
\glslongdefaultfont{\glsaccesslongpl{##1}\ifglxtrinsertinside ##2\fi}%
\ifglxtrinsertinside \else##2\fi
}%
\renewcommand*{\Glsxtrsubsequentfmt}[2]{%
\glslongdefaultfont{\Glsaccesslong{##1}\ifglxtrinsertinside ##2\fi}%
\ifglxtrinsertinside \else##2\fi
}%
\renewcommand*{\Glsxtrsubsequentplfmt}[2]{%
\glslongdefaultfont{\Glsaccesslongpl{##1}\ifglxtrinsertinside ##2\fi}%
\ifglxtrinsertinside \else##2\fi
}%
\renewcommand*{\glsxtrinlinefullformat}[2]{%
\glsfirstlongdefaultfont{\glsaccesslong{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi\glsxtrfullsep{##1}%
\glsxtrparen{\protect\glsfirstabbrvsmfont{\glsaccessshort{##1}}}%
}%
\renewcommand*{\glsxtrinlinefullplformat}[2]{%
\glsfirstlongdefaultfont{\glsaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi\glsxtrfullsep{##1}%
\glsxtrparen{\protect\glsfirstabbrvsmfont{\glsaccessshortpl{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
\glsfirstlongdefaultfont{\Glsaccesslong{##1}\ifglxtrinsertinside##2\fi}%

```

```

        \ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
        \glxtrparen{\protect\glsfirstabbrvsmfont{\glssaccessshort{##1}}}%
    }%
    \renewcommand*{\Glsxtrinlinefullplformat}[2]{%
        \glsfirstlongdefaultfont{\Glsaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
        \ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
        \glxtrparen{\protect\glsfirstabbrvsmfont{\glssaccessshortpl{##1}}}%
    }%
    \renewcommand*{\glxtrfullformat}[2]{%
        \glsfirstlongdefaultfont{\glssaccesslong{##1}\ifglxtrinsertinside##2\fi}%
        \ifglxtrinsertinside\else##2\fi
    }%
    \renewcommand*{\glxtrfullplformat}[2]{%
        \glsfirstlongdefaultfont{\glssaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
        \ifglxtrinsertinside\else##2\fi
    }%
    \renewcommand*{\Glsxtrfullformat}[2]{%
        \glsfirstlongdefaultfont{\glssaccesslong{##1}\ifglxtrinsertinside##2\fi}%
        \ifglxtrinsertinside\else##2\fi
    }%
    \renewcommand*{\Glsxtrfullplformat}[2]{%
        \glsfirstlongdefaultfont{\glssaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
        \ifglxtrinsertinside\else##2\fi
    }%
}
\@glxtr@deprecated@abbrstyle{long-desc-sm}{long-noshort-sm-desc}
\newabbreviationstyle{short-sm-footnote}%
{%
    \glxtrAccSuppAbbrSetNoLongAttrs\glscategorylabel
    \renewcommand*{\CustomAbbreviationFields}{%
        name={\glxtrfootnotename},
        sort={\the\glssshorttok},
        description={\the\glslongtok},%
        first={\protect\glsfirstabbrvsmfont{\the\glssshorttok}%
            \protect\glxtrabbrvfootnote{\the\glslabeltok}%
            {\protect\glsfirstlongfootnotefont{\the\glslongtok}}},%
        firstplural={\protect\glsfirstabbrvsmfont{\the\glssshortpltok}%
            \protect\glxtrabbrvfootnote{\the\glslabeltok}%
            {\protect\glsfirstlongfootnotefont{\the\glslongpltok}}},%
        text={\protect\glssabbrvsmfont{\the\glssshorttok}},%
        plural={\protect\glssabbrvsmfont{\the\glssshortpltok}}}%
    \renewcommand*{\GlsXtrPostNewAbbreviation}{%
        \glsssetAttribute{\the\glslabeltok}{nohyperfirst}{true}%
        \glsshasattribute{\the\glslabeltok}{regular}%
        {%
            \glsssetAttribute{\the\glslabeltok}{regular}{false}%
        }%
        {}%
    }%
}%

```



```

{%
\renewcommand*\glsabbrvfont[1]{\glsabbrvsmfont{##1}}%
\renewcommand*\glsfirstabbrvfont[1]{\glsfirstabbrvsmfont{##1}}%
\renewcommand*\abbrvpluralsuffix{\glsxtrmsuffix}%
\renewcommand*\glsfirstlongfont[1]{\glsfirstlongfootnotefont{##1}}%
\renewcommand*\glslongfont[1]{\glslongfootnotefont{##1}}%
\renewcommand*\glsxtrfullformat[2]{%
\glsfirstabbrvsmfont{\glsaccessshort{##1}\ifglsxtrininsertinside##2\fi}%
\ifglsxtrininsertinside\else##2\fi
\protect\glsxtrabbrvfootnote{##1}%
{\glsfirstlongfootnotefont{\glsaccesslong{##1}}}%
}%
\renewcommand*\glsxtrfullplformat[2]{%
\glsfirstabbrvsmfont{\glsaccessshortpl{##1}\ifglsxtrininsertinside##2\fi}%
\ifglsxtrininsertinside\else##2\fi
\protect\glsxtrabbrvfootnote{##1}%
{\glsfirstlongfootnotefont{\glsaccesslongpl{##1}}}%
}%
\renewcommand*\Glsxtrfullformat[2]{%
\glsfirstabbrvsmfont{\Glsaccessshort{##1}\ifglsxtrininsertinside##2\fi}%
\ifglsxtrininsertinside\else##2\fi
\protect\glsxtrabbrvfootnote{##1}%
{\glsfirstlongfootnotefont{\glsaccesslong{##1}}}%
}%
\renewcommand*\Glsxtrfullplformat[2]{%
\glsfirstabbrvsmfont{\Glsaccessshortpl{##1}\ifglsxtrininsertinside##2\fi}%
\ifglsxtrininsertinside\else##2\fi
\protect\glsxtrabbrvfootnote{##1}%
{\glsfirstlongfootnotefont{\glsaccesslongpl{##1}}}%
}%
\renewcommand*\glsxtrininlinefullformat[2]{%
\glsfirstabbrvsmfont{\glsaccessshort{##1}\ifglsxtrininsertinside##2\fi}%
\ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
\glsxtrparen{\glsfirstlongfootnotefont{\glsaccesslong{##1}}}%
}%
\renewcommand*\glsxtrininlinefullplformat[2]{%
\glsfirstabbrvsmfont{\glsaccessshortpl{##1}\ifglsxtrininsertinside##2\fi}%
\ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
\glsxtrparen{\glsfirstlongfootnotefont{\glsaccesslongpl{##1}}}%
}%
\renewcommand*\Glsxtrininlinefullformat[2]{%
\glsfirstabbrvsmfont{\Glsaccessshort{##1}\ifglsxtrininsertinside##2\fi}%
\ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
\glsxtrparen{\glsfirstlongfootnotefont{\glsaccesslong{##1}}}%
}%
\renewcommand*\Glsxtrininlinefullplformat[2]{%
\glsfirstabbrvsmfont{\Glsaccessshortpl{##1}\ifglsxtrininsertinside##2\fi}%
\ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
\glsxtrparen{\glsfirstlongfootnotefont{\glsaccesslongpl{##1}}}%
}%
}

```

```

}
\@glxtr@deprecated@abbrstyle{footnote-sm}{short-sm-footnote}
\newabbreviationstyle{short-sm-footnote-desc}%
{%
  \glxtrAccSuppAbbrSetNameLongAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glxtrfootnotedesname},
    sort={\glxtrfootnotedesort},
    first={\protect\glsfirstabbrvsmfont{\the\glsshorttok}%
      \protect\glxtrabbrvfootnote{\the\glslabeltok}%
      {\protect\glsfirstlongfootnotefont{\the\glslongtok}}},%
    firstplural={\protect\glsfirstabbrvsmfont{\the\glsshortpltok}%
      \protect\glxtrabbrvfootnote{\the\glslabeltok}%
      {\protect\glsfirstlongfootnotefont{\the\glslongpltok}}},%
    text={\protect\glsabbrvsmfont{\the\glsshorttok}},%
    plural={\protect\glsabbrvsmfont{\the\glsshortpltok}}}%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \glsssetAttribute{\the\glslabeltok}{nohyperfirst}{true}%
    \glshasattribute{\the\glslabeltok}{regular}%
    {%
      \glsssetAttribute{\the\glslabeltok}{regular}{false}%
    }%
    {}%
  }%
}%
{%
  \GlsXtrUseAbbrStyleFmts{short-sm-footnote}%
}
\newabbreviationstyle{short-sm-postfootnote}%
{%
  \glxtrAccSuppAbbrSetNoLongAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glxtrfootnotename},
    sort={\the\glsshorttok},
    description={\the\glslongtok},%
    first={\protect\glsfirstabbrvsmfont{\the\glsshorttok}},%
    firstplural={\protect\glsfirstabbrvsmfont{\the\glsshortpltok}},%
    text={\protect\glsabbrvsmfont{\the\glsshorttok}},%
    plural={\protect\glsabbrvsmfont{\the\glsshortpltok}}}%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \csdef{glxtrpostlink\glscategorylabel}{%
      \glxtrifwasfirstuse
      {%
        \glxtrdopostpunc{\protect\glxtrabbrvfootnote{\glslabel}%
          {\glsfirstlongfootnotefont{\glstrylong{\glslabel}}}}}%
      }%
      {}%
    }%
    \glshasattribute{\the\glslabeltok}{regular}%
    {%

```

```

\glsssetAttribute{\the\glslabeltok}{regular}{false}%
}%
{}%
}%
\renewcommand*{\glstrsetupfulldefs}{%
\let\glstrifwasfirstuse\@secondoftwo
}%
}%
{%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvsmfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvsmfont{##1}}%
\renewcommand*{\abbrvpluralsuffix}{\glstrsmsuffix}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongfootnotefont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongfootnotefont{##1}}%
\renewcommand*{\glstrfullformat}[2]{%
\glsfirstabbrvsmfont{\glsaccessshort{##1}\ifglstrinsertinside##2\fi}%
\ifglstrinsertinside\else##2\fi
}%
\renewcommand*{\glstrfullplformat}[2]{%
\glsfirstabbrvsmfont{\glsaccessshortpl{##1}\ifglstrinsertinside##2\fi}%
\ifglstrinsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
\glsfirstabbrvsmfont{\Glsaccessshort{##1}\ifglstrinsertinside##2\fi}%
\ifglstrinsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
\glsfirstabbrvsmfont{\Glsaccessshortpl{##1}\ifglstrinsertinside##2\fi}%
\ifglstrinsertinside\else##2\fi
}%
\renewcommand*{\glstrinlinefullformat}[2]{%
\glsfirstabbrvsmfont{\glsaccessshort{##1}\ifglstrinsertinside##2\fi}%
\ifglstrinsertinside\else##2\fi\glstrfullsep{##1}%
\glstrparen{\glsfirstlongfootnotefont{\glsaccesslong{##1}}}%
}%
\renewcommand*{\glstrinlinefullplformat}[2]{%
\glsfirstabbrvsmfont{\glsaccessshortpl{##1}\ifglstrinsertinside##2\fi}%
\ifglstrinsertinside\else##2\fi\glstrfullsep{##1}%
\glstrparen{\glsfirstlongfootnotefont{\glsaccesslongpl{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
\glsfirstabbrvsmfont{\Glsaccessshort{##1}\ifglstrinsertinside##2\fi}%
\ifglstrinsertinside\else##2\fi\glstrfullsep{##1}%
\glstrparen{\glsfirstlongfootnotefont{\glsaccesslong{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
\glsfirstabbrvsmfont{\Glsaccessshortpl{##1}\ifglstrinsertinside##2\fi}%
\ifglstrinsertinside\else##2\fi\glstrfullsep{##1}%
\glstrparen{\glsfirstlongfootnotefont{\glsaccesslongpl{##1}}}%
}%

```

```

}
\@glxtr@deprecated@abbrstyle{postfootnote-sm}{short-sm-postfootnote}
\newabbreviationstyle{short-sm-postfootnote-desc}%
{%
  \glxtrAccSuppAbbrSetNameLongAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glxtrfootnotedesname},
    sort={\glxtrfootnotedesort},
    first={\protect\glsfirstabbrvsmfont{\the\glsshorttok}},%
    firstplural={\protect\glsfirstabbrvsmfont{\the\glsshortpltok}},%
    text={\protect\glsabbrvsmfont{\the\glsshorttok}},%
    plural={\protect\glsabbrvsmfont{\the\glsshortpltok}}}%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \csdef{glxtrpostlink\glscategorylabel}{%
      \glxtrifwasfirstuse
      {%
        \glxtrdopostpunc{\protect\glxtrabbrvfootnote{\glslabel}%
          {\glsfirstlongfootnotefont{\glstrylong{\glslabel}}}}}%
      }%
    }%
    \glshasattribute{\the\glslabeltok}{regular}%
    {%
      \glsssetAttribute{\the\glslabeltok}{regular}{false}%
    }%
    {}%
  }%
  \renewcommand*{\glxtrsetupfulldefs}{%
    \let\glxtrifwasfirstuse\@secondoftwo
  }%
}%
\GlsXtrUseAbbrStyleFmts{short-sm-postfootnote}%
}
\newcommand*{\glsabbrvemfont}[1]{\emph{#1}}%
\newcommand*{\glsfirstabbrvemfont}[1]{\glsabbrvemfont{#1}}%
\newcommand*{\glxtremsuffix}{\glxtrabbrvpluralsuffix}
\newcommand*{\glsfirstlongemfont}[1]{\glslongemfont{#1}}%
\newcommand*{\glslongemfont}[1]{\emph{#1}}%
\newabbreviationstyle{long-short-em}%
{%
  \glxtrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glxtrlongshortname},
    sort={\the\glsshorttok},
    first={\protect\glsfirstlongdefaultfont{\the\glslongtok}%
      \protect\glxtrfullsep{\the\glslabeltok}%
      \glxtrparen{\protect\glsfirstabbrvemfont{\the\glsshorttok}}},%
    firstplural={\protect\glsfirstlongdefaultfont{\the\glslongpltok}%
      \protect\glxtrfullsep{\the\glslabeltok}%

```

```

\glxtrparen{\protect\glsfirstabbrvemfont{\the\glsshortpltok}}},%
text={\protect\glsabbrvemfont{\the\glsshorttok}},%
plural={\protect\glsabbrvemfont{\the\glsshortpltok}},%
description={\the\glslongtok}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glsattribute{\the\glslabeltok}{regular}%
{%
\glssetattribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%
{%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvemfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvemfont{##1}}%
\renewcommand*{\abbrvpluralsuffix}{\glxtremsuffix}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%
\renewcommand*{\glxtrfullformat}[2]{%
\glsfirstlongdefaultfont{\glsaccesslong{##1}\ifglxtrininsertinside##2\fi}%
\ifglxtrininsertinside\else##2\fi
\glxtrfullsep{##1}%
\glxtrparen{\glsfirstabbrvemfont{\glsaccessshort{##1}}}%
}%
\renewcommand*{\glxtrfullplformat}[2]{%
\glsfirstlongdefaultfont{\glsaccesslongpl{##1}\ifglxtrininsertinside##2\fi}%
\ifglxtrininsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\glsfirstabbrvemfont{\glsaccessshortpl{##1}}}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
\glsfirstlongdefaultfont{\Glsaccesslong{##1}\ifglxtrininsertinside##2\fi}%
\ifglxtrininsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\glsfirstabbrvemfont{\glsaccessshort{##1}}}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
\glsfirstlongdefaultfont{\Glsaccesslongpl{##1}\ifglxtrininsertinside##2\fi}%
\ifglxtrininsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\glsfirstabbrvemfont{\glsaccessshortpl{##1}}}%
}%
}
\newabbreviationstyle{long-short-em-desc}%
{%
\glxtrAccSuppAbbrSetTextShortAttrs\glscategorylabel
\renewcommand*{\CustomAbbreviationFields}{%
name={\glxtrlongshortdescname},
sort={\glxtrlongshortdescsort},%
first={\protect\glsfirstlongdefaultfont{\the\glslongtok}%
\protect\glxtrfullsep{\the\glslabeltok}}%
\glxtrparen{\protect\glsfirstabbrvemfont{\the\glsshorttok}}},%
firstplural={\protect\glsfirstlongdefaultfont{\the\glslongpltok}}%
}

```

```

\protect\glxtrfullsep{\the\glslabeltok}%
\glxtrparen{\protect\glsfirstabbrvemfont{\the\glsshortpltok}}},%
text={\protect\glsabbrvemfont{\the\glsshorttok}},%
plural={\protect\glsabbrvemfont{\the\glsshortpltok}}%
}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glshasattribute{\the\glslabeltok}{regular}%
{%
\glissetattribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%
{%
\GlsXtrUseAbbrStyleFmts{long-short-em}%
}
\newabbreviationstyle{long-em-short-em}%
{%
\glxtrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
\renewcommand*{\CustomAbbreviationFields}{%
name={\glxtrlongshortname},
sort={\the\glsshorttok},
first={\protect\glsfirstlongemfont{\the\glslongtok}%
\protect\glxtrfullsep{\the\glslabeltok}%
\glxtrparen{\protect\glsfirstabbrvemfont{\the\glsshorttok}}},%
firstplural={\protect\glsfirstlongemfont{\the\glslongpltok}%
\protect\glxtrfullsep{\the\glslabeltok}%
\glxtrparen{\protect\glsfirstabbrvemfont{\the\glsshortpltok}}},%
text={\protect\glsabbrvemfont{\the\glsshorttok}},%
plural={\protect\glsabbrvemfont{\the\glsshortpltok}},%
description={\protect\glslongemfont{\the\glslongtok}}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glshasattribute{\the\glslabeltok}{regular}%
{%
\glissetattribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%
}%
{%
\renewcommand*{\abbrvpluralsuffix}{\glxxtremsuffix}%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvemfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvemfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongemfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongemfont{##1}}%
\renewcommand*{\glxtrfullformat}[2]{%
\glsfirstlongemfont{\glsaccesslong{##1}\ifglxtrininsertinside##2\fi}%
\ifglxtrininsertinside\else##2\fi
\glxtrfullsep{##1}%
\glxtrparen{\glsfirstabbrvemfont{\glsaccessshort{##1}}}%

```

```

}%
\renewcommand*{\glstrfullplformat}[2]{%
  \glstrfirstlongemfont{\glstraccesslongpl{##1}\ifglstrinsertinside##2\fi}%
  \ifglstrinsertinside\else##2\fi\glstrfullsep{##1}%
  \glstrparen{\glstrfirstabbrvemfont{\glstraccessshortpl{##1}}}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \glstrfirstlongemfont{\Glsaccesslong{##1}\ifglstrinsertinside##2\fi}%
  \ifglstrinsertinside\else##2\fi\glstrfullsep{##1}%
  \glstrparen{\glstrfirstabbrvemfont{\Glsaccessshort{##1}}}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \glstrfirstlongemfont{\Glsaccesslongpl{##1}\ifglstrinsertinside##2\fi}%
  \ifglstrinsertinside\else##2\fi\glstrfullsep{##1}%
  \glstrparen{\glstrfirstabbrvemfont{\glstraccessshortpl{##1}}}%
}%
}
\newabbreviationstyle{long-em-short-em-desc}%
{%
  \glstrAccSuppAbbrSetTextShortAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glstrlongshortdescname},
    sort={\glstrlongshortdescsort},%
    first={\protect\glstrfirstlongemfont{\the\glslongtok}%
      \protect\glstrfullsep{\the\glslabeltok}%
      \glstrparen{\protect\glstrfirstabbrvemfont{\the\glsshorttok}}},%
    firstplural={\protect\glstrfirstlongemfont{\the\glslongpltok}%
      \protect\glstrfullsep{\the\glslabeltok}%
      \glstrparen{\protect\glstrfirstabbrvemfont{\the\glsshortpltok}}},%
    text={\protect\glstrabbrvemfont{\the\glsshorttok}},%
    plural={\protect\glstrabbrvemfont{\the\glsshortpltok}}%
  }%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \glshasattribute{\the\glslabeltok}{regular}%
    {%
      \glsssetAttribute{\the\glslabeltok}{regular}{false}%
    }%
    {%
  }%
}%
\GlsXtrUseAbbrStyleFmts{long-em-short-em}%
}
\newabbreviationstyle{short-em-long}%
{%
  \glstrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glstrshortlongname},
    sort={\the\glsshorttok},
    description={\the\glslongtok},%

```

```

first={\protect\glsfirstabbrvemfont{\the\glsshorttok}%
\protect\glstrfullsep{\the\glslabeltok}%
\glstrparen{\protect\glsfirstlongdefaultfont{\the\glslongtok}}},%
firstplural={\protect\glsfirstabbrvemfont{\the\glsshortpltok}%
\protect\glstrfullsep{\the\glslabeltok}%
\glstrparen{\protect\glsfirstlongdefaultfont{\the\glslongpltok}}},%
text={\protect\glsabbrvemfont{\the\glsshorttok}},%
plural={\protect\glsabbrvemfont{\the\glsshortpltok}}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glsattribute{\the\glslabeltok}{regular}%
{%
\glsattribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%
{%
\renewcommand*{\abbrvpluralsuffix}{\glxtremsuffix}%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvemfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvemfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%
\renewcommand*{\glstrfullformat}[2]{%
\glsfirstabbrvemfont{\glsaccessshort{##1}\ifglstrinsertinside##2\fi}%
\ifglstrinsertinside\else##2\fi
\glstrfullsep{##1}%
\glstrparen{\glsfirstlongdefaultfont{\glsaccesslong{##1}}}%
}%
\renewcommand*{\glstrfullplformat}[2]{%
\glsfirstabbrvemfont{\glsaccessshortpl{##1}\ifglstrinsertinside##2\fi}%
\ifglstrinsertinside\else##2\fi
\glstrfullsep{##1}%
\glstrparen{\glsfirstlongdefaultfont{\glsaccesslongpl{##1}}}%
}%
\renewcommand*{\GlsXtrfullformat}[2]{%
\glsfirstabbrvemfont{\Glsaccessshort{##1}\ifglstrinsertinside##2\fi}%
\ifglstrinsertinside\else##2\fi\glstrfullsep{##1}%
\glstrparen{\glsfirstlongdefaultfont{\glsaccesslong{##1}}}%
}%
\renewcommand*{\GlsXtrfullplformat}[2]{%
\glsfirstabbrvemfont{\Glsaccessshortpl{##1}\ifglstrinsertinside##2\fi}%
\ifglstrinsertinside\else##2\fi\glstrfullsep{##1}%
\glstrparen{\glsfirstlongdefaultfont{\glsaccesslongpl{##1}}}%
}%
}%
\newabbreviationstyle{short-em-long-desc}%
{%
\glsXtrAccSuppAbbrSetTextShortAttrs\glscategorylabel
\renewcommand*{\CustomAbbreviationFields}{%
name={\glstrshortlongdescname},

```



```

sort={\glxtrshortlongdescsort},
first={\protect\glsfirstabbrvemfont{\the\glsshorttok}%
\protect\glxtrfullsep{\the\glslabeltok}%
\glxtrparen{\protect\glsfirstlongdefaultfont{\the\glslongtok}}},%
firstplural={\protect\glsfirstabbrvemfont{\the\glsshortpltok}%
\protect\glxtrfullsep{\the\glslabeltok}%
\glxtrparen{\protect\glsfirstlongdefaultfont{\the\glslongpltok}}},%
text={\protect\glsabbrvemfont{\the\glsshorttok}},%
plural={\protect\glsabbrvemfont{\the\glsshortpltok}}%
}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glsattribute{\the\glslabeltok}{regular}%
{%
\glssetattribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%
{\%
\GlsXtrUseAbbrStyleFmts{short-em-long}%
}
\newabbreviationstyle{short-em-long-em}%
{%
\glxtrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
\renewcommand*{\CustomAbbreviationFields}{%
name={\glxtrshortlongname},
sort={\the\glsshorttok},
description={\protect\glslongemfont{\the\glslongtok}},%
first={\protect\glsfirstabbrvemfont{\the\glsshorttok}%
\protect\glxtrfullsep{\the\glslabeltok}%
\glxtrparen{\protect\glsfirstlongemfont{\the\glslongtok}}},%
firstplural={\protect\glsfirstabbrvemfont{\the\glsshortpltok}%
\protect\glxtrfullsep{\the\glslabeltok}%
\glxtrparen{\protect\glsfirstlongemfont{\the\glslongpltok}}},%
text={\protect\glsabbrvemfont{\the\glsshorttok}},%
plural={\protect\glsabbrvemfont{\the\glsshortpltok}}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glsattribute{\the\glslabeltok}{regular}%
{%
\glssetattribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%
}%
{\%
\renewcommand*{\abbrvpluralsuffix}{\glxtremsuffix}%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvemfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvemfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongemfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongemfont{##1}}%

```

```

\renewcommand*{\glxstrfullformat}[2]{%
  \glsfirstabbrvemfont{\glsaccessshort{##1}\ifglxtrinsertinside##2\fi}%
  \ifglxtrinsertinside\else##2\fi
  \glxstrfullsep{##1}%
  \glxtrparen{\glsfirstlongemfont{\glsaccesslong{##1}}}%
}%
\renewcommand*{\glxstrfullplformat}[2]{%
  \glsfirstabbrvemfont{\glsaccessshortpl{##1}\ifglxtrinsertinside##2\fi}%
  \ifglxtrinsertinside\else##2\fi
  \glxstrfullsep{##1}%
  \glxtrparen{\glsfirstlongemfont{\glsaccesslongpl{##1}}}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \glsfirstabbrvemfont{\Glsaccessshort{##1}\ifglxtrinsertinside##2\fi}%
  \ifglxtrinsertinside\else##2\fi\glxstrfullsep{##1}%
  \glxtrparen{\glsfirstlongemfont{\glsaccesslong{##1}}}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \glsfirstabbrvemfont{\Glsaccessshortpl{##1}\ifglxtrinsertinside##2\fi}%
  \ifglxtrinsertinside\else##2\fi\glxstrfullsep{##1}%
  \glxtrparen{\glsfirstlongemfont{\glsaccesslongpl{##1}}}%
}%
}
\newabbreviationstyle{short-em-long-em-desc}%
{%
  \glxstrAccSuppAbbrSetTextShortAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glxstrshortlongdescname},%
    sort={\glxstrshortlongdescsort},%
    first={\protect\glsfirstabbrvemfont{\the\glsshorttok}}%
    \protect\glxstrfullsep{\the\glslabeltok}%
    \glxtrparen{\protect\glsfirstlongemfont{\the\glslongtok}}},%
    firstplural={\protect\glsfirstabbrvemfont{\the\glsshortpltok}}%
    \protect\glxstrfullsep{\the\glslabeltok}%
    \glxtrparen{\protect\glsfirstlongemfont{\the\glslongpltok}}},%
    text={\protect\glsabbrvemfont{\the\glsshorttok}},%
    plural={\protect\glsabbrvemfont{\the\glsshortpltok}}%
  }%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \glshasattribute{\the\glslabeltok}{regular}%
    {%
      \glissetattribute{\the\glslabeltok}{regular}{false}%
    }%
    {}%
  }%
}%
{%
  \GlsXtrUseAbbrStyleFmts{short-em-long-em}%
}
\newabbreviationstyle{short-em}%

```

```

{%
\glstrAccSuppAbbrSetNoLongAttrs\glscategorylabel
\renewcommand*{\CustomAbbreviationFields}{%
  name={\glstrshortnolongname},
  sort={\the\glsshorttok},
  first={\protect\glfirstabbrvemfont{\the\glsshorttok}},
  firstplural={\protect\glfirstabbrvemfont{\the\glsshortpltok}},
  text={\protect\glabbrvemfont{\the\glsshorttok}},
  plural={\protect\glabbrvemfont{\the\glsshortpltok}},
  description={\the\glslongtok}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glsssetAttribute{\the\glslabeltok}{regular}{true}}%
}%
{%
\renewcommand*{\abbrvpluralsuffix}{\glxtremsuffix}%
\renewcommand*{\glabbrvfont}[1]{\glabbrvemfont{##1}}%
\renewcommand*{\glfirstabbrvfont}[1]{\glfirstabbrvemfont{##1}}%
\renewcommand*{\glfirstlongfont}[1]{\glfirstlongdefaultfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%
\renewcommand*{\glstrinlinefullformat}[2]{%
  \protect\glfirstabbrvemfont{\glaccessshort{##1}}%
  \ifglstrinsertinside##2\fi}%
  \ifglstrinsertinside\else##2\fi\glstrfullsep{##1}%
  \glstrparen{\glfirstlongdefaultfont{\glaccesslong{##1}}}%
}%
\renewcommand*{\glstrinlinefullplformat}[2]{%
  \protect\glfirstabbrvemfont{\glaccessshortpl{##1}}%
  \ifglstrinsertinside##2\fi}%
  \ifglstrinsertinside\else##2\fi\glstrfullsep{##1}%
  \glstrparen{\glfirstlongdefaultfont{\glaccesslongpl{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \protect\glfirstabbrvemfont{\Glsaccessshort{##1}}%
  \ifglstrinsertinside##2\fi}%
  \ifglstrinsertinside\else##2\fi\glstrfullsep{##1}%
  \glstrparen{\glfirstlongdefaultfont{\glaccesslong{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \protect\glfirstabbrvemfont{\Glsaccessshortpl{##1}}%
  \ifglstrinsertinside##2\fi}%
  \ifglstrinsertinside\else##2\fi\glstrfullsep{##1}%
  \glstrparen{\glfirstlongdefaultfont{\glaccesslongpl{##1}}}%
}%
\renewcommand*{\glstrfullformat}[2]{%
  \glfirstabbrvemfont{\glaccessshort{##1}}\ifglstrinsertinside##2\fi}%
  \ifglstrinsertinside\else##2\fi
}%
\renewcommand*{\glstrfullplformat}[2]{%
  \glfirstabbrvemfont{\glaccessshortpl{##1}}\ifglstrinsertinside##2\fi}%
  \ifglstrinsertinside\else##2\fi
}

```

```

}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \glsfirstabbrvemfont{\glsaccessshort{##1}\ifglxtrinsertinside##2\fi}%
  \ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \glsfirstabbrvemfont{\glsaccessshortpl{##1}\ifglxtrinsertinside##2\fi}%
  \ifglxtrinsertinside\else##2\fi
}%
}
\letabbreviationstyle{short-em-nolong}{short-em}
\newabbreviationstyle{short-em-desc}%
{%
  \glsxtrAccSuppAbbrSetNoLongAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glsxtrshortdescname},
    sort={\the\glsshorttok},
    first={\protect\glsfirstabbrvemfont{\the\glsshorttok}},
    firstplural={\protect\glsfirstabbrvemfont{\the\glsshortpltok}},
    text={\protect\glsabbrvemfont{\the\glsshorttok}},
    plural={\protect\glsabbrvemfont{\the\glsshortpltok}}}%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \glssetattribute{\the\glslabeltok}{regular}{true}}%
}%
{%
  \renewcommand*{\abbrvpluralsuffix}{\glsxtremsuffix}%
  \renewcommand*{\glsabbrvfont}[1]{\glsabbrvemfont{##1}}%
  \renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvemfont{##1}}%
  \renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongdefaultfont{##1}}%
  \renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%
  \renewcommand*{\glsxtrinlinefullformat}[2]{%
    \glsfirstabbrvemfont{\glsaccessshort{##1}\ifglxtrinsertinside##2\fi}%
    \ifglxtrinsertinside\else##2\fi\glsxtrfullsep{##1}%
    \glsxtrparen{\glsfirstlongdefaultfont{\glsaccesslong{##1}}}%
  }%
  \renewcommand*{\glsxtrinlinefullplformat}[2]{%
    \glsfirstabbrvemfont{\glsaccessshortpl{##1}\ifglxtrinsertinside##2\fi}%
    \ifglxtrinsertinside\else##2\fi\glsxtrfullsep{##1}%
    \glsxtrparen{\glsfirstlongdefaultfont{\glsaccesslongpl{##1}}}%
  }%
  \renewcommand*{\Glsxtrinlinefullformat}[2]{%
    \glsfirstabbrvemfont{\Glsaccessshort{##1}\ifglxtrinsertinside##2\fi}%
    \ifglxtrinsertinside\else##2\fi\glsxtrfullsep{##1}%
    \glsxtrparen{\glsfirstlongdefaultfont{\glsaccesslong{##1}}}%
  }%
  \renewcommand*{\Glsxtrinlinefullplformat}[2]{%
    \glsfirstabbrvemfont{\Glsaccessshortpl{##1}\ifglxtrinsertinside##2\fi}%
    \ifglxtrinsertinside\else##2\fi\glsxtrfullsep{##1}%
    \glsxtrparen{\glsfirstlongdefaultfont{\glsaccesslongpl{##1}}}%
  }%
}

```

```

\renewcommand*{\glxstrfullformat}[2]{%
  \glsfirstabbrvemfont{\glsaccessshort{##1}\ifglxtrinsertinside##2\fi}%
  \ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\glxstrfullplformat}[2]{%
  \glsfirstabbrvemfont{\glsaccessshortpl{##1}\ifglxtrinsertinside##2\fi}%
  \ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \glsfirstabbrvemfont{\glsaccessshort{##1}\ifglxtrinsertinside##2\fi}%
  \ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \glsfirstabbrvemfont{\glsaccessshortpl{##1}\ifglxtrinsertinside##2\fi}%
  \ifglxtrinsertinside\else##2\fi
}%
}
\letabbreviationstyle{short-em-nolong-desc}{short-em-desc}
\newabbreviationstyle{nolong-short-em}%
{%
  \GlsXtrUseAbbrStyleSetup{short-em-nolong}%
}%
{%
  \GlsXtrUseAbbrStyleFmts{short-em-nolong}%
  \renewcommand*{\glxstrinlinefullformat}[2]{%
    \protect\glsfirstlongdefaultfont{\glsaccesslong{##1}%
      \ifglxtrinsertinside##2\fi}%
    \ifglxtrinsertinside\else##2\fi\glxstrfullsep{##1}%
    \glxstrparen{\glsfirstabbrvemfont{\glsaccessshort{##1}}}%
  }%
  \renewcommand*{\glxstrinlinefullplformat}[2]{%
    \protect\glsfirstlongdefaultfont{\glsaccesslongpl{##1}%
      \ifglxtrinsertinside##2\fi}%
    \ifglxtrinsertinside\else##2\fi\glxstrfullsep{##1}%
    \glxstrparen{\glsfirstabbrvemfont{\glsaccessshortpl{##1}}}%
  }%
  \renewcommand*{\Glsxtrinlinefullformat}[2]{%
    \protect\glsfirstlongdefaultfont{\Glsaccesslong{##1}%
      \ifglxtrinsertinside##2\fi}%
    \ifglxtrinsertinside\else##2\fi\glxstrfullsep{##1}%
    \glxstrparen{\glsfirstabbrvemfont{\glsaccessshort{##1}}}%
  }%
  \renewcommand*{\Glsxtrinlinefullplformat}[2]{%
    \protect\glsfirstlongdefaultfont{\Glsaccesslongpl{##1}%
      \ifglxtrinsertinside##2\fi}%
    \ifglxtrinsertinside\else##2\fi\glxstrfullsep{##1}%
    \glxstrparen{\glsfirstabbrvemfont{\glsaccessshortpl{##1}}}%
  }%
}
\newabbreviationstyle{long-noshort-em}%

```

```

{%
\glsxtrAccSuppAbbrSetNameShortAttrs\glscategorylabel
\renewcommand*{\CustomAbbreviationFields}{%
  name={\glsxtrlongnoshortname},
  sort={\the\glsshorttok},
  first={\protect\glsfirstlongdefaultfont{\the\glslongtok}},
  firstplural={\protect\glsfirstlongdefaultfont{\the\glslongpltok}},
  text={\protect\glslongdefaultfont{\the\glslongtok}},
  plural={\protect\glslongdefaultfont{\the\glslongpltok}},%
  description={\the\glslongtok}%
}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glssetattribute{\the\glslabeltok}{regular}{true}}%
}%
{%
\renewcommand*{\abbrvpluralsuffix}{\glsxtremsuffix}%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvemfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvemfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%
\renewcommand*{\glsxtrsubsequentfmt}[2]{%
  \glslongdefaultfont{\glsaccesslong{##1}\ifglsxtrininsertinside ##2\fi}%
  \ifglsxtrininsertinside \else##2\fi
}%
\renewcommand*{\glsxtrsubsequentplfmt}[2]{%
  \glslongdefaultfont{\glsaccesslongpl{##1}\ifglsxtrininsertinside ##2\fi}%
  \ifglsxtrininsertinside \else##2\fi
}%
\renewcommand*{\Glsxtrsubsequentfmt}[2]{%
  \glslongdefaultfont{\Glsaccesslong{##1}\ifglsxtrininsertinside ##2\fi}%
  \ifglsxtrininsertinside \else##2\fi
}%
\renewcommand*{\Glsxtrsubsequentplfmt}[2]{%
  \glslongdefaultfont{\Glsaccesslongpl{##1}\ifglsxtrininsertinside ##2\fi}%
  \ifglsxtrininsertinside \else##2\fi
}%
\renewcommand*{\glsxtrinlinefullformat}[2]{%
  \glsfirstlongdefaultfont{\glsaccesslong{##1}\ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
  \glsxtrparen{\protect\glsfirstabbrvemfont{\glsaccessshort{##1}}}%
}%
\renewcommand*{\glsxtrinlinefullplformat}[2]{%
  \glsfirstlongdefaultfont{\glsaccesslongpl{##1}\ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
  \glsxtrparen{\protect\glsfirstabbrvemfont{\glsaccessshortpl{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \glsfirstlongdefaultfont{\Glsaccesslong{##1}\ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
  \glsxtrparen{\protect\glsfirstabbrvemfont{\glsaccessshort{##1}}}%
}

```

```

}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \glsfirstlongdefaultfont{\Glsaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
  \ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
  \glxtrparen{\protect\glsfirstabbrvemfont{\Glsaccessshortpl{##1}}}%
}%
\renewcommand*{\glxtrfullformat}[2]{%
  \glsfirstlongdefaultfont{\Glsaccesslong{##1}\ifglxtrinsertinside##2\fi}%
  \ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\glxtrfullplformat}[2]{%
  \glsfirstlongdefaultfont{\Glsaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
  \ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \glsfirstlongdefaultfont{\Glsaccesslong{##1}\ifglxtrinsertinside##2\fi}%
  \ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \glsfirstlongdefaultfont{\Glsaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
  \ifglxtrinsertinside\else##2\fi
}%
}
\@glxtr@deprecated@abbrstyle{long-em}{long-noshort-em}
\newabbreviationstyle{long-em-noshort-em}%
{%
  \glxtrAccSuppAbbrSetNameShortAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glxtrlongnoshortname},
    sort={\the\glsshorttok},
    first={\protect\glsfirstlongemfont{\the\glslongtok}},
    firstplural={\protect\glsfirstlongemfont{\the\glslongpltok}},
    text={\protect\glslongemfont{\the\glslongtok}},
    plural={\protect\glslongemfont{\the\glslongpltok}},%
    description={\protect\glslongemfont{\the\glslongtok}}}%
  }%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \glssetattribute{\the\glslabeltok}{regular}{true}}%
}%
{%
  \renewcommand*{\abbrvpluralsuffix}{\glxtremsuffix}%
  \renewcommand*{\glsabbrvfont}[1]{\glsabbrvemfont{##1}}%
  \renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvemfont{##1}}%
  \renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongemfont{##1}}%
  \renewcommand*{\glslongfont}[1]{\glslongemfont{##1}}%
  \renewcommand*{\glxtrsubsequentfmt}[2]{%
    \glslongemfont{\Glsaccesslong{##1}\ifglxtrinsertinside ##2\fi}%
    \ifglxtrinsertinside \else##2\fi
  }%
  \renewcommand*{\glxtrsubsequentplfmt}[2]{%

```

```

\glslongemfont{\glsaccesslongpl{##1}\ifglxtrinsertinside ##2\fi}%
\ifglxtrinsertinside \else##2\fi
}%
\renewcommand*{\Glsxtrsubsequentfmt}[2]{%
\glslongemfont{\Glsaccesslong{##1}\ifglxtrinsertinside ##2\fi}%
\ifglxtrinsertinside \else##2\fi
}%
\renewcommand*{\Glsxtrsubsequentplfmt}[2]{%
\glslongemfont{\Glsaccesslongpl{##1}\ifglxtrinsertinside ##2\fi}%
\ifglxtrinsertinside \else##2\fi
}%
\renewcommand*{\glxtrinlinefullformat}[2]{%
\glsfirstlongemfont{\glsaccesslong{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\protect\glsfirstabbrvemfont{\glsaccessshort{##1}}}%
}%
\renewcommand*{\glxtrinlinefullplformat}[2]{%
\glsfirstlongemfont{\glsaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\protect\glsfirstabbrvemfont{\glsaccessshortpl{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
\glsfirstlongemfont{\Glsaccesslong{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\protect\glsfirstabbrvemfont{\glsaccessshort{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
\glsfirstlongemfont{\Glsaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\protect\glsfirstabbrvemfont{\glsaccessshortpl{##1}}}%
}%
\renewcommand*{\glxtrfullformat}[2]{%
\glsfirstlongemfont{\glsaccesslong{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\glxtrfullplformat}[2]{%
\glsfirstlongemfont{\glsaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
\glsfirstlongemfont{\Glsaccesslong{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
\glsfirstlongemfont{\Glsaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
}%
}
\newabbreviationstyle{long-em-noshort-em-noreg}%
%
```



```

\glxstrAccSuppAbbrSetNameShortAttrs\glscategorylabel
\GlsXtrUseAbbrStyleSetup{long-em-noshort-em}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glissetattribute{\the\glslabeltok}{regular}{false}%
  }%
  {%
  }%
}%
}%
\GlsXtrUseAbbrStyleFmts{long-em-noshort-em}%
}
\newabbreviationstyle{long-noshort-em-desc}%
{%
  \GlsXtrUseAbbrStyleSetup{long-noshort-desc}%
}%
{%
  \renewcommand*{\abbrvpluralsuffix}{\glxtremsuffix}%
  \renewcommand*{\glssabrvfont}[1]{\glssabrvemfont{##1}}%
  \renewcommand*{\glsfirstabrvfont}[1]{\glsfirstabrvemfont{##1}}%
  \renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongdefaultfont{##1}}%
  \renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%
  \renewcommand*{\glsxtrsubsequentfmt}[2]{%
    \glslongdefaultfont{\glssaccesslong{##1}\ifglsxtrininsertinside ##2\fi}%
    \ifglsxtrininsertinside \else##2\fi
  }%
  \renewcommand*{\glsxtrsubsequentplfmt}[2]{%
    \glslongdefaultfont{\glssaccesslongpl{##1}\ifglsxtrininsertinside ##2\fi}%
    \ifglsxtrininsertinside \else##2\fi
  }%
  \renewcommand*{\Glsxtrsubsequentfmt}[2]{%
    \glslongdefaultfont{\Glsaccesslong{##1}\ifglsxtrininsertinside ##2\fi}%
    \ifglsxtrininsertinside \else##2\fi
  }%
  \renewcommand*{\Glsxtrsubsequentplfmt}[2]{%
    \glslongdefaultfont{\Glsaccesslongpl{##1}\ifglsxtrininsertinside ##2\fi}%
    \ifglsxtrininsertinside \else##2\fi
  }%
  \renewcommand*{\glsxtrinlinefullformat}[2]{%
    \glsfirstlongdefaultfont{\glssaccesslong{##1}\ifglsxtrininsertinside##2\fi}%
    \ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
    \glsxtrparen{\protect\glsfirstabrvemfont{\glssaccessshort{##1}}}%
  }%
  \renewcommand*{\glsxtrinlinefullplformat}[2]{%
    \glsfirstlongdefaultfont{\glssaccesslongpl{##1}\ifglsxtrininsertinside##2\fi}%
    \ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
    \glsxtrparen{\protect\glsfirstabrvemfont{\glssaccessshortpl{##1}}}%
  }%
  \renewcommand*{\Glsxtrinlinefullformat}[2]{%

```

```

\glsfirstlongdefaultfont{\Glsaccesslong{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\protect\glsfirstabbrvemfont{\glsaccessshort{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
\glsfirstlongdefaultfont{\Glsaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\protect\glsfirstabbrvemfont{\glsaccessshortpl{##1}}}%
}%
\renewcommand*{\glxtrfullformat}[2]{%
\glsfirstlongdefaultfont{\glsaccesslong{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\glxtrfullplformat}[2]{%
\glsfirstlongdefaultfont{\glsaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
\glsfirstlongdefaultfont{\glsaccesslong{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
\glsfirstlongdefaultfont{\glsaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
}%
}
\@glxtr@deprecated@abbrstyle{long-desc-em}{long-noshort-em-desc}
\newabbreviationstyle{long-em-noshort-em-desc}%
{%
\renewcommand*{\CustomAbbreviationFields}{%
name={\glxtrlongnoshortdescname},
sort={\the\glslongtok},
first={\protect\glsfirstlongemfont{\the\glslongtok}},
firstplural={\protect\glsfirstlongemfont{\the\glslongpltok}},
text={\glslongemfont{\the\glslongtok}},
plural={\glslongemfont{\the\glslongpltok}}}%
}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glssetattribute{\the\glslabeltok}{regular}{true}}%
}%
{%
\renewcommand*{\abbrvpluralsuffix}{\glxtremsuffix}%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvemfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvemfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongemfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongemfont{##1}}%
\renewcommand*{\glxtrsubsequentfmt}[2]{%
\glslongemfont{\glsaccesslong{##1}\ifglxtrinsertinside ##2\fi}%
\ifglxtrinsertinside \else##2\fi
}%
}

```

```

\renewcommand*{\glxtrsubsequentplfmt}[2]{%
  \glslongemfont{\glssaccesslongpl{##1}\ifglxtrininsertinside ##2\fi}%
  \ifglxtrininsertinside \else##2\fi
}%
\renewcommand*{\Glsxtrsubsequentfmt}[2]{%
  \glslongemfont{\Glsaccesslong{##1}\ifglxtrininsertinside ##2\fi}%
  \ifglxtrininsertinside \else##2\fi
}%
\renewcommand*{\Glsxtrsubsequentplfmt}[2]{%
  \glslongemfont{\Glsaccesslongpl{##1}\ifglxtrininsertinside ##2\fi}%
  \ifglxtrininsertinside \else##2\fi
}%
\renewcommand*{\glxtrinlinefullformat}[2]{%
  \glslfirstlongemfont{\glssaccesslong{##1}\ifglxtrininsertinside##2\fi}%
  \ifglxtrininsertinside\else##2\fi\glxtrfullsep{##1}%
  \glxtrparen{\protect\glslfirstabbrvemfont{\glssaccessshort{##1}}}%
}%
\renewcommand*{\glxtrinlinefullplformat}[2]{%
  \glslfirstlongemfont{\glssaccesslongpl{##1}\ifglxtrininsertinside##2\fi}%
  \ifglxtrininsertinside\else##2\fi\glxtrfullsep{##1}%
  \glxtrparen{\protect\glslfirstabbrvemfont{\glssaccessshortpl{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \glslfirstlongemfont{\Glsaccesslong{##1}\ifglxtrininsertinside##2\fi}%
  \ifglxtrininsertinside\else##2\fi\glxtrfullsep{##1}%
  \glxtrparen{\protect\glslfirstabbrvemfont{\glssaccessshort{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \glslfirstlongemfont{\Glsaccesslongpl{##1}\ifglxtrininsertinside##2\fi}%
  \ifglxtrininsertinside\else##2\fi\glxtrfullsep{##1}%
  \glxtrparen{\protect\glslfirstabbrvemfont{\glssaccessshortpl{##1}}}%
}%
\renewcommand*{\glxtrfullformat}[2]{%
  \glslfirstlongemfont{\glssaccesslong{##1}\ifglxtrininsertinside##2\fi}%
  \ifglxtrininsertinside\else##2\fi
}%
\renewcommand*{\glxtrfullplformat}[2]{%
  \glslfirstlongemfont{\glssaccesslongpl{##1}\ifglxtrininsertinside##2\fi}%
  \ifglxtrininsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \glslfirstlongemfont{\glssaccesslong{##1}\ifglxtrininsertinside##2\fi}%
  \ifglxtrininsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \glslfirstlongemfont{\glssaccesslongpl{##1}\ifglxtrininsertinside##2\fi}%
  \ifglxtrininsertinside\else##2\fi
}%
}
\newabbreviationstyle{long-em-noshort-em-desc-noreg}%

```

```

{%
  \GlsXtrUseAbbrStyleSetup{long-em-noshort-em-desc}%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \glshasattribute{\the\glslabeltok}{regular}%
    {%
      \glissetattribute{\the\glslabeltok}{regular}{false}%
    }%
    {}%
  }%
}%
{%
  \GlsXtrUseAbbrStyleFmts{long-em-noshort-em-desc}%
}
\newabbreviationstyle{short-em-footnote}%
{%
  \glsxtrAccSuppAbbrSetNoLongAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glsxtrfootnotename},
    sort={\the\glsshorttok},
    description={\the\glslongtok},%
    first={\protect\glsfirstabbrvemfont{\the\glsshorttok}%
      \protect\glxtrabbrvfootnote{\the\glslabeltok}%
      {\protect\glsfirstlongfootnotefont{\the\glslongtok}}},%
    firstplural={\protect\glsfirstabbrvemfont{\the\glsshortpltok}%
      \protect\glxtrabbrvfootnote{\the\glslabeltok}%
      {\protect\glsfirstlongfootnotefont{\the\glslongpltok}}},%
    text={\protect\glsabbrvemfont{\the\glsshorttok}},%
    plural={\protect\glsabbrvemfont{\the\glsshortpltok}}}%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \glissetattribute{\the\glslabeltok}{nohyperfirst}{true}%
    \glshasattribute{\the\glslabeltok}{regular}%
    {%
      \glissetattribute{\the\glslabeltok}{regular}{false}%
    }%
    {}%
  }%
}%
{%
  \renewcommand*{\abbrvpluralsuffix}{\glxtremsuffix}%
  \renewcommand*{\glsabbrvfont}[1]{\glsabbrvemfont{##1}}%
  \renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvemfont{##1}}%
  \renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongfootnotefont{##1}}%
  \renewcommand*{\glslongfont}[1]{\glslongfootnotefont{##1}}%
  \renewcommand*{\glsxtrfullformat}[2]{%
    \glsfirstabbrvemfont{\glsaccessshort{##1}\ifglxtrininsertinside##2\fi}%
    \ifglxtrininsertinside\else##2\fi
    \protect\glxtrabbrvfootnote{##1}%
    {\glsfirstlongfootnotefont{\glsaccesslong{##1}}}%
  }%
  \renewcommand*{\glsxtrfullplformat}[2]{%

```

```

\glsfirstabbrvemfont{\glsaccessshortpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
\protect\glxtrabbrvfootnote{##1}%
{\glsfirstlongfootnotefont{\glsaccesslongpl{##1}}}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
\glsfirstabbrvemfont{\Glsaccessshort{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
\protect\glxtrabbrvfootnote{##1}%
{\glsfirstlongfootnotefont{\glsaccesslong{##1}}}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
\glsfirstabbrvemfont{\Glsaccessshortpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
\protect\glxtrabbrvfootnote{##1}%
{\glsfirstlongfootnotefont{\glsaccesslongpl{##1}}}%
}%
\renewcommand*{\glxtrinlinefullformat}[2]{%
\glsfirstabbrvemfont{\glsaccessshort{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\glsfirstlongfootnotefont{\glsaccesslong{##1}}}%
}%
\renewcommand*{\glxtrinlinefullplformat}[2]{%
\glsfirstabbrvemfont{\glsaccessshortpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\glsfirstlongfootnotefont{\glsaccesslongpl{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
\glsfirstabbrvemfont{\Glsaccessshort{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\glsfirstlongfootnotefont{\glsaccesslong{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
\glsfirstabbrvemfont{\Glsaccessshortpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
\glxtrparen{\glsfirstlongfootnotefont{\glsaccesslongpl{##1}}}%
}%
}
\@glxtr@deprecated@abbrstyle{footnote-em}{short-em-footnote}
\newabbreviationstyle{short-em-footnote-desc}%
{%
\glxtrAccSuppAbbrSetNameLongAttrs\glscategorylabel
\renewcommand*{\CustomAbbreviationFields}{%
name={\glxtrfootnotedesname},
sort={\glxtrfootnotedesort},
first={\protect\glsfirstabbrvemfont{\the\glsshorttok}%
\protect\glxtrabbrvfootnote{\the\glslabeltok}%
{\protect\glsfirstlongfootnotefont{\the\glslongtok}}},%
firstplural={\protect\glsfirstabbrvemfont{\the\glsshortpltok}%
\protect\glxtrabbrvfootnote{\the\glslabeltok}%

```

```

        {\protect\glsfirstlongfootnotefont{\the\glslongpltok}}},%
text={\protect\glsabbrvemfont{\the\glsshorttok}},%
plural={\protect\glsabbrvemfont{\the\glsshortpltok}}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glssetattribute{\the\glslabeltok}{nohyperfirst}{true}%
\glsattribute{\the\glslabeltok}{regular}%
{%
\glssetattribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%
{%
\GlsXtrUseAbbrStyleFmts{short-em-footnote}%
}
\newabbreviationstyle{short-em-postfootnote}%
{%
\glsxtrAccSuppAbbrSetNoLongAttrs\glscategorylabel
\renewcommand*{\CustomAbbreviationFields}{%
name={\glsxtrfootnotename},
sort={\the\glsshorttok},
description={\the\glslongtok},%
first={\protect\glsfirstabbrvemfont{\the\glsshorttok}},%
firstplural={\protect\glsfirstabbrvemfont{\the\glsshortpltok}},%
text={\protect\glsabbrvemfont{\the\glsshorttok}},%
plural={\protect\glsabbrvemfont{\the\glsshortpltok}}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\csdef{glsxtrpostlink\glscategorylabel}{%
\glsxtrifwasfirstuse
{%
\glsxtrdopostpunc{\protect\glsxtrabbrvfootnote{\glslabel}%
{\glsfirstlongfootnotefont{\glsentrylong{\glslabel}}}}}%
}%
}%
\glsattribute{\the\glslabeltok}{regular}%
{%
\glssetattribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%
\renewcommand*{\glsxtrsetupfulldefs}{%
\let\glsxtrifwasfirstuse\@secondoftwo
}%
}%
{%
\renewcommand*{\abbrvpluralsuffix}{\glsxtremsuffix}%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvemfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvemfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongfootnotefont{##1}}%

```

```

\renewcommand*{\glslongfont}[1]{\glslongfootnotefont{##1}}%
\renewcommand*{\glsxtrfullformat}[2]{%
  \glsfirstabbrvemfont{\glsaccessshort{##1}\ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi
}%
\renewcommand*{\glsxtrfullplformat}[2]{%
  \glsfirstabbrvemfont{\glsaccessshortpl{##1}\ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \glsfirstabbrvemfont{\Glsaccessshort{##1}\ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \glsfirstabbrvemfont{\Glsaccessshortpl{##1}\ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi
}%
\renewcommand*{\glsxtrinlinefullformat}[2]{%
  \glsfirstabbrvemfont{\glsaccessshort{##1}\ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
  \glsxtrparen{\glsfirstlongfootnotefont{\glsaccesslong{##1}}}%
}%
\renewcommand*{\glsxtrinlinefullplformat}[2]{%
  \glsfirstabbrvemfont{\glsaccessshortpl{##1}\ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
  \glsxtrparen{\glsfirstlongfootnotefont{\glsaccesslongpl{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \glsfirstabbrvemfont{\Glsaccessshort{##1}\ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
  \glsxtrparen{\glsfirstlongfootnotefont{\glsaccesslong{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \glsfirstabbrvemfont{\Glsaccessshortpl{##1}\ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi\glsxtrfullsep{##1}%
  \glsxtrparen{\glsfirstlongfootnotefont{\glsaccesslongpl{##1}}}%
}%
}
\@glsxtr@deprecated@abbrstyle{postfootnote-em}{short-em-postfootnote}
\newabbreviationstyle{short-em-postfootnote-desc}%
{%
  \glsxtrAccSuppAbbrSetNameLongAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glsxtrfootnotedesname},
    sort={\glsxtrfootnotedesort},
    first={\protect\glsfirstabbrvemfont{\the\glsshorttok}},%
    firstplural={\protect\glsfirstabbrvemfont{\the\glsshortpltok}},%
    text={\protect\glsabbrvemfont{\the\glsshorttok}},%
    plural={\protect\glsabbrvemfont{\the\glsshortpltok}}}%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%

```

```

\csdef{glxtrpostlink\glscategorylabel}{%
  \glxtrifwasfirstuse
  {%
    \glxtrdopostpunc{\protect\glxtrabbrvfootnote{\glslabel}%
      {\glslfirstlongfootnotefont{\glssentrylong{\glslabel}}}}%
  }%
  {}%
}%
\glshasattribute{\the\glslabeltok}{regular}%
{%
  \glsssetAttribute{\the\glslabeltok}{regular}{false}%
}%
{}%
}%
\renewcommand*{\glxtrsetupfulldefs}{%
  \let\glxtrifwasfirstuse\@secondoftwo
}%
}%
{%
  \GlsXtrUseAbbrStyleFmts{short-em-postfootnote}%
}
\newcommand*{\glxtruserfield}{useri}
\ifdef\glscurrentfieldvalue
{
  \newcommand*{\glxtruserparen}[2]{%
    \glxtrfullsep{#2}%
    \glxtrparen
    {#1\ifglshasfield{\glxtruserfield}{#2}{, \glscurrentfieldvalue}{}}%
  }
}
{
  \newcommand*{\glxtruserparen}[2]{%
    \glxtrfullsep{#2}%
    \glxtrparen
    {#1\ifglshasfield{\glxtruserfield}{#2}{, \@glo@thisvalue}{}}%
  }
}
\newcommand*{\glsabbrvuserfont}[1]{\glsabbrvdefaultfont{#1}}
\newcommand*{\glslfirstabbrvuserfont}[1]{\glsabbrvuserfont{#1}}
\newcommand*{\glslonguserfont}[1]{\glslongdefaultfont{#1}}
\newcommand*{\glslfirstlonguserfont}[1]{\glslonguserfont{#1}}
\newcommand*{\glxtrusersuffix}{\glxtrabbrvpluralsuffix}
\newcommand*{\gluserdescription}[2]{\glslonguserfont{#1}}
\newabbreviationstyle{long-short-user}%
{%
  \glxtrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
\renewcommand*{\CustomAbbreviationFields}{%
  name={\glxtrlongshortname},
  sort={\the\glsshorttok},
  first={\protect\glslfirstlonguserfont{\the\glslongtok}}%
}

```



```

\protect\glxtruserparen{\protect\glsfirstabbrvuserfont{\the\glsshorttok}}%
{\the\glslabeltok}},%
firstplural={\protect\glsfirstlonguserfont{\the\glslongpltok}%
\protect\glxtruserparen
{\protect\glsfirstabbrvuserfont{\the\glsshortpltok}}{\the\glslabeltok}},%
text={\protect\glsabbrvuserfont{\the\glsshorttok}},%
plural={\protect\glsabbrvuserfont{\the\glsshortpltok}},%
description={\protect\glsuserdescription{\the\glslongtok}%
{\the\glslabeltok}}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glshasattribute{\the\glslabeltok}{regular}%
{%
\glissetattribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%
}%
{\%
\renewcommand*{\abbrvpluralsuffix}{\glxtrusersuffix}%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvuserfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvuserfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlonguserfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslonguserfont{##1}}%
\renewcommand*{\glxtrfullformat}[2]{%
\glsfirstlonguserfont{\glsaccesslong{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
\glxtruserparen{\glsfirstabbrvuserfont{\glsaccessshort{##1}}}{##1}%
}%
\renewcommand*{\glxtrfullplformat}[2]{%
\glsfirstlonguserfont{\glsaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
\glxtruserparen{\glsfirstabbrvuserfont{\glsaccessshortpl{##1}}}{##1}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
\glsfirstlonguserfont{\Glsaccesslong{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
\glxtruserparen{\glsfirstabbrvuserfont{\glsaccessshort{##1}}}{##1}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
\glsfirstlonguserfont{\Glsaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
\glxtruserparen{\glsfirstabbrvuserfont{\glsaccessshortpl{##1}}}{##1}%
}%
}
\newabbreviationstyle{long-postshort-user}%
{\%
\glxtrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
\renewcommand*{\CustomAbbreviationFields}{%
name={\glxtrlongshortname},
sort={\the\glsshorttok},

```

```

first={\protect\glsfirstlonguserfont{\the\glslongtok}},%
firstplural={\protect\glsfirstlonguserfont{\the\glslongpltok}},%
text={\protect\glsabbrvuserfont{\the\glsshorttok}},%
plural={\protect\glsabbrvuserfont{\the\glsshortpltok}},%
description={\protect\glsuserdescription{\the\glslongtok}%
{\the\glslabeltok}}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\csdef{glsxtrpostlink\glscategorylabel}{%
\glsxtrifwasfirstuse
}%
\glsxtruserparen
{\glsfirstabbrvuserfont{\glsentryshort{\glslabel}}}%
{\glslabel}%
}%
}%
}%
\glsattribute{\the\glslabeltok}{regular}%
{%
\glsattribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%
}%
{\%
\renewcommand*{\abbrvpluralsuffix}{\glsxtrusersuffix}%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvuserfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvuserfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlonguserfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslonguserfont{##1}}%
\renewcommand*{\glsxtrfullformat}[2]{%
\glsfirstlonguserfont{\glsaccesslong{##1}\ifglsxtrininsertinside##2\fi}%
\ifglsxtrininsertinside\else##2\fi
}%
\renewcommand*{\glsxtrfullplformat}[2]{%
\glsfirstlonguserfont{\glsaccesslongpl{##1}\ifglsxtrininsertinside##2\fi}%
\ifglsxtrininsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
\glsfirstlonguserfont{\Glsaccesslong{##1}\ifglsxtrininsertinside##2\fi}%
\ifglsxtrininsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
\glsfirstlonguserfont{\Glsaccesslongpl{##1}\ifglsxtrininsertinside##2\fi}%
\ifglsxtrininsertinside\else##2\fi
}%
\renewcommand*{\glsxtrinlinefullformat}[2]{%
\glsfirstlonguserfont{\glsaccesslong{##1}\ifglsxtrininsertinside##2\fi}%
\ifglsxtrininsertinside\else##2\fi
\glsxtruserparen{\glsfirstabbrvuserfont{\glsaccessshort{##1}}}{##1}%
}%

```

```

\renewcommand*{\glxstrinlinefullplformat}[2]{%
  \glsfirstlonguserfont{\glssaccesslongpl{##1}\ifglxstrinsertinside##2\fi}%
  \ifglxstrinsertinside\else##2\fi
  \glxtruserparen{\glsfirstabbrvuserfont{\glssaccessshortpl{##1}}}{##1}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \glsfirstlonguserfont{\Glsaccesslong{##1}\ifglxstrinsertinside##2\fi}%
  \ifglxstrinsertinside\else##2\fi
  \glxtruserparen{\glsfirstabbrvuserfont{\glssaccessshort{##1}}}{##1}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \glsfirstlonguserfont{\Glsaccesslongpl{##1}\ifglxstrinsertinside##2\fi}%
  \ifglxstrinsertinside\else##2\fi
  \glxtruserparen{\glsfirstabbrvuserfont{\glssaccessshortpl{##1}}}{##1}%
}%
}
\newcommand*{\glssabbrvscuserfont}{\glssabbrvscfont}%
\newcommand*{\glsfirstabbrvscuserfont}{\glssabbrvscuserfont}%
\newcommand*{\glxtrscusersuffix}{\glxtrscsuffix}
\newcommand*{\glxtrlongshortscusername}{%
  \protect\glssabbrvscuserfont{\the\glssshorttok}%
}
\newabbreviationstyle{long-postshort-sc-user}%
{%
  \glxtrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glxtrlongshortscusername},
    sort={\the\glssshorttok},
    first={\protect\glsfirstlonguserfont{\the\glslongtok}},%
    firstplural={\protect\glsfirstlonguserfont{\the\glslongpltok}},%
    text={\protect\glssabbrvscuserfont{\the\glssshorttok}},%
    plural={\protect\glssabbrvscuserfont{\the\glssshortpltok}},%
    description={\protect\glssuserdescription{\the\glslongtok}%
      {\the\glslabeltok}}}%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \csdef{glxtrpostlink\glscategorylabel}{%
      \glxtrifwasfirstuse
      {%
        \glxtruserparen
        {\glsfirstabbrvscuserfont{\glssentryshort{\glslabel}}}%
        {\glslabel}%
      }%
    }%
  }%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glsssetAttribute{\the\glslabeltok}{regular}{false}%
  }%
  {}%
}%

```

```

}%
{%
\renewcommand*{\abbrvpluralsuffix}{\glxtrscusersuffix}%
\renewcommand*{\glabbrvfont}[1]{\glabbrvcuserfont{##1}}%
\renewcommand*{\glfirstabbrvfont}[1]{\glfirstabbrvcuserfont{##1}}%
\renewcommand*{\glfirstlongfont}[1]{\glfirstlonguserfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslonguserfont{##1}}%
\renewcommand*{\glxtrfullformat}[2]{%
\glfirstlonguserfont{\glaccesslong{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\glxtrfullplformat}[2]{%
\glfirstlonguserfont{\glaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
\glfirstlonguserfont{\Glsaccesslong{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
\glfirstlonguserfont{\Glsaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\glxtrinelinefullformat}[2]{%
\glfirstlonguserfont{\glaccesslong{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
\glxtruserparen{\glfirstabbrvcuserfont{\glaccessshort{##1}}}{##1}%
}%
\renewcommand*{\glxtrinelinefullplformat}[2]{%
\glfirstlonguserfont{\glaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
\glxtruserparen{\glfirstabbrvcuserfont{\glaccessshorttpl{##1}}}{##1}%
}%
\renewcommand*{\Glsxtrinelinefullformat}[2]{%
\glfirstlonguserfont{\Glsaccesslong{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
\glxtruserparen{\glfirstabbrvcuserfont{\glaccessshort{##1}}}{##1}%
}%
\renewcommand*{\Glsxtrinelinefullplformat}[2]{%
\glfirstlonguserfont{\Glsaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
\glxtruserparen{\glfirstabbrvcuserfont{\glaccessshorttpl{##1}}}{##1}%
}%
}
\newcommand*{\glxtrlongshortuserdescname}{%
\protect\glslonguserfont{\the\glslongtok}%
\protect\glxtruserparen
{\protect\glslonguserfont{\the\glslongtok}}{\the\glslongtok}%
}
\newabbreviationstyle{long-postshort-user-desc}%

```

```

{%
\glxtrAccSuppAbbrSetTextShortAttrs\glscategorylabel
\renewcommand*{\CustomAbbreviationFields}{%
  name={\glxtrlongshortuserdescname},
  sort={\the\glslongtok},
  first={\protect\glslonguserfont{\the\glslongtok}},%
  firstplural={\protect\glslonguserfont{\the\glslongpltok}},%
  text={\protect\glsabbrvuserfont{\the\glsshorttok}},%
  plural={\protect\glsabbrvuserfont{\the\glsshortpltok}}}%
}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\csdef{glxtrpostlink\glscategorylabel}{%
\glxtrifwasfirstuse
{%
\glxtruserparen
{\glslonguserfont{\the\glslongtok}}}%
{\glslongpltok}%
}%
}%
\glshasattribute{\the\glslongtok}{regular}%
{%
\glssetattribute{\the\glslongtok}{regular}{false}%
}%
}%
}%
}%
\GlsXtrUseAbbrStyleFmts{long-postshort-user}%
}
\newcommand*{\glxtrlongshortscuserdescname}{%
\protect\glslonguserfont{\the\glslongtok}%
\protect\glxtruserparen
{\protect\glsabbrvscuserfont{\the\glsshorttok}}{\the\glslongtok}%
}
\newabbreviationstyle{long-postshort-sc-user-desc}%
{%
\glxtrAccSuppAbbrSetTextShortAttrs\glscategorylabel
\renewcommand*{\CustomAbbreviationFields}{%
  name={\glxtrlongshortscuserdescname},
  sort={\the\glslongtok},
  first={\protect\glslonguserfont{\the\glslongtok}},%
  firstplural={\protect\glslonguserfont{\the\glslongpltok}},%
  text={\protect\glsabbrvscuserfont{\the\glsshorttok}},%
  plural={\protect\glsabbrvscuserfont{\the\glsshortpltok}}}%
}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\csdef{glxtrpostlink\glscategorylabel}{%
\glxtrifwasfirstuse
{%

```

```

        \glxtruserparen
        {\glsfirstabbrvscuserfont{\glsentryshort{\glslabel}}}%
        {\glslabel}%
    }%
    {}%
}%
\glshasattribute{\the\glslabeltok}{regular}%
{%
    \glissetattribute{\the\glslabeltok}{regular}{false}%
}%
{}%
}%
}%
{%
    \GlsXtrUseAbbrStyleFmts{long-postshort-sc-user}%
}
\newabbreviationstyle{short-postlong-user}%
{%
    \glxtrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
    \renewcommand*{\CustomAbbreviationFields}{%
        name={\glxtrshortlongname},
        sort={\the\glsshorttok},
        first={\protect\glsfirstlonguserfont{\the\glslongtok}},%
        firstplural={\protect\glsfirstlonguserfont{\the\glslongpltok}},%
        text={\protect\glsabbrvuserfont{\the\glsshorttok}},%
        plural={\protect\glsabbrvuserfont{\the\glsshortpltok}},%
        description={\protect\glsuserdescription{\the\glslongtok}%
            {\the\glslabeltok}}}%
    \renewcommand*{\GlsXtrPostNewAbbreviation}{%
        \csdef{glxtrpostlink\glscategorylabel}{%
            \glxtrifwasfirstuse
            {%
                \glxtruserparen
                {\glsfirstlonguserfont{\glsentrylong{\glslabel}}}%
                {\glslabel}%
            }%
            {}%
        }%
        \glshasattribute{\the\glslabeltok}{regular}%
        {%
            \glissetattribute{\the\glslabeltok}{regular}{false}%
        }%
        {}%
    }%
}%
{%
    \renewcommand*{\abbrvpluralsuffix}{\glxtrusersuffix}%
    \renewcommand*{\glsabbrvfont}[1]{\glsabbrvuserfont{##1}}%
    \renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvuserfont{##1}}%
    \renewcommand*{\glsfirstlongfont}[1]{\glsfirstlonguserfont{##1}}%

```

```

\renewcommand*{\glslongfont}[1]{\glslonguserfont{##1}}%
\renewcommand*{\glsxtrfullformat}[2]{%
  \glsfirstabbrvuserfont{\glsaccessshort{##1}\ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi
}%
\renewcommand*{\glsxtrfullplformat}[2]{%
  \glsfirstabbrvuserfont{\glsaccessshortpl{##1}\ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \glsfirstabbrvuserfont{\Glsaccessshort{##1}\ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \glsfirstabbrvuserfont{\Glsaccessshortpl{##1}\ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi
}%
\renewcommand*{\glsxtrinlinefullformat}[2]{%
  \glsfirstabbrvuserfont{\glsaccessshort{##1}\ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi
  \glsxtruserparen{\glsfirstlonguserfont{\glsaccesslong{##1}}}{##1}%
}%
\renewcommand*{\glsxtrinlinefullplformat}[2]{%
  \glsfirstabbrvuserfont{\glsaccessshortpl{##1}\ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi
  \glsxtruserparen{\glsfirstlonguserfont{\glsaccesslongpl{##1}}}{##1}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \glsfirstabbrvuserfont{\Glsaccessshort{##1}\ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi
  \glsxtruserparen{\glsfirstlonguserfont{\glsaccesslong{##1}}}{##1}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \glsfirstabbrvuserfont{\Glsaccessshortpl{##1}\ifglsxtrininsertinside##2\fi}%
  \ifglsxtrininsertinside\else##2\fi
  \glsxtruserparen{\glsfirstlonguserfont{\glsaccesslongpl{##1}}}{##1}%
}%
}
\newcommand*{\glsxtrshortlonguserdescname}{%
  \protect\glsabbrvuserfont{\the\glsshorttok}%
  \protect\glsxtruserparen
    {\protect\glslonguserfont{\the\glslongpltok}}%
    {\the\glslabeltok}%
}
\newabbreviationstyle{short-postlong-user-desc}%
{%
  \glsxtrAccSuppAbbrSetTextShortAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glsxtrshortlonguserdescname},
    sort={\the\glsshorttok},

```

```

first={\protect\glsfirstlonguserfont{\the\glslongtok}},%
firstplural={\protect\glsfirstlonguserfont{\the\glslongpltok}},%
text={\protect\glsabbrvuserfont{\the\glsshorttok}},%
plural={\protect\glsabbrvuserfont{\the\glsshortpltok}}}%
}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\csdef{glsxtrpostlink\glscategorylabel}{%
\glsxtrifwasfirstuse
{%
\glsxtruserparen
{\glsfirstlonguserfont{\glstrylong{\glslabel}}}%
{\glslabel}}%
}%
}%
\glsasattribute{\the\glslabeltok}{regular}%
{%
\glssetattribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%
{\%
\GlsXtrUseAbbrStyleFmts{short-postlong-user}%
}
\newabbreviationstyle{long-short-user-desc}%
{%
\glsxtrAccSuppAbbrSetTextShortAttrs\glscategorylabel
\renewcommand*{\CustomAbbreviationFields}{%
name={\glsxtrlongshortuserdescname},
sort={\glsxtrlongshortdescsort},%
first={\protect\glsfirstlonguserfont{\the\glslongtok}%
\protect\glsxtruserparen{\protect\glsfirstabbrvuserfont{\the\glsshorttok}}}%
{\the\glslabeltok}},%
firstplural={\protect\glsfirstlonguserfont{\the\glslongpltok}%
\protect\glsxtruserparen
{\protect\glsfirstabbrvuserfont{\the\glsshortpltok}}{\the\glslabeltok}},%
text={\protect\glsabbrvfont{\the\glsshorttok}},%
plural={\protect\glsabbrvfont{\the\glsshortpltok}}}%
}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glsasattribute{\the\glslabeltok}{regular}%
{%
\glssetattribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%
{\%
\GlsXtrUseAbbrStyleFmts{long-short-user}%
}

```



```

}
\newabbreviationstyle{short-long-user}%
{%
  \glsxtrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glsxtrshortlongname},
    sort={\the\glsshorttok},
    description={\protect\glsuserdescription{\the\glslongtok}%
      {\the\glslabeltok}},%
    first={\protect\glsfirstabbrvuserfont{\the\glsshorttok}%
      \protect\glsxtruserparen{\protect\glsfirstlonguserfont{\the\glslongtok}}%
      {\the\glslabeltok}},%
    firstplural={\protect\glsfirstabbrvuserfont{\the\glsshortpltok}%
      \protect\glsxtruserparen{\protect\glsfirstlonguserfont{\the\glslongpltok}}%
      {\the\glslabeltok}},%
    text={\protect\glsabbrvuserfont{\the\glsshorttok}},%
    plural={\protect\glsabbrvuserfont{\the\glsshortpltok}}}%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \glsattribute{\the\glslabeltok}{regular}%
    {%
      \glssetattribute{\the\glslabeltok}{regular}{false}%
    }%
    {}%
  }%
}%
{%
  \renewcommand*{\abbrvpluralsuffix}{\glsxtrusersuffix}%
  \renewcommand*{\glsabbrvfont}[1]{\glsabbrvuserfont{##1}}%
  \renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvuserfont{##1}}%
  \renewcommand*{\glsfirstlongfont}[1]{\glsfirstlonguserfont{##1}}%
  \renewcommand*{\glslongfont}[1]{\glslonguserfont{##1}}%
  \renewcommand*{\glsxtrfullformat}[2]{%
    \glsfirstabbrvuserfont{\glsaccessshort{##1}\ifglsxtrininsertinside##2\fi}%
    \ifglsxtrininsertinside\else##2\fi
    \glsxtruserparen{\glsfirstlonguserfont{\glsaccesslong{##1}}}{##1}%
  }%
  \renewcommand*{\glsxtrfullplformat}[2]{%
    \glsfirstabbrvuserfont{\glsaccessshortpl{##1}\ifglsxtrininsertinside##2\fi}%
    \ifglsxtrininsertinside\else##2\fi
    \glsxtruserparen{\glsfirstlonguserfont{\glsaccesslongpl{##1}}}{##1}%
  }%
  \renewcommand*{\Glsxtrfullformat}[2]{%
    \glsfirstabbrvuserfont{\Glsaccessshort{##1}\ifglsxtrininsertinside##2\fi}%
    \ifglsxtrininsertinside\else##2\fi
    \glsxtruserparen{\glsfirstlonguserfont{\Glsaccesslong{##1}}}{##1}%
  }%
  \renewcommand*{\Glsxtrfullplformat}[2]{%
    \glsfirstabbrvuserfont{\Glsaccessshortpl{##1}\ifglsxtrininsertinside##2\fi}%
    \ifglsxtrininsertinside\else##2\fi
    \glsxtruserparen{\glsfirstlonguserfont{\Glsaccesslongpl{##1}}}{##1}%
  }%
}

```

```

}%
}
\newabbreviationstyle{short-long-user-desc}%
{%
\glstrAccSuppAbbrSetTextShortAttrs\glscategorylabel
\renewcommand*{\CustomAbbreviationFields}{%
name={\glstrshortlonguserdescname},
sort={\glstrshortlongdescsort},%
first={\protect\glstrfirstabbrvuserfont{\the\glsshorttok}%
\protect\glstruserparen{\protect\glstrfirstlonguserfont{\the\glslongtok}}%
{\the\glslabeltok}},%
firstplural={\protect\glstrfirstabbrvuserfont{\the\glsshortpltok}%
\protect\glstruserparen{\protect\glstrfirstlonguserfont{\the\glslongpltok}}%
{\the\glslabeltok}},%
text={\protect\glstrabbrvfont{\the\glsshorttok}},%
plural={\protect\glstrabbrvfont{\the\glsshortpltok}}}%
}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\glshasattribute{\the\glslabeltok}{regular}%
{%
\glsssetAttribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%
{%
\GlsXtrUseAbbrStyleFmts{short-long-user}%
}
\newrobustcmd*{\glstrifhyphenstart}[3]{%
\ifx\glstrinsert#1\relax
\expandafter\@glstrifhyphenstart#1\relax\relax
\@end@glstrifhyphenstart{#2}{#3}%
\else
\@glstrifhyphenstart#1\relax\relax\@end@glstrifhyphenstart{#2}{#3}%
\fi
}
\def\@glstrifhyphenstart#1#2\@end@glstrifhyphenstart#3#4{%
\ifx-#1\relax#3\else #4\fi
}
\newcommand*{\glstrlonghyphenshort}[4]{%
{%
\glstrifhyphenstart{#4}{\def\glstrwordsep{-}}{}%
\glstrfirstlonghyphenfont{#2\ifglstrinsertinside{#4}\fi}%
\ifglstrinsertinside\else{#4}\fi
\glstrfullsep{#1}%
\glstrparen{\glstrfirstabbrvhyphenfont{#3\ifglstrinsertinside{#4}\fi}%
\ifglstrinsertinside\else{#4}\fi}%
}%
}
\newcommand*{\glstrabbrvhyphenfont}{\glstrabbrvdefaultfont}%

```

```

\newcommand*{\glsfirstabbrvhyphenfont}{\glsabbrvhyphenfont}%
\newcommand*{\glslonghyphenfont}{\glslongdefaultfont}%
\newcommand*{\glsfirstlonghyphenfont}{\glslonghyphenfont}%
\newcommand*{\glsxtrhyphensuffix}{\glsxtrabbrvpluralsuffix}
\newabbreviationstyle{long-hyphen-short-hyphen}%
{%
  \glsxtrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glsxtrlongshortname},
    sort={\the\glsshorttok},
    first={\protect\glsfirstlonghyphenfont{\the\glslongtok}%
      \protect\glsxtrfullsep{\the\glslabeltok}%
      \glsxtrparen{\protect\glsfirstabbrvhyphenfont{\the\glsshorttok}}},%
    firstplural={\protect\glsfirstlonghyphenfont{\the\glslongpltok}%
      \protect\glsxtrfullsep{\the\glslabeltok}%
      \glsxtrparen{\protect\glsfirstabbrvhyphenfont{\the\glsshortpltok}}},%
    text={\protect\glsabbrvhyphenfont{\the\glsshorttok}},%
    plural={\protect\glsabbrvhyphenfont{\the\glsshortpltok}},%
    description={\protect\glslonghyphenfont{\the\glslongtok}}}%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \glsattribute{\the\glslabeltok}{regular}%
    {%
      \glssetattribute{\the\glslabeltok}{regular}{false}%
    }%
    {}%
  }%
}%
{%
  \renewcommand*{\abbrvpluralsuffix}{\glsxtrhyphensuffix}%
  \renewcommand*{\glsabbrvfont}[1]{\glsabbrvhyphenfont{##1}}%
  \renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvhyphenfont{##1}}%
  \renewcommand*{\glsfirstlongfont}[1]{\glsfirstlonghyphenfont{##1}}%
  \renewcommand*{\glslongfont}[1]{\glslonghyphenfont{##1}}%
  \renewcommand*{\glsxtrfullformat}[2]{%
    \glsxtrlonghyphenshort{##1}{\glsaccesslong{##1}}{\glsaccessshort{##1}}{##2}%
  }%
  \renewcommand*{\glsxtrfullplformat}[2]{%
    \glsxtrlonghyphenshort{##1}{\glsaccesslongpl{##1}}%
    {\glsaccessshortpl{##1}}{##2}%
  }%
  \renewcommand*{\Glsxtrfullformat}[2]{%
    \glsxtrlonghyphenshort{##1}{\glsaccesslong{##1}}{\glsaccessshort{##1}}{##2}%
  }%
  \renewcommand*{\Glsxtrfullplformat}[2]{%
    \glsxtrlonghyphenshort{##1}{\glsaccesslongpl{##1}}%
    {\glsaccessshortpl{##1}}{##2}%
  }%
}
\newabbreviationstyle{long-hyphen-short-hyphen-desc}%
{%

```

```

\glxtrAccSuppAbbrSetTextShortAttrs\glscategorylabel
\renewcommand*{\CustomAbbreviationFields}{%
  name={\glxtrlongshortdescname},
  sort={\glxtrlongshortdescsort},
  first={\protect\glsfirstlonghyphenfont{\the\glslongtok}%
    \protect\glxtrfullsep{\the\glslabeltok}%
    \glxtrparen{\protect\glsfirstabbrvhyphenfont{\the\glsshorttok}}},%
  firstplural={\protect\glsfirstlonghyphenfont{\the\glslongpltok}%
    \protect\glxtrfullsep{\the\glslabeltok}%
    \glxtrparen{\protect\glsfirstabbrvhyphenfont{\the\glsshortpltok}}},%
  text={\protect\glsabbrvhyphenfont{\the\glsshorttok}},%
  plural={\protect\glsabbrvhyphenfont{\the\glsshortpltok}}}
}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glsssetAttribute{\the\glslabeltok}{regular}{false}%
  }%
  {}%
}%
}%
{%
  \GlsXtrUseAbbrStyleFmts{long-hyphen-short-hyphen}%
}
\newcommand*{\glxtrlonghyphennoshort}[3]{%
  {%
    \glxtrifhyphenstart{#3}{\def\glxtrwordsep{-}}{%
      \glsfirstlonghyphenfont{#2\ifglxtrininsertinside{#3}\fi}%
      \ifglxtrininsertinside\else{#3}\fi
    }%
  }
}
\newabbreviationstyle{long-hyphen-noshort-desc-noreg}%
{%
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glxtrlongnoshortdescname},
    sort={\expandonce\glxtrorglong},
    first={\protect\glsfirstlonghyphenfont{\the\glslongtok}},%
    firstplural={\protect\glsfirstlonghyphenfont{\the\glslongpltok}},%
    text={\protect\glslonghyphenfont{\the\glslongtok}},%
    plural={\protect\glslonghyphenfont{\the\glslongpltok}}}
}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glsssetAttribute{\the\glslabeltok}{regular}{false}%
  }%
  {}%
}%
}%
{%

```

```

\GlsXtrUseAbbrStyleFmts{long-hyphen-short-hyphen}%
\renewcommand*{\abbrvpluralsuffix}{\glstrabbrvpluralsuffix}%
\renewcommand*\glsabbrvfont[1]{\glsabbrvdefaultfont{##1}}%
\renewcommand*\glsfirstabbrvfont[1]{\glsfirstabbrvdefaultfont{##1}}%
\renewcommand*\glsfirstlongfont[1]{\glsfirstlonghyphenfont{##1}}%
\renewcommand*\glslongfont[1]{\glslonghyphenfont{##1}}%
\renewcommand*\glsxtrsubsequentfmt[2]{%
  \glstrlonghyphennoshort{##1}{\glsaccesslong{##1}}{##2}%
}%
\renewcommand*\glsxtrsubsequentplfmt[2]{%
  \glstrlonghyphennoshort{##1}{\glsaccesslongpl{##1}}{##2}%
}%
\renewcommand*\Glsxtrsubsequentfmt[2]{%
  \glstrlonghyphennoshort{##1}{\Glsaccesslong{##1}}{##2}%
}%
\renewcommand*\Glsxtrsubsequentplfmt[2]{%
  \glstrlonghyphennoshort{##1}{\Glsaccesslongpl{##1}}{##2}%
}%
\renewcommand*\glsxtrinlinefullformat[2]{%
  \glstrlonghyphennoshort{##1}{\glsaccesslong{##1}}{##2}%
  \glxtrfullsep{##1}%
  \glxtrparen{\protect\glsfirstabbrvfont{\glsaccessshort{##1}}}%
}%
\renewcommand*\glsxtrinlinefullplformat[2]{%
  \glstrlonghyphennoshort{##1}{\glsaccesslongpl{##1}}{##2}%
  \glxtrfullsep{##1}%
  \glxtrparen{\protect\glsfirstabbrvfont{\glsaccessshorttpl{##1}}}%
}%
\renewcommand*\Glsxtrinlinefullformat[2]{%
  \glstrlonghyphennoshort{##1}{\Glsaccesslong{##1}}{##2}%
  \glxtrfullsep{##1}%
  \glxtrparen{\protect\glsfirstabbrvfont{\glsaccessshort{##1}}}%
}%
\renewcommand*\Glsxtrinlinefullplformat[2]{%
  \glstrlonghyphennoshort{##1}{\Glsaccesslongpl{##1}}{##2}%
  \glxtrfullsep{##1}%
  \glxtrparen{\protect\glsfirstabbrvfont{\glsaccessshorttpl{##1}}}%
}%
\renewcommand*\glsxtrfullformat[2]{%
  \glstrlonghyphennoshort{##1}{\glsaccesslong{##1}}{##2}%
}%
\renewcommand*\glsxtrfullplformat[2]{%
  \glstrlonghyphennoshort{##1}{\glsaccesslongpl{##1}}{##2}%
}%
\renewcommand*\Glsxtrfullformat[2]{%
  \glstrlonghyphennoshort{##1}{\Glsaccesslong{##1}}{##2}%
}%
\renewcommand*\Glsxtrfullplformat[2]{%
  \glstrlonghyphennoshort{##1}{\Glsaccesslongpl{##1}}{##2}%
}%

```

```

}
\newabbreviationstyle{long-hyphen-noshort-noreg}%
{%
  \glstrAccSuppAbbrSetNameShortAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glstrlongnoshortname},
    sort={\the\glssshorttok},
    first={\protect\glstrfirstlonghyphenfont{\the\glslongtok}},%
    firstplural={\protect\glstrfirstlonghyphenfont{\the\glslongpltok}},%
    text={\protect\glslonghyphenfont{\the\glslongtok}},%
    plural={\protect\glslonghyphenfont{\the\glslongpltok}},%
    description={\the\glslongtok}%
  }%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \glshasattribute{\the\glslabeltok}{regular}%
    {%
      \glsssetAttribute{\the\glslabeltok}{regular}{false}%
    }%
    {}%
  }%
}%
{%
  \GlsXtrUseAbbrStyleFmts{long-hyphen-noshort-desc-noreg}%
}
\newcommand*{\glstrlonghyphen}[3]{%
  {%
    \glstrifhyphenstart{#3}{\def\glstrwordsep{-}}{}%
    \glstrfirstlonghyphenfont{#1}%
  }%
}
\newcommand*{\glstrposthyphenshort}[2]{%
  {%
    \glstrifhyphenstart{#2}{\def\glstrwordsep{-}}{}%
    \ifglstrinsertinside{\glstrfirstlonghyphenfont{#2}}\else{#2}\fi
    \glstrfullsep{#1}%
    \glstrparen
    {\glstrfirstabbrvhyphenfont{\glstryshort{#1}}\ifglstrinsertinside{#2}\fi}%
    \ifglstrinsertinside\else{#2}\fi
  }%
}%
}
\newcommand*{\glstrposthyphensubsequent}[2]{%
  \glstrabbrvfont{\ifglstrinsertinside {#2}\fi}%
  \ifglstrinsertinside \else{#2}\fi
}
\newabbreviationstyle{long-hyphen-postshort-hyphen}%
{%
  \glstrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glstrlongshortname},

```

```

sort={\the\glsshorttok},
first={\protect\glsfirstlonghyphenfont{\the\glslongtok}},%
firstplural={\protect\glsfirstlonghyphenfont{\the\glslongpltok}},%
text={\protect\glsabbrvhyphenfont{\the\glsshorttok}},%
plural={\protect\glsabbrvhyphenfont{\the\glsshortpltok}},%
description={\protect\glslonghyphenfont{\the\glslongtok}}}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
\csdef{glsxtrpostlink\glscategorylabel}{%
\glsxtrifwasfirstuse
{%
\glsxtrposthyphenshort{\glslabel}{\glsinsert}}%
}%
{%
\glsxtrposthyphensubsequent{\glslabel}{\glsinsert}}%
}%
}%
\glsasattribute{\the\glslabeltok}{regular}%
{%
\glsssetattribute{\the\glslabeltok}{regular}{false}%
}%
}%
}%
{%
\renewcommand*{\abbrvpluralsuffix}{\glsxtrabbrvpluralsuffix}%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvhyphenfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvhyphenfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlonghyphenfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslonghyphenfont{##1}}%
\renewcommand*{\glsxtrsubsequentfmt}[2]{%
\glsabbrvfont{\glsaccessshort{##1}}}%
}%
\renewcommand*{\glsxtrsubsequentplfmt}[2]{%
\glsabbrvfont{\glsaccessshortpl{##1}}}%
}%
\renewcommand*{\Glsxtrsubsequentfmt}[2]{%
\glsabbrvfont{\Glsaccessshort{##1}}}%
}%
\renewcommand*{\Glsxtrsubsequentplfmt}[2]{%
\glsabbrvfont{\Glsaccessshortpl{##1}}}%
}%
\renewcommand*{\glsxtrfullformat}[2]{%
\glsxtrlonghyphen{\glsaccesslong{##1}}{##1}{##2}%
}%
\renewcommand*{\glsxtrfullplformat}[2]{%
\glsxtrlonghyphen{\glsaccesslongpl{##1}}{##1}{##2}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
\glsxtrlonghyphen{\Glsaccesslong{##1}}{##1}{##2}%
}%

```

```

\renewcommand*{\Glsxtrfullplformat}[2]{%
  \glsxtrlonghyphen{\Glsaccesslongpl{##1}}{##1}{##2}%
}%
\renewcommand*{\glsxtrinlinefullformat}[2]{%
  \glsfirstlonghyphenfont{\Glsaccesslong{##1}%
    \ifglsxtrininsertinside{##2}\fi}%
  \ifglsxtrininsertinside \else{##2}\fi
}%
\renewcommand*{\glsxtrinlinefullplformat}[2]{%
  \glsfirstlonghyphenfont{\Glsaccesslongpl{##1}%
    \ifglsxtrininsertinside{##2}\fi}%
  \ifglsxtrininsertinside \else{##2}\fi
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \glsfirstlonghyphenfont{\Glsaccesslong{##1}%
    \ifglsxtrininsertinside{##2}\fi}%
  \ifglsxtrininsertinside \else{##2}\fi
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \glsfirstlonghyphenfont{\Glsaccesslongpl{##1}%
    \ifglsxtrininsertinside{##2}\fi}%
  \ifglsxtrininsertinside \else{##2}\fi
}%
}
\newabbreviationstyle{long-hyphen-postshort-hyphen-desc}%
{%
  \glsxtrAccSuppAbbrSetTextShortAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glsxtrlongshortdescname},
    sort={\glsxtrlongshortdescsort},%
    first={\protect\glsfirstlonghyphenfont{\the\glslongtok}},%
    firstplural={\protect\glsfirstlonghyphenfont{\the\glslongpltok}},%
    text={\protect\glsabbrvhyphenfont{\the\glsshorttok}},%
    plural={\protect\glsabbrvhyphenfont{\the\glsshortpltok}}}%
  }%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \csdef{glsxtrpostlink\glscategorylabel}{%
      \glsxtrifwasfirstuse
      {%
        \glsxtrposthyphenshort{\glslabel}{\glsinsert}%
      }%
      {%
        \glsxtrposthyphensubsequent{\glslabel}{\glsinsert}%
      }%
    }%
    \glshasattribute{\the\glslabeltok}{regular}%
    {%
      \glissetattribute{\the\glslabeltok}{regular}{false}%
    }%
    {}%
  }%

```



```

    }%
}%
{%
  \GlsXtrUseAbbrStyleFmts{long-hyphen-postshort-hyphen}%
}
\newcommand*{\glxtrshorthyphenlong}[4]{%
  {%
    \glxtrifhyphenstart{#4}{\def\glxtrwordsep{-}}{}%
    \glsfirstabbrvhyphenfont{#2\ifglxtrininsertinside{#4}\fi}%
    \ifglxtrininsertinside\else{#4}\fi
    \glxtrfullsep{#1}%
    \glxtrparen{\glsfirstlonghyphenfont{#3\ifglxtrininsertinside{#4}\fi}%
      \ifglxtrininsertinside\else{#4}\fi}%
  }%
}
\newabbreviationstyle{short-hyphen-long-hyphen}%
{%
  \glxtrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glxtrshortlongname},
    sort={\the\glsshorttok},
    first={\protect\glsfirstabbrvhyphenfont{\the\glsshorttok}%
      \protect\glxtrfullsep{\the\glslabeltok}%
      \glxtrparen{\protect\glsfirstlonghyphenfont{\the\glslongtok}}},%
    firstplural={\protect\glsfirstabbrvhyphenfont{\the\glsshortpltok}%
      \protect\glxtrfullsep{\the\glslabeltok}%
      \glxtrparen{\protect\glsfirstlonghyphenfont{\the\glslongpltok}}},%
    text={\protect\glsabbrvhyphenfont{\the\glsshorttok}},%
    plural={\protect\glsabbrvhyphenfont{\the\glsshortpltok}},%
    description={\protect\glslonghyphenfont{\the\glslongtok}}}%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \glshasattribute{\the\glslabeltok}{regular}%
    {%
      \glissetattribute{\the\glslabeltok}{regular}{false}%
    }%
    {}%
  }%
}%
{%
  \renewcommand*{\abbrvpluralsuffix}{\glxtrhyphensuffix}%
  \renewcommand*{\glsabbrvfont}[1]{\glsabbrvhyphenfont{##1}}%
  \renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvhyphenfont{##1}}%
  \renewcommand*{\glsfirstlongfont}[1]{\glsfirstlonghyphenfont{##1}}%
  \renewcommand*{\glslongfont}[1]{\glslonghyphenfont{##1}}%
  \renewcommand*{\glxtrfullformat}[2]{%
    \glxtrshorthyphenlong{##1}{\glsaccessshort{##1}}{\glsaccesslong{##1}}{##2}%
  }%
  \renewcommand*{\glxtrfullplformat}[2]{%
    \glxtrshorthyphenlong{##1}%
    {\glsaccessshortpl{##1}}{\glsaccesslongpl{##1}}{##2}%
  }%
}

```

```

}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \glxstrshorthyphenlong{##1}{\glssaccessshort{##1}}{\Glsaccesslong{##1}}{##2}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \glxstrshorthyphenlong{##1}%
  {\glssaccessshortpl{##1}}{\Glsaccesslongpl{##1}}{##2}%
}%
}
\newabbreviationstyle{short-hyphen-long-hyphen-desc}%
{%
  \glxtrAccSuppAbbrSetTextShortAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glxtrshortlongdescname},
    sort={\glxtrshortlongdescsort},
    first={\protect\glsfirstabbrvhyphenfont{\the\glssshorttok}%
      \protect\glxtrfullsep{\the\glslabeltok}%
      \glxtrparen{\protect\glsfirstlonghyphenfont{\the\glslongtok}}},%
    firstplural={\protect\glsfirstabbrvhyphenfont{\the\glssshortpltok}%
      \protect\glxtrfullsep{\the\glslabeltok}%
      \glxtrparen{\protect\glsfirstlonghyphenfont{\the\glslongpltok}}},%
    text={\protect\glsabbrvhyphenfont{\the\glssshorttok}},%
    plural={\protect\glsabbrvhyphenfont{\the\glssshortpltok}}%
  }%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \glshasattribute{\the\glslabeltok}{regular}%
    {%
      \glsssetAttribute{\the\glslabeltok}{regular}{false}%
    }%
    {}%
  }%
}%
\newcommand*{\glxtrshorthyphen}[3]{%
  {%
    \glxtrifhyphenstart{#3}{\def\glxtrwordsep{-}}{%
      \glsfirstabbrvhyphenfont{#1}%
    }%
  }%
}
\newcommand*{\glxtrposthyphenlong}[2]{%
  {%
    \glxtrifhyphenstart{#2}{\def\glxtrwordsep{-}}{%
      \ifglxtrininsertinside{\glsfirstabbrvhyphenfont{#2}}\else{#2}\fi
      \glxtrfullsep{#1}%
      \glxtrparen
      {\glsfirstlonghyphenfont{\glsentrylong{#1}}\ifglxtrininsertinside{#2}\fi}%
      \ifglxtrininsertinside\else{#2}\fi
    }%
  }%
}

```

```

}%
}
\newabbreviationstyle{short-hyphen-postlong-hyphen}%
{%
  \glxstrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glxstrshortlongname},
    sort={\the\glsshorttok},
    first={\protect\glsfirstabbrvhyphenfont{\the\glsshorttok}},%
    firstplural={\protect\glsfirstabbrvhyphenfont{\the\glsshortpltok}},%
    text={\protect\glsabbrvhyphenfont{\the\glsshorttok}},%
    plural={\protect\glsabbrvhyphenfont{\the\glsshortpltok}},%
    description={\protect\glslonghyphenfont{\the\glslongtok}}}%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \csdef{glxstrpostlink\glscategorylabel}{%
      \glxstrifwasfirstuse
      {%
        \glxstrposthyphenlong{\glslabel}{\glsinsert}}%
      }%
      {%
        \glxstrposthyphensubsequent{\glslabel}{\glsinsert}}%
      }%
    }%
    \glshasattribute{\the\glslabeltok}{regular}%
    {%
      \glissetattribute{\the\glslabeltok}{regular}{false}%
    }%
    {}%
  }%
}%
{%
  \renewcommand*{\abbrvpluralsuffix}{\glxtrabbrvpluralsuffix}%
  \renewcommand*{\glsabbrvfont}[1]{\glsabbrvhyphenfont{##1}}%
  \renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvhyphenfont{##1}}%
  \renewcommand*{\glsfirstlongfont}[1]{\glsfirstlonghyphenfont{##1}}%
  \renewcommand*{\glslongfont}[1]{\glslonghyphenfont{##1}}%
  \renewcommand*{\glxtrsubsequentfmt}[2]{%
    \glsabbrvfont{\glsaccessshort{##1}}}%
  }%
  \renewcommand*{\glxtrsubsequentplfmt}[2]{%
    \glsabbrvfont{\glsaccessshortpl{##1}}}%
  }%
  \renewcommand*{\Glsxtrsubsequentfmt}[2]{%
    \glsabbrvfont{\Glsaccessshort{##1}}}%
  }%
  \renewcommand*{\Glsxtrsubsequentplfmt}[2]{%
    \glsabbrvfont{\Glsaccessshortpl{##1}}}%
  }%
  \renewcommand*{\glxtrfullformat}[2]{%
    \glxtrshorthyphen{\glsaccessshort{##1}}{##1}{##2}%
  }%
}

```

```

}%
\renewcommand*{\glstrfullplformat}[2]{%
  \glstrshorthyphen{\glsaccessshortpl{##1}}{##1}{##2}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \glstrshorthyphen{\Glsaccessshort{##1}}{##1}{##2}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \glstrshorthyphen{\Glsaccessshortpl{##1}}{##1}{##2}%
}%
\renewcommand*{\glstrinlinefullformat}[2]{%
  \glsfirstabbrvhyphenfont{\glsaccessshort{##1}}%
  \ifglstrinsertinside{##2}\fi}%
  \ifglstrinsertinside \else{##2}\fi
}%
\renewcommand*{\glstrinlinefullplformat}[2]{%
  \glsfirstabbrvhyphenfont{\glsaccessshortpl{##1}}%
  \ifglstrinsertinside{##2}\fi}%
  \ifglstrinsertinside \else{##2}\fi
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \glsfirstabbrvhyphenfont{\Glsaccessshort{##1}}%
  \ifglstrinsertinside{##2}\fi}%
  \ifglstrinsertinside \else{##2}\fi
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \glsfirstabbrvhyphenfont{\Glsaccessshortpl{##1}}%
  \ifglstrinsertinside{##2}\fi}%
  \ifglstrinsertinside \else{##2}\fi
}%
}
\newabbreviationstyle{short-hyphen-postlong-hyphen-desc}%
{%
  \glstrAccSuppAbbrSetTextShortAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glstrshortlongdescname},
    sort={\glstrshortlongdescsort},%
    first={\protect\glsfirstabbrvhyphenfont{\the\glsshorttok}},%
    firstplural={\protect\glsfirstabbrvhyphenfont{\the\glsshortpltok}},%
    text={\protect\glsabbrvhyphenfont{\the\glsshorttok}},%
    plural={\protect\glsabbrvhyphenfont{\the\glsshortpltok}}}%
  }%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \csdef{glstrpostlink\glscategorylabel}{%
      \glstrifwasfirstuse
      {%
        \glstrposthyphenlong{\glslabel}{\glsinsert}}%
      }%
    {%
      \glstrposthyphensubsequent{\glslabel}{\glsinsert}}%
    }%
  }%

```

```

    }%
  }%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glssetaattribute{\the\glslabeltok}{regular}{false}%
  }%
  {}%
}%
}%
{%
  \GlsXtrUseAbbrStyleFmts{short-hyphen-postlong-hyphen}%
}
\newcommand*{\glsabbrvonlyfont}{\glsabbrvdefaultfont}%
\newcommand*{\glsfirstabbrvonlyfont}{\glsabbrvonlyfont}%
\newcommand*{\glslongonlyfont}{\glslongdefaultfont}%
\newcommand*{\glsfirstlongonlyfont}{\glslongonlyfont}%
\newcommand*{\glstronlysuffix}{\glstrabbrvpluralsuffix}%
\newcommand*{\glstronlyname}{%
  \protect\glsabbrvonlyfont{\the\glsshorttok}%
}
\newabbreviationstyle{long-only-short-only}%
{%
  \glstrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glstronlyname},
    sort={\the\glsshorttok},
    first={\protect\glsfirstlongonlyfont{\the\glslongtok}},%
    firstplural={\protect\glsfirstlongonlyfont{\the\glslongpltok}},%
    text={\protect\glsabbrvonlyfont{\the\glsshorttok}},%
    plural={\protect\glsabbrvonlyfont{\the\glsshortpltok}},%
    description={\protect\glslongonlyfont{\the\glslongtok}}}%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \glshasattribute{\the\glslabeltok}{regular}%
    {%
      \glssetaattribute{\the\glslabeltok}{regular}{false}%
    }%
    {}%
  }%
}%
}%
{%
  \renewcommand*{\abbrvpluralsuffix}{\glstronlysuffix}%
  \renewcommand*{\glsabbrvfont}[1]{\glsabbrvonlyfont{##1}}%
  \renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvonlyfont{##1}}%
  \renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongonlyfont{##1}}%
  \renewcommand*{\glslongfont}[1]{\glslongonlyfont{##1}}%
  \renewcommand*{\glstrfullformat}[2]{%
    \glsfirstlongonlyfont{\glsaccesslong{##1}\ifglstrinsertinside##2\fi}%
    \ifglstrinsertinside\else##2\fi
  }%
  \renewcommand*{\glstrfullplformat}[2]{%

```

```

\glsfirstlongonlyfont{\glsaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
\glsfirstlongonlyfont{\Glsaccesslong{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
\glsfirstlongonlyfont{\Glsaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\glsxtrinlinefullformat}[2]{%
\glsfirstlongonlyfont{\glsaccesslong{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
\glsxtrfullsep{##1}%
\glsxtrparen{\protect\glsfirstabbrvonlyfont{\glsaccessshort{##1}}}%
}%
\renewcommand*{\glsxtrinlinefullplformat}[2]{%
\glsfirstlongonlyfont{\glsaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
\glsxtrfullsep{##1}%
\glsxtrparen{\protect\glsfirstabbrvonlyfont{\glsaccessshortpl{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
\glsfirstlongonlyfont{\Glsaccesslong{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
\glsxtrfullsep{##1}%
\glsxtrparen{\protect\glsfirstabbrvonlyfont{\Glsaccessshortpl{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
\glsfirstlongonlyfont{\Glsaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
\ifglxtrinsertinside\else##2\fi
\glsxtrfullsep{##1}%
\glsxtrparen{\protect\glsfirstabbrvonlyfont{\Glsaccessshortpl{##1}}}%
}%
}
\newcommand*{\glsxtronlydescsort}{\the\glslongtok}
\newcommand*{\glsxtronlydescname}{%
\protect\glslongfont{\the\glslongtok}%
}
\newabbreviationstyle{long-only-short-only-desc}%
{%
\glsxtrAccSuppAbbrSetTextShortAttrs\glscategorylabel
\renewcommand*{\CustomAbbreviationFields}{%
name={\glsxtronlydescname},
sort={\glsxtronlydescsort},%
first={\protect\glsfirstlongonlyfont{\the\glslongtok}},%
firstplural={\protect\glsfirstlongonlyfont{\the\glslongpltok}},%
text={\protect\glsabbrvonlyfont{\the\glsshorttok}},%
plural={\protect\glsabbrvonlyfont{\the\glsshortpltok}}%
}

```

```

}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%
    \glissetattribute{\the\glslabeltok}{regular}{false}%
  }%
  {}%
}%
}%
{%
  \GlsXtrUseAbbrStyleFmts{long-only-short-only}%
}
\newcommand*{\glsabbrvsconlyfont}{\glsabbrvscfont}%
\newcommand*{\glsfirstabbrvsconlyfont}{\glsabbrvsconlyfont}%
\newcommand*{\glsxtrscnlysuffix}{\glsxtrscsuffix}
\newcommand*{\glsxtrscnlyname}{%
  \protect\glsabbrvsconlyfont{\the\glsshorttok}%
}
\newabbreviationstyle{long-only-short-sc-only}%
{%
  \glsxtrAccSuppAbbrSetFirstLongAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glsxtrscnlyname},
    sort={\the\glsshorttok},
    first={\protect\glsfirstlongonlyfont{\the\glslongtok}},%
    firstplural={\protect\glsfirstlongonlyfont{\the\glslongpltok}},%
    text={\protect\glsabbrvsconlyfont{\the\glsshorttok}},%
    plural={\protect\glsabbrvsconlyfont{\the\glsshortpltok}},%
    description={\protect\glsfirstlongonlyfont{\the\glslongtok}}}%
  \renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \glshasattribute{\the\glslabeltok}{regular}%
    {%
      \glissetattribute{\the\glslabeltok}{regular}{false}%
    }%
    {}%
  }%
}%
}%
{%
  \renewcommand*{\abbrvpluralsuffix}{\glsxtrscnlysuffix}%
  \renewcommand*{\glsabbrvfont}[1]{\glsabbrvsconlyfont{##1}}%
  \renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvsconlyfont{##1}}%
  \renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongonlyfont{##1}}%
  \renewcommand*{\glslongfont}[1]{\glsfirstlongonlyfont{##1}}%
  \renewcommand*{\glsxtrfullformat}[2]{%
    \glsfirstlongonlyfont{\glsaccesslong{##1}\ifglsxtrininsertinside##2\fi}%
    \ifglsxtrininsertinside\else##2\fi
  }%
  \renewcommand*{\glsxtrfullplformat}[2]{%
    \glsfirstlongonlyfont{\glsaccesslongpl{##1}\ifglsxtrininsertinside##2\fi}%
    \ifglsxtrininsertinside\else##2\fi
  }%
}

```

```

}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \glsfirstlongonlyfont{\Glsaccesslong{##1}\ifglxtrinsertinside##2\fi}%
  \ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \glsfirstlongonlyfont{\Glsaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
  \ifglxtrinsertinside\else##2\fi
}%
\renewcommand*{\glxtrinlinefullformat}[2]{%
  \glsfirstlongonlyfont{\glssaccesslong{##1}\ifglxtrinsertinside##2\fi}%
  \ifglxtrinsertinside\else##2\fi
  \glxtrfullsep{##1}%
  \glxtrparen{\protect\glssfirstabbrvsonlyfont{\glssaccessshort{##1}}}%
}%
\renewcommand*{\glxtrinlinefullplformat}[2]{%
  \glsfirstlongonlyfont{\glssaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
  \ifglxtrinsertinside\else##2\fi
  \glxtrfullsep{##1}%
  \glxtrparen{\protect\glssfirstabbrvsonlyfont{\glssaccessshortpl{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullformat}[2]{%
  \glsfirstlongonlyfont{\Glsaccesslong{##1}\ifglxtrinsertinside##2\fi}%
  \ifglxtrinsertinside\else##2\fi
  \glxtrfullsep{##1}%
  \glxtrparen{\protect\glssfirstabbrvsonlyfont{\glssaccessshortpl{##1}}}%
}%
\renewcommand*{\Glsxtrinlinefullplformat}[2]{%
  \glsfirstlongonlyfont{\Glsaccesslongpl{##1}\ifglxtrinsertinside##2\fi}%
  \ifglxtrinsertinside\else##2\fi
  \glxtrfullsep{##1}%
  \glxtrparen{\protect\glssfirstabbrvsonlyfont{\Glsaccessshortpl{##1}}}%
}%
}
\newcommand*{\glxtrsconlydescsort}{\glxtronlydescsort}
\newcommand*{\glxtrsconlydescname}{\glxtronlydescname}
\newabbreviationstyle{long-only-short-sc-only-desc}%
{%
  \glxtrAccSuppAbbrSetTextShortAttrs\glscategorylabel
  \renewcommand*{\CustomAbbreviationFields}{%
    name={\glxtrsconlydescname},
    sort={\glxtrsconlydescsort},%
    first={\protect\glssfirstlongonlyfont{\the\glslongtok}},%
    firstplural={\protect\glssfirstlongonlyfont{\the\glslongpltok}},%
    text={\protect\glssabbrvsonlyfont{\the\glssshorttok}},%
    plural={\protect\glssabbrvsonlyfont{\the\glssshortpltok}}}%
}%
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glshasattribute{\the\glslabeltok}{regular}%
  {%

```



```

        \glsssetAttribute{\the\glslabeltok}{regular}{false}%
    }%
    {}%
}%
{%
    \GlsXtrUseAbbrStyleFmts{long-only-short-sc-only}%
}
\let\@glstr@org@markright\markright
\renewcommand*{\markright}[1]{%
    \glstrmarkhook
    \@glstr@org@markright{\@glstrinmark#1\@glstrnotinmark}%
    \glstrrestoremarkhook
}
\let\@glstr@org@markboth\markboth
\renewcommand*{\markboth}[2]{%
    \glstrmarkhook
    \@glstr@org@markboth
        {\@glstrinmark#1\@glstrnotinmark}%
        {\@glstrinmark#2\@glstrnotinmark}%
    \glstrrestoremarkhook
}
\let\@glstr@org@@starttoc\@starttoc
\renewcommand*{\@starttoc}[1]{%
    \glstrmarkhook
    \@glstrinmark
    \@glstr@org@@starttoc{#1}%
    \@glstrnotinmark
    \glstrrestoremarkhook
}
\newcommand*{\glstrRevertMarks}{%
    \let\markright\@glstr@org@markright
    \let\markboth\@glstr@org@markboth
    \let\@starttoc\@glstr@org@@starttoc
}
\newcommand*{\glstrRevertTocMarks}{%
    \let\@starttoc\@glstr@org@@starttoc
}
\newcommand*{\glstrifinmark}[2]{#2}
\newrobustcmd*{\@glstrinmark}{%
    \let\glstrifinmark\@firstoftwo
}
\newrobustcmd*{\@glstrnotinmark}{%
    \let\glstrifinmark\@secondoftwo
}
\ifdef\texorpdfstring
{
    \newcommand*{\glstrtitleorpdforheading}[3]{\texorpdfstring{#1}{#2}}
}
{

```

```

\newcommand*{\glxstrtitleorpdforheading}[3]{#1}
}
\newcommand*{\glxstrmarkhook}{%
\let\@glxstr@org@MakeUppercase\MakeUppercase
\let\@glxstr@org@glxstrtitleorpdforheading\glxstrtitleorpdforheading
\let\@glxstr@org@glxstrtitleshort\glxstrtitleshort
\let\@glxstr@org@glxstrtitleshortpl\glxstrtitleshortpl
\let\@glxstr@org@Glsxstrtitleshort\Glsxstrtitleshort
\let\@glxstr@org@Glsxstrtitleshortpl\Glsxstrtitleshortpl
\let\@glxstr@org@glxstrtitlename\glxstrtitlename
\let\@glxstr@org@Glsxstrtitlename\Glsxstrtitlename
\let\@glxstr@org@glxstrtitletext\glxstrtitletext
\let\@glxstr@org@Glsxstrtitletext\Glsxstrtitletext
\let\@glxstr@org@glxstrtitleplural\glxstrtitleplural
\let\@glxstr@org@Glsxstrtitleplural\Glsxstrtitleplural
\let\@glxstr@org@glxstrtitlefirst\glxstrtitlefirst
\let\@glxstr@org@Glsxstrtitlefirst\Glsxstrtitlefirst
\let\@glxstr@org@glxstrtitlefirstplural\glxstrtitlefirstplural
\let\@glxstr@org@Glsxstrtitlefirstplural\Glsxstrtitlefirstplural
\let\@glxstr@org@glxstrtitlelong\glxstrtitlelong
\let\@glxstr@org@glxstrtitlelongpl\glxstrtitlelongpl
\let\@glxstr@org@Glsxstrtitlelong\Glsxstrtitlelong
\let\@glxstr@org@Glsxstrtitlelongpl\Glsxstrtitlelongpl
\let\@glxstr@org@glxstrtitlefull\glxstrtitlefull
\let\@glxstr@org@glxstrtitlefullpl\glxstrtitlefullpl
\let\@glxstr@org@Glsxstrtitlefull\Glsxstrtitlefull
\let\@glxstr@org@Glsxstrtitlefullpl\Glsxstrtitlefullpl
\let\glxstrifinmark\@firstoftwo
\let\MakeUppercase\MakeTextUppercase
\let\glxstrtitleorpdforheading\@thirdofthree
\let\glxstrtitleshort\glxstrheadshort
\let\glxstrtitleshortpl\glxstrheadshortpl
\let\Glsxstrtitleshort\Glsxstrheadshort
\let\Glsxstrtitleshortpl\Glsxstrheadshortpl
\let\glxstrtitlename\glxstrheadname
\let\Glsxstrtitlename\Glsxstrheadname
\let\glxstrtitletext\glxstrheadtext
\let\Glsxstrtitletext\Glsxstrheadtext
\let\glxstrtitleplural\glxstrheadplural
\let\Glsxstrtitleplural\Glsxstrheadplural
\let\glxstrtitlefirst\glxstrheadfirst
\let\Glsxstrtitlefirst\Glsxstrheadfirst
\let\glxstrtitlefirstplural\glxstrheadfirstplural
\let\Glsxstrtitlefirstplural\Glsxstrheadfirstplural
\let\glxstrtitlelong\glxstrheadlong
\let\glxstrtitlelongpl\glxstrheadlongpl
\let\Glsxstrtitlelong\Glsxstrheadlong
\let\Glsxstrtitlelongpl\Glsxstrheadlongpl
\let\glxstrtitlefull\glxstrheadfull
\let\glxstrtitlefullpl\glxstrheadfullpl

```

```

\let\Glsxtrtitlefull\Glsxtrheadfull
\let\Glsxtrtitlefullpl\Glsxtrheadfullpl
}
\newcommand*{\glxtrrestoremarkhook}{%
\let\glxtrifinmark\@secondoftwo
\let\MakeUppercase\@glxtr@org@MakeUppercase
\let\glxtrtitleorpdforheading\@glxtr@org@glxtrtitleorpdforheading
\let\glxtrtitleshort\@glxtr@org@glxtrtitleshort
\let\glxtrtitleshortpl\@glxtr@org@glxtrtitleshortpl
\let\Glsxtrtitleshort\@glxtr@org@Glsxtrtitleshort
\let\Glsxtrtitleshortpl\@glxtr@org@Glsxtrtitleshortpl
\let\glxtrtitlename\@glxtr@org@glxtrtitlename
\let\Glsxtrtitlename\@glxtr@org@Glsxtrtitlename
\let\glxtrtitletext\@glxtr@org@glxtrtitletext
\let\Glsxtrtitletext\@glxtr@org@Glsxtrtitletext
\let\glxtrtitleplural\@glxtr@org@glxtrtitleplural
\let\Glsxtrtitleplural\@glxtr@org@Glsxtrtitleplural
\let\glxtrtitlefirst\@glxtr@org@glxtrtitlefirst
\let\Glsxtrtitlefirst\@glxtr@org@Glsxtrtitlefirst
\let\glxtrtitlefirstplural\@glxtr@org@glxtrtitlefirstplural
\let\Glsxtrtitlefirstplural\@glxtr@org@Glsxtrtitlefirstplural
\let\glxtrtitlelong\@glxtr@org@glxtrtitlelong
\let\glxtrtitlelongpl\@glxtr@org@glxtrtitlelongpl
\let\Glsxtrtitlelong\@glxtr@org@Glsxtrtitlelong
\let\Glsxtrtitlelongpl\@glxtr@org@Glsxtrtitlelongpl
\let\glxtrtitlefull\@glxtr@org@glxtrtitlefull
\let\glxtrtitlefullpl\@glxtr@org@glxtrtitlefullpl
\let\Glsxtrtitlefull\@glxtr@org@Glsxtrtitlefull
\let\Glsxtrtitlefullpl\@glxtr@org@Glsxtrtitlefullpl
}
\newcommand*{\glxtrheadshort}[1]{%
\protect\NoCaseChange
{%
\glxifattribute{#1}{headuc}{true}%
{%
\GLSxtrshort[noindex,hyper=false]{#1}[]%
}%
{%
\glxtrshort[noindex,hyper=false]{#1}[]%
}%
}%
}
\newrobustcmd*{\glxtrtitleshort}[1]{%
\glxtrshort[noindex,hyper=false]{#1}[]%
}
\newcommand*{\glxtrheadshortpl}[1]{%
\protect\NoCaseChange
{%
\glxifattribute{#1}{headuc}{true}%
{%

```

```

        \GLSxtrshortpl [noindex,hyper=false]{#1} []%
    }%
    {%
        \glsxtrshortpl [noindex,hyper=false]{#1} []%
    }%
}%
}
\newrobustcmd*{\glsxtrtitleshortpl}[1]{%
    \glsxtrshortpl [noindex,hyper=false]{#1} []%
}
\newcommand*{\Glsxtrheadshort}[1]{%
    \protect\NoCaseChange
    {%
        \glsifattribute{#1}{headuc}{true}%
        {%
            \GLSxtrshort [noindex,hyper=false]{#1} []%
        }%
        {%
            \Glsxtrshort [noindex,hyper=false]{#1} []%
        }%
    }%
}
\newrobustcmd*{\Glsxtrtitleshort}[1]{%
    \Glsxtrshort [noindex,hyper=false]{#1} []%
}
\newrobustcmd*{\GLSxtrtitleshort}[1]{%
    \GLSxtrshort [noindex,hyper=false]{#1} []%
}
\newcommand*{\Glsxtrheadshortpl}[1]{%
    \protect\NoCaseChange
    {%
        \glsifattribute{#1}{headuc}{true}%
        {%
            \GLSxtrshortpl [noindex,hyper=false]{#1} []%
        }%
        {%
            \Glsxtrshortpl [noindex,hyper=false]{#1} []%
        }%
    }%
}
\newrobustcmd*{\Glsxtrtitleshortpl}[1]{%
    \Glsxtrshortpl [noindex,hyper=false]{#1} []%
}
\newrobustcmd*{\GLSxtrtitleshortpl}[1]{%
    \GLSxtrshortpl [noindex,hyper=false]{#1} []%
}
\newcommand*{\glsxtrheadname}[1]{%
    \protect\NoCaseChange
    {%
        \glsifattribute{#1}{headuc}{true}%
    }

```

```

    {%
      \GLSname[noindex,hyper=false]{#1}[]%
    }%
    {%
      \glsname[noindex,hyper=false]{#1}[]%
    }%
  }%
}
\newrobustcmd*{\glsxtrtitlename}[1]{%
  \glsname[noindex,hyper=false]{#1}[]%
}
\newcommand*{\Glsxtrheadname}[1]{%
  \protect\NoCaseChange
  {%
    \glsifattribute{#1}{headuc}{true}%
    {%
      \GLSname[noindex,hyper=false]{#1}[]%
    }%
    {%
      \Glsname[noindex,hyper=false]{#1}[]%
    }%
  }%
}
\newrobustcmd*{\Glsxtrtitlename}[1]{%
  \Glsname[noindex,hyper=false]{#1}[]%
}
\newrobustcmd*{\GLSxtrtitlename}[1]{%
  \GLSname[noindex,hyper=false]{#1}[]%
}
\newcommand*{\glsxtrheadtext}[1]{%
  \protect\NoCaseChange
  {%
    \glsifattribute{#1}{headuc}{true}%
    {%
      \GLStext[noindex,hyper=false]{#1}[]%
    }%
    {%
      \glstext[noindex,hyper=false]{#1}[]%
    }%
  }%
}
\newrobustcmd*{\glsxtrtitletext}[1]{%
  \glstext[noindex,hyper=false]{#1}[]%
}
\newcommand*{\Glsxtrheadtext}[1]{%
  \protect\NoCaseChange
  {%
    \glsifattribute{#1}{headuc}{true}%
    {%
      \GLStext[noindex,hyper=false]{#1}[]%
    }%
  }%
}

```

```

}%
{%
    \Glstext[noindex,hyper=false]{#1}[]%
}%
}%
}
\newrobustcmd*{\Glsxtrtitletext}[1]{%
    \Glstext[noindex,hyper=false]{#1}[]%
}
\newrobustcmd*{\Glsxtrtitletext}[1]{%
    \Glstext[noindex,hyper=false]{#1}[]%
}
\newcommand*{\glsxtrheadplural}[1]{%
    \protect\NoCaseChange
    {%
        \glsifattribute{#1}{headuc}{true}%
        {%
            \GLSplural[noindex,hyper=false]{#1}[]%
        }%
        {%
            \glsplural[noindex,hyper=false]{#1}[]%
        }%
    }%
}
\newrobustcmd*{\glsxtrtitleplural}[1]{%
    \glsplural[noindex,hyper=false]{#1}[]%
}
\newcommand*{\Glsxtrheadplural}[1]{%
    \protect\NoCaseChange
    {%
        \glsifattribute{#1}{headuc}{true}%
        {%
            \GLSplural[noindex,hyper=false]{#1}[]%
        }%
        {%
            \Glsplural[noindex,hyper=false]{#1}[]%
        }%
    }%
}
\newrobustcmd*{\Glsxtrtitleplural}[1]{%
    \Glsplural[noindex,hyper=false]{#1}[]%
}
\newrobustcmd*{\Glsxtrtitleplural}[1]{%
    \GLSplural[noindex,hyper=false]{#1}[]%
}
\newcommand*{\glsxtrheadfirst}[1]{%
    \protect\NoCaseChange
    {%
        \glsifattribute{#1}{headuc}{true}%
        {%

```

```

        \GLSfirst[noindex,hyper=false]{#1}[]%
    }%
    {%
        \glsfirst[noindex,hyper=false]{#1}[]%
    }%
}%
}
\newrobustcmd*{\glsxtrtitlefirst}[1]{%
    \glsfirst[noindex,hyper=false]{#1}[]%
}
\newcommand*{\Glsxtrheadfirst}[1]{%
    \protect\NoCaseChange
    {%
        \glsifattribute{#1}{headuc}{true}%
        {%
            \GLSfirst[noindex,hyper=false]{#1}[]%
        }%
        {%
            \Glsfirst[noindex,hyper=false]{#1}[]%
        }%
    }%
}%
}
\newrobustcmd*{\Glsxtrtitlefirst}[1]{%
    \Glsfirst[noindex,hyper=false]{#1}[]%
}
\newrobustcmd*{\GLSxtrtitlefirst}[1]{%
    \GLSfirst[noindex,hyper=false]{#1}[]%
}
\newcommand*{\glsxtrheadfirstplural}[1]{%
    \protect\NoCaseChange
    {%
        \glsifattribute{#1}{headuc}{true}%
        {%
            \GLSfirstplural[noindex,hyper=false]{#1}[]%
        }%
        {%
            \glsfirstplural[noindex,hyper=false]{#1}[]%
        }%
    }%
}%
}
\newrobustcmd*{\glsxtrtitlefirstplural}[1]{%
    \glsfirstplural[noindex,hyper=false]{#1}[]%
}
\newcommand*{\Glsxtrheadfirstplural}[1]{%
    \protect\NoCaseChange
    {%
        \glsifattribute{#1}{headuc}{true}%
        {%
            \GLSfirstplural[noindex,hyper=false]{#1}[]%
        }%
    }%
}

```

```

    {%
      \Glsfirstplural[noindex,hyper=false]{#1}[]%
    }%
  }%
}
\newrobustcmd*{\Glsxtrtitlefirstplural}[1]{%
  \Glsfirstplural[noindex,hyper=false]{#1}[]%
}
\newrobustcmd*{\Glsxtrtitlefirstplural}[1]{%
  \Glsfirstplural[noindex,hyper=false]{#1}[]%
}
\newcommand*{\glxtrheadlong}[1]{%
  \protect\NoCaseChange
  {%
    \glusifattribute{#1}{headuc}{true}%
    {%
      \GLSxtrlong[noindex,hyper=false]{#1}[]%
    }%
    {%
      \glxtrlong[noindex,hyper=false]{#1}[]%
    }%
  }%
}
\newrobustcmd*{\glxtrtitlelong}[1]{%
  \glxtrlong[noindex,hyper=false]{#1}[]%
}
\newcommand*{\glxtrheadlongpl}[1]{%
  \protect\NoCaseChange
  {%
    \glusifattribute{#1}{headuc}{true}%
    {%
      \GLSxtrlongpl[noindex,hyper=false]{#1}[]%
    }%
    {%
      \glxtrlongpl[noindex,hyper=false]{#1}[]%
    }%
  }%
}
\newrobustcmd*{\glxtrtitlelongpl}[1]{%
  \glxtrlongpl[noindex,hyper=false]{#1}[]%
}
\newcommand*{\Glsxtrheadlong}[1]{%
  \protect\NoCaseChange
  {%
    \glusifattribute{#1}{headuc}{true}%
    {%
      \GLSxtrlong[noindex,hyper=false]{#1}[]%
    }%
    {%
      \Glsxtrlong[noindex,hyper=false]{#1}[]%
    }%
  }%
}

```



```

    }%
  }%
}
\newrobustcmd*{\Glsxtrtitlelong}[1]{%
  \Glsxtrlong[noindex,hyper=false]{#1}[]%
}
\newrobustcmd*{\Glsxtrtitlelong}[1]{%
  \Glsxtrlong[noindex,hyper=false]{#1}[]%
}
\newcommand*{\Glsxtrheadlongpl}[1]{%
  \protect\NoCaseChange
  {%
    \glsifattribute{#1}{headuc}{true}%
    {%
      \Glsxtrlongpl[noindex,hyper=false]{#1}[]%
    }%
    {%
      \Glsxtrlongpl[noindex,hyper=false]{#1}[]%
    }%
  }%
}
}
\newrobustcmd*{\Glsxtrtitlelongpl}[1]{%
  \Glsxtrlongpl[noindex,hyper=false]{#1}[]%
}
\newrobustcmd*{\Glsxtrtitlelongpl}[1]{%
  \Glsxtrlongpl[noindex,hyper=false]{#1}[]%
}
\newcommand*{\glsxtrheadfull}[1]{%
  \protect\NoCaseChange
  {%
    \glsifattribute{#1}{headuc}{true}%
    {%
      \Glsxtrfull[noindex,hyper=false]{#1}[]%
    }%
    {%
      \glsxtrfull[noindex,hyper=false]{#1}[]%
    }%
  }%
}
}
\newrobustcmd*{\glsxtrtitlefull}[1]{%
  \glsxtrfull[noindex,hyper=false]{#1}[]%
}
\newcommand*{\glsxtrheadfullpl}[1]{%
  \protect\NoCaseChange
  {%
    \glsifattribute{#1}{headuc}{true}%
    {%
      \Glsxtrfullpl[noindex,hyper=false]{#1}[]%
    }%
    {%

```

```

        \glsxtrfullpl[noindex,hyper=false]{#1}[]%
    }%
}%
}
\newrobustcmd*{\glsxtrtitlefullpl}[1]{%
    \glsxtrfullpl[noindex,hyper=false]{#1}[]%
}
\newcommand*{\Glsxtrheadfull}[1]{%
    \protect\NoCaseChange
    {%
        \glsifattribute{#1}{headuc}{true}%
        {%
            \GLSxtrfull[noindex,hyper=false]{#1}[]%
        }%
        {%
            \Glsxtrfull[noindex,hyper=false]{#1}[]%
        }%
    }%
}%
}
\newrobustcmd*{\Glsxtrtitlefull}[1]{%
    \GLSxtrfull[noindex,hyper=false]{#1}[]%
}
\newrobustcmd*{\GLSxtrtitlefull}[1]{%
    \GLSxtrfull[noindex,hyper=false]{#1}[]%
}
\newcommand*{\Glsxtrheadfullpl}[1]{%
    \protect\NoCaseChange
    {%
        \glsifattribute{#1}{headuc}{true}%
        {%
            \GLSxtrfullpl[noindex,hyper=false]{#1}[]%
        }%
        {%
            \Glsxtrfullpl[noindex,hyper=false]{#1}[]%
        }%
    }%
}%
}
\newrobustcmd*{\Glsxtrtitlefullpl}[1]{%
    \Glsxtrfullpl[noindex,hyper=false]{#1}[]%
}
\newrobustcmd*{\GLSxtrtitlefullpl}[1]{%
    \GLSxtrfullpl[noindex,hyper=false]{#1}[]%
}
\ifdef\texorpdfstring
{
    \newcommand*{\glsfmtshort}[1]{%
        \texorpdfstring
        {\glsxtrtitleshort{#1}}%
        {\glsentryshort{#1}}%
    }
}

```

```

}
{
  \newcommand*{\glsfmtshort}[1]{%
    \glsxtrtitleshort{#1}}
}
\ifdef\texorpdfstring
{
  \newcommand*{\glsfmtshortpl}[1]{%
    \texorpdfstring
      {\glsxtrtitleshortpl{#1}}%
      {\glsentryshortpl{#1}}%
  }
}
{
  \newcommand*{\glsfmtshortpl}[1]{%
    \glsxtrtitleshortpl{#1}}
}
\ifdef\texorpdfstring
{
  \newcommand*{\Glsfmtshort}[1]{%
    \texorpdfstring
      {\Glsxtrtitleshort{#1}}%
      {\glsentryshort{#1}}%
  }
}
{
  \newcommand*{\Glsfmtshort}[1]{%
    \Glsxtrtitleshort{#1}}
}
\ifdef\texorpdfstring
{
  \newcommand*{\Glsfmtshortpl}[1]{%
    \texorpdfstring
      {\Glsxtrtitleshortpl{#1}}%
      {\glsentryshortpl{#1}}%
  }
}
{
  \newcommand*{\Glsfmtshortpl}[1]{%
    \Glsxtrtitleshortpl{#1}}
}
\ifdef\texorpdfstring
{
  \newcommand*{\glsfmtname}[1]{%
    \texorpdfstring
      {\glsxtrtitlename{#1}}%
      {\glsentryname{#1}}%
  }
}
{

```

```

\newcommand*{\glsfmtname}[1]{%
  \glsxtrtitlename{#1}}
}
\ifdef\texorpdfstring
{
  \newcommand*{\Glsfmtname}[1]{%
    \texorpdfstring
    {\Glsxtrtitlename{#1}}%
    {\glsentryname{#1}}%
  }
}
{
  \newcommand*{\Glsfmtname}[1]{%
    \Glsxtrtitlename{#1}}
}
\ifdef\texorpdfstring
{
  \newcommand*{\GLSfmtname}[1]{%
    \texorpdfstring
    {\GLSxtrtitlename{#1}}%
    {\glsentryname{#1}}%
  }
}
{
  \newcommand*{\GLSfmtname}[1]{%
    \GLSxtrtitlename{#1}}
}
\ifdef\texorpdfstring
{
  \newcommand*{\glsfmttext}[1]{%
    \texorpdfstring
    {\glsxtrtitletext{#1}}%
    {\glsentrytext{#1}}%
  }
}
{
  \newcommand*{\glsfmttext}[1]{%
    \glsxtrtitletext{#1}}
}
\ifdef\texorpdfstring
{
  \newcommand*{\Glsfmttext}[1]{%
    \texorpdfstring
    {\Glsxtrtitletext{#1}}%
    {\glsentrytext{#1}}%
  }
}
{
  \newcommand*{\Glsfmttext}[1]{%
    \Glsxtrtitletext{#1}}
}

```

```

}
\ifdef\texorpdfstring
{
  \newcommand*\GLSfmttext}[1]{%
    \texorpdfstring
    {\GLSxtrtitletext{#1}}%
    {\glentrytext{#1}}%
  }
}
{
  \newcommand*\GLSfmttext}[1]{%
    \GLSxtrtitletext{#1}}
}
\ifdef\texorpdfstring
{
  \newcommand*\glsfmtplural}[1]{%
    \texorpdfstring
    {\glsxtrtitleplural{#1}}%
    {\glentryplural{#1}}%
  }
}
{
  \newcommand*\glsfmtplural}[1]{%
    \glsxtrtitleplural{#1}}
}
\ifdef\texorpdfstring
{
  \newcommand*\Glsfmtplural}[1]{%
    \texorpdfstring
    {\Glsxtrtitleplural{#1}}%
    {\glentryplural{#1}}%
  }
}
{
  \newcommand*\Glsfmtplural}[1]{%
    \Glsxtrtitleplural{#1}}
}
\ifdef\texorpdfstring
{
  \newcommand*\GLSfmtplural}[1]{%
    \texorpdfstring
    {\GLSxtrtitleplural{#1}}%
    {\glentryplural{#1}}%
  }
}
{
  \newcommand*\GLSfmtplural}[1]{%
    \GLSxtrtitleplural{#1}}
}
\ifdef\texorpdfstring

```

```

{
  \newcommand*{\glsfmtfirst}[1]{%
    \texorpdfstring
    {\glxtrtitlefirst{#1}}%
    {\glsentryfirst{#1}}%
  }
}
{
  \newcommand*{\glsfmtfirst}[1]{%
    \glxtrtitlefirst{#1}}
}
\ifdef\texorpdfstring
{
  \newcommand*{\Glsfmtfirst}[1]{%
    \texorpdfstring
    {\Glsxtrtitlefirst{#1}}%
    {\glsentryfirst{#1}}%
  }
}
{
  \newcommand*{\Glsfmtfirst}[1]{%
    \Glsxtrtitlefirst{#1}}
}
\ifdef\texorpdfstring
{
  \newcommand*{\GLSfmtfirst}[1]{%
    \texorpdfstring
    {\GLSxtrtitlefirst{#1}}%
    {\glsentryfirst{#1}}%
  }
}
{
  \newcommand*{\GLSfmtfirst}[1]{%
    \GLSxtrtitlefirst{#1}}
}
\ifdef\texorpdfstring
{
  \newcommand*{\glsfmtfirstpl}[1]{%
    \texorpdfstring
    {\glxtrtitlefirstplural{#1}}%
    {\glsentryfirstplural{#1}}%
  }
}
{
  \newcommand*{\glsfmtfirstpl}[1]{%
    \glxtrtitlefirstplural{#1}}
}
\ifdef\texorpdfstring
{
  \newcommand*{\Glsfmtfirstpl}[1]{%

```

```

        \texorpdfstring
        {\Glsxtrtitlefirstplural{#1}}}%
        {\glsentryfirstplural{#1}}}%
    }
}
{
    \newcommand*{\Glsfmtfirstpl}[1]{%
        \Glsxtrtitlefirstplural{#1}}
}
\ifdef\texorpdfstring
{
    \newcommand*{\Glsfmtfirstpl}[1]{%
        \texorpdfstring
        {\Glsxtrtitlefirstplural{#1}}}%
        {\glsentryfirstplural{#1}}}%
    }
}
{
    \newcommand*{\Glsfmtfirstpl}[1]{%
        \Glsxtrtitlefirstplural{#1}}
}
\ifdef\texorpdfstring
{
    \newcommand*{\glsfmtlong}[1]{%
        \texorpdfstring
        {\glsxtrtitlelong{#1}}}%
        {\glsentrylong{#1}}}%
    }
}
{
    \newcommand*{\glsfmtlong}[1]{%
        \glsxtrtitlelong{#1}}
}
\ifdef\texorpdfstring
{
    \newcommand*{\glsfmtlong}[1]{%
        \texorpdfstring
        {\Glsxtrtitlelong{#1}}}%
        {\glsentrylong{#1}}}%
    }
}
{
    \newcommand*{\Glsfmtlong}[1]{%
        \Glsxtrtitlelong{#1}}
}
\ifdef\texorpdfstring
{
    \newcommand*{\Glsfmtlong}[1]{%
        \texorpdfstring
        {\Glsxtrtitlelong{#1}}}%

```

```

        {\glsentrylong{#1}}%
    }
}
{
    \newcommand*{\GLSfmtlong}[1]{%
        \GLSxtrtitlelong{#1}}
}
\ifdef\texorpdfstring
{
    \newcommand*{\glsfmtlongpl}[1]{%
        \texorpdfstring
        {\glsxtrtitlelongpl{#1}}%
        {\glsentrylongpl{#1}}%
    }
}
{
    \newcommand*{\glsfmtlongpl}[1]{%
        \glsxtrtitlelongpl{#1}}
}
\ifdef\texorpdfstring
{
    \newcommand*{\Glsfmtlongpl}[1]{%
        \texorpdfstring
        {\Glsxtrtitlelongpl{#1}}%
        {\glsentrylongpl{#1}}%
    }
}
{
    \newcommand*{\Glsfmtlongpl}[1]{%
        \Glsxtrtitlelongpl{#1}}
}
\ifdef\texorpdfstring
{
    \newcommand*{\GLSfmtlongpl}[1]{%
        \texorpdfstring
        {\GLSxtrtitlelongpl{#1}}%
        {\glsentrylongpl{#1}}%
    }
}
{
    \newcommand*{\GLSfmtlongpl}[1]{%
        \GLSxtrtitlelongpl{#1}}
}
\newcommand*{\glspdffmtfull}[1]{\glsentrylong{#1} (\glsentryshort{#1})}%
\newcommand*{\glspdffmtfullpl}[1]{\glsentrylongpl{#1} (\glsentryshortpl{#1})}%
\ifdef\texorpdfstring
{
    \newcommand*{\glsfmtfull}[1]{%
        \texorpdfstring
        {\glsxtrtitlefull{#1}}%
    }
}

```



```

        {\glspdffmtfull{#1}}%
    }
}
{
    \newcommand*{\glsfmtfull}[1]{%
        \glstrtitlefull{#1}}
}
\ifdef\texorpdfstring
{
    \newcommand*{\Glsfmtfull}[1]{%
        \texorpdfstring
        {\glstrtitlefull{#1}}%
        {\glspdffmtfull{#1}}}%
    }
}
{
    \newcommand*{\GLSfmtfull}[1]{%
        \GLStrtitlefull{#1}}
}
\ifdef\texorpdfstring
{
    \newcommand*{\GLSfmtfull}[1]{%
        \texorpdfstring
        {\GLSxtrtitlefull{#1}}%
        {\glspdffmtfull{#1}}}%
    }
}
{
    \newcommand*{\GLSfmtfull}[1]{%
        \GLSxtrtitlefull{#1}}
}
\ifdef\texorpdfstring
{
    \newcommand*{\glsfmtfullpl}[1]{%
        \texorpdfstring
        {\glstrtitlefullpl{#1}}%
        {\glspdffmtfullpl{#1}}}%
    }
}
{
    \newcommand*{\glsfmtfullpl}[1]{%
        \glstrtitlefullpl{#1}}
}
\ifdef\texorpdfstring
{
    \newcommand*{\Glsfmtfullpl}[1]{%
        \texorpdfstring
        {\Glsxtrtitlefullpl{#1}}%
        {\glspdffmtfullpl{#1}}}%
    }
}

```

```

}
{
  \newcommand*{\Glsfmtfullpl}[1]{%
    \Glsxtrtitlefullpl{#1}}
}
\ifdef\texorpdfstring
{
  \newcommand*{\GLSfmtfullpl}[1]{%
    \texorpdfstring
    {\Glsxtrtitlefullpl{#1}}%
    {\glspdffmtfullpl{#1}{}}%
  }
}
{
  \newcommand*{\GLSfmtfullpl}[1]{%
    \Glsxtrtitlefullpl{#1}}
}
\newcommand*{\multiglossaryentrysetup}[1]{\setkeys{glsxtrcombined}{#1}}
\newcommand*{@gls@combined@indexmain}{1}
\define@choicekey{glsxtrcombined}{indexmain}%
  [\@gls@combined@indexmain@val\@gls@combined@indexmain]
  {false,true,first}[true]{}
\newcommand*{@gls@combined@indexothers}{2}
\define@choicekey{glsxtrcombined}{indexothers}%
  [\@gls@combined@indexothers@val\@gls@combined@indexothers]
  {false,true,first}[true]{}
\newcommand*{@gls@combined@hyper}{3}
\define@choicekey{glsxtrcombined}{hyper}%
  [\@gls@combined@hyper@val\@gls@combined@hyper]
  {none,allmain,mainonly,individual,otheronly,notmainfirst,nototherfirst,notfirst}{}
\newcommand*{@gls@combined@encapmain}{glsnumberformat}
\define@key{glsxtrcombined}{encapmain}{%
  \renewcommand*{@gls@combined@encapmain}{#1}%
}
\newcommand*{@gls@combined@encapothers}{glsnumberformat}
\define@key{glsxtrcombined}{encapothers}{%
  \renewcommand*{@gls@combined@encapothers}{#1}%
}
\newcommand*{@gls@combined@textformat}{@firstofone}
\define@key{glsxtrcombined}{textformat}{%
  \renewcommand*{@gls@combined@textformat}{#1}%
}
\newcommand*{@gls@combined@category}{}
\define@key{glsxtrcombined}{category}{%
  \renewcommand*{@gls@combined@category}{#1}%
}
\define@key{glsxtrcombinedpreopts}{category}{%
  \renewcommand*{@gls@combined@category}{#1}%
}
\newcommand*{@gls@combined@mglsopts}{}

```

```

\define@key{glsxtrcombined}{mglsopts}{%
  \renewcommand*{\@gls@combined@mglsopts}{#1}%
}
\define@key{glsxtrcombinedpreopts}{mglsopts}{%
  \@gls@combined@mglsopts@do
  {%
    \renewcommand*{\@gls@combined@mglsopts}{#1}%
  }%
}
\newcommand*{\@gls@combined@mglsopts@do}[1]{#1}
\newcommand*{\mglso@disable@mglsopts}{%
  \let\@gls@combined@mglsopts@do\@gls@combined@mglsopts@do@not
}
\newcommand*{\mglso@enable@mglsopts}{%
  \let\@gls@combined@mglsopts@do\@firstofone
}
\newcommand*{\@gls@combined@mglsopts@do@not}[1]{%
  \PackageError{glossaries-extra}{‘mglsopts’ key not permitted inside
    ‘setup’ value}{}%
}
\newcommand*{\@gls@combined@firstprefix}{%
\define@key{glsxtrcombined}{firstprefix}{%
  \renewcommand*{\@gls@combined@firstprefix}{#1}%
}
\newcommand*{\@gls@combined@usedprefix}{%
\define@key{glsxtrcombined}{usedprefix}{%
  \renewcommand*{\@gls@combined@usedprefix}{#1}%
}
\newcommand*{\@gls@combined@firstsuffix}{%
\define@key{glsxtrcombined}{firstsuffix}{%
  \renewcommand*{\@gls@combined@firstsuffix}{#1}%
}
\newcommand*{\@gls@combined@usedsuffix}{%
\define@key{glsxtrcombined}{usedsuffix}{%
  \renewcommand*{\@gls@combined@usedsuffix}{#1}%
}
\define@boolkey{glsxtrcombined}{firstskipmain}[true]{%
\KV@glsxtrcombined@firstskipmainfalse
\define@boolkey{glsxtrcombined}{firstskipothers}[true]{%
\KV@glsxtrcombined@firstskipothersfalse
\define@boolkey{glsxtrcombined}{usedskipmain}[true]{%
\KV@glsxtrcombined@usedskipmainfalse
\define@boolkey{glsxtrcombined}{usedskipothers}[true]{%
\KV@glsxtrcombined@usedskipothersfalse
\newcommand*{\@gls@combined@postlinks@nr}{0}
\define@choicekey{glsxtrcombined}{postlinks}{%
  [\@gls@combined@postlinks@val\@gls@combined@postlinks@nr]
  {none,all,notlast,mainnotlast,mainonly,othernotlast,otheronly}{%
\newcommand*{\@gls@combined@mpostlink@nr}{1}
\define@choicekey{glsxtrcombined}{mpostlink}{%

```

```

[\@gls@combined@mpostlink@val\@gls@combined@mpostlink@nr]
{false,true,firstonly,usedonly}[true]{}
\newcommand*{\@gls@combined@mpostlinkelement@nr}{0}
\define@choicekey{glsxtrcombined}{mpostlinkelement}%
[\@gls@combined@mpostlinkelement@val\@gls@combined@mpostlinkelement@nr]
{last,main,custom}{}
\newcommand*{\glsxtrifmulti}[3]{\ifcsdef{@gls@combined@#1@main}{#2}{#3}}
\newcommand*{\glsxtrmultimain}[1]{\csuse{@gls@combined@#1@main}}
\newcommand*{\glsxtrmultilist}[1]{\csuse{@gls@combined@#1@list}}
\newcommand*{\glsxtrmultitotalelements}[1]{\csuse{@gls@combined@#1@total}}
\newcommand*{\glsxtrmultimainindex}[1]{\csuse{@gls@combined@#1@mainindex}}
\newcommand*{\glsxtrmultilastotherindex}[1]{\csuse{@gls@combined@#1@lastotherindex}}
\newif\ifmultiglossaryentryglobal
\multiglossaryentryglobalfalse
\newcount\mglselementindex
\newrobustcmd{\multiglossaryentry}[1][ ]{%
\def\@gls@combined@current@opts{#1}%
\ifnum\@glsxtr@docdefval=1\relax
\let\@multi@glossentry@donext\@defmultiglossaryentry
\else
\let\@multi@glossentry@donext\@multiglossaryentry
\fi
\@multi@glossentry@donext
}
\newcommand*{\@multiglossaryentry}[1]{%
\def\@gls@combined@current@label{#1}%
\@multi@glossaryentry
}
\newcommand*{\@multi@glossaryentry}[2][ ]{%
\ifcsdef{@gls@combined@\@gls@combined@current@label @main}%
{\PackageError{glossaries-extra}%
{Multi-entry label ‘\@gls@combined@current@label’ already defined}%
{}}%
}%
{%
\@multi@glossary@entry{#1}{#2}%
}%
}
\newcommand*{\@defmultiglossaryentry}[1]{%
\def\@gls@combined@current@label{#1}%
\@def@multi@glossaryentry
}
\newcommand*{\@def@multi@glossaryentry}[2][ ]{%
\let\@def@multi@glossaryentry@do\@multi@glossary@entry
\ifundef\@glsxtr@docdefs@multilist
{%
\gdef\@glsxtr@docdefs@multilist{%
\listxadd
{\@glsxtr@docdefs@multilist}{\expandonce\@gls@combined@current@label}%
}%
}

```

```

{%
  \xifinlist{\@gls@combined@current@label}{\@glsxtr@docdefs@multilist}%
  {%
    \PackageError{glossaries-extra}%
    {Multi-entry label ‘\@gls@combined@current@label’ already defined}%
    {}%
    \let\@def@multi@glossaryentry@do\@gobbletwo
  }%
  {%
    \listxadd
    {\@glsxtr@docdefs@multilist}{\expandonce\@gls@combined@current@label}%
  }%
}%
\@def@multi@glossaryentry@do{#1}{#2}%
}
\newcommand*{\@multi@glossary@doifexists}{\glsdoifexists}
\newrobustcmd{\providemultiglossaryentry}[2][{}]{%
  \def\@gls@combined@current@opts{#1}%
  \def\@gls@combined@current@label{#2}%
  \ifcsdef{\@gls@combined@ \@gls@combined@current@label @main}%
  {\def\@multi@glossentry@donext{\@provide@multi@glossaryentry@noop}}%
  {%
    \ifnum\@glsxtr@docdefval=1\relax
    \def\@multi@glossentry@donext{\@def@multi@glossaryentry}%
    \else
    \def\@multi@glossentry@donext{\@multi@glossaryentry}%
    \fi
  }%
  \@multi@glossentry@donext
}
\newcommand*{\@provide@multi@glossaryentry@noop}[2][{}]{%
\newcommand*{\@multi@glossaryentry@list}{%
\newcommand*{\@multi@glossary@entry}[2]{%
  \protected@edef\@gls@combined@current@main{#1}%
  \protected@edef\@gls@combined@currentlist{#2}%
  \mglselementindex=0\relax
  \@for\@gls@tmp:=\@gls@combined@currentlist\do{%
    \advance\mglselementindex by 1\relax
    \@multi@glossary@doifexists{\@gls@tmp}{}%
    \let\@gls@combined@finalitem\@gls@tmp
    \ifdefvoid\@gls@combined@current@main
    {}%
    {%
      \ifx\@gls@combined@current@main\@gls@tmp
      \ifmultiglossaryentryglobal
      \global\cslet{\@gls@combined@ \@gls@combined@current@label @main}%
      \@gls@combined@current@main
      \csxdef{\@gls@combined@ \@gls@combined@current@label @mainindex}%
      {\the\mglselementindex}%
      \else

```

```

\cslet{@gls@combined@\@gls@combined@current@label @main}%
\@gls@combined@current@main
\csedef{@gls@combined@\@gls@combined@current@label @mainindex}%
{\the\mglselementindex}%
\fi
\else
\ifmultiglossaryentryglobal
\csxdef{@gls@combined@\@gls@combined@current@label @lastotherindex}%
{\the\mglselementindex}%
\else
\csedef{@gls@combined@\@gls@combined@current@label @lastotherindex}%
{\the\mglselementindex}%
\fi
\fi
}%
}%
\ifmultiglossaryentryglobal
\csxdef{@gls@combined@\@gls@combined@current@label @total}%
{\the\mglselementindex}%
\else
\csedef{@gls@combined@\@gls@combined@current@label @total}%
{\the\mglselementindex}%
\fi
\ifnum\mglselementindex<2\relax
\PackageError{glossaries-extra}{At least 2 labels required in
multi-entry element list (\number\mglselementindex\space found)}{}%
\else
\ifdefvoid\@gls@combined@current@main
{}%
{%
\ifcsundef{@gls@combined@\@gls@combined@current@label @main}%
{\PackageError{glossaries-extra}%
{Main element ‘\@gls@combined@current@main’ not found in list}%
{The final element ‘\@gls@combined@finalitem’ will be used instead}%
\let\@gls@combined@current@main\@empty
}%
{}%
}%
\ifdefvoid\@gls@combined@current@main
{%
\ifmultiglossaryentryglobal
\global\cslet{@gls@combined@\@gls@combined@current@label @main}%
\@gls@combined@finalitem
\global\csletcs{@gls@combined@\@gls@combined@current@label @mainindex}%
{@gls@combined@\@gls@combined@current@label @total}%
\csxdef{@gls@combined@\@gls@combined@current@label @lastotherindex}%
{\the\numexpr\mglselementindex-1}%
\else
\cslet{@gls@combined@\@gls@combined@current@label @main}%
\@gls@combined@finalitem

```

```

\csletcs{@gls@combined@\@gls@combined@current@label @mainindex}%
  {@gls@combined@\@gls@combined@current@label @total}%
\csedef{@gls@combined@\@gls@combined@current@label @lastotherindex}%
  {\the\numexpr\mgls@elementindex-1 }%
\fi
}%
{}%
\ifmultiglossaryentryglobal
\global\cslet{@gls@combined@\@gls@combined@current@label @list}%
  {@gls@combined@currentlist}
\protected\csxdef{@gls@combined@\@gls@combined@current@label @options}%
  {@gls@combined@current@opts}%
\expandafter\ifdefinable
\csname if@gls@combined@\@gls@combined@current@label @flag\endcsname
{\expandafter\global\expandafter
\newif\csname if@gls@combined@\@gls@combined@current@label @flag\endcsname}%
\expandafter\global
\csname @gls@combined@\@gls@combined@current@label @flagfalse\endcsname
\else
\cslet{@gls@combined@\@gls@combined@current@label @list}%
  {@gls@combined@currentlist}
\protected\csedef{@gls@combined@\@gls@combined@current@label @options}%
  {@gls@combined@current@opts}%
\newboolean{@gls@combined@\@gls@combined@current@label @flag}%
\csname @gls@combined@\@gls@combined@current@label @flagfalse\endcsname
\fi
\fi
\writemultiglossentry
{@gls@combined@current@opts}{@gls@combined@current@label}%
{\csuse{@gls@combined@\@gls@combined@current@label @main}}{#2}%
\ifmultiglossaryentryglobal
\ifdefempty\@multi@glossaryentry@list
{\let\@multi@glossaryentry@list\@gls@combined@current@label}%
{%
\exppto\@multi@glossaryentry@list{\, \expandonce \@gls@combined@current@label}%
}%
\else
\ifdefempty\@multi@glossaryentry@list
{\global\let\@multi@glossaryentry@list\@gls@combined@current@label}%
{%
\xappto\@multi@glossaryentry@list{\, \expandonce \@gls@combined@current@label}%
}%
\fi
\fi
}
\newcommand*{\@glsxtr@multientry}[4]{%
\ifnum\@glsxtr@docdefval=1\relax
\bgroup
\def\@gls@combined@current@opts{#1}%
\def\@gls@combined@current@label{#2}%
\let\@multi@glossary@doifexists\@secondoftwo

```

```

\let\writemultiglossentry\@gobblefour
\multiglossaryentryglobaltrue
\@multi@glossary@entry{#3}{#4}%
\egroup
\fi
}
\newcommand*{\writemultiglossentry}[4]{%
  \protected@write\@auxout{}\string\@glstr@multientry{#1}{#2}{#3}{#4}}%
}
\newcommand*{\ifmglsused}[3]{%
  \ifbool{@gls@combined@#1@flag}{#2}{#3}%
}
\newcommand*{\mglsunset}[1]{%
  \gls@ifnotmeasuring
  {%
    \glstrifmulti{#1}{\@mglsunset{#1}}%
    {%
      \glstrundefaction{Multi entry ‘#1’ hasn’t been defined}%
      {You need to define ‘#1’ with \string\multiglossaryentry}%
    }%
  }%
}
\newcommand*{\@mglsunset}[1]{%
  \expandafter\global\csname @gls@combined@#1@flagtrue\endcsname
}
\newcommand*{\mglsreset}[1]{%
  \gls@ifnotmeasuring
  {%
    \glstrifmulti{#1}{\@mglsreset{#1}}%
    {%
      \glstrundefaction{Multi entry ‘#1’ hasn’t been defined}%
      {You need to define ‘#1’ with \string\multiglossaryentry}%
    }%
  }%
}
\newcommand*{\@mglsreset}[1]{%
  \expandafter\global\csname @gls@combined@#1@flagfalse\endcsname
}
\newcommand*{\mglslocalunset}[1]{%
  \gls@ifnotmeasuring
  {%
    \glstrifmulti{#1}{\@mglslocalunset{#1}}%
    {%
      \glstrundefaction{Multi entry ‘#1’ hasn’t been defined}%
      {You need to define ‘#1’ with \string\multiglossaryentry}%
    }%
  }%
}
\newcommand*{\@mglslocalunset}[1]{%
  \csname @gls@combined@#1@flagtrue\endcsname

```



```

}
\newcommand*{\mglsllocalreset}[1]{%
\gls@ifnotmeasuring
{%
\glstrifmulti{#1}{\@mglsllocalreset{#1}}%
{%
\glstrundefaction{Multi entry ‘#1’ hasn’t been defined}%
{You need to define ‘#1’ with \string\multiglossaryentry}%
}%
}%
}
\newcommand*{\@mglsllocalreset}[1]{%
\csname @gls@combined@#1@flagfalse\endcsname
}
\newcommand*{\mglunsetall}{%
\@for\@mgl@thislabel:=\@multi@glossaryentry@list\do{\mglunset\@mgl@thislabel}%
}%
\newcommand*{\mglresetall}{%
\@for\@mgl@thislabel:=\@multi@glossaryentry@list\do{\mglreset\@mgl@thislabel}%
}%
\newrobustcmd{\mglsetmain}[2]{%
\ifcsundef{@gls@combined@#1@main}%
{\PackageError{glossaries-extra}{Multi-entry label ‘#1’ not defined}{}}%
{%
\protected@edef\@gls@combined@current@main{#2}%
\letcs@gls@combined@currentlist{@gls@combined@#1@list}%
\mglselementindex=0\relax
\count@=0\relax
\@for\@gls@tmp:=\@gls@combined@currentlist\do{%
\advance\mglselementindex by 1\relax
\ifx\@gls@combined@current@main\@gls@tmp
\count@=\mglselementindex\relax
\let\@gls@combined@finalitem\@gls@tmp
\ifmultiglossaryentryglobal
\global\cslet{@gls@combined@#1@main}\@gls@combined@current@main
\csxdef{@gls@combined@#1@mainindex}{\the\mglselementindex}%
\else
\cslet{@gls@combined@#1@main}\@gls@combined@current@main
\csedef{@gls@combined@#1@mainindex}{\the\mglselementindex}%
\fi
\else
\ifmultiglossaryentryglobal
\csxdef{@gls@combined@#1@lastotherindex}{\the\mglselementindex}%
\else
\csedef{@gls@combined@#1@lastotherindex}{\the\mglselementindex}%
\fi
\fi
}%
\ifnum\count@=0\relax
\PackageError{glossaries-extra}{Label ‘#2’ is not in ‘#1’ set

```

```

(\@gls@combined@currentlist)}{%
\ifmultiglossaryentryglobal
  \global\cslet{@gls@combined@#1@main}\@gls@combined@finalitem
  \csxdef{@gls@combined@#1@mainindex}{\the\mglselementindex}%
  \csxdef{@gls@combined@#1@lastotherindex}{%
    \number\numexpr\mglselementindex-1 }%
  \else
    \cslet{@gls@combined@#1@main}\@gls@combined@finalitem
    \csedef{@gls@combined@#1@mainindex}{\the\mglselementindex}%
    \csedef{@gls@combined@#1@lastotherindex}{%
      \number\numexpr\mglselementindex-1 }%
    \fi
  \fi
}%
}
\newrobustcmd{\mglSetOptions}[2]{%
  \ifcsundef{@gls@combined@#1@main}%
  {\PackageError{glossaries-extra}{Multi-entry label ‘#1’ not defined}{}}%
  {%
    \csdef{@gls@combined@#1@options}{#2}%
  }%
}
\newrobustcmd{\mglAddOptions}[2]{%
  \ifcsundef{@gls@combined@#1@main}%
  {\PackageError{glossaries-extra}{Multi-entry label ‘#1’ not defined}{}}%
  {%
    \ifcseempty{@gls@combined@#1@options}%
    {\csdef{@gls@combined@#1@options}{#2}}%
    {\csappto{@gls@combined@#1@options}{, #2}}%
  }%
}
\newcommand*{\@mgl@all}{}
\define@key{mgl}{all}{\renewcommand*{\@mgl@all}{#1}}
\newcommand*{\@mgl@main}{}
\define@key{mgl}{main}{\renewcommand*{\@mgl@main}{#1}}
\newcommand*{\@mgl@others}{}
\define@key{mgl}{others}{\renewcommand*{\@mgl@others}{#1}}
\newcommand*{\@mgl@setup}{}
\define@key{mgl}{setup}{%
  \@mgl@setup@do{\renewcommand*{\@mgl@setup}{#1}}%
}
\newcommand*{\@mgl@setup@do}[1]{#1}
\newcommand*{\@mgl@setup@do@not}[1]{%
  \PackageError{glossaries-extra}{‘setup’ key not permitted inside
    ‘mglsopts’ value}{}}%
}
\newcommand*{\mgl@disable@setup}{%
  \let\@mgl@setup@do\@mgl@setup@do@not
}
\newcommand*{\mgl@enable@setup}{%

```

```

\let\@mgls@setup@do\@firstofone
}
\newcommand\@mgls@unsetaction{0}
\define@choicekey{mgls}{multiunset}[\@mgls@unsetaction@val\@mgls@unsetaction]%
{global,local,none}{}
\define@boolkey{mgls}{presetlocal}[true]{}
\KV@mgls@presetlocalfalse
\newcommand*\@mgls@hyper{}{}
\define@choicekey{mgls}{hyper}[\@mgls@hyper@val\@mgls@hyper@nr]{true,false}[true]%
{%
\renewcommand*\@mgls@hyper{hyper=#1}%
\ifnum\@mgls@hyper@nr=1\relax
\let\@mgls@hyperlink\@secondoftwo
\else
\let\@mgls@hyperlink\@@mgls@hyperlink
\fi
}
\newcommand*\@@mgls@hyperlink[2]{%
\ifx\@glslink\glsdonohyperlink
#2%
\else
\glsxtr@org@dohyperlink{\glslinkprefix#1}{#2}%
\fi
}
\let\@mgls@hyperlink\@@mgls@hyperlink
\newcommand*\mglsforelements[3]{%
\expandafter\@for\expandafter#2\expandafter:\expandafter
=\csname @gls@combined@#1@list\endcsname\do{#3}%
}
\newcommand*\mglsforotherelements[3]{%
\expandafter\@for\expandafter#2\expandafter:\expandafter
=\csname @gls@combined@#1@list\endcsname\do
{\expandafter\ifdefequal\csname @gls@combined@#1@main\endcsname{#2}{-}{#3}}%
}
\newcommand*\mglsunsettothers[1]{%
\mglsforotherelements{#1}{\@gls@tmp}{\glsunset{\@gls@tmp}}%
}
\newcommand*\mglslocalunsettothers[1]{%
\mglsforotherelements{#1}{\@gls@tmp}{\glslocalunset{\@gls@tmp}}%
}
\newcommand*\mglselementreset[1]{%
\ifKV@mgls@presetlocal
\glslocalreset{#1}%
\else
\glsreset{#1}%
\fi
}
\newcommand*\mglselementunset[1]{%
\ifKV@mgls@presetlocal
\glslocalunset{#1}%

```

```

\else
\glsunset{#1}%
\fi
}
\newcommand*{\@mgls@resetall}{%
\define@choicekey{mgls}{resetall}%
[\@mgls@resetall@val\@mgls@resetall@nr]{false,true}[true]%
{%
\ifcase\@mgls@resetall@nr\relax
\renewcommand*{\@mgls@resetall}{}%
\or
\renewcommand*{\@mgls@resetall}{%
\@for\@gls@resetlabel:=\mglscurrentlist\do{\mglselementreset\@gls@resetlabel}}%
\renewcommand*{\@mgls@unsetall}{}%
\fi
}
\newcommand*{\@mgls@resetmain}{%
\define@choicekey{mgls}{resetmain}
[\@mgls@resetmain@val\@mgls@resetmain@nr]{false,true}[true]%
{%
\ifcase\@mgls@resetmain@nr\relax
\renewcommand*{\@mgls@resetmain}{}%
\or
\renewcommand*{\@mgls@resetmain}{\mglselementreset\mglscurrentmainlabel}%
\renewcommand*{\@mgls@unsetmain}{}%
\fi
}
\newcommand*{\@mgls@resetothers}{%
\define@choicekey{mgls}{resetothers}
[\@mgls@resetothers@val\@mgls@resetothers@nr]{false,true}[true]%
{%
\ifcase\@mgls@resetothers@nr\relax
\renewcommand*{\@mgls@resetothers}{}%
\or
\renewcommand*{\@mgls@resetothers}{%
\@for\@gls@resetlabel:=\mglscurrentlist\do{%
\ifx\@gls@resetlabel\mglscurrentmainlabel
\else
\mglselementreset\@gls@resetlabel
\fi
}%
}%
\renewcommand*{\@mgls@unsetothers}{}%
\fi
}
\newcommand*{\@mgls@unsetall}{%
\define@choicekey{mgls}{unsetall}%
[\@mgls@unsetall@val\@mgls@unsetall@nr]{false,true}[true]%
{%
\ifcase\@mgls@unsetall@nr\relax

```

```

\renewcommand*{\@mgls@unsetall}{}%
\or
\renewcommand*{\@mgls@unsetall}{%
\@for\@gls@unsetlabel:=\mglscurrentlist\do{\mglselementunset\@gls@unsetlabel}}%
\renewcommand*{\@mgls@resetall}{}%
\fi
}
\newcommand*{\@mgls@unsetmain}{%
\define@choicekey{mgls}{unsetmain}
[\@mgls@unsetmain@val\@mgls@unsetmain@nr]{false,true}[true]%
}%
\ifcase\@mgls@unsetmain@nr\relax
\renewcommand*{\@mgls@unsetmain}{}%
\or
\renewcommand*{\@mgls@unsetmain}{\mglselementunset\mglscurrentmainlabel}%
\renewcommand*{\@mgls@resetmain}{}%
\fi
}
\newcommand*{\@mgls@unsetothers}{%
\define@choicekey{mgls}{unsetothers}
[\@mgls@unsetothers@val\@mgls@unsetothers@nr]{false,true}[true]%
}%
\ifcase\@mgls@unsetothers@nr\relax
\renewcommand*{\@mgls@unsetothers}{}%
\or
\renewcommand*{\@mgls@unsetothers}{%
\@for\@gls@unsetlabel:=\mglscurrentlist\do{%
\ifx\@gls@unsetlabel\mglscurrentmainlabel
\else
\mglselementunset\@gls@unsetlabel
\fi
}%
}%
\renewcommand*{\@mgls@resetothers}{}%
\fi
}
\newcommand{\glxtr@setup@docurrent}{%
\ifx\mglscurrentlabel\mglscurrentmainlabel
\mglsisfirstuse
{%
\ifKV@glxtrcombined@firstskipmain
\let\@mgls@do@current@element\@gobble
\else
\let\@mgls@do@current@element\@firstofone
\fi
}%
{%
\ifKV@glxtrcombined@usedskipmain
\let\@mgls@do@current@element\@gobble
\else

```

```

        \let\@mgls@do@current@element\@firstofone
    \fi
}%
\else
\mglsisfirstuse
{%
    \ifKV@glxtrcombined@firstskipothers
        \let\@mgls@do@current@element\@gobble
    \else
        \let\@mgls@do@current@element\@firstofone
    \fi
}%
{%
    \ifKV@glxtrcombined@usedskipothers
        \let\@mgls@do@current@element\@gobble
    \else
        \let\@mgls@do@current@element\@firstofone
    \fi
}%
\fi
}
\newcommand*{\glxtr@mgls@checklastelement}[2]{%
    \ifbool{KV@glxtrcombined@#1skipmain}%
    {%
        \ifbool{KV@glxtrcombined@#1skipothers}%
        {%
            }%
        {%
            \ifnum\mglselementindex=\glxtrmultilastotherindex{#2}\relax
                \let\mglsiflast\@firstoftwo
            \else
                \let\mglsiflast\@secondoftwo
            \fi
        }%
    }%
    {%
        \ifbool{KV@glxtrcombined@#1skipothers}%
        {%
            \ifnum\mglselementindex=\glxtrmultimainindex{#2}\relax
                \let\mglsiflast\@firstoftwo
            \else
                \let\mglsiflast\@secondoftwo
            \fi
        }%
    }%
    \let\mglsiflast\@secondoftwo
}%
}
\newcommand{\glxtrmglsWarnAllSkipped}[3]{%

```

```

\GlossariesExtraWarning{#1}%
#3{#2}%
}
\newcommand*{\glstr@mgl@applyopts}[1]{%
\edef\@mgl@doptions{\noexpand\setkeys*{mgl}{\expandonce#1}}%
\@mgl@doptions
\ifvoid\XKV@rm{\eappto\@mgl@all{\expandonce\XKV@rm}}%
\ifvoid\@mgl@setup
{}%
{%
\edef\@mgl@doptions{%
\noexpand\setkeys*{glstrcombinedpreopts}{\expandonce\@mgl@setup}}%
\mgl@disable@mglsopts
\@mgl@doptions
\mgl@enable@mglsopts
\ifx\@mgl@setuptoptions\@empty
\let\@mgl@setuptoptions\XKV@rm
\else
\let\@mgl@setuptoptions{\expandonce\XKV@rm}%
\fi
}%
\@mgl@resetall
\@mgl@unsetall
\@mgl@resetmain
\@mgl@unsetmain
\@mgl@resetothers
\@mgl@unsetothers
\let\@mgl@resetall\@empty
\let\@mgl@resetmain\@empty
\let\@mgl@resetothers\@empty
\let\@mgl@unsetall\@empty
\let\@mgl@unsetmain\@empty
\let\@mgl@unsetothers\@empty
\ifmglused\mglscurrentmultilabel
{\let\mglsisfirstuse\@secondoftwo}%
{\let\mglsisfirstuse\@firstoftwo}%
}
\providecommand{\@firstofthree}[3]{#1}
\providecommand{\@secondofthree}[3]{#2}
\providecommand{\@thirdofthree}[3]{#3}
\newcommand*{\glstr@mgl@inner}[7]{%
\let\mglslastmainlabel\@empty
\let\mgl@iflastmainwasfirstuse\@firstoftwo
\let\mgl@iflastmainwasplural\@secondoftwo
\let\mgl@iflastmaincapscase\@firstofthree
\let\mgl@iflastmainskipped\@firstoftwo
\bgroup
\ifcsundef{@gls@combined@#2@main}%
{%
\glstrundefaction{Multi entry ‘#2’ hasn’t been defined}%

```

```

{You need to define ‘#2’ with \string\multiglossaryentry}%
\gdef\@mgls@post@hookdefs{%
  \protected@edef\mglslastmultilabel{#2}%
  \let\mglswasfirstuse\@firstoftwo
  \let\mglslastcategory\@empty
  \let\mglsiflastelements\skipped\@firstoftwo
  \let\mglsiflastelementwasfirstuse\@firstoftwo
  \let\mglsiflastelementwasplural\@secondoftwo
  \let\mglsiflastelementcapscase\@firstofthree
  \let\mglslastelementlabel\@empty
  \let\mgls@do@postlinkhook\relax
}%
}%
{%
  \protected@edef\mglscurrentmultilabel{#2}%
  \letcs\mglscurrentmainlabel{\@gls@combined@#2@main}%
  \letcs\mglscurrentlist{\@gls@combined@#2@list}%
  \letcs\mglscurrentoptions{\@gls@combined@#2@options}%
  \ifmglsused\mglscurrentmultilabel
  {\let\mglsisfirstuse\@secondoftwo}%
  {\let\mglsisfirstuse\@firstoftwo}%
  \edef\@mgls@dooptions{%
    \noexpand\setkeys*{glxtrcombinedpreopts}{\expandonce\mglscurrentoptions}}%
  \@mgls@dooptions
  \let\@mgls@setuptoptions\XKV@rm
  \mgls@disable@setup
  \ifdefvoid\@gls@combined@mgls@opts
  {}%
  {\glxtr@mgls@applyopts\@gls@combined@mgls@opts}%
  \mgls@enable@setup
  \ifstrempy{#1}{\def\@mgls@options{#1}\glxtr@mgls@applyopts\@mgls@options}%
  \ifx\@gls@combined@category\empty
  \else
    \glshascategoryattribute{\@gls@combined@category}{multioptions}%
    {%
      \letcs\@mgls@attroptions{\glxtr@categoryattr@\@gls@combined@category
        @multioptions}%
      \let\@gls@combined@mgls@opts\@empty
      \edef\@mgls@dooptions{%
        \noexpand\setkeys*{glxtrcombinedpreopts}{\expandonce\@mgls@attroptions}}%
      \@mgls@dooptions
      \eappto\@mgls@setuptoptions{,\expandonce\XKV@rm}%
      \ifx\@gls@combined@mgls@opts\@empty
      \else
        \let\@mgls@setup\@empty
        \mgls@disable@setup
        \glxtr@mgls@applyopts\@gls@combined@mgls@opts
        \mgls@enable@setup
      \fi
    }%
  }%

```



```

    {}%
\fi
\edef\@mgls@doptions{%
    \noexpand\setkeys{glsxtrcombined}{\expandonce\@mgls@setuptools}}%
\@mgls@doptions
\let\mgls@currentcategory\@gls@combined@category
\ifnum\@gls@combined@hyper=1\relax
    \def\@mgls@combinedlink{\@mgls@hyperlink{\mgls@currentmainlabel}}%
\else
    \def\@mgls@combinedlink{\@firstofone}%
\fi
\def\@gls@combined@encapsulator##1{%
    \@mgls@combinedlink{\csuse{\@gls@combined@textformat}{##1}}}%
\let\@mgls@do@current@element\@firstofone
\mglsisfirstuse
{%
    \ifKV@glxtrcombined@firstskipmain
        \ifKV@glxtrcombined@firstskipothers
            \let\@gls@org@combined@encapsulator\@gls@combined@encapsulator
            \def\@gls@combined@encapsulator##1{%
                \glxtrmglsWarnAllSkipped{All elements skipped for
                    first use of multi-entry '#2'}{#3}%
                {\@gls@org@combined@encapsulator}%
            }%
            \let\@mgls@do@current@element\@gobble
        \fi
    \fi
}%
{%
    \ifKV@glxtrcombined@usedskipmain
        \ifKV@glxtrcombined@usedskipothers
            \let\@gls@org@combined@encapsulator\@gls@combined@encapsulator
            \def\@gls@combined@encapsulator##1{%
                \glxtrmglsWarnAllSkipped{All elements skipped for
                    subsequent use of multi-entry '#2'}{#3}%
                {\@gls@org@combined@encapsulator}%
            }%
            \let\@mgls@do@current@element\@gobble
        \fi
    \fi
}%
\mglsisfirstuse
{%
    \let\mgls@currentprefix\@gls@combined@firstprefix
    \let\mgls@currentsuffix\@gls@combined@firstsuffix
}%
{%
    \let\mgls@currentprefix\@gls@combined@usedprefix
    \let\mgls@currentsuffix\@gls@combined@usedsuffix
}%

```

```

\edef\@mgls@post@hookdefs{%
  \noexpand\def\noexpand\mglslastmultilabel{\expandonce\mglscurrentmultilabel}%
  \noexpand\def\noexpand\mglslastcategory{\mglscurrentcategory}%
}%
\ifx\@mgls@do@current@element\@gobble
  \gappto\@mgls@post@hookdefs{%
    \let\mglsiflastelements\skipped\@firstoftwo
    \let\mglslastelementlabel\@empty
    \let\mglsiflastelementwasfirstuse\@firstoftwo
    \let\mglsiflastelementwasplural\@secondoftwo
    \let\mglsiflastelementcaps\case\@firstofthree
  }%
\fi
\mglsisfirstuse
{%
  \gappto\@mgls@post@hookdefs{\let\mglswasfirstuse\@firstoftwo}%
  \ifcase\@gls@combined@mpostlink@nr\relax
    \gappto\@mgls@post@hookdefs{\let\mgls@do@postlinkhook\relax}%
  \or
    \ifcase\@gls@combined@mpostlinkelement@nr\relax
      \gappto\@mgls@post@hookdefs{\let\mgls@do@postlinkhook\mglslastelementpostlinkhook}%
    \or
      \gappto\@mgls@post@hookdefs{\let\mgls@do@postlinkhook\mglslastmainpostlinkhook}%
    \or
      \gappto\@mgls@post@hookdefs{\let\mgls@do@postlinkhook\mglscustompostlinkhook}%
    \fi
  \or
    \ifcase\@gls@combined@mpostlinkelement@nr\relax
      \gappto\@mgls@post@hookdefs{\let\mgls@do@postlinkhook\mglslastelementpostlinkhook}%
    \or
      \gappto\@mgls@post@hookdefs{\let\mgls@do@postlinkhook\mglslastmainpostlinkhook}%
    \or
      \gappto\@mgls@post@hookdefs{\let\mgls@do@postlinkhook\mglscustompostlinkhook}%
    \fi
  \or
    \gappto\@mgls@post@hookdefs{\let\mgls@do@postlinkhook\relax}%
  \fi
}%
{%
  \gappto\@mgls@post@hookdefs{\let\mglswasfirstuse\@secondoftwo}%
  \ifcase\@gls@combined@mpostlink@nr\relax
    \gappto\@mgls@post@hookdefs{\let\mgls@do@postlinkhook\relax}%
  \or
    \ifcase\@gls@combined@mpostlinkelement@nr\relax
      \gappto\@mgls@post@hookdefs{\let\mgls@do@postlinkhook\mglslastelementpostlinkhook}%
    \or
      \gappto\@mgls@post@hookdefs{\let\mgls@do@postlinkhook\mglslastmainpostlinkhook}%
    \or
      \gappto\@mgls@post@hookdefs{\let\mgls@do@postlinkhook\mglscustompostlinkhook}%
    \fi
  \fi
}

```

```

\or
\gappto\@mgls@post@hookdefs{\let\mgls@do@postlinkhook\relax}%
\or
\ifcase\@gls@combined@mpostlinkelement@nr\relax
\gappto\@mgls@post@hookdefs{\let\mgls@do@postlinkhook\mglslastelementpostlinkhook}%
\or
\gappto\@mgls@post@hookdefs{\let\mgls@do@postlinkhook\mglslastmainpostlinkhook}%
\or
\gappto\@mgls@post@hookdefs{\let\mgls@do@postlinkhook\mglscustompostlinkhook}%
\fi
\fi
}%
\let\mgls@org@postlinkhook\glspostlinkhook
\mglsprefix
\let\mglslastelementlabel\@empty
\@gls@combined@encapsulator
{%
\def\@mgls@previouslabel{}%
\mglselementindex=0\relax
\@for\mglscurrentlabel:=\mglscurrentlist\do{%
\advance\mglselementindex by 1\relax
\glsxtr@setup@docurrent
\ifx\@xfor@nextelement\@nnil
\let\mglsiflast\@firstoftwo
\else
\let\mglsiflast\@secondoftwo
\mglsisfirstuse
{%
\glsxtr@mgls@checklastelement{first}{#2}%
}%
{%
\glsxtr@mgls@checklastelement{used}{#2}%
}%
\fi
\ifcase\@gls@combined@postlinks@nr\relax
\let\glspostlinkhook\relax
\or
\let\glspostlinkhook\mgls@org@postlinkhook
\or
\mglsiflast
{%
\let\glspostlinkhook\relax
}%
{%
\let\glspostlinkhook\mgls@org@postlinkhook
}%
\or
\ifx\mglscurrentlabel\mglscurrentmainlabel
\mglsiflast
{%

```

```

        \let\glspostlinkhook\relax
      }%
    {%
      \let\glspostlinkhook\mgls@org@postlinkhook
    }%
  \else
    \let\glspostlinkhook\relax
  \fi
\or
  \ifx\mglscurrentlabel\mglscurrentmainlabel
    \let\glspostlinkhook\mgls@org@postlinkhook
  \else
    \let\glspostlinkhook\relax
  \fi
\or
  \ifx\mglscurrentlabel\mglscurrentmainlabel
    \let\glspostlinkhook\relax
  \else
    \mglsiflast
    {%
      \let\glspostlinkhook\relax
    }%
    {%
      \let\glspostlinkhook\mgls@org@postlinkhook
    }%
  \fi
\or
  \ifx\mglscurrentlabel\mglscurrentmainlabel
    \let\glspostlinkhook\relax
  \else
    \let\glspostlinkhook\mgls@org@postlinkhook
  \fi
\fi
\mglsiflast
{%
  \xappto\@mgls@post@hookdefs{%
    \noexpand\def\noexpand\mglslastelementlabel
      {\expandonce\mglscurrentlabel}}%
}%
{}%
\@mgls@do@current@element
{%
  \mglselementprehook
  \GlsXtrIfUnusedOrUndefined{\mglscurrentlabel}%
  {\let\@mgls@current@iffirstuse\@firstoftwo}%
  {\let\@mgls@current@iffirstuse\@secondoftwo}%
  \ifx\mglscurrentlabel\mglscurrentmainlabel
    \edef\@mgls@current@options{format=\@gls@combined@encapmain}%
    \ifcase\@gls@combined@indexmain
      \appto\@mgls@current@options{,noindex}%

```

```

\or
\appto\@mgl@current@options{,noindex=false}%
\or
\@mgl@current@iffirstuse
{\appto\@mgl@current@options{,noindex=false}}%
{\appto\@mgl@current@options{,noindex}}%
\fi
\ifcase\@gl@combined@hyper\relax
\appto\@mgl@current@options{,hyper=false}% none
\or
\appto\@mgl@current@options{,hyper=false}% allmain
\or
\appto\@mgl@current@options{,\@mgl@hyper}% mainonly
\or
\appto\@mgl@current@options{,\@mgl@hyper}% individual
\or
\appto\@mgl@current@options{,hyper=false}% otheronly
\or
\mgl@sisfirstuse
{%
\appto\@mgl@current@options{,hyper=false}% notmainfirst
}%
{%
\appto\@mgl@current@options{,\@mgl@hyper}% notmainfirst
}%
\or
\appto\@mgl@current@options{,\@mgl@hyper}% nototherfirst
\or
\mgl@sisfirstuse
{%
\appto\@mgl@current@options{,hyper=false}% notfirst
}%
{%
\appto\@mgl@current@options{,\@mgl@hyper}% notfirst
}%
\fi
\appto\@mgl@current@options{,\@mgl@all,\@mgl@main}%
\else
\edef\@mgl@current@options{format=\@gl@combined@encapothers}%
\ifcase\@gl@combined@indexothers\relax
\appto\@mgl@current@options{,noindex}%
\or
\appto\@mgl@current@options{,noindex=false}%
\or
\@mgl@current@iffirstuse
{\appto\@mgl@current@options{,noindex=false}}%
{\appto\@mgl@current@options{,noindex}}%
\fi
\ifcase\@gl@combined@hyper\relax
\appto\@mgl@current@options{,hyper=false}% none

```

```

\or
\appto\@mglscurrentoptions{,hyper=false}% allmain
\or
\appto\@mglscurrentoptions{,hyper=false}% mainonly
\or
\eappto\@mglscurrentoptions{,\@mglshyper}% individual
\or
\eappto\@mglscurrentoptions{,\@mglshyper}% otheronly
\or
\eappto\@mglscurrentoptions{,\@mglshyper}% notmainfirst
\or
\mglsisfirstuse
{%
\appto\@mglscurrentoptions{,hyper=false}% nototherfirst
}%
{%
\eappto\@mglscurrentoptions{,\@mglshyper}% nototherfirst
}%
\or
\mglsisfirstuse
{%
\appto\@mglscurrentoptions{,hyper=false}% notfirst
}%
{%
\eappto\@mglscurrentoptions{,\@mglshyper}% notfirst
}%
\fi
\appto\@mglscurrentoptions{,\@mglscall,\@mglsothers}%
\fi
\ifx\@mglspreviouslabel\empty
\ifx\mglscurrentlabel\mglscurrentmainlabel
\let\@mglscs#6\relax
\else
\let\@mglscs#4\relax
\fi
\else
\@mglsprevious@iffirstuse
{%
\@mglscurrent@iffirstuse
{\glscombinedfirstsepfirst{\@mglspreviouslabel}{\mglscurrentlabel}}%
{\glscombinedfirstsep{\@mglspreviouslabel}{\mglscurrentlabel}}%
}%
{%
\@mglscurrent@iffirstuse
{\glscombinedsepfirst{\@mglspreviouslabel}{\mglscurrentlabel}}%
{\glscombinedsep{\@mglspreviouslabel}{\mglscurrentlabel}}%
}%
\ifx\mglscurrentlabel\mglscurrentmainlabel
\let\@mglscs#7\relax
\else

```

```

        \let\@mgls@cs#5\relax
    \fi
\fi
\mglsiflast
  {\expandafter\@mgls@cs\expandafter{\@mgls@current@options}{\mglscurrentlabel}[\#3]}%
  {\expandafter\@mgls@cs\expandafter{\@mgls@current@options}{\mglscurrentlabel}[]}%
\ifx\mglscurrentlabel\mglscurrentmainlabel
  \xappto\@mgls@post@hookdefs{%
    \noexpand\def\noexpand\mglslastmainlabel
      {\expandonce\mglscurrentmainlabel}%
  }%
  \glstrifwasfirstuse
  {%
    \gappto\@mgls@post@hookdefs{\let\mglsiflastmainwasfirstuse\@firstoftwo}%
  }%
  {%
    \gappto\@mgls@post@hookdefs{\let\mglsiflastmainwasfirstuse\@secondoftwo}%
  }%
  \glsifplural
  {%
    \gappto\@mgls@post@hookdefs{\let\mglsiflastmainwasplural\@firstoftwo}%
  }%
  {%
    \gappto\@mgls@post@hookdefs{\let\mglsiflastmainwasplural\@secondoftwo}%
  }%
  \glscapscase
  {%
    \gappto\@mgls@post@hookdefs{%
      \let\mglsiflastmaincapscase\@firstofthree
    }%
  }%
  {%
    \gappto\@mgls@post@hookdefs{%
      \let\mglsiflastmaincapscase\@secondofthree
    }%
  }%
  {%
    \gappto\@mgls@post@hookdefs{%
      \let\mglsiflastmaincapscase\@thirdofthree
    }%
  }%
\fi
\let\@mgls@previouslabel\mglscurrentlabel
\let\@mgls@previous@iffirstuse\@mgls@current@iffirstuse
}%
\mglselementposthook
}%
\ifx\mglslastmainlabel\@empty
  \gappto\@mgls@post@hookdefs{\let\mglsiflastmainwasskipped\@firstoftwo}%
\else

```

```

\gappto\@mgls@post@hookdefs{\let\mglsiflastmainsskipped\@secondoftwo}%
\fi
\ifx\@mgls@do@current@element\@gobble
\gappto\@mgls@post@hookdefs{\let\mglsiflastelementsskipped\@firstoftwo}%
\else
\gappto\@mgls@post@hookdefs{\let\mglsiflastelementsskipped\@secondoftwo}%
\fi
\glstrifwasfirstuse
{%
\gappto\@mgls@post@hookdefs{\let\mglsiflastelementwasfirstuse\@firstoftwo}%
}%
{%
\gappto\@mgls@post@hookdefs{\let\mglsiflastelementwasfirstuse\@secondoftwo}%
}%
\glssifplural
{%
\gappto\@mgls@post@hookdefs{\let\mglsiflastelementwasplural\@firstoftwo}%
}%
{%
\gappto\@mgls@post@hookdefs{\let\mglsiflastelementwasplural\@secondoftwo}%
}%
\glscapscase
{%
\gappto\@mgls@post@hookdefs{%
\let\mglsiflastelementcapscase\@firstofthree
}%
}%
{%
\gappto\@mgls@post@hookdefs{%
\let\mglsiflastelementcapscase\@secondofthree
}%
}%
{%
\gappto\@mgls@post@hookdefs{%
\let\mglsiflastelementcapscase\@thirdofthree
}%
}%
}%
\@mgls@post@hookdefs
\mglsuffix
\ifcase\@mgls@unsetaction\relax
\xappto\@mgls@post@hookdefs{%
\noexpand\mglsunset{\expandonce\mglscurrentmultilabel}}%
\or
\xappto\@mgls@post@hookdefs{%
\noexpand\mglslocalunset{\expandonce\mglscurrentmultilabel}}%
\fi
}%
\glstrmglswrite{#2}%
\egroup

```



```

\@mgls@post@hookdefs
\mgls@do@postlinkhook
}
\newcommand*{\mglscustompostlinkhook}{}
\newcommand*{\mglslastelementpostlinkhook}{%
\let\glstrifwasfirstuse\mglsiflastelementwasfirstuse
\let\glsifplural\mglsiflastelementwasplural
\let\glscapscase\mglsiflastelementcapscase
\let\glslabel\mglslastelementlabel
\glspostlinkhook
}
\newcommand*{\mglslastmainpostlinkhook}{%
\let\glstrifwasfirstuse\mglsiflastmainwasfirstuse
\let\glsifplural\mglsiflastmainwasplural
\let\glscapscase\mglsiflastmaincapscase
\let\glslabel\mglslastmainlabel
\glspostlinkhook
}
\newcommand*{\mglsdefcategoryprefix}[2]{%
\csdef{mglsprefix@#1}{#2}%
}
\newcommand*{\mglscategoryprefix}[3]{%
\ifcsdef{mglsprefix@#1}{#2}{#3}%
}
\newcommand*{\mglsusecategoryprefix}[1]{%
\csuse{mglsprefix@#1}%
}
\newcommand*{\mglsprefix}{%
\ifdefempty\mglscurrentcategory
{\mglscurrentprefix}%
{%
\mglscategoryprefix{\mglscurrentcategory}%
{\mglsusecategoryprefix{\mglscurrentcategory}}%
{\mglscurrentprefix}%
}%
}
\newcommand*{\mglsdefcategorysuffix}[2]{%
\csdef{mglssuffix@#1}{#2}%
}
\newcommand*{\mglscategorysuffix}[3]{%
\ifcsdef{mglssuffix@#1}{#2}{#3}%
}
\newcommand*{\mglsusecategorysuffix}[1]{%
\csuse{mglssuffix@#1}%
}
\newcommand*{\mglssuffix}{%
\ifdefempty\mglscurrentcategory
{\ifdefempty\mglscurrentsuffix}{\space(\mglscurrentsuffix)}}%
{%
\mglscategorysuffix{\mglscurrentcategory}%
}

```

```

        {\mglsecategorysuffix{\mglscurrentcategory}}%
        {\ifdefempty{\mglscurrentsuffix}{ }\space(\mglscurrentsuffix)}}%
    }%
}
\newcommand*{\mglselementprehook}{}
\newcommand*{\mglselementposthook}{}
\newcommand*{\glscombinedsep}[2]{%
    \glshasattribute{#1}{combinedsep}%
    {\glsgetattribute{#1}{combinedsep}}%
    { }%
}
\newcommand*{\glscombinedfirstsepfirst}[2]{%
    \glshasattribute{#1}{combinedfirstsepfirst}%
    {\glsgetattribute{#1}{combinedfirstsepfirst}}%
    {\glscombinedsep{#1}{#2}}%
}
\newcommand*{\glscombinedfirstsep}[2]{%
    \glshasattribute{#1}{combinedfirstsep}%
    {\glsgetattribute{#1}{combinedfirstsep}}%
    {\glscombinedsep{#1}{#2}}%
}
\newcommand*{\glscombinedsepfirst}[2]{%
    \glshasattribute{#1}{combinedsepfirst}%
    {\glsgetattribute{#1}{combinedsepfirst}}%
    {\glscombinedsep{#1}{#2}}%
}
\newcommand*{\glssetcombinedsepabbrvnbs}{%
    \renewcommand*{\glscombinedsep}[2]{%
        \glshasattribute{##1}{combinedsep}%
        {\glsgetattribute{##1}{combinedsep}}%
        {\ifhasshort{##1}{~}{ }}%
    }%
    \renewcommand*{\glscombinedsepfirst}[2]{%
        \glshasattribute{##1}{combinedsepfirst}%
        {\glsgetattribute{##1}{combinedsepfirst}}%
        {\ifhasshort{##1}{~}{ }}%
    }%
    \renewcommand*{\glscombinedfirstsep}[2]{%
        \glshasattribute{##1}{combinedfirstsep}%
        {\glsgetattribute{##1}{combinedfirstsep}}%
        { }%
    }%
    \renewcommand*{\glscombinedfirstsepfirst}[2]{%
        \glshasattribute{##1}{combinedfirstsepfirst}%
        {\glsgetattribute{##1}{combinedfirstsepfirst}}%
        { }%
    }%
}
\newcommand*{\glssetcombinedsepabbrvnone}{%
    \renewcommand*{\glscombinedsep}[2]{%

```

```

\glshasattribute{##1}{combinedsep}%
{\glsggetattribute{##1}{combinedsep}}%
{\ifhasshort{##1}{\ifhasshort{##2}{\{ \}}}%
}%
\renewcommand*{\glscombinedsefirst}[2]{%
\glshasattribute{##1}{combinedsefirst}%
{\glsggetattribute{##1}{combinedsefirst}}%
{\ifhasshort{##1}{\{ \}}}%
}%
\renewcommand*{\glscombinedfirstsep}[2]{%
\glshasattribute{##1}{combinedfirstsep}%
{\glsggetattribute{##1}{combinedfirstsep}}%
{\ifhasshort{##2}{\{ \}}}%
}%
\renewcommand*{\glscombinedfirstsefirst}[2]{%
\glshasattribute{##1}{combinedfirstsefirst}%
{\glsggetattribute{##1}{combinedfirstsefirst}}%
{ \}}%
}%
}
\newcommand*{\glssetcombinedsepnarrow}[2]{%
\renewcommand*{\glscombinedsep}[2]{%
\glshasattribute{##1}{combinedsep}%
{\glsggetattribute{##1}{combinedsep}}%
{%
\ifhasshort{##1}%
{\settowidth{\dimen@}{\glsentryshort{##1}}}%
{\settowidth{\dimen@}{\glsentrytext{##1}}}%
\ifdim\dimen@<#1\relax
#2%
\else
\ifhasshort{##2}%
{\settowidth{\dimen@}{\glsentryshort{##2}}}%
{\settowidth{\dimen@}{\glsentrytext{##2}}}%
\ifdim\dimen@<#1\relax
#2%
\else
\space
\fi
\fi
}%
}%
\renewcommand*{\glscombinedsefirst}[2]{%
\glshasattribute{##1}{combinedsefirst}%
{\glsggetattribute{##1}{combinedsefirst}}%
{%
\ifhasshort{##1}%
{\settowidth{\dimen@}{\glsentryshort{##1}}}%
{\settowidth{\dimen@}{\glsentrytext{##1}}}%
\ifdim\dimen@<#1\relax

```

```

#2%
\else
  \ifhaslong{##2}%
    {\settowidth{\dimen@}{\glentrylong{##2}}}%
    {\settowidth{\dimen@}{\glentryfirst{##2}}}%
    \ifdim\dimen@<#1\relax
      #2%
    \else
      \space
    \fi
  \fi
}%
}%
\renewcommand*{\glscmbinedfirstsep}[2]{%
  \glshasattribute{##1}{combinedfirstsep}%
  {\glsggetattribute{##1}{combinedfirstsep}}%
  {%
    \ifhaslong{##1}%
    {\settowidth{\dimen@}{\glentrylong{##1}}}%
    {\settowidth{\dimen@}{\glentryfirst{##1}}}%
    \ifdim\dimen@<#1\relax
      #2%
    \else
      \ifhasshort{##2}%
      {\settowidth{\dimen@}{\glentryshort{##2}}}%
      {\settowidth{\dimen@}{\glentrytext{##2}}}%
      \ifdim\dimen@<#1\relax
        #2%
      \else
        \space
      \fi
    \fi
  }%
}%
\renewcommand*{\glscmbinedfirstsepfir}[2]{%
  \glshasattribute{##1}{combinedfirstsepfir}%
  {\glsggetattribute{##1}{combinedfirstsepfir}}%
  {%
    \ifhaslong{##1}%
    {\settowidth{\dimen@}{\glentrylong{##1}}}%
    {\settowidth{\dimen@}{\glentryfirst{##1}}}%
    \ifdim\dimen@<#1\relax
      #2%
    \else
      \ifhaslong{##2}%
      {\settowidth{\dimen@}{\glentrylong{##2}}}%
      {\settowidth{\dimen@}{\glentryfirst{##2}}}%
      \ifdim\dimen@<#1\relax
        #2%
      \else

```

```

        \space
      \fi
    \fi
  }%
}%
}
\newcommand{\glxtrmglswrite}[1]{%
  \ifx\@glxtr@record@setting\@glxtr@record@setting@off
  \else
    \protected@edef\@glxtr@mglslabel{#1}%
    \ifdef\@glxtr@mglssreflist
    {%
      \expandafter\DTLifinlist\expandafter{\@glxtr@mglslabel}%
      {\@glxtr@mglssreflist}{}%
      {%
        \xappto\@glxtr@mglssreflist{,\expandonce\@glxtr@mglslabel}%
        \if@mglswriteseparaterefs
          \protected@write\@auxout{}{\string\@glxtr@mglssrefs{#1}}%
        \fi
      }%
    }%
  }%
  {%
    \global\let\@glxtr@mglssreflist\@glxtr@mglslabel
    \if@mglswriteseparaterefs
      \protected@write\@auxout{}{\string\@glxtr@mglssrefs{#1}}%
    \else
      \AtEndDocument{\immediate\protected@write\@auxout{}%
        {\string\@glxtr@mglssrefs{\@glxtr@mglssreflist}}}%
    \fi
    \@mglswriteseparateref@cond
  }%
}
\fi
}
\newcommand{\@glxtr@mglssrefs}[1]{}
\newif\if@mglswriteseparaterefs \@mglswriteseparaterefsfalse
\newcommand{\mglswriteSeparateRefsTrue}{\global\@mglswriteseparaterefstrue}
\newcommand{\mglswriteSeparateRefsFalse}{\global\@mglswriteseparaterefsfalse}
\newcommand*{\@mglswriteseparateref@cond}{%
  \gdef\mglswriteSeparateRefsTrue{\PackageError{glossaries-extra}%
    {Too late to use \string\mglswriteSeparateRefsTrue}%
    {\string\mglswriteSeparateRefsTrue\space can only be used before
    the first instance of any \string\mglswrite-like command}}%
  \gdef\mglswriteSeparateRefsFalse{\PackageError{glossaries-extra}%
    {Too late to use \string\mglswriteSeparateRefsFalse}%
    {\string\mglswriteSeparateRefsFalse\space can only be used before
    the first instance of any \string\mglswrite-like command}}%
}
\newcommand{\glxtr@newmglsw}[5]{%
  \edef\@glxtr@newmglsw@do{%
    \noexpand\newrobustcmd*{\expandonce{\csname #1\endcsname}}%

```

```

        {\noexpand\@gls@hyp@opt\expandonce{\csname ns@glxtr@#1\endcsname}}%
\noexpand\newcommand*{\expandonce{\csname ns@glxtr@#1\endcsname}}[2][{}%
\noexpand\new@ifnextchar[%
    {\expandonce{\csname glxtr@#1\endcsname}{####1}{####2}}}%
    {\expandonce{\csname glxtr@#1\endcsname}{####1}{####2}}[]}%
}%
\noexpand\def\expandonce{\csname glxtr@#1\endcsname}####1####2[####3]{%
\noexpand\def\noexpand\glxtrcurrentmgls\csname{#1}%
\noexpand\glxtr@mgl@mcs@inner{####1}{####2}{####3}%
    {\noexpand#2}{\noexpand#3}{\noexpand#4}{\noexpand#5}%
}%
}%
\@glxtr@newmgls@do
\ifx\@glxtr@record@setting\@glxtr@record@setting@off
\else
    \ifdef\@glxtr@mgl@likelist
    {\xappto\@glxtr@mgl@likelist{, #1}}%
    {%
        \gdef\@glxtr@mgl@likelist{#1}%
        \AtEndDocument{\immediate\protected@write\@auxout{%
            {\string\@glxtr@mgl@like{\@glxtr@mgl@likelist}}}%
        }%
    }%
\fi
}
\newcommand*{\@glxtr@mgl@like}[1]{%
\noexpand\@glxtr@mgl@like{#1}%
\def\@glxtr@mgl@or@mcs{#1}%
\def\@glxtr@mgl@or@gcs{#2}%
\@ifstar{\s@GlsXtrMglsOrGls}%
{%
    \@ifnextchar+{\PLUS\@firstoftwo{\p@GlsXtrMglsOrGls}}%
    {%
        \ifdefempty\@gls@alt@hyp@opt@char\@GlsXtrMglsOrGls\alt@GlsXtrMglsOrGls
        }%
    }%
}
\noexpand\@alt@GlsXtrMglsOrGls{
\expandafter\@ifnextchar\@gls@alt@hyp@opt@char
{\@firstoftwo{\@alt@GlsXtrMglsOrGls}}{\@GlsXtrMglsOrGls}%
}
\noexpand\@GlsXtrMglsOrGls[2][{}%
\glxtrifmulti{#2}%
{\@glxtr@mgl@or@mcs{#1}{#2}}%
{\@glxtr@mgl@or@gcs{#1}{#2}}%
}
\noexpand\@s@GlsXtrMglsOrGls[2][{}%
\glxtrifmulti{#2}%
{\@glxtr@mgl@or@mcs*{#1}{#2}}%
{\@glxtr@mgl@or@gcs*{#1}{#2}}%
}
}

```

```

\newcommand*{\p@GlsXtrMglsOrGls}[2][{}]{%
  \glxstrifmulti{#2}%
  {\@glxstr@mgl@mcs+[#1]{#2}}%
  {\@glxstr@mgl@gcs+[#1]{#2}}%
}
\newcommand*{\@alt@GlsXtrMglsOrGls}[2][{}]{%
  \glxstrifmulti{#2}%
  {\expandafter\@glxstr@mgl@mcs\@gl@alt@hyp@opt@char[#1]{#2}}%
  {\expandafter\@glxstr@mgl@gcs\@gl@alt@hyp@opt@char[#1]{#2}}%
}
\glxtr@newmgls{mgl}{\@gl@}{\@gl@}{\@gl@}{\@gl@}%
\glxtr@newmgls{mglspl}{\@glspl@}{\@glspl@}{\@glspl@}{\@glspl@}%
\glxtr@newmgls{mglmainpl}{\@gl@}{\@gl@}{\@glspl@}{\@glspl@}%
\glxtr@newmgls{Mgl}{\@Gls@}{\@gl@}{\@Gls@}{\@gl@}%
\glxtr@newmgls{Mglspl}{\@Glspl@}{\@glspl@}{\@Glspl@}{\@glspl@}%
\glxtr@newmgls{Mglmainpl}{\@Gls@}{\@gl@}{\@Glspl@}{\@glspl@}%
\glxtr@newmgls{MGl}{\@Gls@}{\@Gls@}{\@Gls@}{\@Gls@}%
\glxtr@newmgls{MGlSpl}{\@Glspl@}{\@Glspl@}{\@Glspl@}{\@Glspl@}%
\glxtr@newmgls{MGL}{\@GLS@}{\@GLS@}{\@GLS@}{\@GLS@}%
\glxtr@newmgls{MGLSpl}{\@GLSpl@}{\@GLSpl@}{\@GLSpl@}{\@GLSpl@}%
\glxtr@newmgls{MGLSmainpl}{\@GLS@}{\@GLS@}{\@GLSpl@}{\@GLSpl@}%
\def\@glslongortext#1#2[#3]{%
  \ifglshaslong{#2}{\@glxtrlong{#1}{#2}[#3]}{\@glstext@{#1}{#2}[#3]}%
}
\def\@glsshortortext#1#2[#3]{%
  \ifglshasshort{#2}{\@glxtrshort{#1}{#2}[#3]}{\@glstext@{#1}{#2}[#3]}%
}
\def\@glfullorfirst#1#2[#3]{%
  \ifglshasshort{#2}{\@glxtr@full{#1}{#2}[#3]}{\@glfirst@{#1}{#2}[#3]}%
}
\def\@Glslongortext#1#2[#3]{%
  \ifglshaslong{#2}{\@Glsxtrlong{#1}{#2}[#3]}{\@Glstext@{#1}{#2}[#3]}%
}
\def\@Glsshortortext#1#2[#3]{%
  \ifglshasshort{#2}{\@Glsxtrshort{#1}{#2}[#3]}{\@Glstext@{#1}{#2}[#3]}%
}
\def\@Glsfullorfirst#1#2[#3]{%
  \ifglshasshort{#2}{\@Glsxtr@full{#1}{#2}[#3]}{\@Glsfirst@{#1}{#2}[#3]}%
}
\glxtr@newmgls{mglsshort}%
{\@glsshortortext}{\@glsshortortext}{\@glsshortortext}{\@glsshortortext}%
\glxtr@newmgls{mglslong}%
{\@glslongortext}{\@glslongortext}{\@glslongortext}{\@glslongortext}%
\glxtr@newmgls{mglfull}%
{\@glfullorfirst}{\@glfullorfirst}{\@glfullorfirst}{\@glfullorfirst}%
\glxtr@newmgls{Mglsshort}%
{\@Glsshortortext}{\@Glsshortortext}{\@Glsshortortext}{\@Glsshortortext}%
\glxtr@newmgls{Mglslong}%
{\@Glslongortext}{\@Glslongortext}{\@Glslongortext}{\@Glslongortext}%

```

```

\glxtr@newmgls{Mglsfull}%
{\@Glsfullorfirst}{\@Glsfullorfirst}{\@Glsfullorfirst}{\@Glsfullorfirst}%
\glxtr@newmgls{mglsname}%
{\@Glsname@}{\@Glsname@}{\@Glsname@}{\@Glsname@}%
\glxtr@newmgls{Mglsname}%
{\@Glsname@}{\@Glsname@}{\@Glsname@}{\@Glsname@}%
\glxtr@newmgls{MGlsname}%
{\@Glsname@}{\@Glsname@}{\@Glsname@}{\@Glsname@}%
\def\@glssymbolorgls#1#2[#3]{%
  \ifglshassymbol{#2}{\@glssymbol@{#1}{#2}[#3]}{\@Gls@{#1}{#2}[#3]}%
}
\def\@glssymbolorgls#1#2[#3]{%
  \ifglshassymbol{#2}{\@glssymbol@{#1}{#2}[#3]}{\@Gls@{#1}{#2}[#3]}%
}
\glxtr@newmgls{mglssymbol}%
{\@glssymbolorgls}{\@glssymbolorgls}{\@glssymbolorgls}{\@glssymbolorgls}%
\glxtr@newmgls{Mglssymbol}%
{\@glssymbolorgls}{\@glssymbolorgls}{\@glssymbolorgls}{\@glssymbolorgls}%
\glxtr@newmgls{MGlssymbol}%
{\@glssymbolorgls}{\@glssymbolorgls}{\@glssymbolorgls}{\@glssymbolorgls}%
\newcommand{\mglsfield}{useri}
\def\@glsgfieldorgls#1#2[#3]{%
  \glxtrifhasfield{\mglsfield}{#2}%
  {\@glsgdisp[#1]{#2}{\glscurrentfieldvalue#3}}%
  {\@Gls@{#1}{#2}[#3]}%
}
\def\@Glsfieldorgls#1#2[#3]{%
  \glxtrifhasfield{\mglsfield}{#2}%
  {\@glsgdisp[#1]{#2}{\xmakefirstuc\glscurrentfieldvalue#3}}%
  {\@Gls@{#1}{#2}[#3]}%
}
\glxtr@newmgls{mglsusefield}%
{\@glsgfieldorgls}{\@glsgfieldorgls}{\@glsgfieldorgls}{\@glsgfieldorgls}%
\glxtr@newmgls{Mglsusefield}%
{\@Glsfieldorgls}{\@Glsfieldorgls}{\@Glsfieldorgls}{\@Glsfieldorgls}%
\glxtr@newmgls{MGlsusefield}%
{\@Glsfieldorgls}{\@Glsfieldorgls}{\@Glsfieldorgls}{\@Glsfieldorgls}%
\newcommand*{\mpglsWarning}{%
  \GlossariesExtraWarning{glossaries-prefix.sty is required for
    \string\mpgls\space family of commands (either load after
    glossaries-extra.sty or use the ‘prefix’ package option)}%
}
\def\@pglsorgls#1#2[#3]{%
  \ifdef\@pgls@{\@pgls@{#1}{#2}[#3]}{\mpglsWarning\@Gls@{#1}{#2}[#3]}%
}
\def\@pglsorglspl#1#2[#3]{%
  \ifdef\@pglspl@{\@pglspl@{#1}{#2}[#3]}{\mpglsWarning\@glspl@{#1}{#2}[#3]}%
}
\def\@Pglsorgls#1#2[#3]{%
  \ifdef\@Pgls@{\@Pgls@{#1}{#2}[#3]}{\mpglsWarning\@Gls@{#1}{#2}[#3]}%
}

```



```

}
\def\@pglsorglspl#1#2[#3]{%
  \ifdef\@pglspl@{\@pglspl@{#1}{#2}[#3]}\mpglsWarning\@glspl@{#1}{#2}[#3]}%
}
\def\@PglSorglspl#1#2[#3]{%
  \ifdef\@PglSpl@{\@PglSpl@{#1}{#2}[#3]}\mpglsWarning\@GLspl@{#1}{#2}[#3]}%
}
\def\@PGLSorgls#1#2[#3]{%
  \ifdef\@PGLS@{\@PGLS@{#1}{#2}[#3]}\mpglsWarning\@GLS@{#1}{#2}[#3]}%
}
\def\@PGLSorglspl#1#2[#3]{%
  \ifdef\@PGLSpl@{\@PGLSpl@{#1}{#2}[#3]}\mpglsWarning\@GLSpl@{#1}{#2}[#3]}%
}
\glsxtr@newmgls{mpgls}{\@pglsorgls@}{\@gls@}{\@pglsorgls@}{\@gls@}%
\glsxtr@newmgls{mpglspl}{\@pglsorglspl@}{\@glspl@}{\@pglsorglspl@}{\@glspl@}%
\glsxtr@newmgls{mpglsmainpl}{\@pglsorgls@}{\@gls@}{\@pglsorglspl@}{\@glspl@}%
\glsxtr@newmgls{Mpgls}{\@PglSorgls@}{\@gls@}{\@PglSorgls@}{\@gls@}%
\glsxtr@newmgls{Mpglspl}{\@PglSorglspl@}{\@glspl@}{\@PglSorglspl@}{\@glspl@}%
\glsxtr@newmgls{Mpglsmainpl}{\@PglSorgls@}{\@gls@}{\@PglSorglspl@}{\@glspl@}%
\glsxtr@newmgls{MPGls}{\@PglSorgls@}{\@GLS@}{\@PglSorgls@}{\@GLS@}%
\glsxtr@newmgls{MPGlspl}{\@PglSorglspl@}{\@GLspl@}{\@PglSorglspl@}{\@GLspl@}%
\glsxtr@newmgls{MPGlsmainpl}{\@PglSorgls@}{\@GLS@}{\@PglSorglspl@}{\@GLSpl@}%
\glsxtr@newmgls{MPGLS}{\@PGLSorgls@}{\@GLS@}{\@PGLSorgls@}{\@GLS@}%
\glsxtr@newmgls{MPGLSpl}{\@PGLSorglspl@}{\@GLSpl@}{\@PGLSorglspl@}{\@GLSpl@}%
\glsxtr@newmgls{MPGLSmainpl}{\@PGLSorgls@}{\@GLS@}{\@PGLSorglspl@}{\@GLSpl@}%
\newcommand*{\RequireGlossariesExtraLang}[1]{%
  \ifundefined{ver@glossariesxtr-#1.ldf}\input{glossariesxtr-#1.ldf}{}%
}
\newcommand*{\ProvidesGlossariesExtraLang}[1]{%
  \ProvidesFile{glossariesxtr-#1.ldf}%
}
\newcommand{\glsxtr@loaddialect}{%
  \IfTrackedLanguageFileExists{\this@dialect}%
  {glossariesxtr-}% prefix
  {.ldf}%
  {%
    \RequireGlossariesExtraLang{\CurrentTrackedTag}%
  }%
  {}% not found
  \@glsxtrdialecthook
}
\@ifpackageloaded{tracklang}{%
  \AnyTrackedLanguages
  {%
    \ForEachTrackedDialect{\this@dialect}{\glsxtr@loaddialect}%
  }%
  {}%
} {}
\@glsxtr@redefstyles
\@glsxtr@do@style

```

9.2 Rollback v1.48 (glossaries-extra-bib2gls-2021-11-22.sty)

Version 1.48 preserved for rollback.

```

\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{glossaries-extra-bib2gls}[2021/11/22 v1.48 (NLCT)]
\ifglsacronym
  \providecommand*\printunsrtacronyms[1] [] {%
    \printunsrtglossary[type=\acronymtype,#1]}%
\fi
\ifglossaryexists{index}
{
  \providecommand*\printunsrtindex[1] [] {%
    \printunsrtglossary[type=index,#1]}%
}{}
\ifglossaryexists{symbols}
{
  \providecommand*\printunsrtsymbols[1] [] {%
    \printunsrtglossary[type=symbols,#1]}%
}{}
\ifglossaryexists{numbers}
{
  \providecommand*\printunsrtnumbers[1] [] {%
    \printunsrtglossary[type=numbers,#1]}%
}{}
\ifglossaryexists{abbreviations}
{
  \providecommand*\printunsrtabbreviations[1] [] {%
    \printunsrtglossary[type=abbreviations,#1]}%
}{}
\renewcommand*\glsdisplaynumberlist[1] {%
  \glsdoifexists{#1}%
  {%
    {\let\bibglsdelimN\glsnumlistsep
     \let\bibglslastDelimN\glsnumlistlastsep
     \glsxtrusefield{#1}{location}}%
  }%
}%
}
\robustify\glsdisplaynumberlist
\renewcommand*\glsentrynumberlist[1]{\glsxtrusefield{#1}{location}}
\newcommand*\glshex{}\string\u
\newcommand*\glsapturedgroup{}\string\$
\newcommand*\GlsXtrIfHasNonZeroChildCount{%
  \ifstar\s@GlsXtrIfHasNonZeroChildCount\@GlsXtrIfHasNonZeroChildCount
}
\newcommand*\@GlsXtrIfHasNonZeroChildCount[3]{%
  \@GlsXtrIfFieldNonZero{childcount}{#1}{#2}{#3}%
}
\newcommand*\s@GlsXtrIfHasNonZeroChildCount[3]{%
  \@GlsXtrIfFieldNonZero{childcount}{#1}{#2}{#3}%
}

```

```

}
\newcommand*\glstrprovidecommand{\providecommand}
\newcommand*\glstrenewcommand{\@star@or@long\glstr@renewcommand}
\newcommand*\glstr@renewcommand[1]{%
\begingroup \escapechar\m@ne\xdef\@gtempa{\string#1}\endgroup
\expandafter\@ifundefined\@gtempa
{%
\GlossariesExtraWarning{can't redefine \noexpand#1(not already defined)}%
}%
\relax
\relax
\let\@ifdefinable\@rc@ifdefinable
\newcommand#1%
}
\newcommand*\glstr@wrglossarylocation[2]{#1}
\ifdef\hyperref
{%
\newcommand*\GlsXtrIndexCounterLink[2]{%
\glstrifhasfield{indexcounter}{#2}%
{\hyperref[wrglossary.\glscurrentfieldvalue]{#1}}%
{#1}%
}
}
{
\newcommand*\GlsXtrIndexCounterLink[2]{#1}
}
\newcommand*\GlsXtrDualField{dual}
\newcommand*\GlsXtrDualBackLink[2]{%
\glstrifhasfield{\GlsXtrDualField}{#2}%
{\glshyperlink[#1]{\glscurrentfieldvalue}}%
{#2}%
}
\newcommand*\GlsXtrBibTeXEntryAliases{%
article=bibtexentry,
book=bibtexentry,
booklet=bibtexentry,
conference=bibtexentry,
inbook=bibtexentry,
incollection=bibtexentry,
inproceedings=bibtexentry,
manual=bibtexentry,
mastersthesis=bibtexentry,
misc=bibtexentry,
phdthesis=bibtexentry,
proceedings=bibtexentry,
techreport=bibtexentry,
unpublished=bibtexentry
}
\newcommand*\GlsXtrProvideBibTeXFields{%
\glsaddstoragekey{address}{}{\glstrbibaddress}%

```

```

\glsaddstoragekey{author}{\glsxtrbibauthor}%
\glsaddstoragekey{booktitle}{\glsxtrbibbooktitle}%
\glsaddstoragekey{chapter}{\glsxtrbibchapter}%
\glsaddstoragekey{edition}{\glsxtrbibedition}%
\glsaddstoragekey{howpublished}{\glsxtrbibhowpublished}%
\glsaddstoragekey{institution}{\glsxtrbibinstitution}%
\glsaddstoragekey{journal}{\glsxtrbibjournal}%
\glsaddstoragekey{month}{\glsxtrbibmonth}%
\glsaddstoragekey{note}{\glsxtrbibnote}%
\glsaddstoragekey{number}{\glsxtrbibnumber}%
\glsaddstoragekey{organization}{\glsxtrbiborganization}%
\glsaddstoragekey{pages}{\glsxtrbibpages}%
\glsaddstoragekey{publisher}{\glsxtrbibpublisher}%
\glsaddstoragekey{school}{\glsxtrbibschooll}%
\glsaddstoragekey{series}{\glsxtrbibseries}%
\glsaddstoragekey{title}{\glsxtrbibtitle}%
\glsaddstoragekey{bibtexkey}{\glsxtrbibtype}%
\glsaddstoragekey{volume}{\glsxtrbibvolume}%
}
\newcommand*\glsxtrmultisupplocation[3]{%
  {%
    \def\glsxtrsupplocationurl{#2}%
    \glsnumber{#1}%
  }%
}
\newcommand*\glsxtrdisplaysuppl[5]{%
  \setentrycounter[1]{#2}%
  \glsxtrmultisupplocation{#5}{#4}{#3}%
}
\ifundef\hyperlink
{
  \newcommand*\glsxtrdisplaylocnameref[8]{%
    \glsnoidxdisplayloc{#1}{#2}{#3}{#4}%
  }
}
{
  \newcommand*\glsxtrdisplaylocnameref[8]{%
    \ifcsdef{glsxtr#2locfmt}%
    {\glsxtrnameref{#3}{\csuse{glsxtr#2locfmt}{#4}{#5}}{#2.#7}{#8}}%
    {%
      \ifstrempy{#5}%
      {%
        \glsxtrnameref{#3}{#4}{#2.#7}{#8}%
      }%
      {%
        \ifstrequal{#2}{page}%
        {\glsxtrnameref{#3}{#4}{#2.#7}{#8}}%
        {\glsxtrnameref{#3}{#5}{#2.#7}{#8}}%
      }%
    }%
  }%
}

```

```

    }
}
\newcommand*{\glxstreuationlocfmt}[2]{(#1)}
\newcommand*{\glxtrnamerefink}[4]{%
  \begingroup
    \let\glshypernumber\@firstofone
    \ifstrempy{#4}%
      {\glxtrfmtinternalnameref{#3}{#1}{#2}}%
      {\glxtrfmtexternalnameref{#3}{#1}{#2}{#4}}%
    \endgroup
}
\newcommand{\glxtrnameloclink}[6]{%
  \begingroup
    \setentrycounter[#1]{#2}%
    \def\glxtr@locationhypertext{#5}%
    \let\glshypernumber\@firstofone
    \def\@glsnumberformat{#3}%
    \def\glxtrsupplocationurl{#6}%
    \toks@={}%
    \@glxtr@bibgls@removespaces#4 \@nil
  \endgroup
}
\def\@glxtr@bibgls@removespaces#1 #2\@nil{%
  \toks@=\expandafter{\the\toks@#1}%
  \ifx\#2\%
    \edef\@glo@tmp{\the\toks@}%
    \ifx\@glo@tmp\empty
      \else
        \protected@edef\@glo@tmp{\glsetentrycounter\@glo@counterprefix\the\toks@}%
        \ifdefvoid\glxtrsupplocationurl
          {%
            \expandafter\glxtrfmtinternalnameref\expandafter{\@glo@tmp}%
            {\@glsnumberformat}{\glxtr@locationhypertext}%
          }%
          {%
            \expandafter\glxtrfmtexternalnameref\expandafter{\@glo@tmp}%
            {\@glsnumberformat}{\glxtr@locationhypertext}{\glxtrsupplocationurl}%
          }%
        \fi
      \else
        \@gls@ReturnAfterFi{%
          \@glxtr@bibgls@removespaces#2\@nil
        }%
      \fi
    }
\newcommand*{\glxtrfmtinternalnameref}[3]{%
  \csuse{#2}{\glsdohyperlink{#1}{#3}}%
}
\newcommand*{\glxtrfmtexternalnameref}[4]{%
  \csuse{#2}{\hyperref{#4}{#1}{#3}}%
}

```

```

}
\newcommand*{\glxtrSetWidest}[3]{%
  \ifdef\glupdatewidest
  {%
    \ifdef\glslongextraUpdateWidest
    {%
      \ifstrempy{#1}
      {%
        \glupdatewidest[#2]{#3}%
        \ifnum#2=0\relax
        \glslongextraUpdateWidest{#3}%
        \else
        \glslongextraUpdateWidestChild{#2}{#3}%
        \fi
      }%
    }%
    \apptoglossarypreamble[#1]{\glupdatewidest[#2]{#3}}%
    \ifnum#2=0\relax
    \apptoglossarypreamble[#1]{\glslongextraUpdateWidest{#3}}%
    \else
    \apptoglossarypreamble[#1]{\glslongextraUpdateWidestChild{#2}{#3}}%
    \fi
  }%
}%
{%
  \ifstrempy{#1}
  {%
    \glupdatewidest[#2]{#3}%
  }%
  {%
    \apptoglossarypreamble[#1]{\glupdatewidest[#2]{#3}}%
  }%
}%
\ifdef\glsetwidest
{%
  \ifdef\glslongextraUpdateWidest
  {%
    \ifstrempy{#1}
    {%
      \glsetwidest[#2]{#3}%
      \ifnum#2=0\relax
      \glslongextraUpdateWidest{#3}%
      \else
      \glslongextraUpdateWidestChild{#2}{#3}%
      \fi
    }%
  }%
  {%
    \apptoglossarypreamble[#1]{\glsetwidest[#2]{#3}}%
  }%
}

```

```

        \ifnum#2=0\relax
        \apptoglossarypreamble[#1]{\glslongextraUpdateWidest{#3}}%
        \else
        \apptoglossarypreamble[#1]{\glslongextraUpdateWidestChild{#2}{#3}}%
        \fi
    }%
}%
{%
    \ifstrempy{#1}
    {%
        \glssetwidest[#2]{#3}%
    }%
    {%
        \apptoglossarypreamble[#1]{\glssetwidest[#2]{#3}}%
    }%
}%
}%
{%
    \ifdef\glslongextraUpdateWidest
    {%
        \ifstrempy{#1}
        {%
            \ifnum#2=0\relax
            \glslongextraUpdateWidest{#3}%
            \else
            \glslongextraUpdateWidestChild{#2}{#3}%
            \fi
        }%
        {%
            \ifnum#2=0\relax
            \apptoglossarypreamble[#1]{\glslongextraUpdateWidest{#3}}%
            \else
            \apptoglossarypreamble[#1]{\glslongextraUpdateWidestChild{#2}{#3}}%
            \fi
        }%
    }%
    {}%
}%
}%
}
\newcommand*{\glsxtrSetWidestFallback}[2]{%
    \ifnum#1=0\relax
    \ifdef\glsFindWidestTopLevelName
    {%
        \glsFindWidestTopLevelName[#2]%
    }%
    {%
        \GlossariesExtraWarning{You need stylemods={tree} to
            provide a fallback for set-widest}%
    }%
}

```

```

\else
\ifdef\glsFindWidestLevelTwo
{%
\glsFindWidestLevelTwo[#2]%
\ifdef\glslongextraUpdateWidestChild
{%
\glslongextraUpdateWidestChild{#1}{\csuse{@glswidestnamei}}%
\glslongextraUpdateWidestChild{#1}{\csuse{@glswidestnameii}}%
}%
}%
}%
{%
\GlossariesExtraWarning{You need stylemods={tree} to
provide a fallback for set-widest}%
}%
\fi
}
\newcommand*{\@glstr@labelprefixes}{}
\newcommand*{\glstrclearlabelprefixes}{%
\renewcommand*{\@glstr@labelprefixes}{}%
}
\newcommand*{\glstraddlabelprefix}[1]{%
\ifstrempy{#1}%
{\glstraddlabelprefix{\empty}}%
{%
\ifdefempty\@glstr@labelprefixes
{\def\@glstr@labelprefixes{#1}}%
{\appto\@glstr@labelprefixes{,#1}}%
}%
}
\newcommand*{\glstrprependlabelprefix}[1]{%
\ifstrempy{#1}%
{\glstrprependlabelprefix{\empty}}%
{%
\ifdefempty\@glstr@labelprefixes
{\def\@glstr@labelprefixes{#1}}%
{\preto\@glstr@labelprefixes{#1,}}%
}%
}
\newcommand*{\glstrifinlabelprefixlist}[3]{%
\ifstrempy{#1}%
{\glstrifinlabelprefixlist{\empty}{#2}{#3}}%
{%
\DTLifinlist{#1}{\@glstr@labelprefixes}{#2}{#3}%
}%
}
\AtBeginDocument{%
\protected@write\@auxout{}{\string\providecommand{\string\@glstr@prefixlabellist}[1]{}}%
\protected@write\@auxout{}{\string\@glstr@prefixlabellist{\@glstr@labelprefixes}}%
}

```



```

\newcommand*{\@glsxtr@get@prefixedlabel}[1]{%
  \begingroup
  \protected@edef\@gls@thislabel{#1}%
  \@for\@glsxtr@prefix:=\@glsxtr@labelprefixes\do
  {%
    \protected@edef\@gls@thislabel{\@glsxtr@prefix#1}%
    \ifglsentryexists{\@gls@thislabel}{\@endfortrue}{}%
  }%
  \edef\@glo@tmp{\endgroup\noexpand\def\noexpand\@gls@thislabel{\@gls@thislabel}}\@glo@tmp
}
\newrobustcmd*{\dgl}{\@gls@hyp@opt\dgl}
\newcommand*{\@dgl}[2][]{%
  \@glsxtr@get@prefixedlabel{#2}%
  \new@ifnextchar[{\@gls@{#1}{\@gls@thislabel}}{\@gls@{#1}{\@gls@thislabel}}[]}%
}
\newrobustcmd*{\dglspl}{\@gls@hyp@opt\dglspl}
\newcommand*{\@dglspl}[2][]{%
  \@glsxtr@get@prefixedlabel{#2}%
  \new@ifnextchar[{\@glspl@{#1}{\@gls@thislabel}}{\@glspl@{#1}{\@gls@thislabel}}[]}%
}
\newrobustcmd*{\dGls}{\@gls@hyp@opt\dGls}
\newcommand*{\@dGls}[2][]{%
  \@glsxtr@get@prefixedlabel{#2}%
  \new@ifnextchar[{\@GLs@{#1}{\@gls@thislabel}}{\@GLs@{#1}{\@gls@thislabel}}[]}%
}
\newrobustcmd*{\dGLspl}{\@gls@hyp@opt\dGLspl}
\newcommand*{\@dGLspl}[2][]{%
  \@glsxtr@get@prefixedlabel{#2}%
  \new@ifnextchar[{\@GLspl@{#1}{\@gls@thislabel}}{\@GLspl@{#1}{\@gls@thislabel}}[]}%
}
\newrobustcmd*{\dGLS}{\@gls@hyp@opt\dGLS}
\newcommand*{\@dGLS}[2][]{%
  \@glsxtr@get@prefixedlabel{#2}%
  \new@ifnextchar[{\@GLS@{#1}{\@gls@thislabel}}{\@GLS@{#1}{\@gls@thislabel}}[]}%
}
\newrobustcmd*{\dGLSpl}{\@gls@hyp@opt\dGLSpl}
\newcommand*{\@dGLSpl}[2][]{%
  \@glsxtr@get@prefixedlabel{#2}%
  \new@ifnextchar[{\@GLSpl@{#1}{\@gls@thislabel}}{\@GLSpl@{#1}{\@gls@thislabel}}[]}%
}
\newrobustcmd*{\dglslink}[3][]{%
  \@glsxtr@get@prefixedlabel{#2}%
  \glslink[#1]{\@gls@thislabel}{#3}%
}
\newrobustcmd*{\dglsdisp}[3][]{%
  \@glsxtr@get@prefixedlabel{#2}%
  \glsdisp[#1]{\@gls@thislabel}{#3}%
}
\newrobustcmd*{\glsxtrmultientryadjustedname}[4]{%
  \bgroup

```

```

\let\@glxstrmultientryadjustednamesep\glxstrmultientryadjustednamesep
\let\@glxstrmultientryadjustednamepresep\glxstrmultientryadjustednamepresep
\let\@glxstrmultientryadjustednamepostsep\glxstrmultientryadjustednamepostsep
\let\@glxstrmultientryadjustednameother\glxstrmultientryadjustednameother
\let\@glxstrmultientryadjustednamefmt\glxstrmultientryadjustednamefmt
\let\@glxstrmultientryadjustednamefirstother\glxstrmultientryadjustednameother
\let\@glxstrmultientryadjustednamefirstfmt\glxstrmultientryadjustednamefmt
\@glxstrmultientryadjustedname{#1}{#2}{#3}{#4}%
\egroup
}
\newrobustcmd*\Glsxstrmultientryadjustedname}[4]{%
  \bgroup
  \let\@glxstrmultientryadjustednamesep\glxstrmultientryadjustednamesep
  \let\@glxstrmultientryadjustednamepresep\glxstrmultientryadjustednamepresep
  \let\@glxstrmultientryadjustednamepostsep\glxstrmultientryadjustednamepostsep
  \let\@glxstrmultientryadjustednameother\glxstrmultientryadjustednameother
  \let\@glxstrmultientryadjustednamefmt\glxstrmultientryadjustednamefmt
  \let\@glxstrmultientryadjustednamefirstother\Glsxstrmultientryadjustednameother
  \let\@glxstrmultientryadjustednamefirstfmt\Glsxstrmultientryadjustednamefmt
  \@glxstrmultientryadjustedname{#1}{#2}{#3}{#4}%
  \egroup
}
\newrobustcmd*\GlsXstrmultientryadjustedname}[4]{%
  \bgroup
  \let\@glxstrmultientryadjustednamesep\glxstrmultientryadjustednamesep
  \let\@glxstrmultientryadjustednamepresep\glxstrmultientryadjustednamepresep
  \let\@glxstrmultientryadjustednamepostsep\glxstrmultientryadjustednamepostsep
  \let\@glxstrmultientryadjustednameother\GlsXstrmultientryadjustednameother
  \let\@glxstrmultientryadjustednamefmt\GlsXstrmultientryadjustednamefmt
  \let\@glxstrmultientryadjustednamefirstother\GlsXstrmultientryadjustednameother
  \let\@glxstrmultientryadjustednamefirstfmt\GlsXstrmultientryadjustednamefmt
  \@glxstrmultientryadjustedname{#1}{#2}{#3}{#4}%
  \egroup
}
\newrobustcmd*\GLSxstrmultientryadjustedname}[4]{%
  \bgroup
  \let\@glxstrmultientryadjustednamesep\glxstrmultientryadjustednamesep
  \let\@glxstrmultientryadjustednamepresep\glxstrmultientryadjustednamepresep
  \let\@glxstrmultientryadjustednamepostsep\glxstrmultientryadjustednamepostsep
  \let\@glxstrmultientryadjustednameother\GLSxstrmultientryadjustednameother
  \let\@glxstrmultientryadjustednamefmt\GLSxstrmultientryadjustednamefmt
  \let\@glxstrmultientryadjustednamefirstother\GLSxstrmultientryadjustednameother
  \let\@glxstrmultientryadjustednamefirstfmt\GLSxstrmultientryadjustednamefmt
  \@glxstrmultientryadjustedname{#1}{#2}{#3}{#4}%
  \egroup
}
\newcommand*\@glxstrmultientryadjustedname}[4]{%
  \letcs\mglscurrentmainlabel{\@glsc@combined@#4@main}%
  \letcs\mglscurrentmainlist{\@glsc@combined@#4@list}%
  \letcs\mglscurrentmainoptions{\@glsc@combined@#4@options}%

```

```

\ifblank{#1}%
{%
  \@glxstrmultientryadjustednamefirstfmt{#2}%
}%
{%
  \def\@mgls@previouslabel{}%
  \let\@gls@xtradjustedother\@glxstrmultientryadjustednamefirstother
  \@for\mglscurrentlabel:=#1\do{%
    \ifx\@mgls@previouslabel\empty
    \else
      \@glxstrmultientryadjustednamesep{\@mgls@previouslabel}{\mglscurrentlabel}%
    \fi
    \@gls@xtradjustedother{\mglscurrentlabel}%
    \let\@mgls@previouslabel\mglscurrentlabel
    \let\@gls@xtradjustedother\@glxstrmultientryadjustednameother
  }%
  \@glxstrmultientryadjustednamepresep{\@mgls@previouslabel}{\mglscurrentmainlabel}%
  \@glxstrmultientryadjustednamefmt{#2}%
}%
\ifblank{#3}%
{%
  \let\@mgls@previouslabel\mglscurrentmainlabel
  \let\@gls@xtrmultientryadjustednamesep\@glxstrmultientryadjustednamepostsep
  \@for\mglscurrentlabel:=#3\do{%
    \@glxstrmultientryadjustednamesep{\@mgls@previouslabel}{\mglscurrentlabel}%
    \@glxstrmultientryadjustednameother{\mglscurrentlabel}%
    \let\@mgls@previouslabel\mglscurrentlabel
    \let\@gls@xtrmultientryadjustednamesep\@glxstrmultientryadjustednamesep
  }%
}%
}
\newcommand*{\glxstrmultientryadjustednamesep}{\glscombinedfirstsepfirst}
\newcommand*{\glxstrmultientryadjustednamepresep}{\glxstrmultientryadjustednamesep}
\newcommand*{\glxstrmultientryadjustednamepostsep}{\glxstrmultientryadjustednamesep}
\newcommand*{\glxstrmultientryadjustednamefmt}[1]{#1}
\newcommand*{\glxstrmultientryadjustednameother}[1]{\glstryname{#1}}
\newcommand*{\Glsxtrmultientryadjustednamefmt}[1]{\makefirstuc{#1}}
\newcommand*{\Glsxtrmultientryadjustednameother}[1]{\Glsentryname{#1}}
\newcommand*{\GlsXtrmultientryadjustednameother}[1]{%
  \glstrytitlecase{#1}{name}}
\ifdef\glscapitalisewords
{%
  \newcommand*{\GlsXtrmultientryadjustednamefmt}[1]{\glscapitalisewords{#1}}
}
{
  \newcommand*{\GlsXtrmultientryadjustednamefmt}[1]{\capitalisewords{#1}}
}
\newcommand*{\GlsXtrmultientryadjustednameother}[1]{%
  \mfirstucMakeUppercase{\glstryname{#1}}}

```

```

\newcommand*{\GLSxtrmultientryadjustednamefmt}[1]{\mfirstucMakeUppercase{#1}}
\providecommand*{\Alpha}{\mathrm{A}}
\providecommand*{\Beta}{\mathrm{B}}
\providecommand*{\Epsilon}{\mathrm{E}}
\providecommand*{\Zeta}{\mathrm{Z}}
\providecommand*{\Eta}{\mathrm{H}}
\providecommand*{\Iota}{\mathrm{I}}
\providecommand*{\Kappa}{\mathrm{K}}
\providecommand*{\Mu}{\mathrm{M}}
\providecommand*{\Nu}{\mathrm{N}}
\providecommand*{\Omicron}{\mathrm{O}}
\providecommand*{\Rho}{\mathrm{P}}
\providecommand*{\Tau}{\mathrm{T}}
\providecommand*{\Chi}{\mathrm{X}}
\providecommand*{\Digamma}{\mathrm{F}}
\providecommand*{\omicron}{\mathit{o}}
@ifpackageloaded{upgreek}%
{
  \providecommand*{\Upalpha}{\mathrm{A}}
  \providecommand*{\Upbeta}{\mathrm{B}}
  \providecommand*{\Upepsilon}{\mathrm{E}}
  \providecommand*{\Upzeta}{\mathrm{Z}}
  \providecommand*{\Upeta}{\mathrm{H}}
  \providecommand*{\Upiota}{\mathrm{I}}
  \providecommand*{\Upkappa}{\mathrm{K}}
  \providecommand*{\Upmu}{\mathrm{M}}
  \providecommand*{\Upnu}{\mathrm{N}}
  \providecommand*{\Upomicron}{\mathrm{O}}
  \providecommand*{\Uprho}{\mathrm{P}}
  \providecommand*{\Uptau}{\mathrm{T}}
  \providecommand*{\Upchi}{\mathrm{X}}
  \providecommand*{\upomicron}{\mathrm{o}}
}%
{}% upgreek.sty not loaded
\newcommand*{\glxtrcontrolrules}{%
  \string'\glshex 200B\string'\string=\glshex 200C\string=\glshex 200D
  \string=\glshex 200E\string=\glshex 200F\string=\glshex 0000\string=\glshex 0001
  \string=\glshex 0002\string=\glshex 0003\string=\glshex 0004\string=\glshex 0005
  \string=\glshex 0006\string=\glshex 0007\string=\glshex 0008
  \string=\string'\glshex 0009\string'\string=\string'\glshex 000B\string'
  \string=\glshex 000E\string=\glshex 000F\string=\string'\glshex
0010\string'\string=\glshex 0011
  \string=\glshex 0012\string=\glshex 0013\string=\glshex 0014\string=\glshex 0015
  \string=\glshex 0016\string=\glshex 0017\string=\glshex 0018\string=\glshex 0019
  \string=\glshex 001A\string=\glshex 001B\string=\glshex 001C\string=\glshex 001D
  \string=\glshex 001E\string=\glshex 001F\string=\glshex 007F\string=\glshex 0080
  \string=\glshex 0081\string=\glshex 0082\string=\glshex 0083\string=\glshex 0084
  \string=\glshex 0085\string=\glshex 0086\string=\glshex 0087\string=\glshex 0088
  \string=\glshex 0089\string=\glshex 008A\string=\glshex 008B\string=\glshex 008C
  \string=\glshex 008D\string=\glshex 008E\string=\glshex 008F\string=\glshex 0090

```

```

\string=\glshex 0091\string=\glshex 0092\string=\glshex 0093\string=\glshex 0094
\string=\glshex 0095\string=\glshex 0096\string=\glshex 0097\string=\glshex 0098
\string=\glshex 0099\string=\glshex 009A\string=\glshex 009B\string=\glshex 009C
\string=\glshex 009D\string=\glshex 009E\string=\glshex 009F
}
\newcommand*{\glxtrspacerules}{%
\string' \string'\string;
\string'\glshex 00A0\string'\string;
\string'\glshex 2000\string'\string;
\string'\glshex 2001\string'\string;
\string'\glshex 2002\string'\string;
\string'\glshex 2003\string'\string;
\string'\glshex 2004\string'\string;
\string'\glshex 2005\string'\string;
\string'\glshex 2006\string'\string;
\string'\glshex 2007\string'\string;
\string'\glshex 2008\string'\string;
\string'\glshex 2009\string'\string;
\string'\glshex 200A\string'\string;
\string'\glshex 3000\string'
}
\newcommand*{\glxtrnonprintablerules}{%
\string'\glshex FEFF\string'\string;
\string'\glshex 000A\string'\string;
\string'\glshex 0009\string'\string;
\string'\glshex 000C\string'\string;
\string'\glshex 000B\string'
}

\newcommand*{\glxtrcombiningdiacriticrules}{%
\glxtrcombiningdiacriticIrules\string;
\glxtrcombiningdiacriticIIrules\string;
\glxtrcombiningdiacriticIIIrules\string;
\glxtrcombiningdiacriticIVrules
}
\newcommand*{\glxtrcombiningdiacriticIrules}{%
\glshex 0301\string;% combining acute
\glshex 0300\string;% combining grave
\glshex 0306\string;% combining breve
\glshex 0302\string;% combining circumflex
\glshex 030C\string;% combining caron
\glshex 030A\string;% combining ring
\glshex 030D\string;% combining vertical line above
\glshex 0308\string;% combining diaeresis
\glshex 030B\string;% combining double acute
\glshex 0303\string;% combining tilde
\glshex 0307\string;% combining dot above
\glshex 0304% combining macron
}
\newcommand*{\glxtrcombiningdiacriticIIrules}{%

```

```

\glshex 0337\string;% combining short solidus overlay
\glshex 0327\string;% combining cedilla
\glshex 0328\string;% combining ogonek
\glshex 0323\string;% combining dot below
\glshex 0332\string;% combining low line
\glshex 0305\string;% combining overline
\glshex 0309\string;% combining hook above
\glshex 030E\string;% combining double vertical line above
\glshex 030F\string;% combining double grave accent
\glshex 0310\string;% combining candrabindu
\glshex 0311\string;% combining inverted breve
\glshex 0312\string;% combining turned comma above
\glshex 0313\string;% combining comma above
\glshex 0314\string;% combining reversed comma above
\glshex 0315\string;% combining comma above right
\glshex 0316\string;% combining grave accent below
\glshex 0317% combining acute accent below
}
\newcommand*{\glxtrcombiningdiacriticIIIrules}{%
\glshex 0318\string;% combining left tack below
\glshex 0319\string;% combining right tack below
\glshex 031A\string;% combining left angle above
\glshex 031B\string;% combining horn
\glshex 031C\string;% combining left half ring below
\glshex 031D\string;% combining up tack below
\glshex 031E\string;% combining down tack below
\glshex 031F\string;% combining plus sign below
\glshex 0320\string;% combining minus sign below
\glshex 0321\string;% combining palatalized hook below
\glshex 0322\string;% combining retroflex hook below
\glshex 0324\string;% combining diaeresis below
\glshex 0325\string;% combining ring below
\glshex 0326\string;% combining comma below
\glshex 0329\string;% combining vertical line below
\glshex 032A\string;% combining bridge below
\glshex 032B\string;% combining inverted double arch below
\glshex 032C\string;% combining caron below
\glshex 032D\string;% combining circumflex accent below
\glshex 032E\string;% combining breve below
\glshex 032F\string;% combining inverted breve below
\glshex 0330\string;% combining tilde below
\glshex 0331\string;% combining macron below
\glshex 0333\string;% combining double low line
\glshex 0334\string;% combining tilde overlay
\glshex 0335\string;% combining short stroke overlay
\glshex 0336\string;% combining long stroke overlay
\glshex 0338\string;% combining long solidus overlay
\glshex 0339\string;% combining combining right half ring below
\glshex 033A\string;% combining inverted bridge below
\glshex 033B\string;% combining square below

```

```

\glshex 033C\string;% combining seagull below
\glshex 033D\string;% combining x above
\glshex 033E\string;% combining vertical tilde
\glshex 033F\string;% combining double overline
\glshex 0342\string;% combining Greek perispomeni
\glshex 0344\string;% combining Greek dialytika tonos
\glshex 0345\string;% combining Greek ypogegrammeni
\glshex 0360\string;% combining double tilde
\glshex 0361\string;% combining double inverted breve
\glshex 0483\string;% combining Cyrillic titlo
\glshex 0484\string;% combining Cyrillic palatalization
\glshex 0485\string;% combining Cyrillic dasia pneumata
\glshex 0486\string;% combining Cyrillic psili pneumata
}
\newcommand*{\glxtrcombiningdiacriticIVrules}{%
\glshex 20D0\string;% combining left harpoon above
\glshex 20D1\string;% combining right harpoon above
\glshex 20D2\string;% combining long vertical line overlay
\glshex 20D3\string;% combining short vertical line overlay
\glshex 20D4\string;% combining anticlockwise arrow above
\glshex 20D5\string;% combining clockwise arrow above
\glshex 20D6\string;% combining left arrow above
\glshex 20D7\string;% combining right arrow above
\glshex 20D8\string;% combining ring overlay
\glshex 20D9\string;% combining clockwise ring overlay
\glshex 20DA\string;% combining anticlockwise ring overlay
\glshex 20DB\string;% combining three dots above
\glshex 20DC\string;% combining four dots above
\glshex 20DD\string;% combining enclosing circle
\glshex 20DE\string;% combining enclosing square
\glshex 20DF\string;% combining enclosing diamond
\glshex 20E0\string;% combining enclosing circle backslash
\glshex 20E1\string;% combining left right arrow above
}
\newcommand*{\glxtrhyphenrules}{%
\string'\string-\string'\string;% ASCII hyphen
\glshex 00AD\string;% soft hyphen
\glshex 2010\string;% hyphen
\glshex 2011\string;% non-breaking hyphen
\glshex 2012\string;% figure dash
\glshex 2013\string;% en dash
\glshex 2014\string;% em dash
\glshex 2015\string;% horizontal bar
\glshex 2212\string=\glshex 207B\string=\glshex 208B% minus sign
}
\newcommand*{\glxtrgeneralpuncrules}{%
\glxtrgeneralpuncIrules
\string<\glxtrcurrencyrules
\string<\glxtrgeneralpuncIIrules
}

```

```

\newcommand*{\glxtrgeneralpuncIrules}{%
\string'\glshex 005F\string'% underscore
\string<\glshex 00AF\string'% macron
\string<\string'\glshex 002C\string'% comma
\string<\string'\glshex 003B\string'% semi-colon
\string<\string'\glshex 003A\string'% colon
\string<\string'\glshex 0021\string'% exclamation mark
\string<\glshex 00A1\string'% inverted exclamation mark
\string<\string'\glshex 003F\string'% question mark
\string<\glshex 00BF\string'% inverted question mark
\string<\string'\glshex 002F\string'% solidus
\string<\string'\glshex 002E\string'% full stop
\string<\glshex 00B4\string'% acute accent
\string<\string'\glshex 0060\string'% grave accent
\string<\string'\glshex 005E\string'% circumflex accent
\string<\glshex 00A8\string'% diaeresis
\string<\string'\glshex 007E\string'% tilde
\string<\glshex 00B7\string'% middle dot
\string<\glshex 00B8\string'% cedilla
\string<\string'\glshex 0027\string'% straight apostrophe
\string<\string'\glshex 0022\string'% straight double quote
\string<\glshex 00AB\string'% left guillemet
\string<\glshex 00BB\string'% right guillemet
\string<\string'\glshex 0028\string'% left parenthesis
\string=>\glshex 207D\string=>\glshex 208D\string'% super/subscript left parenthesis
\string<\string'\glshex 0029\string'% right parenthesis
\string=>\glshex 207E\string=>\glshex 208E\string'% super/subscript right parenthesis
\string<\string'\glshex 005B\string'% left square bracket
\string<\string'\glshex 005D\string'% right square bracket
\string<\string'\glshex 007B\string'% left curly bracket
\string<\string'\glshex 007D\string'% right curly bracket
\string<\glshex 00A7\string'% section sign
\string<\glshex 00B6\string'% pilcrow sign
\string<\glshex 00A9\string'% copyright sign
\string<\glshex 00AE\string'% registered sign
\string<\string'\glshex 0040\string'% at sign
}
\newcommand*{\glxtrcurrencyrules}{%
\glshex 00A4\string'% currency sign
\string<\glshex 0E3F\string'% Thai currency symbol baht
\string<\glshex 00A2\string'% cent sign
\string<\glshex 20A1\string'% colon sign
\string<\glshex 20A2\string'% cruzeiro sign
\string<\string'\glshex 0024\string'% dollar sign
\string<\glshex 20AB\string'% dong sign
\string<\glshex 20AC\string'% euro sign
\string<\glshex 20A3\string'% French franc sign
\string<\glshex 20A4\string'% lira sign
\string<\glshex 20A5\string'% mill sign
\string<\glshex 20A6\string'% naira sign

```



```

\string<\glshex 20A7% peseta sign
\string<\glshex 00A3% pound sign
\string<\glshex 20A8% rupee sign
\string<\glshex 20AA% new sheqel sign
\string<\glshex 20A9% won sign
\string<\glshex 00A5% yen sign
}
\newcommand*{\glxtrgeneralpuncIrules}{%
\string'\glshex 002A\string'% asterisk
\string<\string'\glshex 005C\string'% backslash
\string<\string'\glshex 0026\string'% ampersand
\string<\string'\glshex 0023\string'% hash sign
\string<\string'\glshex 0025\string'% percent sign
\string<\string'\glshex 002B\string'% plus sign
\string=\glshex 207A\string=\glshex 208A% super/subscript plus sign
\string<\glshex 00B1% plus-minus sign
\string<\glshex 00F7% division sign
\string<\glshex 00D7% multiplication sign
\string<\string'\glshex 003C\string'% less-than sign
\string<\string'\glshex 003D\string'% equals sign
\string<\string'\glshex 003E\string'% greater-than sign
\string<\glshex 00AC% not sign
\string<\string'\glshex 007C\string'% vertical bar (pipe)
\string<\glshex 00A6% broken bar
\string<\glshex 00B0% degree sign
\string<\glshex 00B5% micron sign
}
\newcommand*{\glxtrGeneralLatinIrules}{%
\glxtrLatinA
\string<b,B%
\string<c,C%
\string<d,D%
\string<\glxtrLatinE
\string<f,F%
\string<g,G%
\string<\glxtrLatinH
\string<\glxtrLatinI
\string<j,J%
\string<\glxtrLatinK
\string<\glxtrLatinL
\string<\glxtrLatinM
\string<\glxtrLatinN
\string<\glxtrLatinO
\string<\glxtrLatinP
\string<q,Q%
\string<r,R%
\string<\glxtrLatinS
\string<\glxtrLatinT
\string<u,U%
\string<v,V%

```

```

\string<w,W%
\string<\glxtrLatinX
\string<y,Y%
\string<z,Z
}
\newcommand*{\glxtrGeneralLatinIIrules}{%
\glxtrLatinA
\string<b,B%
\string<c,C%
\string<d,D%
\string<\glxtrLatinEth
\string<\glxtrLatinE
\string<f,F%
\string<g,G%
\string<\glxtrLatinH
\string<\glxtrLatinI
\string<j,J%
\string<\glxtrLatinK
\string<\glxtrLatinL
\string<\glxtrLatinM
\string<\glxtrLatinN
\string<\glxtrLatinO
\string<\glxtrLatinP
\string<q,Q%
\string<r,R%
\string<\glxtrLatinS
\string& SS \string, \glxtrLatinEszettSs
\string<\glxtrLatinT
\string<u,U%
\string<v,V%
\string<w,W%
\string<\glxtrLatinX
\string<y,Y%
\string<z,Z%
}
\newcommand*{\glxtrGeneralLatinIIIrules}{%
\glxtrLatinA
\string<b,B%
\string<c,C%
\string<d,D%
\string<\glxtrLatinEth
\string<\glxtrLatinE
\string<f,F%
\string<g,G%
\string<\glxtrLatinH
\string<\glxtrLatinI
\string<j,J%
\string<\glxtrLatinK
\string<\glxtrLatinL
\string<\glxtrLatinM

```

```

\string<\glxtrLatinN
\string<\glxtrLatinO
\string<\glxtrLatinP
\string<q,Q%
\string<r,R%
\string<\glxtrLatinS
\string& SZ, \glxtrLatinEszettSz
\string<\glxtrLatinT
\string<u,U%
\string<v,V%
\string<w,W%
\string<\glxtrLatinX
\string<y,Y%
\string<z,Z%
}
\newcommand*{\glxtrGeneralLatinIVrules}{%
\glxtrLatinA
\string& AE , \glxtrLatinAELigature
\string<b,B%
\string<c,C%
\string<d,D%
\string<\glxtrLatinEth
\string<\glxtrLatinE
\string<f,F%
\string<g,G%
\string<\glxtrLatinH
\string<\glxtrLatinI
\string<j,J%
\string<\glxtrLatinK
\string<\glxtrLatinL
\string<\glxtrLatinM
\string<\glxtrLatinN
\string<\glxtrLatinO
\string& OE , \glxtrLatinOELigature
\string<\glxtrLatinP
\string<q,Q%
\string<r,R%
\string<\glxtrLatinS
\string& SS , \glxtrLatinEszettSs
\string<\glxtrLatinT
\string& th =\glshex 00DE
\string& TH =\glshex 00FE
\string<u,U%
\string<v,V%
\string<w,W%
\string<\glxtrLatinX
\string<y,Y%
\string<z,Z%
}
\newcommand*{\glxtrGeneralLatinVrules}{%

```

```

\glxtrLatinA
\string<b,B%
\string<c,C%
\string<d,D%
\string<\glxtrLatinEth
\string<\glxtrLatinE
\string<f,F%
\string<g,G%
\string<\glxtrLatinH
\string<\glxtrLatinI
\string<j,J%
\string<\glxtrLatinK
\string<\glxtrLatinL
\string<\glxtrLatinM
\string<\glxtrLatinN
\string<\glxtrLatinO
\string<\glxtrLatinP
\string<q,Q%
\string<r,R%
\string<\glxtrLatinS
\string& SS , \glxtrLatinEszettSs
\string<\glxtrLatinT
\string& th =\glshex 00DE
\string& TH =\glshex 00FE
\string<u,U%
\string<v,V%
\string<w,W%
\string<\glxtrLatinX
\string<y,Y%
\string<z,Z%
}
\newcommand*{\glxtrGeneralLatinVirules}{%
\glxtrLatinA
\string<b,B%
\string<c,C%
\string<d,D%
\string<\glxtrLatinEth
\string<\glxtrLatinE
\string<f,F%
\string<g,G%
\string<\glxtrLatinH
\string<\glxtrLatinI
\string<j,J%
\string<\glxtrLatinK
\string<\glxtrLatinL
\string<\glxtrLatinM
\string<\glxtrLatinN
\string<\glxtrLatinO
\string<\glxtrLatinP
\string<q,Q%

```

```

\string<r,R%
\string<\glxtrLatinS
\string& SZ , \glxtrLatinEszettSz
\string<\glxtrLatinT
\string& th =\glshex 00DE
\string& TH =\glshex 00FE
\string<u,U%
\string<v,V%
\string<w,W%
\string<\glxtrLatinX
\string<y,Y%
\string<z,Z%
}
\newcommand*{\glxtrGeneralLatinVIIrules}{%
\glxtrLatinA
\string<\glxtrLatinAELigature
\string<b,B%
\string<c,C%
\string<d,D%
\string<\glxtrLatinEth
\string<\glxtrLatinE
\string<f,F%
\string<\glxtrLatinInsularG
\string<\glxtrLatinH
\string<\glxtrLatinI
\string<j,J%
\string<\glxtrLatinK
\string<\glxtrLatinL
\string<\glxtrLatinM
\string<\glxtrLatinN
\string<\glxtrLatinO
\string<\glxtrLatinOELigature
\string<\glxtrLatinP
\string<q,Q%
\string<r,R%
\string<\glshex 017F=\glxtrLatinS % s and long s
\string<\glxtrLatinT
\string<\glxtrLatinThorn
\string<u,U%
\string<v,V%
\string< w\string=\glshex 01BF, W\string=\glshex 01F7
\string<\glxtrLatinX
\string<y,Y%
\string<z,Z%
}
\newcommand*{\glxtrGeneralLatinVIIIrules}{%
\glxtrLatinA
\string& AE , \glxtrLatinAELigature
\string<b,B%
\string<c,C%

```

```

\string<\glshex 00F0\string;d,\glshex 00D0\string;D% D and eth
\string<\glxtrLatinE
\string<f,F%
\string<g,G%
\string<\glxtrLatinH
\string<\glxtrLatinI
\string<j,J%
\string<\glxtrLatinK
\string<\glshex 0142\string=\glxtrLatinL\string=\glshex 0141% L and \L
\string<\glxtrLatinM
\string<\glxtrLatinN
\string<\glshex 00F8\string=\glxtrLatinO\string=\glshex 00D8% O and \O
\string& OE , \glxtrLatinOELigature
\string<\glxtrLatinP
\string<q,Q%
\string<r,R%
\string<\glxtrLatinS
\string& SS , \glxtrLatinEszettSs
\string<\glxtrLatinT
\string& th =\glshex 00DE
\string& TH =\glshex 00FE
\string<u,U%
\string<v,V%
\string<w,W%
\string<\glxtrLatinX
\string<y,Y%
\string<z,Z%
}
\newcommand*{\glxtrLatinA}{%
  a\string=\glshex 00AA\string=\glshex 2090,A
}
\newcommand*{\glxtrLatinE}{%
  e\string=\glshex 2091,E
}
\newcommand*{\glxtrLatinH}{%
  h\string=\glshex 2095,H
}
\newcommand*{\glxtrLatinI}{%
  i\string=\glshex 2071,I
}
\newcommand*{\glxtrLatinK}{%
  k\string=\glshex 2096,K
}
\newcommand*{\glxtrLatinL}{%
  l\string=\glshex 2097,L
}
\newcommand*{\glxtrLatinM}{%
  m\string=\glshex 2098,M
}
\newcommand*{\glxtrLatinN}{%

```

```

    n\string=\glshex 207F\string=\glshex 2099,N
}
\newcommand*{\glxtrLatinO}{%
    o\string=\glshex 00BA\string=\glshex 2092,O
}
\newcommand*{\glxtrLatinP}{%
    p\string=\glshex 209A,P
}
\newcommand*{\glxtrLatinS}{%
    s\string=\glshex 209B,S
}
\newcommand*{\glxtrLatinT}{%
    t\string=\glshex 209C,T
}
\newcommand*{\glxtrLatinX}{%
    x\string=\glshex 2093,X
}
\newcommand*{\glxtrLatinSchwa}{%
    \glshex 0259\string=\glshex 2094,\glshex 018F
}
\newcommand*{\glxtrLatinEszettSs}{%
    \glshex 00DF% eszett
    \string=\glshex 017Fs % long S s
}
\newcommand*{\glxtrLatinEszettSz}{%
    \glshex 00DF% eszett
    \string= \glshex 017Fz % long S z
}
\newcommand*{\glxtrLatinEth}{%
    \glshex 00F0,\glshex 00D0% eth
}
\newcommand*{\glxtrLatinThorn}{%
    \glshex 00FE,\glshex 00DE% thorn
}
\newcommand*{\glxtrLatinAELigature}{%
    \glshex 00E6,\glshex 00C6% AE-ligature
}
\newcommand*{\glxtrLatinOELigature}{%
    \glshex 0153,\glshex 0152% OE-ligature
}
\newcommand*{\glxtrLatinAA}{%
    \glshex 00E5=a\glshex 030A,% \aa
    \glshex 00C5=A\glshex 030A% \AA
}
\newcommand*{\glxtrLatinWynn}{%
    \glshex 01BF,\glshex 01F7% wynn
}
\newcommand*{\glxtrLatinInsularG}{%
    \glshex 1D79,\glshex A77D% insular G
    \string; g, G
}

```

```

}
\newcommand*{\glxtrLatinOslash}{%
  \glshex 00F8,\glshex 00D8% \o, \O
}
\newcommand*{\glxtrLatinLslash}{%
  \glshex 0142,\glshex 0141% \l, \L
}
\newcommand*{\glxtrMathUpGreekIrules}{%
  \glxtrUpAlpha
  \string<\glxtrUpBeta
  \string<\glxtrUpGamma
  \string<\glxtrUpDelta
  \string<\glxtrUpEpsilon
  \string<\glxtrUpDigamma
  \string<\glxtrUpZeta
  \string<\glxtrUpEta
  \string<\glxtrUpTheta
  \string<\glxtrUpIota
  \string<\glxtrUpKappa
  \string<\glxtrUpLambda
  \string<\glxtrUpMu
  \string<\glxtrUpNu
  \string<\glxtrUpXi
  \string<\glxtrUpOmicron
  \string<\glxtrUpPi
  \string<\glxtrUpRho
  \string<\glxtrUpSigma
  \string<\glxtrUpTau
  \string<\glxtrUpUpsilon
  \string<\glxtrUpPhi
  \string<\glxtrUpChi
  \string<\glxtrUpPsi
  \string<\glxtrUpOmega
}
\newcommand*{\glxtrMathUpGreekIIrules}{%
  \glxtrUpAlpha
  \string<\glxtrUpBeta
  \string<\glxtrUpGamma
  \string<\glxtrUpDelta
  \string<\glxtrUpEpsilon
  \string<\glxtrUpZeta
  \string<\glxtrUpEta
  \string<\glxtrUpTheta
  \string<\glxtrUpIota
  \string<\glxtrUpKappa
  \string<\glxtrUpLambda
  \string<\glxtrUpMu
  \string<\glxtrUpNu
  \string<\glxtrUpXi
  \string<\glxtrUpOmicron

```



```

\string<\glxtrUpPi
\string<\glxtrUpRho
\string<\glxtrUpSigma
\string<\glxtrUpTau
\string<\glxtrUpUpsilon
\string<\glxtrUpPhi
\string<\glxtrUpChi
\string<\glxtrUpPsi
\string<\glxtrUpOmega
}
\newcommand*{\glxtrMathItalicGreekIrules}{%
\glxtrMathItalicAlpha
\string<\glxtrMathItalicBeta
\string<\glxtrMathItalicGamma
\string<\glxtrMathItalicDelta
\string<\glxtrMathItalicEpsilon
\string<\glxtrUpDigamma
\string<\glxtrMathItalicZeta
\string<\glxtrMathItalicEta
\string<\glxtrMathItalicTheta
\string<\glxtrMathItalicIota
\string<\glxtrMathItalicKappa
\string<\glxtrMathItalicLambda
\string<\glxtrMathItalicMu
\string<\glxtrMathItalicNu
\string<\glxtrMathItalicXi
\string<\glxtrMathItalicOmicron
\string<\glxtrMathItalicPi
\string<\glxtrMathItalicRho
\string<\glxtrMathItalicSigma
\string<\glxtrMathItalicTau
\string<\glxtrMathItalicUpsilon
\string<\glxtrMathItalicPhi
\string<\glxtrMathItalicChi
\string<\glxtrMathItalicPsi
\string<\glxtrMathItalicOmega
}
\newcommand*{\glxtrMathItalicGreekIIrules}{%
\glxtrMathItalicAlpha
\string<\glxtrMathItalicBeta
\string<\glxtrMathItalicGamma
\string<\glxtrMathItalicDelta
\string<\glxtrMathItalicEpsilon
\string<\glxtrMathItalicZeta
\string<\glxtrMathItalicEta
\string<\glxtrMathItalicTheta
\string<\glxtrMathItalicIota
\string<\glxtrMathItalicKappa
\string<\glxtrMathItalicLambda
\string<\glxtrMathItalicMu

```

```

\string<\glxstrMathItalicNu
\string<\glxstrMathItalicXi
\string<\glxstrMathItalicOmicron
\string<\glxstrMathItalicPi
\string<\glxstrMathItalicRho
\string<\glxstrMathItalicSigma
\string<\glxstrMathItalicTau
\string<\glxstrMathItalicUpsilon
\string<\glxstrMathItalicPhi
\string<\glxstrMathItalicChi
\string<\glxstrMathItalicPsi
\string<\glxstrMathItalicOmega
}
\newcommand*{\glxstrMathItalicUpperGreekIrules}{%
\glshex 1D6E2% upper case alpha (maths italic)
\string<\glshex 1D6E3% upper case beta (maths italic)
\string<\glshex 1D6E4% upper case gamma (maths italic)
\string<\glshex 1D6E5% upper case delta (maths italic)
\string<\glshex 1D6E6% upper case epsilon (maths italic)
\string<\glshex 03DC% upper case digamma
\string<\glshex 1D6E7% upper case zeta (maths italic)
\string<\glshex 1D6E8% upper case eta (maths italic)
\string<\glshex 1D6E9% upper case theta (maths italic)
\string=<\glshex 1D6F3% upper case theta variant (maths italic)
\string<\glshex 1D6EA% upper case iota (maths italic)
\string<\glshex 1D6EB% upper case kappa (maths italic)
\string<\glshex 1D6EC% upper case lambda (maths italic)
\string<\glshex 1D6ED% upper case mu (maths italic)
\string<\glshex 1D6EE% upper case nu (maths italic)
\string<\glshex 1D6EF% upper case xi (maths italic)
\string<\glshex 1D6F0% upper case omicron (maths italic)
\string<\glshex 1D6F1% upper case pi (maths italic)
\string<\glshex 1D6F2% upper case rho (maths italic)
\string<\glshex 1D6F4% upper case sigma (maths italic)
\string<\glshex 1D6F5% upper case tau (maths italic)
\string<\glshex 1D6F6% upper case upsilon (maths italic)
\string<\glshex 1D6F7% upper case phi (maths italic)
\string<\glshex 1D6F8% upper case chi (maths italic)
\string<\glshex 1D6F9% upper case psi (maths italic)
\string<\glshex 1D6FA% upper case omega (maths italic)
}
\newcommand*{\glxstrMathItalicUpperGreekIIrules}{%
\glshex 1D6E2% upper case alpha (maths italic)
\string<\glshex 1D6E3% upper case beta (maths italic)
\string<\glshex 1D6E4% upper case gamma (maths italic)
\string<\glshex 1D6E5% upper case delta (maths italic)
\string<\glshex 1D6E6% upper case epsilon (maths italic)
\string<\glshex 1D6E7% upper case zeta (maths italic)
\string<\glshex 1D6E8% upper case eta (maths italic)
\string<\glshex 1D6E9% upper case theta (maths italic)

```

```

\string=\glshex 1D6F3% upper case theta variant (maths italic)
\string<\glshex 1D6EA% upper case iota (maths italic)
\string<\glshex 1D6EB% upper case kappa (maths italic)
\string<\glshex 1D6EC% upper case lambda (maths italic)
\string<\glshex 1D6ED% upper case mu (maths italic)
\string<\glshex 1D6EE% upper case nu (maths italic)
\string<\glshex 1D6EF% upper case xi (maths italic)
\string<\glshex 1D6F0% upper case omicron (maths italic)
\string<\glshex 1D6F1% upper case pi (maths italic)
\string<\glshex 1D6F2% upper case rho (maths italic)
\string<\glshex 1D6F4% upper case sigma (maths italic)
\string<\glshex 1D6F5% upper case tau (maths italic)
\string<\glshex 1D6F6% upper case upsilon (maths italic)
\string<\glshex 1D6F7% upper case phi (maths italic)
\string<\glshex 1D6F8% upper case chi (maths italic)
\string<\glshex 1D6F9% upper case psi (maths italic)
\string<\glshex 1D6FA% upper case omega (maths italic)
}
\newcommand*{\glxtrMathItalicLowerGreekIrules}{%
\glshex 1D6FC% lower case alpha (maths italic)
\string<\glshex 1D6FD% lower case beta (maths italic)
\string<\glshex 1D6FE% lower case gamma (maths italic)
\string<\glshex 1D6FF% lower case delta (maths italic)
\string<\glshex 1D700% lower case epsilon (maths italic)
\string=\glshex 1D716% lower case epsilon variant (maths italic)
\string<\glshex 03DD% lower case digamma
\string<\glshex 1D701% lower case zeta (maths italic)
\string<\glshex 1D702% lower case eta (maths italic)
\string<\glshex 1D703% lower case theta (maths italic)
\string=\glshex 1D717% lower case theta variant (maths italic)
\string<\glshex 1D704% lower case iota (maths italic)
\string<\glshex 1D705% lower case kappa (maths italic)
\string=\glshex 1D718% lower case kappa variant (maths italic)
\string<\glshex 1D706% lower case lambda (maths italic)
\string<\glshex 1D707% lower case mu (maths italic)
\string<\glshex 1D708% lower case nu (maths italic)
\string<\glshex 1D709% lower case xi (maths italic)
\string<\glshex 1D70A% lower case omicron (maths italic)
\string<\glshex 1D70B% lower case pi (maths italic)
\string=\glshex 1D71B% lower case pi variant (maths italic)
\string<\glshex 1D70C% lower case rho (maths italic)
\string=\glshex 1D71A% lower case rho variant (maths italic)
\string<\glshex 1D70D% lower case final sigma (maths italic)
\string=\glshex 1D70E% lower case sigma (maths italic)
\string<\glshex 1D70F% lower case tau (maths italic)
\string<\glshex 1D710% lower case upsilon (maths italic)
\string<\glshex 1D711% lower case phi (maths italic)
\string=\glshex 1D719% lower case phi variant (maths italic)
\string<\glshex 1D712% lower case chi (maths italic)
\string<\glshex 1D713% lower case psi (maths italic)

```

```

\string<\glshex 1D714% lower case omega (maths italic)
}
\newcommand*{\glxstrMathItalicLowerGreekIrules}{%
\glshex 1D6FC% lower case alpha (maths italic)
\string<\glshex 1D6FD% lower case beta (maths italic)
\string<\glshex 1D6FE% lower case gamma (maths italic)
\string<\glshex 1D6FF% lower case delta (maths italic)
\string<\glshex 1D700% lower case epsilon (maths italic)
\string=\glshex 1D716% lower case epsilon variant (maths italic)
\string<\glshex 1D701% lower case zeta (maths italic)
\string<\glshex 1D702% lower case eta (maths italic)
\string<\glshex 1D703% lower case theta (maths italic)
\string=\glshex 1D717% lower case theta variant (maths italic)
\string<\glshex 1D704% lower case iota (maths italic)
\string<\glshex 1D705% lower case kappa (maths italic)
\string=\glshex 1D718% lower case kappa variant (maths italic)
\string<\glshex 1D706% lower case lambda (maths italic)
\string<\glshex 1D707% lower case mu (maths italic)
\string<\glshex 1D708% lower case nu (maths italic)
\string<\glshex 1D709% lower case xi (maths italic)
\string<\glshex 1D70A% lower case omicron (maths italic)
\string<\glshex 1D70B% lower case pi (maths italic)
\string=\glshex 1D71B% lower case pi variant (maths italic)
\string<\glshex 1D70C% lower case rho (maths italic)
\string=\glshex 1D71A% lower case rho variant (maths italic)
\string<\glshex 1D70D% lower case final sigma (maths italic)
\string=\glshex 1D70E% lower case sigma (maths italic)
\string<\glshex 1D70F% lower case tau (maths italic)
\string<\glshex 1D710% lower case upsilon (maths italic)
\string<\glshex 1D711% lower case phi (maths italic)
\string=\glshex 1D719% lower case phi variant (maths italic)
\string<\glshex 1D712% lower case chi (maths italic)
\string<\glshex 1D713% lower case psi (maths italic)
\string<\glshex 1D714% lower case omega (maths italic)
}
\newcommand*{\glxstrMathGreekIrules}{%
\glxstrMathItalicAlpha
\string;\glxstrUpAlpha
\string<\glxstrMathItalicBeta
\string;\glxstrUpBeta
\string<\glxstrMathItalicGamma
\string;\glxstrUpGamma
\string<\glxstrMathItalicDelta
\string;\glxstrUpDelta
\string<\glxstrMathItalicEpsilon
\string;\glxstrUpEpsilon
\string<\glxstrUpDigamma
\string<\glxstrMathItalicZeta
\string;\glxstrUpZeta
\string<\glxstrMathItalicEta

```

```

\string;\glxtrUpEta
\string<\glxtrMathItalicTheta
\string;\glxtrUpTheta
\string<\glxtrMathItalicIota
\string;\glxtrUpIota
\string<\glxtrMathItalicKappa
\string;\glxtrUpKappa
\string<\glxtrMathItalicLambda
\string;\glxtrUpLambda
\string<\glxtrMathItalicMu
\string;\glxtrUpMu
\string<\glxtrMathItalicNu
\string;\glxtrUpNu
\string<\glxtrMathItalicXi
\string;\glxtrUpXi
\string<\glxtrMathItalicOmicron
\string;\glxtrUpOmicron
\string<\glxtrMathItalicPi
\string;\glxtrUpPi
\string<\glxtrMathItalicRho
\string;\glxtrUpRho
\string<\glxtrMathItalicSigma
\string;\glxtrUpSigma
\string<\glxtrMathItalicTau
\string;\glxtrUpTau
\string<\glxtrMathItalicUpsilon
\string;\glxtrUpUpsilon
\string<\glxtrMathItalicPhi
\string;\glxtrUpPhi
\string<\glxtrMathItalicChi
\string;\glxtrUpChi
\string<\glxtrMathItalicPsi
\string;\glxtrUpPsi
\string<\glxtrMathItalicOmega
\string;\glxtrUpOmega
}
\newcommand*{\glxtrMathGreekIIrules}{%
\glxtrMathItalicAlpha
\string;\glxtrUpAlpha
\string<\glxtrMathItalicBeta
\string;\glxtrUpBeta
\string<\glxtrMathItalicGamma
\string;\glxtrUpGamma
\string<\glxtrMathItalicDelta
\string;\glxtrUpDelta
\string<\glxtrMathItalicEpsilon
\string;\glxtrUpEpsilon
\string<\glxtrMathItalicZeta
\string;\glxtrUpZeta
\string<\glxtrMathItalicEta

```

```

\string;\glxtrUpEta
\string<\glxtrMathItalicTheta
\string;\glxtrUpTheta
\string<\glxtrMathItalicIota
\string;\glxtrUpIota
\string<\glxtrMathItalicKappa
\string;\glxtrUpKappa
\string<\glxtrMathItalicLambda
\string;\glxtrUpLambda
\string<\glxtrMathItalicMu
\string;\glxtrUpMu
\string<\glxtrMathItalicNu
\string;\glxtrUpNu
\string<\glxtrMathItalicXi
\string;\glxtrUpXi
\string<\glxtrMathItalicOmicron
\string;\glxtrUpOmicron
\string<\glxtrMathItalicPi
\string;\glxtrUpPi
\string<\glxtrMathItalicRho
\string;\glxtrUpRho
\string<\glxtrMathItalicSigma
\string;\glxtrUpSigma
\string<\glxtrMathItalicTau
\string;\glxtrUpTau
\string<\glxtrMathItalicUpsilon
\string;\glxtrUpUpsilon
\string<\glxtrMathItalicPhi
\string;\glxtrUpPhi
\string<\glxtrMathItalicChi
\string;\glxtrUpChi
\string<\glxtrMathItalicPsi
\string;\glxtrUpPsi
\string<\glxtrMathItalicOmega
\string;\glxtrUpOmega
}
\newcommand*{\glxtrUpAlpha}{%
\glshex 03B1,% lower case alpha
\glshex 0391% upper case alpha
}
\newcommand*{\glxtrUpBeta}{%
\glshex 03B2,% lower case beta
\glshex 0392% upper case beta
}
\newcommand*{\glxtrUpGamma}{%
\glshex 03B3,% lower case gamma
\glshex 0393% upper case gamma
}
\newcommand*{\glxtrUpDelta}{%
\glshex 03B4,% lower case delta

```

```

\glshex 0394% upper case delta
}
\newcommand*{\glxtrUpEpsilon}{%
\glshex 03B5% lower case epsilon
\string=\glshex 03F5,% lower case epsilon variant
\glshex 0395% upper case epsilon
}
\newcommand*{\glxtrUpDigamma}{%
\glshex 03DD,% lower case digamma
\glshex 03DC% upper case digamma
}
\newcommand*{\glxtrUpZeta}{%
\glshex 03B6,% lower case zeta
\glshex 0396% upper case zeta
}
\newcommand*{\glxtrUpEta}{%
\glshex 03B7,% lower case eta
\glshex 0397% upper case eta
}
\newcommand*{\glxtrUpTheta}{%
\glshex 03B8% lower case theta
\string=\glshex 03D1,% lower case theta variant
\glshex 0398% upper case theta
}
\newcommand*{\glxtrUpIota}{%
\glshex 03B9,% lower case iota
\glshex 0399% upper case iota
}
\newcommand*{\glxtrUpKappa}{%
\glshex 03BA% lower case kappa
\string=\glshex 03F0,% lower case kappa variant
\glshex 039A% upper case kappa
}
\newcommand*{\glxtrUpLambda}{%
\glshex 03BB,% lower lambda
\glshex 039B% upper case lambda
}
\newcommand*{\glxtrUpMu}{%
\glshex 03BC,% lower case mu
\glshex 039C% upper case mu
}
\newcommand*{\glxtrUpNu}{%
\glshex 03BD,% lower case nu
\glshex 039D% upper case nu
}
\newcommand*{\glxtrUpXi}{%
\glshex 03BE,% lower case xi
\glshex 039E% upper case xi
}
\newcommand*{\glxtrUpOmicron}{%

```

```

\glshex 03BF,% lower case omicron
\glshex 039F% upper case omicron
}
\newcommand*{\glxtrUpPi}{%
\glshex 03C0% lower case pi
\string=\glshex 03D6,% lower case pi variant
\glshex 03A0% upper case pi
}
\newcommand*{\glxtrUpRho}{%
\glshex 03C1% lower case rho
\string=\glshex 03F1,% lower case rho variant
\glshex 03A1% upper case rho
}
\newcommand*{\glxtrUpSigma}{%
\glshex 03C2% lower case sigma
\string=\glshex 03C3,% lower case sigma
\glshex 03A3% upper case sigma
}
\newcommand*{\glxtrUpTau}{%
\glshex 03C4,% lower case tau
\glshex 03A4% upper case tau
}
\newcommand*{\glxtrUpUpsilon}{%
\glshex 03C5,% lower case upsilon
\glshex 03A5% upper case upsilon
}
\newcommand*{\glxtrUpPhi}{%
\glshex 03C6% lower case phi
\string=\glshex 03D5,% lower case phi variant
\glshex 03A6% upper case phi
}
\newcommand*{\glxtrUpChi}{%
\glshex 03C7,% lower case chi
\glshex 03A7% upper case chi
}
\newcommand*{\glxtrUpPsi}{%
\glshex 03C8,% lower case psi
\glshex 03A8% upper case psi
}
\newcommand*{\glxtrUpOmega}{%
\glshex 03C9,% lower case omega
\glshex 03A9% upper case omega
}
\newcommand*{\glxtrMathItalicAlpha}{%
\glshex 1D6FC,% lower case alpha (maths italic)
\glshex 1D6E2% upper case alpha (maths italic)
}
\newcommand*{\glxtrMathItalicBeta}{%
\glshex 1D6FD,% lower case beta (maths italic)
\glshex 1D6E3% upper case beta (maths italic)
}

```



```

}
\newcommand*{\glstrMathItalicGamma}{%
\glshex 1D6FE,% lower case gamma (maths italic)
\glshex 1D6E4% upper case gamma (maths italic)
}
\newcommand*{\glstrMathItalicDelta}{%
\glshex 1D6FF,% lower case delta (maths italic)
\glshex 1D6E5% upper case delta (maths italic)
}
\newcommand*{\glstrMathItalicEpsilon}{%
\glshex 1D700% lower case epsilon (maths italic)
\string=\glshex 1D716,% lower case epsilon variant (maths italic)
\glshex 1D6E6% upper case epsilon (maths italic)
}
\newcommand*{\glstrMathItalicZeta}{%
\glshex 1D701,% lower case zeta (maths italic)
\glshex 1D6E7% upper case zeta (maths italic)
}
\newcommand*{\glstrMathItalicEta}{%
\glshex 1D702,% lower case eta (maths italic)
\glshex 1D6E8% upper case eta (maths italic)
}
\newcommand*{\glstrMathItalicTheta}{%
\glshex 1D703% lower case theta (maths italic)
\string=\glshex 1D717,% lower case theta variant (maths italic)
\glshex 1D6E9% upper case theta (maths italic)
\string=\glshex 1D6F3% upper case theta variant (maths italic)
}
\newcommand*{\glstrMathItalicIota}{%
\glshex 1D704,% lower case iota (maths italic)
\glshex 1D6EA% upper case iota (maths italic)
}
\newcommand*{\glstrMathItalicKappa}{%
\glshex 1D705% lower case kappa (maths italic)
\string=\glshex 1D718,% lower case kappa variant (maths italic)
\glshex 1D6EB% upper case kappa (maths italic)
}
\newcommand*{\glstrMathItalicLambda}{%
\glshex 1D706,% lower case lambda (maths italic)
\glshex 1D6EC% upper case lambda (maths italic)
}
\newcommand*{\glstrMathItalicMu}{%
\glshex 1D707,% lower case mu (maths italic)
\glshex 1D6ED% upper case mu (maths italic)
}
\newcommand*{\glstrMathItalicNu}{%
\glshex 1D708,% lower case nu (maths italic)
\glshex 1D6EE% upper case nu (maths italic)
}
\newcommand*{\glstrMathItalicXi}{%

```

```

\glshex 1D709,% lower case xi (maths italic)
\glshex 1D6EF% upper case xi (maths italic)
}
\newcommand*{\glsxtrMathItalicOmicron}{%
\glshex 1D70A,% lower case omicron (maths italic)
\glshex 1D6F0% upper case omicron (maths italic)
}
\newcommand*{\glsxtrMathItalicPi}{%
\glshex 1D70B% lower case pi (maths italic)
\string=\glshex 1D71B,% lower case pi variant (maths italic)
\glshex 1D6F1% upper case pi (maths italic)
}
\newcommand*{\glsxtrMathItalicRho}{%
\glshex 1D70C% lower case rho (maths italic)
\string=\glshex 1D71A,% lower case rho variant (maths italic)
\glshex 1D6F2% upper case rho (maths italic)
}
\newcommand*{\glsxtrMathItalicSigma}{%
\glshex 1D70D% lower case final sigma (maths italic)
\string=\glshex 1D70E,% lower case sigma (maths italic)
\glshex 1D6F4% upper case sigma (maths italic)
}
\newcommand*{\glsxtrMathItalicTau}{%
\glshex 1D70F,% lower case tau (maths italic)
\glshex 1D6F5% upper case tau (maths italic)
}
\newcommand*{\glsxtrMathItalicUpsilon}{%
\glshex 1D710,% lower case upsilon (maths italic)
\glshex 1D6F6% upper case upsilon (maths italic)
}
\newcommand*{\glsxtrMathItalicPhi}{%
\glshex 1D711% lower case phi (maths italic)
\string=\glshex 1D719,% lower case phi variant (maths italic)
\glshex 1D6F7% upper case phi (maths italic)
}
\newcommand*{\glsxtrMathItalicChi}{%
\glshex 1D712,% lower case chi (maths italic)
\glshex 1D6F8% upper case chi (maths italic)
}
\newcommand*{\glsxtrMathItalicPsi}{%
\glshex 1D713,% lower case psi (maths italic)
\glshex 1D6F9% upper case psi (maths italic)
}
\newcommand*{\glsxtrMathItalicOmega}{%
\glshex 1D714,% lower case omega (maths italic)
\glshex 1D6FA% upper case omega (maths italic)
}
\newcommand*{\glsxtrMathItalicPartial}{%
\glshex 1D715% partial differential (maths italic)
}

```

```

\newcommand*{\glxtrMathItalicNabla}{%
  \glshex 1D6FB% nabla (maths italic)
}
\newcommand*{\glxtrDigitrules}{%
  0\string=\glshex 2080\string=\glshex 2070
  \string<\glshex 2081\string=\glshex 00B9
  \string<\glshex 2082\string=\glshex 00B2
  \string<\glshex 2083\string=\glshex 00B3
  \string<\glshex 2084\string=\glshex 2074
  \string<\glshex 2085\string=\glshex 2075
  \string<\glshex 2086\string=\glshex 2076
  \string<\glshex 2087\string=\glshex 2077
  \string<\glshex 2088\string=\glshex 2078
  \string<\glshex 2089\string=\glshex 2079
}
\newcommand*{\glxtrBasicDigitrules}{%
  0\string<\glshex 2080\string<\glshex 2070
  \string<\glshex 2081\string<\glshex 00B9
  \string<\glshex 2082\string<\glshex 00B2
  \string<\glshex 2083\string<\glshex 00B3
  \string<\glshex 2084\string<\glshex 2074
  \string<\glshex 2085\string<\glshex 2075
  \string<\glshex 2086\string<\glshex 2076
  \string<\glshex 2087\string<\glshex 2077
  \string<\glshex 2088\string<\glshex 2078
  \string<\glshex 2089\string<\glshex 2079
}
\newcommand*{\glxtrSubScriptDigitrules}{%
  \glshex 2080% subscript 0
  \string<\glshex 2081% subscript 1
  \string<\glshex 2082% subscript 2
  \string<\glshex 2083% subscript 3
  \string<\glshex 2084% subscript 4
  \string<\glshex 2085% subscript 5
  \string<\glshex 2086% subscript 6
  \string<\glshex 2087% subscript 7
  \string<\glshex 2088% subscript 8
  \string<\glshex 2089% subscript 9
}
\newcommand*{\glxtrSuperScriptDigitrules}{%
  \glshex 2070% superscript 0
  \string<\glshex 00B9% superscript 1
  \string<\glshex 00B2% superscript 2
  \string<\glshex 00B3% superscript 3
  \string<\glshex 2074% superscript 4
  \string<\glshex 2075% superscript 5
  \string<\glshex 2076% superscript 6
  \string<\glshex 2077% superscript 7
  \string<\glshex 2078% superscript 8
  \string<\glshex 2079% superscript 9
}
\newcommand*{\glxtrFractionrules}{%
  \glshex 215F% fraction numerator one (1/)
  \string<\glshex 2189% zero thirds (0/3 = 0)
  \string<\glshex 2152% one tenth (1/10 = 0.1)
  \string<\glshex 2151% one ninth (1/9 ~ 0.111)
  \string<\glshex 215B% one eighth (1/8 = 0.125)
  \string<\glshex 2150% one seventh (1/7 ~ 0.143)
}

```

```

\string<\glshex 2159% one sixth ( $1/6 \sim 0.167$ )
\string<\glshex 2155% one fifth ( $1/5 = 0.2$ )
\string<\glshex 00BC% one quarter ( $1/4 = 0.25$ )
\string<\glshex 2153% one third ( $1/3 \sim 0.333$ )
\string<\glshex 215C% three eighths ( $3/8 = 0.375$ )
\string<\glshex 2156% two fifths ( $2/5 = 0.4$ )
\string<\glshex 00BD% one half ( $1/2 = 0.5$ )
\string<\glshex 2157% three fifths ( $3/5 = 0.6$ )
\string<\glshex 215D% five eighths ( $5/8 = 0.625$ )
\string<\glshex 2154% two thirds ( $2/3 \sim 0.667$ )
\string<\glshex 00BE% three quarters ( $3/4 = 0.75$ )
\string<\glshex 2158% four fifths ( $4/5 = 0.8$ )
\string<\glshex 215A% five sixths ( $5/6 \sim 0.833$ )
\string<\glshex 215E% seven eighths ( $7/8 = 0.875$ )
}
\renewcommand{\@glxtrdialecthook}{%
  \ifundef\CurrentTrackedScript
  {%
    \TrackLangIfHasDefaultScript{\CurrentTrackedLanguage}%
    {%
      \edef\CurrentTrackedScript{%
        \TrackLangGetDefaultScript\CurrentTrackedLanguage}%
      }%
    }%
  }%
  {}%
\ifdef\CurrentTrackedScript
{%
  \let\gls@orgTrackLangRequireDialectPrefix\TrackLangRequireDialectPrefix
  \def\TrackLangRequireDialectPrefix{glossariesxtr-}%
  \let\CurrentTrackedTag\CurrentTrackedScript
  \IfFileExists{\TrackLangRequireDialectPrefix\CurrentTrackedTag.ldf}
  {\RequireGlossariesExtraLang{\CurrentTrackedTag}}%
  {}%
  \let\TrackLangRequireDialectPrefix\gls@orgTrackLangRequireDialectPrefix
}%
{}%
}
\ifdef\glxtr@loaddialect
{%
  \@ifpackageloaded{tracklang}
  {%
    \AnyTrackedLanguages
    {%
      \ForEachTrackedDialect{\this@dialect}{\glxtr@loaddialect}%
    }%
  }%
}
{}
}

```

{}

9.3 Rollback v1.48 (glossaries-extra-stylemods-2021-11-22.sty)

Version 1.48 preserved for rollback.

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{glossaries-extra-stylemods}[2021/11/22 v1.48 (NLCT)]
\newcommand*{\@glstr@loadstyles}{}
\DeclareOption{all}{%
  \appto\@glstr@loadstyles{%
    \RequirePackage{glossary-inline}%
    \RequirePackage{glossary-list}%
    \RequirePackage{glossary-tree}%
    \RequirePackage{glossary-mcols}%
    \RequirePackage{glossary-long}%
    \RequirePackage{glossary-longragged}%
    \RequirePackage{glossary-longbooktabs}%
    \RequirePackage{glossary-super}%
    \RequirePackage{glossary-superragged}%
    \RequirePackage{glossary-bookindex}[=v1.48]%
    \RequirePackage{glossary-longextra}[=v1.48]%
    \RequirePackage{glossary-topic}[=v1.48]%
  }
}
\DeclareOption*{%
  \IfFileExists{glossary-\CurrentOption.sty}
  {\eappto\@glstr@loadstyles{%
    \noexpand\RequirePackage{glossary-\CurrentOption}}}%
  {%
    \PackageError{glossaries-extra-styles}%
      {Unknown option ‘\CurrentOption’}{}%
  }%
}
\ProcessOptions
\@glstr@loadstyles
\providecommand*{\glstr@prelocation}{\space}
\providecommand{\renewglossarystyle}[2]{%
  \ifcsundef{@glstyle@#1}%
  {%
    \PackageError{glossaries-extra}{Glossary style ‘#1’ isn’t already defined}{}%
  }%
  {%
    \csdef{@glstyle@#1}{#2}%
  }%
}
\ifdef{\@glstyle@listdotted}
{%
  \renewglossarystyle{listdotted}{%
```

```

\setglossarystyle{list}%
\renewcommand*{\glossentry}[2]{%
  \item[]\makebox[\glslistdottedwidth][l]{%
    \glsentryitem{##1}%
    \glstarget{##1}{\glossentryname{##1}}%
    \unskip\leaders\hbox to 2.9mm{\hss.}\hfill\strut}%
    \glossentrydesc{##1}\glspostdescription}%
\renewcommand*{\subglossentry}[3]{%
  \item[]\makebox[\glslistdottedwidth][l]{%
    \glssubentryitem{##2}%
    \glstarget{##2}{\glossentryname{##2}}%
    \unskip\leaders\hbox to 2.9mm{\hss.}\hfill\strut}%
    \glossentrydesc{##2}\glspostdescription}%
  }
}
{%
}
\ifdef{\@glsstyle@list}
{%
  \newcommand{\glslistprelocation}{\glstxtrprelocation}
  \newcommand{\glslistchildprelocation}{\glslistprelocation}
  \newcommand{\glslistchildpostlocation}{.}
  \newcommand{\glslistdesc}[1]{\glossentrydesc{#1}\glspostdescription}
  \newcommand{\glslistgroupskip}{\nobreak\indexspace\nobreak}
  \newcommand{\glslistitem}[1]{%
    \item[\glsentryitem{#1}]%
    \glstarget{#1}{\glossentryname{#1}}}%
  }
\providecommand{\glslistinit}{%
  \ifdef\GetTitleStringDisableCommands
  {%
    \GetTitleStringSetup{expand}%
    \GetTitleStringDisableCommands{%
      \let\glsentryitem\@gobble
      \let\glstarget\@secondoftwo
      \let\glossentryname\glslistexpandedname
      \let\glslistgroupheaderfmt\@firstofone
      \let\glsgetgrouptitle\@firstofone
      \let\glsnavhypertarget\@secondoftwo
      \let\glsnavigation\relax
    }%
  }%
  {}%
}
\providecommand{\glslistexpandedname}[1]{%
  \ifcsname glo@\glsdetoklabel{#1}@name\endcsname
  \expandafter\expandonce\csname glo@\glsdetoklabel{#1}@name\expandafter\endcsname
  \fi
}
\renewglossarystyle{list}{%

```

```

\renewenvironment{theglossary}%
  {\glslistinit\begin{description}}{\end{description}}%
\renewcommand*{\glossaryheader}{}%
\renewcommand*{\glsgroupheading}[1]{}%
\renewcommand*{\glossentry}[2]{%
  \glslistitem{##1}\glslistdesc{##1}\glslistprelocation ##2}%
\renewcommand*{\subglossentry}[3]{%
  \glssubentryitem{##2}%
  \glstarget{##2}{\strut}\space
  \glslistdesc{##2}%
  \glslistchildprelocation ##3\glslistchildpostlocation}%
\renewcommand*{\glsgroupskip}{\ifglsnogroupskip\else\glslistgroupskip\fi}%
}
{}
\ifdef{\@glsstyle@altlist}
{%
  \newcommand{\glsaltlistitem}[1]{%
    \glslistitem{##1}%
    \mbox{}\par\nobreak\@afterheading
  }
  \renewglossarystyle{altlist}{%
    \setglossarystyle{list}%
    \renewcommand*{\glossentry}[2]{%
      \glsaltlistitem{##1}%
      \glslistdesc{##1}\glslistprelocation ##2}%
    \renewcommand{\subglossentry}[3]{%
      \par
      \glssubentryitem{##2}%
      \glstarget{##2}{\strut}\glslistdesc{##2}%
      \glslistchildprelocation ##3}%
    }
  }
{}
\ifdef{\@glsstyle@listgroup}
{%
  \newcommand{\glslistgroupheaderitem}[2]{\item[{##2}]}
  \newcommand{\glslistgroupafterheader}{%
    \mbox{}\par\nobreak\@afterheading
  }
  \renewglossarystyle{listgroup}{%
    \setglossarystyle{list}%
    \renewcommand*{\glsgroupheading}[1]{%
      \glslistgroupheaderitem{##1}{\glslistgroupheaderfmt{\glssetgrouptitle{##1}}}%
      \glslistgroupafterheader
    }%
  }
}
{}
\ifdef{\@glsstyle@listhypergroup}

```

```

{%
  \renewglossarystyle{listhypergroup}{%
    \setglossarystyle{list}%
    \renewcommand*{\glossaryheader}{%
      \glslistnavigationitem{\glsnavigation}}%
    \renewcommand*{\glsgroupheading}[1]{%
      \glslistgroupheaderitem{##1}{\glslistgroupheaderfmt
        {\glsnavhypertarget{##1}{\glsgetgrouptitle{##1}}}}%
      \glslistgroupafterheader
    }%
  }
}
{}
\ifdef{\@glsstyle@altlistgroup}
{%
  \renewglossarystyle{altlistgroup}{%
    \setglossarystyle{altlist}%
    \renewcommand*{\glsgroupheading}[1]{%
      \glslistgroupheaderitem{##1}%
      {\glslistgroupheaderfmt{\glsgetgrouptitle{##1}}}%
      \glslistgroupafterheader
    }%
  }
}
{}
\ifdef{\@glsstyle@altlisthypergroup}
{%
  \renewglossarystyle{altlisthypergroup}{%
    \setglossarystyle{altlist}%
    \renewcommand*{\glossaryheader}{%
      \glslistnavigationitem{\glsnavigation}}%
    \renewcommand*{\glsgroupheading}[1]{%
      \glslistgroupheaderitem{##1}{\glslistgroupheaderfmt
        {\glsnavhypertarget{##1}{\glsgetgrouptitle{##1}}}}%
      \glslistgroupafterheader
    }%
  }
}
{}
\ifcsdef{@glsstyle@long}
{%
  \renewglossarystyle{long}{%
    \renewenvironment{theglossary}%
      {\begin{longtable}{lp{\glsdescwidth}}%
      {\end{longtable}}%
    \renewcommand*{\glossaryheader}{}%
    \renewcommand*{\glsgroupheading}[1]{}%
    \renewcommand{\glossentry}[2]{%
      \glsentryitem{##1}\glstarget{##1}{\glossentryname{##1}} &
      \glossentrydesc{##1}\glspostdescription
    }
  }
}

```



```

\glstrprelocation ##2\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
  &
  \glssubentryitem{##2}%
  \glstarget{##2}{\strut}\glossentrydesc{##2}\glspostdescription
  \glstrprelocation ##3\tabularnewline
}%
\ifglsnogroupskip
  \renewcommand*{\glsgroupskip}{}%
\else
  \renewcommand*{\glsgroupskip}{& \tabularnewline}%
\fi
}
}
{}
\ifcsdef{@glstyle@long3col}
{%
  \renewglossarystyle{long3col}{%
    \renewenvironment{theglossary}%
      {\begin{longtable}{lp{\glstdescwidth}p{\glspagelistwidth}}}%
      {\end{longtable}}%
    \renewcommand*{\glossaryheader}{}%
    \renewcommand*{\glsgroupheading}[1]{}%
    \renewcommand{\glossentry}[2]{%
      \glssubentryitem{##1}\glstarget{##1}{\glossentryname{##1}} &
      \glossentrydesc{##1}\glspostdescription & ##2\tabularnewline
    }%
    \renewcommand{\subglossentry}[3]{%
      &
      \glssubentryitem{##2}%
      \glstarget{##2}{\strut}\glossentrydesc{##2}\glspostdescription &
      ##3\tabularnewline
    }%
    \ifglsnogroupskip
      \renewcommand*{\glsgroupskip}{}%
    \else
      \renewcommand*{\glsgroupskip}{& \tabularnewline}%
    \fi
  }
}
{}
\ifcsdef{@glstyle@long4col}
{%
  \renewglossarystyle{long4col}{%
    \renewenvironment{theglossary}%
      {\begin{longtable}{llll}}%
      {\end{longtable}}%
    \renewcommand*{\glossaryheader}{}%
    \renewcommand*{\glsgroupheading}[1]{}%
  }
}

```

```

\renewcommand{\glossentry}[2]{%
  \glentryitem{##1}\glstarget{##1}{\glossentryname{##1}} &
  \glossentrydesc{##1}\glspostdescription &
  \glossentrysymbol{##1} &
  ##2\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
  &
  \glssubentryitem{##2}%
  \glstarget{##2}{\strut}\glossentrydesc{##2}\glspostdescription &
  \glossentrysymbol{##2} & ##3\tabularnewline
}%
\ifglsgroupskip
  \renewcommand*{\glsgroupskip}{}%
\else
  \renewcommand*{\glsgroupskip}{& & \tabularnewline}%
\fi
}
}
{}
\ifcsdef{@glstyle@longragged}
{%
  \renewglossarystyle{longragged}{%
    \renewenvironment{theglossary}%
      {\begin{longtable}{l>{\raggedright}p{\glstdescwidth}}}%
      {\end{longtable}}%
    \renewcommand*{\glossaryheader}{}%
    \renewcommand*{\glsgroupheading}[1]{}%
    \renewcommand{\glossentry}[2]{%
      \glentryitem{##1}\glstarget{##1}{\glossentryname{##1}} &
      \glossentrydesc{##1}\glspostdescription\glstrprelocation ##2%
      \tabularnewline
    }%
    \renewcommand{\subglossentry}[3]{%
      &
      \glssubentryitem{##2}%
      \glstarget{##2}{\strut}\glossentrydesc{##2}%
      \glspostdescription\glstrprelocation ##3%
      \tabularnewline
    }%
    \ifglsgroupskip
      \renewcommand*{\glsgroupskip}{}%
    \else
      \renewcommand*{\glsgroupskip}{& \tabularnewline}%
    \fi
  }
}
{}
\ifcsdef{@glstyle@longragged3col}
{%

```

```

\renewglossarystyle{longragged3col}{%
  \renewenvironment{theglossary}%
    {\begin{longtable}{l>{\raggedright}p{\glstdescwidth}%
      >{\raggedright}p{\glspagelistwidth}}}%
    {\end{longtable}}%
  \renewcommand*{\glossaryheader}{}%
  \renewcommand*{\glsgroupheading}[1]{}%
  \renewcommand{\glossentry}[2]{%
    \glentryitem{##1}\glstarget{##1}{\glossentryname{##1}} &
    \glossentrydesc{##1}\glspostdescription & ##2\tabularnewline
  }%
  \renewcommand{\subglossentry}[3]{%
    &
    \glssubentryitem{##2}%
    \glstarget{##2}{\strut}\glossentrydesc{##2}\glspostdescription &
    ##3\tabularnewline
  }%
  \ifglsgroupskip
    \renewcommand*{\glsgroupskip}{}%
  \else
    \renewcommand*{\glsgroupskip}{& &\tabularnewline}%
  \fi
}
{}
\ifcsdef{@glstyle@altlongragged4col}
{%
  \renewglossarystyle{altlongragged4col}{%
    \renewenvironment{theglossary}%
      {\begin{longtable}{l>{\raggedright}p{\glstdescwidth}l%
        >{\raggedright}p{\glspagelistwidth}}}%
      {\end{longtable}}%
    \renewcommand*{\glossaryheader}{}%
    \renewcommand*{\glsgroupheading}[1]{}%
    \renewcommand{\glossentry}[2]{%
      \glentryitem{##1}\glstarget{##1}{\glossentryname{##1}} &
      \glossentrydesc{##1}\glspostdescription & \glossentrysymbol{##1} &
      ##2\tabularnewline
    }%
    \renewcommand{\subglossentry}[3]{%
      &
      \glssubentryitem{##2}%
      \glstarget{##2}{\strut}\glossentrydesc{##2}\glspostdescription &
      \glossentrysymbol{##2} & ##3\tabularnewline
    }%
    \ifglsgroupskip
      \renewcommand*{\glsgroupskip}{}%
    \else
      \renewcommand*{\glsgroupskip}{& & &\tabularnewline}%
    \fi
  }
}

```

```

    }
  }
  {}
  \ifcsdef{@glsstyle@super}
  {%
    \renewglossarystyle{super}{%
      \renewenvironment{theglossary}%
        {\tablehead{}\tabletail{}}%
        \begin{supertabular}{lp{\glsdescwidth}}}%
        {\end{supertabular}}%
      \renewcommand*{\glossaryheader}{}%
      \renewcommand*{\glsgroupheading}[1]{}%
      \renewcommand{\glossentry}[2]{%
        \glsentryitem{##1}\glstarget{##1}{\glossentryname{##1}} &
        \glossentrydesc{##1}\glspostdescription
        \glsxtrprelocation ##2\tabularnewline
      }%
      \renewcommand{\subglossentry}[3]{%
        &
        \glssubentryitem{##2}%
        \glstarget{##2}{\strut}\glossentrydesc{##2}\glspostdescription
        \glsxtrprelocation ##3\tabularnewline
      }%
      \ifglsgroupskip
        \renewcommand*{\glsgroupskip}{}%
      \else
        \renewcommand*{\glsgroupskip}{& \tabularnewline}%
      \fi
    }
  }
  {}
  \ifcsdef{@glsstyle@super3col}
  {%
    \renewglossarystyle{super3col}{%
      \renewenvironment{theglossary}%
        {\tablehead{}\tabletail{}}%
        \begin{supertabular}{lp{\glsdescwidth}p{\glspagelistwidth}}}%
        {\end{supertabular}}%
      \renewcommand*{\glossaryheader}{}%
      \renewcommand*{\glsgroupheading}[1]{}%
      \renewcommand{\glossentry}[2]{%
        \glsentryitem{##1}\glstarget{##1}{\glossentryname{##1}} &
        \glossentrydesc{##1}\glspostdescription & ##2\tabularnewline
      }%
      \renewcommand{\subglossentry}[3]{%
        &
        \glssubentryitem{##2}%
        \glstarget{##2}{\strut}\glossentrydesc{##2}\glspostdescription &
        ##3\tabularnewline
      }%
    }
  }

```

```

\ifglsgroupskip
\renewcommand*{\glsgroupskip}{}%
\else
\renewcommand*{\glsgroupskip}{ & &\tabularnewline}%
\fi
}
}
{}
\ifcsdef{@glstyle@super4col}
{%
\renewglossarystyle{super4col}{%
\renewenvironment{theglossary}%
{\tablehead{}\tabletail{}}%
\begin{supertabular}{1111}{%
\end{supertabular}}%
\renewcommand*{\glossaryheader}{}%
\renewcommand*{\glsgroupheading}[1]{}%
\renewcommand{\glossentry}[2]{%
\glentryitem{##1}\glstarget{##1}{\glossentryname{##1}} &
\glossentrydesc{##1}\glspostdescription &
\glossentrysymbol{##1} & ##2\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
&
\glssubentryitem{##2}%
\glstarget{##2}{\strut}\glossentrydesc{##2}\glspostdescription &
\glossentrysymbol{##2} & ##3\tabularnewline
}%
\ifglsgroupskip
\renewcommand*{\glsgroupskip}{}%
\else
\renewcommand*{\glsgroupskip}{& &\tabularnewline}%
\fi
}
}
{}
\ifcsdef{@glstyle@superragged}
{%
\renewglossarystyle{superragged}{%
\renewenvironment{theglossary}%
{\tablehead{}\tabletail{}}%
\begin{supertabular}{1>\raggedright}p{\glstylewidth}{%
\end{supertabular}}%
\renewcommand*{\glossaryheader}{}%
\renewcommand*{\glsgroupheading}[1]{}%
\renewcommand{\glossentry}[2]{%
\glentryitem{##1}\glstarget{##1}{\glossentryname{##1}} &
\glossentrydesc{##1}\glspostdescription\glstrprelocation ##2%
\tabularnewline
}%

```

```

\renewcommand{\subglossentry}[3]{%
  &
  \glssubentryitem{##2}%
  \glstarget{##2}{\strut}\glossentrydesc{##2}\glspostdescription
  \glstrprelocation ##3%
  \tabularnewline
}%
\ifglsgroupskip
  \renewcommand*{\glsgroupskip}{}%
\else
  \renewcommand*{\glsgroupskip}{& \tabularnewline}%
\fi
}
}
{}
\ifcsdef{@glstyle@superragged3col}
{%
  \renewglossarystyle{superragged3col}{%
    \renewenvironment{theglossary}%
      {\tablehead{}\tabletail{}}%
      \begin{supertabular}{l>{\raggedright}p{\glswidth}%
        >{\raggedright}p{\glspagelistwidth}}}%
      {\end{supertabular}}%
    \renewcommand*{\glossaryheader}{}%
    \renewcommand*{\glsgroupheading}[1]{}%
    \renewcommand{\glossentry}[2]{%
      \glssubentryitem{##1}\glstarget{##1}{\glossentryname{##1}} &
      \glossentrydesc{##1}\glspostdescription &
      ##2\tabularnewline
    }%
    \renewcommand{\subglossentry}[3]{%
      &
      \glssubentryitem{##2}%
      \glstarget{##2}{\strut}\glossentrydesc{##2}\glspostdescription &
      ##3\tabularnewline
    }%
    \ifglsgroupskip
      \renewcommand*{\glsgroupskip}{}%
    \else
      \renewcommand*{\glsgroupskip}{& \tabularnewline}%
    \fi
  }
}
{}
\ifcsdef{@glstyle@altsuperragged4col}
{%
  \renewglossarystyle{altsuperragged4col}{%
    \renewenvironment{theglossary}%
      {\tablehead{}\tabletail{}}%
      \begin{supertabular}{l>{\raggedright}p{\glswidth}l%

```

```

>{\raggedright}p{\glspagelistwidth}}}%
{\end{supertabular}}}%
\renewcommand*{\glossaryheader}{}%
\renewcommand{\glossentry}[2]{%
  \glssentryitem{##1}\glstarget{##1}{\glossentryname{##1}} &
  \glossentrydesc{##1}\glspostdescription &
  \glossentrysymbol{##1} & ##2\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
  &
  \glssubentryitem{##2}%
  \glstarget{##2}{\strut}\glossentrydesc{##2}\glspostdescription &
  \glossentrysymbol{##2} & ##3\tabularnewline
}%
\ifglsnogroupskip
  \renewcommand*{\glsgroupskip}{}%
\else
  \renewcommand*{\glsgroupskip}{& & \tabularnewline}%
\fi
}
}
{}
\ifdef{\@glstyle@inline}
{%
  \renewcommand*{\glspostinline}{.\spacefactor\sfcode'\.}
  \renewcommand*{\glsinlinedescformat}[3]{%
    \space#1\glsxtrpostdescription}
  \renewcommand*{\glsinlinesubdescformat}[3]{%
    #1\glsxtrpostdescription}
}
{}
\ifdef\glstreenamefmt
{
  \newcommand{\glstreedefaultnamefmt}[1]{\textbf{#1}}
  \renewcommand{\glstreenamefmt}[1]{\glstreedefaultnamefmt{#1}}
  \def\glstreegroupheaderfmt#1{\glstreedefaultnamefmt{#1}}
  \def\glstreenavigationfmt#1{\glstreedefaultnamefmt{#1}}
  \newcommand{\glstreePreHeader}[2]{%
}
{}
\ifdef{\@glstyle@index}
{
  \newcommand*{\glstreeprelocation}{\glsxtrprelocation}
  \newcommand*{\glstreechildprelocation}{\glstreeprelocation}
  \newcommand{\glstreegroupskip}{\indexspace}
  \newcommand{\glstreegroupheaderskip}{\nopagebreak\glstreegroupskip\nobreak}
  \renewglossarystyle{index}{%
    \renewenvironment{theglossary}%
      {\setlength{\parindent}{0pt}}%
      {\setlength{\parskip}{0pt plus 0.3pt}}%

```

```

        \let\item\glstreeitem
        \let\subitem\glstreesubitem
        \let\subsubitem\glstreesubsubitem
    }%
{\par}%
\renewcommand*{\glossaryheader}{}%
\renewcommand*{\glsgroupheading}[1]{}%
\renewcommand*{\glossentry}[2]{%
    \item\glssentryitem{##1}%
    \glstreenamefmt{\glstarget{##1}{\glossentryname{##1}}}%
    \glstreesymbol{##1}%
    \glstreeDescLoc{##1}{##2}%
}%
\renewcommand{\subglossentry}[3]{%
    \ifcase##1\relax
        \item
    \or
        \subitem
        \glssubentryitem{##2}%
    \else
        \subsubitem
    \fi
    \glstreenamefmt{\glstarget{##2}{\glossentryname{##2}}}%
    \glstreechildsymbol{##2}%
    \glstreeChildDescLoc{##2}{##3}%
}%
\renewcommand*{\glsgroupskip}{\ifglsgnোগroupskip\else\glstreegroupskip\fi}%
}
{}
\ifdef{\@glsstyle@indexgroup}
{%
    \renewglossarystyle{indexgroup}{%
        \setglossarystyle{index}%
        \renewcommand*{\glsgroupheading}[1]{%
            \glstrgetgrouptitle{##1}{\glstr@grptitle}%
            \glstreePreHeader{##1}{\glstr@grptitle}%
            \item\glstreegroupheaderfmt{\glstr@grptitle}%
            \glstreegroupheaderskip\@afterheading
        }%
    }
}
{}
\ifdef{\@glsstyle@indexhypergroup}
{%
    \renewglossarystyle{indexhypergroup}{%
        \setglossarystyle{index}%
        \renewcommand*{\glossaryheader}{%
            \item\glstreenavigationfmt{\glstr@navigation}%
            \glstreegroupheaderskip\@afterheading}%
    }
}

```



```

\renewcommand*{\glsgroupheading}[1]{%
  \glstrgetgrouptitle{##1}{\glstr@grptitle}%
  \glstreePreHeader{##1}{\glstr@grptitle}%
  \item\glstreegroupheaderfmt
    {\glshnavhypertarget{##1}{\glstr@grptitle}}%
  \glstreegroupheaderskip\@afterheading}%
}%
}
{}
\ifdef{\@glsstyle@tree}
{%
\newcommand{\glstxtrtreepredesc}{\glstreepredesc}
\newcommand{\glstxtrtreechildpredesc}{\glstreechildpredesc}
\newcommand{\glstreedesc}[1]{%
  \glstxtrtreepredesc\glossentrydesc{#1}\glspostdescription
}
\newcommand{\glstreeDescLoc}[2]{%
  \ifglshasdesc{#1}%
  {\glstreedesc{#1}\glstreeprelocation}%
  {\ifglshassymbol{#1}{\glstreeprelocation}{\glstreeNoDescSymbolPreLocation}}%
  #2%
}
\newcommand{\glstreeNoDescSymbolPreLocation}{\space}
\newcommand{\glstreesymbol}[1]{%
  \ifglshassymbol{#1}{\space(\glossentrysymbol{#1})}{}%
}%
\newcommand{\glstreechilddesc}[1]{%
  \glstxtrtreechildpredesc\glossentrydesc{#1}\glspostdescription
}%
\newcommand{\glstreeChildDescLoc}[2]{%
  \ifglshasdesc{#1}%
  {\glstreechilddesc{#1}\glstreechildprelocation}%
  {\ifglshassymbol{#1}{\glstreechildprelocation}%
    {\glstreeNoDescSymbolPreLocation}}%
  }%
  #2%
}%
\newcommand{\glstreechildsymbol}[1]{%
  \glstreesymbol{#1}%
}%
\renewglossarystyle{tree}{%
  \renewenvironment{theglossary}%
    {\setlength{\parindent}{0pt}%
     \setlength{\parskip}{0pt plus 0.3pt}}%
    {}%
  \renewcommand*{\glossaryheader}{}%
  \renewcommand*{\glsgroupheading}[1]{}%
  \renewcommand{\glossentry}[2]{%
    \hangindent0pt\relax
    \parindent0pt\relax

```

```

\glstentryitem{##1}\glstreenamefmt{\glstarget{##1}{\glossentryname{##1}}}%
\glstreesymbol{##1}%
\glstreeDescLoc{##1}{##2}\par
}%
\renewcommand{\subglossentry}[3]{%
\hangindent##1\glstreeindent\relax
\parindent##1\glstreeindent\relax
\ifnum##1=1\relax
\glssubentryitem{##2}%
\fi
\glstreenamefmt{\glstarget{##2}{\glossentryname{##2}}}%
\glstreechildsymbol{##2}%
\glstreeChildDescLoc{##2}{##3}\par
}%
\renewcommand*{\glsgroupskip}{\ifglsnogroupskip\else\glstreegroupskip\fi}%
}%
}
{}
\ifdef{\@glsstyle@treegroup}
{%
\renewglossarystyle{treegroup}{%
\setglossarystyle{tree}%
\renewcommand{\glsgroupheading}[1]{%
\glstrgetgrouptitle{##1}{\glstr@grptitle}%
\glstreePreHeader{##1}{\glstr@grptitle}%
\par\noindent\glstreegroupheaderfmt{\glstr@grptitle}%
\glstreegroupheaderskip\@afterheading}%
}
}
{}
\ifdef{\@glsstyle@treehypergroup}
{%
\renewglossarystyle{treehypergroup}{%
\setglossarystyle{tree}%
\renewcommand*{\glossaryheader}{%
\par\noindent\glstreenavigationfmt{\glsnavigation}%
\glstreegroupheaderskip\@afterheading}%
\renewcommand*{\glsgroupheading}[1]{%
\glstrgetgrouptitle{##1}{\glstr@grptitle}%
\glstreePreHeader{##1}{\glstr@grptitle}%
\par\noindent
\glstreegroupheaderfmt
{\glsnavhypertarget{##1}{\glstr@grptitle}}%
\glstreegroupheaderskip\@afterheading}%
}
}
{}
\ifdef{\@glsstyle@treenoname}
{%
\newcommand{\glstreenonamedesc}[1]{%

```

```

\glstreepredesc\glossentrydesc{#1}\glspostdescription
}%
\newcommand{\glstreenonamesymbol}[1]{%
\ifglshassymbol{#1}{\space\glossentrysymbol{#1}}{}}%
}%
\newcommand{\glstreenonameDescLoc}[2]{%
\glstreenonamedesc{#1}\glstreeprelocation#2%
}
\newcommand{\glstreenonamechilddesc}[1]{%
\glossentrydesc{#1}\glspostdescription
}%
\newcommand{\glstreenonameChildDescLoc}[2]{%
\glstreenonamechilddesc{#1}\glstreechildprelocation#2%
}
\renewglossarystyle{treenoname}{%
\renewenvironment{theglossary}%
{\setlength{\parindent}{0pt}%
\setlength{\parskip}{0pt plus 0.3pt}}%
{}%
\renewcommand*{\glossaryheader}{}%
\renewcommand*{\glsgroupheading}[1]{}%
\renewcommand{\glossentry}[2]{%
\hangindent0pt\relax
\parindent0pt\relax
\glstryitem{##1}\glstreenamefmt{\glstarget{##1}{\glossentryname{##1}}}%
\glstreenonamesymbol{##1}%
\glstreenonameDescLoc{##1}{##2}\par
}%
\renewcommand{\subglossentry}[3]{%
\hangindent##1\glstreeindent\relax
\parindent##1\glstreeindent\relax
\ifnum##1=1\relax
\glssubentryitem{##2}%
\fi
\glstarget{##2}{\strut}%
\glstreenonameChildDescLoc{##2}{##3}\par
}%
\renewcommand*{\glsgroupskip}{\ifglsnogroupskip\else\glstreegroupskip\fi}%
}
{}
\ifdef{\@glstyle@treenonamegroup}
{%
\renewglossarystyle{treenonamegroup}{%
\setglossarystyle{treenoname}%
\renewcommand{\glsgroupheading}[1]{%
\glstrgetgrouptitle{##1}{\glxtr@grptitle}%
\glstreePreHeader{##1}{\glxtr@grptitle}%
\par\noindent\glstreegroupheaderfmt{\glxtr@grptitle}%
\glstreegroupheaderskip\@afterheading
}
}

```

```

    }%
  }
}
{}
\ifdef{\@glsstyle@treenonamehypergroup}
{%
  \renewglossarystyle{treenonamehypergroup}{%
    \setglossarystyle{treenoname}%
    \renewcommand*{\glossaryheader}{%
      \par\noindent\glstreenavigationfmt{\glsnavigation}%
      \glstreegroupheaderskip\@afterheading}%
    \renewcommand*{\glsgroupheading}[1]{%
      \glstrgetgrouptitle{##1}{\glstr@grptitle}%
      \glstreePreHeader{##1}{\glstr@grptitle}%
      \par\noindent
      \glstreegroupheaderfmt{\glsnavhypertarget{##1}{\glstr@grptitle}}%
      \glstreegroupheaderskip\@afterheading}%
    }
  }
}
{}
\ifdef{\@glsstyle@alttree}
{%
  \newcommand{\glsalttreepredesc}{}
  \newcommand{\glsalttreechildpredesc}{\glsalttreepredesc}
  \newcommand{\glstralttreeSymbolDescLocation}[2]{%
    {%
      \let\par\glstrAltTreePar
      \let\glstrtreepredesc\glsalttreepredesc
      \let\glstrtreechildpredesc\glsalttreechildpredesc
      \ifglshassymbol{#1}{(\glossentrysymbol{#1})\space}{}%
      \glstreeDescLoc{#1}{#2}\par
    }%
  }
}
\newlength\glstrAltTreeIndent
\newcommand{\glstrAltTreePar}{%
  \@par
  \glstrAltTreeSetHangIndent
  \setlength{\parindent}{\dimexpr\hangindent+\glstrAltTreeIndent}%
}
\newcommand{\glstralttreeSubSymbolDescLocation}[3]{%
  \glstralttreeSymbolDescLocation{#2}{#3}%
}
\newlength\glstrtreeetopindent
\newcommand*{\glstralttreeInit}{%
  \settowidth{\glstrtreeetopindent}{\glstreenamefmt{\glsgetwidestname\space}}%
  \glstrAltTreeIndent=\parindent
}
\newcommand*{\glssetwidest}[2][0]{%
  \csgdef{@glswidestname\romannumeral#1}{#2}%
}

```

```

\newcommand*\eglssetwidest}[2][0]{%
  \protected@csedef{@glswidestname\romannumeral#1}{#2}%
}
\newcommand*\xglsetwidest}[2][0]{%
  \protected@csxdef{@glswidestname\romannumeral#1}{#2}%
}
\newcommand*\glupdatewidest}[2][0]{%
  \ifcsundef{@glswidestname\romannumeral#1}%
  {\csdef{@glswidestname\romannumeral#1}{#2}}%
  {%
    \settowidth{\dimen@}{\csuse{@glswidestname\romannumeral#1}}%
    \settowidth{\dimen@ii}{#2}%
    \ifdim\dimen@ii>\dimen@
      \csdef{@glswidestname\romannumeral#1}{#2}%
    \fi
  }%
}
\newcommand*\gglsupdatewidest}[2][0]{%
  \ifcsundef{@glswidestname\romannumeral#1}%
  {\csgdef{@glswidestname\romannumeral#1}{#2}}%
  {%
    \settowidth{\dimen@}{\csuse{@glswidestname\romannumeral#1}}%
    \settowidth{\dimen@ii}{#2}%
    \ifdim\dimen@ii>\dimen@
      \csgdef{@glswidestname\romannumeral#1}{#2}%
    \fi
  }%
}
\newcommand*\eglsupdatewidest}[2][0]{%
  \ifcsundef{@glswidestname\romannumeral#1}%
  {\protected@csedef{@glswidestname\romannumeral#1}{#2}}%
  {%
    \settowidth{\dimen@}{\csuse{@glswidestname\romannumeral#1}}%
    \settowidth{\dimen@ii}{#2}%
    \ifdim\dimen@ii>\dimen@
      \protected@csedef{@glswidestname\romannumeral#1}{#2}%
    \fi
  }%
}
\newcommand*\xglupdatewidest}[2][0]{%
  \ifcsundef{@glswidestname\romannumeral#1}%
  {\protected@csxdef{@glswidestname\romannumeral#1}{#2}}%
  {%
    \settowidth{\dimen@}{\csuse{@glswidestname\romannumeral#1}}%
    \settowidth{\dimen@ii}{#2}%
    \ifdim\dimen@ii>\dimen@
      \protected@csxdef{@glswidestname\romannumeral#1}{#2}%
    \fi
  }%
}

```

```

\newcommand*{\glsgetwidestname}{\@glswidestname}
\newcommand*{\glsgetwidestsubname}[1]{%
  \ifcsundef{@glswidestname\romannumeral#1}%
    {\@glswidestname}%
    {\csuse{@glswidestname\romannumeral#1}}%
}
\let\glsFindWidestTopLevelName\glsfindwidesttoplevelname
\newrobustcmd*{\glsFindWidestUsedTopLevelName}[1][\@glo@types]{%
  \dimen@=0pt\relax
  \gls@tmplen=0pt\relax
  \foralllglossaries[#1]{\@gls@type}%
  {%
    \forglsentries[\@gls@type]{\@glo@label}%
    {%
      \ifglsused{\@glo@label}%
      {%
        \ifglshasparent{\@glo@label}%
        {}%
        {%
          \settowidth{\dimen@}%
            {\glstreenamfmt{\glsentryname{\@glo@label}}}%
          \ifdim\dimen@>\gls@tmplen
            \gls@tmplen=\dimen@
            \eglssetwidest{\glsentryname{\@glo@label}}%
          \fi
        }%
      }%
    }%
  }%
}
\newrobustcmd*{\glsFindWidestUsedAnyName}[1][\@glo@types]{%
  \dimen@=0pt\relax
  \gls@tmplen=0pt\relax
  \foralllglossaries[#1]{\@gls@type}%
  {%
    \forglsentries[\@gls@type]{\@glo@label}%
    {%
      \ifglsused{\@glo@label}%
      {%
        \settowidth{\dimen@}%
          {\glstreenamfmt{\glsentryname{\@glo@label}}}%
        \ifdim\dimen@>\gls@tmplen
          \gls@tmplen=\dimen@
          \eglssetwidest{\glsentryname{\@glo@label}}%
        \fi
      }%
    }%
  }%
}

```

```

}
\newrobustcmd*{\glsFindWidestAnyName}[1][\@glo@types]{%
  \dimen@=0pt\relax
  \gls@tmplen=0pt\relax
  \forallglossaries[#1]{\@gls@type}%
  {%
    \forglsentries[\@gls@type]{\@glo@label}%
    {%
      \settowidth{\dimen@}%
        {\glstreenamfmt{\glsentryname{\@glo@label}}}%
      \ifdim\dimen@>\gls@tmplen
        \gls@tmplen=\dimen@
        \eglssetwidest{\glsentryname{\@glo@label}}%
      \fi
    }%
  }%
}
\newrobustcmd*{\glsFindWidestUsedLevelTwo}[1][\@glo@types]{%
  \dimen@=0pt\relax
  \dimen@i=0pt\relax
  \dimen@ii=0pt\relax
  \forallglossaries[#1]{\@gls@type}%
  {%
    \forglsentries[\@gls@type]{\@glo@label}%
    {%
      \ifglsused{\@glo@label}%
      {%
        \ifglshasparent{\@glo@label}%
        {%
          \protected@edef\@glo@parent{\csuse{glo@\glsdetoklabel{\@glo@label}@parent}}%
          \ifglshasparent{\@glo@parent}%
          {%
            \protected@edef\@glo@parent{\csuse{glo@\glsdetoklabel{\@glo@parent}@parent}}%
            \ifglshasparent{\@glo@parent}%
            {}%
          }%
        }%
        \settowidth{\gls@tmplen}%
          {\glstreenamfmt{\glsentryname{\@glo@label}}}%
        \ifdim\gls@tmplen>\dimen@ii
          \dimen@ii=\gls@tmplen
          \eglssetwidest[2]{\glsentryname{\@glo@label}}%
        \fi
      }%
    }%
    {%
      \settowidth{\gls@tmplen}%
        {\glstreenamfmt{\glsentryname{\@glo@label}}}%
      \ifdim\gls@tmplen>\dimen@i
        \dimen@i=\gls@tmplen
        \eglssetwidest[1]{\glsentryname{\@glo@label}}%
      \fi
    }%
  }%
}

```

```

        \fi
    }%
}%
{%
    \settowidth{\gls@tmplen}%
        {\glstreenamefmt{\glsentryname{\@glo@label}}}%
    \ifdim\gls@tmplen>\dimen@
        \dimen@=\gls@tmplen
        \eglssetwidest{\glsentryname{\@glo@label}}%
    \fi
}%
}%
}%
}%
}%
}
\newrobustcmd*{\glsFindWidestLevelTwo}[1][\@glo@types]{%
    \dimen@=0pt\relax
    \dimen@i=0pt\relax
    \dimen@ii=0pt\relax
    \foralllglossaries[#1]{\@gls@type}%
    {%
        \forglsentries[\@gls@type]{\@glo@label}%
        {%
            \ifglshasparent{\@glo@label}%
            {%
                \protected@edef\@glo@parent{\csuse{glo\glsdetoklabel{\@glo@label}@parent}}%
                \ifglshasparent{\@glo@parent}%
                {%
                    \protected@edef\@glo@parent{\csuse{glo\glsdetoklabel{\@glo@parent}@parent}}%
                    \ifglshasparent{\@glo@parent}%
                    {%
                        \settowidth{\gls@tmplen}%
                            {\glstreenamefmt{\glsentryname{\@glo@label}}}%
                        \ifdim\gls@tmplen>\dimen@ii
                            \dimen@ii=\gls@tmplen
                            \eglssetwidest[2]{\glsentryname{\@glo@label}}%
                        \fi
                    }%
                }%
            }%
        }%
        \settowidth{\gls@tmplen}%
            {\glstreenamefmt{\glsentryname{\@glo@label}}}%
        \ifdim\gls@tmplen>\dimen@i
            \dimen@i=\gls@tmplen
            \eglssetwidest[1]{\glsentryname{\@glo@label}}%
        \fi
    }%
}%

```



```

    {%
      \settowidth{\gls@tmplen}%
        {\glstreenamefmt{\glsentryname{\@glo@label}}}%
      \ifdim\gls@tmplen>\dimen@
        \dimen@=\gls@tmplen
        \eglssetwidest{\glsentryname{\@glo@label}}%
      \fi
    }%
  }%
}%
}
\newrobustcmd*{\glsFindWidestUsedAnyNameSymbol}[2][\@glo@types]{%
  \dimen@=0pt\relax
  \gls@tmplen=0pt\relax
  #2=0pt\relax
  \forallglossaries[#1]{\@gls@type}%
  {%
    \forglentries[\@gls@type]{\@glo@label}%
    {%
      \ifglsused{\@glo@label}%
      {%
        \settowidth{\dimen@}%
          {\glstreenamefmt{\glsentryname{\@glo@label}}}%
        \ifdim\dimen@>\gls@tmplen
          \gls@tmplen=\dimen@
          \eglssetwidest{\glsentryname{\@glo@label}}%
        \fi
        \settowidth{\dimen@}%
          {\glsentrysymbol{\@glo@label}}%
        \ifdim\dimen@>#2\relax
          #2=\dimen@
        \fi
      }%
    }%
  }%
}
\newrobustcmd*{\glsFindWidestAnyNameSymbol}[2][\@glo@types]{%
  \dimen@=0pt\relax
  \gls@tmplen=0pt\relax
  #2=0pt\relax
  \forallglossaries[#1]{\@gls@type}%
  {%
    \forglentries[\@gls@type]{\@glo@label}%
    {%
      \settowidth{\dimen@}%
        {\glstreenamefmt{\glsentryname{\@glo@label}}}%
      \ifdim\dimen@>\gls@tmplen
        \gls@tmplen=\dimen@
        \eglssetwidest{\glsentryname{\@glo@label}}%
      \fi
    }%
  }%
}

```

```

\fi
\settowidth{\dimen@}%
{\glsentrysymbol{\@glo@label}}%
\ifdim\dimen@>#2\relax
#2=\dimen@
\fi
}%
}%
}
\newrobustcmd*{\glsFindWidestUsedAnyNameSymbolLocation}[3][\@glo@types]{%
\dimen@=0pt\relax
\gls@tmplen=0pt\relax
#2=0pt\relax
#3=0pt\relax
\forallglossaries[#1]{\@gls@type}%
{%
\forallglsentries[\@gls@type]{\@glo@label}%
{%
\ifglsused{\@glo@label}%
{%
\settowidth{\dimen@}%
{\glstreenamfmt{\glsentryname{\@glo@label}}}%
\ifdim\dimen@>\gls@tmplen
\gls@tmplen=\dimen@
\eglssetwidest{\glsentryname{\@glo@label}}%
\fi
\settowidth{\dimen@}%
{\glsentrysymbol{\@glo@label}}%
\ifdim\dimen@>#2\relax
#2=\dimen@
\fi
\settowidth{\dimen@}%
{\GlsXtrFormatLocationList{\glsentrynumberlist{\@glo@label}}}%
\ifdim\dimen@>#3\relax
#3=\dimen@
\fi
}%
}%
}%
}%
}
\newrobustcmd*{\glsFindWidestAnyNameSymbolLocation}[3][\@glo@types]{%
\dimen@=0pt\relax
\gls@tmplen=0pt\relax
#2=0pt\relax
#3=0pt\relax
\forallglossaries[#1]{\@gls@type}%
{%
\forallglsentries[\@gls@type]{\@glo@label}%
{%

```

```

\settowidth{\dimen@}%
{\glstreenamefmt{\glstryname{\@glo@label}}}%
\ifdim\dimen@>\gls@tmplen
\gls@tmplen=\dimen@
\eglssetwidest{\glstryname{\@glo@label}}%
\fi
\settowidth{\dimen@}%
{\glstrysymbol{\@glo@label}}%
\ifdim\dimen@>#2\relax
#2=\dimen@
\fi
\settowidth{\dimen@}%
{\GlsXtrFormatLocationList{\glstrynumberlist{\@glo@label}}}%
\ifdim\dimen@>#3\relax
#3=\dimen@
\fi
}%
}%
}
\newrobustcmd*{\glsFindWidestUsedAnyNameLocation}[2][\@glo@types]{%
\dimen@=0pt\relax
\gls@tmplen=0pt\relax
#2=0pt\relax
\forall glossaries[#1]{\@gls@type}%
{%
\forall glsentries[\@gls@type]{\@glo@label}%
{%
\ifglssused{\@glo@label}%
{%
\settowidth{\dimen@}%
{\glstreenamefmt{\glstryname{\@glo@label}}}%
\ifdim\dimen@>\gls@tmplen
\gls@tmplen=\dimen@
\eglssetwidest{\glstryname{\@glo@label}}%
\fi
\settowidth{\dimen@}%
{\GlsXtrFormatLocationList{\glstrynumberlist{\@glo@label}}}%
\ifdim\dimen@>#2\relax
#2=\dimen@
\fi
}%
}%
}%
}%
}
\newrobustcmd*{\glsFindWidestAnyNameLocation}[2][\@glo@types]{%
\dimen@=0pt\relax
\gls@tmplen=0pt\relax
#2=0pt\relax
\forall glossaries[#1]{\@gls@type}%

```

```

{%
\for glsentries [\@gls@type]{\@glo@label}%
{%
\settowidth{\dimen@}%
{\glstreenamefmt{\glstentryname{\@glo@label}}}%
\ifdim\dimen@>\gls@tmplen
\gls@tmplen=\dimen@
\eglssetwidest{\glstentryname{\@glo@label}}%
\fi
\settowidth{\dimen@}%
{\GlsXtrFormatLocationList{\glstentrynumberlist{\@glo@label}}}%
\ifdim\dimen@>#2\relax
#2=\dimen@
\fi
}%
}%
}
\newcommand*{\glxtrComputeTreeIndent}[1]{%
\glstreeindent=\glxtrtreetopindent\relax
}
\newcommand*{\glxtrComputeTreeSubIndent}[3]{%
\ifcsundef{\glswidestname\romannumeral#1}%
{%
\settowidth{#3}{\glstreenamefmt{\@glswidestname\space}}%
}%
{%
\settowidth{#3}{\glstreenamefmt{%
\csname @glswidestname\romannumeral#1\endcsname\space}}%
}%
}
}
\newcommand*{\glxtrAltTreeSetHangIndent}{\hangindent\glstreeindent}
\newcommand*{\glxtrAltTreeSetSubHangIndent}[1]{\hangindent\glstreeindent}
\renewglossarystyle{almtree}{%
\renewenvironment{theglossary}%
{%
\glxtralmtreeInit
\def\@gls@prevlevel{-1}%
\mbox{}\par}%
{\par}%
\renewcommand*{\glossaryheader}{}%
\renewcommand*{\glsgroupheading}[1]{}%
\renewcommand{\glosentry}[2]{%
\ifnum\@gls@prevlevel=0\relax
\else
\glxtrComputeTreeIndent{##1}%
\fi
\parindent\glstreeindent
\glxtrAltTreeSetHangIndent
\makebox[0pt][r]%
}%

```

```

\glstreenamebox{\glstreeindent}%
{%
  \glstryitem{##1}%
  \glstreenamefmt{\glstarget{##1}{\glossentryname{##1}}}%
}%
}%
\glxtralttreeSymbolDescLocation{##1}{##2}%
\def\@gls@prevlevel{0}%
}
\renewcommand{\subglossentry}[3]{%
  \ifnum##1=1\relax
    \glssubentryitem{##2}%
  \fi
  \ifnum\@gls@prevlevel=##1\relax
  \else
    \glxtrComputeTreeSubIndent{##1}{##2}{\gls@tmplen}%
    \ifnum\@gls@prevlevel<##1\relax
      \setlength\glstreeindent\gls@tmplen
      \addtolength\glstreeindent\parindent
      \parindent\glstreeindent
    \else
      \ifnum\@gls@prevlevel=0\relax
        \glxtrComputeTreeIndent{##2}%
      \else
        \glxtrComputeTreeSubIndent{\@gls@prevlevel}{##2}{\glstreeindent}%
      \fi
      \addtolength\parindent{-\glstreeindent}%
      \setlength\glstreeindent\parindent
    \fi
  \fi
  \glxtrAltTreeSetSubHangIndent{##1}%
  \makebox[Opt][r]{\glstreenamebox{\gls@tmplen}{%
    \glstreenamefmt{\glstarget{##2}{\glossentryname{##2}}}}}%
  \glxtralttreeSubSymbolDescLocation{##1}{##2}{##3}%
  \def\@gls@prevlevel{##1}%
}%
\renewcommand*{\glsgroupskip}{\ifglsnogroupskip\else\glstreegroupskip\fi}%
}
}%
{%
}
\ifdef{\@glsstyle@alttreegroup}
{%
  \renewglossarystyle{alttreegroup}{%
    \setglossarystyle{alttree}%
    \renewcommand{\glsgroupheading}[1]{\par
      \def\@gls@prevlevel{-1}%
      \hangindentOpt\relax
      \parindentOpt\relax
      \glxtrgetgrouptitle{##1}{\glxtr@grptitle}%

```

```

        \glstreePreHeader{##1}{\glstr@grptitle}%
        \glstreegroupheaderfmt{\glstr@grptitle}%
        \glstreegroupheaderskip
    }%
}%
}%
{%
}
\ifdef{\@glsstyle@almtreehypergroup}
{%
    \renewglossarystyle{almtreehypergroup}{%
        \setglossarystyle{almtree}%
        \renewcommand*{\glossaryheader}{%
            \par
            \def\@gls@prevlevel{-1}%
            \hangindentOpt\relax
            \parindentOpt\relax
            \glstreenavigationfmt{\glsnavigation}%
            \glstreegroupheaderskip
        }%
        \renewcommand*{\glsgroupheading}[1]{%
            \glstrgetgrouptitle{##1}{\glstr@grptitle}%
            \glstreePreHeader{##1}{\glstr@grptitle}%
            \par
            \def\@gls@prevlevel{-1}%
            \hangindentOpt\relax
            \parindentOpt\relax
            \glstreegroupheaderfmt{\glsnavhypertarget{##1}{\glstr@grptitle}}%
            \glstreegroupheaderskip
        }%
    }
}%
{%
}
\ifdef{\@glsstyle@mcolindexgroup}
{%
    \renewglossarystyle{mcolindexgroup}{%
        \setglossarystyle{mcolindex}%
        \renewcommand*{\glsgroupheading}[1]{%
            \glstrgetgrouptitle{##1}{\glstr@grptitle}%
            \glstreePreHeader{##1}{\glstr@grptitle}%
            \item\glstreegroupheaderfmt{\glstr@grptitle}%
            \glstreegroupheaderskip\@afterheading
        }%
    }
}%
{%
}
\ifdef{\@glsstyle@mcolindexhypergroup}
{%

```

```

\renewglossarystyle{mcolindexhypergroup}{%
  \setglossarystyle{mcolindex}%
  \renewcommand*{\glossaryheader}{%
    \item\glstreenavigationfmt{\glsnavigation}%
    \glstreegroupheaderskip\@afterheading
  }%
  \renewcommand*{\glsgroupheading}[1]{%
    \glstrgetgrouptitle{##1}{\glstr@grptitle}%
    \glstreePreHeader{##1}{\glstr@grptitle}%
    \item\glstreegroupheaderfmt
      {\glsnavhypertarget{##1}{\glstr@grptitle}}%
    \glstreegroupheaderskip\@afterheading
  }%
}
}%
{%
}
\ifdef{\@glsstyle@mcolindexspannav}
{%
  \renewglossarystyle{mcolindexspannav}{%
    \setglossarystyle{index}%
    \renewenvironment{theglossary}%
    {%
      \begin{multicols}{\glsmcols}[\noindent\glstreenavigationfmt{\glsnavigation}]]%
      \setlength{\parindent}{0pt}%
      \setlength{\parskip}{0pt plus 0.3pt}%
      \let\item\glstreeitem}%
    {\end{multicols}}%
    \renewcommand*{\glsgroupheading}[1]{%
      \glstrgetgrouptitle{##1}{\glstr@grptitle}%
      \glstreePreHeader{##1}{\glstr@grptitle}%
      \item\glstreegroupheaderfmt
        {\glsnavhypertarget{##1}{\glstr@grptitle}}%
      \glstreegroupheaderskip\@afterheading
    }%
  }
}%
{%
}
\ifdef{\@glsstyle@mcoltreegroup}
{%
  \renewglossarystyle{mcoltreegroup}{%
    \setglossarystyle{mcoltree}%
    \renewcommand{\glsgroupheading}[1]{%
      \glstrgetgrouptitle{##1}{\glstr@grptitle}%
      \glstreePreHeader{##1}{\glstr@grptitle}%
      \par\noindent\glstreegroupheaderfmt{\glstr@grptitle}%
      \glstreegroupheaderskip\@afterheading
    }%
  }
}

```

```

}%
{%
}
\ifdef{\@glsstyle@mcoltreehypergroup}
{%
  \renewglossarystyle{mcoltreehypergroup}{%
    \setglossarystyle{mcoltree}%
    \renewcommand*{\glossaryheader}{%
      \par\noindent\glstreenavigationfmt{\glsnavigation}%
      \glstreegroupheaderskip
    }%
    \renewcommand*{\glsgroupheading}[1]{%
      \glsxtrgetgrouptitle{##1}{\glsxtr@grptitle}%
      \glstreePreHeader{##1}{\glsxtr@grptitle}%
      \par\noindent
      \glstreegroupheaderfmt{\glsnavhypertarget{##1}{\glsxtr@grptitle}}%
      \glstreegroupheaderskip\@afterheading
    }%
  }
}%
{%
}
\ifdef{\@glsstyle@mcoltreespannav}
{%
  \renewglossarystyle{mcoltreespannav}{%
    \setglossarystyle{tree}%
    \renewenvironment{theglossary}%
    {%
      \begin{multicols}{\glsncols}%
        [noindent\glstreenavigationfmt{\glsnavigation}]%
        \setlength{\parindent}{0pt}%
        \setlength{\parskip}{0pt plus 0.3pt}%
      }%
    \end{multicols}}%
    \renewcommand*{\glsgroupheading}[1]{%
      \glsxtrgetgrouptitle{##1}{\glsxtr@grptitle}%
      \glstreePreHeader{##1}{\glsxtr@grptitle}%
      \par\noindent
      \glstreegroupheaderfmt{\glsnavhypertarget{##1}{\glsxtr@grptitle}}%
      \glstreegroupheaderskip\@afterheading
    }%
  }
}%
{%
}
\ifdef{\@glsstyle@mcoltreenamegroup}
{%
  \renewglossarystyle{mcoltreenamegroup}{%
    \setglossarystyle{mcoltreename}%
    \renewcommand{\glsgroupheading}[1]{%

```



```

\glstrgetgrouptitle{##1}{\glstr@grptitle}%
\glstreePreHeader{##1}{\glstr@grptitle}%
\par\noindent\glstreegroupheaderfmt{\glstr@grptitle}%
\glstreegroupheaderskip\@afterheading
}%
}
}%
{%
}
\ifdef{\@glsstyle@mcoltreenamehypergroup}
{%
\renewglossarystyle{mcoltreenamehypergroup}{%
\setglossarystyle{mcoltreename}%
\renewcommand*{\glossaryheader}{%
\par\noindent\glstreenavigationfmt{\glsnavigation}%
\glstreegroupheaderskip
}%
\renewcommand*{\glsgroupheading}[1]{%
\glstrgetgrouptitle{##1}{\glstr@grptitle}%
\glstreePreHeader{##1}{\glstr@grptitle}%
\par\noindent
\glstreegroupheaderfmt{\glsnavhypertarget{##1}{\glstr@grptitle}}%
\glstreegroupheaderskip\@afterheading}%
}
}%
{%
}
\ifdef{\@glsstyle@mcoltreenamepannav}
{%
\renewglossarystyle{mcoltreenamepannav}{%
\setglossarystyle{treename}%
\renewenvironment{theglossary}%
{%
\begin{multicols}{\glscols}%
[\noindent\glstreenavigationfmt{\glsnavigation}]%
\setlength{\parindent}{0pt}%
\setlength{\parskip}{0pt plus 0.3pt}%
}%
{\end{multicols}}%
\renewcommand*{\glsgroupheading}[1]{%
\glstrgetgrouptitle{##1}{\glstr@grptitle}%
\glstreePreHeader{##1}{\glstr@grptitle}%
\par\noindent
\glstreegroupheaderfmt{\glsnavhypertarget{##1}{\glstr@grptitle}}%
\glstreegroupheaderskip\@afterheading}%
}
}%
{%
}
\ifdef{\@glsstyle@mcolalttree}

```

```

{%
  \renewglossarystyle{mcolalmtree}{%
    \setglossarystyle{almtree}%
    \renewenvironment{theglossary}%
    {%
      \glxtralmtreeInit
      \def\@gls@prevlevel{-1}%
      \begin{multicols}{\glsmcols}%
    }%
    {\par\end{multicols}}%
  }
}%
{%
}
\ifdef{\@glsstyle@mcolalmtreegroup}
{%
  \renewglossarystyle{mcolalmtreegroup}{%
    \setglossarystyle{mcolalmtree}%
    \renewcommand{\glsgroupheading}[1]{%
      \glxtrgetgrouptitle{##1}{\glxtr@grptitle}%
      \glstreePreHeader{##1}{\glxtr@grptitle}%
      \par
      \def\@gls@prevlevel{-1}%
      \hangindentOpt\relax
      \parindentOpt\relax
      \glstreegroupheaderfmt{\glxtr@grptitle}%
      \glstreegroupheaderskip
    }%
  }
}%
{%
}
\ifdef{\@glsstyle@mcolalmtreehypergroup}
{%
  \renewglossarystyle{mcolalmtreehypergroup}{%
    \setglossarystyle{mcolalmtree}%
    \renewcommand*{\glossaryheader}{%
      \par
      \def\@gls@prevlevel{-1}%
      \hangindentOpt\relax
      \parindentOpt\relax
      \glstreenavigationfmt{\glsnavigation}%
      \glstreegroupheaderskip
    }%
    \renewcommand*{\glsgroupheading}[1]{%
      \glxtrgetgrouptitle{##1}{\glxtr@grptitle}%
      \glstreePreHeader{##1}{\glxtr@grptitle}%
      \par
      \def\@gls@prevlevel{-1}%
      \hangindentOpt\relax
    }
  }
}

```

```

        \parindent0pt\relax
        \glstreegroupheaderfmt{\glsnavhypertarget{##1}{\glxstr@grptitle}}%
        \glstreegroupheaderskip
    }%
}
}%
{%
}
\ifdef{\@glsstyle@mcalttreespannav}
{%
    \renewglossarystyle{mcalttreespannav}{%
        \setglossarystyle{alttree}%
        \renewenvironment{theglossary}%
        {%
            \glxtralttreeInit
            \def\@gls@prevlevel{-1}%
            \begin{multicols}{\glsmcols}%
                [\noindent\glstreenavigationfmt{\glsnavigation}]%
            }%
        }\par\end{multicols}}%
    \renewcommand*{\glsgroupheading}[1]{%
        \glxstrgetgrouptitle{##1}{\glxstr@grptitle}%
        \glstreePreHeader{##1}{\glxstr@grptitle}%
        \par
        \def\@gls@prevlevel{-1}%
        \hangindent0pt\relax
        \parindent0pt\relax
        \glstreegroupheaderfmt{\glsnavhypertarget{##1}{\glxstr@grptitle}}%
        \glstreegroupheaderskip
    }%
}
}%
{%
}
\ifx\@glossary@default@style\relax
\else
    \setglossarystyle{\@glxstr@current@style}
\fi

```

9.4 Rollback v1.48 (glossary-bookindex-2021-11-22.sty)

Version 1.48 preserved for rollback.

```

\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{glossary-bookindex}[2021/11/22 v1.48 (NLCT)]
\RequirePackage{multicol}
\RequirePackage{glossary-tree}
\newcommand{\glxstrbookindexcols}{2}
\newcommand*{\glxstrbookindexname}[1]{\glossentryname{#1}}
\newcommand*{\glxstrbookindexsubname}[1]{\glxstrbookindexname{#1}}

```

```

\providecommand*\glstrprelocation{\space}

\newcommand*\glstrbookindexprelocation[1]{%
  \glstrifhasfield{location}{#1}%
  {\glstrprelocation}%
  {\glstrprelocation}%
}
\newcommand*\glstrbookindexsubprelocation[1]{%
  \glstrbookindexprelocation{#1}%
}
\newcommand*\glstrbookindexlocation[2]{#2}
\newcommand*\glstrbookindexsublocation{\glstrbookindexlocation}
\newcommand*\glstrbookindexparentchildsep{\nopagebreak}
\newcommand*\glstrbookindexparentschildsep{\glstrbookindexparentchildsep}
\newcommand*\glstrbookindexbetween[2]{}
\newcommand*\glstrbookindexsubbetween[2]{}
\newcommand*\glstrbookindexsubsubbetween[2]{}
\newcommand*\glstrbookindexatendgroup[1]{}
\newcommand*\glstrbookindexsubatendgroup[1]{}
\newcommand*\glstrbookindexsubsubatendgroup[1]{}
\newcommand*\glstrbookindexgroupskip{\ifglsnogroupskip\else\indexspace\fi}
\newcommand*\glstrbookindexformatheader[1]{%
  \par{\centering\glstreegroupheaderfmt{#1}\par}%
}
\ifdef\pdfbookmark
{%
  \newcommand*\glstrbookindexbookmark[2]{%
    \ifdefstring{\@glossarysec}{chapter}%
    {\pdfbookmark[1]{#1}{#2}}%
    {\pdfbookmark[2]{#1}{#2}}%
  }
}
{%
  \newcommand*\glstrbookindexbookmark[2]{}
}
\newcommand*\glstrbookindexbookmarkprefix{\currentglossary.}
\newcommand*\glstrbookindexcolspread{}
\newcommand*\glstrbookindexmulticolenv{\multicols}
\newglossarystyle{bookindex}{%
  \setglossarystyle{index}%
  \renewenvironment{theglossary}%
  {%
    \ifnum\glstrbookindexcols>1\relax
    \ifdefempty\glstrbookindexcolspread
    {%
      \edef\glstr@beginbookindex{%
        \noexpand\begin{\glstrbookindexmulticolenv}
        {\glstrbookindexcols}%
      }%
    }%
  }%
}

```

```

{%
  \edef\glxstr@beginbookindex{%
    \noexpand\begin{\glxstrbookindexmulticolseenv}%
    {\glxstrbookindexcols}{\glxstrbookindexcolspread}%
  }%
}%
\else
  \def\glxstr@beginbookindex{%
\fi
\glxstr@beginbookindex
\setlength{\parindent}{0pt}%
\setlength{\parskip}{0pt plus 0.3pt}%
\let\@glxstr@bookindex@sep\glxstrbookindexparentchildsep
\let\@glxstr@bookindex@subsep\glxstrbookindexparentsubchildsep
\let\@glxstr@bookindex@between\@gobble
\let\@glxstr@bookindex@subbetween\@gobble
\let\@glxstr@bookindex@subsubbetween\@gobble
\let\@glxstr@bookindex@atendgroup\relax
\let\@glxstr@bookindex@subatendgroup\relax
\let\@glxstr@bookindex@subsubatendgroup\relax
\let\@glxstr@bookindex@groupskip\relax
}%
{%
  \@glxstr@bookindex@subsubatendgroup
  \@glxstr@bookindex@subatendgroup
  \@glxstr@bookindex@atendgroup
  \ifnum\glxstrbookindexcols>1\relax
    \edef\glxstr@endbookindex{%
      \noexpand\end{\glxstrbookindexmulticolseenv}%
    }%
  \else
    \def\glxstr@endbookindex{%
\fi
\glxstr@endbookindex
}%
\renewcommand*{\glossaryheader}{\raggedright}%
\renewcommand*{\glossentry}[2]{%
  \@glxstr@bookindex@between{##1}%
  \let\@glxstr@bookindex@sep\glxstrbookindexparentchildsep
  \let\@glxstr@bookindex@subsep\glxstrbookindexparentsubchildsep
  \let\@glxstr@bookindex@subbetween\@gobble
  \let\@glxstr@bookindex@subsubbetween\@gobble
  \edef\@glxstr@bookindex@between{%
    \noexpand\glxstrbookindexbetween{##1}%
  }%
  \edef\@glxstr@bookindex@atendgroup{%
    \noexpand\glxstrbookindexatendgroup{##1}%
  }%
  \let\@glxstr@bookindex@subatendgroup\relax
  \let\@glxstr@bookindex@subsubatendgroup\relax

```

```

\glstreeitem
  \glstentryitem{##1}%
  \glstarget{##1}{\glxstrbookindexname{##1}}%
  \glxstrbookindexprelocation{##1}%
  \glxstrbookindexlocation{##1}{##2}%
}%
\renewcommand{\subglossentry}[3]{%
  \ifcase##1\relax
    \glstreeitem
  \or
    \@glxstr@bookindex@sep
    \@glxstr@bookindex@subbetween{##2}%
    \let\@glxstr@bookindex@sep\relax
    \let\@glxstr@bookindex@subsubbetween\@gobble
    \let\@glxstr@bookindex@subsep\glxstrbookindexparentschildsep
    \edef\@glxstr@bookindex@subbetween{%
      \noexpand\glxstrbookindexsubbetween{##2}%
    }%
    \edef\@glxstr@bookindex@atsubendgroup{%
      \noexpand\glxstrbookindexatsubendgroup{##1}%
    }%
    \glstreesubitem
    \glssubentryitem{##2}%
  \else
    \@glxstr@bookindex@subsep
    \@glxstr@bookindex@subsubbetween{##2}%
    \let\@glxstr@bookindex@subsep\relax
    \edef\@glxstr@bookindex@subsubbetween{%
      \noexpand\glxstrbookindexsubsubbetween{##2}%
    }%
    \edef\@glxstr@bookindex@atsubsubendgroup{%
      \noexpand\glxstrbookindexatsubsubendgroup{##1}%
    }%
    \glstreesubsubitem
  \fi
  \glstarget{##2}{\glxstrbookindexsubname{##2}}%
  \glxstrbookindexsubprelocation{##2}%
  \glxstrbookindexsublocation{##2}{##3}%
}%
\renewcommand*{\glsgroupskip}{}%
\renewcommand*{\glsgroupheading}[1]{%
  \@glxstr@bookindex@subsubatendgroup
  \@glxstr@bookindex@subatendgroup
  \@glxstr@bookindex@atendgroup
  \@glxstr@bookindex@groupskip
  \let\@glxstr@bookindex@groupskip\glxstrbookindexgroupskip
  \let\@glxstr@bookindex@between\@gobble
  \let\@glxstr@bookindex@atendgroup\relax
  \let\@glxstr@bookindex@subatendgroup\relax
  \let\@glxstr@bookindex@subsubatendgroup\relax

```

```

\glxstrgetgrouptitle{##1}{\glxstrcurrentgrptitle}%
\glxstrbookindexbookmark{\glxstrcurrentgrptitle}{\glxstrbookindexbookmarkprefix##1}%
\glxstrbookindexformatheader{\glxstrcurrentgrptitle}%
\nopagebreak\indexspace\nopagebreak\@afterheading
}%
}
\newcommand{\glxstrbookindexthepage}{%
\ifdef\currentglossary{\currentglossary.\arabic{page}}{\arabic{page}}%
}
\newcommand*{\glxstrbookindexmarkentry}[1]{%
\protected@write\@auxout
{\let\glxstrbookindexthepage\relax}%
{\string\glxstrsetbookindexmark{\glxstrbookindexthepage}{#1}}%
}
\newcommand*{\glxstrsetbookindexmark}[2]{%
\ifcsundef{glxstr@idxfirstmark@#1}%
{\csgdef{glxstr@idxfirstmark@#1}{#2}}%
{}%
\csgdef{glxstr@idxlastmark@#1}{#2}%
}
\newcommand*{\glxstrbookindexfirstmarkfmt}[1]{%
\glstryname{#1}%
}
\newcommand*{\glxstrbookindexfirstmark}{%
\letcs{glxstr@label}{glxstr@idxfirstmark@\glxstrbookindexthepage}%
\ifdef\glxstr@label
{\glxstrbookindexfirstmarkfmt{\glxstr@label}}%
{}%
}
\newcommand*{\glxstrbookindexlastmarkfmt}[1]{%
\glstryname{#1}%
}
\newcommand*{\glxstrbookindexlastmark}{%
\letcs{glxstr@label}{glxstr@idxlastmark@\glxstrbookindexthepage}%
\ifdef\glxstr@label
{\glxstrbookindexlastmarkfmt{\glxstr@label}}%
{}%
}
}

```

9.5 Rollback v1.48 (glossary-longextra-2021-11-22.sty)

Version 1.48 preserved for rollback.

```

\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{glossary-longextra}[2021/11/22 v1.48 (NLCT)]
\RequirePackage{glossary-longbooktabs}
\newcommand{\glslongextraNameFmt}[1]{%
\glstryitem{#1}\glstarget{#1}{\glossentryname{#1}}%
}
\newcommand{\glslongextraDescFmt}[1]{%

```

```

\glossentrydesc{#1}\glspostdescription
}
\newcommand{\glslongextraSymbolFmt}[1]{\glossentrysymbol{#1}}
\newcommand{\glslongextraLocationFmt}[2]{#2}
\newcommand{\glslongextraSubNameFmt}[2]{%
\glssubentryitem{#2}\glstarget{#2}{\strut}%
}
\newcommand{\glslongextraSubDescFmt}[2]{%
\glslongextraDescFmt{#2}%
}
\newcommand{\glslongextraSubSymbolFmt}[2]{%
\glslongextraSymbolFmt{#2}%
}
\newcommand{\glslongextraSubLocationFmt}[3]{#3}
\newcommand{\glslongextraNameAlign}[1]{}
\newcommand{\glslongextraDescAlign}{>{\raggedright}p{\glsdescwidth}}
\newcommand{\glslongextraSymbolAlign}{c}
\newcommand{\glslongextraLocationAlign}{>{\raggedright}p{\glslistwidth}}
\newcommand{\glslongextraGroupHeading}[2]{}
\newcommand{\glslongextraHeaderFmt}[1]{\textbf{#1}}
\newcommand{\glslongextraNameDescHeader}{%
\glslongextraNameDescTabularHeader\endhead
\glslongextraNameDescTabularFooter\endfoot
}
\newcommand{\glslongextraNameDescTabularHeader}{%
\toprule
\glslongextraHeaderFmt\entryname &
\glslongextraHeaderFmt\descriptionname\tabularnewline
\midrule
}
\newcommand{\glslongextraNameDescTabularFooter}{%
\bottomrule
}
\newcommand*{\glslongextraSetWidest}[1]{%
\def\@glslongextrawidestname{#1}%
}
\newcommand*{\@glslongextrawidestname}{\csuse{\glswidestname}}
\newcommand*{\glslongextraUpdateWidest}[1]{%
\ifundef\@glslongextrawidestname
{\def\@glslongextrawidestname{#1}}%
{%
\settowidth{\dimen@}{\@glslongextrawidestname}%
\settowidth{\dimen@ii}{#1}%
\ifdim\dimen@ii>\dimen@
\def\@glslongextrawidestname{#1}%
\fi
}%
}
\newcommand*{\glslongextraUpdateWidestChild}[2]{}
\newcommand{\glslongextraSetDescWidth}{%

```



```

\settowidth{\gls@tmplen}{\glslongextraHeaderFmt\entryname}%
\settowidth{\dimen@}{\glsnamefont{\@glslongextrawidestname}}%
\ifdim\dimen@>\gls@tmplen
  \gls@tmplen=\dimen@
\fi
\setlength{\glsdescwidth}{\dimexpr\linewidth-4\tabcolsep-\gls@tmplen}%
}
\newcommand{\glslongextraSymSetDescWidth}{%
  \glslongextraSetDescWidth
  \settowidth{\gls@tmplen}{\glslongextraHeaderFmt\symbolname}%
  \setlength{\glsdescwidth}{\dimexpr\glsdescwidth-2\tabcolsep-\gls@tmplen}%
}
\newcommand{\glslongextraLocSetDescWidth}{%
  \glslongextraSetDescWidth
  \setlength{\glsdescwidth}{\dimexpr\glsdescwidth-2\tabcolsep-\glspagelistwidth}%
}
\newcommand{\glslongextraSymLocSetDescWidth}{%
  \glslongextraSymSetDescWidth
  \setlength{\glsdescwidth}{\dimexpr\glsdescwidth-2\tabcolsep-\glspagelistwidth}%
}
\newif\ifGlsLongExtraUseTabular
\GlsLongExtraUseTabularfalse
\newcommand*{\glslongextraTabularVAlign}{c}
\newglossarystyle{long-name-desc}{%
  {%
    \ifGlsLongExtraUseTabular
      \renewenvironment{theglossary}{%
        {%
          \glslongextraSetDescWidth
          \edef\@glslongextra@begintab{%
            \noexpand\begin{tabular}[\glslongextraTabularVAlign]{%
              \expandonce\glslongextraNameAlign
              \expandonce\glslongextraDescAlign}}%
          \@glslongextra@begintab
        }%
        {%
          \glslongextraNameDescTabularFooter
          \end{tabular}%
        }%
      }%
      \renewcommand*{\glossaryheader}{\glslongextraNameDescTabularHeader}%
    \else
      \renewenvironment{theglossary}{%
        {%
          \glspatchLToutput
          \glslongextraSetDescWidth
          \edef\@glslongextra@begintab{%
            \noexpand\begin{longtable}{%
              \expandonce\glslongextraNameAlign
              \expandonce\glslongextraDescAlign}}%
          \@glslongextra@begintab
        }%
      }%
    \fi
  }%
}

```

```

}%
{\end{longtable}}}%
\renewcommand*{\glossaryheader}{\glslongextraNameDescHeader}%
\fi
\renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{2}{##1}}%
\renewcommand{\glossentry}[2]{%
  \glslongextraNameFmt{##1} &
  \glslongextraDescFmt{##1}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
  \glslongextraSubNameFmt{##1}{##2}
  &
  \glslongextraSubDescFmt{##1}{##2}%
  \tabularnewline
}%
\ifglsnogroupskip
  \renewcommand*{\glsgroupskip}{}%
\else
  \renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
}
\newcommand{\glslongextraNameDescLocationHeader}{%
  \glslongextraNameDescLocationTabularHeader\endhead
  \glslongextraNameDescLocationTabularFooter\endfoot
}
\newcommand{\glslongextraNameDescLocationTabularHeader}{%
  \toprule
  \glslongextraHeaderFmt\entryname &
  \glslongextraHeaderFmt\descriptionname &
  \glslongextraHeaderFmt\pagelistname\tabularnewline
  \midrule
}
\newcommand{\glslongextraNameDescLocationTabularFooter}{%
  \bottomrule
}
\newglossarystyle{long-name-desc-loc}%
{%
  \ifGlsLongExtraUseTabular
    \renewenvironment{theglossary}%
    {%
      \glslongextraLocSetDescWidth
      \edef\@glslongextra@begintab{%
        \noexpand\begin{tabular}{\glslongextraTabularVAlign}{%
          \expandonce\glslongextraNameAlign
          \expandonce\glslongextraDescAlign
          \expandonce\glslongextraLocationAlign
        }}%
      \@glslongextra@begintab
    }%
  {%

```

```

\glslongextraNameDescLocationTabularFooter
\end{tabular}%
}%
\renewcommand*{\glossaryheader}{\glslongextraNameDescLocationTabularHeader}%
\else
\renewenvironment{theglossary}%
{
\glspatchLToutput
\glslongextraLocSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{longtable}%
\expandonce\glslongextraNameAlign
\expandonce\glslongextraDescAlign
\expandonce\glslongextraLocationAlign
}%
\@glslongextra@begintab
}%
{\end{longtable}}%
\renewcommand*{\glossaryheader}{\glslongextraNameDescLocationHeader}%
\fi
\renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{3}{##1}}%
\renewcommand{\glossentry}[2]{%
\glslongextraNameFmt{##1} &
\glslongextraDescFmt{##1} &
\glslongextraLocationFmt{##1}{##2}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
\glslongextraSubNameFmt{##1}{##2}&
\glslongextraSubDescFmt{##1}{##2}&
\glslongextraSubLocationFmt{##1}{##2}{##3}%
\tabularnewline
}%
\ifglsnogroupskip
\renewcommand*{\glsgroupskip}{}%
\else
\renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
}
\newcommand{\glslongextraDescNameHeader}{%
\glslongextraDescNameTabularHeader\endhead
\glslongextraDescNameTabularFooter\endfoot
}
\newcommand{\glslongextraDescNameTabularHeader}{%
\toprule
\glslongextraHeaderFmt\descriptionname&
\glslongextraHeaderFmt\entryname \tabularnewline
\midrule
}
\newcommand{\glslongextraDescNameTabularFooter}{%
\bottomrule

```

```

}
\newglossarystyle{long-desc-name}%
{%
  \ifGlsLongExtraUseTabular
  \renewenvironment{theglossary}%
  {%
    \glslongextraSetDescWidth
    \edef\@glslongextra@begintab{%
      \noexpand\begin{tabular}[\glslongextraTabularVAlign]{%
        \expandonce\glslongextraDescAlign
        \expandonce\glslongextraNameAlign}}%
    \@glslongextra@begintab
  }%
  {%
    \glslongextraDescNameTabularFooter
    \end{tabular}%
  }%
  \renewcommand*\glossaryheader{\glslongextraDescNameTabularHeader}%
\else
\renewenvironment{theglossary}%
{%
  \glspatchLToutput
  \glslongextraSetDescWidth
  \edef\@glslongextra@begintab{%
    \noexpand\begin{longtable}{%
      \expandonce\glslongextraDescAlign
      \expandonce\glslongextraNameAlign}}%
  \@glslongextra@begintab
}%
{\end{longtable}}%
\renewcommand*\glossaryheader{\glslongextraDescNameHeader}%
\fi
\renewcommand*\glsgroupheading[1]{\glslongextraGroupHeading{2}{##1}}%
\renewcommand{\glossentry}[2]{%
  \glslongextraDescFmt{##1} &
  \glslongextraNameFmt{##1}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
  \glslongextraSubDescFmt{##1}{##2} &
  \glslongextraSubNameFmt{##1}{##2}\tabularnewline
}%
\ifglsgroupskip
\renewcommand*\glsgroupskip{}%
\else
\renewcommand*\glsgroupskip{\glspenaltygroupskip}%
\fi
}
\newcommand{\glslongextraLocationDescNameHeader}{%
\glslongextraLocationDescNameTabularHeader\endhead
\glslongextraLocationDescNameTabularFooter\endfoot

```

```

}
\newcommand{\glslongextraLocationDescNameTabularHeader}{%
\toprule
\glslongextraHeaderFmt\pagelistname&
\glslongextraHeaderFmt\descriptionname&
\glslongextraHeaderFmt\entryname \tabularnewline
\midrule
}
\newcommand{\glslongextraLocationDescNameTabularFooter}{%
\bottomrule
}
\newglossarystyle{long-loc-desc-name}%
{%
\ifGlsLongExtraUseTabular
{%
\glslongextraLocSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{tabular}[\glslongextraTabularVAlign]{%
\expandonce\glslongextraLocationAlign
\expandonce\glslongextraDescAlign
\expandonce\glslongextraNameAlign}}%
\@glslongextra@begintab
}%
{%
\glslongextraLocationDescNameTabularFooter
\end{tabular}%
}%
\renewcommand*{\glossaryheader}{\glslongextraLocationDescNameTabularHeader}%
\else
\renewenvironment{theglossary}%
{%
\glspatchLToutput
\glslongextraLocSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{longtable}{%
\expandonce\glslongextraLocationAlign
\expandonce\glslongextraDescAlign
\expandonce\glslongextraNameAlign}}%
\@glslongextra@begintab
}%
{\end{longtable}}%
\renewcommand*{\glossaryheader}{\glslongextraLocationDescNameHeader}%
\fi
\renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{3}{##1}}%
\renewcommand{\glossentry}[2]{%
\glslongextraLocationFmt{##1}{##2} &
\glslongextraDescFmt{##1} &
\glslongextraNameFmt{##1}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%

```

```

\glslongextraSubLocationFmt{##1}{##2}{##3} &
\glslongextraSubDescFmt{##1}{##2} &
\glslongextraSubNameFmt{##1}{##2}\tabularnewline
}%
\ifglsgnogroupskip
\renewcommand*{\glsgroupskip}{}%
\else
\renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
}
\newcommand{\glslongextraNameDescSymHeader}{%
\glslongextraNameDescSymTabularHeader\endhead
\glslongextraNameDescSymTabularFooter\endfoot
}
\newcommand{\glslongextraNameDescSymTabularHeader}{%
\toprule
\glslongextraHeaderFmt\entryname &
\glslongextraHeaderFmt\descriptionname &
\glslongextraHeaderFmt\symbolname\tabularnewline
\midrule
}
\newcommand{\glslongextraNameDescSymTabularFooter}{%
\bottomrule
}
\newglossarystyle{long-name-desc-sym}%
{%
\ifGlsLongExtraUseTabular
\renewenvironment{theglossary}%
{%
\glslongextraSymSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{tabular}[\glslongextraTabularVAlign]{%
\expandonce\glslongextraNameAlign
\expandonce\glslongextraDescAlign
\expandonce\glslongextraSymbolAlign
}}%
\@glslongextra@begintab
}%
{%
\glslongextraNameDescSymTabularFooter
\end{tabular}%
}%
\renewcommand*{\glossaryheader}{\glslongextraNameDescSymTabularHeader}%
\else
\renewenvironment{theglossary}%
{%
\glspatchLToutput
\glslongextraSymSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{longtable}{%

```

```

\expandonce\glslongextraNameAlign
\expandonce\glslongextraDescAlign
\expandonce\glslongextraSymbolAlign
}}%
\@glslongextra@begintab
}%
{\end{longtable}}%
\renewcommand*{\glossaryheader}{\glslongextraNameDescSymHeader}%
\fi
\renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{3}{##1}}%
\renewcommand{\glossentry}[2]{%
\glslongextraNameFmt{##1} &
\glslongextraDescFmt{##1} &
\glslongextraSymbolFmt{##1}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
\glslongextraSubNameFmt{##1}{##2} &
\glslongextraSubDescFmt{##1}{##2} &
\glslongextraSubSymbolFmt{##1}{##2}%
\tabularnewline
}%
\ifglsgroupskip
\renewcommand*{\glsgroupskip}{}%
\else
\renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
}
\newcommand{\glslongextraNameDescSymLocationHeader}{%
\glslongextraNameDescSymLocationTabularHeader\endhead
\glslongextraNameDescSymLocationTabularFooter\endfoot
}
\newcommand{\glslongextraNameDescSymLocationTabularHeader}{%
\toprule
\glslongextraHeaderFmt\entryname &
\glslongextraHeaderFmt\descriptionname &
\glslongextraHeaderFmt\symbolname &
\glslongextraHeaderFmt\pagelistname\tabularnewline
\midrule
}
\newcommand{\glslongextraNameDescSymLocationTabularFooter}{%
\bottomrule
}
\newglossarystyle{long-name-desc-sym-loc}%
{%
\ifGlsLongExtraUseTabular
\renewenvironment{theglossary}%
{%
\glslongextraSymLocSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{tabular}[\glslongextraTabularVAlign]{%

```

```

        \expandonce\glslongextraNameAlign
        \expandonce\glslongextraDescAlign
        \expandonce\glslongextraSymbolAlign
        \expandonce\glslongextraLocationAlign
    } }%
    \@glslongextra@begintab
}%
{%
    \glslongextraNameDescSymLocationTabularFooter
    \end{tabular}%
}%
\renewcommand*{\glossaryheader}{\glslongextraNameDescSymLocationTabularHeader}%
\else
\renewenvironment{theglossary}%
{%
    \glspatchLToutput
    \glslongextraSymLocSetDescWidth
    \edef\@glslongextra@begintab{%
        \noexpand\begin{longtable}{%
            \expandonce\glslongextraNameAlign
            \expandonce\glslongextraDescAlign
            \expandonce\glslongextraSymbolAlign
            \expandonce\glslongextraLocationAlign
        } }%
    \@glslongextra@begintab
}%
    {\end{longtable}}%
    \renewcommand*{\glossaryheader}{\glslongextraNameDescSymLocationHeader}%
\fi
\renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{4}{##1}}%
\renewcommand{\glosentry}[2]{%
    \glslongextraNameFmt{##1} &
    \glslongextraDescFmt{##1} &
    \glslongextraSymbolFmt{##1}&
    \glslongextraLocationFmt{##1}{##2}\tabularnewline
}%
\renewcommand{\subglosentry}[3]{%
    \glslongextraSubNameFmt{##1}{##2} &
    \glslongextraSubDescFmt{##1}{##2} &
    \glslongextraSubSymbolFmt{##1}{##2}&
    \glslongextraSubLocationFmt{##1}{##2}{##3}%
    \tabularnewline
}%
\ifglsgnognogroupskip
    \renewcommand*{\glsgroupskip}{}%
\else
    \renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
}
\newcommand{\glslongextraNameSymDescHeader}{%

```



```

\glslongextraNameSymDescTabularHeader\endhead
\glslongextraNameSymDescTabularFooter\endfoot
}
\newcommand{\glslongextraNameSymDescTabularHeader}{%
\toprule
\glslongextraHeaderFmt\entryname &
\glslongextraHeaderFmt\symbolname &
\glslongextraHeaderFmt\descriptionname\tabularnewline
\midrule
}
\newcommand{\glslongextraNameSymDescTabularFooter}{%
\bottomrule
}
\newglossarystyle{long-name-sym-desc}{%
{%
\ifGlsLongExtraUseTabular
\renewenvironment{theglossary}{%
{%
\glslongextraSymSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{tabular}\@glslongextraTabularVAlign}{%
\expandonce\glslongextraNameAlign
\expandonce\glslongextraSymbolAlign
\expandonce\glslongextraDescAlign
}}%
\@glslongextra@begintab
}%
{%
\glslongextraNameSymDescTabularFooter
\end{tabular}}%
}%
\renewcommand*{\glossaryheader}{\glslongextraNameSymDescTabularHeader}%
\else
\renewenvironment{theglossary}{%
{%
\glspatchLToutput
\glslongextraSymSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{longtable}{%
\expandonce\glslongextraNameAlign
\expandonce\glslongextraSymbolAlign
\expandonce\glslongextraDescAlign
}}%
\@glslongextra@begintab
}%
{\end{longtable}}%
\renewcommand*{\glossaryheader}{\glslongextraNameSymDescHeader}%
\fi
\renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{3}{##1}}%
\renewcommand{\glossentry}[2]{%

```

```

\glslongextraNameFmt{##1} &
\glslongextraSymbolFmt{##1} &
\glslongextraDescFmt{##1}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
\glslongextraSubNameFmt{##1}{##2} &
\glslongextraSubSymbolFmt{##1}{##2} &
\glslongextraSubDescFmt{##1}{##2}\tabularnewline
}%
\ifglsgnogroupskip
\renewcommand*{\glsgroupskip}{}%
\else
\renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
}
\newcommand{\glslongextraNameSymDescLocationHeader}{%
\glslongextraNameSymDescLocationTabularHeader\endhead
\glslongextraNameSymDescLocationTabularFooter\endfoot
}
\newcommand{\glslongextraNameSymDescLocationTabularHeader}{%
\toprule
\glslongextraHeaderFmt\entryname &
\glslongextraHeaderFmt\symbolname &
\glslongextraHeaderFmt\descriptionname &
\glslongextraHeaderFmt\pagelistname\tabularnewline
\midrule
}
\newcommand{\glslongextraNameSymDescLocationTabularFooter}{%
\bottomrule
}
\newglossarystyle{long-name-sym-desc-loc}%
{%
\ifGlsLongExtraUseTabular
\renewenvironment{theglossary}%
{%
\glslongextraSymLocSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{tabular}[\glslongextraTabularVAlign]{%
\expandonce\glslongextraNameAlign
\expandonce\glslongextraSymbolAlign
\expandonce\glslongextraDescAlign
\expandonce\glslongextraLocationAlign
}}%
\@glslongextra@begintab
}%
{%
\glslongextraNameSymDescLocationTabularFooter
\end{tabular}%
}%
\renewcommand*{\glossaryheader}{\glslongextraNameSymDescLocationTabularHeader}%

```

```

\else
\renewenvironment{theglossary}%
{%
\glspatchLToutput
\glslongextraSymLocSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{longtable}{%
\expandonce\glslongextraNameAlign
\expandonce\glslongextraSymbolAlign
\expandonce\glslongextraDescAlign
\expandonce\glslongextraLocationAlign
}}%
\@glslongextra@begintab
}%
{\end{longtable}}%
\renewcommand*\{glossaryheader\}{\glslongextraNameSymDescLocationHeader}%
\fi
\renewcommand*\{glsgroupheading\}[1]{\glslongextraGroupHeading{4}{##1}}%
\renewcommand{\glossentry}[2]{%
\glslongextraNameFmt{##1} &
\glslongextraSymbolFmt{##1} &
\glslongextraDescFmt{##1} &
\glslongextraLocationFmt{##1}{##2}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
\glslongextraSubNameFmt{##1}{##2} &
\glslongextraSubSymbolFmt{##1}{##2} &
\glslongextraSubDescFmt{##1}{##2} &
\glslongextraSubLocationFmt{##1}{##2}{##3}\tabularnewline
}%
\ifglsnogroupskip
\renewcommand*\{glsgroupskip\}{}%
\else
\renewcommand*\{glsgroupskip\}{\glspenaltygroupskip}%
\fi
}
\newcommand{\glslongextraSymDescNameHeader}{%
\glslongextraSymDescNameTabularHeader\endhead
\glslongextraSymDescNameTabularFooter\endfoot
}
\newcommand{\glslongextraSymDescNameTabularHeader}{%
\toprule
\glslongextraHeaderFmt\symbolname &
\glslongextraHeaderFmt\descriptionname &
\glslongextraHeaderFmt\entryname\tabularnewline
\midrule
}
\newcommand{\glslongextraSymDescNameTabularFooter}{%
\bottomrule
}

```

```

\newglossarystyle{long-sym-desc-name}%
{%
  \ifGlsLongExtraUseTabular
  \renewenvironment{theglossary}%
  {%
    \glslongextraSymSetDescWidth
    \edef\@glslongextra@begintab{%
      \noexpand\begin{tabular}[\glslongextraTabularVAlign]{%
        \expandonce\glslongextraSymbolAlign
        \expandonce\glslongextraDescAlign
        \expandonce\glslongextraNameAlign
      }}%
    \@glslongextra@begintab
  }%
  {%
    \glslongextraSymDescNameTabularFooter
    \end{tabular}%
  }%
  \renewcommand*{\glossaryheader}{\glslongextraSymDescNameTabularHeader}%
\else
\renewenvironment{theglossary}%
{%
  \glspatchLToutput
  \glslongextraSymSetDescWidth
  \edef\@glslongextra@begintab{%
    \noexpand\begin{longtable}{%
      \expandonce\glslongextraSymbolAlign
      \expandonce\glslongextraDescAlign
      \expandonce\glslongextraNameAlign
    }%
  }%
  \@glslongextra@begintab
}%
  {\end{longtable}}%
  \renewcommand*{\glossaryheader}{\glslongextraSymDescNameHeader}%
\fi
\renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{3}{##1}}%
\renewcommand{\glossentry}[2]{%
  \glslongextraSymbolFmt{##1} &
  \glslongextraDescFmt{##1} &
  \glslongextraNameFmt{##1}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
  \glslongextraSubSymbolFmt{##1}{##2} &
  \glslongextraSubDescFmt{##1}{##2} &
  \glslongextraSubNameFmt{##1}{##2}\tabularnewline
}%
\ifglsgroupskip
  \renewcommand*{\glsgroupskip}{}%
\else
  \renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%

```

```

\fi
}
\newcommand{\glslongextraLocationSymDescNameHeader}{%
\glslongextraLocationSymDescNameTabularHeader\endhead
\glslongextraLocationSymDescNameTabularFooter\endfoot
}
\newcommand{\glslongextraLocationSymDescNameTabularHeader}{%
\toprule
\glslongextraHeaderFmt\pagelistname &
\glslongextraHeaderFmt\symbolname &
\glslongextraHeaderFmt\descriptionname &
\glslongextraHeaderFmt\entryname\tabularnewline
\midrule
}
\newcommand{\glslongextraLocationSymDescNameTabularFooter}{%
\bottomrule
}
\newglossarystyle{long-loc-sym-desc-name}%
{%
\ifGlsLongExtraUseTabular
\renewenvironment{theglossary}%
{%
\glslongextraSymLocSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{tabular}[\glslongextraTabularVAlign]{%
\expandonce\glslongextraLocationAlign
\expandonce\glslongextraSymbolAlign
\expandonce\glslongextraDescAlign
\expandonce\glslongextraNameAlign
}}%
\@glslongextra@begintab
}%
{%
\glslongextraLocationSymDescNameTabularFooter
\end{tabular}%
}%
\renewcommand*{\glossaryheader}{\glslongextraLocationSymDescNameTabularHeader}%
\else
\renewenvironment{theglossary}%
{%
\glspatchLToutput
\glslongextraSymLocSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{longtable}{%
\expandonce\glslongextraLocationAlign
\expandonce\glslongextraSymbolAlign
\expandonce\glslongextraDescAlign
\expandonce\glslongextraNameAlign
}}%
\@glslongextra@begintab

```

```

}%
{\end{longtable}}}%
\renewcommand*{\glossaryheader}{\glslongextraLocationSymDescNameHeader}%
\fi
\renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{4}{##1}}%
\renewcommand{\glossentry}[2]{%
  \glslongextraLocationFmt{##1}{##2} &
  \glslongextraSymbolFmt{##1} &
  \glslongextraDescFmt{##1} &
  \glslongextraNameFmt{##1}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
  \glslongextraSubLocationFmt{##1}{##2}{##3} &
  \glslongextraSubSymbolFmt{##1}{##2} &
  \glslongextraSubDescFmt{##1}{##2} &
  \glslongextraSubNameFmt{##1}{##2}\tabularnewline
}%
\ifglsgnogroupskip
  \renewcommand*{\glsgroupskip}{}%
\else
  \renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
}
\newcommand{\glslongextraDescSymNameHeader}{%
  \glslongextraDescSymNameTabularHeader\endhead
  \glslongextraDescSymNameTabularFooter\endfoot
}
\newcommand{\glslongextraDescSymNameTabularHeader}{%
  \toprule
  \glslongextraHeaderFmt\descriptionname &
  \glslongextraHeaderFmt\symbolname &
  \glslongextraHeaderFmt\entryname\tabularnewline
  \midrule
}
\newcommand{\glslongextraDescSymNameTabularFooter}{%
  \bottomrule
}
\newglossarystyle{long-desc-sym-name}%
{%
  \ifGlsLongExtraUseTabular
    \renewenvironment{theglossary}%
    {%
      \glslongextraSymSetDescWidth
      \edef\@glslongextra@begintab{%
        \noexpand\begin{tabular}[\glslongextraTabularVAlign]{%
          \expandonce\glslongextraDescAlign
          \expandonce\glslongextraSymbolAlign
          \expandonce\glslongextraNameAlign
        }}%
      \@glslongextra@begintab
    }
  \fi
}

```

```

}%
{%
  \glslongextraDescSymNameTabularFooter
  \end{tabular}%
}%
\renewcommand*{\glossaryheader}{\glslongextraDescSymNameTabularHeader}%
\else
\renewenvironment{theglossary}%
{%
  \glspatchLToutput
  \glslongextraSymSetDescWidth
  \edef\@glslongextra@begintab{%
    \noexpand\begin{longtable}{%
      \expandonce\glslongextraDescAlign
      \expandonce\glslongextraSymbolAlign
      \expandonce\glslongextraNameAlign
    }}%
  \@glslongextra@begintab
}%
{\end{longtable}}%
\renewcommand*{\glossaryheader}{\glslongextraDescSymNameHeader}%
\fi
\renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{3}{##1}}%
\renewcommand{\glossentry}[2]{%
  \glslongextraDescFmt{##1} &
  \glslongextraSymbolFmt{##1} &
  \glslongextraNameFmt{##1}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
  \glslongextraSubDescFmt{##1}{##2} &
  \glslongextraSubSymbolFmt{##1}{##2} &
  \glslongextraSubNameFmt{##1}{##2}\tabularnewline
}%
\ifglsgroupskip
  \renewcommand*{\glsgroupskip}{}%
\else
  \renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
}
\newcommand{\glslongextraLocationDescSymNameHeader}{%
  \glslongextraLocationDescSymNameTabularHeader\endhead
  \glslongextraLocationDescSymNameTabularFooter\endfoot
}
\newcommand{\glslongextraLocationDescSymNameTabularHeader}{%
  \toprule
  \glslongextraHeaderFmt\pagelistname &
  \glslongextraHeaderFmt\descriptionname &
  \glslongextraHeaderFmt\symbolname &
  \glslongextraHeaderFmt\entryname\tabularnewline
  \midrule

```

```

}
\newcommand{\glslongextraLocationDescSymNameTabularFooter}{%
\bottomrule
}
\newglossarystyle{long-loc-desc-sym-name}%
{%
\ifGlsLongExtraUseTabular
\renewenvironment{theglossary}%
{%
\glslongextraSymLocSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{tabular}[\glslongextraTabularVAlign]{%
\expandonce\glslongextraLocationAlign
\expandonce\glslongextraDescAlign
\expandonce\glslongextraSymbolAlign
\expandonce\glslongextraNameAlign
}}%
\@glslongextra@begintab
}%
{%
\glslongextraLocationDescSymNameTabularFooter
\end{tabular}%
}%
\renewcommand*{\glossaryheader}{\glslongextraLocationDescSymNameTabularHeader}%
\else
\renewenvironment{theglossary}%
{%
\glspatchLToutput
\glslongextraSymLocSetDescWidth
\edef\@glslongextra@begintab{%
\noexpand\begin{longtable}{%
\expandonce\glslongextraLocationAlign
\expandonce\glslongextraDescAlign
\expandonce\glslongextraSymbolAlign
\expandonce\glslongextraNameAlign
}}%
\@glslongextra@begintab
}%
{\end{longtable}}%
\renewcommand*{\glossaryheader}{\glslongextraLocationDescSymNameHeader}%
\fi
\renewcommand*{\glsgroupheading}[1]{\glslongextraGroupHeading{4}{##1}}%
\renewcommand{\glossentry}[2]{%
\glslongextraLocationFmt{##1}{##2} &
\glslongextraDescFmt{##1} &
\glslongextraSymbolFmt{##1} &
\glslongextraNameFmt{##1}\tabularnewline
}%
\renewcommand{\subglossentry}[3]{%
\glslongextraSubLocationFmt{##1}{##2}{##3} &

```



```

\glslongextraSubDescFmt{##1}{##2} &
\glslongextraSubSymbolFmt{##1}{##2} &
\glslongextraSubNameFmt{##1}{##2}\tabularnewline
}%
\ifglsgnogroupskip
\renewcommand*{\glsgroupskip}{}%
\else
\renewcommand*{\glsgroupskip}{\glspenaltygroupskip}%
\fi
}

```

9.6 Rollback v1.48 (glossary-topic-2021-11-22.sty)

Version 1.48 preserved for rollback.

```

\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{glossary-topic}[2021/11/22 v1.48 (NLCT)]
\RequirePackage{multicol}
\newglossarystyle{topic}{%
\renewenvironment{theglossary}%
{%
\glstopicInit
\def\glstopic@prechildren{}%
\def\glstopic@prevlevel{-1}%
}%
{\par}%
\renewcommand*{\glossaryheader}{}%
\renewcommand*{\glsgroupheading}[1]{%
\def\glstopic@prevlevel{-1}%
\glstopicGroupHeading{##1}%
}%
\renewcommand{\glossentry}[2]{%
\hangindent0pt\relax
\parindent\glstopicParIndent\relax
\glstopicItem{##1}{##2}%
\ifglshasdesc{##1}%
{%
\def\glstopic@prechildren{}%
}%
{%
\def\glstopic@prechildren{\nopagebreak}%
}%
}%
\renewcommand{\subglossentry}[3]{%
\ifnum\glstopic@prevlevel=0\relax\glstopic@prechildren\fi
\def\glstopic@prevlevel{##1}%
\begingroup
\glstopicAssignSubIndent{##1}%
\glstopicSubItem{##1}{##2}{##3}%
\par

```

```

\endgroup
}%
\renewcommand*{\glsgroupskip}{}%
}
\newcommand*{\glstopicGroupHeading}[1]{%
\newcommand*{\glstopicItem}[2]{%
\glspare\glstopicPreSkip\glspare\noindent
\glstopicMarker{#1}%
\glstopicTitleFont
{%
\glstryitem{#1}\glstarget{#1}{\glstopicTitle{#1}}%
}%
\ifglshasdesc{#1}%
{\glspare\nobreak\glstopicMidSkip\glspare\nobreak
\@afterheading\glstopicDesc{#1}\glspare\glstopicPostSkip}%
{\glspare\nobreak\glstopicPostSkip}%
\glstopicLoc{#1}{#2}%
}
\newcommand*{\glstopicMarker}[1]{%
\newcommand*{\glstopicTitle}[1]{\Glossentryname{#1}%
\ifglshassymbol{#1}{\space(\glossentrysymbol{#1})}{}}%
}
\newcommand*{\glstopicTitleFont}[1]{\textbf{\large #1}}
\newcommand*{\glstopicDesc}[1]{\Glossentrydesc{#1}\glspostdescription}
\newcommand*{\glstopicLoc}[2]{%
\newlength\glstopicParIndent
\setlength\glstopicParIndent{20pt}
\newlength\glstopicSubIndent
\setlength\glstopicSubIndent{20pt}
\newcommand{\glstopicInit}{%
\newcommand*{\glstopicAssignSubIndent}[1]{%
\par
\parindent\dimexpr#1\glstopicSubIndent-\glstopicSubIndent\relax
\glstopicAssignWidest{#1}%
\glstopicsubitemhangindent=\dimexpr\parindent+\glstopicwidest\relax
\hangindent\glstopicsubitemhangindent\relax
\everypar{\hangindent\glstopicsubitemhangindent\relax
\parindent\dimexpr\glstopicSubItemParIndent+\glstopicsubitemhangindent\relax}%
}
\newlength\glstopicsubitemhangindent
\newlength\glstopicSubItemParIndent
\glstopicSubItemParIndent\parindent
\newlength\glstopicwidest
\newcommand*{\glstopicAssignWidest}[1]{%
\ifcsundef{@glswidestlength\romannumeral#1}%
{%
\ifcsdef{@glswidestname\romannumeral#1}%
{%
\settowidth{\glstopicwidest}{%
\glstopicSubNameFont{\csuse{@glswidestname\romannumeral#1}}%

```

```

\glstopicSubItemSep
}%
}%
{\setlength{\glstopicwidest}{0pt}}%
\csedef{@glswidestlength\romannumeral#1}{\the\glstopicwidest}%
}%
{\setlength{\glstopicwidest}{\csuse{@glswidestlength\romannumeral#1}}}%
}
\newcommand*{\glstopicPreSkip}{\medskip}
\newcommand*{\glstopicMidSkip}{\smallskip}
\newcommand*{\glstopicPostSkip}{\smallskip}
\newcommand*{\glstopicSubItem}[3]{%
\glstopicSubItemBox{#1}{\glstopicSubNameFont{\glstryitem{#2}%
\glstarget{#2}{\glossentryname{#2}}}%
\glstopicSubItemSep
}%
\ifglshassymbol{#2}{(\glossentrysymbol{#2})\space}{}%
\ifglshasdesc{#2}%
{\glossentrydesc{#2}\glspostdescription\glstopicSubPreLocSep}{}%
\glstopicSubLoc{#2}{#3}%
}
\newcommand*{\glstopicSubItemSep}{\quad}
\newcommand*{\glstopicSubItemBox}[2]{%
\ifdim\glstopicwidest>0pt\relax\makebox[\glstopicwidest][l]{#2}\else#2\fi
}
\newcommand*{\glstopicSubNameFont}[1]{\textbf{#1}}
\newcommand*{\glstopicSubPreLocSep}{\space}
\newcommand*{\glstopicSubLoc}[2]{#2}
\newcommand*{\glstopicCols}{2}
\newcommand*{\glstopicColsEnv}{multicols}
\newglossarystyle{topicmcols}{%
\renewenvironment{theglossary}%
{%
\glstopicInit
\def\glstopic@prechildren{}%
\def\glstopic@postchildren{}%
\def\glstopic@prevlevel{-1}%
}%
{%
\ifnum\glstopic@prevlevel>0\relax\glstopic@postchildren\fi
\par
}%
\renewcommand*{\glossaryheader}{}%
\renewcommand*{\glsgroupheading}[1]{%
\ifnum\glstopic@prevlevel>0\relax\glstopic@postchildren\fi
\def\glstopic@prevlevel{-1}%
\glstopicGroupHeading{##1}%
}%
\renewcommand{\glossentry}[2]{%
\ifnum\glstopic@prevlevel>0\relax\glstopic@postchildren\fi

```

```

\def\glstopic@prevlevel{0}%
\hangindent0pt\relax
\parindent\glstopicParIndent\relax
\glstopicItem{##1}{##2}%
\ifnum\glstopicCols>1\relax
  \ifglshasdesc{##1}%
  {%
    \edef\glstopic@prechildren{%
      \noexpand\begin{\glstopicColsEnv}{\glstopicCols}%
    }%
  }%
  {%
    \edef\glstopic@prechildren{%
      \noexpand\nopagebreak
      \noexpand\begin{\glstopicColsEnv}{\glstopicCols}%
    }%
  }%
  \edef\glstopic@postchildren{\noexpand\end{\glstopicColsEnv}}%
\fi
}%
\renewcommand{\subglossentry}[3]{%
  \ifnum\glstopic@prevlevel=0\relax\glstopic@prechildren\fi
  \def\glstopic@prevlevel{##1}%
  \glstopicAssignSubIndent{##1}%
  \glstopicSubItem{##1}{##2}{##3}%
}%
\renewcommand*{\glsgroupskip}{}%
}

```

Change History

0.1 – 2015-11-22		\@Acrlong: added redefinition .	134
General: Initial experimental		\@Acrlongpl: added redefinition	136
release	2	\@Acrshort: added redefinition .	132
0.2 – 2015-11-30		\@Acrshortpl: added	
\Glsfmtshort: new	378	redefinition	133
\glsfmtshort: new	377	\@GLSdesc@: added redefinition .	120
\Glsfmtshortpl: new	378	\@GLSdescplural@: added	
\glsfmtshortpl: new	378	redefinition	121
short: switched inline full form		\@GLSfirst@: added redefinition	114
to short (long)	471	\@GLSfirstplural@: added	
0.3 – 2015-12-02		redefinition	117
\@ACRlong: added redefinition .	135	\@GLSname@: added redefinition .	119
\@ACRlongpl: added redefinition	136	\@GLSplural@: added	
\@ACRshort: added redefinition .	132	redefinition	116
\@ACRshortpl: added		\@GLSsymbol@: added	
redefinition	134	redefinition	122

\@GLSsymbolplural@: added		\@glsplural@: added	
redefinition	124	redefinition	115
\@GLStext@: added redefinition .	112	\@glssymbolplural@: added	
\@GLSuseri@: added redefinition	125	redefinition	123
\@GLSuserii@: added		\@glxtr@defaultnoglossarywarning:	
redefinition	126	new	201
\@GLSuseriii@: added		\@glxtr@field@linkdefs: new	111
redefinition	127	\@glxtr@insertdots: new . . .	327
\@GLSuseriv@: added		\@print@glossary: added	
redefinition	128	redefinition	198
\@GLSuserv@: added redefinition	130	\@glabbrvdefaultfont: renamed	
\@GLSuservi@: added		from \@abbrvdefaultfont . .	336
redefinition	131	\@glaccessdesc: new	248
\@GLsdesc@: added redefinition .	120	\@glaccessdescplural: new . .	249
\@GLsdescplural@: added		\@glaccessfirst: new	242
redefinition	121	\@glaccessfirstplural: new .	244
\@GLsfirst@: added redefinition	114	\@glaccesslong: new	253
\@GLsfirstplural@: added		\@glaccesslong: new	253
redefinition	117	\@glaccessname: new	238
\@GLsname@: added redefinition .	119	\@glaccessplural: new	241
\@GLsplural@: added		\@glaccessshort: new	251
redefinition	115	\@glaccessshort: new	250
\@GLssymbol@: added		\@glaccessshortpl: new	252
redefinition	122	\@glaccessshortpl: new	252
\@GLssymbolplural@: added		\@glaccesssymbol: new	245
redefinition	123	\@glaccesssymbolplural: new .	246
\@GLstext@: added redefinition .	113	\@glaccesstext: new	240
\@GLsuseri@: added redefinition	124	\@glentryfmt: added check for	
\@GLsuserii@: added		short	91
redefinition	126	\@glslongpltok: new	327
\@GLsuseriii@: added		\@glsshortpltok: new	327
redefinition	127	\@glxtr@newabbreviation: fixed	
\@GLsuseriv@: added		family name in \@setkeys . .	329
redefinition	128	\@glxtrdiscardperiod: added	
\@GLsuserv@: added redefinition	129	check for plural	324
\@GLsuservi@: added		\@GLSxtrlongpl: new	348
redefinition	130	\@GLsxtrlongpl: new	348
\@acrlong: added redefinition .	134	\@glxtrlongpl: new	347
\@acrlongpl: added redefinition	135	\@glxtrNoGlossaryWarning: new	25
\@acrshort: added redefinition .	132	\@glxtrpostlinkAddDescOnFirstUse:	
\@acrshortpl: added		new	323
redefinition	133	\@glxtrpostlinkAddSymbolOnFirstUse:	
\@gl@field@link: added		new	323
optional argument	98	\@glxtrpostlinkendsentence:	
\@glsdescplural@: added		new	323
redefinition	120	\@GLSxtrshortpl: new	346
\@glfirst@: added redefinition	113	\@GLsxtrshortpl: new	346
\@glfirstplural@: added		\@glxtrshortpl: new	345
redefinition	116	long-short-desc: fixed name to	
		use \@glstok	460

short-long-desc: fixed name to use \glslabeltok	462	renamed from \Glsentryfmtshort	378
0.4 – 2015-12-03		\glsfmtshort: changed to use \glsxtrtitleshort	377
\@glsxtr@doabbreviationsdef: added redefinition of \acronymtype	20	renamed from \Glsentryfmtshort	377
\Glsfmtshort: changed to use \Glsxtrshort	378	\Glsfmtshortpl: changed to use \Glsxtrtitleshortpl	378
\glsfmtshort: changed to use \glsxtrshort	377	renamed from \Glsentryfmtshortpl	378
\Glsfmtshortpl: changed to use \glsxtrshortpl	378	\glsfmtshortpl: changed to use \glsxtrtitleshortpl	378
\glsfmtshortpl: changed to use \glsxtrshortpl	378	renamed from \Glsentryfmtshortpl	378
\glsxtrifemptyglossary: new .	39	\Glsfmttext: new	379
\glsxtrnewnumber: added extra argument	299	\glsfmttext: new	379
\glsxtrnewsymbol: added extra argument	299	\glshasattribute: new	295
\MakeAcronymsAbbreviations: set the default type to \acronymtype	178	\glshascategoryattribute: new	294
\newterm: fixed name argument	299	\glsxtremsuffix: new	514
0.5 – 2015-12-07		\GlsXtrEnableEntryCounting: new	162
\@cGLS: new	168	\glsxtrifcounttrigger: new .	166
\@cGLS@: new	168	\glsxtrscfont: new	479
\@cGLSpl: new	168	\glsxtrscsuffix: new	479
\@cGLSpl@: new	168	\glsxtrsmfont: new	496
\@glsxtr@setentrycountunsetattr: new	163	\glsxtrsmsuffix: new	497
\cGLS: new	168	long-noshort-em: new	526
\cGLSformat: new	168	long-noshort-em-desc: new . .	531
\cGLSpl: new	168	long-noshort-sm: new	505
\cGLSplformat: new	168	long-noshort-sm-desc: new . .	507
\GlossariesExtraWarningNoLine: new	18	long-short-em: new	514
\glsenableentrycount: new . .	163	long-short-em-desc: new	516
\glsfirstabbrvdefaultfont: new	335	long-short-sm: new	497
\glsfirstlongdefaultfont: new	337	long-short-sm-desc: new	498
\Glsfmtfirst: new	380	short-em: new	523
\glsfmtfirst: new	380	short-em-desc: new	524
\Glsfmtfirstpl: new	380	short-em-footnote: new	535
\glsfmtfirstpl: new	380	short-em-long: new	518
\Glsfmtplural: new	379	short-em-long-desc: new	520
\glsfmtplural: new	379	short-em-postfootnote: new .	537
\Glsfmtshort: changed to use \Glsxtrtitleshort	378	short-sc-footnote: new	491
		short-sc-postfootnote: new .	494
		short-sm: new	501
		short-sm-desc: new	502
		short-sm-footnote: new	508
		short-sm-long: new	499
		short-sm-long-desc: new	500
		short-sm-postfootnote: new .	511

0.5.1 – 2015-12-02		
\Glsaccessstext: new	240	
0.5.1 – 2015-12-07		
General: removed		
\ifglstruseuchead	365	
\@glstr@doaccsupp: new	24	
footnote: switch off regular		
attribute if set	464	
\Glsaccessdesc: new	248	
\Glsaccessdescplural: new	250	
\Glsaccessfirst: new	243	
\Glsaccessfirstplural: new	244	
\Glsaccessname: new	239	
\Glsaccessplural: new	242	
\Glsaccesssymbol: new	246	
\Glsaccesssymbolplural: new	247	
\Glsxtrheadfirst: now uses		
headuc attribute	371	
\glxtrheadfirst: now uses		
headuc attribute	371	
\Glsxtrheadfirstplural: now		
uses headuc attribute	372	
\glxtrheadfirstplural: now		
uses headuc attribute	372	
\Glsxtrheadplural: now uses		
headuc attribute	370	
\glxtrheadplural: now uses		
headuc attribute	370	
\Glsxtrheadshort: now uses		
headuc attribute	366	
\glxtrheadshort: now uses		
headuc attribute	365	
\Glsxtrheadshortpl: now uses		
headuc attribute	367	
\glxtrheadshortpl: now uses		
headuc attribute	366	
\Glsxtrheadtext: now uses		
headuc attribute	369	
\glxtrheadtext: now uses		
headuc attribute	369	
long-short: switch off regular		
attribute if set	459	
long-short-desc: switch off		
regular attribute if set	460	
long-short-sc-desc: switch off		
regular attribute if set	481	
postfootnote: switch off regular		
attribute if set	467	
short-em-footnote: switch off		
regular attribute if set	535	
short-em-footnote-desc: switch		
off regular attribute if set	537	
short-long: switch off regular		
attribute if set	461	
short-long-desc: switch off		
regular attribute if set	463	
short-postfootnote-desc:		
switch off regular attribute if		
set	469	
short-sc-footnote: switch off		
regular attribute if set	491	
short-sc-footnote-desc: switch		
off regular attribute if set	493	
short-sm-footnote: switch off		
regular attribute if set	509	
short-sm-footnote-desc: switch		
off regular attribute if set	511	
0.5.2 – 2015-12-08		
General: fixed typo in		
glossaries-accsupp and tidied		
up code to use just one		
\@ifpackageloaded	238	
removed \glstrabbrvfmt	349	
\@GLSdesc@: added accessibility		
support	120	
\@GLSdescplural@: added		
accessibility support	121	
\@GLSfirst@: added accessibility		
support	114	
\@GLSfirstplural@: added		
accessibility support	117	
\@GLSname@: added accessibility		
support	119	
\@GLSplural@: added accessibility		
support	116	
\@GLSsymbol@: added accessibility		
support	122	
\@GLSsymbolplural@: added		
accessibility support	124	
\@GLStext@: added accessibility		
support	112	
\@GLSdesc@: added accessibility		
support	120	
\@GLSdescplural@: added		
accessibility support	121	
\@GLSfirst@: added accessibility		
support	114	
\@GLSfirstplural@: added		
accessibility support	117	

\@Glsname@: add accessibility support	119	\GLSaccessshort: new	251, 283
\@Glsplural@: added accessibility support	115	\GLSaccessshortpl: new	253, 284
\@Glsymbol@: added accessibility support	122	\GLSaccesssymbol: new	246, 280
\@Glsymbolplural@: added accessibility support	123	\GLSaccesssymbolplural: new	247, 281
\@Glstext@: added accessibility support	113	\GLSaccessstext: new	241, 277
\@glsdesc@: added accessibility support	119	\glsentryfmt: moved	
\@glsdescplural@: added accessibility support	120	\glssetabbrvfmt from	
\@glsfirst@: added accessibility support	113	\glsxtrabbrvfmt to here	91
\@glsfirstplural@: added accessibility support	116	\GLSXtrEnableInitialTagging: new	318
\@glsname@: added accessibility support	118	\glsxtrfieldtitlecase: new	300
\@glsplural@: added accessibility support	115	\GLSXtrFormatLocationList: new	89
\@glsymbol@: added accessibility support	122	\glsxtrnewabbrevpresetkeyhook: new	332
\@glsymbolplural@: added accessibility support	123	\glsxtrtagfont: new	320
\@glstext@: added accessibility support	112	\KV@printgloss@nonumberlist: added	90
\@glsxtr@activate@initialtagging: new	320	\mfu@checkword@do: added	319
\@glsxtr@do@titlecaps@warn: new	320	\setabbreviationstyle: added	
\@glsxtr@tag: new	320	check for post-definition style switch	355
\glossaryentrynumbers: added	88	0.5.3 – 2015-12-09	
\Glossentrydesc: added	317	General: removed	
\Glossentryname: added	305	\GLSXtrNoGlsWarningNoAutoMakeMain	200
\Glossentrysymbol: added	317	\@glsxtr@autoindex@at: new	315
\GLSaccessdesc: new	249, 282	\@glsxtr@autoindex@encap: new	316
\GLSaccessdescplural: new	250, 282	\@glsxtr@autoindex@esc: new	316
\GLSaccessfirst: new	243, 279	\@glsxtr@autoindex@level: new	316
\GLSaccessfirstplural: new	245, 279	\@glsxtr@autoindex@setname: new	314
\GLSaccesslong: new	254, 285	\@glsxtr@doabbreviationsdef: new	19
\GLSaccesslongpl: new	255, 285	\glsdescwidth: added	88
\Glsaccesslongpl: new	255	\glspagelistwidth: added	88
\glsaccesslongpl: new	254	\glsxtrdoautoindexname: new	313
\GLSaccessname: new	239, 276	\glsxtrpostnamehook: new	308
\GLSaccessplural: new	242, 278	\if@glsxtr@format@override: new	312
		\ProvidesGlossariesExtraLang: new	438
		\RequireGlossariesExtraLang: new	437
		0.5.4 – 2015-12-15	
		\@@newglossaryentry@defunitcounters: new	169

\@GLSxtr@p@acrlong@: new ...	154	\@glxstr@unitcountlist: new .	169
\@GLSxtr@p@acrlongpl@: new .	154	\@glxstrpl: new	85
\@GLSxtr@p@acrshort@: new ..	153	\@newglossaryentryposthook:	
\@GLSxtr@p@acrshortpl@: new .	153	added empty see value if not	
\@GLSxtr@p@long@: new	153	set and added ‘see’ to field	
\@GLSxtr@p@longpl@: new	153	key map	67
\@GLSxtr@p@plural@: new	152	\@sGlsXtrEnableOnTheFly: new	83
\@GLSxtr@p@short@: new	152	\cGlsformat: added	169
\@GLSxtr@p@shortpl@: new ...	153	\cglformat: added	169
\@GLSxtr@p@text@: new	151	\cGlsplformat: added	169
\@GlsXtrEnableOnTheFly: new .	84	\cglspformat: added	169
\@Glsxtr: new	85	\gl:disablehyper: added	150
\@Glsxtr@p@acrlong@: new ...	154	\gl:donohyperlink: added ...	150
\@Glsxtr@p@acrlongpl@: new .	154	\gl:enableentryunitcount:	
\@Glsxtr@p@acrshort@: new ..	153	new	171
\@Glsxtr@p@acrshortpl@: new .	153	\gl:hasattribute: added check	
\@Glsxtr@p@long@: new	153	for entry’s existence	295
\@Glsxtr@p@longpl@: new	153	\gl:sifattribute: added check	
\@Glsxtr@p@plural@: new	152	for entry’s existence	295
\@Glsxtr@p@short@: new	152	\gl:postlinkhook: added	
\@Glsxtr@p@shortpl@: new ...	152	existence check	321
\@Glsxtr@p@text@: new	151	\Glsxtr: new	84
\@Glsxtrpl: new	85	\glxtr: new	84
\@alt@glshyp@opt: new	145	\glxtrcat: new	84
\@glsh@alt@hyp@opt: new	145	\glxtrdohyperlink: added ...	148
\@glsh@alt@hyp@opt@char: new .	145	\glxtrdowrglossaryhook: new	145
\@glsh@alt@hyp@opt@keys: new .	146	\GlsXtrEnableEntryUnitCounting:	
\@glsh@increment@currunitcount:		new	174
new	170	\GlsXtrEnableOnTheFly: new .	83
\@glsh@local@increment@currunitcount:		\Glsxtrpl: new	85
new	170	\glxtrpl: new	85
\@glsh@setdefault@glshlink@opts:		\glxtrpostlocalreset: new .	162
new	141	\glxtrpostlocalunset: new .	161
\@glxtr: new	84	\glxtrpostreset: new	162
\@glxtr@addunitcounter: new	169	\glxtrpostunset: new	159
\@glxtr@currunitcount: new .	171	\glxtrprotectlinks: new ...	151
\@glxtr@ifunitcounter: new .	170	\GlsXtrSetAltModifier: new .	146
\@glxtr@p@acrlong@: new ...	154	\GlsXtrSetDefaultGlsOpts:	
\@glxtr@p@acrlongpl@: new .	154	new	143
\@glxtr@p@acrshort@: new ..	153	\glxtrstarflywarn: new	84
\@glxtr@p@acrshortpl@: new .	153	\GlsXtrWarning: new	86
\@glxtr@p@long@: new	153	\MakeAcronymsAbbreviations:	
\@glxtr@p@longpl@: new	153	now disables	
\@glxtr@p@plural@: new	152	\setacronymstyle	178
\@glxtr@p@short@: new	152	1.0 – 2016-01-24	
\@glxtr@p@shortpl@: new ...	152	\@glxtr@autoindexcrossrefs:	
\@glxtr@p@text@: new	151	new	17
\@glxtr@prevunitcount: new .	171	\@glxtr@idx@displaynumberlist:	
\@glxtr@setentryunitcountunsetattr:		new	190
new	175		

\@glxtr@idx@entrynumberlist:	1.03 – 2016-04-27
new	192
\@glxtr@noidx@displaynumberlist:	\@GLSfirstplural@: bug fix:
new	misspelt cs name 117
\@glxtr@noidx@entrynumberlist:	\@GLSplural@: fixed bug
new	\@GLSplural@ should be
\@glxtr@noidx@numberlistloop:	redefined not \@GLSplural 116
new	\@GLSfirstplural@: bug fix:
\@glxtr@reg@glosslist: new .	misspelt cs name 117
\makeglossaries: new	\@GLSplural@: fixed bug
1.01 – 2016-02-02	\@GLSplural@ should be
\glxtrdiscardperiod: added	redefined not \@GLSplural 115
check for first use	\@GLSplural@: fixed bug
short-desc: fixed typo in	\@GLSplural@ should be
\glxtrinlinefullformat	redefined not \@GLSplural 115
and added missing second	\glxtrtitlelongpl: bug fix:
argument	changed \glxtrlong to
1.02 – 2016-04-25	\glxtrlongpl 374
\@glxtr@current@style: new .	\glxtrtitleshortpl: bug fix:
\Glsfmtfull: new	changed \glxtrshort to
\Glsfmtfull: new	\glxtrshortpl 366
\Glsfmtfullpl: new	1.04 – 2015-04-30
\Glsfmtfullpl: new	short-em-footnote: renamed
\Glsfmtlong: new	from “footnote-em” 535
\Glsfmtlong: new	1.04 – 2016-05-02
\Glsfmtlongpl: new	\@@glxtrpostloctag: new . . . 90
\Glsfmtlongpl: new	\@GLSdesc@: set abbreviation and
\Glsxrheadfull: new	regular format 120
\Glsxrheadfull: new	\@GLSdescplural@: set
\Glsxrheadfullpl: new	abbreviation and regular
\Glsxrheadfullpl: new	format 121
\Glsxrheadlong: new	\@GLSfirst@: set abbreviation
\Glsxrheadlong: new	format 114
\Glsxrheadlongpl: new	\@GLSfirstplural@: set
\Glsxrheadlongpl: new	abbreviation and regular
\Glsxrtitlefull: new	format 117
\Glsxrtitlefull: new	\@GLSname@: set abbreviation and
\Glsxrtitlefullpl: new	regular format 119
\Glsxrtitlefullpl: new	\@GLSplural@: set abbreviation
\Glsxrtitlelong: new	and regular format 116
\Glsxrtitlelong: new	\@GLSsymbol@: set regular
\Glsxrtitlelongpl: new	format 122
\Glsxrtitlelongpl: new	\@GLSsymbolplural@: set regular
\ifglxtrinsertinside: new .	format 124
postfootnote: added redef of	\@GLStext@: set abbreviation and
\glxtrsetupfulldefs . . .	regular format 112
short-postfootnote-desc:	\@GLSuseri@: set regular format 125
added redef of	\@GLSuserii@: set regular
\glxtrsetupfulldefs . . .	format 126
stylemods: new	\@GLSuseriii@: set regular
	format 127

<code>\@GLSuseriv@</code> : set regular format	128	<code>\@glsplural@</code> : set abbreviation and regular format	115
<code>\@GLSuseriv@</code> : set regular format	130	<code>\@glsymbol@</code> : set regular format	122
<code>\@GLSuservi@</code> : set regular format	131	<code>\@glsymbolplural@</code> : set regular format	123
<code>\@Glsdesc@</code> : set abbreviation and regular format	120	<code>\@glstext@</code> : set abbreviation and regular format	112
<code>\@Glsdescplural@</code> : set abbreviation and regular format	121	<code>\@glsxtr@deprecated@abbrstyle</code> : new	359
<code>\@Glsfirst@</code> : set abbreviation and regular format	114	<code>\@glsxtr@do@style</code> : new	26
<code>\@Glsfirstplural@</code> : set abbreviation and regular format	117	<code>\@glsxtr@doloctag</code> : new	90
<code>\@Glsname@</code> : set abbreviation and regular format	119	<code>\@glsxtr@idx@entrynumberlist</code> : switched from <code>\let</code> to <code>\newcommand</code>	192
<code>\@Glsplural@</code> : set abbreviation and regular format	115	<code>\@glsxtr@pagetag</code> : new	90
<code>\@Glsymbol@</code> : set regular format	122	<code>\@glsxtr@pagetag</code> : new	90
<code>\@Glsymbolplural@</code> : set regular format	123	<code>\@glsxtr@preloctag</code> : new	90
<code>\@Glstext@</code> : set abbreviation and regular format	113	<code>\@glsxtr@postloctag</code> : new	90
<code>\@Glsuseri@</code> : set regular format	124	<code>\@glsxtr@preloctag</code> : new	89, 90
<code>\@Glsuserii@</code> : set regular format	126	<code>\glossentrydesc</code> : added glossdescfont attribute check	301
<code>\@Glsuseriii@</code> : set regular format	127	<code>\Glossentryname</code> : added glossnamefont attribute check	305
<code>\@Glsuseriv@</code> : set regular format	128	<code>\glossentryname</code> : added glossnamefont attribute check	302
<code>\@Glsuseriv@</code> : set regular format	129	moved post name hook inside condition	305
<code>\@Glsuservi@</code> : set regular format	130	<code>\glsabbrvmfont</code> : new	514
<code>\@gls@preglossaryhook</code> : added check for entry's existence .	320	<code>\glsabbrvuserfont</code> : new	542
<code>\@glsdesc@</code> : set abbreviation and regular format	119	<code>\glsfirstabbrvmfont</code> : new	514
<code>\@glsdescplural@</code> : set abbreviation and regular format	120	<code>\glsfirstabbrvuserfont</code> : new	542
<code>\@glsfirst@</code> : set abbreviation and regular format	113	<code>\glsfirstlongemfont</code> : new	514
<code>\@glsfirstplural@</code> : set abbreviation and regular format	116	<code>\glsfirstlonguserfont</code> : new	542
<code>\@glsname@</code> : set abbreviation and regular format	118	<code>\glsifnotregularcategory</code> : new	297
		<code>\glslongdefaultfont</code> : new	336
		<code>\glslongemfont</code> : new	514
		<code>\glslongfont</code> : new	336
		<code>\glslonguserfont</code> : new	542
		<code>\glsxtrassignfieldfont</code> : new	111
		<code>\GlsXtrEnablePreLocationTag</code> : new	89
		<code>\glsxtrfirstscfont</code> : new	479
		<code>\glsxtrfirstsmfont</code> : new	497
		<code>\glsxtrlongshortdescsort</code> : new	459

\glstrpostnamehook: added		
category check	308	
\glstrregularfont: new	91	
\glstruserfield: new	540	
\glstruserparen: new	540	
\glstrusersuffix: new	542	
\GlsXtrWarnDeprecatedAbbrStyle:		
new	359	
\letabbreviationstyle: new	359	
long-em-noshort-em: new	528	
long-em-noshort-em-desc: new	533	
long-em-short-em: new	516	
long-em-short-em-desc: new	518	
long-noshort: new	478	
long-noshort-desc: new	477	
long-noshort-em: renamed from		
“long-em”	526	
long-noshort-em-desc: renamed		
from “long-desc-em”	531	
long-noshort-sc: renamed from		
“long-sc”	487	
long-noshort-sc-desc: renamed		
from “long-desc-sc”	489	
long-noshort-sm: renamed from		
“long-sm”	505	
long-noshort-sm-desc: renamed		
from \long-desc-sm	507	
long-short-user: new	542	
long-short-user-desc: new	550	
\newabbreviationstyle: bug fix:		
corrected test for existence	357	
\renewabbreviationstyle: new	358	
short-em-long-em: new	520	
short-em-long-em-desc: new	522	
short-em-nolong: new	524	
short-em-nolong-desc: new	526	
short-em-postfootnote:		
renamed from		
“postfootnote-em”	537	
short-footnote: new	466	
short-long-user: new	551	
short-long-user-desc: new	552	
short-nolong: new	472	
short-nolong-desc: new	474	
short-postfootnote: new	469	
short-sc-footnote: renamed		
from “footnote-sc”	491	
short-sc-nolong: new	485	
short-sc-nolong-desc: new	486	
short-sc-postfootnote:		
renamed from		
“postfootnote-sc”	494	
short-sm-footnote: renamed		
from “footnote-sm”	508	
short-sm-nolong: new	502	
short-sm-nolong-desc: new	504	
short-sm-postfootnote:		
renamed from		
“postfootnote-sm”	511	
style: new	26	
1.05 – 2016-06-10		
\eglssetwidest: new	686	
\glsFindWidestAnyName: new	692	
\glsFindWidestAnyNameLocation:		
new	697	
\glsFindWidestAnyNameSymbol:		
new	695	
\glsFindWidestAnyNameSymbolLocation:		
new	696	
\glsFindWidestLevelTwo: new	693	
\glsFindWidestUsedAnyName:		
new	691	
\glsFindWidestUsedAnyNameLocation:		
new	697	
\glsFindWidestUsedAnyNameSymbol:		
new	694	
\glsFindWidestUsedAnyNameSymbolLocation:		
new	695	
\glsFindWidestUsedLevelTwo:		
new	692	
\glsFindWidestUsedTopLevelName:		
new	691	
\glsfirstlongfootnotefont:		
new	463	
\glsgetwidestname: new	690	
\glsgetwidestsubname: new	691	
\glslongfootnotefont: new	463	
\glstrAltTreeIndent: new	688	
\glstrAltTreeInit: new	689	
\glstrAltTreePar: new	689	
\glstrAltTreeSetHangIndent:		
new	698	
\glstrAltTreeSetSubHangIndent:		
new	698	
\glstrAltTreeSubSymbolDescLocation:		
new	689	
\glstrAltTreeSymbolDescLocation:		
new	688	

\glxstrComputeTreeIndent:			
new	698	\glxstrabbrvfootnote: new	463
\glxstrComputeTreeSubIndent:		\glxstrchecknohyperfirst:	
new	698	new	113
\glxstrtreetopindent: new	689	\glxstrfieldtitlecasecs: new	300
short-em-long: fixed incorrect		\glxstrifinmark: new	362
font used by long form	519	\GLSxtrp: new	157
\xglsssetwidest: new	687	\Glsxtrp: new	157
1.06 – 2016-06-18		\glxtrp: new	156
General: disabled docdef key at		\glxtrsetpopts: new	154
the start of the document	38	long-short-desc: added missing	
docdef option changed to		text key	460
choice	16	fixed misspelling of	
\@glsoifexistsorwarn: new	17	\glsabbrvfont	460
\@glxstr@docdefval: new	16	postfootnote: removed	
\@glxstr@usesee: new	68	\footnote from first keys	467
\glxstr@usesee: new	68	switched from	
\glxstrusesee: new	68	\glsfirstlongfont to	
\glxstruseseeformat: new	68	\glsfirstlongfootnotefont	468
\if@glxstrdocdefrestricted:		\RestoreAcronyms: modified	
new	17	\@gls@link@checkfirsthyper	
1.07 – 2016-08-15		to set	
\@@glxtrp: new	154	\glxstrifwasfirstuse	179
\@GLSfirst@: added check for		short-long-desc: added text	
nohyperfirst attribute	114	key	462
\@GLSfirstplural@: added check		fixed misspelling of	
for nohyperfirst attribute	118	\glsabbrvfont in plural key	463
\@GLSxtrp: new	155	1.08 – 2016-12-13	
\@GLSfirst@: added check for		\@@glxstr@record: new	6
nohyperfirst attribute	114	\@GLS@: added \@glxstr@record	100
\@GLSfirstplural@: added check		\@GLSpl@: added	
for nohyperfirst attribute	117	\@glxstr@record	100
\@Glsxtrp: new	155	\@Gls@: added \@glxstr@record	99
\@gls@preglossaryhook: added		\@GLspl@: added	
\glossxtrsetpopts	321	\@glxstr@record	99
\@glsfirst@: added check for		\@gls@: added \@glxstr@record	99
nohyperfirst attribute	113	\@gls@@link: added	
\@glsfirstplural@: added check		\@glxstr@record	100
for nohyperfirst attribute	117	\@gls@field@link: added	
\@glxstrinmark: new	362	\@glxstr@record	98
\@glxstrnotinmark: new	362	\@gls@saveentrycounter: new	36
\@glxtrp: new	155	\@glsdisp: added	
\@glxtrp@opt: new	154	\@glxstr@record	100
footnote: changed first forms to		\@GLspl@: added	
use		\@glxstr@record	99
\glsfirstlongfootnotefont	464	\@glxstr@dorecord: new	8
\glossxtrsetpopts: new	154	\@glxstr@err@undefaction: new	4
\glsps: new	157	\@glxstr@record: new	5
\glspt: new	157	\@glxstr@warn@onexistsordo:	
\glxstr@entry@p: new	156	new	4

\@glxtr@warn@undefaction:	\@glxtr@s@newignoredglossary:
new 4	new 62
\@print@unsrt@glossary: new . 214	\@glxtr@shortcutsval: new . . 206
\@gladd: added	\@glxtr@texencoding: new . . 205
\@glxtr@record 109	\@glxtr@writefields: new . . 206
\@glsoifexists: now defines	\@GlsXtrLoadResources: new . . 205
\@glslabel 65	\@glxtrpageref: new 57
\@glxtr@@do@wrglossary: new . 36	\@glxtrresourcefile: changed
\@glxtr@addloclistfield: new 11	extension to .glstex 203
\@glxtr@indexonly@saveentrycounter:	\@newignoredglossary: added
new 11	starred version 61
\@glxtr@record: new 208	1.12 – 2017-02-03
\@glxtr@resource: new 205	General: added target key to
\@glxtr@saveentrycounter: new 36	printgloss family 188
\@glxtr@setup@record: new . . 11	\@@glxtr@recordcounter: new 10
\@glxtrassignfieldfont: added	\@Gls@preglossaryhook: check
check for existence 111	for definition 320
\@glxtrresourcefile: new . . 203	\@glxtr@counterrecordhook:
\@printunsrtglossaries: new . 214	new 208
\@printunsrtglossary: new . . 214	\@glxtr@display@loc: new . . 195
record: added record package	\@glxtr@docounterrecord:
option 14	new 209
1.09 – 2016-12-16	\@glxtr@longnewglossaryentry:
\@glxtr@gettype: new 190	new 61
\@glxtr@mixed@assign@sortkey:	\@glxtr@noop@recordcounter:
new 190	new 10
\@printglossary: redefined to	\@glxtr@op@recordcounter:
save options 187	new 11
\@glxtr@makeglossaries: new . 190	\@glxtr@provide@storagekey:
1.10 – 2016-12-17	new 40
\@GLSpl@: fixed bug caused by	\@glxtr@resourcefile: added
typo in command name . . . 100	catcode change for @ 204
1.11 – 2017-01-19	\@glxtr@s@longnewglossaryentry:
\@glxtr@do@redef@for@gl@sentries:	new 60
new 4	\@glxtr@entryfmt: new 42
\@glxtr@noidx@do: new 224	\@glxtr@indexaliased: new . . 142
\@glxtr@redef@for@gl@sentries:	\@glxtr@setaliasnoindex: new 142
new 4	\@newglossaryentryposthook:
\@glxtr@shortcutsval: new . . 23	added check for alias key . . . 77
\@glxtr@unsrt@getgrouptitle:	\@no@glxtr@indexaliased: new 142
new 222	\@printunsrtglossary: new . . 214
\@print@noidx@glossary: added	\@apptoglossarypreamble: new . 57
redefinition 194	\@csGlsXtrLetField: new 50
\@glxtr@addloclistfield:	\@eGlsXtrSetField: new 51
added group key 12	\@gGlsXtrSetField: new 50
added location key 11	\@glsnoidxdisplayloc: added
\@glxtr@fields: new 205	redefinition 195
\@glxtr@linkprefix: new 206	\@glsettoctitle: added patch . 63
\@glxtr@org@newignoredglossary:	\@glxtr@counterrecord: new . 208
new 61	\@glxtr@langtag: new 206

\glsxtr@newabbreviation: new	328	\glsxtrsetfieldifexists: new	50
\glsxtr@org@newignoredglossary:		\glsxtrunsrtdo: new	223
Added check for existence	61	\Glsxtrusefield: new	49
\glsxtr@pluralsuffixes: new	206	\glsxtrusefield: new	49
\glsxtr@provideignoredglossary:		long-postshort-user: new	543
new	63	long-postshort-user-desc:	
\glsxtr@s@newignoredglossary:		new	547
Added check for existence	62	\longnewglossaryentry: added	
\glsxtr@s@provideignoredglossary:		starred version	60
new	64	postdot: new	18
\glsxtrabbrvpluralsuffix:		\preglossarypreamble: new	58
new	337	\print@noop@unsrtglossaryunit:	
\glsxtralias: new	77	new	222
\glsxtrcopytoglossary: new	64	\print@op@unsrtglossaryunit:	
\glsxtrdeffield: new	49	new	221
\glsxtrdisplayendloc: new	196	\printunsrtglossary: added	
\glsxtrdisplayendlochook:		starred form	214
new	196	\printunsrtglossaryhandler:	
\glsxtrdisplaysingleloc: new	196	new	221
\glsxtrdisplaystartloc: new	196	\printunsrtglossaryunit: new	11
\glsxtrdohyperlink: added		\printunsrtglossaryunitsetup:	
check for alias field	149	new	221
\glsxtrdeffield: new	49	\provideignoredglossary: new	63
\glsxtrentryfmt: new	42	\s@glsxtr@provide@storagekey:	
\glsxtrfielddolistloop: new	44	new	40
\glsxtrfieldforlistloop: new	44	\s@printunsrtglossary: new	214
\glsxtrfieldifinlist: new	44	short-postlong-user: new	548
\glsxtrfieldlistadd: new	43	short-postlong-user-desc:	
\glsxtrfieldlistadd: new	43	new	550
\glsxtrfieldlistgadd: new	43	\xGlsXtrSetField: new	51
\glsxtrfieldlistxadd: new	43	1.13 – 2017-02-07	
\glsxtrfieldxifinlist: new	44	\@glsdisp: removed	
\glsxtrfmt: new	41	\@glsxtr@org@glsdisp	100
\GlsXtrFmtDefaultOptions: new	41	\glsxtrsetaliasnoindex:	
\GlsXtrFmtField: new	41	switched to	
\glsxtrifkeydefined: new	39	\providecommand	142
\glsxtrindexaliased: new	143	1.14 – 2017-04-18	
\GlsXtrLetField: new	50	General: added \glsadd option	
\GlsXtrLetFieldToField: new	50	theHvalue	109
\GlsXtrLoadResources: removed		added \glsadd option	
restriction on only one per		thevalue	109
document	205	\@gls@link: added redefinition	106
\glsxtrlocrangefmt: new	196	\@gls@noidx@getgrouptitle:	
\glsxtrpostlongdescription:		new	192
new	61	\@gls@removespaces: new	197
\glsxtrprovidestoragekey: new	40	\@glsxtr@do@automake@err:	
\GlsXtrRecordCounter: new	208	new	208
\glsxtrresourcecount: new	204	\@glsxtr@org@gloautosee: new	35
\glsxtrsetaliasnoindex: new	142	\@glsxtr@record: added third	
\GlsXtrSetField: new	50	arg	5

<code>\@glxtr@recordsee</code> : new	11	<code>short-postlong-user</code> : fixed	
<code>\gl:disablehyper</code> : added		spelling of <code>\gl:abbrvfont</code> .	548
redefinition	150	<code>short-postlong-user-desc</code> :	
<code>\gl:enableentrycount</code> : fixed		fixed spelling of	
assignment of <code>\@cGls@</code> . . .	164	<code>\gl:abbrvfont</code>	550
<code>\gl:enableentryunitcount</code> :		1.16 – 2017-06-15	
fixed assignment of <code>\@cGls@</code>	173	<code>\@glo@autosee</code> : added	
<code>\gl:navigation</code> : new	194	redefinition	35
<code>\gl:xtr@org@getgrouptitle</code> :		<code>\@gl:noidx@getgrouptitle</code> :	
new	193	fixed bug	192
<code>\gl:xtr@recordsee</code> : new	5	<code>\@gl:xtr@addunusedxrefs</code> :	
<code>\gl:xtr@writefields</code> : added		added check for <code>seealso</code> field .	78
check for <code>automake</code>	207	<code>\@gl:xtr@checkgroup</code> : use	
<code>\gl:xtrdisplayendloc</code> : added		<code>\csuse</code> instead of <code>\csname</code> .	223
check for empty format . . .	196	<code>\@gl:xtr@dorecordnodefer</code> : new	9
<code>\gl:xtrgetgrouptitle</code> : new . .	193	<code>\@gl:xtr@record@only@setup</code> :	
<code>\gl:xtrinitwrgloss</code> : new	101	added check for	
<code>\gl:xtrlocationhyperlink</code> :		<code>\@gl:setupsort@none</code>	13
new	197	<code>\@gl:xtr@unsrt@gloss@init</code> :	
<code>\gl:xtrsetgrouptitle</code> : new . .	194	corrected misspelt command	216
<code>\gl:xtrsupphypernumber</code> : new .	197	<code>\@printunsrt@glossary@handler</code> :	
<code>\ifgl:xtrwrglossbefore</code> : new .	101	new	221
1.15 – 2017-05-10		<code>autoseeindex</code> : new	17
<code>\@gl:xtr@dorecord</code> : corrected		<code>\gl:checkseeallowed</code> : added	
premature expansion of		redefinition	35
<code>\@gl:locref</code>	8	<code>\gl:xtr@writefields</code> : added	
footnote: fixed spelling of		<code>\providecommand</code> lines . . .	206
<code>\gl:abbrvfont</code>	464	<code>\gl:xtrautoindex</code> : new	314
long-em-short-em: fixed spelling		<code>\gl:xtrautoindexassignsort</code> :	
of <code>\gl:abbrvfont</code>	517	new	314
long-postshort-user: fixed		<code>\gl:xtrautoindexentry</code> : new .	314
spelling of <code>\gl:abbrvfont</code> .	544	<code>\gl:xtrindexseealso</code> : new . . .	74
long-postshort-user-desc:		<code>\gl:xtrseealso</code> labels: new . .	77
fixed spelling of		<code>\gl:xtrseelist</code> : new	72
<code>\gl:abbrvfont</code>	547	<code>\gl:xtruseealso</code> : new	72
long-short: fixed spelling of		<code>\gl:xtruseealsoformat</code> : new	72
<code>\gl:abbrvfont</code>	458	<code>\seealso</code> name: new	74
long-short-user: fixed spelling		1.17 – 2017-08-09	
of <code>\gl:abbrvfont</code>	542	General: removed some	
postfootnote: fixed spelling of		inconsistencies in the	
<code>\gl:abbrvfont</code>	467	abbreviation styles	458
short-em-long-em: fixed spelling		<code>\@gl:xtr@mark@wordseps</code> : new .	328
of <code>\gl:abbrvfont</code>	521	<code>\@gl:xtr@markwordseps</code> : new .	328
short-long: fixed spelling of		<code>\@gl:xtr@noidx@displaynumberlist</code> :	
<code>\gl:abbrvfont</code>	461	replace hard-coded ?? with	
short-long-user: fixed spelling		<code>\gl:xtrundeftag</code>	191
of <code>\gl:abbrvfont</code>	551	<code>\@gl:xtr@noidx@entrynumberlist</code> :	
short-postfootnote-desc: fixed		replace hard-coded ?? with	
spelling of <code>\gl:abbrvfont</code> .	469	<code>\gl:xtrundeftag</code>	192

\@glxstr@noidx@numberlistloop: replace hard-coded ?? with \glxstrundeftag	191	\glxstrshortlongdescname: new	462
\@glxstrtrifhyphenstart: new . . .	553	\glxstrshortlongdescsort: new	462
\glxabbrvhyphenfont: new . . .	555	\Glsxtrsubsequentfmt: new . .	353
\glxabbrvonlyfont: new	592	\glxtrsubsequentfmt: new . .	352
\glxabbrvscfont: new	479	\Glsxtrsubsequentplfmt: new .	353
\glxabbrvsmfont: new	496	\glxtrsubsequentplfmt: new .	352
\glxabbrvuserfont: initialised to default font	542	\glxtrword: new	328
\glxfirstabbrvhyphenfont: new	555	\glxtrwordsep: new	327
\glxfirstabbrvonlyfont: new .	592	long-em-noshort-em-desc-noreg: new	534
\glxfirstabbrvscfont: new . .	479	long-em-noshort-em-noreg: new	530
\glxfirstabbrvsmfont: new . .	497	long-hyphen-noshort-desc-noreg: new	562
\glxfirstlonghyphenfont: new	555	long-hyphen-noshort-noreg: new	569
\glxfirstlongonlyfont: new .	592	long-hyphen-postshort-hyphen: new	572
\glxlonghyphenfont: new	555	long-hyphen-postshort-hyphen-desc: new	577
\glxlongonlyfont: new	592	long-hyphen-short-hyphen: new	556
\glxlonguserfont: initialised to default font	542	long-hyphen-short-hyphen-desc: new	561
\glxstr@newabbreviation: added \glxstrorgshort and \glxstrorglong	328	long-noshort-desc-noreg: new	477
\GlsXtrDefineAcShortcuts: new	21	long-noshort-noreg: new	478
\glxstrgenabbrvfmt: added check for \ifglxstrinsertinside . .	350	long-only-short-only: new . .	592
\glxstrhyphensuffix: new . . .	555	long-only-short-only-desc: new	594
\glxstrtrifhyphenstart: new . .	553	long-short-user-desc: corrected first forms	550
\glxstrtrlonghyphen: new	569	short-hyphen-long-hyphen: new	579
\glxstrtrlonghyphennoshort: new	561	short-hyphen-long-hyphen-desc: new	584
\glxstrtrlonghyphenshort: new .	554	short-hyphen-postlong-hyphen: new	586
\glxstrtrlongshortdescname: new	460	short-hyphen-postlong-hyphen-desc: new	591
\glxstrtronlydescname: new . . .	594	short-long-user-desc: corrected first forms	553
\glxstrtronlydescsort: new . . .	594	short-nolong-desc-noreg: new	474
\glxstrtronlysuffix: new	592	short-nolong-noreg: new	472
\glxstrtparen: new	332		
\glxstrposthyphenlong: new .	585		
\glxstrposthyphenshort: new .	570		
\glxstrposthyphensubsequent: new	571		
\glxstrshortdescname: new . .	472		
\glxstrshorthyphen: new	585		
\glxstrshorthyphenlong: new .	578		
\glxstrshorthyphennoinsert: new	572		

1.18 – 2017-08-10

stylemods: changed default value
to “default” 25

1.19 – 2017-09-09

General: added `\glslink` option
`theHvalue` 103
added `\glslink` option
`thevalue` 103
`\@glstr@defaultnumberformat:`
new 5
`\@glstr@dorecord:` Use
`\@glstr@recordloc` instead of
`\@glstr@loc` 8
`\@glstr@dorecordnodefer:` Use
`\theentrycounter` for the
location rather than
`\@glstr@loc` 9
`\@glstr@record@setting:` new 12
`\@glstr@record@setting@alsoindex:`
new 12
`\@glstrifhasfield:` new 47
`\glstr@writefields:` removed
double-quotes around
`\jobname` 207
`\glstrdoautoindexname:`
changed format test 313
`\glstrhyperlink:` new 149
`\glstrifhasfield:` new 47
`\GlsXtrSetDefaultNumberFormat:`
new 5
`\s@glstrifhasfield:` new ... 47

1.20 – 2017-09-11

`\@glstrhypernameprefix:` new 188
`\glstrhypertarget:` added
redefinition 189
`\printunsrtglossaryunitsetup:`
switched from redefining
`\glolinkprefix` to
`\@glstrhypernameprefix` 222

1.21 – 2017-11-03

General: adjusted `mcalttree` .. 708
modified index to remove hard
coded `\space` 678
modified list to remove hard
coded `\space` 665
moved conditional outside of
`\glsgroupskip`
..... 669, 670, 672, 674–677
new 712
redefined `altlistgroup` to
discourage breaks after group
headings 668

redefined `altlisthypergroup`
to discourage breaks after
group headings 668
redefined `alttreegroup` to
discourage breaks after group
headings 700
redefined `alttreehypergroup`
to discourage breaks after
group headings 701
redefined `indexgroup` to
discourage breaks after group
headings 679
redefined `indexhypergroup` to
discourage breaks after group
headings 680
redefined `listgroup` to
discourage breaks after group
headings 667
redefined `listhypergroup` to
discourage breaks after group
headings 667
redefined `mcalttreegroup` to
discourage breaks after group
headings 708
redefined
`mcalttreehypergroup` to
discourage breaks after group
headings 709
redefined `mcalttreespannav`
to discourage breaks after
group headings 711
redefined `mcindexgroup` to
discourage breaks after group
headings 703
redefined
`mcindexhypergroup` to
discourage breaks after group
headings 703
redefined `mcindexspannav` to
discourage breaks after group
headings 704
redefined `mcalttreegroup` to
discourage breaks after group
headings 705
redefined `mcalttreehypergroup`
to discourage breaks after
group headings 705
redefined
`mcaltreenonamegroup` to

discourage breaks after group headings	706	\@glxstrglossentry: new	209
redefined		\@glxstrnewgls: new	229
mcoltreenamehypergroup to discourage breaks after group headings	707	\@glxstrsetaliasnoindex: changed to use	
redefined		\glxstrifhasfield instead of	
mcoltreenamehypergroup to discourage breaks after group headings	707	\ifglshasfield	142
redefined		\@glxstrwrglossmark: new . . .	27
mcoltreenamehypergroup to discourage breaks after group headings	707	\@rGLS: new	235
redefined mcoltreenamehypergroup to discourage breaks after group headings	706	\@rGLS@: new	235
redefined treegroup to discourage breaks after group headings	683	\@rGLSpl: new	235
redefined treehypergroup to discourage breaks after group headings	684	\@rGLSpl@: new	235
redefined treenamegroup to discourage breaks after group headings	686	\@rGls: new	234
redefined		\@rGls@: new	234
treenamehypergroup to discourage breaks after group headings	686	\@rGlspl: new	234
\@glxstr@record: added check for default options	7	\@rGlspl@: new	234
\@glxstrwrglossmark: new . .	27	\@rgls: new	233
\@glslink: changed \let to \def	150	\@rgls@: new	233
\@glxstr@checkgroup: new . .	223	\@rglspl: new	234
\@glxstr@defpostpunc: new . .	18	\@rglspl@: new	234
\@glxstr@do@record@wrglossary: new	5	all: new	663
\@glxstr@dosee@alsoindex@glossary: new	35	debug: new	28
\@glxstr@doseeglossary: new .	34	\glssetwidest: new	686
\@glxstr@noidx@do: removed code dealing with the group	225	\glsdisablehyper: added check for existence	150
\@glxstr@printunsrtglossaryskipentry: new	220	changed to use \def rather than \let	150
\@glxstr@record@setting@off: new	13	\glsenablehyper: changed to use	
\@glxstr@record@setting@only: new	12	\def rather than \let	150
\@glxstr@resourcefile: now disables record key	203	\Glsfmtname: new	379
\@glxstr@rglstrigger@record: new	232	\glsfmtname: new	378
		\glshe: new	599
		\glslistchildpostlocation: new	665
		\glslistchildprelocation: new	665
		\glslistprelocation: new . . .	665
		\glsnavhyperlink: patched . . .	146
		\glsseeitemformat: new	69
		\glsshowtarget: new	34
		\glstreechildprelocation: new	678
		\glstreeprelocation: new . . .	678
		\glstriggerrecordformat: new	233
		\glsuseabbrvfont: new	349
		\glsuselongfont: new	349
		\glxstr@do@alsoindex@wrglossary: new	6
		\glxstr@org@do@wrglossary: new	36
		\glxstr@org@dohyperlink: new	146

\glxstr@setbookindexmark:		\GlsXtrIfFieldEqStr: new ...	53
new	720	\glxstriflabelinlist: new ..	221
\glxstrbookindexatendgroup:		\glxstrifrecordtrigger: new .	232
new	714	\glxstrindexseealso: added	
\glxstrbookindexbetween: new	713	check that the entry exists ..	75
\glxstrbookindexbookmark:		\glxstrinithyperoutside: new	104
new	715	\GlsXtrLocationRecordCount:	
\glxstrbookindexcols: new ..	712	new	231
\glxstrbookindexcolspread:		\glxstrnewgls: new	226, 230
new	715	\glxstrnewGLSlike: new	230
\glxstrbookindexfirstmark:		\glxstrnewglslike: new	230
new	720	\glxstrnewrgls: new	230
\glxstrbookindexfirstmarkfmt:		\glxstrnewrglslike: new	230
new	720	\glxstrnewrglslike: new	230
\glxstrbookindexformatheader:		\glxstrprelocation: new	664, 713
new	714	\GlsXtrRecordCount: new	231
\glxstrbookindexgroupskip:		\glxstrrecordtriggervalue:	
new	714	new	231
\glxstrbookindexlastmark:		\glxstrresourceinit: new ...	204
new	720	\GlsXtrSetRecordCountAttribute:	
\glxstrbookindexlastmarkfmt:		new	232
new	720	\GlsXtrTitleName: new	368
\glxstrbookindexmarkentry:		\glxstrTitleName: new	368
new	719	\glxstrTitleorpdforheading:	
\glxstrbookindexname: new ..	713	new	362
\glxstrbookindexparentchildsep:		\GlsXtrTotalRecordCount: new	231
new	713	\glxstrwrglossmark: new	27
\glxstrbookindexparentsubchildsep:		\ifglxstr@hyperoutside: new .	103
new	713	nolong-short: new	474
\glxstrbookindexprelocation:		nolong-short-em: new	526
new	713	nolong-short-noreg: new	475
\glxstrbookindexsubatendgroup:		nolong-short-sc: new	486
new	714	nolong-short-sm: new	504
\glxstrbookindexsubbetween:		nopostdot: new	18
new	713	postpunc: new	18
\glxstrbookindexsubname: new	713	\printunsrtglossaryentryprocesshook:	
\glxstrbookindexsubprelocation:		new	220
new	713	\printunsrtglossarypredoglossary:	
\glxstrbookindexsubsubatendgroup:		new	221
new	714	\printunsrtglossaryskipentry:	
\glxstrbookindexsubsubbetween:		new	220
new	714	\rGLS: new	235
\glxstrbookindexthepage: new	719	\rGls: new	234
\glxstrdetoklocation: new ..	231	\rgls: new	233
\glxstretablerecordcount:		\rGLSformat: new	236
new	231	\rGlsformat: new	236
\glxstrglossentry: new	209	\rglsformat: new	236
\glxstrgroupfield: new	223	\rGLSpl: new	235
\GlsXtrHeadName: new	368	\rGlspl: new	234
\glxstrHeadName: new	368	\rglspl: new	233

\rGLSplformat: new	236	\GlsXtrDefineAcShortcuts:	
\rGLsplformat: new	236	changed \newabbr definition	
\rglsplformat: new	236	to use \providecommand	22
\s@glxstrifhasfield: switched		\glxstrfmtdisplay: new	42
from \ifdef to \ifundef	47	\glxstrifcustomdiscardperiod:	
short-sc: corrected first letter		new	322
uppercasing	484	\GlsXtrIfFieldUndef: new	49
short-sm: corrected first letter		\glxstrrestorepostpunc: new	187
uppercasing	502	\s@glxstrfmt: new	41
shortcuts: ac	24	\s@glxstrfmt: new	41
1.22 – 2017-11-08		\xglsupdatewidest: new	688
\@glxstr@nopostpunc: new	187	1.24 – 2017-11-14	
\@glxstr@orgprintglossary:		\@glsadd: added \@gls@setsort	110
changed explicit \let for		\glxstrforcsvfield: new	44
\nopostdesc to		\glxstrlocalsetgrouptitle:	
\glxstractivatenopost	186	new	194
\@glxstrglossentryother: new	211	1.25 – 2017-11-14	
\glossentrynameother: new	309	\glxstrbookindexmulticolenv:	
\glsseeitemformat: switched		new	715
check from regular to short	69	1.25 – 2017-11-24	
\glxstr@setaccessdisplay:		\glsextrapostnamehook: new	308
new	308	\glxstrfootnotename: new	464
\glxstr@writefields: provide		\glxstrlongnoshortdescname:	
\glxstr@record in aux file	206	new	475
\glxstractivatenopost: new	186	\glxstrlongnoshortname: new	478
\glxstrbookindexprelocation:		\glxstrlongshortname: new	439
removed check for no post		\glxstrlongshortuserdescname:	
dot	713	new	546
\glxstrglossentryother: new	211	\glxstronlyname: new	592
\glxstrnopostpunc: new	187	\glxstrpostlinkAddDescOnFirstUse:	
1.23 – 2017-11-12		changed to use	
\@@glxstrfmt: added check for		\glxstrparen	323
indexing	42	\glxstrpostlinkAddSymbolOnFirstUse:	
added grouping	41	changed to use	
new	41	\glxstrparen	323
\@glxstr@nopostpunc@postdesc:		\glxstrshortlongname: new	461
new	187	\glxstrshortlonguserdescname:	
\@glxstr@restore@postpunc:		new	549
new	187	\glxstrshortnolongname: new	470
\@glxtrentryfmt: fixed missing		1.26 – 2018-01-05	
label argument	42	\@glxstr@do@inc@linkcount:	
\@glxstrfmt: new	41	new	237
\eglsupdatewidest: new	688	\glslinkpresetkeys: new	104
\glsupdatewidest: new	687	\glxstr@inc@linkcount: new	104
\glsupdatewidest: new	687	\GlsXtrEnableLinkCounting:	
\GlsXtrDefineAbbreviationShortcuts:		new	238
changed \newabbr definition		\GlsXtrIfLinkCounterDef: new	238
to use \providecommand	21	\glxstrinclinkcounter: new	237
		\GlsXtrLinkCounterName: new	238
		\GlsXtrLinkCounterValue: new	237

\GlsXtrTheLinkCounter: new	237	\glxtrLatinAA: new	646
1.27 – 2018-02-26		\glxtrLatinAELigature: new	646
General: added		\glxtrLatinE: new	644
glossaries-extra-bib2gls.sty	598	\glxtrLatinEszettSs: new	646
\@glxtrdialecthook: new	38	\glxtrLatinEszettSz: new	646
\Alpha: new	625	\glxtrLatinEth: new	646
\Beta: new	625	\glxtrLatinH: new	644
\Chi: new	625	\glxtrLatinI: new	644
\Digamma: new	625	\glxtrLatinInsularG: new	646
\Epsilon: new	625	\glxtrLatinK: new	645
\Eta: new	625	\glxtrLatinL: new	645
\glxtr@loaddialect: new	438	\glxtrLatinLslash: new	647
\glxtrBasicDigitrules: new	661	\glxtrLatinM: new	645
\glxtrcombiningdiacriticIIrules:		\glxtrLatinN: new	645
new	630	\glxtrLatinO: new	645
\glxtrcombiningdiacriticIrules:		\glxtrLatinOELigature: new	646
new	630	\glxtrLatinOslash: new	647
\glxtrcombiningdiacriticIrules:		\glxtrLatinP: new	645
new	630	\glxtrLatinS: new	645
\glxtrcombiningdiacriticIVrules:		\glxtrLatinSchwa: new	645
new	631	\glxtrLatinT: new	645
\glxtrcombiningdiacriticrules:		\glxtrLatinThorn: new	646
new	629	\glxtrLatinWynn: new	646
\glxtrcontrolrules: new	628	\glxtrLatinX: new	645
\glxtrcurrencyrules: new	636	\glxtrMathGreekIrules: new	653
\glxtrdigitrules: new	660	\glxtrMathGreekIrules: new	652
\glxtrfractionrules: new	661	\glxtrMathItalicAlpha: new	657
\glxtrGeneralLatinIrules:		\glxtrMathItalicBeta: new	657
new	638	\glxtrMathItalicChi: new	660
\glxtrGeneralLatinIrules:		\glxtrMathItalicDelta: new	657
new	638	\glxtrMathItalicEpsilon:	
\glxtrGeneralLatinIrules:		new	657
new	637	\glxtrMathItalicEta: new	658
\glxtrGeneralLatinIVrules:		\glxtrMathItalicGamma: new	657
new	639	\glxtrMathItalicGreekIrules:	
\glxtrGeneralLatinVIIrules:		new	648
new	642	\glxtrMathItalicGreekIrules:	
\glxtrGeneralLatinVIIrules:		new	648
new	641	\glxtrMathItalicIota: new	658
\glxtrGeneralLatinVrules:		\glxtrMathItalicKappa: new	658
new	640	\glxtrMathItalicLambda: new	658
\glxtrGeneralLatinVrules:		\glxtrMathItalicLowerGreekIrules:	
new	640	new	651
\glxtrgeneralpuncIIrules:		\glxtrMathItalicLowerGreekIrules:	
new	636	new	650
\glxtrgeneralpuncIrules:		\glxtrMathItalicMu: new	658
new	633	\glxtrMathItalicNabla: new	660
\glxtrgeneralpuncrules: new	633	\glxtrMathItalicNu: new	659
\glxtrhyphenrules: new	632	\glxtrMathItalicOmega: new	660
\glxtrLatinA: new	644		

\@gls@removespaces: added	\@glsxtrbuffer@unset: new ..	159
expansion	\glsaddpostsetkeys: new	109
\@glsxtr@wrglossary@locationhyperlink:	\glsaddpresetkeys: new	109
new	\glsuserdescription: new ...	542
\glsxtr@inc@wrglossaryctr:	\glsxtrabbreviationfont: new	91
new	\GlsXtrDualBackLink: new ...	602
\glsxtr@wrglossarylocation:	\GlsXtrDualField: new	602
new	\GlsXtrExpandedFmt: new	104
\GlsXtrBibTeXEntryAliases:	\GLSxtrlong: added	
new	\@glsxtr@record	345
\glsxtrfieldforlistloop:	\Glsxtrlong: added	
corrected argument order in	\@glsxtr@record	344
\forlistcsloop	\glsxtrlong: added	
\GlsXtrIndexCounterLink: new	\@glsxtr@record	343
\GlsXtrInternalLocationHyperlink:	\GLSxtrlongpl: added	
new	\@glsxtr@record	349
\GlsXtrProvideBibTeXFields:	\Glsxtrlongpl: added	
new	\@glsxtr@record	348
indexcounter: new	\glsxtrlongpl: added	
\setentrycounter: new	\@glsxtr@record	347
1.30 – 2018-04-25	\GLSxtrshort: added	
\@glsxtr@dorecord: don't	\@glsxtr@record	343
suppress expansion of	\Glsxtrshort: added	
\@glsrecordlocref	\@glsxtr@record	342
\@glsxtr@record: added check	\glsxtrshort: added	
for post-key hook	\@glsxtr@record	341
added check for pre-key hook .	\GLSxtrshortpl: added	
\@GLSxtr@fullpl: added	\@glsxtr@record	347
\@glsxtr@record	\Glsxtrshortpl: added	
\@GlsXtrStopUnsetBuffering:	\@glsxtr@record	346
new	\glsxtrshortpl: added	
\@Glsxtr@fullpl: added	\@glsxtr@record	345
\@glsxtr@record	\GlsXtrStartUnsetBuffering:	
\@glsadd: added	new	159
\glsaddpostsetkeys	\GlsXtrStopUnsetBuffering:	
added \glsaddpresetkeys ..	new	161
\@glsxtr@full: added	indexcounter: added check for	
\@glsxtr@record	wrglossary counter	27
\@glsxtr@fullpl: added	\s@GlsXtrStopUnsetBuffering:	
\@glsxtr@record	new	161
\@glsxtr@glossadd@postkeys:	1.31 – 2018-05-09	
new	General: added prefix key for	
\@glsxtr@glossadd@prekeys:	glslink	104
new	added prefix key for	
\@glsxtr@glslink@postkeys:	printgloss	188
new	changed \let to \def	188
\@glsxtr@glslink@prekeys: new	\@GlsXtrStartUnsetBuffering:	
\@glsxtr@local@textformat:	new	159
new	\@gls@ifaccessattribute@set:	
\@glsxtr@unset: new	new	271

\@gls@initaccesskeys:		\GlsXtrStandaloneGlossaryType:	
new	270, 290	new	211
\@gls@setup@default@short@access:		\GlsXtrStandaloneSubEntryItem:	
new	272	new	211
\@glsxtr@record@noglossarywarning:		\s@GlsXtrStartUnsetBuffering:	
new	202	new	159
\@glsxtrbuffer@nodup@unset:		1.32 – 2018-05-24	
new	160	\GlsXtrForeignText: new	54
\glsaddeach: new	110	\GlsXtrForeignTextField: new	56
\glsapturedgroup: new	599	\GlsXtrUnknownDialectWarning:	
\glsdefpostdesc: new	321	new	56
\glsdefpostlink: new	322	1.33 – 2018-07-26	
\glsdefpostname: new	308	\ifglsused: added redefinition .	59
\glsdohypertarget: bug fix:		1.34 – 2018-07-29	
ensure that new version is		docdef: atom	16
picked up	190	\gls@begindocdefs: atom	80
\glslistdesc: new	665	\GlsXtrIfUnusedOrUndefined:	
\glslocalreseteach: new	162	new	38
\glslocalunseteach: new	162	\glsxtrNoGlossaryWarning:	
\glsrechilddesc: new	682	added package warning	25
\glsrechildsymbol: new ...	682	\ifglsxtrdocdefrestricted:	
\glsreedefaultnamefmt: new .	677	changed to allow for atom as	
\glsreedesc: new	681	well	17
\glsregrgroupheaderfmt: added		1.35 – 2018-08-13	
redefinition	678	\@gls@@link: initialise post-link	
\glsreenamefmt: added		hook commands	100
redefinition	677	1.36 – 2018-08-18	
\glsreenavigationfmt: added		\glsxtrautoindexesc: new ...	314
redefinition	678	\glsxtrdisplaysupplc: new .	603
\glsreenonamechilddesc: new	685	\glsxtrmultisupplcation:	
\glsreenonamedesc: new	684	new	603
\glsreenonamesymbol: new ..	684	1.37 – 2018-11-30	
\glsreesymbol: new	682	General: new	720
\glsxtr@newabbreviation: added		\@@glsxtr@dorecord: nameref ..	9
\ExtraCustomAbbreviationFields		\@@glsxtr@record: added check	
.....	328	for auto-add	7
\GlsXtrForUnsetBufferedList:		\@dGLS: new	615
new	161	\@dGLSpl: new	615
\GlsXtrIfFieldCmpNum: new ..	48	\@dGLs: new	614
\GlsXtrIfFieldEqNum: new ...	48	\@dGLspl: new	615
\GlsXtrIfFieldEqXpStr: new .	53	\@dglS: new	614
\GlsXtrIfFieldNonZero: new .	47	\@dglSpl: new	614
\GlsXtrIfHasNonZeroChildCount:		\@gls@getcounterprefix: new .	37
new	600	\@glsadd: ensure that \glsadd	
\GlsXtrIfXpFieldEqXpStr: new	54	performs indexing	110
\glsxtrpostlinkAddSymbolDescOnFirstUse\@glslongextrawidestname:		new	725
new	324	\@glsxtr@bibgls@removespaces:	
\GlsXtrRecordWarning: new ..	201	new	606
\glsxtrRevertTocMarks: new .	362		

\@glxtr@check@bibgls@nameref:	\glslongextraLocationDescNameTabularHeader:
new 204	new 731
\@glxtr@do@nameref@record:	\glslongextraLocationDescSymNameHeader:
new 10	new 743
\@glxtr@get@prefixedlabel:	\glslongextraLocationDescSymNameTabularFooter:
new 612	new 744
\@glxtr@if@record@only: new	\glslongextraLocationDescSymNameTabularHeader:
12	new 744
\@glxtr@ifnum@mmode: new ...	\glslongextraLocationFmt:
9	new 721
\@glxtr@labelprefixes: new .	\glslongextraLocationSymDescNameHeader:
610	new 740
\@glxtr@prefixlabellist:	\glslongextraLocationSymDescNameTabularFooter:
new 611	new 741
\@glxtr@providenewgls: new .	\glslongextraLocationSymDescNameTabularHeader:
226	new 740
\@glxtr@record@only@setup:	\glslongextraLocSetDescWidth:
new 13	new 726
\@glxtr@record@setting@nameref:	\glslongextraNameAlign: new .
new 12	723
\@glxtr@use@equation@counter@or:	\glslongextraNameDescHeader:
new 104	new 724
\dGLS: new 615	\glslongextraNameDescLocationHeader:
\dglS: new 614	new 728
\dglSdisp: new 615	\glslongextraNameDescLocationTabularFooter:
\dglSlink: new 615	new 728
\dGLSpl: new 615	\glslongextraNameDescLocationTabularHeader:
equations: new 17	new 728
floats: new 17	\glslongextraNameDescSymHeader:
\glsadd: added grouping 109	new 732
\glslongextraDescAlign: new .	\glslongextraNameDescSymLocationHeader:
723	new 734
\glslongextraDescFmt: new ..	\glslongextraNameDescSymLocationTabularFooter:
721	new 734
\glslongextraDescNameHeader:	\glslongextraNameDescSymLocationTabularHeader:
new 729	new 734
\glslongextraDescNameTabularFooter:	\glslongextraNameDescSymTabularFooter:
new 730	new 733
\glslongextraDescNameTabularHeader:	\glslongextraNameDescSymTabularHeader:
new 729	new 732
\glslongextraDescSymNameHeader:	\glslongextraNameDescTabularFooter:
new 742	new 724
\glslongextraDescSymNameTabularFooter:	\glslongextraNameDescTabularHeader:
new 742	new 724
\glslongextraDescSymNameTabularHeader:	\glslongextraNameFmt: new ..
new 742	721
\glslongextraGroupHeading:	\glslongextraNameSymDescHeader:
new 724	new 735
\glslongextraHeaderFormat:	\glslongextraNameSymDescLocationHeader:
new 724	new 737
\glslongextraLocationAlign:	\glslongextraNameSymDescLocationTabularFooter:
new 724	new 737
\glslongextraLocationDescNameHeader:	
new 731	
\glslongextraLocationDescNameTabularFooter:	
new 731	

\glslongextraNameSymDescLocationTabularHeader:	\glsxtrdisplaylocnameref:
new 737	new 604
\glslongextraNameSymDescTabularFooter:	\glsxtrfmtexternalnameref:
new 736	new 606
\glslongextraNameSymDescTabularHeader:	\glsxtrfmtinternalnameref:
new 736	new 606
\glslongextraSetDescWidth:	\GLSxTRhiername: new 71
new 725	\GLSxtrhiername: new 71
\glslongextraSetWidest: new . 724	\GlsXtrhiername: new 70
\glslongextraSubDescFmt: new 722	\Glsxtrhiername: new 70
\glslongextraSubLocationFmt:	\glsxtrhiername: new 69
new 723	\glsxtrhiernamesep: new 72
\glslongextraSubNameFmt: new 722	\glsxtridentifyglslike: new . 226
\glslongextraSubSymbolFmt:	\glsxtrifinlabelprefixlist:
new 722	new 610
\glslongextraSymbolAlign:	\GlsXtrLocationField: new . . 224
new 723	\glsxtrnameloclink: new 605
\glslongextraSymbolFmt: new . 721	\glsxtrnamereflink: new 605
\glslongextraSymDescNameHeader:	\glsxtrprependlabelprefix:
new 739	new 610
\glslongextraSymDescNameTabularFooter:	\GlsXtrSetAltModifier: write
new 739	modifier to aux 146
\glslongextraSymDescNameTabularHeader:	\glsxtrSetWidest: new 607
new 739	\glsxtrSetWidestFallback:
\glslongextraSymLocSetDescWidth:	new 609
new 726	\GlsXtrStandaloneEntryName:
\glslongextraSymSetDescWidth:	new 210
new 725	\GlsXtrStandaloneEntryOther:
\glslongextraTabularVAlign:	new 212
new 727	\GLSxtrusefield: new 49
\glslongextraUpdateWidest:	\GLSxtrusefield: fixed internal
new 725	command and added check
\glslongextraUpdateWidestChild:	for \texorpdfstring 49
new 725	\ifGlsLongExtraUseTabular:
\glsrenewcommand: new 601	new 727
\glsseeitemformat: removed	long-desc-name: new 730
reference to \glslabel 69	long-desc-sym-name: new 742
\glsxtr@dblfloat: new 17	long-loc-desc-name: new 731
\glsxtr@do@autoadd: new 105	long-loc-desc-sym-name: new . 744
\glsxtr@float: new 17	long-loc-sym-desc-name: new . 741
\glsxtr@record@nameref: new . 208	long-name-desc: new 727
\glsxtr@renewcommand: new . . 601	long-name-desc-loc: new 728
\glsxtr@writefields: provide	long-name-desc-sym: new 733
\glsxtr@record@nameref in	long-name-desc-sym-loc: new . 734
aux file 206	long-name-sym-desc: new 736
\glsxtraddlabelprefix: new . 610	long-name-sym-desc-loc: new . 737
\GlsXtrAutoAddOnFormat: new . 105	long-sym-desc-name: new 739
\glsxtrclearlabelprefixes:	1.38 – 2018-12-01
new 610	all: added glossary-longextra . . 663

\glslongextraNameFmt: bug fix: removed double param . . .	721	short-sc-desc: bug fix: omit description key as advertised in the manual	485
1.39 – 2019-03-22		short-sm-desc: corrected to omit description key as advertised in the manual	502
General: added label key for printgloss	188	1.40 – 2019-03-22	
\@glxtr@dorecord: added protection for fragile commands	8	General: new	772
\@GlsXtrIfFieldCmpNum: new .	48	all: added glossary-topic	663
\@GlsXtrIfFieldEqNum: new .	48	\glstopicAssignSubIndent: new	775
\@GlsXtrIfFieldEqStr: new .	53	\glstopicAssignWidest: new .	775
\@GlsXtrIfFieldEqXpStr: new .	53	\glstopicCols: new	776
\@GlsXtrIfFieldNonZero: new .	47	\glstopicColsEnv: new	777
\@GlsXtrIfXpFieldEqXpStr: new	54	\glstopicDesc: new	774
\@gls@removespaces: changed \x to \@glo@tmp	197	\glstopicGroupHeading: new .	773
\glxtrbookindexlocation: new	713	\glstopicInit: new	774
\glxtrbookindexsublocation: new	713	\glstopicItem: new	773
\glxtrentryparentname: new .	49	\glstopicLoc: new	774
\GlsXtrIfFieldCmpNum: added starred version	48	\glstopicMarker: new	774
\GlsXtrIfFieldEqNum: added starred version	48	\glstopicMidSkip: new	776
\GlsXtrIfFieldEqStr: added starred form	53	\glstopicName: new	774
\GlsXtrIfFieldEqXpStr: added starred form	53	\glstopicParIndent: new	774
\GlsXtrIfFieldNonZero: added starred version	47	\glstopicPostSkip: new	776
\GlsXtrIfXpFieldEqXpStr: added starred form	54	\glstopicPreSkip: new	776
\glxtrsetglossarylabel: new	188	\glstopicSubIndent: new	774
\glxtrshortdescname: corrected to show long form as advertised in the manual . .	472	\glstopicSubItem: new	776
\s@GlsXtrIfFieldCmpNum: new .	48	\glstopicSubItemBox: new . . .	776
\s@GlsXtrIfFieldEqNum: new .	48	\glstopicSubItemSep: new . . .	776
\s@GlsXtrIfFieldEqStr: new .	53	\glstopicSubLoc: new	776
\s@GlsXtrIfFieldEqXpStr: new	54	\glstopicSubNameFont: new . .	776
\s@GlsXtrIfXpFieldEqXpStr: new	54	\glstopicTitleFont: new	774
short-desc: corrected to omit description key as advertised in the manual	472	\glstopicwidest: new	775
short-em-desc: bug fix: omit description key as advertised in the manual	524	topic: new	772
		topicmcols: new	777
		1.40 – 2019-03-31	
		\glsfirstabbrvdefaultfont: changed definition from \glsabbrvfont to \glsabbrvdefaultfont for consistency	335
		\GlsXtrDefaultResourceOptions: new	202
		long-hyphen-noshort-noreg: corrected formatting commands	569
		\printunsrtabbreviations: new	598
		\printunsrtacronyms: new . . .	598
		\printunsrtindex: new	598

\printunsrtnumbers: new	598	\@gls@setup@default@access	
\printunsrtsymbols: new	598	272
1.41 – 2019-04-09		\@glslink: switched from	
bookindex: changed		\glsdohyperlink to	
\thisgrptitle to		\glxtrdohyperlink	150
\glxtrcurrentgrptitle .	718	\@glxtr@abbrlists: new	177
\glslistgroupskip: new	665	\@glxtr@acronymlists: new .	177
\glstopicAssignSubIndent:		\@glxtr@addabbreviationlist:	
moved \par from		new	177
\glstopicSubItem	775	\@glxtr@base@acrcmd: new . .	131
\glstopicSubItem: added check		\@glxtr@doloadprefix: new .	24
for description	776	\@glxtr@org@addtoacronymlists:	
moved \par to		new	177
\glstopicAssignSubIndent	776	\@glxtr@org@setacronymlists:	
\glstopicSubLoc: moved \space		new	177
to \glstopicSubPreLocSep	776	\@glxtr@entryfmt: added	
\glstopicSubPreLocSep: new .	776	\glslabel and scope	43
\glstreeChildDescLoc: new . .	682	debug: showaccsupp	28
\glstreeDescLoc: new	681	footnote: added missing text	
\glstreegroupskip: new	678	key	464
\glstreePreHeader: new	678	footnote-desc: new	467
\glxtralttreeSymbolDescLocation:		\forallabbreviationlists:	
added check for description	688	new	177
topic: added penalty if no		\forallacronyms: new	178
description	772	\glsdefaultshortaccess: new .	271
topicmcols: added penalty if no		\glsdisplaynumberlist: added	599
description	777	\glsenablehyper: switched from	
1.42 – 2020-02-03		\glsdohyperlink to	
General: added \@afterheading	703	\glxtrdohyperlink	150
\@@glxtr@record: moved label		\glstrynumberlist: added . .	599
definition outside of		\GLSfmtfirst: new	380
conditional	6	\GLSfmtfirsttpl: new	381
\@ACRfull: added redefinition .	137	\GLSfmtfull: new	382
\@ACRfullpl: added redefinition	137	\Glsfmtfull: switched pdf case	
\@Acrfull: added redefinition .	137	to use \glspdffmtfull . . .	382
\@Acrfullpl: added redefinition	137	\glsfmtfull: switched pdf case	
\@GlsXtrIfFieldValueInCsvList:		to use \glspdffmtfull . . .	382
new	45	\GLSfmtfullpl: new	383
\@acrfull: added redefinition .	136	\Glsfmtfullpl: switched pdf case	
\@acrfullpl: added redefinition	137	to use \glspdffmtfullpl .	382
\@domakeglossaries: provided		\glsfmtfullpl: switched pdf case	
definition for		to use \glspdffmtfullpl .	382
\@domakeglossaries	180	\GLSfmtlong: new	381
\@gls@assign@actual: new . . .	272	\GLSfmtlongpl: new	381
\@gls@entry@field: redefined .	58	\GLSfmtname: new	379
\@gls@setup@default@access:		\GLSfmtplural: new	380
added		\GLSfmttext: new	379
\glsdefaultshortaccess .	272	\glspdffmtfull: new	382
\@gls@setup@default@short@access:		\glspdffmtfullpl: new	382
renamed to			

\glseeitemformat: switched to using \glsfmttext and \glsfmtname	69	\GLSXTRhiername: switched to using \GLSfmttext and \GLSfmtname	71
\glsshowtarget: added check for \glsshowtargetouter	34	\GLSxtrhiername: switched to using \glsfmttext, \glsfmtname, \GLSfmttext and \GLSfmtname	71
\glstreeChildDescLoc: added \glstreeNoDescSymbolPreLocation	682	\GlsXtrhiername: switched to using \Glsfmttext and \Glsfmtname	70
\glstreegroupheaderskip: new	678	\GLSxtrhiername: switched to using \glsfmttext and \glsfmtname	70
\glstreeNoDescSymbolPreLocation: new	681	\glsxtrhiername: switched to using \glsfmttext and being obtained	329
\glsxtr@newabbreviation: moved apply abbreviation style to after category key has removed \relax and updated \@gls@short instead of \glsshorttok	330	\GlsXtrIfFieldValueInCsvList: new	45
replaced explicit \spacefactor with \@	330	\glsxtrpdfentryfmt: new	42
\glsxtr@writefields: added check for order=letter	207	\glsxtrprovideaccsuppcmd: new	274
\glsxtrAccSuppAbbrSetFirstLongAttrs: new	275, 291	\glsxtrscs suffix: added \protect	479
\glsxtrAccSuppAbbrSetNameLongAttrs: new	275, 291	\GlsXtrSetAltModifier: added check	146
\glsxtrAccSuppAbbrSetNameShortAttrs: new	275, 291	\GLSxtrtitlefirst: new	372
\glsxtrAccSuppAbbrSetNoLongAttrs: new	275, 291	\GLSxtrtitlefirstplural: new	373
\glsxtrAccSuppAbbrSetTextShortAttrs: new	275, 291	\GLSxtrtitlefull: new	376
\glsxtralttreeSymbolDescLocation: switched to using \glstreeDescLoc	688	\GLSxtrtitlefullpl: new	377
\glsxtrassignactualsetup: new	271	\GLSxtrtitlelong: new	374
\glsxtrbookindexbookmarkprefix: new	715	\GLSxtrtitlelongpl: new	375
\GlsXtrDiscardUnsetBuffering: new	161	\GLSxtrtitlename: new	368
\glsxtrdohyperlink: new (was former redefinition of \glsdohyperlink)	148	\GLSxtrtitleplural: new	371
\glsxtrequationlocfmt: new .	605	\GLSxtrtitleshort: new	367
\glsxtrfieldformatcsvlist: new	45	\GLSxtrtitleshortpl: new . . .	367
\glsxtrfieldformatlist: new .	44	\GLSxtrtitletext: new	370
\glsxtrfootnotedesname: new	466	\glsxtrusealias: new	72
\glsxtrfootnotedes sort: new	466	long-em-noshort-em: removed \protect from \glsxtremsuffix	529
		long-em-noshort-em-desc: removed \protect from \glsxtremsuffix	533
		long-em-short-em: added missing text key	516
		removed \protect from \glsxtremsuffix	517
		long-hyphen-noshort-desc-noreg: added missing text key . . .	562

long-hyphen-postshort-hyphen:		\makenoidxglossaries: added	
added missing text key ...	572	\@domakeglossaries	80
long-hyphen-short-hyphen:		postfootnote: added missing	
added missing text key ...	556	text key	467
long-noshort-em: removed		prefix: new	24
\protect from		\RestoreAcronyms: added display	
\glxstremsuffix	527	style	179
long-noshort-em-desc: removed		\s@GlsXtrIfFieldValueInCsvList:	
\protect from		new	45
\glxstremsuffix	531	\seealso: add check for	
long-noshort-sc: moved		\also:	74
\protect inside		short-em: removed \protect	
\glxtrscsuffix	488	from \glxstremsuffix ...	523
long-noshort-sc-desc: moved		short-em-desc: removed	
\protect inside		\protect from	
\glxtrscsuffix	489	\glxstremsuffix	525
long-noshort-sm: removed		short-em-footnote: added	
\protect from		missing text key	535
\glxtrmsuffix	505	removed \protect from	
long-noshort-sm-desc: removed		\glxstremsuffix	535
\protect from		short-em-footnote-desc: new .	537
\glxtrmsuffix	507	short-em-long: added missing	
long-only-short-only: added		text key	518
missing text key	592	removed \protect from	
removed \protect from		\glxstremsuffix	519
\glxtronlysuffix	593	short-em-long-em: added	
long-postshort-user: added		missing text key	520
missing text key	543	removed \protect from	
long-short: added missing text		\glxstremsuffix	521
key	458	short-em-postfootnote: added	
long-short-em: added missing		missing text key	537
text key	514	removed \protect from	
removed \protect from		\glxstremsuffix	538
\glxstremsuffix	515	short-em-postfootnote-desc:	
long-short-sc: added missing		new	539
text key	479	short-footnote-desc: new ...	466
moved \protect inside		short-hyphen-long-hyphen:	
\glxtrscsuffix	480	added missing text key ...	579
long-short-sm: added missing		short-hyphen-postlong-hyphen:	
text key	497	added missing text key ...	586
removed \protect from		short-long: added missing text	
\glxtrmsuffix	497	key	461
long-short-user: added missing		short-long-user: added missing	
text key	542	text key	551
\makeglossaries: added		short-postfootnote-desc:	
\@domakeglossaries	180	added missing text key ...	469
let \@makeglossary to		new	469
\@gobble instead of \relax	182	short-postlong-user: added	
removed redefinition of		missing text key	548
\makeglossary	182		

short-sc: moved \protect inside		added leveloffset key	189
\glxtrscsuffix	484	\@glxtr@assign@leveloffset:	
short-sc-desc: moved \protect		new	189
inside \glxtrscsuffix	485	\@glxtr@leveloffset: new	189
short-sc-footnote: added		\@glxtr@noidx@do: replaced	
missing text key	491	\ifglshasparent with	
moved \protect inside		\@glxtr@ifischild	225
\glxtrscsuffix	492	\@print@unsrt@innnerglossary:	
short-sc-footnote-desc: new	493	new	218
short-sc-long: added missing		\doifglossarynoexistsordo:	
text key	481	switched to starred form of	
moved \protect inside		\ifglossaryexists	66
\glxtrscsuffix	482	\glswriteentry: replaced	
short-sc-postfootnote: added		\ifglused with	
missing text key	494	\GlsXtrIfUnusedOrUndefined	
moved \protect inside			144
\glxtrscsuffix	494	\glxtr@printgloss@checkexists:	
short-sc-postfootnote-desc:		new	185
new	496	\glxtralittreeSymbolDescLocation:	
short-sm: removed \protect		removed duplicate	
from \glxtrsmsuffix	501	description	688
short-sm-desc: removed		\ifglossaryexists: added check	
\protect from		for starred form	38
\glxtrsmsuffix	503	\np@glxtr@assign@leveloffset:	
short-sm-footnote: added		new	189
missing text key	508	\p@glxtr@assign@leveloffset:	
removed \protect from		new	189
\glxtrsmsuffix	509	\pp@glxtr@assign@leveloffset:	
short-sm-footnote-desc: new	511	new	189
short-sm-long: added missing		\printunsrtglossary: added	
text key	499	check for	
removed \protect from		\@printgloss@checkexists	214
\glxtrsmsuffix	499	printunsrtglossarywrap: new	217
short-sm-postfootnote: added		\printunsrtinnnerglossary:	
missing text key	511	new	217
removed \protect from		1.45 – 2020-04-01	
\glxtrsmsuffix	512	General: removed duplicate	
short-sm-postfootnote-desc:		description	685
new	513	\glstreenonameChildDescLoc:	
1.42 – 2020-02-13		new	685
\@glossentrysymbol: new	318	\glstreenonameDescLoc: new	685
\glsentrypdsymbol: new	318	1.46 – 2021-09-18	
1.42 – ?		\@glxtrsetaliasnoindex:	
postfootnote-desc: new	470	changed to use starred version	
1.43 – 2020-02-28		of \glxtrifhasfield	142
\@glxtrentryfmt: changed \def		1.46 – 2021-09-20	
to \edef to avoid infinite		General: changed \edef to	
recursion	43	\protected@edef	77, 326
1.44 – 2020-03-23		\@@glxtr@record: changed	
General: added groups key	189	\edef to \protected@edef	6

\@newglossaryentry@defunitcounters:	\protected@xdef	186
changed \edef to	\@glstr@rglstrigger@record:	
\protected@edef	changed \edef to	
\@glossentrysymbol: changed	\protected@edef	232
\edef to \protected@edef	\@glstr@warn@hybrid@noprintgloss:	
318	new	13
\@gls@increment@currunitcount:	\@glstr@entryfmt: changed	
changed \edef to	\edef to \protected@edef .	43
\protected@edef	\@glstr@glossentry: changed	
170	\edef to \protected@edef	209
\@gls@link: changed \edef to	\@glstr@glossentryother:	
\protected@edef	changed \edef to	
106, 107	\protected@edef	211
\@gls@link@checkfirsthyper:	\@glstr@indexaliased: changed	
changed \edef to	\edef to \protected@edef	142
\protected@edef	\@makeglossaries@warn@noprintglossary:	
140	new	180
\@gls@local@increment@currunitcount:	\@newglossaryentryposthook:	
changed \edef to	changed \edef to	
\protected@edef	\protected@edef	77, 78
170	\@print@unsrt@glossary:	
\@gls@setup@default@access:	changed \eappto to	
changed \edef to	\protected@eappto	215
\protected@edef	\@print@unsrt@innerglossary:	
272, 273	changed \eappto to	
\@glsadd: changed \edef to	\protected@eappto	219
\protected@edef	\@printunsrt@glossary@handler:	
109	changed \xdef to	
\@glstr@addabbreviationlist:	\protected@xdef	221
changed \eappto to	\glossentrydesc: changed \edef	
\protected@eappto	to \protected@edef . .	301, 302
177	\Glossentryname: changed \edef	
changed \edef to	to \protected@edef . .	305, 306
\protected@edef	\glossentryname: changed \edef	
177	to \protected@edef . .	302, 304
\@glstr@bibgls@removespaces:	\glossentrynameother: changed	
changed \x to \@glo@tmp . .	\edef to \protected@edef	309
606	\glsalttreechildpredesc: new	688
\@glstr@do@inc@linkcount:	\glsalttreepredesc: new	688
changed \x to \@glo@tmp . .	\glsdisablehyper: changed	
237	\edef to \protected@edef	150
\@glstr@do@record@wrglossary:	\glsdoifexists: changed \edef	
changed \edef to	to \protected@edef	65
\protected@edef	\glsenableentryunitcount:	
5	changed \edef to	
\@glstr@do@redef@for@glentries:	\protected@edef	172, 173
changed \edef to	\glsFindWidestLevelTwo:	
\protected@edef	changed \edef to	
4	\protected@edef	693
\@glstr@get@prefixedlabel:		
changed \edef to		
\protected@edef		
612		
changed \x to \@glo@tmp . .		
614		
\@glstr@get@prefixedlabel@field:		
changed \x to \@glo@tmp . .		
618		
\@glstr@mixed@assign@sortkey:		
changed \edef to		
\protected@edef		
190		
\@glstr@op@recordcounter:		
changed \eappto to		
\protected@eappto		
11		
\@glstr@orgprintglossary:		
changed \xdef to		

<code>\glsFindWidestUsedLevelTwo:</code>	changed <code>\edef</code> to		changed <code>\edef</code> to	
<code>\protected@edef</code>	692		<code>\protected@edef</code>	181–183
<code>\glsnavhyperlink:</code> changed			<code>\makenoidxglossaries:</code> changed	
<code>\edef</code> to <code>\protected@edef</code>	147		<code>\edef</code> to <code>\protected@edef</code> .	80
<code>\glstopicAssignSubIndent:</code> bug			<code>printunsrtglossarywrap:</code>	
182 maintain hangindent for			changed <code>\xdef</code> to	
multiple paragraphs	775		<code>\protected@xdef</code>	218
<code>\glstopicsubitemhangindent:</code>			<code>record:</code> added hybrid	14
new	775		<code>\setabbreviationstyle:</code> changed	
<code>\glstopicSubItemParIndent:</code>			<code>\edef</code> to <code>\protected@edef</code>	355
new	775		<code>topic:</code> added <code>\par</code> (bug 176) . .	773
<code>\glsxtr@org@newignoredglossary:</code>			grouping added to scope	
changed <code>\eappto</code> to			<code>\everypar</code> (bug 182)	773
<code>\protected@eappto</code>	62	1.47 –		
changed <code>\edef</code> to			<code>\@GlsXtrIfValueInFieldCsvList:</code>	
<code>\protected@edef</code>	62		new	46
<code>\glsxtr@provideignoredglossary:</code>			<code>\@xGlsXtrIfValueInFieldCsvList:</code>	
changed <code>\eappto</code> to			new	46
<code>\protected@eappto</code>	64		<code>\s@GlsXtrIfValueInFieldCsvList:</code>	
changed <code>\edef</code> to			new	46
<code>\protected@edef</code>	63		<code>\s@xGlsXtrIfValueInFieldCsvList:</code>	
<code>\glsxtr@s@newignoredglossary:</code>			new	47
changed <code>\edef</code> to		1.47 – 2021-11-04		
<code>\protected@edef</code>	62		<code>\@GlsXtrIfHasNonZeroChildCount:</code>	
<code>\glsxtr@s@provideignoredglossary:</code>			new	600
changed <code>\edef</code> to			<code>\@glsxtrcopytoglossary:</code>	
<code>\protected@edef</code>	64		replaced <code>\cseappto</code> with	
<code>\glsxtr@setaccessdisplay:</code>			<code>\protected@cseappto</code>	64
changed <code>\edef</code> to			<code>\@glsxtrforcsvfield:</code> new . . .	44
<code>\protected@edef</code>	308		<code>\@glsxtrsetaliasnoindex:</code>	
<code>\glsxtralttreeSymbolDescLocation:</code>			changed to use <code>\ifcvoid</code> .	142
switch to using			<code>\glsaltlistitem:</code> new	667
<code>\glsalttreepredesc</code> and			<code>\glslistexpandedname:</code> new . .	666
<code>\glsalttreechildpredesc</code>	688		<code>\glslistgroupafterheader:</code>	
<code>\glsxtrdisplayendloc:</code> changed			new	667
<code>\edef</code> to <code>\protected@edef</code>	196		<code>\glslistgroupheaderitem:</code> new	667
<code>\glsxtrdisplaystartloc:</code>			<code>\glslistinit:</code> new	665
changed <code>\edef</code> to			<code>\glslistitem:</code> new	665
<code>\protected@edef</code>	196		<code>\glsseefirstitem:</code> new	74
<code>\glsxtrdoautoindexname:</code>			<code>\glsseelastoxfordsep:</code> new . .	74
changed <code>\eappto</code> to			<code>\glsseelist:</code> redefined	72
<code>\protected@eappto</code>	313		<code>\glsunsetcategoryattribute:</code>	
<code>\glsxtrseelist:</code> changed <code>\edef</code>			new	294
to <code>\protected@edef</code>	72		<code>\glsxtrapptocsvfield:</code> new . .	50
<code>\glsxtrtreechildpredesc:</code> new	681		<code>\glsxtrfieldtitlecasecs:</code>	
<code>\glsxtrtreepredesc:</code> new	681		added check for	
<code>\makeglossaries:</code> adjust warning			<code>\glscapitalisewords</code>	300
on missing glossary for			<code>\GlsXtrIfHasNonZeroChildCount:</code>	
“alsoindex”	181		added starred version	600

\GlsXtrIfValueInFieldCsvList:		\@gls@combined@postlinks:	
new	46	new	393
\s@glstrforcsvfield: new	45	\@gls@combined@textformat:	
\s@GlsXtrIfFieldNonZero: new	47	new	391
\s@GlsXtrIfHasNonZeroChildCount:		\@gls@combined@usedprefix:	
new	600	new	392
\xGlsXtrIfValueInFieldCsvList:		\@gls@combined@usedskipmain:	
new	46	new	392
1.48 – 2021-11-22		\@gls@combined@usedskipothers:	
\@@gls@navhypertarget: new	147	new	392
\@mgls@hyperlink: new	403	\@gls@combined@usedsuffix:	
\@GlsXtrMglsOrGls: new	429	new	392
\@Glsfieldorgls: new	434	\@gls@do@glunset: new	141
\@Glsfullorfirst@: new	431	\@gls@restore@glsllocal: new	141
\@Glslongortext@: new	431	\@gls@save@glsllocal: new	141
\@Glsshortortext@: new	431	\@glsfieldorgls: new	434
\@PGLSorgls: new	435	\@glsfullorfirst@: new	431
\@PGLSorglspl: new	435	\@glslongortext@: new	431
\@Pglsorgls: new	435	\@glsnavhypertarget: added	
\@Pglsorglspl: new	435	patch	147
\@alt@GlsXtrMglsOrGls: new	429	\@glsshortortext@: new	431
\@def@multi@glossaryentry:		\@glsshowtarget: new	34
new	394	\@glsshowtargetmarkfmt: new	34
\@defmultiglossaryentry: new	394	\@glssymbolorgls: new	433
\@firstofthree: new	409	\@glssymbolorgls: new	433
\@gls@combined@category: new	391	\@glstr@addunused: added	
\@gls@combined@encapmain:		check for multientry labels	79
new	390	\@glstr@do@org@target: new	190
\@gls@combined@encapothers:		\@glstr@doshowtarget: new	28
new	391	\@glstr@mglslake: new	428
\@gls@combined@firstprefix:		\@glstr@mglssrefs: new	426
new	392	\@glstr@mglswrite: new	426
\@gls@combined@firstskipmain:		\@glstr@multientry: new	398
new	392	\@glstr@seefirstitem: new	74
\@gls@combined@firstskipothers:		\@glstr@seeitem: new	74
new	392	\@glstrmultientryadjustedname:	
\@gls@combined@firstsuffix:		new	623
new	392	\@glstrshowtargetleft: new	29
\@gls@combined@hyper: new	390	\@glstrshowtargetmark: new	29
\@gls@combined@indexmain:		\@glstrshowtargetright: new	29
new	390	\@mgls@all: new	402
\@gls@combined@indexothers:		\@mgls@disable@writeseparateref@cond:	
new	390	new	427
\@gls@combined@mglsopts: new	391	\@mgls@hyper: new	403
\@gls@combined@mglsopts@do:		\@mgls@hyperlink: new	403
new	391, 392	\@mgls@main: new	402
\@gls@combined@mpostlink:		\@mgls@others: new	402
new	393	\@mgls@resetall: new	404
\@gls@combined@mpostlinkelement:		\@mgls@resetmain: new	405
new	393	\@mgls@resetothers: new	405

\@mgl@setup: new	402	\glsshowtarget: removed check	
\@mgl@setup@do: new	402	for \glsshowtargetouter	34
\@mgl@setup@do@not: new	402	\glsshowtargetfont: new	33
\@mgl@unsetaction: new	403	\glsshowtargetinner: new	33
\@mgl@unsetall: new	405	\glsshowtargetinnersymleft:	
\@mgl@unsetmain: new	405	new	33
\@mgl@unsetothers: new	406	\glsshowtargetinnersymright:	
\@mgl@localreset: new	400	new	34
\@mgl@localunset: new	400	\glsshowtargetouter: new	34
\@mgl@reset: new	399	\glxtr@mgl@applyopts: new	408
\@mgl@unset: new	399	\glxtr@mgl@checklastelement:	
\@multi@glossary@doifexists:		new	407
new	395	\glxtr@mgl@inner: new	409
\@multi@glossary@entry: new	395	\glxtr@newmgl: new	427
\@multi@glossary@entry: new	394	\glxtr@setup@docurrent: new	406
\@multi@glossary@entry@list:		\glxtr@dohyperlink: added	
new	395	check for multi-entry	149
\@multiglossary@entry: new	394	\glxtr@ifmulti: new	393
\@pglsorgls: new	435	\glxtr@longshortscuserdescname:	
\@pglsorglspl: new	435	new	547
\@provide@multi@glossary@entry@noop:		\glxtr@longshortscuserdescname:	
new	395	new	545
\@secondofthree: new	409	\GlsXtrMglOrGls: new	428
\@thirdofthree: new	409	\glxtr@mgl@WarnAllSkipped:	
\alt@GlsXtrMglOrGls: new	428	new	408
\gl@abbrvs@onlyfont: new	595	\GLSxtr@multientry@adjustedname:	
\gl@abbrvs@userfont: new	545	new	622
\gl@combined@firstsep: new	423	\GlsXtr@multientry@adjustedname:	
\gl@combined@firstsep@first:		new	622
new	423	\Glsxtr@multientry@adjustedname:	
\gl@combined@sep: new	422	new	622
\gl@combined@sep@first: new	423	\glxtr@multientry@adjustedname:	
\gl@doshowtarget: new	33	new	621
\gl@first@abbrvs@onlyfont:		\GLSxtr@multientry@adjustednamefmt:	
new	595	new	624
\gl@first@abbrvs@userfont:		\GlsXtr@multientry@adjustednamefmt:	
new	545	new	624
\gl@link@wrcontent: new	105	\Glsxtr@multientry@adjustednamefmt:	
\gl@nav@hypertarget: new	147	new	624
\gl@set@categories@attribute:		\glxtr@multientry@adjustednamefmt:	
new	293	new	624
\gl@set@categories@attributes:		\GLSxtr@multientry@adjustedname@other:	
new	293	new	624
\gl@set@combined@sep@abbrv@nbsp:		\GlsXtr@multientry@adjustedname@other:	
new	423	new	624
\gl@set@combined@sep@abbrv@none:		\Glsxtr@multientry@adjustedname@other:	
new	424	new	624
\gl@set@combined@sep@narrow:		\glxtr@multientry@adjustedname@other:	
new	424	new	624

\glstrmultientryadjustednamepostsep:	\mglselementprehook: new ...	422
new	\mglselementreset: new	404
\glstrmultientryadjustednamepresep:	\mglselementunset: new	404
new	\mgl\$field: new	434
\glstrmultientryadjustednamesep:	\mgl\$forelements: new	403
new	\mgl\$forotherelements: new ..	403
\glstrmultilasttootherindex:	\Mgl\$full: new	432
new	\mgl\$full: new	432
\glstrmultilist: new	\mgl\$hascategoryprefix: new ..	421
\glstrmultimain: new	\mgl\$hascategorysuffix: new ..	422
\glstrmultimainindex: new ..	\mgl\$lastelementpostlinkhook:	
\glstrmultitotalelements:	new	421
new	\mgl\$lastmainpostlinkhook:	
\glstrsconlydescname: new ..	new	421
\glstrsconlydescsort: new ..	\mgl\$localreset: new	400
\glstrsconlyname: new	\mgl\$localunset: new	399
\glstrsconlysuffix: new ...	\mgl\$localunsetothers: new ..	404
\glstrscusersuffix: new ...	\Mgl\$long: new	432
\glstrshowtargetinner: new ..	\mgl\$long: new	432
\glstrshowtargetouter: new ..	\MGL\$mainpl: new	431
\glstrshowtargetsymbolleft:	\MGL\$mainpl: new	430
new	\Mgl\$mainpl: new	430
\glstrshowtargetsymbolright:	\mgl\$mainpl: new	429
new	\MGL\$name: new	433
\if@mgl\$@writeseparaterefs:	\Mgl\$name: new	433
new	\mgl\$name: new	433
\ifKV@mgl\$@presetlocal: new ..	\MGL\$pl: new	431
\ifmgl\$used: new	\MGL\$pl: new	430
\ifmultiglossaryentryglobal:	\Mgl\$pl: new	430
new	\mgl\$pl: new	429
long-only-short-sc-only: new	\mgl\$prefix: new	422
long-only-short-sc-only-desc:	\mgl\$reset: new	399
new	\mgl\$resetall: new	400
long-postshort-sc-user: new ..	\mgl\$seefirstitem: new	74
long-postshort-sc-user-desc:	\mgl\$seeitem: new	74
new	\mgl\$SetMain: new	400
\MGL\$: new	\mgl\$SetOptions: new	401
\Mgl\$: new	\Mgl\$short: new	432
\Mgl\$: new	\mgl\$short: new	432
\mgl\$: new	\mgl\$suffix: new	422
\mgl\$@disable@mgl\$opts: new ..	\MGL\$symbol: new	434
\mgl\$@disable@setup: new ...	\Mgl\$symbol: new	433
\mgl\$@enable@mgl\$opts: new ..	\mgl\$symbol: new	433
\mgl\$@enable@setup: new	\mgl\$sunset: new	399
\mgl\$AddOptions: new	\mgl\$sunsetall: new	400
\mgl\$custompostlinkhook: new	\mgl\$sunsetothers: new	404
\mgl\$defcategoryprefix: new ..	\mgl\$usecategoryprefix: new ..	421
\mgl\$defcategorysuffix: new ..	\mgl\$usecategorysuffix: new ..	422
\mgl\$elementindex: new	\MGL\$usefield: new	434
\mgl\$elementposthook: new ..	\Mgl\$usefield: new	434

\mglseusefield: new	434	\@@glxstr@dorecord: new	8
\mglswriteSeparateRefsFalse:		\@@glxstr@setup@bibgliaux:	
new	427	new	15
\mglswriteSeparateRefsTrue:		\@@glxstrbuffer@check@repeats:	
new	427	new	160
\MPGLS: new	437	\@@glxstrbuffer@check@repeats@notused:	
\MPGLs: new	436	new	160
\Mpgls: new	436	\@@glxstrbuffer@do@check@repeat:	
\mpgls: new	435	new	160
\MPGLSmainpl: new	437	\@@glxstrwrglosscountermark:	
\MPGLsmainpl: new	437	new	28
\Mpglsmainpl: new	436	\@@newglossaryentry@defcounters:	
\mpglsmainpl: new	436	new	165
\MPGLSpl: new	437	\@GLSXTrhiername: new	71
\MPGLspl: new	436	removed unwanted eol	71
\Mpglspl: new	436	\@GLSXtrhiername: new	71
\mpglspl: new	436	\@GLsXtrhiername: new	70
\mpglsWarning: new	435	\@GLsentryfield: new	31
\multiglossaryentry: new	393	\@GLsxfmt: new	42
\multiglossaryentrysetup:		\@GLsxtrhiername: new	70
new	390	\@bibglswrite@aux: new	16
\p@GLsXtrMglsOrGls: new	429	\@d@inner@GLSfield: new	621
\providemultiglossaryentry:		\@d@inner@GLsfield: new	621
new	395	\@d@inner@glslfield: new	620
\s@GLsXtrMglsOrGls: new	429	\@dGLS@field: new	620
showtargets: new	29	\@dGLSfield: new	620
\writemultiglossentry: new	398	\@dGLs@field: new	620
1.49 – 2022-10-14		\@dGLsdisp: new	616
General: add gettitlestring patch		\@dGLsfield: new	619
for		\@dGLslink: new	615
\glxstrtitleorpdforheading		\@dglsl@field: new	619
.....	362	\@dglslsdisp: new	616
added		\@dglslfield: new	619
\glssubgroupheading	666,	\@dglslslink: new	615
669–676, 679–685,		\@glsl@alt@hyp@opt: changed	
699, 700, 702–706, 708, 710, 711		\let to \def for	
added postamble key for		\@glsl@hyp@opt@cs	145
printgloss	188	\@glsl@assign@actual: removed	
added preamble key for		use of \pdfstringdef	272
printgloss	188	\@glsl@automake@types: new	180
added flatten key	189	\@glsl@default@glslslink@opts:	
corrected name of		new	141
longpluralaccess field	270	\@glsl@default@restore@glslslocal:	
new	778	new	141
split shortplural and longplural		\@glsl@do@glslsreset: new	101
into separate family	326	\@glsl@do@glslspreunset: new	102
\@@dglsl@: new	614	\@glsl@glslslink@hyper@update@hook:	
\@@dglsl@@field: new	619	new	102
\@glsl@expand@field: added		\@glsl@ignore@restore@glslslocal:	
redefinition	60	new	141

\@gls@link@postkeys@checkfirsthyper:	\@glsxtr@unsrt@gloss@init:
new 139	new 216
\@gls@noexpand@field: added	save hierarchical level
redefinition 59	information 216
\@gls@warn@makegloss@incompatible:	\@glsxtrbuffer@check@repeats:
new 185	new 160
\@gls@warn@noidx@incompatible:	\@glsxtrcopytoglossary: new . 64
new 82	\@glsxtrglossentryother: bug
\@glsxtr@initprocess: new . 216	fix: corrected arguments to
\@glslink@prefix@label: new . 105	\GlsXtrStandaloneEntryOther
\@glstable@defaultpreamble: 212
new 812	\@glsxtrhiername: new 69
\@glsuseri@: added redefinition 124	\@glsxtrnewglslink: new 227
\@glsuserii@: added	\@glsxtrnoidxgroups@nomakegloss:
redefinition 125	new 193
\@glsuseriii@: added	\@glsxtrundefdebug: new 28
redefinition 126	\@glsxtrwrglosscountermark:
\@glsuseriv@: added	new 27
redefinition 128	\@noglslink@prefix@label:
\@glsuserv@: added redefinition 129	new 106
\@glsuservi@: added	\@p@glossarysection: moved
redefinition 130	\phantomsection 58
\@glsxtr@assignMakeUppercase:	\@set@bibgls@write@aux: new . 16
new 32	\@xp@gls@getcounterprefix:
\@glsxtr@current@innertextformat@csname: new 36	
new 103	abbr-long-short: new 750
\@glsxtr@current@textformat@csname:	abbr-short-long: new 748
new 103	bibglsaux: new 15
\@glsxtr@dglsnomatch: new .. 611	bookindex: added
\@glsxtr@field@linkdefs:	\glssubgroupheading 719
removed \glsinsert 111	replaced \edef with
\@glsxtr@get@prefixedlabel@field:	\protected@edef 717
new 616	\d@inner@GLSfield: new 621
\@glsxtr@inc@indexcount: new 143	\d@inner@Glsfield: new 620
\@glsxtr@local@innertextformat:	\d@inner@glsfield: new 620
new 104	desc-name: new 792
\@glsxtr@noidx@do: check if	\dGlsdisp: new 616
location field has been	\dGLSfield: new 620
changed 225	\dGlsfield: new 619
\@glsxtr@providenewglsfamily:	\dglsgfield: new 619
new 227	\dglsgfieldactualfieldlabel:
\@glsxtr@providenewglslink:	new 619
new 227	\dglsgfieldcurrentfieldlabel:
\@glsxtr@restoreMakeUppercase:	new 619
new 32	\dglsgfieldfallbackfieldlabel:
\@glsxtr@saveMakeUppercase:	new 619
new 32	\dGlslink: new 615
\@glsxtr@setup@bibglsaux: new 15	\GlossariesAbbrStyleTooComplexWarning:
\@glsxtr@truevalue: new 296	new 356

\gls@warn@makegloss@incompatible:	\GLSaccessfmtsymbolplural:
new 185	new 248, 281
\gls@warn@noidx@incompatible:	\Glsaccessfmtsymbolplural:
new 82	new 247, 281
\gls@warn@noidxmakegloss@incompatible:	\glsaccessfmtsymbolplural:
new 82	new 247, 280
\glsabspc: new 179	\GLSaccessfmttext: new . 241, 277
\GLSaccessfmtdesc: new . 249, 282	\Glsaccessfmttext: new . 240, 277
\Glsaccessfmtdesc: new . 248, 281	\glsaccessfmttext: new . 240, 277
\glsaccessfmtdesc: new . 248, 281	\GLSaccessfmtuseri: new 258, 286
\GLSaccessfmtdescplural:	\Glsaccessfmtuseri: new 257, 286
new 250, 282	\glsaccessfmtuseri: new 256, 286
\Glsaccessfmtdescplural:	\GLSaccessfmtuserii: new 260, 287
new 250, 282	\Glsaccessfmtuserii: new 259, 287
\glsaccessfmtdescplural:	\glsaccessfmtuserii: new 258, 286
new 249, 282	\GLSaccessfmtuseriii:
\GLSaccessfmtfirst: new 244, 279	new 262, 288
\Glsaccessfmtfirst: new 243, 278	\Glsaccessfmtuseriii:
\glsaccessfmtfirst: new 243, 278	new 262, 288
\GLSaccessfmtfirstplural:	\glsaccessfmtuseriii:
new 245, 279	new 261, 287
\Glsaccessfmtfirstplural:	\GLSaccessfmtuseriv: new 265, 289
new 244, 279	\Glsaccessfmtuseriv: new 264, 288
\glsaccessfmtfirstplural:	\glsaccessfmtuseriv: new 263, 288
new 244, 279	\GLSaccessfmtuserv: new 267, 290
\GLSaccessfmtlong: new . 254, 285	\Glsaccessfmtuserv: new 266, 289
\Glsaccessfmtlong: new . 254, 284	\glsaccessfmtuserv: new 265, 289
\glsaccessfmtlong: new . 253, 284	\GLSaccessfmtuservi: new 269, 290
\GLSaccessfmtlongpl: new 255, 285	\Glsaccessfmtuservi: new 269, 290
\Glsaccessfmtlongpl: new 255, 285	\glsaccessfmtuservi: new 268, 290
\glsaccessfmtlongpl: new 254, 285	\GLSaccessuseri: new ... 257, 286
\GLSaccessfmtname: new . 240, 276	\Glsaccessuseri: new ... 256, 286
\Glsaccessfmtname: new . 239, 276	\glsaccessuseri: new ... 256, 286
\glsaccessfmtname: new . 239, 276	\GLSaccessuserii: new .. 260, 287
\GLSaccessfmtplural: new 242, 278	\Glsaccessuserii: new .. 259, 287
\Glsaccessfmtplural: new 242, 278	\glsaccessuserii: new .. 258, 286
\glsaccessfmtplural: new 241, 277	\GLSaccessuseriii: new . 262, 288
\GLSaccessfmtshort: new 252, 283	\Glsaccessuseriii: new . 261, 287
\Glsaccessfmtshort: new 251, 283	\glsaccessuseriii: new . 260, 287
\glsaccessfmtshort: new 251, 283	\GLSaccessuseriv: new .. 264, 289
\GLSaccessfmtshortpl:	\Glsaccessuseriv: new .. 263, 288
new 253, 284	\glsaccessuseriv: new .. 263, 288
\Glsaccessfmtshortpl:	\GLSaccessuserv: new ... 267, 289
new 252, 284	\Glsaccessuserv: new ... 266, 289
\glsaccessfmtshortpl:	\glsaccessuserv: new ... 265, 289
new 252, 283	\GLSaccessuservi: new .. 269, 290
\GLSaccessfmtsymbol: new 246, 280	\Glsaccessuservi: new .. 268, 290
\Glsaccessfmtsymbol: new 246, 280	\glsaccessuservi: new .. 267, 290
\glsaccessfmtsymbol: new 245, 280	\glsaddallunindexed: new ... 144
	\glsalttreesubgroupitem: new 700

\glsapptopostlink: new	322	\Glsfmttext: added	
\glsdefaultshortaccess:		\MFUsentencecase	379
reverted to original definition	271	\glsгенentryfmt: added	
\glsdoifexists: added		redefinition	94
\glstrundefdebug	65	\glshashchar: new	599
\glsenableentryunitcount:		\glsifapplyinnerfmtfield: new	94
added		\glsifattributetrue: new	296
\ifglsresetcurrcount	172, 173	\glsifcategoryattributehasitem:	
\glsencapwrcontent: new	144	new	296
\glsentryindexcount: new	144	\glsifcategoryattributetrue:	
\glsexclapplyinnerfmtfield:		new	296
new	94	\glsifindexed: new	144
\glsfirstinnerfmtabbrvfont:		\glsindexsetting: new	30
new	335	\glsindexsubgroupitem: new	679
\glsfirstinnerfmtlongfont:		\glsinitreunsets: new	103
new	336	\glsinnerfmtabbrvfont: new	336
\glsfirstxppabbrvfont: new	335	\glsinnerfmtlongfont: new	336
\glsfirstxplongfont: new	337	\glslinkwrcontent: removed	
\GLSfmtfield: new	93	grouping	105
\Glsfmtfield: new	92	\glslongextraDescSymHeader:	
\glsfmtfield: new	92	new	748
\Glsfmtfirst: added		\glslongextraDescSymTabularFooter:	
\MFUsentencecase	380	new	748
\Glsfmtfirstpl: added		\glslongextraDescSymTabularHeader:	
\MFUsentencecase	380	new	748
\GLSfmtfull: add upper case		\glslongextraLongFmt: new	722
bookmark	382	\glslongextraLongHeader: new	750
\Glsfmtfull: added		\glslongextraLongShortHeader:	
\MFUsentencecase	382	new	751
\GLSfmtfullpl: add upper case		\glslongextraLongShortTabularFooter:	
bookmark	383	new	752
\Glsfmtfullpl: added		\glslongextraLongShortTabularHeader:	
\MFUsentencecase	382	new	751
\GLSfmtinsert: new	93	\glslongextraShortHeader:	
\glsfmtinsert: new	93	new	750
\Glsfmtlong: added		\glslongextraShortLongHeader:	
\MFUsentencecase	381	new	749
\Glsfmtlongpl: added		\glslongextraShortLongTabularFooter:	
\MFUsentencecase	381	new	750
\Glsfmtname: added		\glslongextraShortLongTabularHeader:	
\MFUsentencecase	379	new	750
\Glsfmtplural: added		\glslongextraShortNoNameSetDescWidth:	
\MFUsentencecase	379	new	726
\GLSfmtshort: new	378	\glslongextraShortTargetFmt:	
\Glsfmtshort: added		new	722
\MFUsentencecase	378	\glslongextraSubGroupHeading:	
\GLSfmtshortpl: new	378	new	724
\Glsfmtshortpl: added		\glslongextraSubLongFmt: new	723
\MFUsentencecase	378	\glslongextraSubShortTargetFmt:	
		new	723

<code>\glslongextraSubSymbolOrName:</code>	<code>\glstableblockalign: new ...</code>	789
new	<code>\glstableblockentry: new ...</code>	789
<code>\glslongextraSubSymbolTargetFmt:</code>	<code>\glstableblockheader: new ..</code>	789
new	<code>\glstableblockperrowcount:</code>	
<code>\glslongextraSymbolNameAlign:</code>	new	778
new	<code>\glstableblocksubentry: new .</code>	789
<code>\glslongextraSymbolOrName:</code>	<code>\glstableblocksubentrysep:</code>	
new	new	779
<code>\glslongextraSymbolTargetFmt:</code>	<code>\glstableblockwidth: new ...</code>	809
new	<code>\glstablecaption: new</code>	807
<code>\glslongextraSymDescHeader:</code>	<code>\glstablecenteralign: new ..</code>	780
new	<code>\glstableChildEntries: new .</code>	819
<code>\glslongextraSymDescTabularFooter:</code>	<code>\glstablecolsperblock: new .</code>	788
new	<code>\glstablecurrentblockindex:</code>	
<code>\glslongextraSymDescTabularHeader:</code>	new	778
new	<code>\glstableDesc: new</code>	787
<code>\glslongextraSymNoNameSetDescWidth:</code>	<code>\glstabledesccolalign: new .</code>	780
new	<code>\glstableDescFmt: new</code>	787
<code>\glslowercase: new</code>	<code>\glstabledescheader: new ...</code>	779
31	<code>\glstabledescwidth: new</code>	809
<code>\glsmfuaddmap: new</code>	<code>\glstableDescWithOther: new .</code>	787
32	<code>\glstablefinishlengthupdates:</code>	
<code>\glsmfublocker: new</code>	new	789
32	<code>\glstablefinishrow: new</code>	819
<code>\glsmfuexcl: new</code>	<code>\glstablefirstthead: new</code>	808
32	<code>\glstablefoot: new</code>	808
<code>\glspretopostlink: new</code>	<code>\glstableGroupHeaderFmt: new</code>	811
322	<code>\glstablegroupheading: new .</code>	811
<code>\glssentencecase: new</code>	<code>\glstablehead: new</code>	808
31	<code>\glstableHeaderFmt: new</code>	788
<code>\glsssetcategoryattributes:</code>	<code>\glstableiffilter: new</code>	809
new	<code>\glstableifmeasuring: new ..</code>	809
294	<code>\glstableifpar: new</code>	780
<code>\glsssetcombinedsepabbrvnbsps:</code>	<code>\glstableinitlengthupdates:</code>	
corrected spelling of	new	789
<code>\ifglshassshort</code>	<code>\glstablelastfoot: new</code>	808
423	<code>\glstableleftalign: new</code>	780
<code>\glsssetcombinedsepabbrvnnone:</code>	<code>\glstablelengthupdate: new .</code>	789
corrected spelling of	<code>\glstablemeasureandupdate:</code>	
<code>\ifglshassshort</code>	new	810
424	<code>\glstablenamecolalign: new .</code>	780
<code>\glssshowtargetfonttext: new .</code>	<code>\glstableNameFmt: new</code>	781
33	<code>\glstablenameheader: new ...</code>	778
<code>\glssshowtargetinner: added</code>	<code>\glstableNameNoDesc: new ...</code>	785
check for math mode	<code>\glstableNameSingleFmt: new .</code>	782
33	<code>\glstableNameSinglePostName:</code>	
<code>\glssubgroupheading: new ...</code>	new	783
224	<code>\glstableNameSinglePostSubName:</code>	
<code>\glstable@begin: new</code>	new	785
809		
<code>\glstable@blockalignsep: new</code>		
779		
<code>\glstable@child: new</code>		
818		
<code>\glstable@filter: new</code>		
809		
<code>\glstable@groupheading: new .</code>		
811		
<code>\glstable@ifhaspreamble: new</code>		
810		
<code>\glstable@init: new</code>		
810		
<code>\glstable@n@amps: new</code>		
819		
<code>\glstable@parcase: new</code>		
780		
<code>\glstable@stepentry: new ...</code>		
810		
<code>\glstable@stepsubentry: new .</code>		
810		

\glstableNameSingleSubSuppl:		\glstreeSubPreHeader: new ..	678
new	785	\glssupercase: new	31
\glstableNameSingleSuppl:		\glswrglossdisableanchorcmds:	
new	783	new	37
\glstableNameSingleSymSep:		\glxppabrvfont: new	336
new	783	\glxplongfont: new	336
\glstableNameTarget: new ..	781	\glxtr@check@complexstyle:	
\glstablenamewidth: new	809	new	356
\glstablenewstyle: new	789	\glxtr@do@ifcomplexstyle@allcaps:	
\glstablenextcaption: new ..	807	new	356
\glstableOther: new	781	\glxtr@do@ifcomplexstyle@insert:	
\glstableotherfield: new ...	781	new	356
\glstableotherheader: new ..	779	\glxtr@do@select@nameref@record:	
\glstableOtherNoDesc: new ..	788	new	612
\glstableOtherSep: new	783	\glxtr@doifexists: new	65
\glstablepostnextcaption:		\glxtr@doifnoexists: new ..	65
new	807	\GLSxtr@fullformat@fallback:	
\glstablePreChildren: new ..	779	new	334
\glstablerightalign: new ...	780	\GLSxtr@fullplformat@fallback:	
\glstablerowspan: new	808	new	334
\glstablesetstyle: new	789	\glxtr@mgl@sinner: initialise	
\glstableSubDesc: new	787	hooks	410
\glstableSubDescFmt: new ...	787	\glxtr@newabbreviation:	
\glstableSubDescWithOther:		added \glxtrorgkeylist ..	328
new	787	bug fix: markwords doesn't	
glstablesubentries: new	779	include plural suffix	329
\glstableSubNameFmt: new ...	781	\glxtr@processunknownoptions:	
\glstableSubNameNoDesc: new .	785	new	30
\glstableSubNameSingleFmt:		\glxtr@save@mfu: new	205
new	783	\glxtr@select@entry: new ..	612
\glstableSubNameTarget: new .	781	\glxtr@select@entry@nameref:	
\glstableSubOther: new	782	new	612
\glstableSubOtherNoDesc: new	788	\glxtr@shortfieldname: new .	98
\glstableSubSymbolFmt: new .	786	\glxtr@title@field: new ...	365
\glstableSubSymbolNameFmt:		\glxtr@wrglossary@encap:	
new	787	new	143
\glstableSubSymbolNameTarget:		\glxtr@writefields: encoding	
new	787	test replaced \ifdef with	
\glstableSymbolcolalign: new	780	\ifdefvoid and reversed	
\glstableSymbolFmt: new	786	args	207
\glstableSymbolheader: new .	779	removed test for fontspec ...	207
\glstableSymbolNameFmt: new .	786	\glxtractualanchor: new ...	604
\glstableSymbolNameTarget:		\glxtrAddCounterRecordHook:	
new	786	new	208
\glstableSymbolwidth: new ..	809	\glxtraddgroup: new	220
\glstabletotalcols: new	778	\glxtraddunusedxrefs: new .	78
\glstexpdfstring: new	31	\glxtraliashook: new	78
\glstopicSubGroupHeading:		\glxtrassignactualsetup:	
new	773	added \glstextup	271
\glstreesubgroupitem: new ..	683		

<code>\glxstrassignlinktextfmt:</code>		<code>\glxstrGeneralLatinAtoGrules:</code>	
new	103	new	643
<code>\glxstrattrentrytextfmt: new</code>	91	<code>\glxstrGeneralLatinAtoMrules:</code>	
<code>\glxstrbookindexformatsubheader:</code>		new	643
new	715	<code>\glxstrGeneralLatinHtoMrules:</code>	
<code>\glxstrbookindexpostgroupskip:</code>		new	644
new	714	<code>\glxstrGeneralLatinNtoSrules:</code>	
<code>\glxstrbookindexpostsubgroupskip:</code>		new	644
new	714	<code>\glxstrGeneralLatinNtoZrules:</code>	
<code>\glxstrbookindexpregroupskip:</code>		new	643
new	714	<code>\glxstrGeneralLatinTtoZrules:</code>	
<code>\glxstrbookindexpresubgroupskip:</code>		new	644
new	714	<code>\glxstrgeneralpuncaccentsrules:</code>	
<code>\glxstrbookindexsubbookmark:</code>		new	633
new	715	<code>\glxstrgeneralpuncbracketrules:</code>	
<code>\GlsXtrClearUnsetBuffer: new</code>	161	new	634
<code>\glxstrcopytoglossary: added</code>		<code>\glxstrgeneralpuncmarksrules:</code>	
starred form	64	new	633
<code>\glxstrcurrentfield: new</code>	98	<code>\glxstrgeneralpuncquoterules:</code>	
<code>\glxstrdefaultentrytextfmt:</code>		new	634
new	91	<code>\glxstrgeneralpuncsignrules:</code>	
<code>\glxstrdefaultrevert: new</code>	337	new	636
<code>\glxstrdiscardperiodretainfirstuse:</code>		<code>\glxstrglossentryother: use</code>	
new	324	default header if first	
<code>\glxstrdoidentify: new</code>	226	argument empty	211
<code>\glxstrdopostpunc: made</code>		<code>\GLSxtrheadfirst: new</code>	371
robust	326	<code>\GLSxtrheadfirstplural: new</code>	373
<code>\GlsXtrDualBackLink: corrected</code>		<code>\GLSxtrheadfull: new</code>	376
false part	602	<code>\GLSxtrheadfullpl: new</code>	377
<code>\Glsxtrentryfmt: new</code>	43	<code>\GLSxtrheadlong: new</code>	374
<code>\Glsxtrfmt: new</code>	42	<code>\GLSxtrheadlongpl: new</code>	375
<code>\GLSxtrfullformat: new</code>	333	<code>\GLSxtrheadname: new</code>	368
<code>\Glsxtrfullformat: added check</code>		<code>\GLSxtrheadplural: new</code>	370
for insert inside and inner		<code>\GLSxtrheadshort: new</code>	367
fmt	333	<code>\GLSxtrheadshortpl: new</code>	367
<code>\glxstrfullformat: added check</code>		<code>\GLSxtrheadtext: new</code>	369
for insert inside and inner		<code>\GLSxtrhiername: added</code>	
fmt	332	<code>\expandafters</code>	71
<code>\GLSxtrfullplformat: new</code>	334	added <code>\glstexorpdfstring</code>	71
<code>\Glsxtrfullplformat: added</code>		<code>\GLSxtrhiername: added</code>	
check for insert inside and		<code>\expandafters</code>	71
inner fmt	333	added <code>\glstexorpdfstring</code>	71
<code>\glxstrfullplformat: added</code>		<code>\GlsXtrhiername: added</code>	
check for insert inside and		<code>\expandafters</code>	70
inner fmt	333	added <code>\glstexorpdfstring</code>	70
<code>\glxstrfullsaveinsert: new</code>	112	<code>\GLSxtrhiername: added</code>	
<code>\glxstrfullsep: added inner</code>		<code>\expandafters</code>	70
fmt	334	added <code>\glstexorpdfstring</code>	70
<code>\glxstrgenentrytextfmt: new</code>	92	<code>\glxstrhiername: added</code>	
<code>\glxstrGeneralInitRules: new</code>	627	<code>\expandafters</code>	69

added \glstexorpdfstring .	69	\glstrshowtargetsymbolright:	
\glstridentifyglfamily:		added check for math mode .	33
new	227	\GlsXtrStandaloneEntryHeadName:	
\glstridentifyglslink: new .	227	new	209
\glstrifallcaps: new	98	\GlsXtrStandaloneEntryHeadOther:	
\glstrifheaduc: new	156	new	212
\glstrifintoc: new	156	\GlsXtrStandaloneEntryPdfName:	
\glstrifwasglslake: new ...	97	new	209
\glstrifwasglslakeandfirstuse:		\GlsXtrStandaloneEntryPdfOther:	
new	98	new	212
\glstrifwassubsequentorshort:		\GLSxtrsubsequentfmt: new ..	353
new	98	\GLSxtrsubsequentplfmt: new .	354
\glstrifwassubsequentuse:		\glstrtaggedlist: new	73
new	98	\glstrtaggedlistsep: new ..	73
\glstrIgnorableRules: new .	627	\glstrtitlednamereflink:	
\GLSxtrinlinfullformat: new	334	new	605
\GLSxtrinlinfullplformat:		\glstrtitleopts: new	365
new	335	\glstrundefdebug: new	28
\GlsXtrLetField: corrected		\GlsXtrUnsetBufferDisableRepeatLocal:	
spelling	50	new	160
\Glsxtrlong: now simulates first		\GlsXtrUnsetBufferEnableRepeatLocal:	
use	344	new	160
\glstrMFUsave: new	205	\GLSxtrusefield: added	
\GlsXtrMglsOrGls: removed		uppercase PDF bookmark	
spurious \PLUS	428	alternative	49
\glstrnewglldisp: new	229	\Glsxtrusefield: now using	
\glstrnewglslink: new	228	\@Glsentryfield	49
\glstrnoidxgroups: new	193	\glstrwordsephyphen: new ..	327
\Glsxtrpdfentryfmt: new	43	\glstrwrglossarylocfmt: new	605
\glstrpostlinkAddDescOnFirstUse:		\glstrwrglosscountermark:	
added inner formatting ...	323	new	28
\glstrpostlinkAddSymbolOnFirstUse:		\ifglresetcurrcount: new ..	163
added inner formatting ...	323	\ifGlsXtrPrefixLabelFallbackLast:	
\glstrpostlinkSymbolDescSep:		new	612
new	324	\IfTeXParserLib: new	599
\glstrpreglossarystyle: new	87	long-desc-name: added	
\GlsXtrResetLocalBuffer: new	160	\glssubgroupheading	730
\glstrrevert: new	337	long-desc-sym: new	747
\glstrsaveinsert: new	112	long-desc-sym-name: added	
\glstrseelists: new	67	\glssubgroupheading	743
\glstrseelistsdelim: new ..	67	long-loc-desc-name: added	
\glstrseelistsencap: new ..	67	\glssubgroupheading	732
\glstrsetbibglaux: new ...	15	long-loc-desc-sym-name: added	
\glstrsetcomplexstyle: new .	355	\glssubgroupheading	745
\glstrsetlongfirstuse: new .	343	long-loc-sym-desc-name: added	
\GlsXtrSetPlusModifier: new .	146	\glssubgroupheading	742
\GlsXtrSetStarModifier: new .	146	long-name-desc: added	
\glstrshowtargetsymbolleft:		\glssubgroupheading	727
added check for math mode .	33	long-name-desc-loc: added	
		\glssubgroupheading	729

long-name-desc-sym: added		\Pglxtrtitleshort: new	387
\glssubgroupheading	733	\Pglxtrtitleshortpl: new . .	388
long-name-desc-sym-loc: added		\printunsrtglossaryunitpostskip:	
\glssubgroupheading	735	new	222
long-name-sym-desc: added		\printunsrttable: new	813
\glssubgroupheading	737	\prohibit@glxtrnoidxgroups:	
long-name-sym-desc-loc: added		new	193
\glssubgroupheading	738	\renewabbreviationstyle: reset	
long-sym-desc: new	745	subsequent fints	359
long-sym-desc-name: added		\s@glxtrcopytoglossary: new	65
\glssubgroupheading	740	\s@Glsxtrfmt: new	42
name: new	791	\setupglsadd: new	101
name-desc: new	789	\setupglslink: new	101
name-desc-symbol: new	799	\shortcut@GLS: new	20
name-other: new	803	\shortcut@Gls: new	20
name-symbol: new	791	\shortcut@gls: new	20
name-symbol-desc: new	795	\shortcut@GLSpl: new	20
\newdglfield: new	621	\shortcut@Glspl: new	20
\newdglfieldlike: new	621	\shortcut@glspl: new	20
other-name: new	804	shortcuts: abother	24
other-symbol: new	806	acother	24
\PGLSfmtlong: new	388	symbol-name: new	793
\Pglsfmtlong: new	388	symbol-other: new	805
\pglsfmtlong: new	388	table: new	819
\PGLSfmtlongpl: new	389	topic: added	
\Pglsfmtlongpl: new	389	\glssubgroupheading	772
\pglsfmtlongpl: new	388	topicmccols: added	
\PGLSfmtshort: new	387	\glssubgroupheading	777
\Pglsfmtshort: new	387	1.49 – 2022-10-24	
\pglsfmtshort: new	387	General: added glossaries-extra	
\PGLSfmtshortpl: new	388	abbrstyles.def	438
\Pglsfmtshortpl: new	387	\glxtremrevert: new	514
\pglsfmtshortpl: new	387	\glxtrfootnotelongformat:	
\PGLSprefix: new	383	new	453
\Pglsprefix: new	383	\glxtrfootnotelongplformat:	
\pglsprefix: new	383	new	453
\PGLSxtrlong: new	386	\GLSxtrlongformat: new	441
\Pglxtrlong: new	385	\Glsxtrlongformat: new	440
\pglxtrlong: new	385	\glxtrlongformat: new	439
\PGLSxtrlongpl: new	386	\GLSxtrlongformatgrp: new . .	444
\Pglxtrlongpl: new	386	\Glsxtrlongformatgrp: new . .	443
\pglxtrlongpl: new	386	\glxtrlongformatgrp: new . .	442
\PGLSxtrshort: new	384	\GLSxtrlonghyphennoshort:	
\Pglxtrshort: new	384	new	562
\pglxtrshort: new	384	\glxtrlonghyphennoshortdescsort:	
\PGLSxtrshortpl: new	385	new	562
\Pglxtrshortpl: new	385	\glxtrlonghyphennoshortsort:	
\pglxtrshortpl: new	384	new	569
\Pglxtrtitlelong: new	388	\GLSxtrlonghyphenshort: new .	554
\Pglxtrtitlelongpl: new . . .	389		

\glsxtrlonghyphenshortsort:		\glsxtrshorthyphenlong:	
new	556	new	554
\GLSxtrlongplformat: new ...	441	\GLSxtrshortlongformat: new .	453
\Glsxtrlongplformat: new ...	440	\Glsxtrshortlongformat: new .	452
\glsxtrlongplformat: new ...	439	\glsxtrshortlongformat: new .	452
\GLSxtrlongplformatgrp: new .	444	\GLSxtrshortlongplformat:	
\Glsxtrlongplformatgrp: new .	443	new	453
\glsxtrlongplformatgrp: new .	442	\Glsxtrshortlongplformat:	
\GLSxtrlongshortformat: new .	451	new	452
\Glsxtrlongshortformat: new .	451	\glsxtrshortlongplformat:	
\glsxtrlongshortformat: new .	450	new	452
\GLSxtrlongshortplformat:		\GLSxtrshortplformat: new ..	447
new	451	\Glsxtrshortplformat: new ..	446
\Glsxtrlongshortplformat:		\glsxtrshortplformat: new ..	445
new	451	\GLSxtrshortplformatgrp: new	450
\glsxtrlongshortplformat:		\Glsxtrshortplformatgrp: new	449
new	451	\glsxtrshortplformatgrp: new	448
\glsxtrpostabbrvfootnote:		\glsxtrsmrevert: new	497
new	463	\glsxtruserfieldfmt: new ...	540
\glsxtrpostfootnotelongformat:		\GLSxtruserlongformat: new .	455
new	453	\glsxtruserlongformat: new .	455
\GLSxtrposthyphenlong: new .	585	\GLSxtruserlongplformat: new	455
\GLSxtrposthyphenlongpl: new	586	\glsxtruserlongplformat: new	455
\glsxtrposthyphenlongpl: new	586	\GLSxtruserlongshortformat:	
\GLSxtrposthyphenshort: new .	570	new	456
\GLSxtrposthyphenshortpl:		\Glsxtruserlongshortformat:	
new	571	new	456
\glsxtrposthyphenshortpl:		\glsxtruserlongshortformat:	
new	571	new	456
\GLSxtrposthyphensubsequent:		\GLSxtruserlongshortplformat:	
new	572	new	457
\glsxtrpostuserlongformat:		\Glsxtruserlongshortplformat:	
new	455	new	456
\glsxtrpostusersshortformat:		\glsxtruserlongshortplformat:	
new	454	new	456
\glsxtrsconlyrevert: new ...	595	\GLSxtruserparen: new	541
\glsxtrscrevert: new	479	\glsxtruserparensep: new ...	540
\glsxtrscuserrevert: new ...	545	\GLSxtrusersshortformat: new .	454
\GLSxtrshortformat: new	446	\glsxtrusersshortformat: new .	454
\Glsxtrshortformat: new	445	\GLSxtrusersshortlongformat:	
\glsxtrshortformat: new	445	new	458
\GLSxtrshortformatgrp: new .	449	\Glsxtrusersshortlongformat:	
\Glsxtrshortformatgrp: new .	448	new	457
\glsxtrshortformatgrp: new .	447	\glsxtrusersshortlongformat:	
\GLSxtrshorthyphenlong: new .	578	new	457
\glsxtrshorthyphenlongsort:		\GLSxtrusersshortlongplformat:	
new	579	new	458
\GLSxtrshorthyphenlong:		\Glsxtrusersshortlongplformat:	
new	555	new	457

\glxtrusershortlongplformat:		\@glxtr@checkgroup: check	
new	457	nogroupskip setting	224
\GLSxtrusershortplformat:		\@print@unsrt@glossary: add	
new	454	post-begin hook	215
\glxtrusershortplformat:		add post-entry hook	215
new	454	add pre-end hook	216
postfootnote: removed redef of		add pre-entry hook	215
\glxtrsetupfulldefs ...	467	removed \glsresetentrylist	215
short-em-postfootnote:		\@print@unsrt@innerglossary:	
removed redef of		add post-entry hook	219
\glxtrsetupfulldefs ...	538	add pre-entry hook	219
short-em-postfootnote-desc:		all: added glossary-table	663
removed redef of		desc-other-name: new	797
\glxtrsetupfulldefs ...	540	desc-other-symbol-name: new .	801
short-postfootnote-desc:		desc-symbol-other-name: new .	801
removed redef of		\glslongextraCustomIIAlign:	
\glxtrsetupfulldefs ...	469	new	753
short-sc-postfootnote:		\glslongextraCustomIField:	
removed redef of		new	752
\glxtrsetupfulldefs ...	494	\glslongextraCustomIFmt: new	752
short-sc-postfootnote-desc:		\glslongextraCustomIHeader:	
removed redef of		new	752
\glxtrsetupfulldefs ...	496	\glslongextraCustomIIAlign:	
short-sm-postfootnote:		new	753
removed redef of		\glslongextraCustomIIField:	
\glxtrsetupfulldefs ...	512	new	752
short-sm-postfootnote-desc:		\glslongextraCustomIIFmt:	
removed redef of		new	752
\glxtrsetupfulldefs ...	513	\glslongextraCustomIIHeader:	
\xpglsxtrpostabbrvfootnote:		new	752
new	463	\glslongextraCustomIIIAAlign:	
\xpglsxtrposthyphenlong: new	586	new	753
\xpglsxtrposthyphenshort:		\glslongextraCustomIIIField:	
new	571	new	752
\xpglsxtrposthyphensequent:		\glslongextraCustomIIIFmt:	
new	572	new	753
1.49 – ?		\glslongextraCustomIIHeader:	
\GlsXtrIfInGlossary: new ...	39	new	753
1.50 – 2018-05-09		\glslongextraCustomIINameTabularHeader:	
\glsendrange: new	111	new	755
\glsstartrange: new	110	\glslongextraCustomIIISetDescWidth:	
\glxtr@rangeformat: new ...	110	new	762
1.50 – 2022-10-14		\glslongextraCustomIINameHeader:	
\glstablefinishrow: new	819	new	754
1.50 – 2022-11-08		\glslongextraCustomIINameTabularHeader:	
\@glsadd: new	109	new	754
\@glstable@clearpage: new ..	813	\glslongextraCustomIISetDescWidth:	
\@glstable@clearpage@iflt:		new	762
new	813	\glslongextraCustomIINameHeader:	
		new	753

\glslongextraCustomINameTabularHeader:	\glsmeasurewidth: new	31
new	\glstable@finish: new	812
\glslongextraCustomISetDescWidth:	\glstable@grouphook: new	812
new	\glstable@n@to@amps: new	819
\glslongextraCustomNameIIHeader:	\glstable@postentryhook: new	812
new	\glstable@preentryhook: new	811
\glslongextraCustomTabularFooter:	\glstableDescWithOther: new	787
new	\glstablefootstrut: new	808
\glslongextraDescCustomIINameHeader:	\glstableiffilterchild: new	818
new	\glstableifhasotherfield:	
\glslongextraDescCustomIINameTabularHeader:	new	781
new	\glstableName: new	781
\glslongextraDescCustomIINameHeader:	\glstableNameSingleFmt:	
new	changed	
\glslongextraDescCustomIINameTabularHeader:	\GlsXtrIfFieldUndef to	
new	\ifglshasfieldvoid	782, 783
\glslongextraDescCustomINameHeader:	moved other field inside	
new	\glstableNameSingleSuppl	782
\glslongextraDescCustomINameTabularHeader:	\glstablenewline: new	812
new	\glstableothercolalign: new	780
\glslongextraNameCustomIDescHeader:	\glstableOtherFmt: new	781
new	\glstableOtherIfSet: new	788
\glslongextraNameCustomIDescTabularHeader:	\glstableotherwidth: new	809
new	\glstableOtherWithSep: new	782
\glslongextraNameCustomIHeader:	\glstablePostGroupNewLine:	
new	new	811
\glslongextraNameCustomIIDescHeader:	\glstablepostpreambleskip:	
new	new	808
\glslongextraNameCustomIIDescTabularHeader:	\glstableprepostambleskip:	
new	new	808
\glslongextraNameCustomIIHeader:	\glstablespanwidth: new	809
new	\glstableSubDescSep: new	783
\glslongextraNameCustomIIIDescHeader:	\glstableSubDescSymbolOther:	
new	new	787
\glslongextraNameCustomIIIDescTabularHeader:	\glstablesubentryalign: new	779
new	\glstablesubentrywidth: new	779
\glslongextraNameCustomIIIHeader:	\glstableSubName: new	781
new	\glstableSubNameNoDesc:	
\glslongextraNameCustomIIITabularHeader:	changed \glstableOther to	
new	\glstableSubOtherWithSep	785
\glslongextraNameCustomIITabularHeader:	\glstableSubNameSep: new	785
new	\glstableSubNameSingleFmt:	
\glslongextraNameCustomITabularHeader:	changed	
new	\GlsXtrIfFieldUndef to	
\glslongextraSubCustomIFmt:	\ifglshasdesc	783
new	changed \GlsXtrIfFieldUndef	
\glslongextraSubCustomIIFmt:	to \ifglshassymbol	783, 784
new	\glstableSubNameSymbolNoDesc:	
\glslongextraSubCustomIIIFmt:	new	785
new	\glstableSubOtherIfSet: new	788

\glstableSubOtherSep: new ..	783	1.50 – removed	
\glstableSubOtherWithSep:		\glstable@n@amps: new	819
new	782	1.51 – 2023-04-24	
\glstableSubSep: new	785	\@glxtr@get@prefixedlabel@field:	
\glstableSubSymbol: new	786	add found entry to list ...	617
\glstableSubSymbolName: new .	787	clear list	618
\glstableSubSymbolWithSep:		\GlossariesExtraInfo: new ..	18
new	786	\GLSps: new	158
\glstableSymbol: new	786	\Glsps: new	158
\glstableSymbolName: new ...	786	\GLSpt: new	158
\glxtrcontinuedname: new ..	437	\Glspt: new	158
\GlsXtrSetDefaultRangeFormat:		\glxtr@locale: new	205
new	110	\glxtrmarkhook: save missing	
\if@glstable@afterheading:		\GLSxtrtitlefirst	363
new	813	save missing	
long-custom1-name: new	756	\GLSxtrtitlename	363
long-custom2-name: new	758	\glxtrpInit: new	154
long-custom3-name: new	760	\GlsXtrResourceInitEscSequences:	
long-desc-custom1-name: new .	768	new	599
long-desc-custom2-name: new .	769	\glxtrshortlonguserdescname:	
long-desc-custom3-name: new .	770	changed \glslongpltok to	
long-name-custom1: new	755	\glslongtok	549
long-name-custom1-desc: new .	763	\glxtrtarget: new	213
long-name-custom2: new	757	\glxtrtargetfield: new	214
long-name-custom2-desc: new .	764	1.52 – 2023-06-28	
long-name-custom3: new	759	\@glxtr@mglswrite: replaced	
long-name-custom3-desc: new .	766	\protected@write with	
name-other-desc: new	796	\write	426
name-other-symbol-desc: new .	802	\pretoglossarypreamble: new .	57
name-symbol-other-desc: new .	798	1.52 – 2023-09-23	
\printunsrtglossarygrouphook:		\glsnavigationitem: added ...	194
new	220	1.53 – 2023-09-29	
\printunsrtglossarypostbegin:		\glsnavhypergroupdotarget:	
new	221	added	147
\printunsrtglossarypostentryprocesshook:		1.54 – 2024-01-03	
new	220	\@Glsentryfield: switched to	
\printunsrtglossarypreend:		\glspdfsentencecase	31
new	221	\Glsfmtfull: switched to	
\printunsrtglossarypreentryprocesshook:		\glspdfsentencecase	382
new	220	\Glsfmtfullpl: switched to	
\printunsrttable: added		\glspdfsentencecase	382
expandafter	815	\Glsfmtlong: switched to	
moved init hook just after keys		\glspdfsentencecase	381
set	814	\Glsfmtlongpl: switched to	
table: \glstableChildEntries		\glspdfsentencecase	381
moved to block style	820	\glspdfsentencecase: new ...	31
1.50 – move		\Pglsfmtlong: switched to	
\glstableSubNameTarget: moved		\glspdfsentencecase	388
\glssubentryitem	781	\Pglsfmtlongpl: switched to	
		\glspdfsentencecase	389

\Pglsfmtshort: switched to	1.56 – 2025-02-07
\glspdfsentencecase	\glsxtrgeneralpuncbracketIIrules:
387	new 635
\Pglsfmtshortpl: switched to	\glsxtrgeneralpuncbracketIrules:
\glspdfsentencecase	new 634
387	\glsxtrgeneralpuncbracketIrules:
1.54 – 2025-01-03	new 634
\@Glsxtrglossentry: new	\glsxtrgeneralpuncbracketIVrules:
210	new 635
\@Glsxtrglossentryother: new	\glsxtrgeneralpuncdotrules:
212	new 633
\@glxtr@mglsl@linkdefs: new .	\glsxtrgeneralpuncIIrules:
428	new 637
\BibGlsOptions: new	\glsxtrGeneralPuncRules: new
203	627
\Glossentrynameother: new . .	\glsxtrhyphenIrules: new . .
310	632
\glxtr@setlocationanchor:	\glsxtrhyphenIrules: new . .
new 603	632
\glxtrbookindexsubsubitem:	\glxtrminusrules: new
new 714	632
\glxtrbookindexsubtarget:	1.57 – 2025-03-04
new 712	\glsfmtfirstpl: corrected case
\glxtrbookindextarget: new .	for PDF bookmark
712	380
\glxtrcontrolIrules: new .	1.57 – ??
629	\@glsl@noidx@getgrouptitle:
\glxtrcontrolIrules: new . .	check for new datatool
628	integration 192
\Glsxtrglossentry: new	1.58 – 2025-03-12
210	\@glsl@noidx@reference: new
\Glsxtrglossentryother: new .	81
212	\@print@noidx@glossary: check
\glxtrhyperlink: added check	for glossaries v4.57
for \glsl@hyperlinkhook .	194
149	\glslforeachincategory: check
\glxtrprenamehook: new	for empty glossary
308	298
\GlsXtrStandaloneEntryHeadNameFirstUc:	\rGlsplformat: corrected
new 210	command name spelling . .
\GlsXtrStandaloneEntryHeadOtherFirstUc:	236
new 213	\rglsplformat: corrected
\GlsXtrStandaloneEntryNameFirstUc:	command name spelling . .
new 210	236
\GlsXtrStandaloneEntryOtherFirstUc:	1.59 – 2025-03-18
new 213	\GlsXtrClearAutoAddOnFormat:
\GlsXtrStandaloneEntryPdfNameFirstUc:	new 105
new 210	\makeglossaries: bug fix:
\GlsXtrStandaloneEntryPdfOtherFirstUc:	corrected cs name spelling .
new 213	184
\glxtrtargetdup: new	1.6 – 2025-04-12
213	\@glsl@noidx@addtorefs:
\IfNotBibGls: new	provided 82
599	\@glsl@restricted@newentryhook:
long-postshort-sc-user:	new 82
corrected inline format . . .	\eglssetwidest: check for new
546	function 686
1.55 – 2025-01-29	\eglsupdatewidest: changed to
\@glxtr@resourcefile: new .	document command
203	688
\glslbibdata: new	\gglsetwidest: check for new
203	function 686
\GlsXtrLoadResources: switched	
to using	
\@glxtr@resourcefile . .	
205	
\glxtrresourcefile:	
deprecated 203	

\glsupdatewidest: changed to	expansion	686
document command	\xglsetwidest: use protected	
\GlossEntryName: new	expansion	687
\GLOSSentrynameother: new	1.8 – 2025-08-13	
\GlossEntryNameOther: new	\predglsfieldhook: new	618
\glsupdatewidest: changed to	\predglshook: new	614
document command	\predglslinkhook: new	615
\makeglossaries: check for	1.9 – 2025-11-03	
\GlsNoIdxDoRerunCheck	\@printunsrtglossary@unit@nosec:	
\xglsetwidest: check for new	new	222
function	\glxtrseeitemformat: new	69
\xglupdatewidest: changed to	2.0 – 2026-03-26	
document command	\glxtrabbrvpluralsuffix: use	
1.7 – 2025-05-14	\glsacrpluralsuffix instead	
\eglsetwidest: use protected	of \glspluralsuffix	337